biocentral: embedding-based protein predictions

Sebastian Franz[1,*,♦], Tobias Olenyi[1,5,*], Paula Schloetermann[3],
Amine Smaoui[1], Luisa F. Jimenez-Soto[4], Burkhard Rost[1,2]

1   School of Computation, Information, and Technology (CIT), Department of Informatics, Bioinformatics & Computational Biology, TUM (Technical University of Munich), 85748 Garching/Munich, Germany
2   TUM School of Life Sciences Weihenstephan (WZW), Alte Akademie 8, Freising, Germany & TUM-IAS
3   iteratec GmbH, St.-Martin-Str. 114, 81669 Munich, Germany
4   Walther-Straub Institute of Pharmacology and Toxicology – LMU, Goethestrasse 33, 80336 Munich, Germany
5   School of Computer Science, University of Auckland, Private Bag 92019, Auckland 1142, New Zealand
*   Authors contributed equally.
♦   Corresponding author: sebastian.franz@tum.de
   http://www.rostlab.org/, Tel: +49-289-17-811 (email Rost: assistant@rostlab.org)

ABSTRACT

The rise of protein Language Models (pLMs) is reshaping the landscape of protein prediction. Embeddings are powerful protein representations provided by pLMs, but they come at a cost: their generation requires expensive hardware, and leveraging models often requires expert knowledge. To some extent, these hurdles limit the ease of use and benefits of those methods both for experimental and computational biologists. With biocentral, we aim at providing a free and open embedding-based service which addresses these challenges. We support standardized access to most pLMs currently in use, enabling researchers to generate embeddings, get embedding-based protein feature predictions, and train embedding-based models. Here, we showcase biocentral in a large-scale analysis of the BFVD virus database through biocentral's predict module. Next, we show how readily biocentral's training module reproduces an existing embedding-based prediction method. The server is accessible through a graphical user interface and a programmatic Application Programming Interface (API) at: https://biocentral.rostlab.org

Keywords: protein language model embeddings, bioinformatics tools, protein structure, bacterial exotoxins

Abbreviations: **3D**: three-dimensional, **API:** Application Programming Interface, **BFVD:** Big Fantastic Virus Database, **BLAST**: Basic Local Alignment Search Tool, **FNN:** Feedforward Neural Network, **GPU:** Graphics Processing Unit, **MCC:** Matthews Correlation Coefficient, **MSA**: Multiple Sequence Alignment, **NCBI**: National Center for Biotechnology Information, **ONNX:** Open Neural Network Exchange, **pLDDT:** predicted local distance difference test, **pLM:** protein Language Model, **SVM:** Support Vector Machine, **UniProtKB**: Universal Protein Resource Knowledgebase (database).

INTRODUCTION

Protein language models (*pLMs*) can generate high-dimensional vectors representing
proteins. These vectors, known as *embeddings,* typically hold about 1,000 values for each
residue. Recent methods effectively leverage embeddings for a variety of feature
predictions, ranging from phenotype predictions such as disorder and membrane
interactions, and virus-host interaction to 3D structure prediction [1-4]. The effective
development and use of such methods often require expert knowledge along with access to
non-standard hardware, most notably powerful GPUs with large cache and fast disk
storage. This creates disparity: only well-funded labs can use the latest methods.
Over the past three decades, efforts to democratize protein prediction have led to a
diverse ecosystem of computational tools. Integrated platforms such as the first online
server for protein structure prediction, *PredictProtein* [5, 6] and *Phyre* [7] pioneered freely
available one-stop prediction but depended on slow, MSA-based workflows. Later, workflow
engines such as *Galaxy* [8] and *Nextflow* [9, 10] emphasized reproducibility and modularity,
albeit at the cost of technically demanding deployments. More recently, programmatic
frameworks such as *bio_embeddings* [11] have combined excellent flexibility and
performance but rely on programming expertise and local computational resources.
UniProtKB [12] has begun providing precomputed *ProtT5* [13] embeddings for its core
protein database, making these large-scale, standardized protein representations broadly
accessible.
biocentral leverages modern pLMs to provide fast, embedding-based predictions through
a web interface and an Application Programming Interface (API), building upon the
foundational vision of *PredictProtein*. By combining the accessibility of integrated servers
with the scalability of programmatic frameworks, it aims to enable expert-centric pipelines
and open, reproducible access to state-of-the-art protein embeddings and predictions. The
goal of *biocentral* is to make computational tools more accessible to biomedical researchers
by reducing technical barriers to the latest models and methods, thus allowing these
domain experts to really focus on results interpretation and scientific discovery.
We demonstrate the application of *biocentral* through two examples. Firstly, we use the
biocentral prediction module to predict transmembrane regions through *TMbed* [2] based on
ProtT5 for all sequences in the *BFVD* virus database [14] with the goal to update our existing
TMvisDB resource [15]. Secondly, we leverage the embedding and training modules of
biocentral to reproduce a recently published method using embeddings to identify bacterial
exotoxins from sequence, namely *ExoTox* [16]. The *ExoTox* model is available as part of the
prediction module of *biocentral.*
biocentral is available at https://biocentral.rostlab.org. For ease-of-use in coding
environments, we provide an API package (for *Python* and *Dart*) at
https://github.com/biocentral/biocentral_api. The service repository can be found at
https://github.com/biocentral/biocentral_server. A frontend is constantly being developed
and available at https://app.biocentral.cloud.

METHODS

Service architecture

Our lab has a long-standing history of developing publicly accessible protein prediction services [5, 17]. The transition toward embedding-based methods required rethinking these systems in light of new computational and maintenance challenges [11]. Two core issues emerged: (1) fragile software dependencies that hindered long-term maintainability and (2) complex coordination of costly resources such as GPUs, databases, and API gateways.

To address the first issue, *biocentral* introduced a modular, distributed architecture built on containerized services. Each functional component runs independently via *docker-compose*, enabling deployment across machines and independent scaling. Embedding caching reduces redundant GPU computation, while an *Open Neural Network Exchange* (*ONNX*)-based [18] workflow standardizes model integration and reduces dependency conflicts. This pipeline allows leveraging the *Nvidia Triton* inference server for optimized and distributed model inference [19]. Our architecture simplifies sustainable operation, maintenance, and rapid incorporation of new resources like pLMs and prediction methods.

Core modules

Embedding module. The embedding module forms the computational core of *biocentral*, providing per-residue (per-token) and per-protein (pooled) pLM embeddings for any compatible transformer model hosted on *HuggingFace* [20]. Embedding generation is implemented via the *biotrainer* framework [21], with additional support for *ONNX*-optimized versions of commonly used pLMs such as *ProtT5* [13] and *ESM-2* (8M, 3B) [3]. These optimized models are executed through the *NVIDIA Triton* inference server for optimal resource usage [22].

To minimize redundant computation, generated embeddings are cached in a *PostgreSQL* database indexed by a sequence hash and the model identifier. Caching embeddings uses up a lot of disk space (roughly 1 GB for 1,000 sequences for per-residue *ProtT5* embeddings). That is why the database is cleaned up regularly following a first-in-first-out principle to have the latest used embeddings available.

Beyond embedding generation, the module can interoperate with the *ProtSpace* library [23] to provide standardized and robust embedding analysis and visualization.

Prediction module. Building on the embedding module, *biocentral's* prediction module integrates several established models for different protein prediction tasks (Table 1). Each model is included as a lightweight interface that defines input and output transformations, records metadata such as the underlying pLM, and links to the corresponding optimized *ONNX/Triton* model. The wrapper itself contains no machine-learning logic; the latter is entirely handled by the *ONNX* runtime. The exported *ONNX* model, derived from the original architecture and pre-trained weights, can be deployed independently via *Triton*.

This modular workflow enables rapid integration of new methods into *biocentral* without introducing additional dependencies or computational overhead. The current release includes a broad range of models (Table 1), which we continuously expand both internally and in collaboration with model developers (SOM; Algorithm 1).

Table 1: Prediction models in *biocentral* [Δ]

Prediction of	Model	pLM	Citation
Per-residue/per-token			
Protein secondary structure	ProtT5-sec	ProtT5	[13]
Binding residues	BindEmbed	ProtT5	[24]
Evolutionary conservation	ProtT5_conservation	ProtT5	[25]
Natively disordered regions	SETH	ProtT5	[1]
Subcellular location	LightAttention-LX	ProtT5	[26]
Transmembrane regions & signal peptides	TMbed	ProtT5	[2]
Variant effect	VespaG	ESM-2 (3B)	[27]
Per-protein/pooling			
Membrane association	LightAttention-membrane	ProtT5	[26]
Bacterial exotoxins	ExoTox	ProtT5	[16]

Δ Each model is exported to ONNX and checked for consistency with the original (delta<10^{-3}). Additionally, models are included in the main codebase as lightweight wrappers around data-processing.

Model training. The training module allows for the development of new supervised prediction models based on *pLM* embeddings. The module is implemented using *biotrainer* [21]. Input parameters are provided as a *biotrainer* configuration file. The config options are validated, and the configuration is checked for internal consistency before training. If available, embeddings are loaded from the internal *PostgreSQL* database; otherwise, they are computed on the fly before training. After successful completion, model checkpoint(s) and a summary file are returned to the user. This allows for full reproducibility and control over the training process and results. *Biotrainer* provides several sanity checks and test set baselines out-of-the-box, that allow for a quick initial evaluation of the training process and model quality. The module enables rapid prototyping of biomedical prediction models based on embeddings and will be extended in the future.

Soft- & hardware

Software stack: The server is implemented in Python 3.12 using the *FastAPI* web framework [28]. Deployment is handled via *docker-compose*, allowing for the orchestration of multiple containers that may even run on different machines. This setup enables local deployment for advanced users, if sufficient hardware capabilities are available. The programmatic API was generated using *openapi-generator* with the *OpenAPI* specifications [29] from the *FastAPI* framework. To handle the underlying complexity, we provide a stable high-level interface exposing core functions such as *train*, *embed* and *predict* for straightforward programmatic use. A graphical user interface is available as an early version and constantly being developed further. It is built using *Dart/Flutter* for cross-platform compatibility, supporting all common desktop platforms and web browsers.

Deployment hardware: The *biocentral* service is currently deployed on a DELL PowerEdge R7525 with two AMD 7313 (32 thread) processors, 256GB RAM, and an NVIDIA A10 (24GB) GPU.

Data sets for case studies

Big Fantastic Virus Database (BFVD). The *Big Fantastic Virus Database (BFVD)* is a
comprehensive repository holding 351,242 predicted viral protein structures derived from
UniRef30 viral sequence clusters [14]. Structures were predicted by *ColabFold* [30] and
subsequently refined by integrating homologous sequences from a large assembled-
sequencing data set. *BFVD* represents a highly diverse set of viral structures, over 60% of
which show little or no structural similarity to AFDB (the database with *AlphaFold2*
predictions of protein structure [31]) or to the experimental 3D structures from the *PDB* [32].

ExoTox. *ExoTox* is a machine-learning model predicting bacterial exotoxins from sequences
of secreted non-toxic bacterial proteins [16]. The method was trained on a curated dataset
of 1,069 bacterial exotoxins and 1,308 secreted non-toxins derived from *UniProtKB/Swiss-*
Prot [12] and *PSORTb 3.0b* [33]. Redundancy was reduced to ≤30% pairwise sequence
identity (PIDE) using *MMseqs2* [34] to ensure non-overlapping training and test sets, i.e., no
pair in the data set had >30% PIDE. Input to *ExoTox* were the first twenty principal
components of pooled (per-protein averaged) *ProtT5* embeddings. All models were
evaluated using the Matthew's Correlation Coefficient (MCC), calculated using Equation 1.

Equation 1: Matthew's Correlation Coefficient (MCC)

$$MCC = \frac{TP*TN\text{-}FP*FN}{\sqrt{(TP+FP)*(TP+FN)*(TN+FP)*(TN+FN)}}$$

$TP = True\ Positive$
$TN = True\ Negative$
$FP = False\ Positive$
$FN = False\ Negative$

Support Vector Machine (SVM) [35] trained on these embeddings performed well in
distinguishing exotoxins from secreted controls (MCC≈0.94 [16]), outperforming both
sequence-based (*BLAST* [36]) and generalized toxin predictors.

RESULTS AND DISCUSSION

Predicting for large datasets: membrane proteins in BVFD

To explore the applicability of *biocentral* for large-scale dataset analysis, we used *TMbed*
[2] to predict transmembrane topology across all predicted viral proteins from *BFVD* [14].
After a basic filtering step, we submitted the dataset of 345,141 sequences in seven
batches of around 50,000 proteins. In total, the computation took around two days.

TMbed predicted transmembrane regions in approximately 11.6% of all investigated
BFVD entries. To examine whether these predictions reflect biologically meaningful trends,
we compared the results between enveloped and non-enveloped viruses. Contrary to what
was expected, proteins from enveloped viruses less frequently contained proteins with
predicted transmembrane regions [37] than those from non-enveloped viruses or from
unknown envelope status (Table 2). While these observations remain inconclusive, they
suggest that *TMbed*'s applicability to the domain of viruses might be limited without
finetuning.

Table 2: TMbed predictions on BFVD [Δ]

Envelope Status	Nprot with TM predictions	Nprot without TM predictions	Total	Percentage TM
Envelope	96	936	1,032	9.3%
Non-Envelope	11,013	90,008	101,021	10.9%
Unknown	29,024	214,064	243,088	11.9%

Δ For each protein sequence in BFVD [14], TMbed [2] predicted transmembrane (TM) regions. Here, we did not
distinguish between predicted transmembrane helices and strands/barrels; instead, we only counted the number
of proteins (Nprot) with (2nd column) and without (3rd column) TM-regions. We distinguished between viruses with
and without envelopes based on NCBI annotations [38]. Overall, proteins from enveloped viruses show a lower
relative frequency of TMbed-predicted membrane interactions compared to non-enveloped or those unknown.
This suggests that the applicability of TMbed to viral sequences might be limited, as the contrary would be
expected [37].

We further examined this by analyzing sequences predicted to contain both alpha-helical
(TMH) and beta-barrel (TMB) regions—a combination unlikely to exist in nature and previ-
ously used as a lower bound for incorrect predictions [2]. Out of all 345,141 viral proteins,
43 proteins (<0.2‰) were predicted with such mistakes. Only 19 of all proteins with predict-
ed TM regions had high-confidence 3D structure predictions (pLDDT>70 provided by
BFVD). We examined the shortest protein (A0A516M0S4; 54 residues; average pLDDT ≈ 88)
and the longest protein (A0A6J5RKD4; 339 residues; average pLDDT ≈ 85) (SOM; Figure 1).
While the irregular pattern of predicted beta-barrel residues suggests a mistake, the struc-
ture resembles similar pore-forming structures [39], hinting at the predictor's confusion.
All membrane predictions on the *BVFD* facilitated through *biocentral* are now integrated
into *TMVisDB* [15], extending its coverage to viral proteins. Although our results show that
predictions from *TMbed* on viral structures must be treated with caution, we still believe that
making these predictions available can lead to new insights for future model development
and protein structure analysis.

Training embedding-based models from scratch: reproducing ExoTox

Exotoxins produced by bacteria are proteins released into the extracellular space and can affect target cells. Precise detection of these toxins can improve pharmaceutical development and guarantee the security of medical treatments that utilize bacteria. The recently released *ExoTox* prediction method [16] inputs *ProtT5* embeddings (reduced to the largest 20 principal components) and is trained on a curated subset of bacterial exotoxins and secreted non-toxic proteins. Using *biocentral*, we reproduce this method as evidenced by reaching similar performance on the same test set (MCC≈0.93, Equation 1) as a feed-forward neural network (FNN) (compared to the original SVM), while outperforming all evaluated baselines (Figure 1). Creating this model only requires providing annotated sequences (with labels and sets) before calling the biocentral training module. This reduces initial model development time without prior programming knowledge from weeks or months to days or even hours. The results also show that models trained via *biocentral* can serve as a control group or sanity check for more sophisticated, specialized architectures.

We compiled a complete guide of the steps required for reproduction in the supplementary online material (SOM; Algorithm 2). The original ExoTox SVM was converted to *ONNX* and is available as a predictor in the *biocentral* prediction module.

Figure 1: Comparison of the original ExoTox model against the reproduced FNN and baselines [Δ]

Δ Comparing MCC of the original ExoTox predictor [16] (SVM) against the reproduced FNN and baseline encodings. The reproduced model matches the original's performance closely, indicating that the biocentral training module can reproduce a published biological predictor. Both ProtT5-based models outperform the common baselines of one-hot encoded sequences and BLOSUM62 [40] (encoding an amino acid by its respective substitution vector) as well as AAOntology, where an amino acid is encoded by its respective values from 568 physicochemical scales [41]. All these models and baselines outperform random performance, empirically evaluated using randomly generated embedding vectors (dimension: 128) as input, and a randomly initialized, untrained model using ProtT5 embeddings.

Limitations and Future Work

The *biocentral* project will continue to evolve. Maintainability and longevity remain central goals. To strengthen portability and sustainability, we plan to explore advanced deployment methods, such as Kubernetes-based orchestration. This would simplify deployment across diverse cloud environments and improve resilience to changes in available computational resources and funding.

Beyond maintaining and expanding the current ecosystem, we aim to extend *biocentral* towards the emerging field of protein design and engineering, broadening access to state-of-the-art generative and optimization tools. Additionally, we plan to further emphasize training and fine-tuning of existing models to make machine learning more accessible to users. We hope to expand the catalogue of prediction models through community engagement, encouraging external model developers to contribute and collaborate on shared standards of accessibility and interpretability.

Our case study of *TMbed* demonstrates that large-scale predictions through *biocentral* can lead to a better understanding of model limitations, especially for sequences that deviate strongly from the training distribution. To address this issue, we plan to develop model-specific applicability domain layers that document strengths and weaknesses, and guide users toward reasonable use of predictive models. Thus, a collaboration between domain experts applying prediction models to their field of research and model developers can speed up model development in the future.

The reproduction of the *ExoTox* predictor showed that *biocentral* enables rapid prototyping of prediction models on biological data. This can significantly lower the barriers for biomedical researchers to create custom deep learning predictors. On the other side, abstracting away the required technological expertise to create such models has the potential to decrease the ability to interpret the model's behavior and results. We plan to address this by extending the provided frontend with utilities for model comparison and explainability, supporting the interpretation process for domain experts.

CONCLUSION

We introduced *biocentral*, a freely available service that makes state-of-the-art, embedding-based protein predictions accessible to a broad community. Through its modular architecture, standardized *ONNX* model format, and *Triton*-based inference, the server offers a reproducible and sustainable framework for integrating and deploying protein prediction models. The two case studies demonstrate both its scalability for large datasets and its capacity to reproduce existing embedding-based methods with minimal effort.

By abstracting the complexity of machine-learning pipelines into a stable programmatic interface, *biocentral* establishes a pattern that others can adopt to publish and maintain their models in a unified, interoperable format. In this way, it extends the long-standing vision of democratizing protein prediction, removing barriers between method developers and end-users, and creating a common platform that evolves with the advancing field of protein language models.

AVAILABILITY AND REQUIREMENTS

Project name: biocentral
Project home page: https://github.com/biocentral/
Operating system(s): Platform independent
Programming language: Python 3.12
Other requirements:
o   Redis 7 (alpine)
o   PostgreSQL 15
o   SeaweedFS (chrislusf/seaweedfs)
o   NVIDIA Triton Inference Server 24.12
o   Prometheus (prom/prometheus)
o   taxoniq (≥1.0.1, <2.0.0)
o   blosc2 (≥2.7.1, <3.0.0)
o   psycopg[binary] (≥3.2.3, <4.0.0)
o   rq (≥2.1.0, <3.0.0)
o   python-dotenv (≥1.2.1, <2.0.0)
o   gpytorch (≥1.14, <2.0)
o   onnxruntime-gpu (≥1.16.0, <2.0.0; Linux only)
o   onnxruntime (≥1.16.0, <2.0.0; non-Linux platforms)
o   tritonclient[grpc] (≥2.61.0)
o   circuitbreaker (≥2.0.0)
o   httpx (≥0.28.1)
o   pydantic (≥2.12.4)
o   fastapi (≥0.121.0)
o   uvicorn (≥0.38.0)
o   prometheus-client (≥0.20.0)
o   prometheus-fastapi-instrumentator (≥6.1.0)
o   fastapi-limiter (≥0.1.6)
o   biotrainer (github.com/biocentral/biotrainer.git@fix/api-improvements)
o   protspace (github.com/tsenoner/protspace.git@v3.1.1)
o   hvi_toolkit (github.com/SebieF/hvi_toolkit.git@maintenance/update-biotrainer)
o   vespag (github.com/biocentral/VespaG.git@onnx-deployment)
o   tmbed (github.com/biocentral/TMbed.git@onnx-deployment)
300
301 **Hardware requirements:** NVIDIA GPU with CUDA support (recommended: ≥16GB VRAM
302 for full model deployment)
303 **License:** GPL-3.0
304 **Any restrictions on use by non-academics:** None
305

DECLARATIONS

Availability of data and materials

The code for the biocentral service is available at https://github.com/biocentral/biocentral_server, the API client's code at https://github.com/biocentral/biocentral_api, both open source under GPL-3.0. The API is available at https://biocentral.rostlab.org/docs. The frontend is available at https://app.biocentral.cloud. The Big Fantastic Virus Database (BFVD) is available under https://bfvd.steineggerlab.workers.dev/. The ExoTox dataset is available here: https://data.ub.uni-muenchen.de/576/. The scripts for creating the analysis of the BFVD TMbed predictions and the reproduction of the ExoTox predictor is available in the supplementary materials. The latter was also published as an example for the usage of the biocentral API at https://github.com/biocentral/biocentral_api/tree/main/python/examples/exotox_reproduction.

Competing interests

The authors declare no competing interests.

Authors' contributions

S.F. conceptualized the project; S.F. and T.O developed software and methodology, with P.S. contributing to software and model conversion. S.F. and T.O performed analyses with A.S. contributing data and L. JS. contributing data and expertise. S.F. and T.O wrote the initial manuscript with all authors contributing. B.R. provided supervision and acquired funding. All authors read and approved the final manuscript.

Funding

The Bavarian Ministry of Education supported the work of S.F., T.O., L.JS., and B.R. through funding to the TUM and LMU.

Acknowledgments

We thank Nikita Kugut (TUM) for his support with many aspects of this work. We thank the Technical University of Munich (TUM) for providing facilities and resources. Finally, we thank those who deposit experimental data in public databases, maintain these databases, and develop methods to enrich experimental data.
Declaration of generative AI and AI-assisted technologies in the writing process:
While preparing this work, the authors used Claude.ai and ChatGPT.com to check the language and grammar of this manuscript. After using these services, the authors reviewed and edited the content as needed and take full responsibility for the content of the published article.

Ethics approval and consent to participate

Not applicable

Consent for publication

Not applicable

REFERENCES

1. Ilzhöfer, D., Heinzinger, M. & Rost, B. (2022). SETH predicts nuances of residue disorder from protein embeddings. Frontiers in Bioinformatics. **2**, 1019597.

2. Bernhofer, M. & Rost, B. (2022). TMbed: transmembrane proteins predicted through language model embeddings. BMC bioinformatics. **23**, 326.

3. Lin, Z., Akin, H., Rao, R., Hie, B., Zhu, Z., Lu, W., Smetanin, N., Verkuil, R., Kabeli, O., Shmueli, Y., dos Santos Costa, A., Fazel-Zarandi, M., Sercu, T., Candido, S. & Rives, A. (2023). Evolutionary-scale prediction of atomic-level protein structure with a language model. Science. **379**, 1123–1130. https://doi.org/doi:10.1126/science.ade2574.

4. Weissenow, K. & Rost, B. (2025). Are protein language models the new universal key? Current Opinion in Structural Biology. **91**, 102997.

5. Rost, B. (1996). [31] PHD: Predicting one-dimensional protein structure by profile-based neural networks. In Methods in enzymology pp. 525–539, Elsevier.

6. Rost, B. & Sander, C. (1992). Jury returns on structure prediction. Nature. **360**, 540–540.

7. Powell, H. R., Islam, S. A., David, A. & Sternberg, M. J. (2025). Phyre2. 2: a community resource for template-based protein structure prediction. Journal of molecular biology. 168960.

8. Jalili, V., Afgan, E., Gu, Q., Clements, D., Blankenberg, D., Goecks, J., Taylor, J. & Nekrutenko, A. (2020). The Galaxy platform for accessible, reproducible and collaborative biomedical analyses: 2020 update. Nucleic acids research. **48**, W395–W402.

9. Langer, B. E., Amaral, A., Baudement, M.-O., Bonath, F., Charles, M., Chitneedi, P. K., Clark, E. L., Di Tommaso, P., Djebali, S. & Ewels, P. A. (2025). Empowering bioinformatics communities with Nextflow and nf-core. Genome Biology. **26**, 228.

10. Di Tommaso, P., Chatzou, M., Floden, E. W., Barja, P. P., Palumbo, E. & Notredame, C. (2017). Nextflow enables reproducible computational workflows. Nature biotechnology. **35**, 316–319.

11. Dallago, C., Schütze, K., Heinzinger, M., Olenyi, T., Littmann, M., Lu, A. X., Yang, K. K., Min, S., Yoon, S. & Morton, J. T. (2021). Learned embeddings from deep learning to visualize and predict protein sets. Current Protocols. **1**, e113.

12. Boutet, E., Lieberherr, D., Tognolli, M., Schneider, M. & Bairoch, A. (2007). UniProtKB/Swiss-Prot: the manually annotated section of the UniProt KnowledgeBase. In Plant bioinformatics: methods and protocols pp. 89–112, Springer.

13. Elnaggar, A., Heinzinger, M., Dallago, C., Rehawi, G., Wang, Y., Jones, L., Gibbs, T., Feher, T., Angerer, C., Steinegger, M., Bhowmik, D. & Rost, B. (2022). ProtTrans: Toward Understanding the Language of Life Through Self-Supervised Learning. IEEE Trans Pattern Anal Mach Intell. **44**, 7112–7127. https://doi.org/10.1109/TPAMI.2021.3095381.

14. Kim, R. S., Levy Karin, E., Mirdita, M., Chikhi, R. & Steinegger, M. (2025). BFVD—a large repository of predicted viral protein structures. Nucleic acids research. **53**, D340–D347.

15. Olenyi, T., Marquet, C., Grekova, A., Houri, L., Heinzinger, M., Dallago, C. & Rost, B. (2025). TMVisDB: Annotation and 3D-visualization of transmembrane proteins. Journal of Molecular Biology. 168997.

16. Krueger, T., Durmaz, D. A. & Jimenez-Soto, L. F. (2025). Exo-Tox: Identifying Exotoxins from secreted bacterial proteins. BioData Mining. **18**, 52.

17. Bernhofer, M., Dallago, C., Karl, T., Satagopam, V., Heinzinger, M., Littmann, M., Olenyi, T., Qiu, J., Schütze, K. & Yachdav, G. (2021). PredictProtein-predicting protein structure and function for 29 years. Nucleic acids research. **49**, W535–W540.

18. Developers, O. R. (2021). ONNX Runtime. https://onnxruntime.ai

19. Corporation, N. (2025). Triton inference server: an optimized cloud and edge inferencing solution. https://github.com/triton-inference-server

20. Wolf, T., Debut, L., Sanh, V., Chaumond, J., Delangue, C., Moi, A., Cistac, P., Rault, T., Louf, R. & Funtowicz, M. (2019). Huggingface's transformers: State-of-the-art natural language processing. arXiv preprint arXiv:1910.03771.

21. Sanchez, J. G., Franz, S., Heinzinger, M., Rost, B. & Dallago, C. (2022). Standards, tooling and benchmarks to probe representation learning on proteins. In NeurIPS 2022 Workshop on Learning Meaningful Representations of Life.

22. Savard, C., Manganelli, N., Holzman, B., Gray, L., Perloff, A., Pedro, K., Stenson, K. & Ulmer, K. (2024). Optimizing high-throughput inference on graph neural networks at shared computing facilities with the nvidia triton inference server. Computing and Software for Big Science. **8**, 14.

23. Senoner, T., Olenyi, T., Heinzinger, M., Spannagl, A., Bouras, G., Rost, B. & Koludarov, I. (2025). ProtSpace: a tool for visualizing protein space. Journal of Molecular Biology. 168940.

24. Littmann, M., Heinzinger, M., Dallago, C., Weissenow, K. & Rost, B. (2021). Protein embeddings and deep learning predict binding residues for various ligand classes. Scientific reports. **11**, 23916.

25. Marquet, C., Heinzinger, M., Olenyi, T., Dallago, C., Erckert, K., Bernhofer, M., Nechaev, D. & Rost, B. (2022). Embeddings from protein language models predict conservation and variant effects. Human genetics. **141**, 1629–1647.

26. Stärk, H., Dallago, C., Heinzinger, M. & Rost, B. (2021). Light attention predicts protein location from the language of life. Bioinformatics Advances. **1**, vbab035.

27. Marquet, C., Schlensok, J., Abakarova, M., Rost, B. & Laine, E. (2024). Expert-guided protein language models enable accurate and blazingly fast fitness prediction. Bioinformatics. **40**, btae621.

28. Lathkar, M. (2023). High-Performance Web Apps with FastAPI. California: Apress Berkeley.

29. Initiative, T. O. (2025). The OpenAPI Specification. https://github.com/OAI/OpenAPI-Specification

30. Mirdita, M., Schütze, K., Moriwaki, Y., Heo, L., Ovchinnikov, S. & Steinegger, M. (2022). ColabFold: making protein folding accessible to all. Nature methods. **19**, 679–682.

31. Varadi, M., Anyango, S., Deshpande, M., Nair, S., Natassia, C., Yordanova, G., Yuan, D., Stroe, O., Wood, G. & Laydon, A. (2022). AlphaFold Protein Structure Database: massively expanding the structural coverage of protein-sequence space with high-accuracy models. Nucleic acids research. **50**, D439–D444.

32. Berman, H. M., Westbrook, J., Feng, Z., Gilliland, G., Bhat, T. N., Weissig, H., Shindyalov, I. N. & Bourne, P. E. (2000). The protein data bank. Nucleic acids research. **28**, 235–242.

33. Yu, N. Y., Wagner, J. R., Laird, M. R., Melli, G., Rey, S., Lo, R., Dao, P., Sahinalp, S. C., Ester, M. & Foster, L. J. (2010). PSORTb 3.0: improved protein subcellular localization prediction with refined localization subcategories and predictive capabilities for all prokaryotes. Bioinformatics. **26**, 1608–1615.

34. Steinegger, M. & Söding, J. (2017). MMseqs2 enables sensitive protein sequence searching for the analysis of massive data sets. Nature biotechnology. **35**, 1026–1028.

35. Stitson, M., Weston, J., Gammerman, A., Vovk, V. & Vapnik, V. (1996). Theory of support vector machines. University of London. **117**, 188–191.

36. Altschul, S. F., Gish, W., Miller, W., Myers, E. W. & Lipman, D. J. (1990). Basic local alignment search tool. Journal of molecular biology. **215**, 403–410.

37. Lenard, J. (2008). Viral membranes. Encyclopedia of virology. 308.

38. Sayers, E. W., Beck, J., Bolton, E. E., Brister, J. R., Chan, J., Connor, R., Feldgarden, M., Fine, A. M., Funk, K. & Hoffman, J. (2025). Database resources of the National Center for Biotechnology Information in 2025. Nucleic acids research. **53**, D20–D29.

39. Tanaka, K., Caaveiro, J. M., Morante, K., González-Mañas, J. M. & Tsumoto, K. (2015). Structural basis for self-assembly of a cytolytic pore lined by protein and lipid. Nature communications. **6**, 6337.

40. Henikoff, S. & Henikoff, J. G. (1992). Amino acid substitution matrices from protein blocks. Proceedings of the National Academy of Sciences. **89**, 10915–10919.

441   41. Breimann, S., Kamp, F., Steiner, H. & Frishman, D. (2024). AAontology: An ontology of amino
442   acid scales for interpretable machine learning. Journal of molecular biology. **436**, 168717.
443