Coordinated multilaminar dynamics underlie multiplexed computation in motor cortex

Laura López-Galdo[1,2], Simon Nougaret[1], Demian Battaglia[2]*, Bjørg Elisabeth Kilavik[1]*

[1] Institut de Neurosciences de la Timone (INT), UMR 7289, Aix-Marseille Université, CNRS, 13005 Marseille, France.

[2] Laboratoire de Neurosciences Cognitives et Adaptatives (LNCA), UMR 7364, CNRS, Université de Strasbourg, 67000 Strasbourg, France.

* These authors contributed equally

Abstract

Functional multiplexing is a signature of higher-order brain regions. Beyond single-unit mixed selectivity, the six-layered cortical microcircuit has been proposed as an optimal substrate for such parallel computations. Recurrent connections within and across layers allow cortical columns to retain incoming information for some time and integrate it into stable latent representations, thereby acting as functional units. The key question is whether the multiplexing capacity arises from specialized processing within individual layers or the collective coordination of multi-layer activity patterns. Here, we analyzed laminar recordings from the motor cortex of macaque monkeys performing a complex delayed match-to-sample task. We identified laminarly distributed, behaviorally specific subspaces that captured the encoding of distinct task-related variables. These subspaces, spanning the entire column and expressed as coordinated activity patterns, were functionally reused to encode the same variable over time and flexibly recycled to encode new ones. Subtle variations of laminar weights gave rise to multiple coexistent laminar coding subspaces, enabling multiplexing at the columnar level. Task-related information propagated across layers in temporally organized trajectories that transiently localized in superficial or deep layers at distinct trial epochs. These organized laminar trajectories were consistently observed across recording sites, but exhibited site-specific propagation patterns. The activity of the population on the other hand lacked structured dynamics. Thus, laminar trajectories of information emerged atop a background of spatially and temporally unspecific activity-fluctuations.

Introduction

Higher-order cortical areas excel at multiplexing. Their ability to process several kinds of information in parallel relies on the mixed selectivity of single units, the flexible interaction of neural populations, as well as the generation of functional cell assemblies **(Buzsáki, 2010; Rigotti *et al.*, 2013; Fusi, Miller and Rigotti, 2016; Tye *et al.*, 2024)**. The canonical cortical microcircuit has been proposed as an optimal substrate to perform such computations **(Mountcastle, 1997; Douglas and Martin, 2004; Bastos *et al.*, 2012)**. Canonical circuit descriptions attempt to model the vertical organization of the neocortex as a six-layered architecture, characterized by strong recurrent connections within layers and largely stereotyped patterns of input-output connections between them. This canonic connectivity enables cortical columns to buffer in time multiple incoming transient inputs in parallel, so that the information they convey can be combined into stable latent representations **(Nolan *et al.*, 2025)**. The question remains open, however, of whether such multiplexed computations are performed through parallel processes taking place simultaneously in different specialized layers **(Bastos *et al.*, 2012; Mendoza-Halliday *et al.*, 2024)** or, rather, through the collective coordination of multiple layers, operating in an integrated and not easily separable fashion **(Nigam, Pojoga and Dragoi, 2019; Nolan *et al.*, 2025)**. Here, by analyzing laminar recordings in the motor cortex of a monkey performing a complex visuomotor task, we provide novel evidence that challenges the idea of localizing different types of task-related information in distinct specialized layers. Instead, we find that these information types are simultaneously encoded within alternative low-dimensional spaces of coordinated neural activity, all generated by the interactions between a multiplicity of layers. At specific moments in time, however, task-related information becomes dynamically concentrated in either superficial or deep layers, and traveling waves of information emerge against a background of more unstructured, generic fluctuations of activity spanning the entire column.

Motor cortex represents a privileged place for investigating complex multilaminar processing. Far from being a pure *output structure*, this precentral region acts as a functional hub within diverse distributed networks, which provide it with direct access to both sensory and cognitive inputs to guide behavior **(Wise, 1999; Rizzolatti and Luppino, 2001; Battaglia-Mayer and Caminiti, 2019)**. Integrating these heterogeneous signals relies therefore necessarily on the anatomical constraints and functional connections within the cortical column. At the same time, contrarily to the well-defined laminar organization of primary sensory areas, motor cortex displays a less strict division between incoming and outgoing projections, enhanced intra-laminar connectivity and an almost indistinguishable layer IV **(Shipp, 2005; Shipp, Adams and Friston, 2013; García-Cabezas and Barbas, 2014; Godlove *et al.*, 2014; Ninomiya *et al.*, 2015; Borra *et al.*, 2021)**.

To investigate the computational mechanism emerging from this *weakly laminated* vertical structure, researchers recorded electrophysiological signals from the premotor cortex

in monkeys during complex tasks. Based on single-unit activity, Chandrasekaran and colleagues proposed a segregation scheme of information processing **(Chandrasekaran *et al.*, 2017)**, with decisions preferentially encoded in superficial layers and movement-related signals in deep layers. Conversely, Opris and colleagues found that neurons were equally modulated across layers, with behavioral performance instead relying on synchrony between neuron pairs at different depths within cortical *minicolumns* **(Opris *et al.*, 2011, 2015; Opris, 2013)**. These studies thus propose two different mechanisms of cortical multiplexing: a layer-based versus a column-based scheme of computation.

When task complexity increases, the interpretability of single-unit responses decreases and their heterogeneity increases, as individual neurons often exhibit mixed selectivity and encode simultaneously multiple task variables with different encoding schemes **(Rigotti *et al.*, 2013)**. However, interpretability is rescued by considering the joint activity of multiple neurons as describing a trajectory in a space of the system's dynamic configurations **(Mante *et al.*, 2013; Zhang *et al.*, 2025)**. It thus appears that lower-dimensional manifolds -or vector subspaces in a simpler linear framework- parameterized by a few latent variables can be identified **(Churchland *et al.*, 2012; Shenoy, Sahani and Churchland, 2013; Vyas *et al.*, 2020; Genkin *et al.*, 2025)** in which dynamic trajectories unfold and separate meaningfully according to behavioral features **(Gallego *et al.*, 2017; Perich, Narain and Gallego, 2025)**, consistently across time and individuals **(Gallego *et al.*, 2020; Safaie *et al.*, 2023)**. Furthermore, recent findings indicate that neural subspaces exhibit flexibility, being both *reused* to support the same function over time, and *recycled* to encode novel variables **(Wentz *et al.*, 2025)**. This low-dimensional subspace view was extended to provide new theories for cortico-cortical interactions, suggesting that communication could be gated through the alignment of source and target subspaces, which are not necessarily the ones in which the largest variability of activity arise **(Semedo *et al.*, 2019)**. Together, these findings put forward dynamic neural subspaces as a unifying framework to understand both intra- and inter-areal computations.

In the present work, we examined how the motor cortex exploits its intertwined laminar structure to generate latent representations. Different layers define a *laminar space* (Figure 1), where their activity forms vectors of instantaneous multilaminar states. By tracking task-relevant patterns within this space, we agnostically assessed whether these informative subspaces are localized in depth -suggesting individual layers act as functional units- or instead span multiple depths, pointing to the full column as the functional unit. Furthermore, we investigated whether these coding spaces were *reused* over time to maintain stable representations of the same variables, or were flexibly *recycled* for alternative variables at different task epochs **(Wentz *et al.*, 2025)**.

Information multiplexing, manifested as the simultaneous representation of two distinct latent variables by a same circuit, was supported by the coexistence of different low-dimensional subspaces arising from different combinations of layers within the full-

dimensional laminar space. The fact that complex multilaminar coordination patterns were reused consistently in a behaviorally related manner suggests that information processing relies more on integration than strict segregation across layers. Yet, we found that the encoding subspaces themselves evolved over time, giving rise to a structured flow of task-related information that smoothly alternated between being predominantly represented in superficial and in deeper layers. Laminar localization of information could therefore emerge at times, but only as transient episodes within a broader dynamic that always unfolded over the entire laminar space and varied across recording sites.

Figure 1 - Hypothesis: Laminar functional units in the motor cortex enable multiplexing. *a, The motor cortex encodes multiple task variables (e.g., force, direction, visual cues, time, reward, choice). b, The laminar organization of the cortex provides a substrate for multiplexing. c, Two possible multiplexing mechanisms are illustrated. Left: Layer segregated multiplexing: different layers act as independent functional units, each preferentially encoding specific variables. In state-space, coding subspaces would be defined by channels within the same layer, and movement along individual axes would describe the encoded variables. Right: Column distributed multiplexing: the entire column acts as a functional unit, with different combinations of channels contributing to the encoding of different variables. In this case, coding subspaces would be formed by channels spanning the entire column, and trajectories within these low-dimensional spaces would capture variable encoding. d, Coding-specific subspaces could be reused whenever the same variable is being encoded or recycled to encode distinct parameters over time.*

Results

Multi-unit activity during delayed match-to-sample task

To study the spatial and temporal structure of laminar coding subspaces in the motor cortex we analyzed laminar population activity across different layers during visuomotor behavior in monkeys, in a task requiring simultaneous encoding of cue identity and direction.

Specifically, two monkeys were trained to perform a highly temporally predictive delayed match-to-sample (DMS) task (Figure 2-a). This complex task requested the monkeys to transform the information about the identities of the cues (color condition) into the reaching direction to be performed after the GO. They had to hold in memory the SEL cue identity and match it with the appropriate SC to determine the correct movement direction.

After monkeys had learnt the task, we recorded the neural activity during task performance using acute multi-channel linear (laminar) arrays in the primary motor/premotor cortex. This gave us access to different cortical columns along the cortical sheet (Figure 2-b). We then measured neuronal population activity across layers computing the Multi-Unit Activity (MUA) signal on each individual channel, reflecting the fluctuations of the local population spiking nearby each contact **(Stark and Abeles, 2007)**.

Trial-averaged neural activity in individual channels across all layers showed modulations with respect to the two main variables encoded during the task: 1) color condition (selection cue identity) and 2) movement direction (see Figure 2-c, d, respectively, for an example site). Such modulations were, however, weak, often not significant, and heterogeneous in their exact depth across the different cortical sites.

Dimensional reduction of population activity dynamics

To filter out irrelevant variability, we performed a dimensional reduction of population activity recorded simultaneously across all channels, by applying two different linear methods: principal component analysis (PCA) and linear discriminant analysis (LDA). While PCA captures the directions of maximum variability, LDA identifies axes that specifically maximize separation across the probed conditions, thereby defining coding subspaces in which trial trajectories for those conditions (SEL color or target direction) are better separated. These models were estimated in a time-resolved manner along the trial, and neural activity was projected at every time onto the current first axis in each case.

When separating trials by color condition, the single-trial PCA projections showed time courses resembling those observed at the single-channel level. Differences between color conditions -quantified by significant mutual information (MI)- arose mainly around the presentation of visual cues (example site, Figure 2-e, top). In contrast, LDA projections were able to track color information throughout the trial, reflected in longer-lasting periods of significant MI, extending into the delay periods (example site, Figure 2-e, bottom).

Figure 2 - Laminar dynamics in the motor cortex encode task-related variables. *a, Monkeys performed a temporally predictive delayed match-to-sample reaching task. In each trial, a color-coded selection cue (SEL) indicated the color to attend to (sample). Then, three differently colored spatial cues (SCs) -only one matching the color of SEL- and a GO signal were presented. After GO, the monkeys had to perform a center-out reaching movement to the memorized location of the color-matching SC (match) to obtain a liquid reward. The SCs were always presented in the same order (SC1 blue – SC2 green – SC3 pink), but their location was random (1 out of 4 possible diagonal locations). Each delay lasted 1s and each visual cue 300ms. This task requested monkeys to transform the cue identity (color condition) into a movement direction (match SC). b, Left: Laminar sites plotted on the MRI-based cortical surface reconstruction of monkey T (anterior left, posterior right); AS: arcuate sulcus, CS: central sulcus. Right: Example multi-unit activity (MUA) recorded with a linear multielectrode array at one site. c, Trial-averaged MUA separated by color-condition (SEL identity) for one channel per layer, spanning the cortical column. Shaded area: 95% confidence intervals (CI). d, Same as in (c) for green (green-SEL) trials separated by movement direction; black: upper right, purple: lower right, yellow: lower left, orange: upper left. e, Neural activity projected onto the first axis of Principal Component Analysis (PCA, top) and Linear Discriminant Analysis (LDA, bottom), calculated in 200ms windows with 25ms shift. Time-resolved projections were concatenated to reconstruct the trial. Color condition (SEL identity) means are displayed as color-coded lines with 95% CI (shaded). Graybars below indicate significant*

For movement direction, PCA projections did not capture direction-specific dynamics,
with not significant MI at any point (example site, Figure 2-f, top). LDA projections, however,
still diverged according to target direction, starting from the moment in which the valid spatial
cue (color-matching SC) was presented, i.e. when information about the target movement
direction first became available (see example session for green trials, in which valid direction
was presented at SC2, Figure 2-f, bottom).

Therefore, the directions of maximum variability do not align with the coding axes for
task-related variables. This indicates that most inter-trial variability is task-unrelated -or at
least not directly linked to color and target direction encoding- and that supervised
approaches such as LDA are required to better disentangle the spatiotemporal organization
of task-relevant activity fluctuations in laminar space.

Revisiting coding subspaces along the trial

Since LDA latent dimensions effectively captured the dynamics of the two main task-
related variables, we next investigated the contributions of different layers to generate these
coding subspaces and how stable they were throughout the trial.

At every time, an LD direction is recomputed and defined by a vector of entries over
every channel depth in laminar space, providing the weighted and signed contribution of each
channel's activity to the considered coding subspace. To visualize channel contributions, we
plotted these dynamically-changing weights for $LD1_{color}$ and $LD1_{direction}$ (example site, Figure 3-
a, color: top, direction: bottom) in a matrix form where each vertical slice represents the LD
at a different time. The primary coding axes for both color and direction displayed strong
heterogeneity in channel contributions within and across layers, alongside remarkable
temporal changes.

Visual inspection of the computed LDs did not reveal any marked concentration of
relevant weights at specific depths. To quantify the degree of laminar spread in the weights
defining the coding subspaces, we used a Shannon entropy metric such that a value of one
indicates equal contributions from all channels, while a value of zero indicates that the LD is
perfectly aligned with activity in just a single channel. Here, all subspaces (both variables at all
times) exhibited an entropy level around 0.75, implying that information was highly
distributed along the column (example site, Figure 3-b); besides the shown example session,
similarly large values were generally observed across all sites recorded (Figure 3-c).

We then checked whether these spatially distributed laminar coding subspaces were
retrieved at different times. To this end, we performed a recurrence analysis to quantify the
similarity between LDs extracted at any possible pair of time points along the trial (in terms of
a bounded cosine similarity, where 0 means orthogonality of vectors and 1 perfect alignment).

Clear task-related cross-temporal patterns emerged for both color and direction, as shown in Figure 3-d, by the recurrence matrices for the example session displayed in Figure 3-(a, b), and especially from the recurrence matrices in Figure 3-e, averaged over all recording sites for each of the monkeys. Blocks and stripes in the recurrence matrices denote phenomena such as transient stabilization of a coding subspace (a block along the diagonal; larger blocks indicate longer stabilization) or repeated recruitment of previously used coding subspaces (off-diagonal stripes or blocks, denoting enhanced inter-time similarity of LDs).

Figure 3 - Laminar coding spaces are revisited along the trial. a, Heatmaps displaying the weights of all time-resolved LD1$_{color}$ (top) and LD1$_{direction}$ (green trials, bottom) models for the example site. Horizontal lines indicate the boundaries of cortical layers; x-axis: trial time, y-axis: channels. b, Time-resolved Shannon Entropy of weight vectors in (a). Values of zero indicate all weight in a single channel and one equal contribution from all channels. x-axis: trial time. c, Distribution of the average entropies of LD1$_{color}$ (gray) and LD1$_{direction}$ (green) weights across all recorded sites; whiskers indicate 5th-95th CI. d, Cross-temporal map of absolute cosine similarity across pairs of weights in (a); left: LD1$_{color}$, right: LD1$_{direction}$; x-axis, y-axis: trial time. Maps represent the average across 50 similarity maps built on resamples of training data. e, Same as in (d) but averaged per monkey across all sites; left: Monkey M, right: Monkey T, top: LD1$_{color}$, bottom: LD1$_{direction}$ in green trials.

Focusing first on the color encoding, and specifically on the dynamics LD1$_{color}$ axis, we observed in the session-specific recurrence matrix (Figure 3-d, left) the emergence of off-diagonal stripes and off-diagonal blocks, reappearing when new spatial cues were presented. These cue-aligned off-diagonal blocks persisted even after averaging across all recording sites, being particularly evident for the first monkey (Figure 3-e, top left) and more blurred for the second (Figure 3-e, top right).

The off-diagonal blocks observed in Figure 3-e, top indicate that the coding subspaces carrying information about color conditions in the epochs following SC2, and SC3 largely

overlap with the coding subspace already recruited at SC1 (and, for monkey M, even with that engaged earlier at SEL cue). At the single-session level (Figure 3-d, left), the off-diagonal stripes connecting these block locations reveal an even tighter temporal replication of the precise sequence of color-coding subspaces, recruited throughout the delay periods between two consecutive cue presentations.

Considering next the encoding of target direction, the dynamics of the direction-related LD1 differed from those of the color subspaces. The target direction cannot be determined until the spatial cue matching the selection cue color -hereafter the matching cue- is presented (e.g., before SC2 if the color pre-cued at SEL is green). Figures Figure *3*-d (right, single representative session) and Figure *3*-e (bottom, averaged across sessions) show recurrence matrices for the $LD1_{direction}$ in green trials, while analogous matrices for blue and pink trials are provided in Suppl.Figure 1-b. Before the presentation of the matching cue, the direction-coding subspaces evolved in a largely random manner. After the matching cue, however, the direction-coding space stabilized, as indicated by a darker diagonal block appearing immediately after the cue (compare Figure 3-e, bottom, for green trials where the matching cue is SC2, with Suppl.Figure 1-c for blue and pink trials, where the matching cues are SC1 and SC3, respectively). Notably, we observed a spatial alignment between the direction-coding subspace during the delay following the matching cue and that preceding the GO signal, consistent with the notion of a preparatory subspace that is revisited prior to movement initiation.

While the averaged recurrence $LD1_{direction}$ matrices for both monkeys preserved several salient elements of single-session matrices, some differences were observed across the two animals. These differences likely reflect previously reported differences in spontaneous micromovements **(Nougaret *et al.*, 2024)**, more transient in monkey M than in monkey T (see discussion). Specifically, in Monkey T, the stability of the direction-coding subspace was weaker but persisted longer after the matching cue, extending up to movement onset following GO. By contrast, in Monkey M, stability was more intermittent, but the pre-GO and post-match delay coding subspaces showed stronger alignment. Irrespective of subtle differences between monkeys and encoded variables, these results indicate that the dynamics of coding subspaces were strongly constrained by the task structure.

In the following, we focus on specific cases of *reusing* and *recycling* of reference coding subspaces observed at selected moments of the task. In the final results section, we will then adopt a more continuous, time-resolved approach to examine the spatiotemporal reconfiguration of coding subspaces throughout the task.

The functional subspace encoding cue identity is recycled as a match subspace

Given that similar color-encoding subspaces were revisited during visual cue presentations (Figure 3-e, top), we first analyzed how color-related information was specifically represented within these subspaces by projecting single-trial laminar MUA onto one of them. As a reference, we chose the subspace encoding cue identity during SEL. To perform the task, monkeys had to select the spatial cue matching the selection cue (SEL) color. Therefore, we hypothesized that the laminar space encoding the cue identity (color) during SEL could either be reused during spatial cues to again encode the same cue identity/color (H_1) or recycled as a match space (H_2) (Figure 4-a). These two hypotheses yield specific predictions about how the cue-identity space at SEL should generalize:

Under H_1, the cue-identity subspace would be functionally reused as a *pure color-coding space*, such that the population state represents the color displayed on the screen, regardless of whether the currently shown cue is a distractor or the matching spatial cue. In this case, the codes defined for blue, green, and pink cues at SEL would be reused for all trials at SC1, SC2, and SC3, respectively. Consequently, trajectory snippets for single trials associated with different colors, when projected onto the reference coding subspace, should converge toward distinct split locations characteristic of each color, independently of when that cue was presented (Figure 4-a, bottom left).

In contrast, H2 proposes that the cue-identity subspace at SEL is functionally recycled as a *match space* during the presentation of the SCs (Figure 4-a, bottom left). Under this scenario, what is encoded in the reference subspace at later SCs is not the color displayed on the screen, but instead whether the cue matches the color originally presented at SEL. In other words, the code no longer represents cue color per se, but rather its validity -i.e., its pertinence for extracting directional information. Accordingly, the projected multilaminar neural activity snippets would converge toward just two split locations, corresponding to "valid" or "non-valid," irrespective of the specific color shown (e.g., blue-trial snippets at SC1, green-trial snippets at SC2, and pink-trial snippets at SC3 would all converge, after projection onto the reference subspace, toward the common spot encoding the cue as "valid").

To test these hypotheses, we first built the reference coding subspace for cue identity at SEL. As there are three colors to discriminate, such a subspace (LD_{color}) is spanned by two discriminant vectors whose weights over different columnar depths -the different channels in the laminar probe- are shown to the left of Figure 4-b for a representative site. To the right of Figure 4-b we then show the average projections of trials for different color conditions (SEL color) over the first axis of this reference space. We observed that the condition-averaged activity presented a peak in correspondence of each of the visual cues. However, the amplitude of the SCs peaks was higher whenever they matched the color condition, the first evidence that cue color is processed differently across trial epochs.

Figure 4 - The coding space for cue identity is functionally recycled as a match space. *a, Schematic illustration of two hypothesis: cue identity subspace reuse for color encoding (H₁) or recycling for match encoding (H₂). Cue identity space revisiting was tested based on cosine similarity between SEL and SC epochs (upper left). An LDA model was trained at the selection cue (SEL, train epoch) to separate color conditions (blue, green and pink). Neural activity during spatial cues (SCs, test epochs) was then projected into this model. Bottom left: H₁ (color encoding). Stars represent trial-averaged states for each SC, color-coded by SC color (SC1: blue, SC2: green, SC3: pink). Bottom right: H₂ (match encoding). Upwards triangles indicate trial-averaged states for matching trials (e.g. green at SC2) and downwards triangles states for non-matching trials (e.g. green at SC1/SC3). b, Left: Channel weights for LD1/LD2 at SEL. Right: Trial-averaged projections on LD1, separated by SEL color; line: mean, shaded: 95% CI, x-axis: trial time. c, Condition-averaged trajectories around SEL in the LD1-LD2 space, color-coded by SEL color. Large colored dots represent the state of maximum cross-condition variance during the train epoch. Color-coded stars describe trial-averaged projections on SC1 (blue), SC2 (green) and SC3 (pink). d, Same LD1-LD2 space as in (c); with trial-averaged projections color-coded by the SC color. Upwards triangles: matching trials, downwards triangles: non-matching trials; (e.g. match: green upwards triangle for green trials at SC2; non-match: green downwards triangle for blue and pink trials at SC2). Gray line: validity axis. e, Distribution of the single-trial distance metric (Δ_dist), computed as the difference between distance to correct (d_c) and incorrect (d_i) clusters; dark gray: data, light brown: permutations. Analysis was repeated across 200 train/test splits and 1000 permutations to test for SEL*

space (train epoch), H_1 (color encoding) and H_2 (match encoding). f, Summary across sites. Left: Monkey M, right: Monkey T. Only sites with a significant SEL space (Δ_{dist} data < 95th percentile of permutations) were included. Dots: mean Δ_{dist} for each test: SEL, H_1, H_2 (both data and permutations); dark connecting lines: significant results after Bonferroni correction. (b-e), Example site: Mo180412002-pr1.

An even stronger indication against the pure color space hypothesis (H_1) comes from bidimensional projection on the plane spanned by the first and second LD axes (Figure 4-c). The big dots correspond to the moment of maximum cross-condition variance in the train epoch, colored based on the SEL cue identity; the small colored dots represent the condition-averaged projected trajectory snippets during SEL. We then projected in this same reference space trajectory snippets during a small window surrounding SC1, SC2 and SC3 presentations and marked as colored stars (respectively blue, green and pink) the average barycenter of these projected test snippets. We observed that these stars clustered in the middle of the plane, far from the split locations coding SEL cue identity. Therefore, we conclude that this reference subspace was not reused to encode color, since colored stars did not overlap with colored dots.

To test for H2, we again projected laminar MUA on the same reference subspace, but according to a different, validity-based split. Specifically, in Figure 4-d we show averaged trajectory projections and average barycenters for trials at SC1, SC2 or SC3, color-coded by spatial cue color and further separated by validity condition. Upward triangles correspond to barycenters of MUA trajectory snippet projections of matching cues (e.g. around SC1 for blue trials). Instead, downward triangles correspond to the barycenters in non-matching condition (e.g. around SC1 for green and pink trials). For reference, we also show the colored-dots corresponding to the original color separation at SEL (same as Figure 4-c). Here, we can observe a clear distinction between two clusters, with barycenters grouped according to the validity or not (match vs non-match conditions) of the currently shown cue, irrespective of its color, precisely in line with the predictions of H2 and in contrast with the ones of H1. We could thus find a one-dimensional axis embedded in the originally bidimensional reference coding plane which was able to separate valid from invalid when the data was projected onto it. This corresponds to a case of recycling –transformation of representation beyond identical reusing– of the original coding subspace for cue identity.

Figures Figure *4*-c,d provide visualizations of average trial dynamics of a representative recording session. To validate these observations across all individual trials and cortical sites, we employed a quantitative statistical measure. Specifically, for each recording site we constructed a site-specific reference color coding subspace at SEL and determined, within this space, the barycenters of the categories to be discriminated (blue vs. green vs. pink at SEL; valid vs. invalid at later SCs). For each individual trial, we then computed the average distance of projected snippets to these category barycenters. The rationale is that a decoder generalizes properly if the distances of a trial's projection to the wrong category barycenters are significantly larger than its distance to the correct barycenter, with significance assessed

via permutation testing. We thus quantified this effect through the difference Δdist between distances to incorrect versus correct categories under different conditions.

Figure Figure *4*-e illustrates statistical testing of generalization based on Δdist for a specific site, while results from other sites in both monkeys are summarized more compactly in Figure 4-f. As expected, projected snippets at SEL clustered significantly closer to the correct color category barycenters than to others, with cross-validated Δdist consistently above chance (Figure 4-e, left). In contrast, when projecting snippets from later SCs, the separation by color was no longer significant (i.e., H1 fails), as Δdist did not exceed chance levels (Figure 4-e, center). However, when discriminating instead between the two categories "valid" vs. "invalid," Δdist for projected snippets from later SCs rose again consistently above chance (i.e., H2 is validated, at least for this recording site; Figure 4-e, right).

The recycling of the color-identity subspace at SEL differed between the two monkeys. In monkey M, where the SEL color subspace revisiting at later SCs was clear already from the site-averaged similarity map (Figure 3-e, top left), 18 out of 27 sites presented a significant cue identity space at SEL. From those, H1 was rejected for all of them (light lines, not significant) and H2 was confirmed in 14 out of 18 sites (dark lines, significant) (Figure 4-f, left). This indicates that, for this monkey, the cue identity space at the selection cue was *recycled* as a match-to-sample space at the spatial cues, enabling the transformation of the cue information into a match/non-match representation.

In Monkey T, by contrast, we already noted that the average recurrence matrix for color-coding LDs (Figure 3-e, top right) lacked the off-diagonal block indicating cross-similarity between SEL and spatial cues. This is explained by the fact that, for most sites in monkey T, we were unable to identify a color-identity coding subspace at SEL. Indeed, such a subspace significantly discriminating cue color identity at SEL was found in only 3 out of 14 sites. In the rare cases where these cue-color subspace existed, 2 of the 3 continued to operate as color-coding spaces (consistent with H1), and 1 of them also simultaneously acted as a validity-coding space. In conclusion, for monkey T, analysis of the recycling of cue-identity coding spaces at later SCs is largely ill-posed, as the reference subspace itself generally fails to exist. Instead, the data suggests the presence of a stable representation of the color condition across all task periods (Suppl.Figure 2), consistent with other behavioral differences observed in this animal (see discussion).

The match space is functionally reused at the spatial cues

Although Monkey T did not exhibit a clear cue-identity space at SEL that could be later recycled, the recurrence matrix (Figure 3-e, top right) nonetheless indicated the presence of persistent color-coding subspaces. We therefore examined whether an alternative reference coding subspace, extracted at a different task moment, might instead be functionally reused. Specifically, we focused on color coding subspaces at a later cue (e.g. SC1) and hypothesized

(H$_1$) that it could be reused at other cues (e.g. SC2 and SC3) to encode cue validity (Figure 5-a).

Figure 5 - The match space is functionally reused across spatial cues. *a, Schematic illustration of the match space reusing hypothesis across spatial cues (H$_1$). Match space revisiting was tested based on cosine similarity among SCs (upper left). An LDA model was trained at SC1 (train epoch), to separate match from non-match (blue vs. others). Neural activity during the other spatial cues (SC2/3, test epochs) was projected into this model. Bottom: H$_1$ (match encoding). Upwards triangles indicate trial-averaged states for matching trials (e.g. green at SC2) and downwards triangles states for non-matching trials (e.g. green at SC1/SC3). b, Left: Channel weights for LD1 at SC1. Right: Trial-averaged projections on LD1, separated by SEL color; line: mean, shaded: 95% CI, x-axis: trial time. c, Condition averaged trajectories around SC1 in the LD1 axis. Blue triangles represent the maximum cross-condition variance (match/non-match) during the train epoch. Color-coded triangles describe the trial-averaged projections on the other SCs color coded by SC color. Upwards triangles: matching trials, downwards triangles: non-matching trials. d, Distribution of the single-trial distance metric (Δ$_{dist}$), computed as the difference between distance to correct (d$_c$) and incorrect (d$_i$) clusters; dark gray: data, light brown: permutations. Analysis was repeated across 200 train/test splits and 1000 permutations to test for SC1 match space (train epoch), SC2/SC3 match spaces (test epochs); stars denote significant difference. e, Summary across sites. Left: Monkey M, right: Monkey T. Only sites with a significant SC1 match space (Δ$_{dist}$ data < 95th percentile of permutations) were included. Dots: mean Δ$_{dist}$ for each test: SC1, H$_1$(SC2/SC3) (both data and permutations); dark connecting lines: significant results after Bonferroni correction. (b-d), Example site: t150327002/3-pr1.*

To test this hypothesis, we constructed a new reference LDA model (e.g., at SC1) to discriminate between valid and invalid trials. Since the categories to be separated were now only two (valid vs. invalid), the extracted coding subspaces were explicitly one-dimensional. As before, the weights of the discriminant vectors were not concentrated in a few layers but were broadly distributed across cortical depths (see example site for Monkey T in Figure 5-b, left).

When examining the time courses of trial projections onto this axis, averaged by color condition, we observed a marked peak at the matching cue, already suggesting subspace reusing (Figure 5-b, right). An alternative representation is shown in Figure 5-c, where we illustrate the average time evolution of trajectory snippets around SC1, projected onto the reference LD axis for blue (valid) and green/pink (invalid) trials. These projections converged to distinct barycenters (upward vs. downward blue triangles), well separated along the reference LD. Similarly, trajectory snippets around the other SCs converged to distinct barycenters (upward vs downward triangles) depending on their validity. Across all cases, barycenters clustered along the reference LD axis according to validity, irrespective of color identity or task epoch.

We next quantified discrimination at the single-trial level using the Δdist metric. Individual trials were separated well above chance not only around SC1, where the reference space was constructed, but also when reusing the same space to discriminate validity at later cues SC2 and SC3 (Figure 5-d, example session). This ability generalized well across monkeys and recording sites (15/20 in M; 4/8 in T; Figure 5-e).

In summary, both monkeys displayed a visual subspace encoding cue validity - independently of cue identity- that was functionally reused during spatial cue presentations. In Monkey M, this subspace was recycled from the cue-identity space, whereas in monkey T it was restricted to spatial cues. In both cases, this subspace might serve as a gating mechanism, determining whether incoming spatial information is retained or ignored.

Two distinct subspaces -visual and motor- encode target direction

After the encoding of cue identity and validity, we investigated the encoding of direction. Specifically, we hypothesized that a coding subspace for the target direction existed, and was reused across trials whenever the correct SC was presented (H_1). Note that target direction refers to the movement direction to be performed at GO, which can only be inferred at the time of the matching cue presentation. This distinction will become important when considering the encoding of distractor directions, also visually shown, but not task relevant.

If such a coding subspace existed (H_1), the same code for target direction would be preserved across spatial cues (Figure 6-a). The directional code would be maintained when building a subspace in one cue and projecting the activity around the others (e.g. building the subspace on green trials at SC2 and projecting blue trials at SC1 or pink at SC3, Figure 6-a, bottom).

For illustration, we first built the LDA direction subspace for green trials at SC2. The first two discriminant axes of this subspace are shown for an example site in Figure 6-b(left), together with trial projections onto the first discriminant axis (right). Because target direction is inferred at different cues depending on trial color identity, we plotted separate direction-averaged time series for blue, green, and pink trials. As with all other coding subspaces

examined so far (and consistent with the entropy analyses in Figure 3-c), the first two discriminants for target direction exhibited weights broadly distributed across cortical depths. The projected MUA time series likewise showed a clear separation between trials with different visually displayed target directions at the matching cue epoch (SC1 for blue, SC2 for green, SC3 for pink), but not at other cues. This observation already is compatible with hypothesis H_1: direction-coding subspaces constructed at a matching cue would encode target directions at other matching cues, but not generic directions at arbitrary cues (see later section).

The 2D projections onto the plane defined by the two LD axes provided an even clearer visualization of whether a direction-specific code was reused across matching SCs (Figure 6-c). As in previous figures, large squares represent the barycenters of green trials at SC2 (training epoch), with colors indicating the target direction. Direction-averaged trajectories are also shown, highlighting their divergence toward distinct barycenters corresponding to visually presented directions. In addition, we projected trajectory snippets from blue trials at SC1 and pink trials at SC3 onto the same direction-coding reference space built at SC2. Their barycenters are shown as smaller squares using the same directional color code. Further generalization to other cues is addressed in Suppl.Figure 3-a.

The spatial organization of the direction representation in the train epoch was preserved during the test epochs, i.e. small colored-squares clustered together with their same-color big squares (example site, Figure 6-b), consistent with H_1 predictions. Visual impressions from this example projection plot are once again confirmed by the significance of Δdist analyses at the single-trial level and over distinct sites (see Figure 6-d for example site and Figure 6-e for all sessions in both monkeys). In monkey M, 24 out of 28 sites showed significant generalization at SC2 and 22/24 sites confirmed H1 (Figure 6-e, Monkey M, left). Similarly, in Monkey T, the visual target direction space for SC2 was found in 9 out of 14 sites and 6 out of these 9 confirmed H1 (Figure 6-e, Monkey M, right). Similar generalization performance was observed when constructing the reference space at other matching SCs (Suppl.Figure 3-b).

These results demonstrate the existence of a target-direction encoding space that is reused whenever the matching spatial cue is encoded.

When considering direction encoding, a potential ambiguity arises between visual and motor interpretations. At SCs, directional information reflects the screen location of the visual cue, a *visual* notion of direction. Around the GO signal, however, movement is executed (and prepared) in a specific direction, corresponding to a *motor* notion of direction. Which type of direction is represented in the reused subspaces identified above?

***Figure 6 - There is a visual, non motor, space functionally reused to encode target
direction.*** *a, Schematic illustration of the target direction space reusing hypothesis across spatial cues
(H_1). An LDA model was trained in green trials at SC2 (train epoch), to separate target direction (4
possible). Neural activity during the other spatial cues (SC1/3, test epochs) was projected into this
model. Bottom: H_1 (target direction encoding). Big squares represent green-trial-averaged states for
the four target directions at SC2. Small squares depict upper-left direction trial-averaged states for blue
condition during SC1 (top) and pink condition during SC3 (bottom). b, Left: Channel weights for LD1/LD2
at SC2. Right: Trial-averaged projections on LD1, separated by movement direction. From top to
bottom: blue, green, pink projected trials. Line color: black: upper right, purple: lower right, yellow:
lower left, orange: upper left. Line: mean, shaded: 95% CI, x-axis: trial time. c, Condition-averaged
trajectories around SC2 in the LD1-LD2 space, green trials color-coded by target direction. Large colored
squares represent the state of maximum cross-condition variance during the train epoch. Color-coded
small squares describe trial-averaged projections per movement direction during test epochs: blue trials
projected at SC1 and pink trials at SC3. d, Distribution of the single-trial distance metric (Δ_{dist}), computed
as the difference between distance to correct (d_c) and incorrect (d_i) clusters; dark gray: data, light
brown: permutations. Analysis was repeated across 200 train/test splits and 1000 permutations to test
for SC2 target direction space (train epoch), SC1/SC3 target direction spaces (test epochs); stars denote
significant differences. e, Summary across sites. Left: Monkey M, right: Monkey T. Only sites with a
significant SC2 target direction space (Δ_{dist} data < 95^{th} percentile of permutations) were included. Dots:
mean Δ_{dist} for each test: SEL, H_1 (both data and permutations); dark gray connecting lines: significant
results after Bonferroni correction. f, Left: Schematic illustration of the target direction space recycled
as the preparatory space (pre-GO, test epoch). Right: Same LD1-LD2 space as in (c); with green trial-
averaged projections around the GO signal, color-coded by the target direction. (b-d, f), Example site:
Mo180412002-pr1.*

To address this question, we projected MUA trajectory snippets recorded just before the GO signal into the reference space constructed at SC2, separating trials again by the target direction. The barycenters of these projections are shown as crosses, color-coded as in Figure 6-f (example site). In this session, the crosses did not align with the square clusters, indicating that the code expressed at SCs for visually presented target directions was not recycled in the pre-GO window, where direction reflects motor preparation. The direction-encoding subspaces constructed at SCs, and reused across them, capture specifically *visual* -but not motor- target direction. The single-trial quantification across sites and monkeys confirmed and validated this finding: the visual target direction space at SC2 was not recycled as a preparatory space before the GO (recycling occurring in only 1 out 24 sites in Monkey M and none out 9 sites in Monkey T, Suppl.Figure 5-a, left).

This negative result could have been trivially explained by the absence of a preparatory space, i.e., by a lack of detectable direction encoding prior to the movement. To rule this out, we built a new reference direction-coding subspace in the pre-GO period, constructing cross-validated LDAs for the planned movement direction. The majority of sites exhibited a significant preparatory space when trained and tested within this epoch (21/24 in monkey M; 7/9 in monkey T; Suppl.Figure 5-a, right). Thus, two distinct direction-encoding subspaces exist: one for visual target direction, reused across SCs, and another for motor target direction, specifically recruited during the preparatory pre-GO window and not recycled from earlier visual cue epochs.

Finally, we tested whether the visual target-direction encoding spaces also represented the directions of distractor cues presented at non-matching SCs, i.e., visually displayed directions not informative about the final motor output. As shown in Suppl.Figure 4(a: example site; b: generalization), in Monkey M the directions of distractor cues presented *before* the matching cue (e.g., green distractors in pink trials) were also encoded. However, the directions of distractors *after* the matching cue (e.g., green distractors in blue trials) were no longer encoded. In monkey T, we found no evidence of distractor-direction encoding.

Thus, although the visual direction-encoding subspaces constructed at SCs differ from the one recruited during motor preparation in the pre-GO window, they nevertheless prioritize motor-relevant directional information: visual directions unrelated to the target motor direction are either ignored or discarded once the target information needed for motor preparation has been acquired.

Coding subspaces in motor cortex have a fine and dynamic laminar organization

After analyzing the reuse and recycling of coding subspaces for both color and direction, we return to our initial question: are the complex operations required to process

diverse color and direction information performed by specialized, layer-localized populations, or do they rely on the coordinated activity across multiple layers?

By identifying multiple coding subspaces at different task moments, we instantaneously "localized" information, i.e., at a certain time, information about a particular feature could be extracted from fluctuations along specific latent dimensions. However, localization in latent space does not imply laminar localization. The discriminant directions defining these coding subspaces did not show strong weight concentration at a few depths, instead, weights were broadly distributed across the column. Thus, fluctuations along discriminant axis correspond to simultaneous MUA variations across multiple depths, with task-related information emerging necessarily from coordinated multi-layer activity patterns. Taken together, our findings suggest that the cortical column, rather than individual layers, operates as the functional unit.

However, depth-specific entries of LDA-defined subspaces are not perfectly uniform, unlike those of the first principal components, which capture mostly task-unrelated generic variability and display far more homogeneous weights (cf. Suppl.Figure 1-a). Although discriminant directions do not show a clear dominance of specific laminar depths over others, it is precisely through subtle heterogeneities in the relative contributions of different depths that they can be distinguished from one another, thereby opening the way to the possibility of multiplexed coding subspaces (e.g., for direction and for color). A more detailed analysis of these fine laminar involvement patterns is therefore required.

We began by analyzing the similarity of laminar weights across different discriminant directions. First, we tested whether subspaces encoding the same task-related variables were more aligned in the high-dimensional space of laminar vectors. To this end, we measured the principal angle between coding subspaces, with smaller angles indicating greater overlap and similarity between their fine laminar organization **(Knyazev and Argentati, 2002)**.

In both monkeys, the subspaces coding for the same latent variable were better aligned, (Figure 7-a), consistent with the reuse findings described above for both cue validity and direction. On the contrary, subspaces computed at the same time-window but coding for different variables presented a significantly reduced overlap (Figure 7-b; 17/27 in Monkey M and 5/14 in Monkey T). These representations, although all broadly distributed across cortical depths and layers, remain thus distinguishable owing to subtle variations in their non-localized laminar profiles, enabling multiplexed representations.

The analyses in Figure 7-a focused only on selected reference coding subspaces. However, as shown in Figure 3, linear discriminants can be computed at every time point along the task, and their fine laminar structure varies continuously. As summarized in Figure 7-c these laminar-weight variations can be interpreted geometrically as a continuous change of orientation of the coding subspace encoding a specific variable of interest (e.g., selection cue color). Such dynamic reconfiguration can be described as a trajectory in the "space of

subspaces", mathematically the so-called Grassmannian manifold over the space defined by laminar depths.

Figure 7 – Laminar trajectories of coding subspaces are temporally organized. *a, Average subspace angle between pairs of coding hyperplanes across all sites, with darker color for smaller angle. Left: Monkey M, right: Monkey T. b, Statistical summary across sites. Top: Monkey M, bottom: Monkey T. Difference in average angle between hyperplanes coding for the same variable (within) vs. coding for different variables (across). Negative values mean hyperplanes are better aligned when coding for the same variable. Dots: angular difference for data (dark gray) and permutations (light brown); dark gray connecting lines: significant results (p_val <0.05). c, Schematic illustration of the 'state-space of subspaces'. Left: Hyperplane encoding color condition at time t1, represented as the LD1 vector of channel weights. This coding hyperplane rotates in time, and the evolution of the LD1 can be captured by reducing the dimensionality of the coding vectors. Right: Each hyperplane was reduced to two dimensions with PCA. A trajectory in the state-space of subspaces (PC1-PC2) describes hyperplane rotations over time, for activity (PCA) and coding (LDA) subspaces. d, Example trajectories in the state-space of subspaces. Top: trajectory of SEL cue information (LDA$_{color}$, Mo180412002-pr1). Bottom left: trajectory of activity (PCA, Mo180412002-pr1). Bottom right: trajectory of SEL cue information (LDA$_{color}$, Mo180619002-pr1); x-axis: trial time, y-axis: PC1, z-axis: PC2; color: ratio of weight strength between superficial and deep channels.*

These trajectories of coding subspaces can be visualized via dimensional-reduction approaches. For instance, one can apply a principal component analysis to the set of time-dependent principal discriminant axes for a given feature (e.g., the LD1$_{color}$) and project each time-resolved discriminant direction onto the first two principal components. Time can then be unwrapped as a third dimension, producing plots such as Figure 7-c (right), where each dot represents the LD1$_{color}$ vector at a given time. The resulting trajectory captured the temporal evolution of the coding space.

In this representation, the color-coding subspace trajectory formed a characteristic helix, whose loops were paced by the task structure (Figure 7-d, top, example site). This helical shape indicates that, after each visual cue, the principal axis of the coding subspace drifts

along a specific trajectory that is approximately repeated across task blocks and reset to a similar starting condition at each new cue. Such helical trajectories were systematically observed across many sites, albeit with varying degrees of precision (Figure 7-d, bottom right; Suppl.Figure 6).

We emphasize that this peculiar organization of fine laminar-weight variations characterized the dynamics of coding subspaces, but not the raw MUA activity itself. At each time point, the direction of maximum variability in neural activity is captured by the first principal component of MUA computed within the corresponding time window. Similar to LDA, the principal components can also be projected into a reduced space, describing the activity trajectory in the space of subspaces. However, this trajectory proved to be remarkably trivial and unrelated to the task (Figure 7-d, bottom left). The dominant variability of neural activity evolves along a task-independent direction, corresponding to relatively homogeneous up- and down-scaling of activity across layers (cf. Suppl.Figure 1-a). Task-relevant information instead resides in smaller fluctuations along discriminant axes, which are superimposed on this larger, unspecific variability. The instantaneous position of a discriminant axis thus indicates where to look for task-related information across laminar depths, and the trajectory of its evolution constitutes a trajectory of information-bearing fluctuations, tiny signals, composed of coordinated multilaminar activity, embedded within much larger, task-irrelevant variability. In short, while trajectories of raw activity fluctuations are trivial, trajectories of information-carrying modulations are highly structured.

The presence of a helical trajectory of information-coding subspaces indicates task-related variations in the fine, inhomogeneous laminar involvement patterns that define these subspaces. But how, specifically, did these laminar patterns vary?

To uncover potential spatial structure in the temporally organized variations of coding subspaces, we computed an index of layer involvement (see *Index of layer involvement*), such that large positive (negative) values indicate relative stronger weights in superficial (deep) layers. When coloring the helical trajectories by this index, we observed a characteristic alternation of red and blue segments. This pattern indicates that information-carrying fluctuations tend to shift between different depths of the column, propagating from superficial to deep layers and vice versa over the course of a trial. Similar dynamic patterns were observed across many sites (Suppl.Figure 6). However, the specific direction of propagation varied across sites. In some sessions, color-related information was initially concentrated in superficial layers and then propagated toward deeper layers (e.g., Figure 7-d, top). In others, the pattern was reversed, with an initially ascending propagation from deeper to superficial layers (e.g., Figure 7-d, bottom right). What is ubiquitous is the presence of propagating information across laminar depths, not the specific direction in which it propagates.

Discussion

Our results show that task-related information is not confined to a few specific layers at any given time. Instead, it is encoded through the coordinated activity of the entire columnar circuit in the motor cortex. These coding subspaces -defined as lower-dimensional hyperplanes- are flexibly reused and recycled throughout the trial: related variables, such as cue identity and match, recruit overlapping subspaces, whereas the same variable, such as target direction, engages distinct subspaces depending on its behavioral context. Consequently, multiplexing of distinct task-related variables emerges from subtle inhomogeneities in layer contributions within highly distributed activity patterns. Moreover, this coordination-based encoding is dynamic, with alternating and time-varying enhancement of superficial and deep layer contributions.

Cortical columns allow multiplexing in motor cortex

The extensive recurrent connections dominating the cortical columns allow them to transiently maintain incoming information and potentially operate as individual processing units (Nolan *et al.*, 2025). In this study, all laminar coding subspaces identified in the motor cortex were highly distributed, supporting the hypothesis that the functional unit corresponds to the entire column. In agreement with (Opris *et al.*, 2011, 2015; Opris, 2013), coordination across layers generated columnar activity patterns capable of encoding multiple task-related variables. In their case, neurons in both superficial and deep layers were equally modulated, reflected in our study as distributed lower-dimensional subspaces capturing the states and trajectories of the latent variables. In contrast, Chandrasekaran et al. (2017) argued for a layer-based computational unit in premotor cortex. They reported an overall superficial-to-deep decrease of visuomotor index, suggesting that decision-related activity was more prominent in superficial layers, together with an earlier onset of decision encoding in this layer (~15ms). However, their depth profile of index followed a cubic trend, increasing again towards the deepest channel (at 2.5mm), and individual sites exhibited notable laminar variability. The difference of laminar coverage between their study (~2.3mm) and ours (>4mm), along with this site-by-site variability, could therefore account for the apparent discrepancies between our results, especially considering that the reported cortical thickness of the motor cortex is around 3.5 mm (Koo *et al.*, 2012; Beul and Hilgetag, 2017).

If the cortical column operates as a distributed functional unit, a central question is how it can simultaneously encode multiple variables. Multiplexing has been largely associated with the mixed selectivity at the single-unit level, which increases the dimensionality of the population-level representations (Rigotti *et al.*, 2013; Fusi, Miller and Rigotti, 2016; Tye *et al.*, 2024; Zhang *et al.*, 2025). Our findings suggest that an analogous principle applies at the laminar scale: multiplexing arises from the coexistence of variable-specific subspaces within the cortical column. The partial overlap of these subspaces mirrors the mixed selectivity of

neurons, suggesting that the column generates a high-dimensional laminar code potentially enabling the linear decoding of multiple task variables by multiple downstream readouts.

Despite layer V being traditionally considered the main output pathway of the motor cortex towards subcortical structures and spinal cord **(Jones and Wise, 1977; Dum and Strick, 1991; Harris and Shepherd, 2015)**, recent evidence indicates a more complex picture. For instance, **Borra et al. (2021)** reported equally strong cortico-striatal projections from layers III, V and VI, with distinct basal ganglia regions receiving characteristically weighted combinations of these laminar inputs. This organization suggests that downstream targets could, in principle, access parameter-specific laminar subspaces and exploit laminar multiplexing. Such subspace-specific communication channels, determined by source-target interactions, resemble the *communication subspace* concept **(Semedo *et al.*, 2019)**, extended here to the columnar network. In this context, rather than involving only layer-to-layer interactions, the communication subspace may overlap with local coding subspaces, establishing instead a multi-layer-to-region flow of information.

Different behavioral strategies across monkeys

In this study, monkeys learned a complex delayed match-to-sample task. Despite extensive training and overall correct behavioral performance, individual strategies may have emerged. The instruction was to remember the direction of the spatial cue matching the color of the selection cue. However, monkeys could either wait for the matching cue to appear or anticipate its occurrence, given that the order of the spatial cues was fixed. Based on the eye-movement profiles described for the two animals in **Nougaret et al. (2024)**, we believe that only monkey M anticipated the match. In that same study, we observed that uninstructed hand and eye movements were informative of color condition and were more stable in monkey T than in monkey M. This stability difference could account for the neural stability differences observed across monkeys (Figure 3-e), as well as for the sustained color-encoding space in monkey T (Suppl.Figure 2).

A further inter-subject difference concerned the lack of a consistent cue-identity subspace at SEL in Monkey T (Figure 4-f). Because trials were presented in blocks sharing the same selection-cue color (~15 per block), the cue identity was already predictable before presentation, and thus may not have required transient encoding at SEL.

Thus, while inter-individual strategy differences might have shaped specific encoding features, the laminar and temporal organization of the coding spaces remained largely consistent across subjects

Dynamic encoding of *cue* and *direction* in laminar subspaces

This task required the encoding of two independent parameters -cue identity and direction-whose behavioral relevance changed dynamically across epochs, providing a framework to investigate how laminar representations flexibly reorganize. The cue identity information (at

SEL) had to be transformed into a match/non-match signal to gate spatial information at the valid SC. Direction, in turn, acted as the choice parameter, yet alternated between relevant and irrelevant contexts and had to be retrieved from working memory at GO.

The encoding of target direction during the preparatory delay preceding movement has been extensively characterized in motor cortex (Tanji and Evarts, 1976; Wise, 1985; Riehle and Requin, 1989; Messier and Kalaska, 2000; Cisek and Kalaska, 2005; Churchland *et al.*, 2006; Churchland, Santhanam and Shenoy, 2006; Thura and Cisek, 2014). Our results suggest that the population preparatory space is transiently visited during the delay following the informative cue, and reemerges during the final delay before GO (Suppl.Figure 5-b). The absence of sustained directionally-selective preparatory activity in the motor cortex could be related to the long delay durations (e.g., more than 3s for blue trials) and the intervening distractor cues.

The directional tuning observed during these preparatory epochs typically differs from that during movement execution, with distinct subsets of neurons contributing to each (Riehle and Requin, 1989), resulting in largely orthogonal subspaces in population state-space (Churchland and Shenoy 2024). This dissociation between preparatory and executory subspaces parallels our finding that visual and motor subspaces accurately encoded direction, while the underlying coding subspaces were misaligned. Additionally, distractors were represented within the visual subspace -in one monkey- when presented before target information (Suppl.Figure 4). In the other cases, distractor directions were not represented within that subspace, possibly encoded along orthogonal directions, as suggested for the prefrontal cortex by Qian et al. (2025) and for the intraparietal sulcus by Ritz and Shenhav (2024).

Beyond direction, the motor cortex is also known to represent abstract rules such as serial order (Carpenter, Georgopoulos and Pellizzer, 1999; Carpenter *et al.*, 2018). Since the cue color (at SEL) indicated order in the upcoming spatial-cue sequence, its encoding might reflect the temporal estimation of the match; consistently, this effect was only observed in the monkey anticipating the relevant cues. In addition, we found validity (match/non-match) encoding during the spatial cues -a higher-order, non-visual feature directly relevant for selecting the correct information.

Taken together, these results suggest that neural activity in the motor cortex organizes into lower-dimensional subspaces whose geometry reflects not only what is encoded, but also its behavioral relevance.

Temporal recruitment of laminar coding subspaces

The idea that coordinated activity patterns across the cortical column define behaviorally relevant coding subspaces was further supported by their temporal reuse and recycling. Such subspace flexibility has recently been reported in the prefrontal cortex, suggesting that,

beyond encoding specific variables, subspaces might be optimized for certain computations **(Wentz *et al.*, 2025)**.

The low-dimensional structure describing the encoding of task-related variables is thought to form a behavior-specific neural manifold, containing all possible population states constrained both by intrinsic circuitry and extrinsic task demands **(Perich, Narain and Gallego, 2025)**. The evolution of dynamics within these subspaces remains remarkably stable across neuronal populations and even across individuals of the same species **(Gallego *et al.*, 2020; Safaie *et al.*, 2023)**, as we observed when comparing target direction representations built from different cues (Suppl.Figure 3-a).

To continuously track these latent trajectories, coding subspaces themselves underwent a dynamic reconfiguration, describing a helical trajectory in the 'space of subspaces' (Figure 7-c, top, example site). These temporally structured trajectories followed the periodicity of the task, re-tracing similar paths after each spatial cue and capturing the laminar flow of color-specific information throughout the trial. The coordinated patterns of activity across the cortical column dynamically reshaped, instantaneously localizing color information to superficial or deep layers in a site-specific manner. Such rotational dynamics have been linked to traveling waves **(Kuzmina, Kriukov and Lebedev, 2024)**; in our case, rather than reflecting traveling waves of activity (uninformative PCA trajectory: Figure 7-c, bottom left) they reflect traveling waves of information across the laminar circuit. These trajectories reveal that laminar coding patterns vary according to an organized temporal structure, effectively describing the propagation and instantaneous localization, of color information across cortical depth. In conclusion, our results highlight a previously underappreciated principle: computation in motor cortex emerges from dynamic trajectories of multilaminar information flow, not from hardwired laminar specializations.

Materials and Methods

Experimental design

Animal preparation

We analyzed an electrophysiological dataset collected in our laboratory and previously described in **Nougaret *et al.* (2024)**. In brief, the study included two adult macaque monkeys (M: 14Kg, T: 10kg, male, macaca mulatta). Animal care followed the European Commission Regulations (Directive 2010/63/EU on the protection of animals used for scientific purposes) applied to French laws (decision of the 1st of February 2013). All experiments took place in a licensed institution (B1301404), after being evaluated by the local Ethics Committee (CEEA 071) and approved by the French Ministry of High Education and Research (authorization 03383.02). The monkeys participating in this study were daily monitored to ensure their welfare and good physical condition. They were water-restricted in their cage, and liquid

reward was provided during experimental sessions. If the intake during task performance was not sufficient (below 18ml/kg), extra water and/or fruit was given in their home cage. On weekends or resting days, they received the complete ration of liquid (water and/or fruits) in their home cage. Animals were pair-housed with free access to dry pellets and regularly provided with toys and enrichment. Data from the same two monkeys, but from the other hemisphere, was used in previous studies (CITE).

Monkeys were trained to perform a visuomotor delayed match-to-sample task (see details below). Once they had learnt the task, a cylindrical titanium recording chamber (19mm inner diameter) was implanted above the motor cortex (M1 and PMd), in the hemisphere contralateral to the trained arm. MRI scans prior to surgery as well as intra-cortical electrical microstimulation (ICMS; as described in **Asanuma and Rosén, 1972**) during the first recording weeks, ensured that multi-electrode recordings targeted upper limb regions (Figure 2-e).

Behavioral setup and task

The behavioral paradigm, also described in **Nougaret *et al.* (2024)**, consisted of a highly temporally predictive delayed match-to-sample task (DMS) (Fig-2, a). The monkeys were presented with an initial color-coded selection cue (SEL), followed by three spatial cues (SCs) and a GO signal. The task required arm-reaching movements, after the GO, in the direction of the spatial cue matching the color of the SEL cue. A vertical computer monitor was used to display the visual scene, and monkeys used a handle freely movable in the horizontal plane to perform the movements. Visual targets appeared in the four possible diagonal directions.

A new trial was initiated when the monkey placed the cursor (small white square of 0.4cm edge) inside the central fixation dot (yellow flashing disc of 0.45cm radius). After a 50ms auditory tone and 1000ms central hand fixation, a selection cue (SEL) was displayed at the center of the screen during 300ms, indicating the color condition for the current trial. Specifically, SEL was one out of three possible colored polygons (blue, green or pink- 3cm radius). The offset of SEL was followed by a 1000ms delay. After that, three spatial cues were sequentially presented (SC1, SC2 and SC3) for 300ms each, with fixed inter-cue delays of 1000ms. The three SCs corresponded to a sequence of three colored circles (0.9cm radius), blue-green-pink, always presented in the same order. For each SC, all four diagonal positions were equally likely, and independent of the position of the others; this implied that consecutive SCs could be presented in the same location. After a last 1000ms delay following SC3 (last spatial cue), the GO signal was presented. At the moment of the GO, the animal was required to perform the reaching movement in the direction of the memorized valid SC (i.e. matching the SEL color). The GO signal was not directionally informative. If the monkey touched the peripheral correct target within 500ms of reaction time, the trial was successfully completed and liquid reward was delivered.

All in all, there were 192 unique trials, given by 3 possible color conditions (color of SEL) and 4 independent locations for SC1, SC2 and SC3. Trials were presented in small blocks with the same color condition (~15 trials), in order to facilitate the task. For Monkey T, only 3

out of 4 possible directions were presented each day (randomly selected in each behavioral session), to compensate for a less number of performed trials. Within the block, unique trials were pseudo-randomly selected, and incorrect trials were repeated at the end of the block until all trials were correctly executed.

Briefly, this behavioral paradigm corresponds to a temporally predictive delayed match to sample. The valid SC was cued at the trial start by SEL, and it could be temporally predicted (fixed order of SCs). The spatial location of the SCs (valid and invalid) was unpredictable.

Data acquisition

During recording days (maximally 5 days a week), a multi-electrode, computer-controlled microdrive (MT-EPS, Alpha Omega, Nazareth Illith, Israel) was attached to the recording chamber and used to transdurally insert up to five single-tip microelectrodes (typical impedance 0.3-1.2MΩ at 1,000Hz; FHC) or up to two linear microelectrode arrays (either V- or S-probes, Plexon, Dallas, TX, USA or LMA, Alpha Omega; each with 24 or 32 contacts, inter-contact spacing either 100, 150 or 200μm; 12.5 or 15μm micrometer contact diameters) into motor cortex.

We define a 'site' as the neural recording obtained from a single electrode (single tip or linear array) within a given behavioral session. When multiple electrodes were simultaneously inserted, each recording was considered a separate site. In this study, we only considered sites recorded with linear arrays.

The arrays were positioned and lowered independently within the chamber (Flex-MT drive; Alpha Omega) in each session. Individual guide-tubes for each array were used that did not penetrate the dura (no guide was used for the more rigid LMA array). The reference was specific to each array type. For the LMA (Alpha Omega) it was an insulated wire exposed at the tip, either emerged in the chamber saline, or attached with a crocodile clip to the probe stainless steel tube (which in turn was lowered into the chamber liquid, but not extending into brain tissue, as the lower part of the probe was epoxy-insulated). For the V- and S-probes (Plexon) in most cases the reference was the stainless steel shaft of the array (extending into brain tissue, in near proximity to the probe's recording contacts). In a few sessions, the reference was instead placed on a skull-screw on the more posterior headpost (6/36 sites using V-probes in monkey T) or on a screw on the saline-filled recording chamber (2/50 sites using S-probes in monkey M). For both array types, the ground was either connected to a skull-screw of the remote titanium head-fixation post, or to a screw of the titanium recording chamber.

All linear array recordings were obtained on a recording platform with components commercialized by Blackrock Neurotech (Salt Lake City, UT, USA). This system included Cereplex M digital head-stages (versions PN 6956, PN 9360 and PN 10129) connected to a Digital Hub (versions PN 6973, PN 6973 DEV 16-021, PN 10480) via custom HDMI cables (versions PN 8083, PN 8068), which transmitted signals via fiber optics to a 128 channel Neural

Signal Processor (NSP hardware version 1.0), and control software Cerebus Central Suite (v6.03 and v6.05 for monkeys T and M, respectively; running on Windows 7). Neuronal signals were hardware filtered (0.3Hz – 7.5 kHz), digitized and saved for offline analysis at a sampling rate of 30 kHz. Behavioral event codes (TTL, 8 bits) were transmitted online to the DAQ system from the VCortex software (version 2.2 running on Win XP; NIMH, http://dally.nimh.nih.gov), which was used to control the behavioral task.

Linear probe insertion and cortical layer estimation

For each site, while lowering the linear probes, the neuronal activity was monitored to determine the depth at which the first neuronal signals could be heard (hash) and seen on DAQ monitor, on the deepest probe channels. Typically, the contacts just above the ones with the first multiunit activity would have a clear heartbeat signal in the LFP, confirming their position inside the dura. The contacts above would typically have much more noise (incl. 50Hz line noise), since we only filled the recording chamber with saline after having correctly positioned the probe. The probes were then moved down in small regular steps of 50-100 microns (micrometers), while observing that the neuronal and heartbeat signal would shift upwards along the contacts. When all but 2-3 contacts were inside the brain, the probe was left in place for 1-3H, to allow the tissue to settle around the probe before we started the neuronal recordings. If we then observed neuronal activity on all contacts, we retracted the probe until we observed heartbeat on the top 1-2 contacts, and neuronal signals only from contacts 2 or 3 and below. Sometimes the neuronal tissue would still drift up slightly around the probe during the recordings, but typically less than the spacing between neighbouring channels. To counteract the effect of such drift in the MUA signal, we adopted a drift correction pre-processing step (see below).

A slightly tilted adapter added to the recording chamber ensured that the probes would penetrate the cortex perpendicular to the cortical layers, as long as we remained sufficiently distant from landmarks such as the central and arcuate sulci and the precentral dimple. The positions of these landmarks were estimated from anatomical MRI scans and confirmed with the ICMS chamber mapping done with single electrodes in the initial recording sessions.

Cortical layers were defined based on depth from the dura, individually for each site. The macaque M1 and PMd is about 3.5mm thick, on the gyral surface **(Koo *et al.*, 2012; Beul and Hilgetag, 2017)**. This thickness was confirmed in our animals with anatomical MRI). As the macaque cortex has an approximate equal thickness of superficial and deep layers **(Hutsler, Lee and Porter, 2005)**, we considered the upper 1.8 mm as superficial layers (L2/3) and anything below as deep layers (L5/6). Layers 2 and 3 were grouped together -given the absence of a clear anatomical boundary- and instead subdivided into L23-SUP (superficial half) and L23-DEEP (deep half). Channels extending 0.85 below L23-DEEP were assigned to layer 5 (L5), and deeper channels to layer 6 (L6). Since some linear arrays spanned up to 4 mm depth, L6 channels may have included interstitial neurons from the underlying white matter. These

interstitial neurons are thought to represent late-born layer VI neurons that failed to fully migrate into the cortical plate **(Kostovic and Rakic, 1980)**. Given their shared morphological and functional properties, they are often grouped with L6 neurons.

Measurements like current source density (CSD), extensively used in primary visual cortex to estimate layer IV, are less reliable in higher order cortical areas with a less clearly defined layer structure, like motor/premotor cortex, notably regarding the input L4.

Data analysis

Neural dataset

As mentioned above, in this study we restricted our analysis to neural data recorded with linear electrode arrays, which allowed us to capture population activity across the full cortical column simultaneously. Since laminar probes were acutely inserted at different cortical locations, achieving perfect channel-to-channel vertical alignment across sites was challenging. Therefore, each laminar site was treated as an independent dataset in all analyses. To compensate for the reduction in statistical power, we included only behavioral sessions in which the monkeys completed at least 90 correct trials (corresponding to approximately two entire blocks of all color conditions, with ~15 trials per block).

The resulting dataset contained 27 sites for monkey M, and 14 sites for monkey T, obtained across 19 and 10 behavioral sessions, respectively. All sites included channels spanning at least three distinct cortical layers, and were distributed along the PMd/M1 cortical sheet. Both animals had successfully learnt the task, as indicated by an average performance of 80% of correct choices in complete trials (hand fixation maintained until the GO), as reported in **Nougaret *et al.* (2024)**.

Preprocessing

Extracting the Multi-Unit Activity (MUA)

To obtain a neural population measure, we extracted the multi-unit activity (MUA) as the envelope around the high-pass filtered continuous signal, as described in **Stark and Abeles (2007)**. The step-by-step process involved:

- Filter the raw 30 KHz electrophysiology continuous signal from each channel using a band-pass filter (300-6000Hz).
- Clip the values above and beyond +/- 2 standard deviations.
- Rectify the signal by squaring it.
- Smooth the continuous data by low pass filtering it at 250Hz, and downsample it to 1 KHz.
- Negative values resulting from filtering were set to zero, and take the square root of the signal.

The MUA represents the superimposed activity of multiple neurons around the electrode. It reflects the population signal even in the absence of sortable single units, allowing us to sample across all laminar channels. Furthermore, it captures the local activity in the vicinity of each contact, respecting the laminar differences on the underlying neuronal populations.

Correcting for spatial drift

As mentioned above, because the laminar probes were acutely inserted, spatial drift occurred during some sessions, even if we waited after inserting the probes before initiating the recordings. This drift was reflected as slow baseline shifts in the MUA signal and by the appearance or disappearance of single units over time. After confirming that the time-scale of the drift was much longer than any task-related fluctuations, we corrected it by subtracting a moving average from the MUA signal. This moving average, serving as an 'online baseline,' was computed by smoothing the signal with a 30s window using *uniform_filter1d* (from *scipy.ndimage*). The 30s timescale was chosen to be longer than individual trials but shorter than a condition block, ensuring that non-artifactual fluctuations in neuronal activity were preserved. The correction was applied independently to each channel, and edge effects were discarded. In order to center data around zero, the corrected MUA in each channel was z-scored.

Alignment between the neuronal signal and the behavior

We here only analyzed behaviorally correct trials. In most of the analysis presented in this manuscript, the MUA was aligned to the initial selection cue (SEL). Complete trials were defined from 500ms before the monkeys touched the central target (corresponding to 1s before SEL) until the average target-touch time for that session. Analysis studying the preparatory period of the movement were instead aligned on the GO signal. In general, since all temporal delays were stable across conditions, aligning trials at the start (SEL) strongly preserved their temporal synchronization.

Removal of artefactual channels

Channels with extremely bursty neurons (detected using offline spike sorting) were excluded to avoid biasing results toward a single persistent-firing neuron. This was rare: only 4 channels (<<0.5% of all sites) were removed.

Single-channel temporal evolution

Single-channel MUA activity was grouped by color condition (SEL identity) or movement direction and then averaged across trials. The shaded area represents the 95 confidence interval of the mean. A Savitzky-Golay filter of 5th order with 200ms window was applied for temporal smoothing, using the *savgol_filter* function (from *scipy.signal*). To study the temporal modulations associated with movement, the trials were grouped by color condition, since the movement information was given at different times for the three different color conditions.

Time-resolved dimensionality reduction

Two dimensionality reduction methods were used throughout this manuscript: Principal Component Analysis (PCA) and Linear Discriminant Analysis (LDA), implemented using the *sklearn.decomposition* and *sklearn.discriminant_analysis* modules, respectively. Both methods generate low-dimensional representations of high-dimensional data, in this case, using linear combination of channel weights. To avoid overfitting, models were trained on a random subset of trials (50% for color, 70% for direction) and tested on the remaining trials. Overlapping windows of 200ms, sliding by 25ms, were used to estimate the model iteratively across time.

- *PCA* captures the direction of maximum variability of the data, and it was applied to single-trial activity in an unsupervised manner.
- *LDA* finds the axes that best split the data in two or more given classes. It is a supervised method which works at the single-trial level, by providing to the model both the neural data (in all channels) and the categorical variable (color condition or movement direction).

After dimensionality reduction, *weights* and *projections* are extracted. The weights represent the contribution of each of the channels in the laminar probe, and the projections the specific state of the population activity in the lower-dimensional space.

Because PCA/LDA have sign indeterminacy, the orientation of the axes can flip when recomputing the model iteratively in different windows along the trial, leading to mismatches across time. To address this, we enforced a consistent sign by selecting the orientation that maximized projection stability, and adjusted both weights and projections accordingly. The temporal evolution of LDA/PCA projections is generated by concatenating the individual-window projections, assigning them the temporal value of the middle of the window. Weights were visualized as vertically arranged heatmaps, aligned with probe orientation, in which the color-code represented the contribution of each channel (e.g., **Figure 3**).

Mutual information

We used mutual information (MI), specifically *WfMi* from *frites.workflow* (Combrisson et al., 2022), to quantify the amount of information about a behavioral variable contained in the single trial data, at individual sites. The numerical values are normalized by dividing by the theoretical maximum MI, given by $\log_2(\#categories)$. Only significant values of MI were plotted (computed using permutation test).

Entropy

We used Shannon entropy (*H*) to quantify how distributed or localized the vector weights in each site were. To compute this, the weight vector was first normalized, squared, and converted into a probability distribution. Entropy was then computed as:

$$H = -(p_i * \log(p_i))$$

where p_i denotes the normalized squared weight of channel *i*.

A low entropy value indicates that the vector is dominated by a few channels (localized), whereas a high entropy value indicates that contributions are more evenly distributed across channels. To account for the varying number of probe channels across recording sites, we normalized the entropy by its maximum possible value, $\log(N)$, where *N* is the number of channels. After normalization, an entropy of 1 indicates equal contributions from all channels, while 0 indicates that only a single channel contributes.

Similarity

We quantified the temporal stability across windows of the weight vectors per site using the absolute cosine similarity:

$$Sim(t_i, t_j) = abs\left(\frac{w_{t_i} w_{t_j}}{\|w_{t_i}\| \|w_{t_j}\|}\right)$$

where w_{t_i} and w_{t_j} are the weight vectors at times t_i and t_j, respectively. Taking the absolute value compensates for the sign indeterminacy inherent in PCA/LDA solutions. Similarity values range from 0 (orthogonal vectors) to 1 (perfectly aligned vectors).

To assess the consistency of the results, the weight vectors were recomputed across 50 bootstrap resamples of trials, cosine similarity was evaluated on these resampled vectors, and the final similarity for each site was obtained as the average across bootstraps.

Subspace 2D analysis

Population activity in a fixed temporal window around the event of interest was used to fit an LDA model. Neural activity at other times was then projected into the same 2D subspace. Trajectories were temporally smoothed and condition-averaged for visualization purposes (both train and test trials). All quantitative analyses were performed on single-trial MUA.

Cue identity space (at SEL)

Building the LDA space

To define the cue identity space, the LDA was trained to separate the three cue colors presented at SEL (blue, green, pink). A 300ms window starting 150ms after SEL onset was used. Half of the trials (50%) were randomly selected for training, ensuring class balance. To increase the number of training samples, each trial was subdivided into non-overlapping 50ms bins, resulting in six samples per trial. Remaining trials were used for testing, averaging each test trial over the 300ms window around SEL to obtain a single projection in the 2D space.

Generalization of color space

To test whether the cue identity space generated at SEL also encoded color at later time points, single-trial activity at the spatial cues (SCs) was projected into the 2D axes defined at SEL, without retraining the LDA model. For evaluation, trial labels were assigned according to the color presented at the SC: SC1 = blue, SC2 = green, SC3 = pink. A 300ms window (onset +150ms) was used for the projections.

Finding the validity axis

To define a validity axis within the cue identity space, single-trial activity around the SCs was projected into the SEL-defined 2D axes. Training trials were re-labeled as valid or invalid based on the color match between SEL and SC (e.g., for SC1: blue trials = valid, green and pink = invalid). Using these re-labeled training trials, a new LDA was trained on the 2D coordinates of the SEL space to separate valid from invalid cues. Test trials were projected onto this validity axis to evaluate generalization. Chance level was estimated by recomputing the validity axis with shuffled validity labels.

Visual target direction space (at SCs)

Building the LDA space

To define the visual target direction space, LDA was trained to separate the directions (three for monkey T or four for monkey M; see above) presented at a given SC. A 300ms window starting 150ms after SC onset was used. Since the informative SC depended on the color condition (SEL color), only matching trials were used at each SC. 70% of these matching trials were randomly selected for training, ensuring class balance. To increase the number of training samples, each trial was subdivided into non-overlapping 50ms bins, resulting in six samples per trial. Remaining trials were used for testing, averaging each test trial over the 300ms window around the matching SC to obtain a single projection in the 2D space.

Generalization at other cues

To test whether the target space generalized across SCs, test trials from other color conditions at their respective matching SCs were projected into the LDA space defined above. For example, a space trained to separate target directions in blue trials at SC1 was used to project green trials at SC2, to assess whether the directional code was maintained. A 300ms window starting 150ms after matching SC was used for the projections.

Encoding distractors

To evaluate encoding of distractor directions (irrelevant SCs), non-matching trials were projected into the same LDA space. Using the same example, a space trained to separate (valid) target directions in blue trials at SC1 was used to project green trials at SC1, to assess whether the (blue) distractor direction was represented.

Generalization as a preparatory space

To determine whether the LDA space encoding visual target direction at SCs corresponded to the directionally-tuned preparatory activity shortly before movement onset, single-trial activity was projected into the LDA space using a 200 ms window aligned to the GO signal.

Single-trial distance metric

All 2D projections were analyzed at the single trial level. For each trial, the Euclidean distance between the projected point and each class center (computed as the class-average of the training data) was calculated. The distance difference was defined as:

$$\Delta distance = d_{correct} - d_{incorrect}$$

where $d_{correct}$ and $d_{incorrect}$ are the distances to the correct and incorrect class centers, respectively. If multiple incorrect classes existed, their distances were averaged.

The distance difference ($\Delta distance$) was computed across all test trials for each train/test split. Values close to zero indicate no information about the class, whereas negative values indicate that trials are closer to their correct class.

To assess robustness, the entire procedure (including recomputing the LDA model) was repeated over 200 bootstrap resamples. At each bootstrap, five additional shuffles of class labels were performed to estimate chance-level performance.

Significance testing

Significance was assessed using permutation testing to estimate the chance distribution for each analysis. In general, a measure (in most of the cases the mean distance difference) was considered significant if it fell below the 5th percentile of the permutation distribution.

P-values were computed based on the overlap between the empirical and chance distributions. When multiple comparisons were performed simultaneously, p-values were adjusted using Bonferroni correction.

Angle between subspaces

To quantify the alignment of coding subspaces in the high-dimensional space, we computed the angles between the hyperplanes defined by LDA weight vectors, following the approach in **Knyazev and Argentati (2002)**. The *subspace_angles* function from *scipy.linalg* was used to calculate these angles across the different 2D planes. Since each pair of 2D planes yields two principal angles, we took the average of these two values to obtain a single measure of alignment per plane pair. Larger angles indicate stronger misalignment, whereas smaller angles indicate greater similarity between subspaces.

Trajectory in the Grassmannian space

To examine the temporal evolution of the LDA axes in the space of subspaces, laminar weights vectors were reduced to two dimensions using PCA. Absolute values of the weights were used to correct for sign indeterminacy. The resulting trajectories were color-coded according to a layer index, indicating whether superficial or deep layers contributed more strongly at each time point.

Index of layer involvement

To quantify the relative contribution of superficial and deep cortical layers to each LDA axis, we computed an index of layer involvement. First, we took the absolute value of the LDA weights and computed the average contribution across the weights in each layer, normalized by the sum of layer-averaged contributions, so that the total contribution summed to 1. We then averaged the contributions within superficial layers (L23-SUP, L23-DEEP) and deep layers (L5, L6). Finally, the layer involvement index was computed as the ratio of superficial to deep contributions. An index of 1 indicates equal contribution from superficial and deep layers, values greater than 1 indicate stronger superficial involvement, and values less than 1 indicate stronger deep involvement.

References

Asanuma, H., & Rosin, I. (1972). Topographical organization of cortical efferent zones projecting to distal forelimb muscles in the monkey. *Experimental Brain Research*, *14*(3), 243–256. https://doi.org/10.1007/BF00816161

Bastos, A. M., Usrey, W. M., Adams, R. A., Mangun, G. R., Fries, P., & Friston, K. J. (2012). Canonical Microcircuits for Predictive Coding. *Neuron*, *76*(4), 695–711. https://doi.org/10.1016/j.neuron.2012.10.038

Battaglia-Mayer, A., & Caminiti, R. (2019). Corticocortical Systems Underlying High-Order Motor Control. *The Journal of Neuroscience*, *39*(23), 4404–4421. https://doi.org/10.1523/jneurosci.2094-18.2019

Beul, S. F., & Hilgetag, C. C. (2017). *Neuron density fundamentally relates to architecture and connectivity of the primate cerebral cortex*. Neuroscience. https://doi.org/10.1101/117051

Borra, E., Rizzo, M., Gerbella, M., Rozzi, S., & Luppino, G. (2021). Laminar Origin of Corticostriatal Projections to the Motor Putamen in the Macaque Brain. *The Journal of Neuroscience*, *41*(7), 1455–1469. https://doi.org/10.1523/JNEUROSCI.1475-20.2020

Buzsáki, G. (2010). Neural Syntax: Cell Assemblies, Synapsembles, and Readers. *Neuron*, *68*(3), 362–385. https://doi.org/10.1016/j.neuron.2010.09.023

Carpenter, A. F., Baud-Bovy, G., Georgopoulos, A. P., & Pellizzer, G. (2018). Encoding of Serial Order in Working Memory: Neuronal Activity in Motor, Premotor, and Prefrontal Cortex during a Memory Scanning Task. *The Journal of Neuroscience*, *38*(21), 4912–4933. https://doi.org/10.1523/JNEUROSCI.3294-17.2018

Carpenter, A. F., Georgopoulos, A. P., & Pellizzer, G. (1999). Motor Cortical Encoding of Serial Order in a Context-Recall Task. *Science*, *283*(5408), 1752–1757. https://doi.org/10.1126/science.283.5408.1752

Chandrasekaran, C., Peixoto, D., Newsome, W. T., & Shenoy, K. V. (2017). Laminar differences in decision-related neural activity in dorsal premotor cortex. *Nature Communications*, *8*(1), 614. https://doi.org/10.1038/s41467-017-00715-0

Churchland, M. M., Cunningham, J. P., Kaufman, M. T., Foster, J. D., Nuyujukian, P., Ryu, S. I., & Shenoy, K. V. (2012). Neural population dynamics during reaching. *Nature*, *487*(7405), 51–56. https://doi.org/10.1038/nature11129

Churchland, M. M., Santhanam, G., & Shenoy, K. V. (2006). Preparatory Activity in Premotor and Motor Cortex Reflects the Speed of the Upcoming Reach. *Journal of Neurophysiology*, *96*(6), 3130–3146. https://doi.org/10.1152/jn.00307.2006

Churchland, M. M., Yu, B. M., Ryu, S. I., Santhanam, G., & Shenoy, K. V. (2006). Neural Variability in Premotor Cortex Provides a Signature of Motor Preparation. *The Journal of Neuroscience*, *26*(14), 3697–3712. https://doi.org/10.1523/JNEUROSCI.3762-05.2006

Cisek, P., & Kalaska, J. F. (2005). Neural Correlates of Reaching Decisions in Dorsal Premotor Cortex: Specification of Multiple Direction Choices and Final Selection of Action. *Neuron*, *45*(5), 801–814. https://doi.org/10.1016/j.neuron.2005.01.027

Douglas, R. J., & Martin, K. A. C. (2004). NEURONAL CIRCUITS OF THE NEOCORTEX. *Annual Review of Neuroscience*, *27*(1), 419–451. https://doi.org/10.1146/annurev.neuro.27.070203.144152

Dum, R., & Strick, P. (1991). The origin of corticospinal projections from the premotor areas in the frontal lobe. *The Journal of Neuroscience*, *11*(3), 667–689. https://doi.org/10.1523/JNEUROSCI.11-03-00667.1991

Fusi, S., Miller, E. K., & Rigotti, M. (2016). Why neurons mix: High dimensionality for higher cognition. *Current Opinion in Neurobiology*, *37*, 66–74. https://doi.org/10.1016/j.conb.2016.01.010

Gallego, J. A., Perich, M. G., Chowdhury, R. H., Solla, S. A., & Miller, L. E. (2020). Long-term stability of cortical population dynamics underlying consistent behavior. *Nature Neuroscience*, *23*(2), 260–270. https://doi.org/10.1038/s41593-019-0555-4

Gallego, J. A., Perich, M. G., Miller, L. E., & Solla, S. A. (2017). Neural Manifolds for the Control of Movement. *Neuron*, *94*(5), 978–984. https://doi.org/10.1016/j.neuron.2017.05.025

García-Cabezas, M. Á., & Barbas, H. (2014). Area 4 has layer IV in adult primates. *European Journal of Neuroscience*, *39*(11), 1824–1834. https://doi.org/10.1111/ejn.12585

Genkin, M., Shenoy, K. V., Chandrasekaran, C., & Engel, T. A. (2025). The dynamics and geometry of choice in the premotor cortex. *Nature*. https://doi.org/10.1038/s41586-025-09199-1

Godlove, D. C., Maier, A., Woodman, G. F., & Schall, J. D. (2014). Microcircuitry of Agranular Frontal Cortex: Testing the Generality of the Canonical Cortical Microcircuit. *The Journal of Neuroscience*, *34*(15), 5355–5369. https://doi.org/10.1523/JNEUROSCI.5127-13.2014

Harris, K. D., & Shepherd, G. M. G. (2015). The neocortical circuit: Themes and variations. *Nature Neuroscience*, *18*(2), 170–181. https://doi.org/10.1038/nn.3917

Hutsler, J. J., Lee, D.-G., & Porter, K. K. (2005). Comparative analysis of cortical layering and supragranular layer enlargement in rodent carnivore and primate species. *Brain Research*, *1052*(1), 71–81. https://doi.org/10.1016/j.brainres.2005.06.015

Jones, E. G., & Wise, S. P. (1977). Size, laminar and columnar distribution of efferent cells in the sensory-motor cortex of monkeys. *Journal of Comparative Neurology*, *175*(4), 391–437. https://doi.org/10.1002/cne.901750403

Knyazev, A. V., & Argentati, M. E. (2002). Principal Angles between Subspaces in an *A* -Based Scalar Product: Algorithms and Perturbation Estimates. *SIAM Journal on Scientific Computing*, *23*(6), 2008–2040. https://doi.org/10.1137/S1064827500377332

Koo, B.-B., Schettler, S. P., Murray, D. E., Lee, J.-M., Killiany, R. J., Rosene, D. L., Kim, D.-S., & Ronen, I. (2012). Age-related effects on cortical thickness patterns of the Rhesus monkey brain. *Neurobiology of Aging*, *33*(1), 200.e23-200.e31. https://doi.org/10.1016/j.neurobiolaging.2010.07.010

Kostovic, I., & Rakic, P. (1980). Cytology and time of origin of interstitial neurons in the white matter in infant and adult human and monkey telencephalon. *Journal of Neurocytology*, *9*(2), 219–242. https://doi.org/10.1007/BF01205159

Kuzmina, E., Kriukov, D., & Lebedev, M. (2024). Neuronal travelling waves explain rotational dynamics in experimental datasets and modelling. *Scientific Reports*, *14*(1), 3566. https://doi.org/10.1038/s41598-024-53907-2

Mante, V., Sussillo, D., Shenoy, K. V., & Newsome, W. T. (2013). Context-dependent computation by recurrent dynamics in prefrontal cortex. *Nature*, *503*(7474), 78–84. https://doi.org/10.1038/nature12742

Mendoza-Halliday, D., Major, A. J., Lee, N., Lichtenfeld, M. J., Carlson, B., Mitchell, B., Meng, P. D., Xiong, Y., Westerberg, J. A., Jia, X., Johnston, K. D., Selvanayagam, J., Everling, S., Maier, A., Desimone, R., Miller, E. K., & Bastos, A. M. (2024). A ubiquitous spectrolaminar motif of local field potential power across the primate cortex. *Nature Neuroscience*, *27*(3), 547–560. https://doi.org/10.1038/s41593-023-01554-7

Messier, J., & Kalaska, J. F. (2000). Covariation of Primate Dorsal Premotor Cell Activity With Direction and Amplitude During a Memorized-Delay Reaching Task. *Journal of Neurophysiology*, *84*(1), 152–165. https://doi.org/10.1152/jn.2000.84.1.152

Mountcastle, V. (1997). The columnar organization of the neocortex. *Brain*, *120*(4), 701–722. https://doi.org/10.1093/brain/120.4.701

Nigam, S., Pojoga, S., & Dragoi, V. (2019). Synergistic Coding of Visual Information in Columnar Networks. *Neuron*, *104*(2), 402-411.e4. https://doi.org/10.1016/j.neuron.2019.07.006

Ninomiya, T., Dougherty, K., Godlove, D. C., Schall, J. D., & Maier, A. (2015). Microcircuitry of agranular frontal cortex: Contrasting laminar connectivity between occipital and frontal areas. *Journal of Neurophysiology*, *113*(9), 3242–3255. https://doi.org/10.1152/jn.00624.2014

Nolan, S. O., Melugin, P. R., Erickson, K. R., Adams, W. R., Farahbakhsh, Z. Z., Mcgonigle, C. E., Kwon, M. H., Costa, V. D., Hackett, T. A., Cuzon Carlson, V. C., Constantinidis, C., Lapish, C. C., Grant, K. A., & Siciliano, C. A. (2025). Recurrent activity propagates through labile ensembles in macaque dorsolateral prefrontal microcircuits. *Current Biology*, *35*(2), 431-443.e4. https://doi.org/10.1016/j.cub.2024.11.069

Nougaret, S., López-Galdo, L., Caytan, E., Poitreau, J., Barthélemy, F. V., & Kilavik, B. E. (2024). Low and high beta rhythms have different motor cortical sources and distinct roles in movement control and spatiotemporal attention. *PLOS Biology*, *22*(6), e3002670. https://doi.org/10.1371/journal.pbio.3002670

Opris, I. (2013). Inter-laminar microcircuits across neocortex: Repair and augmentation. *Frontiers in Systems Neuroscience*, *7*. https://doi.org/10.3389/fnsys.2013.00080

Opris, I., Fuqua, J. L., Gerhardt, G. A., Hampson, R. E., & Deadwyler, S. A. (2015). Prefrontal cortical recordings with biomorphic MEAs reveal complex columnar-laminar microcircuits for BCI/BMI implementation. *Journal of Neuroscience Methods*, *244*, 104–113. https://doi.org/10.1016/j.jneumeth.2014.05.029

Opris, I., Hampson, R. E., Stanford, T. R., Gerhardt, G. A., & Deadwyler, S. A. (2011). Neural Activity in Frontal Cortical Cell Layers: Evidence for Columnar Sensorimotor Processing. *Journal of Cognitive Neuroscience*, *23*(6), 1507–1521. https://doi.org/10.1162/jocn.2010.21534

Perich, M. G., Narain, D., & Gallego, J. A. (2025). A neural manifold view of the brain. *Nature Neuroscience*, *28*(8), 1582–1597. https://doi.org/10.1038/s41593-025-02031-z

Qian, Y., Herikstad, R., & Libedinsky, C. (2025). Working Memory Updating in the Macaque Lateral Prefrontal Cortex. *The Journal of Neuroscience*, *45*(37), e1770242024. https://doi.org/10.1523/JNEUROSCI.1770-24.2024

Riehle, A., & Requin, J. (1989). Monkey primary motor and premotor cortex: Single-cell activity related to prior information about direction and extent of an intended movement. *Journal of Neurophysiology*, *61*(3), 534–549. https://doi.org/10.1152/jn.1989.61.3.534

Rigotti, M., Barak, O., Warden, M. R., Wang, X.-J., Daw, N. D., Miller, E. K., & Fusi, S. (2013). The importance of mixed selectivity in complex cognitive tasks. *Nature*, *497*(7451), 585–590. https://doi.org/10.1038/nature12160

Ritz, H., & Shenhav, A. (2024). Orthogonal neural encoding of targets and distractors supports multivariate cognitive control. *Nature Human Behaviour*, *8*(5), 945–961. https://doi.org/10.1038/s41562-024-01826-7

Rizzolatti, G., & Luppino, G. (2001). The Cortical Motor System. *Neuron*, *31*(6), 889–901. https://doi.org/10.1016/S0896-6273(01)00423-8

Safaie, M., Chang, J. C., Park, J., Miller, L. E., Dudman, J. T., Perich, M. G., & Gallego, J. A. (2023). Preserved neural dynamics across animals performing similar behaviour. *Nature*, *623*(7988), 765–771. https://doi.org/10.1038/s41586-023-06714-0

Semedo, J. D., Zandvakili, A., Machens, C. K., Yu, B. M., & Kohn, A. (2019). Cortical Areas Interact through a Communication Subspace. *Neuron*, *102*(1), 249-259.e4. https://doi.org/10.1016/j.neuron.2019.01.026

Shenoy, K. V., Sahani, M., & Churchland, M. M. (2013). Cortical Control of Arm Movements: A Dynamical Systems Perspective. *Annual Review of Neuroscience*, *36*(1), 337–359. https://doi.org/10.1146/annurev-neuro-062111-150509

Shipp, S. (2005). The importance of being agranular: A comparative account of visual and motor cortex. *Philosophical Transactions of the Royal Society B: Biological Sciences*, *360*(1456), 797–814. https://doi.org/10.1098/rstb.2005.1630

Shipp, S., Adams, R. A., & Friston, K. J. (2013). Reflections on agranular architecture: Predictive coding in the motor cortex. *Trends in Neurosciences*, *36*(12), 706–716. https://doi.org/10.1016/j.tins.2013.09.004

Stark, E., & Abeles, M. (2007). Predicting Movement from Multiunit Activity. *The Journal of Neuroscience*, *27*(31), 8387–8394. https://doi.org/10.1523/jneurosci.1321-07.2007

Tanji, J., & Evarts, E. V. (1976). Anticipatory activity of motor cortex neurons in relation to direction of an intended movement. *Journal of Neurophysiology*, *39*(5), 1062–1068. https://doi.org/10.1152/jn.1976.39.5.1062

Thura, D., & Cisek, P. (2014). Deliberation and Commitment in the Premotor and Primary Motor Cortex during Dynamic Decision Making. *Neuron*, *81*(6), 1401–1416. https://doi.org/10.1016/j.neuron.2014.01.031

Tye, K. M., Miller, E. K., Taschbach, F. H., Benna, M. K., Rigotti, M., & Fusi, S. (2024). Mixed selectivity: Cellular computations for complexity. *Neuron*, *112*(14), 2289–2303. https://doi.org/10.1016/j.neuron.2024.04.017

Vyas, S., Golub, M. D., Sussillo, D., & Shenoy, K. V. (2020). Computation Through Neural Population Dynamics. *Annual Review of Neuroscience*, *43*(1), 249–275. https://doi.org/10.1146/annurev-neuro-092619-094115

Wentz, P. T., Brincat, S. L., Pasupathy, A., & Miller, E. K. (2025). Recycling of prefrontal subspaces dynamically multiplexes information. *bioRxiv*, 2025.05.02.651965. https://doi.org/10.1101/2025.05.02.651965

Wise, S. P. (1985). The Primate Premotor Cortex: Past, Present, and Preparatory. *Annual Review of Neuroscience*, *8*(1), 1–19. https://doi.org/10.1146/annurev.ne.08.030185.000245

Wise, S. P. (1999). Motor Cortex. In *Encyclopedia of Neuroscience* (2nd ed.). Elsevier.

Zhang, Y., Chen, Y., Wang, T., & Cui, H. (2025). Neural geometry from mixed sensorimotor selectivity for predictive sensorimotor control. *eLife*, *13*, RP100064. https://doi.org/10.7554/eLife.100064

Supplementary Figures

***Suppl.Figure 1 - Activity spaces evolution (PCA) and direction coding spaces (LDA$_{direction}$)
for blue and pink trials.*** *a, Left: Heatmap of weights from time-resolved PCA models for one example
site. Right: Cross-temporal map of absolute cosine similarity across pairs of weights shown on the left.
b, Top panels: Heatmaps displaying the weights of all time-resolved LDA$_{direction}$ models for the example
site using blue (top) and pink (bottom) trials. Bottom panels: Neural activity projected onto the first
axis of LDA$_{direction}$ (top: blue trials; bottom: pink trials), computed in overlapping 200ms windows and
concatenated across the trial. Condition means (movement direction) are displayed as color-coded lines
with 95% CI (shaded). Dark bars below indicate significant mutual information (MI), with intensity
reflecting magnitude; white indicates non-significant bins. Right panels: cross-temporal map of
absolute cosine similarity across pairs of weights in LDA$_{direction}$, for blue (top) and pink (bottom) trials.
Each map is the average of 50 similarity matrices from resampled training data. c, Same as in (b, right)
but averaged per monkey across all sites; left: Monkey M, right: Monkey T, top: blue trials, bottom:
pink trials. (a-b), Example site: Mo180412002-pr1.*

Suppl.Figure 2 - Sustained color-condition space in Monkey T. *Left: Schematic illustration of reusing the cue identity space at SEL to encode cue color transiently at SC1 (blue), SC2 (green) and SC3 (pink). Right: Example site. Trial-averaged projections on LD1$_{color}$, separated by SEL color; line: mean, shaded: 95% CI, x-axis: trial time. Color-bar below indicate significant mutual information (MI); white indicates non-significant bins.*

Suppl.Figure 3 - Generalization from other SCs. *a, Example site. Condition-averaged trajectories around the training epoch when models were built at SC1 (left), SC2 (middle) and SC3 (right) for target direction on matching trials. Large colored dots represent the state of maximum cross-condition variance during the train epoch (matching trials). Small color-coded dots represent trial-averaged projections for correct trials at their respective matching SC. Small color-coded squares represent trial-averaged projections for non-matching trials, i.e., trials projected at the train epoch but coded by the direction of the presented cue. Color code: yellow: lower left, orange: upper left, purple: lower right, black: upper right. b, Summary of the single-trial distance metric (Δ_{dist}) across sites for models trained at SC1 (blue trials, left) and SC3 (pink trials, right). Only sites with a significant SC target direction space (Δ_{dist} data < 95th percentile of permutations) were tested for generalization. Dots: mean Δ_{dist} for each test: SEL, H_1 (data: brown, permutations: gray); dark connecting lines: significant results after Bonferroni correction. Top: Monkey M; bottom: Monkey T.*

Suppl.Figure 4 - Encoding distractors. *a, Top: Schematic illustration of distractor encoding. In blue (left) and pink (right) trials, the direction of SC2 (green) acted as a distractor rather than a target direction. We tested whether the distractor direction-state (SC2), i.e. direction of SC2 for non-matching trials, overlapped with target direction states (directional split of green trials at SC2). Bottom: Example site. Condition-averaged trajectories for blue (left) and pink (right) trials projected onto the SC2 target direction space (built on green trials). Color code: SC2 direction; Cross: average of blue trials at SC2, diamond: average of pink trials at SC2. b, Summary of the single-trial distance metric (Δ_{dist}) across sites for models trained at SC2 (green trials) and tested in the direction of SC2 in blue (left) and pink (right) projections. Only sites with a significant SC2 target direction space (Δ_{dist} data < 95th percentile of permutations) were included. Dots: mean Δ_{dist} for each test (SC2 direction in blue and pink trials; data: brown, permutations: gray). Dark connecting lines: significant results after Bonferroni correction. Top: Monkey M; bottom: Monkey T.*

Suppl.Figure 5 - Cue-direction space vs Preparatory space. *a, Summary of the single-trial distance metric (Δ_{dist}) across sites for generalization of the cue space to the preparatory epoch (left) and existence of preparatory space (right). Only sites with a significant SC2 target direction space (Δ_{dist} data < 95th percentile of permutations) were included for SC2 generalization (left). Top: Monkey M, bottom: Monkey T. Dots: mean Δ_{dist} for each test (data: brown, permutations: gray); dark connecting lines: significant results after Bonferroni correction. b, Example site: Mo180412002-pr1. Neural projections on an $LDA_{direction}$ model built during matching cues (left) or in the preparatory epoch (pre-GO, right), separated by color condition (top: blue, middle: green, bottom: pink). Bottom colored-bar represents the time-resolved mutual information; white indicates non-significant bins.*

Suppl.Figure 6 - Trajectory of the coding vectors in the space of subspaces. *Sites displaying a clear off-diagonal stripe in the similarity matrix are displayed. Right for each site: Site-specific trajectories of cue information (LDA$_{color}$) in the state-space of subspaces; x-axis: trial time, y-axis: PC1, z-axis: PC2; color: ratio of weight strength between superficial and deep channels. Left for each site: Cross-temporal map of absolute cosine similarity across pairs of weights in LD1$_{color}$. Each map is the average of 50 similarity matrices from resampled training data in each site; x-axis, y-axis: trial time.*