Generative inverse design of RNA structure and function with gRNAde

Chaitanya K. Joshi [1,*] , **Edoardo Gianni** [2,*] , **Samantha L. Y. Kwok** [2,*] , **Simon V. Mathis** [1] , **Pietro Liò** [1,+] , **Philipp Holliger** [2,+]

[1] Department of Computer Science and Technology, University of Cambridge, 15 JJ Thomson Avenue, Cambridge, CB3 0FD, United Kingdom

[2] MRC Laboratory of Molecular Biology, Francis Crick Avenue, Cambridge, CB2 0QH, United Kingdom

* Equal contributions

[+] Corresponding authors: pl219@cam.ac.uk, ph1@mrc-lmb.cam.ac.uk

Abstract

The design of RNA molecules with bespoke three-dimensional structures and functions is a central goal in synthetic biology and biotechnology. However, progress has been limited by the challenges of designing complex tertiary interactions such as pseudoknots, as well as engineering novel catalytic functions—problems that have remained largely intractable for automated methods. Here we present and experimentally validate a high-throughput generative AI pipeline for inverse design of RNA structure and function. Central to the pipeline is **gRNAde**, an RNA language model conditioned on 3D backbone structures and sequence constraints. In a community-wide, blinded RNA design competition on the Eterna platform, the gRNAde pipeline designs complex pseudoknotted RNAs at high success rates matching that of human experts, significantly outperforming other physics- and AI-based automated algorithms. We further demonstrate gRNAde's capability to generatively design functional RNA polymerase ribozymes with up to 20% sequence divergence from the wild type, discovering highly active variants in a functional landscape previously inaccessible to rational design and directed evolution. gRNAde thus provides an experimentally validated, open-source platform for automated design of complex RNA structures, paving the way for fully programmable RNA catalysts and nanostructures.

Open-source code: github.com/chaitjo/geometric-rna-design

Introduction

The unique dual capacity of RNA to both encode genetic information in its sequence and perform biochemical functions through complex three-dimensional folds grants it a central role in biology[1]. RNA structure underpins a vast range of cellular processes as well as emerging biotechnologies and therapeutics[2,3,4,5]. The ability to design RNA structure and function is thus a key enabling technology for modern biology.

Despite this promise, two fundamental and interconnected challenges limit progress in RNA design: the design of complex three-dimensional structures and the engineering of novel catalytic functions. The first challenge we address is exemplified by RNA pseudoknots, sophisticated structural motifs where single-stranded regions base pair with complementary sequences, creating interwoven stem-loop structures. These elements are critical for a wide range of biological functions, from enabling viral replication in SARS-CoV-2[6] to forming the catalytic core of ribozymes[7], yet their topological complexity makes them notoriously difficult to predict or design computationally[8,9]. This represents a major gap in our ability to engineer RNAs with precise three-dimensional topologies. The second, and arguably greater, challenge is to go beyond static structure and engineer complex catalytic functions. Designing RNA enzymes (ribozymes) with novel or enhanced activities, such as the RNA polymerase ribozyme for RNA-based self-replication[10–14], requires navigating an astronomical sequence space where functional solutions are exceedingly rare. Existing computational approaches, from traditional rational design[15] to recent deep learning models that use evolutionary information[16,17] or base pairing constraints[18], are often limited by handcrafted heuristics or the need for multiple sequence alignments. This leaves a critical gap for automated methods that can accurately design 3D topologies and catalytic functions directly from geometric principles, particularly for targets without evolutionary precedents.

This work introduces a comprehensive solution to these twin challenges. Our generative AI method, **gRNAde**[1], learns the principles of RNA folding directly from 3D structural data, and is integrated into a complete design-build-test pipeline. The foundational architecture, which leverages an RNA language model to generate sequences conditioned on 3D backbone structures has been described previously[19,20], but its practical ability to solve major experimental challenges in RNA engineering remained untested. Here, we present the first extensive experimental validation of the gRNAde pipeline, demonstrating its successful application to these previously intractable problems in RNA engineering. By systematically validating gRNAde's performance in both a blinded structural design competition on Eterna[21] as well as a complex functional design campaign for novel RNA polymerase ribozymes[13], this study enables a generalizable, automated, and open-source platform for RNA design.

---

[1] gRNAde stands for *Geometric RNA Design*; pronounced as 'grenade'.

Figure 1 | The gRNAde high-throughput pipeline for generative RNA design.

The automated workflow integrates deep learning-based sequence generation with computational screening to identify optimal candidates for experimental validation.

A. The pipeline takes multi-modal design constraints as input, optionally including a target pseudoknotted secondary structure, a target 3D backbone structure, and partial sequence constraints such as those derived from fitness landscapes.

B. gRNAde, a structure-conditioned RNA language model, uses these constraints to generate a large and diverse library of candidate sequences, typically on the order of one million. These candidates are then passed to the computational filtering stage.

C. In the filtering stage, each designed sequence is evaluated by RibonanzaNet2, an RNA structure foundation model. RibonanzaNet predicts the secondary structure and a per-nucleotide SHAPE chemical reactivity profile for each candidate.

D. RibonanzaNet predictions for each design are scored against the target secondary structure and SHAPE profile using metrics such as the Matthews Correlation Coefficient (MCC), Mean Absolute Error (MAE), and the OpenKnot Score. The top-ranked designs are then selected for wet-lab synthesis and validation.

Results

A generalizable pipeline for high-throughput RNA design

To address the challenges of RNA design at scale, an automated pipeline was developed to integrate the generative capabilities of gRNAde[19,20] with high-throughput computational screening (**Figure 1**). This workflow provides a practical and efficient method for identifying promising RNA sequences for experimental validation.

Conceptually, gRNAde is a generative language model for RNA, translating a multi-modal structural 'prompt' into novel sequences predicted to adopt a desired fold. This design specification, analogous to a textual prompt for a large language model, is highly flexible; it can consist of a target pseudoknotted secondary structure, 3D backbone coordinates, and partial sequence constraints that must be preserved (**Figure 1A**). Unlike traditional physics-based or heuristic methods, gRNAde is a data-driven model whose design principles are learned directly from the thousands of experimentally determined RNA structures in the Protein Data Bank[23]. Its core advance is the direct integration of 3D geometric information using Graph Neural Networks (**Figure 1B**), allowing it to capture the subtle tertiary interactions and non-canonical pairings that define complex RNA folds—features inaccessible to methods restricted to 2D representations.

The full design pipeline proceeds in a three-step workflow. First, in the generation stage, gRNAde is used to produce a large and diverse library of candidate sequences, typically on the order of one million, for a given structural target. Second, in the screening stage, each generated sequence is evaluated using RibonanzaNet[22], an RNA structure foundation model. RibonanzaNet serves as a high-throughput computational proxy for experimental characterization by predicting per-nucleotide chemical reactivity profiles and pseudoknotted secondary structure (**Figure 1C**). These reactivity profiles, which measure the accessibility of each nucleotide to chemical modification, are highly sensitive reporters of an RNA's folded 3D structure and flexibility[24,25]. The choice of RibonanzaNet is motivated by its training on a massive and diverse dataset of both natural and synthetic RNAs, making it well-suited to evaluate novel, designed sequences. Third, in the selection stage, the computationally screened candidates are scored and ranked (**Figure 1D**). Key metrics include the Matthews Correlation Coefficient (MCC) between the predicted secondary structure and the target, and the Mean Absolute Error (MAE) between the predicted chemical reactivity profile and a target profile. This filtering process distills the massive initial library down to a small, high-quality set of candidates for synthesis and wet-lab validation. This entire pipeline is highly efficient, capable of generating and screening **one million designs in under 12 hours on a single GPU**, making it a powerful tool for exploring RNA sequence space on an unprecedented scale.

Expert-level design of pseudoknotted RNA structures

To rigorously assess the pipeline's ability to solve the "Structure Challenge", gRNAde was entered into the Eterna OpenKnot Benchmark, a community-wide, blinded competition to design sequences for complex pseudoknotted RNA targets. The benchmark is exceptionally challenging, with targets spanning a wide range of biologically critical structured RNA classes, including riboswitches, viral elements, ribozymes, and synthetic structures, ensuring a robust test of the method's generalizability. Submitted designs are experimentally synthesized and evaluated at Stanford University, with performance quantified by an "OpenKnot Score" derived from high-throughput chemical probing data; a score above 90 indicates a high-confidence successful design. This benchmark provides an unbiased comparison against both state-of-the-art automated methods and the collective intelligence of human experts[21].

Across 20 challenging targets of up to 100 nucleotides (nts) in length (OpenKnot Round 3), the fully automated gRNAde pipeline achieved a 100% success rate on natural RNAs and a 90% success rate on synthetic targets, on par with expert human designers who also achieved 100% and 90% success rates, respectively (**Figure 2A-D**). In stark contrast, the state-of-the-art physics-based method, Rosetta[7], only succeeded on 40% of natural and 70% of synthetic targets. RFdiffusion[26], the next-best public AI method, also struggled with success rates of 80% and 60%, respectively. These difficulties were particularly pronounced with longer targets of 240 nts in OpenKnot Round 4 (**Supplementary Figure 1**). Here, gRNAde remained competitive with experts, solving 67% of natural and 70% of synthetic targets, while Rosetta was not scalable enough to be evaluated and RFdiffusion succeeded on only 33% and 50%, respectively. Full results of the competition, including additional compensatory mutagenesis and cryo-EM experiments, will be detailed in a forthcoming joint publication and signify a **milestone in biomolecular design:** our fully automated gRNAde pipeline has matched human experts across a blinded, challenging set of RNA structure design tasks.

Notably, gRNAde's designs consistently outperformed the wildtype sequences from which the natural targets were derived. Wildtype sequences achieved success rates of only 80% on short targets and a striking 0% on long natural targets. This finding underscores a key principle: while natural sequences may form alternative conformations, gRNAde's designs are often more "ideal" solutions for a target structure than their natural counterparts. The molecular basis for this superior performance is evident in the experimental data. For the natural ZMP Riboswitch target, the chemical reactivity profile of the gRNAde design precisely matches the expected pattern for the target fold, while the wildtype sequence shows anomalous reactivity patterns suggesting an alternative conformation (**Figure 2E**). This trend holds for synthetic targets as well; for the PN.v282 puzzle, the gRNAde design again shows a near-perfect reactivity profile, whereas the wildtype exhibits high reactivity in paired regions, indicating a failure to form the correct structure (**Figure 2F**). This direct experimental evidence confirms that the gRNAde pipeline can generate novel sequences that are optimized for complex target topologies compared to natural sequences subject to multiple evolutionary pressures.

Figure 2 | gRNAde achieves expert-level accuracy in the Eterna OpenKnot Benchmark for RNA pseudoknot design.

Figure 2 | gRNAde achieves expert-level accuracy in the Eterna OpenKnot Benchmark for RNA pseudoknot design.

Performance of wildtype sequences, Rosetta[9], MPNN[27], RFdiffusion[26], gRNAde, and expert human designers in the Eterna OpenKnot Round 3 challenge, which targeted pseudoknotted RNAs of up to 100 nucleotides.

A, B. Results for 10 natural RNA targets. **C, D.** Results for 10 synthetic RNA targets. Left-sided panels A and C show the distribution of OpenKnot scores for individual designs across all puzzles (success threshold > 90, red dashed line). Right-sided panels B and D show the overall success rate, defined as the percentage of puzzles for which at least one design scored above 90. gRNAde achieves success rates of 100% (natural) and 90% (synthetic), matching expert human performance and substantially outperforming both Rosetta (physics-based) and RFdiffusion (next best AI method).

E, F. Molecular validation of design success through chemical probing. Nucleotides are overlaid on the target secondary structures and colored by reactivity, with darker reds indicating higher reactivity and greater accessibility for unpaired positions. Conversely, nucleotides part of base pairs and pseudoknots are expected to have lower reactivity.

E. For the natural ZMP Riboswitch target, the best gRNAde design (right, score = 94.3) shows a chemical reactivity profile largely consistent with the target fold, whereas the wildtype sequence (left, score = 90.0) shows anomalous reactivity in the loop region around position 50-55, suggesting misfolding.

F. For the synthetic PN.v282 target, the gRNAde design (right, score = 97.5) again shows a superior reactivity pattern compared to the wildtype sequence (left, score = 80.5), which exhibits high reactivity in various paired regions, indicating disrupted base pairing.

Generative design of functional RNA enzymes

Having demonstrated expert-level performance at designing complex structural topologies, the next challenge was to address the design of function. The gRNAde pipeline was applied to engineer the 5TU catalytic subunit of a triplet-based RNA polymerase ribozyme[13], a highly complex enzyme that serves as a model for RNA self-replication and the origins of life. This design task is particularly demanding, as it requires preserving a delicate network of tertiary contacts, including two essential kissing-loop interactions that preorganize the enzyme's active site (**Figure 3A, B**), a challenge that goes far beyond simple secondary structure conservation. The scientific goal was not merely to improve the enzyme, but to test the limits of its functional sequence diversity[17], which has direct implications for the plausibility of RNA-based self-synthesis and the emergence of early life[28,29]. This was achieved by using gRNAde to perform large-scale generative "jumps" in sequence space (**Figure 3C**), aiming to discover functional variants at mutational distances far beyond those accessible through conventional directed evolution or simple rational design. By traversing vast sequence distances in a single step, gRNAde shortens the time investment of multiple selection rounds, offering an accelerated path or novel starting points for directed evolution.

The gRNAde pipeline dramatically outperformed baseline methods in discovering active ribozymes. For designs with 15-19 mutations relative to the 152 nt wildtype sequence, gRNAde yielded a 31.5% success rate in identifying active variants in a high-throughput sequencing-based functional assay (**Figure 3D**). In contrast, a "rational design" baseline that respects secondary structure but lacks 3D awareness, even when coupled with the same RibonanzaNet filtering used in gRNAde, achieved only 15% success rate. This **two-fold improvement** demonstrates that the performance gain stems directly from gRNAde's superior generative capability, not just the downstream filtering. Without filtering, gRNAde showed a **ten-fold improvement** over rational design, which had a success rate of just 3%.

Furthermore, gRNAde discovered not only more functional variants but also variants with higher catalytic activity. The fitness distribution of active gRNAde designs was generally superior to that of the rational design baselines, with designs exceeding the activity of the wildtype enzyme up to 30 mutations, a region of sequence space where rational design produced no active variants (**Figure 3E**). Three active gRNAde variants each for mutational distance ranges 15-19, 20-24, and 25-29 were further validated via a low-throughput gel assay, showing high Pearson correlation coefficient of 0.85 with the high-throughput fitness data (**Figure 3F, Supplementary Figure 2**). Notably, variants 122 and 143 differed from the wildtype by 18 and 19 mutations, yet exhibited an 1.6-fold and 1.1-fold enrichment in the functional assay, respectively. These results showcase a remarkable combination of sequence novelty and improved functionality achieved with gRNAde.

Figure 3 | Generative design and functional validation of RNA polymerase ribozymes.

Figure 3 | Generative design and functional validation of RNA polymerase ribozymes.

The gRNAde pipeline was used to design functional variants of the triplet-based RNA polymerase ribozyme (TPR), substantially outperforming rational design baselines.

A. Cryo-EM structure of the TPR heterodimer, showing the catalytic 5TU subunit (colored), which was the target for generative design, and the auxiliary t1 subunit (grey), which was held constant. Position-specific design probabilities, derived from experimental fitness landscape data, are mapped onto the 5TU structure. Lighter yellows indicate regions with a high probability of being re-designed by gRNAde, while critical functional sites were constrained to the wildtype sequence (indicated in darker reds).

B. Position-specific design probabilities mapped onto the 5TU secondary structure.

C. Workflow for design and validation of 5TU variants. The 3D backbone structure, along with constraints sampled from the fitness landscape data, were input to the full gRNAde pipeline (**Figure 1**) as well as two baselines: rational design with the same computational filtering as gRNAde, and rational design without filtering. A library of 2,000 total designs was screened via a high-throughput functional assay. The native 5TU and 9 gRNAde designs were further validated using a low-throughput gel, which was then used to calibrate the activity threshold for the high-throughput data.

D. Success rate of generating active designs (fitness ≥ -1.86, corresponding to variant 319) binned by mutational distance from the wildtype sequence. At 15–19 mutations, the gRNAde pipeline achieves a 31.5% success rate, substantially outperforming filtered rational design (15.0%) and unfiltered rational design (3.0%).

E. Fitness distributions for all functional designs across mutational distances. The fitness of gRNAde designs is consistently higher than that of the baselines, with many variants exceeding the activity of the wildtype (fitness > 0).

F. Correlation between high-throughput functional assay and low-throughput gel for the native 5TU sequence and 9 gRNAde variants. The fitness scores are highly correlated with the average per-junction ligation efficiency from the gel (Pearson r = 0.85), and the fitness of the least active variant 319 is used as an activity threshold for the high-throughput assay.

Mechanistic insights from gRNAde's generative design strategy

To understand the basis for gRNAde's superior performance across diverse RNA design tasks, we analyzed the mutational patterns in active ribozyme designs from the gRNAde pipeline compared to rational design with filtering. Rational design tended to mainly mutate canonical base-paired positions while conserving unpaired loops, a strategy that preserves secondary structure but fails to account for essential tertiary interactions (**Figure 4B**). gRNAde, in contrast, generated active designs with a more balanced mutational profile, frequently altering nucleotides in unpaired regions and loops (**Figure 4A, C**). Critically, it showed a strong preference for mutating a structurally complex unpaired region near the template-binding site that is essential for the kissing loop interface between the 5TU and t1 subunits (**Figure 4D, E**). This demonstrates that gRNAde, by training on a diverse corpus of 3D structures, has learned sophisticated, **non-local structure-function relationships** that go far beyond simple base-pairing rules, allowing it to successfully navigate a complex functional landscape.

To further contextualize gRNAde's design strategy against human expertise, we revisited the OpenKnot Benchmark to analyze successful designs in Round 7 by computing their native sequence recovery from the wildtype or starting sequence (**Figure 4F**). The analysis revealed that while gRNAde matched the structural accuracy of human experts, its designs were significantly more distant in sequence space. The median native sequence recovery for gRNAde designs was 32%, substantially lower than the 72% observed for human experts. This divergence demonstrates that unlike human designers, who exhibit a strong bias toward smaller edits close to the native sequence, gRNAde can successfully perform generative jumps in sequence space for diverse RNA targets. This capability underscores gRNAde's key advantages: its data-driven understanding of structurally complex, unpaired regions and its capacity to retain the target structure across vast sequence distances.

Figure 4 | Mechanistic analysis of gRNAde design strategies.

Figure 4 | Mechanistic analysis of gRNAde design strategies.

The analysis compares gRNAde's design strategy against rational design and human experts, demonstrating its capacity to learn non-local, 3D-informed structure-function relationships and achieve highly sequence-divergent yet structurally accurate designs.

A-C. Per-position mutation probability ("hotspots") for active RNA polymerase ribozyme designs generated by gRNAde (A) and rational design with filtering (B), and the difference between them (C).

D, E. The difference in mutation probability is mapped onto the secondary structure (D) and tertiary structure (E) of the catalytic subunit 5TU that was the target of design. This reveals distinct design strategies: Rational design preferentially mutates canonical base-paired positions (blue) in active designs, whereas gRNAde identifies novel hotspots in structurally complex, unpaired regions (red), particularly near the template-binding site (J1/3) as well as ends of helices P5 and P9.

F. Median native sequence recovery of successful designs from gRNAde and expert human designers in OpenKnot Round 7, presented by position type (pseudoknotted, paired, unpaired, and all positions) for natural (left) and synthetic (right) RNA targets. Across all position types, gRNAde designs exhibit significantly lower median native sequence recovery (32%) compared to human experts (72%). This demonstrates gRNAde's capacity to achieve large generative jumps in sequence space while matching expert accuracy at forming the target structure.

Discussion

This work has introduced and experimentally validated a general-purpose deep learning pipeline for the inverse design of RNA. The results demonstrate that the gRNAde method can solve two of the most significant and long-standing challenges in the field. First, in a blinded, community-wide competition, the automated pipeline designed complex pseudoknotted structures with an accuracy matching that of human experts, establishing a new state-of-the-art for structural RNA design. Second, the pipeline was used to generatively explore the functional landscape of a complex RNA polymerase ribozyme, discovering highly active enzymes at vast sequence distances from any known functional variant. This dual success on fundamentally different problems—one focused on static structural accuracy, the other on dynamic catalytic function—validates the power and generality of the approach.

The findings have broader implications for our understanding of both natural and engineered biological systems. The OpenKnot competition results, where gRNAde's designs proved more stable for targeted structural goals than their native counterparts, suggest that data-driven optimization can uncover biophysical solutions that are more ideal than those found by evolution, which operates under a multitude of competing constraints. Similarly, the discovery of a diverse and functional ribozyme quasispecies, with active variants differing by nearly 20% of their sequence, demonstrates that the functional sequence space for complex RNA is both vast and contains structurally-similar solutions at mutational distances previously inaccessible to directed evolution. Generative models like gRNAde provide a powerful new tool to explore this vast, uncharted territory, providing an alternative to local exploration by directed evolution or the limitations of human-centric rational design.

Beyond its direct applications, this work highlights the potential for a virtuous cycle in computational biology, where the success of gRNAde in generating vast libraries of high-quality designs has enabled the creation of new, large-scale datasets. For example, a follow-on collaboration used gRNAde to generate 68 million plausible sequences for 1.6 million pseudoknotted structures, a dataset orders of magnitude larger than previously possible. This dataset then trained RibonanzaNet 2, a next-generation predictive model with significantly improved accuracy. This creates a powerful feedback loop where generative models produce data to train better structure prediction models, which can then be incorporated back into the design pipeline as more accurate filters, further accelerating progress.

Looking forward, as advances in experimental techniques like cryo-EM continue to expand the universe of known RNA structures[30,31], the data foundations for RNA structure prediction and design models will grow, making pipelines like gRNAde increasingly powerful and bringing the goal of programmable RNA biology closer to reality. We anticipate that gRNAde will be widely useful, enabling the design of novel riboswitches, ribozymes, and RNA nanostructures. To accelerate progress and enable broader community use, gRNAde's datasets, training code, and design pipelines are fully open-source at github.com/chaitjo/geometric-rna-design.

Methods

gRNAde model and training

The gRNAde model is a structure-conditioned autoregressive language model for RNA sequence design. We have previously described the model architecture[19] and workflow[20] in detail. Here, we made key modifications to the input representation and training procedure to enable design from both secondary and tertiary structure, as well as sequence constraints.

The model takes as input a target RNA's pseudoknotted secondary structure, a 3D backbone structure, and partial sequence constraints. Each of these three input modalities is optional and the model can flexibly handle missing inputs. Each nucleotide is represented as a node in a geometric graph, featurized using a 3-bead coarse-grained representation (P, C4', and N1/N9 atoms)[32] and local geometric properties[33]. A key architectural modification from the initial version of gRNAde is the explicit integration of secondary structure information into the graph. Each node is connected to its neighbors by edges of three types: (a) its 32 nearest neighbors along the RNA backbone (1D); (b) all nodes involved in base pairs and pseudoknots from the secondary structure (2D); and (c) its 32 nearest neighbors in 3D space, if a 3D structure is provided. Edge features encode the edge type, relative distances and orientations between nodes. The core of the model is an SE(3)-equivariant Graph Neural Network[34] (GNN) encoder composed of Geometric Vector Perceptron (GVP-GNN) layers[35], which processes the geometric graph to produce a latent representation for each nucleotide. An autoregressive GVP-GNN decoder then uses these representations to predict the nucleotide sequence from 5' to 3'. We use 4 layers each for the encoder and decoder. If a partial sequence is provided as a constraint, the decoder fixes the identity of those nucleotides via logit biasing and designs the remainder of the sequence, similar to ProteinMPNN[36].

The model was trained on a dataset of 4,211 RNA structures with up to 500 nucleotides, covering a diverse set of topologies from the Protein Data Bank[37] at resolution <= 4.0 A, curated by RNASolo[23] with a temporal cutoff of 31 October 2023. To enable design without complete 3D information, we introduced a novel training strategy: for a randomly selected 50% of training examples at each training epoch, the 3D backbone coordinates and corresponding 3D edges were dropped out. This forces the model to learn the implicit 3D structural information contained within the 1D and 2D graph connectivity alone. As a result, the trained model can generate high-quality designs even when a 3D structure is unavailable or unreliable. This capability was critical for designing the synthetic targets in the OpenKnot Benchmark, where only a target secondary structure was available.

Computational design and screening pipeline

For each design task, an initial library of approximately 1 million candidate sequences was generated using gRNAde by sampling from the model's output distribution with varying temperatures (0.1 to 1.0) and random seeds. This allows the model to balance high-confidence, lower-diversity sampling (low temperature) with broader exploration of the solution space (high temperature).

Each generated sequence was then screened using RibonanzaNet, an RNA structure foundation model[22]. We chose RibonanzaNet as its predictions of per-nucleotide chemical reactivity and secondary structure serve as a more reliable computational proxy for experimental folding than current 3D structure predictors. While we initially evaluated 3D self-consistency using RhoFold[38], this metric was excluded after control experiments revealed that the predictor failed to recover the correct backbone geometry for native sequences in the Eterna OpenKnot Benchmark. Given this inability to reliably fold the 'ground truth' inputs, we concluded that current 3D prediction tools are not sufficiently robust to serve as filters for de novo designs.

The screening process involved predicting a per-nucleotide chemical reactivity profile (for the 2A3 modifier) and a secondary structure for each sequence. Designs were then ranked based on two primary scores: (1) a Secondary Structure Score, calculated as the Matthews Correlation Coefficient (MCC) between the predicted and target secondary structures. For natural targets, we applied a stringent filter, retaining only sequences with an MCC > 0.9 to ensure a high likelihood of correct folding; this criterion was omitted for synthetic targets as RibonanzaNet's secondary structure predictor was fine-tuned only on natural sequences. (2) a Chemical Reactivity Score, calculated as the Mean Absolute Error (MAE) between the predicted reactivity profile and a target profile (either from experimental data or predicted from the native sequence). For the OpenKnot Benchmark, instead of the MAE, we used an *in silico* OpenKnot Score between the predicted reactivity profile and the target secondary structure.

The entire pipeline is highly efficient; generating and scoring one million sequences for a design campaign takes under 12 hours on a single NVIDIA A100 GPU. After removing duplicates, this process typically yields hundreds of thousands of unique sequences, from which the top-ranked candidates were selected for experimental validation. This high-throughput capability contrasts sharply with physics-based methods like Rosetta[9], where generating a single design can take over 24 hours on a CPU, making large-scale exploration computationally prohibitive.

Eterna OpenKnot Benchmark blinded competition

The gRNAde pipeline was benchmarked in the Eterna OpenKnot Benchmark rounds 7a and 7b, targeting 40 diverse pseudoknotted RNA structures. We submitted two distinct sets of 20 designs per target—one conditioned on both the target 3D backbone and pseudoknotted secondary structure, and one conditioned solely on the secondary structure—to assess the necessity of explicit 3D inputs. For synthetic targets lacking experimental structures, predicted backbones provided by the Eterna organizers were utilized for the 3D-conditioned set.

Experimental validation was performed independently by the Eterna organizers at Stanford University. Synthesized RNAs were subjected to high-throughput chemical probing using SHAPE (Selective 2'-Hydroxyl Acylation analyzed by Primer Extension) with the reagent as 2-aminopyridine-3-carboxylic acid imidazolide (2A3)[39,40]. The resulting reactivity data was used to calculate an OpenKnot Score[22] (between 0-100), which quantifies the agreement between the experimental SHAPE profile and the desired profile of unpaired and paired nucleotides for the target structure. An OpenKnot Score greater than 90 was considered a high-confidence successful design that is likely to fold into the target structure.

To provide a direct automated baseline for comparison, the organizers also independently submitted 20 designs using Rosetta's RNA inverse design protocol[9], the current state-of-the-art physics-based method for 3D RNA design. As an additional sanity check, the organizers evaluated 10 replicates of the wildtype (native) RNA sequence for each puzzle. While wildtype sequences are expected to achieve high OpenKnot scores, particularly for natural RNAs, they may not represent the optimal sequence for structure formation, which is precisely what the design challenge aims to discover. The competition also included other, contemporaneous AI-based methods from Stanford University[41], University of Washington[26,27], and Texas A&M University (not public). A full head-to-head comparison of all automated methods will be presented in a forthcoming publication.

Polymerase ribozyme design

Functional variants of the 5TU catalytic subunit of the triplet polymerase ribozyme[42] were designed based on its cryo-EM structure[13], while the sequence of the t1 auxiliary subunit was held constant. To guide the design process, we defined position-specific mutation probabilities for the 5TU subunit derived from the fitness landscape data of McRae et al. This procedure combined two complementary metrics:

1. Maximum single-mutant fitness, showing tolerance to point mutations. Fitness values were uniformly binned into 3 categories (1 = low, 2 = medium, 3 = high).
2. Higher-order mutant combinability score[43], quantifying how well mutations at each position can be combined with other mutations to create active variants. Combinability values were uniformly binned into 3 categories (1 = low, 2 = medium, 3 = high).

To yield the final design probability for each position (**Figure 3B**), the binned single-mutant fitness and combinability scores were summed and divided by 6. This yields a probability value between 0.0 to 1.0 for each position. To preserve essential catalytic activity, key functional residues at the catalytic site (positions 41-43), template binding region (positions 22-24), and triple helix-forming adenosines (positions 25-30) were constrained to the wildtype identity by setting their design probability to zero.

The design probabilities are used as stochastic constraints for positions to be mutated when creating a batch of designs with gRNAde. 1 Million designs were generated with gRNAde and filtered to select 1,000 candidates spanning mutational distances of 15 to 40 from the wildtype sequence (40 designs per mutational distance). This represents a significant extension beyond the coverage of the fitness landscape data from McRae et al., which had almost negligible sampling beyond 6 mutations.

To isolate the contributions of gRNAde's sequence generation versus our computational filtering pipeline, we implemented two rational design heuristics as baselines. The first, **'rational design only'**, involved generating 1 million sequences using position-specific nucleotide identity sampling that respected base-pairing constraints, from which 500 designs were selected randomly (20 per mutational distance). The nucleotide identity for unpaired positions is sampled randomly. The second, **'rational design with filtering'**, applied our full RibonanzaNet computational filtering pipeline to the same pool of 1 million rationally generated sequences to select the top 500 candidates. This experimental design allows for a direct comparison of gRNAde against commonly used rational approaches while ablating the specific contribution of the generative model.

High-throughput ribozyme activity assay

The designed 5TU variants from gRNAde, rational design with filtering, and rational design only were synthesized as a pooled DNA oligonucleotide library (termed gRNAde_library henceforth) of 1989 sequences. This accounts for duplicates and additionally includes the native 5TU sequence. The library was subjected to an in vitro activity selection assay that measures templated RNA synthesis.

Preparation of DNA templates for transcription

PCR amplification of gRNAde_library was performed using Platinum SuperFi II PCR Master Mix (Invitrogen). Each reaction had a total volume of 50 µL and included 1 µM of primers forceGG and HDVrec along with gRNAde_library that was used as a template. The thermal cycling protocol involved an initial denaturation at 98 ℃ for 30 seconds, followed by 10 cycles of: denaturation at 98 ℃ for 10 seconds, primer annealing at 55.8 ℃ for 10 seconds, and extension at 72 ℃ for 15 seconds. This was followed by a final extension at 72 ℃ for 5 minutes, then held at 10 ℃. 4 µL of the PCR mixture was then run on a 4% UltraPure agarose (Life Technologies Ltd) gel to check that the size of the amplified construct is correct. The resultant amplified DNA library was then purified using a PCR purification kit (Qiagen).

To add on the T7 promoter sequence, the flexible linker, and the templates for copying, the purified DNA library was then used as template in another round of PCR. This was also conducted using Platinum SuperFi II PCR Master Mix (Invitrogen) under similar conditions using the primers HDVrt and 5T7HP6x6AUA_forceGG. The 5T7HP6x6AUA_forceGG primer allows for the addition of the T7 promoter sequence, the template encoding 6 AUA triplets to be copied by the ribozyme, and the flexible linker made of 6x(AACA) repeats. The HDVrt primer allows for the introduction of a HDV ribozyme 3′-end cassette. To vary the linker length and the template used to measure the ribozyme activity, this was repeated with 5T7HP12x6AUA_forceGG (template encodes 6 AUA triplets, linker contains 12x(AACA) repeats), 5T7HP6x6GAA_forceGG (template encodes 6 GAA triplets, linker contains 6x(AACA) repeats), and 5T7HP12x6GAA_forceGG (template encodes 6 GAA triplets, linker contains 12x(AACA) repeats) replacing 5T7HP6x6AUA_forceGG. The sizes of the constructs were also checked on a 4% UltraPure agarose (Life Technologies Ltd) gel and the DNA constructs were then purified using a PCR purification kit (Qiagen).

Preparation of RNA constructs

The four DNA templates were then transcribed following an RNA transcription protocol based on the Megascript method[44] using T7 RNA polymerase. The 50 µL reaction mixture contained 40 mM Tris buffer at pH 8, along with 10 mM DTT, 2 mM spermidine, and 20 mM MgCl. Each nucleotide triphosphate was added at 7.5 mM concentration. The DNA template was included at approximately 5 pmoles. The reaction also included 0.01 units/µL yeast inorganic pyrophosphatase (Thermo Fischer Scientific) and approximately 72 µg/mL T7 RNA polymerase (expressed and purified in house). After incubating overnight at 37 ℃ (12-16 hours), the mixture

was treated with Turbo DNase (Thermo Fischer Scientific) at 0.1 units/µL for one hour.

To increase the efficiency of HDV cleavage, the *in vitro* transcription reactions were then subjected to temperature cycling. Transcription reactions were first incubated at 50 °C for 1 minute and then placed on ice for 3 minutes. Subsequently, for every 50 µL transcription reaction, 20 µL of gel loading buffer (95% formamide, 25 mM EDTA, bromophenol blue) was added, and the mixture was incubated at 50 °C for another minute. After placing the mixture on ice for 3 minutes, 120 µL of gel loading buffer was added, and the mixture was heated to 94 °C for 5 minutes. Then, the samples were loaded into a PAGE gel for purification.

After heat denaturation at 94 °C for 5 minutes, samples were loaded onto a denaturing polyacrylamide gel made of a 10% acrylamide/bis-acrylamide 19:1 solution (Severn Biotech), 8M urea, 1x Tris-borate-EDTA buffer (89 mM Tris pH 7.6, 89 mM boric acid, 2 mM EDTA). Electrophoresis was performed at 30W constant power using a Cambridge Electrophoresis EV400 system using bromophenol blue as a marker for migration. Target bands were visualized by UV shadowing and cut out from the gel. The excised gel pieces were crushed using a 1000 µL pipette tip and soaked in Tris-EDTA buffer (10mM Tris pH 7.4, 1mM EDTA) to create a suspension. Following one freeze-thaw cycle (dry ice freezing, 50 °C thawing) and rotation in the cold room overnight, the solution was filtered through 0.22 µm filters (Costar), and the RNA was extracted using ethanol precipitation with 73% ethanol. Final product concentration was measured using a Nanodrop ND-1000 spectrophotometer (Thermo Fisher Scientific) at 260nm using sequence-specific extinction coefficients calculated with the Oligocalc software[45].

High-throughput screening of polymerase ribozyme activity

To test the activity of the designed polymerase ribozyme variants a single round of *in vitro* selection for primer extension was carried out on pooled libraries of ribozyme sequences. The library composition before and after a single selection round was assessed via next-generation sequencing, and relative enrichment values were computed as proxies for fitness.

A single selection round was carried out similarly to previous reports[13,42], where ribozyme variants are tethered via a flexible RNA linker to a template. Completion of the template copying leads to covalent linkage of the synthesized product to the ribozyme responsible to the synthesis, ensuring genotype-phenotype linkage. Active variants can therefore be enriched by selective pull-down and denaturing PAGE purification of the full-length product-ribozyme conjugates.

The selection round reactions were set up as follows: 5 pmoles of the 6x6AUA library (contains both the 5TU variants to be tested and the 6 AUA template) was annealed with equimolar t1.5 ribozyme, BCy3P10 primer and 1.25 nmol of AUA triplet in 125 µL of water with 0.1% tween (80 °C 2 min, 17 °C 10 min). The annealed mixture was then placed on ice, 125 µL of chilled 2x extension buffer (100 mM Tris-Cl pH 8.3, 400 mM $MgCl_2$) was added, and the reaction was frozen with dry ice and incubated at -7 °C overnight. The reactions were then stopped using equimolar EDTA to chelate magnesium ions. This was repeated using the 12x6AUA library under the same conditions.

A similar setup was used for the 6x6GAA and the 12x6GAA libraries. Key differences involve adding GAA triplet instead of the AUA triplet and incubating the reaction at -7 °C for 3 hours instead of overnight.

The biotinylated RNA was isolated from the reactions by binding to streptavidin coated paramagnetic beads (Dynabeads MyOne Streptavidin C1, Invitrogen). Beads were washed twice in BWBT buffer (0.2 M NaCl, 10 mM Tris·HCl pH 7.4, 1 mM EDTA, 0.1% Tween-20), twice in NaBET25 (25 mM NaOH, 1mM EDTA, 0.05% Tween 20), twice in BWBT, and then resuspended in 95% Formamide with 25 mM EDTA. This suspension was heated at 94°C for 5 minutes to elute the biotinylated products from the beads. The eluate was loaded on a denaturing PAGE gel to separate the full-length product from the primer and intermediate products. The full-length products were PAGE purified and extracted from the gel fragments onto streptavidin coated paramagnetic beads. The beads were isolated from the gel slurry by filtering of the supernatant using 50 μm size filters (Partec Celltrics, Wolflabs). The beads were then transferred to a series of reactions to enable the amplification of the bead-bound sequences. Namely, the 2′,3′-cyclic phosphate resulting from HDV cleavage was removed using T4 PNK (NEB). A constant adaptor sequence (AdeHDVlig) was then ligated to the 3′-end of the bead-bound recovered sequences using T4 RNA ligase 2 truncated KQ (NEB). The ligated product was then used as template for RT-PCR using SuperScript III One-Step RT-PCR System with Platinum Taq DNA Polymerase (Invitrogen), with primers HDVrec and forceGG at 0.5 μM each. The library prior to the selection was also PNK treated, adapter ligated and RT-PCR amplified in parallel, with no purification in between each step (5 pmoles of RNA was used in a 50 μL T4 PNK reaction, 0.1 pmoles were carried forward in an adaptor ligation reaction, and 0.01 pmoles were used for RT-PCR).

The RT-PCR products were further amplified to introduce the P7 and P5 Illumina sequencing adapters by PCR (primers used for each library are detailed in **Supplementary Table 1**) using GoTaq Hot Start (Promega). The PCR products were agarose gel purified (Qiagen), quantified using Qubit dsDNA HS Assay Kit (Invitrogen) and sequenced using a MiSeq sequencer using a 600-cycle v3 chemistry kit set-up for 2x250 reads. The reads were paired and quality filtered using fastp[46] and demultiplexed using cutadapt[47]. The demultiplexed reads were analysed with python scripts available at github.com/chaitjo/geometric-rna-design.

Fitness calculation

The fractional abundance of each variant in the pre-selection (input) and post-selection (output) libraries was determined by next-generation sequencing as described above. Fitness was calculated as the log2 enrichment of a variant relative to the wildtype 5TU sequence. Sequences with at least 5 reads in the pre-selection library and at least 1 read in the post-selection library were classified as active if the fitness was above an activity threshold. Sequences with zero reads in post-selection libraries which cannot be assigned a fitness value were classified as inactive.

We used the 6x6AUA libraries with a short linker incubated overnight for the results in the main

text (**Figure 3**). These libraries were chosen based on obtaining the highest Pearson correlation coefficient of 0.86 between the average per-junction ligation efficiency from a low-throughput gel assay (described subsequently) and the high-throughput fitness (**Supplementary Figures 3, 4**). We used the high-throughput fitness of the least active variant 319 (as determined by the gel) as our activity threshold at -1.86.

Primer extension low-throughout assay of ribozyme variants

In order to assay the activity of 5TU and its gRNAde-designed variants in detail, we individually transcribed and purified each RNA sequence (as described in Preparation of RNA constructs). The PAGE purified RNA was used to set-up primer extension reactions were the RNA variants were challenged to copy a template using triplet substrates. The reaction was set-up by mixing primer, template, 5TU ribozyme variant, t1.5 subunit, in 0.1% Tween-20 in half the final reaction volume and heat annealing (80 ℃ 2 min, 17 ℃ 10 min). The remaining reaction volume containing 2x chilled reaction buffer (100 mM Tris-Cl pH 8.3, 400 mM MgCl$_2$) was added to the reactions, which were then frozen in dry ice and incubated at -7 ℃ for the time indicated in a R4 series TC120 refrigerated cooling bath (Grant). The primer extension was separated using denaturing PAGE, and visualized on a Typhoon Trio scanner (GE Healthcare). The band intensity values were measured using ImageQuantTL (Cytiva) and used to compute the per-junction ligation efficiency, as following:

$$\frac{1}{n-1}\sum_{i=2}^{n}\frac{\sum_{j=i}^{n}x_j}{\sum_{j=i-1}^{n}x_j}$$

where x_j is the band intensity corresponding to the j^{th} triplet incorporation.

Data and Code Availability

The gRNAde pipeline is open-source and available at github.com/chaitjo/geometric-rna-design under a permissive MIT License. Training datasets and pre-trained model weights are available at huggingface.co/chaitjo/gRNAde. Sequencing data from the ribozyme activity assay, analysis scripts, and final designed sequences have been deposited in a public repository and will be made available upon publication. The data from the Eterna OpenKnot Benchmark is publicly available at github.com/eternagame/OpenKnotAIDesignData.

Acknowledgements

We thank Rhiju Das and the Eterna organizers for hosting the OpenKnot Benchmark and for sharing the associated experimental data. We thank Arian Jamasb, Ramon Vinãs, Charles Harris, Alex Morehead, and Rishabh Anand for their contributions to the initial version of gRNAde. We thank Bryce Clifton, Kevin Goeij, Ganesh Agam, Maria Brunderova, and Rushikesh Dasoondi for useful discussions.

CKJ was supported by the A*STAR Singapore National Science Scholarship, Qualcomm Innovation Fellowship, and University of Cambridge Dawn HPC Pioneer Project grant. SLYK was supported by the Cambridge Trust PhD Scholarship. SVM was supported by the UKRI Centre for Doctoral Training in Application of Artificial Intelligence to the study of Environmental Risks (EP/S022961/1). This work was supported by the Medical Research Council (MRC) as part of United Kingdom Research and Innovation (also known as UK Research and Innovation (UKRI)) (MRC program grant MC_U105178804) (EG, SLYK, PH). For the purpose of open access, the MRC Laboratory of Molecular Biology has applied a CC BY public copyright license to any Author Accepted Manuscript version arising.

Author Contributions

All authors developed the methodology. CKJ implemented the gRNAde code and generated computational designs with inputs from SVM. EG and SLYK performed the polymerase ribozyme experiments. CKJ, EG, and SLYK analyzed the experimental data. CKJ, EG, and SLYK wrote the paper with inputs from all authors.

Supplementary Figures

Supplementary Figure 1 | gRNAde maintains competitive performance on long RNA pseudoknots in the Eterna OpenKnot Benchmark.

Supplementary Figure 1 | gRNAde maintains competitive performance on long RNA pseudoknots in the Eterna OpenKnot Benchmark.

Performance of wildtype sequences, Rosetta[9], MPNN[26], RFdiffusion[25], gRNAde, and expert human designers for the Eterna OpenKnot Round 4 challenge, which targeted pseudoknotted RNAs of up to 240 nucleotides.

A. Distribution of OpenKnot scores for individual designs across 10 natural target puzzles (success threshold > 90, red dashed line).

B. The success rate on natural targets, defined as the percentage of puzzles for which at least one design scored above 90.

C. Distribution of OpenKnot scores for individual designs across 10 synthetic target puzzles (success threshold > 90, red dashed line).

D. The success rate on synthetic targets, defined as the percentage of puzzles for which at least one design scored above 90.

gRNAde achieves success rates of 67% on natural targets and 70% on synthetic targets, substantially outperforming RFdiffusion (next best AI). Rosetta (physics-based) could not be evaluated due to scalability issues. Native sequences achieved very low success rates on both categories, which demonstrates gRNAde's ability to design idealized sequences for complex pseudoknotted RNA structures.

A

Variant:	122	143	33	299	203	319	473	516	549	5TU
Edit distance:	19	18	15	22	20	22	27	27	29	0

B

Template encoding 14 CGU

Supplementary Figure 2 | Synthesis of a CGU repeat template by 5TU and gRNAde designed variants.

Supplementary Figure 2 | Synthesis of a CGU repeat template by 5TU and gRNAde designed variants.

A. Primer extension reactions on a template encoding 14 repeats of CGU were carried out using the top 9 variants by fitness in the 12x6 GAA high-throughput screen. Variant identity and edit-distance from 5TU is labelled below the gel. Reactions were analysed on a 20% 19:1 mono:bis acrylamide denaturing PAGE gel. Reaction conditions: 0.25 μM primer F10, 0.25 μM template tP10_14CGU, 0.25 μM each 5TU variant, 0.25 μM t1.5, 5 μM pppCGU, 200 mM MgCl$_2$, 50 mM Tris-Cl pH 8.3, 0.05% Tween-20, 18 h incubation at -7C. Reactions were stopped with equimolar EDTA to the Magnesium concentration and formamide to a final concentration of 75% and denatured for 5 minutes at 94 °C. To improve resolution, a competing strand containing an unlabelled version of the synthesized product was mixed at 10-fold excess over the template strand prior to heat denaturation and loading.

B. Visual representation of the primer extension process by 5TU+t1.5. A short fluorescently labelled (green star) RNA sequence primer (dark green) is extended by 5TU+t1.5 (3D representation) by one triphosphorylated trinucleotide (triplet) at the time in a template dependent manner (using template encoding 14 CGU repeats). Each triplet addition corresponds to a slower mobility band in the denaturing PAGE gel of (A), with more efficient ribozyme variants adding more triplets to the primer in the same time-frame.

Supplementary Figure 3 | Correlation analysis of different experimental conditions for the high-throughput functional assay with the low-throughput gel assay.

Scatter plots showing the correlation between the high-throughput fitness and average gel per-junction ligation efficiency for native 5TU sequence and 9 gRNAde variants under six different experimental conditions. We observe the highest correlation with the AUA libraries with a short linker incubated overnight.

Supplementary Figure 4 | Correlation analysis of computational filtering metrics with experimental fitness.

Scatter plots showing the correlation between RibonanzaNet chemical reactivity scores and experimental fitness values for designs from the gRNAde pipeline as well as rational design with and without filtering. Increasing point sizes correspond to increasing mutational distance range. We observe the highest correlation for designs from the gRNAde pipeline.

Supplementary Table 1 | Oligonucleotide sequences used for high-throughput ribozyme activity assay

Modifications are marked with the supplier's specific code. 'GP' indicates oligonucleotides that were gel purified using PAGE, while sequences without this designation were used in their original supplied form. Sequences in black are DNA while sequences in green are RNA.

Application	Name	Source, purification	Sequence	Notes
Library of all 5TU variants assayed for activity	gRNAde_library	Twist Bioscience	AACAAACAACAAAACAAACAAACAGGATCTTCTCGATCTAACAAAAAAGACAAATCTGCCACAAAGCTTGAGAGCATCTTCGGATGCAGAGGCGGCAGCCTTCGGTGGCGCGATAGCGCCAACGTTCTCAACTATGACACGCAAAACGCGTGCTCCGTTGAATGGAGTTTATCATGGGGTCGGCATGGCATC	This is a library containing 1989 sequences, including 5TU (sequence shown). Underlined nucleotides indicate the ribozyme sequence that is variable depending on the variant tested. The first two Gs are kept constant to facilitate PCR. The list of sequences can be found at github.com/chaitjo/geometric-rna-design
Used for PCR amplification of gRNAde_library	forceGG	IDT	AACAAACAACAAAACAAACAAACAGG	Forward primer for PCR
	HDVrec	IDT	GATGCCATGCCGACCC	Reverse primer for PCR
Used for PCR to add on T7 RNA polymerase transcription start site and templates	5T7HP6x6AUA_forceGG	IDT	GATCGATCTCGCCCGCGAAATTAATACGACTCACTATAGGTCCGAAAGGACCTATTATTATTATTATTATCGGTTGGCAGAACAAACAACAAAACAAACAAACAGG	Forward primer for PCR: shorter linker with more challenging template (6 AUA)
	5T7HP12x6AUA_forceGG	IDT	GATCGATCTCGCCCGCGAAATTAATACGACTCACTATAGGTCCGAAAGGACCTATTATTATTATTATTATCGGTTGGCAGAACAAACAACAAACAAACAAACAAACAACAAAACAAACAAACAGG	Forward primer for PCR: longer linker with more challenging template (6 AUA)

	5T7HP6x6GAA_forceGG	IDT	GATCGATCTCGCCCGCGAAATTAATACGACTCACTATAGGTCCGAAAGGACCTTCTTCTTCTTCTTCTTCCGGTTGGCAGAACAAACAACAAAACAAACAAACAGG	Forward primer for PCR: shorter linker with easier template (6 GAA)
	5T7HP12x6GAA_forceGG	IDT	GATCGATCTCGCCCGCGAAATTAATACGACTCACTATAGGTCCGAAAGGACCTTCTTCTTCTTCTTCCGGTTGGCAGAACAAACAAACAAACAAACAAACAAACAACAAAACAAACAAACAGG	Forward primer for PCR: longer linker with easier template (6 GAA)
	HDVrt	IDT	CTTCTCCCTTAGCCTACCGAAGTAGCCCAGGTCGGACCGCGAGGAGGTGGAGATGCCATGCCGACCC	Reverse primer for PCR
Primer extension assay	BCy3P10	IDT, GP	/5Biosg//iCy3/CUGCCAACCG	Primer used in assay
	T1.5	IVT, GP	GACCAAUCUGCCCUCAGAGCCCGAGAACAUCUUCGGAUGCAGAGGAGGCAGGCUUCGGUGGCGCGAUAGCGCCAACGUCCUCAACCUCCAAUGCAUCCCACCACAUGAUGAGCCUGAAGAGCCUUGGUUUUUUUG	5TU works together with t1.5 as a heterodimer
	tP10_14CGU	IDT, GP	ACGACGACGACGACGACGACGACGACGACGACGACGACGCGGUUGGCAG	Template used for primer extension assay
	P10CGU20comp	IVT, RNE	GGCUGCCAACCGCGUCGUCGUCGUCGUCGUCGUCGUCGUCGUCGUCGUCGUCGUCGUCGUCGUCGUCGUCGUCGU	Used as "competing oligo" to improve resolution of primer extension assay

	P10CGU20comp(tx)	IDT	ACGACGACGACGACGACGAC GACGACGACGACGACGACGA CGACGACGACGACGACGACG CGGTTGGCAGCCTATAGTGAG TCGTATTAATTTCGCGGGC	Used with 5T7 to prepare the template for transcription of P10CGU20com p.
	F10	IDT, GP	/56-FAM/CUGCCAACCG	Used as primer in primer extension assay
Illumina sequencing primers	P71force GG	IDT	CAAGCAGAAGACGGCATACGA GATGTGACTGGAGTTCAGACG TGTGCTCTTCCGATCNNNATCA CGAACAAACAACAAAACAAAC AAACAGG	
	P51HDV ba	IDT	AATGATACGGCGACCACCGAG ATCTACACTCTTTCCCTACACG ACGCTCTTCCGATCTNNNATCA CGGATGCCATGCCGACCC	Used for 6x6 AUA pre-selection
	P52HDV ba	IDT	AATGATACGGCGACCACCGAG ATCTACACTCTTTCCCTACACG ACGCTCTTCCGATCTNNNCGA TGTGATGCCATGCCGACCC	Used for 12x6 AUA pre-selection
	P53HDV ba	IDT	AATGATACGGCGACCACCGAG ATCTACACTCTTTCCCTACACG ACGCTCTTCCGATCTNNNTTAG GCGATGCCATGCCGACCC	Used for 6x6 GAA pre-selection
	P54HDV ba	IDT	AATGATACGGCGACCACCGAG ATCTACACTCTTTCCCTACACG ACGCTCTTCCGATCTNNNTGA CCAGATGCCATGCCGACCC	Used for 12x6 GAA pre-selection
	P55HDV ba	IDT	AATGATACGGCGACCACCGAG ATCTACACTCTTTCCCTACACG ACGCTCTTCCGATCTNNNACA GTGGATGCCATGCCGACCC	Used for 6x6 AUA overnight
	P56HDV ba	IDT	AATGATACGGCGACCACCGAG ATCTACACTCTTTCCCTACACG ACGCTCTTCCGATCTNNNGCC AATGATGCCATGCCGACCC	Used for 12x6 AUA overnight

	P57HDV ba	IDT	AATGATACGGCGACCACCGAG ATCTACACTCTTTCCCTACACG ACGCTCTTCCGATCTNNNCAG ATCGATGCCATGCCGACCC	Used for 6x6 GAA 3 hours
	P58HDV ba	IDT	AATGATACGGCGACCACCGAG ATCTACACTCTTTCCCTACACG ACGCTCTTCCGATCTNNNACT TGAGATGCCATGCCGACCC	Used for 12x6 GAA 3 hours
	P59HDV ba	IDT	AATGATACGGCGACCACCGAG ATCTACACTCTTTCCCTACACG ACGCTCTTCCGATCTNNNGAT CAGGATGCCATGCCGACCC	Used for 6x6 GAA 6 hours
	P510HD Vba	IDT	AATGATACGGCGACCACCGAG ATCTACACTCTTTCCCTACACG ACGCTCTTCCGATCTNNNTAG CTTGATGCCATGCCGACCC	Used for 12x6 GAA 6 hour

References

1. Cech, T. R. *The Catalyst: RNA and the Quest to Unlock Life's Deepest Secrets*. (WW Norton & Company, 2024).

2. Guo, P. The emerging field of RNA nanotechnology. *Nat. Nanotechnol.* **5**, 833–842 (2010).

3. Damase, T. R. *et al.* The limitless future of RNA therapeutics. *Front. Bioeng. Biotechnol.* **9**, 628137 (2021).

4. Doudna, J. A. & Charpentier, E. The new frontier of genome engineering with CRISPR-Cas9. *Science* (2014).

5. Green, A. A. *et al.* Complex cellular logic computation using ribocomputing devices. *Nature* **548**, 117–121 (2017).

6. Zhang, K. *et al.* Cryo-EM and antisense targeting of the 28-kDa frameshift stimulation element from the SARS-CoV-2 RNA genome. *Nat. Struct. Mol. Biol.* **28**, 747–754 (2021).

7. Staple, D. W. & Butcher, S. E. Pseudoknots: RNA structures with diverse functions. *PLoS Biol.* (2005).

8. Rivas, E. & Eddy, S. R. A dynamic programming algorithm for RNA structure prediction including pseudoknots. *J. Mol. Biol.* (1999).

9. Das, R., Karanicolas, J. & Baker, D. Atomic accuracy in predicting and designing noncanonical RNA structure. *Nat. Methods* (2010).

10. Wochner, A., Attwater, J., Coulson, A. & Holliger, P. Ribozyme-catalyzed transcription of an active ribozyme. *Science* (2011).

11. Attwater, J., Wochner, A. & Holliger, P. In-ice evolution of RNA polymerase ribozyme activity. *Nat. Chem.* (2013).

12. Tjhung, K. F., Shokhirev, M. N., Horning, D. P. & Joyce, G. F. An RNA polymerase ribozyme that synthesizes its own ancestor. *Proceedings of the National Academy of Sciences* (2020).

13. McRae, E. K. S. *et al.* Cryo-EM structure and functional landscape of an RNA polymerase ribozyme. *Proceedings of the National Academy of Sciences* (2024).

14. Gianni, E. *et al.* A polymerase ribozyme that can synthesize both itself and its complementary strand. *bioRxiv* (2024) doi:10.1101/2024.10.11.617851.

15. Yesselman, J. D. *et al.* Computational design of three-dimensional RNA structure and function. *Nat. Nanotechnol.* (2019).

16. Sumi, S., Hamada, M. & Saito, H. Deep generative design of RNA family sequences. *Nat. Methods* (2024).

17. Lambert, C. N. *et al.* Exploring the space of self-reproducing ribozymes using generative models. *Nature Communications* **16**, 7836 (2025).

18. Riley, A. T., Robson, J. M., Ulanova, A. & Green, A. A. Generative and predictive neural networks for the design of functional RNA molecules. *Nature Communications* **16**, 4155 (2025).

19. Joshi, C. K. *et al.* gRNAde: Geometric Deep Learning for 3D RNA inverse design. *International Conference on Learning Representations (ICLR)* (2025).

20. Joshi, C. K. & Liò, P. gRNAde: A Geometric Deep Learning Pipeline for 3D RNA Inverse Design. in *RNA Design: Methods and Protocols* (eds. Churkin, A. & Barash, D.) 121–135 (Springer, Methods in Molecular Biology (MIMB, volume 2847), 2024).

21. Lee, J. *et al.* RNA design rules from a massive open laboratory. *Proceedings of the National Academy of Sciences* (2014).

22. He, S. *et al.* Ribonanza: deep learning of RNA structure through dual crowdsourcing. *bioRxiv* (2024).

23. Adamczyk, B., Antczak, M. & Szachniuk, M. RNAsolo: a repository of cleaned PDB-derived RNA 3D structures. *Bioinformatics* (2022).

24. Strobel, E. J., Yu, A. M. & Lucks, J. B. High-throughput determination of RNA structures. *Nat. Rev. Genet.* (2018).

25. Cao, X., Zhang, Y., Ding, Y. & Wan, Y. Identification of RNA structures and their roles in RNA functions. *Nat. Rev. Mol. Cell Biol.* (2024).

26. Favor, A. *et al.* De novo design of RNA and nucleoprotein complexes. *bioRxiv* (2025) doi:10.1101/2025.10.01.679929.

27. Kubaney, A. *et al.* RNA sequence design and protein-DNA specificity prediction with NA-MPNN. *bioRxiv* (2025) doi:10.1101/2025.10.03.679414.

28. Woese, C. R., Dugre, D. H., Saxinger, W. C. & Dugre, S. A. The molecular basis for the genetic code. *Proc. Natl. Acad. Sci. U. S. A.* **55**, 966–974 (1966).

29. Orgel, L. E. Evolution of the genetic apparatus. *J. Mol. Biol.* **38**, 381–393 (1968).

30. Kappel, K. *et al.* Accelerated cryo-EM-guided determination of three-dimensional RNA-only structures. *Nat. Methods* **17**, 699–707 (2020).

31. Bonilla, S. L. & Kieft, J. S. The promise of cryo-EM to explore RNA structural dynamics. *J. Mol. Biol.* **434**, 167802 (2022).

32. Wadley, L. M., Keating, K. S., Duarte, C. M. & Pyle, A. M. Evaluating and learning from RNA pseudotorsional space: quantitative validation of a reduced representation for RNA structure. *J. Mol. Biol.* (2007).

33. Ingraham, J., Garg, V., Barzilay, R. & Jaakkola, T. Generative Models for Graph-Based Protein Design. in *NeurIPS* (2019).

34. Duval, A. *et al.* A hitchhiker's guide to Geometric GNNs for 3D atomic systems. *arXiv [cs.LG]* (2023) doi:10.48550/ARXIV.2312.07511.

35. Jing, B., Eismann, S., Suriana, P., Townshend, R. J. L. & Dror, R. Learning from Protein Structure with Geometric Vector Perceptrons. *International Conference on Learning Representations (ICLR)* (2020).

36. Dauparas, J. *et al.* Robust deep learning based protein sequence design using ProteinMPNN. *Science* (2022).

37. Berman, H. M. *et al.* The Protein Data Bank. *Nucleic Acids Res.* **28**, 235–242 (2000).

38. Shen, T. *et al.* Accurate RNA 3D structure prediction using a language model-based deep learning approach. *Nat. Methods* **21**, 2287–2298 (2024).

39. Siegfried, N. A., Busan, S., Rice, G. M., Nelson, J. A. E. & Weeks, K. M. RNA motif discovery by SHAPE and mutational profiling (SHAPE-MaP). *Nat. Methods* **11**, 959–965 (2014).

40. Marinus, T., Fessler, A. B., Ogle, C. A. & Incarnato, D. A novel SHAPE reagent enables the analysis of RNA structure in living cells with unprecedented accuracy. *Nucleic Acids Res.* **49**, e34 (2021).

41. Choe, C. A., El Nesr, G., Espeleta, A., Das, R. & Huang, P. 3D Inverse Design of RNA using Deep Learning. (2024).

42. Attwater, J., Raguram, A., Morgunov, A. S., Gianni, E. & Holliger, P. Ribozyme-catalysed RNA synthesis using triplet building blocks. *Elife* (2018).

43. Gantz, M. *et al.* Microdroplet screening rapidly profiles a biocatalyst to enable its AI-assisted engineering. *bioRxiv* (2024) doi:10.1101/2024.04.08.588565.

44. Milburn, S. C., Goldrick, M. & Winkler, M. Compositions and methods for increasing the yields of in vitro RNA transcription and other polynucleotide synthetic reactions. *US Patent* (1993).

45. Kibbe, W. A. OligoCalc: an online oligonucleotide properties calculator. *Nucleic Acids Res.* **35**, W43–6 (2007).

46. Chen, S., Zhou, Y., Chen, Y. & Gu, J. fastp: an ultra-fast all-in-one FASTQ preprocessor. *Bioinformatics* **34**, i884–i890 (2018).

47. Martin, M. Cutadapt removes adapter sequences from high-throughput sequencing reads. *EMBnet J.* **17**, 10 (2011).