CODEX2: full-spectrum copy number variation detection by high-throughput DNA sequencing

Yuchao Jiang[1,2,*], Katherine L Nathanson[3,4], Nancy R Zhang[5,*]

1   Department of Biostatistics, Gillings School of Global Public Health, University of North Carolina, Chapel Hill, NC 27599, USA.

2   Department of Genetics, School of Medicine, University of North Carolina, Chapel Hill, NC 27599, USA.

3   Division of Translational Medicine and Human Genetics, Department of Medicine, Perelman School of Medicine, University of Pennsylvania, Philadelphia, PA 19104, USA.

4   Abramson Cancer Center, Perelman School of Medicine, University of Pennsylvania, Philadelphia, PA 19104, USA.

5   Department of Statistics, The Wharton School, University of Pennsylvania, Philadelphia, PA 19104, USA.

∗   To whom correspondence should be addressed. Tel: (+1) 215-898-8222; Fax: (+1) 215-898-1280; Email: yuchaoj@email.unc.edu, nzh@wharton.upenn.edu.

Abstract (100 words)

High-throughput DNA sequencing enables detection of copy number variations (CNVs) on the genome-wide scale with finer resolution compared to array-based methods, but suffers from biases and artifacts that lead to false discoveries and low sensitivity. We describe CODEX2, a statistical framework for full-spectrum CNV profiling that is sensitive for variants with both common and rare population frequencies and that is applicable to study designs with and without negative control samples. We demonstrate and evaluate CODEX2 on whole-exome and targeted sequencing data, where biases are the most prominent. CODEX2 outperforms existing methods and, in particular, significantly improves sensitivity for common CNVs.

Key words: copy number variation, normalization, next-generation sequencing, latent factor, negative control.

Background

Copy number variations (CNVs) are large deletions and duplications of segments of the chromosome. CNVs are pervasive in the human genome and play a causal role in diseases such as cancer [1]. In the study of disease, CNVs usually appear in two contexts: *germline* CNVs refer to inherited variants, many of which are polymorphic at the population level [2]; in contrary, *somatic* CNVs refer to the variants resulting from somatic mutations, such as those commonly observed in cancer. Germline CNVs can also be described as *common* or *rare* based on their population frequencies. This paper addresses the problem of detection of both germline and somatic CNVs, and, in particular, of improving detection sensitivity for common CNVs under both categories.

With the dramatic growth of sequencing capacity and the accompanying drop in sequencing cost, massively parallel next-generation sequencing offers appealing platforms for genome-wide CNV detection. Whole-genome sequencing (WGS) offers an unbiased genome-wide approach to detect CNVs, while whole-exome sequencing (WES) and targeted sequencing allow the identification of disease-associated variants in coding regions with direct functional interpretation. Despite the rapid technological progress, CNV detection using high-throughput sequencing still faces analytical challenges due to the pervasive biases and artifacts that are introduced during library preparation and sequencing. Proper data normalization is crucial, especially for WES and targeted sequencing, where technical biases are usually magnitudes larger than CNV signal.

In studies where deep coverage of specific genome regions is desired [3-5], or where the cohort of interest is large, WES and targeted sequencing are often preferred as cheaper alternatives to WGS. For example, the DiscovEHR Collaboration (http://www.discovehrshare.com) has sequenced the exomes of more than 50,000 participants, and the Exome Aggregation Consortium (http://exac.broadinstitute.org) has generated WES data for 60,706 unrelated individuals taken from multiple disease-specific and population genetic studies. This paper was primarily motivated by the challenges in WES and targeted sequencing data, but the methods developed here have also been integrated into a CNV detection pipeline for WGS data (Zhou et al., https://doi.org/10.1101/172700), where Mendelian concordance analysis on genetically

related samples shows that the normalization methods prescribed here allow for more
accurate CNV calls.

CNV detection (by WES and targeted sequencing) is primarily based on detecting
local changes in read coverage along the genome. This is based on the simple intuition
that regions with copy number gain should have increased read coverage, and regions
with copy number loss should have decreased read coverage. However, read coverage
depends not just on copy number but also on many other factors, such as GC content [6],
mappability [7], and other local sequence characteristics [8]. Therefore, read coverage
tends to fluctuate even when there is no CNV, and is especially variable in WES and
targeted sequencing data due to the biases and artifacts introduced during the targeting
and amplification steps [9-11].

Many methods are available for CNV detection in high throughput sequencing data
[9-15]; a detailed review of recent advances is in Methods. Despite much progress [16],
significant challenges still remain. Independent benchmark results from multiple studies
[9, 11, 13, 17] show that existing methods suffer from low precision and recall rates,
especially for the detection of common germline CNV signals. This is not unexpected,
since in WES and targeted sequencing data, and also to an extent in WGS data, the
technical background bias for each genomic target varies across samples, leading to false
positives and negatives if not properly removed. To remove this technical background,
recent methods have relied on low-dimensional linear factor models to capture the
background bias [9, 10], which tend to control false positives. Yet, these low-dimensional
linear factor models also tend to remove common CNVs that correlate with the estimated
factors. In this paper, we show that this issue also affects the detection of somatic CNVs
in cancer genomes, where CNVs that are recurrent across multiple cancer samples can
be accidentally removed in the normalization step. Due to these limitations, current
genetic studies using WES and targeted sequencing data have focused mostly on single
nucleotide variations and, at best, rare CNVs [18-20].

Here we propose CODEX2 for full-spectrum CNV detection in high-throughput
sequencing data. By full-spectrum, we mean sensitive detection of both common and rare
CNVs. CODEX2 can be applied to two scenarios: the case-control scenario where the
goal is to detect CNVs that are enriched in the case samples (Figure 1A), and the scenario

where control samples are not available and the goal is simply to profile all CNVs in all

samples (Figure 1B). CODEX2 is evaluated in three ways. First, we reanalyze the WES

data of the HapMap samples from the 1000 Genomes Project [2], where matched

microarrays and experimental validation [21-23] are used to assess performance. Results

here show that CODEX2 significantly improve both sensitivity and specificity over existing

methods, especially for common CNVs. Next, we apply CODEX2 to targeted sequencing

data of melanoma cancer cell lines and successfully identify recurrent CNVs. We show

that the recurrence rates that are highly concordant with those obtained from a separate

cohort studied by the Cancer Genome Atlas (TCGA) [1]. Finally, we perform extensive

simulations to benchmark existing methods and to explore how key variables, such as

population frequency and CNV length, influence performance. CODEX2 is compiled as

an open-source R-package available at https://github.com/yuchaojiang/CODEX2.

Results

Methods overview

Figure 1 illustrates the two experimental designs where CODEX2 can be applied: The

case-control design where a group of negative control samples are available and the goal

is to detect CNVs present disproportionately in the case samples (Figure 1A), and the

design with no negative control samples, such as the Exome Aggregation Consortium,

where the goal is to detect all CNVs present in all samples (Figure 1B). The key innovation

in CODEX2 is the construction and usage of *negative control genome regions* in a

genome-wide latent factor model for sample- and position-specific background correction,

and the utilization of *negative control samples*, under a case-control design, to further

improve background bias estimation under this model. The negative control genome

regions defined by CODEX2 are regions that do not harbor *common* CNVs, but are still

allowed to harbor rare CNVs, and can be constructed from existing studies or learned

from data.

Figure 2 illustrates how a CODEX2 normalization works, and how it differs from

CODEX and SVD-based normalization methods such as XHMM [10]. For simplicity, we

assume that the background bias can be captured by a 1-dimensional latent factor, which

we call the "latent batch effect". Against this background, let's assume there are two

CNVs: Region A, where the carrier status (the vector indicating whether each sample is a carrier) is correlated with the underlying latent batch, and region B, where the carrier status is uncorrelated with the latent batch. The signal for these two CNV regions is obscured by the background batch effect in the observed data. In a standard SVD or CODEX normalization, which does not make use of negative controls, all samples and all genomic regions are used in the estimation of the latent background model, resulting in contamination of background estimates by the CNV signal. The contamination is especially severe for CNV A, which is correlated with the latent batch. For CODEX2, in scenario where negative controls are available, only the negative control samples are used to fit the latent factor model, which is then used to predict the background bias of the rest of the samples. In scenario where negative control samples are not available but negative control regions are identified, the latent factor model is fitted only using the negative control regions, and then used to "fill in" the background bias for the rest of the regions. This way, we avoid the contamination of the background estimates by the CNV signal, thus attaining better separation of signal from noise, as can be seen from the histograms of the normalized z-scores. More details are given in Methods.

CODEX2 estimates a separate background factor for each genomic target/region in each sample, which can then be used to normalize the observed coverage and detect CNV regions using the recursive Poisson-likelihood segmentation algorithm in Jiang et al. [11].

Analysis of WES data from the 1000 Genomes Project

We first evaluate CODEX2 by reanalyzing a publicly available WES data set from the 1000 Genomes Project [2], which contains 90 healthy individuals. 40 are Utah residents with northern and western European ancestry; 20 are Japanese from Tokyo; 26 are Yoruba people from Ibadan. Gender is well balanced with 44 males and 46 females. All samples have CNV profiles from three previous microarray studies with experimental validations [21-23]. Please refer to Jiang et al. [11] for more details on the sample input and the microarray studies.

To assess performance of CODEX2 and to benchmark, we use the experimentally validated CNVs from these three previous studies [21-23] as gold standards. Specifically,

we adopt a stringent quality control procedure (i.e., the reported CNV must overlap with
at least 2 and at most 20 exons, have less than 5% NA rate across all samples, and have
at most three copy number states). These 'gold-standard' CNVs are categorized as
common if they are present in more than 10% of the samples, and rare otherwise. Using
this 'validation set', we are able to assess the performance of XHMM [10], EXCAVATOR
[13], CODEX [11], and CODEX2 on detecting common and rare CNVs. Figure 3 shows
the precision and recall rates across the four benchmarked methods, using the CNVs
validated by each of the three studies [21-23] as ground truth. The grey lines are the
contours of the F-measure, defined as the harmonic mean of precision and recall. XHMM,
which is designed for detection of rare CNVs, lacks sensitivity to common CNVs, so does
EXCAVATOR. CODEX detects proportionately more common CNVs but still lacks
sensitivity. The best of the three existing methods achieve less than 40% recall rate for
common CNVs. CODEX2 achieves a recall rate of 87.6%, 57.2%, and 83.1% in the three
validation sets, respectively, while simultaneously making substantial improvements to
specificity. Across all 3 validation sets, CODEX2 achieves good performance for both
common and rare CNVs, with significant improvement in precision and recall for common
CNV detection.
154

Analysis of targeted sequencing data of melanoma cases and controls
We further apply CODEX2 to a cohort study of melanoma from Garman et al.
(unpublished) including 334 cases (untreated human melanoma cell lines, patient-derived
xenografts, and tumors) and 16 controls. Samples are sequenced on a custom capture
panel of 108 genes, which have been previously implicated in tumorigenesis of melanoma.
For almost all tumor suppressor genes, the entire gene region (exons and introns) were
sequenced to facilitate CNV calling; for oncogenes, only exons were sequenced. For
cases where the full gene is captured and sequenced, we separate the gene region into
consecutive windows of 500 base pairs. This results in a panel of 1398 targets across
350 samples.
We apply CODEX2 to this data set and compare against CODEX. The number of
Poisson latent factors in the background model is determined by BIC for both programs.
The use of negative controls in estimating its background model allows CODEX2 to be

more robust to model tuning: For CODEX2, the number of latent factors has minimal
effect on normalization and more generally on CNV detection, since only the normal
samples are used to estimate the bias coefficient for each exon (Supplementary Table 1).
In comparison, for CODEX, the number of CNV events reduces as the number of latent
factors increases (Supplementary Table 1). Since the 108 genes are sparsely scattered
across the genome, segmentation is performed within each gene separately. Furthermore,
due to clonal heterogeneity and normal cell contamination, copy numbers may not be
integers, and are assumed to be continuous and fractional to represent attenuated mean
estimates of the genome mixtures. We categorize a CNV event to be high gain, gain,
diploid, one-copy deletion, and two-copy deletion, if the profiled copy number is above
3.3, between 2.3 and 3.3, between 1.7 and 2.3, between 0.7 and 1.7, and below 0.7,
respectively. Figure 4 shows the heatmaps of the segmentation results by CODEX and
CODEX2. Each row corresponds to a sample, with the first 16 samples towards the
bottom corresponding to the normal controls; each column corresponds to a target in the
gene panel. In melanoma, somatic deletions of tumor suppressors (e.g., *PTEN*) and
duplications of oncogenes (e.g., *BRAF*) are known to have high incidence rates [1]. From
visual inspection of the heatmaps in Figure 4, we see that CODEX2 successfully retains
these expected recurrent deletions and duplications, while CODEX, which does not make
use of the negative control samples in fitting the background model, misinterprets the
recurrent signals as a background latent factor.

To rigorously evaluate CODEX2's accuracy on this data, we compare the
frequencies of the profiled gains and losses, that is, the proportion of samples in which a
call is made, with frequencies from an independent melanoma patient cohort in TCGA [1].
Specifically, for each gene target, we plot in Figure 5 the proportion of samples carrying
a deletion (or duplication) in TCGA, versus this corresponding proportion in our current
data set. CODEX2 achieves much higher concordance with TCGA results, with overall
correlation across genes reaching 0.842 for deletions and 0.853 for gains, as compared
to CODEX (correlation = 0.52 for deletions and 0.049 for gains). CODEX2 detects in
these cell line samples a higher frequency of *BRAF* amplification and *CDKN2A* loss, as
compared to the frozen-tissue derived TCGA results, which is not surprising due to the
relative *in vitro* growth advantage of cells carrying these mutations. Based on the results

199 by CODEX2, Garman et al. (unpublished) further separate the cohort based on cancer

200 subtypes and clinicopathological characteristics (responses to targeted and/or

201 immunotherapy) and investigate the differences in mutational profiles between groups.

202 The accurate profiling of CNVs in this data set enables unbiased downstream analysis.

204 ***Performance assessment via spike-in studies***

205 To understand how variables such as CNV length and population frequency affect the

206 sensitivity of CODEX, CODEX2, and methods based on singular value decomposition

207 (SVD, such as XHMM and CoNIFER), we conduct *in silico* spike-in studies. We start with

208 the exon read depth data from chromosome 16 to 22 in the 90 samples we analyzed from

209 the 1000 Genomes Project, and apply filtering to remove putative existing CNVs. We then

210 add, to the background count matrix under the null, heterozygous CNV signals of varying

211 length, frequency, and degree of correlation with the first latent factor in the background

212 model. See details of simulation setup in Methods.

213  As an illustration, Figure 6 shows a small subset of the CNV regions in the spike-

214 in data with the ground truth, the post-normalization heatmap, and the CNV assignments

215 across multiple methods, with the "null" regions containing no CNVs removed for easier

216 visualization. The histograms in Figure 6 show the distribution of the normalized z-scores,

217 with exons that harbor CNVs in red and exons within diploid regions in grey. We see that

218 CODEX2 achieves clear separation of the deletions and diploids with the distributions

219 centered on the expected values, $\log{(1/2)}$. The segmentations by CODEX and XHMM

220 contain false negatives as well as false positives, especially in regions where common

221 CNV signals reside, while improved normalization by CODEX2 allows almost perfect

222 segmentation. Supplementary Figure 3 further shows the true latent background

223 parameters (estimated using raw read depth without spike-in, which represents the null

224 model that would be unobservable in a real data scenario) and the estimated parameters

225 obtained by CODEX and CODEX2 on the "observed data" containing added CNVs. Our

226 results show that while the sample loadings $\{h_1, h_2, h_3\}$ are consistent between CODEX,

227 CODEX2, and the ground truth, the exon-specific factors $\{g_1, g_2, g_3\}$ estimated by

228 CODEX are biased due to the inclusion of the mean CNV signals, reflecting the same

trend in Supplementary Figure 2. CODEX2 corrects this bias through the use of the
mixture model.

We systematically compare the performance of CODEX2 against existing methods
by spiking in CNVs of length 5, 10, 20, and 40 exons with population frequency $p \in$
$\{5\%, 10\%, ... , 95\%\}$, repeating each simulation run 20 times. The precision and recall rates
achieved by each method are shown in Figure 7. The plots show how two variables:
population frequency and degree of correlation with batch effect, impact the accuracy of
methods. The results show that CODEX and SVD-based methods are sensitive to both
variables, while CODEX2 maintains high accuracy across all frequencies and all degrees
of correlation. CODEX2 has nearly perfect performance, while CODEX and SVD-based
methods suffer from low sensitivity and specificity, especially for common CNVs with
frequencies around 50%. We also investigate the effect of CNV length on performance
and show that CODEX and SVD-based methods have lower sensitivity and specificity for
longer CNVs, as compared to CODEX2 (Supplementary Figure 4).

We further study the relationship between CNV carrier status and batch effects—
44 and 46 samples are sequenced by the Baylor College of Medicine and the Washington
University Genome Sequencing Center respectively—and show that when they are highly
correlated, CODEX suffers from low sensitivity, while CODEX2 is able to recover the CNV
signals from the batch effect (Figure 7). Detailed results from an example run are shown
in Supplementary Figure 5, where the spiked-in CNVs are highly correlated with the batch
effect (i.e., most of the carriers are from one of the sequencing centers). CODEX
estimates the latent factors assuming all exons are null, with the fitted regression line
lying between the carriers and non-carriers, resulting in low sensitivity for true deletions
in carriers and false positives as duplications in non-carriers. CODEX2, on the other hand,
estimates the exon-specific latent factors in common CNV regions using the proposed
EM algorithm and successfully separates the carriers from the non-carriers, which leads
to clean down-stream segmentation. Here we show that normalization is of first-order
effect.

Methods

Multiple efforts have been made to recover CNV signals from experimental noise.
VarScan2 [12], ExomeDepth [14], and ExomeCNV [15] control for baseline fluctuations
in read coverage by relying on matched normal samples or building an optimized
reference set. EXCAVATOR [13] adopts a median normalization approach for bias
removal. It was soon realized that the magnitudes of the various sources of bias are
sample-specific, and thus cannot be completely removed by normalizing to control
samples or reference sets. This motivated CoNIFER [9] and XHMM [10] to adopt SVD to
estimate sample-specific backgrounds, which can be more effective. SVD is, however,
designed for capturing linear biases in continuous-valued observations. GC content has
been shown to have a sample-specific, non-linear bias in sequencing data. Furthermore,
read counts are not fit well by Gaussian models, even after transformation, due to their
fluctuation over a very wide range. Our previous work, CODEX [11], adopts a Poisson
latent factor model for count-based sequencing data and estimates a sample-specific
background for each genomic position that incorporates nonlinear biases due to GC
content, target-specific capture and amplification efficiency, and low-dimensional latent
systemic artifacts.

We will start by giving an overview of the SVD-based methods by CoNIFER [9]
and XHMM [10] and the Poisson latent factor model by CODEX [11]. We will discuss the
limitations of existing models and the reason why they lack sensitivity for common CNVs.
We will then describe the model for CODEX2, leaving algorithmic details to the
Supplements.

Existing methods

Denote Y as a $n \times m$ matrix of raw read depth, where Y_{ij} corresponds to the read depth
for exon $i \in \{1, \dots, n\}$ in sample $j \in \{1, \dots, m\}$. SVD-based methods CoNIFER [9] and
XHMM [10] remove the strongest K SVD components,

$$Y^* = Y - U_K D_K V_K^T,$$

where U_K and V_K correspond to the top K left and right singular vectors, respectively, and
D_K corresponds to the diagonal matrix of the K largest singular values. Each column of
Y^* is column-standardized. The genome is then segmented by hidden Markov model
(HMM) into 'diploid', 'deletion', or 'duplication' states.

This paper extends CODEX [11], which improves upon SVD-based approaches in

several ways: CODEX adopts a Poisson model that more accurately models count data,

and importantly, it explicitly models observable and measurable sources of bias, such as

GC content and exon length, in addition to unmeasurable biases, due to unanticipated

experimental variables, in the form of latent factors. In particular, GC content bias exhibits

nonlinear patterns of variation across samples [6, 11], and thus CODEX uses a non-linear

sample-specific function instead of a low-rank linear factor to capture this bias. Since an

understanding of the CODEX model is integral to our ensuing discussion, we review it

here. CODEX assumes that

299
$$Y_{ij} \sim \text{Poisson}(\lambda_{ij}),$$

300
$$\lambda_{ij} = N_j f_j(GC_i)\beta_i \exp\left(\sum_{k=1}^{K} g_{ik} h_{jk}\right),$$

where N_j is the total number of reads in sample j, $f_j(\cdot)$ is the GC content bias function for

sample j, GC_i is the GC percentage of exon i, β_i is an exon-specific factor capturing

multiplicative effects due to features such as exon length, and $\boldsymbol{g}_k = \{g_{1k}, \ldots, g_{nk}\}$, $\boldsymbol{h}_k =$

$\{h_{1k}, \ldots, h_{mk}\}$ are the kth ($1 \leq k \leq K$) Poisson latent factors. The Poisson latent factors

form a low-dimensional background model to capture unanticipated experimental

variables, similar to the singular vectors in SVD-based normalization models [9, 10].

CODEX uses maximum likelihood to estimate the parameters of the null model, where $\boldsymbol{g}$

and $\boldsymbol{h}$ are assumed to be orthogonal to ensure identifiability (see Supplementary

Algorithm 1 for details). For the remaining details on model selection, parameter

estimation, and genome segmentation, see Jiang et al. [11].

These SVD- and factor-based methods, so far, all lack sensitivity for common

CNVs. This is because common CNVs bias the estimation of the low-dimensional linear

factors ($\boldsymbol{g}_k$ and $\boldsymbol{h}_k$ in CODEX's model and $\boldsymbol{U}_k$, $\boldsymbol{V}_k$ in SVD-based algorithms), which, in

CNV regions, capture part of the CNV signal. Therefore, subsequent removal of these

factors also removes the signal for the CNVs. Supplementary Figure 2 shows a toy

example illustrating this issue, focusing on one exon i^* and assuming that $K = 1$. For this

exon, CNV signals are *in silico* added at six population frequencies, creating six scenarios.

For each scenario, simulated read counts $\boldsymbol{Y}_i = \{Y_{i1}, \ldots, Y_{im}\}$ are plotted against the sample

factors $\boldsymbol{h}_1 = \{h_{11}, \ldots, h_{m1}\}$. The samples that carry the CNV are shown in red, the rest are

shown in black. In each iteration of CODEX, Poisson log-linear regression is performed

for Y_i on h_1 to get g_{i1}, the 'loading' for exon i. CODEX estimates g_{i1} assuming that the

great majority of the samples are 'nulls', that is, they don't carry CNVs, resulting in

estimated background values shown in green. Ideally, the background curve should be fit

to the control samples, the true 'nulls', as shown in blue. Yet in real data we don't know

which are the true carriers of this CNV, and the background curve is thus contaminated

with signal, lying between the carriers and the non-carriers. The higher the incident rate

of the CNV, the higher the contamination of the background by signal, and the closer the

fitted green curve to the carriers rather than the non-carriers. This, as a result, leads to

low sensitivity in detecting the true CNV carriers. The effect of population frequency on

detection sensitivity by CODEX and SVD-based algorithms is also explored by simulation

shown in Figure 6 and Figure 7.

Full-spectrum CNV detection

Figure 1 gives an overview of the two scenarios of CODEX2. To describe CODEX2, we

first consider the simpler scenario where negative control samples are available. Without

loss of generality, we consider a cohort comprised of both tumor and normal samples, the

normal samples may not be matched to the tumor samples. Our goal is to identify CNVs

present in the cancer samples but not in the normal samples. Duplications of oncogenes

and deletions of tumor suppressors are commonly seen in cancer samples and have been

reported to be associated with cancer. It is therefore crucial to detect somatic CNVs

recurrent only in cancer samples with high sensitivity and specificity. Denote J_c as the set

of indices of the normal samples, which serve as negative control. Assuming that the

normal samples are copy-number-neutral, the negative control samples are used by

CODEX2 to estimate the exon-specific bias $\boldsymbol{\beta}$ and latent factors $\boldsymbol{g}$ to avoid attenuating

and removing common CNV signals. Poisson regression is then to each cancer sample

to obtain the sample loadings $\boldsymbol{h}$. The sample-specific background values are then

computed using $\boldsymbol{\beta}, \boldsymbol{g}, \boldsymbol{h}$ and used in Poisson likelihood segmentation to identify CNVs.

Refer to Supplementary Algorithm 2 for the detailed estimation procedure.

Now let's consider the scenario where negative control samples are not available.

We denote I^* as a set of indices of the exons that harbor highly recurrent CNVs, the

compliment of which are the indices of exons within the negative control regions. The set

$\boldsymbol{I}^*$ can be obtained based on prior knowledge (e.g., common deletions in tumor

suppressors), from existing database (e.g., the Database of Genomic Variants), or

empirically from a first-pass CODEX run. That is, if an exon lies within a common CNV

region, CODEX will return a high standard deviation of the normalized z-scores across all

samples for this exon – Supplementary Figure 2 shows that for a common CNV, the

estimated null will be biased towards the alternative, which has high incidence rate. Figure

1B shows an example on identifying germline CNVs from a population of samples (e.g.,

healthy individuals from the 1000 Genomes Project). For step 1 in Supplementary

Algorithm 2, we no longer have a set of controls samples to directly estimate the exon-

specific parameters. We propose an expectation-maximization (EM) algorithm embedded

in our iterative parameter estimation procedure, where the missing data is the carrier

status of the samples. Specifically, for each exon $i \in \boldsymbol{I}^*$,

$$Y_{i^*j} \sim \text{Poisson}(\lambda_{i^*j}),$$

$$\log(\lambda_{i^*j}) = \log(N_j) + \log(f_j(GC_{i^*})) + \log(\beta_{i^*}) + \sum_{k=1}^{K} g_{i^*k} h_{jk} + \alpha_{i^*j},$$

where

$$\alpha_{i^*j} = \begin{cases} \mu_{i^*} & \text{with probability } \pi_{i^*}, \\ 0 & \text{with probability } 1 - \pi_{i^*}. \end{cases}$$

π_{i^*} is the incident rate for the CNV that span exon i^*, and μ_{i^*} is the deviation from the null

on the log scale, which can be either pre-fixed (e.g., $\log(1/2)$ for heterozygous deletion)

or estimated by CODEX2. For simplicity, here we show the case where there is only one

type of CNV event within the carriers. This can be easily extended to multiple subgroups

with a model selection metric, which is enabled in the CODEX2 package. $\boldsymbol{N}$, $\boldsymbol{f}(\boldsymbol{GC})$, and

$\boldsymbol{h}$ can be using negative control regions shown in Supplementary Algorithm 3 step 1 and

2. We adopt an EM algorithm to estimate the unknown parameters $\Theta =$

$\{\beta_{i^*}, g_{i^*1}, \dots, g_{i^*K}, \pi_{i^*}, \mu_{i^*} | i^* \in \boldsymbol{I}^*\}$ with missing data:

$$Z_{i^*j} = \begin{cases} 1 & \text{if sample } j \text{ has CNV spanning exon } i^*, \\ 0 & \text{otherwise.} \end{cases}$$

Refer to Supplementary Algorithm 3 for implementation details.

CODEX2 offers the choice of Akaike information criterion (AIC), Bayesian

information criterion (BIC), and variance reduction to determine the optimal number of

latent factors. In CODEX and SVD-based methods (XHMM and CoNIFER), the number

of latent factors is a critical model tuning parameter that affects normalization and

segmentation results. It is often not clear whether to use the AIC, BIC, or simple visual

examination of the scree plot, and this arbitrariness plagues all methods that rely on SVD,

PCA, or factor models. By using negative controls to guide the estimation of the

background model, CODEX2 is less sensitive to the number of latent factors

(Supplementary Table 1), thus giving results that are easier to reproduce.

387   For segmentation, CODEX2 adopts the same Poisson likelihood ratio based

approach as CODEX. Please refer to Jiang et al. [11] for details. For targeted sequencing,

where a smaller pre-selected panel of targets are sequenced, the normalization model is

exactly the same; the segmentation is performed within each gene separately. For WGS,

refer to Zhou et al. (https://doi.org/10.1101/172700) for details.

Simulation setup

We start with the exonic read depth data of chromosome 16 to 22 from the 90 samples

we analyzed from the 1000 Genomes Project, and apply filtering to remove putative

existing CNVs. Specifically, the filtering step removes all exons that: (i) are called to

harbor CNV events by XHMM, EXCAVATOR, CODEX, or CODEX2, (ii) overlap with

duplication and deletion reported in the Database of Genomic Variants, (iii) don't pass

quality control procedure by CODEX (median coverage between 40 and 4000, length

between 30 and 2000 base pairs, mappability less than 0.95, GC content between 30%

and 70%), (iv) have standard deviation of normalized z-scores across samples above 0.3,

or maximum of normalized z-scores above 0.8, or minimum normalized z-scores below -

0.8 across all samples. This way we are left with 4035 'null' exons that are CNV-free

across 90 samples. Treating this filtered count matrix as background, we fit the

background model of CODEX, with the estimated parameters as ground truth. The

optimal number of latent factors is 3 by AIC, BIC and variance reduction (Supplementary

Figure 3) and is kept the same for subsequent analysis for CODEX2, CODEX, and SVD-

based method. We then add, to this background count matrix, heterozygous CNV signals

of varying length, frequency, and degree of correlation with the first latent factor in the

background model. In more detail, we spike in heterozygous deletions, of varying lengths

and population frequencies, by reducing the raw depth of coverage for exons spanned by

the CNV from y to $y \times c/2$, where c is sampled from a normal distribution with mean 1 and

standard deviation 0.1. Note that heterozygous deletions with frequency p in the

population have exactly the same detection accuracy as duplications with frequency $1 -$

p, since all copy number events are defined in reference to a population average.

Discussion and conclusions

A limitation shared by all existing CNV detection methods, highlighted by multiple

independent benchmarking studies, is the lack sensitivity for common variants. Similarly,

in our experience applying CODEX [11] to WES and targeted sequencing of tumor

samples, we easily detect sporadic mutations but miss the highly recurrent mutations. To

meet the widespread demand for improved CNV detection, we develop in this paper a

new method, CODEX2, to remove technical noise and improve CNV signal-to-noise ratio

for all sequencing platforms including WES and targeted sequencing. CODEX2 builds on

our existing method CODEX [11] with a significant improvement of sensitivity for common

variants, thus allowing full-spectrum CNV detection. CODEX2 can be applied to two

scenarios: the case-control scenario where the goal is to detect CNVs that are enriched

in the case samples, and the scenario where control samples are not available and the

goal is simply to profile all CNVs.

We extensively benchmark CODEX2 against existing methods in three ways. In

the first evaluation, we reanalyze the WES of the HapMap samples from the 1000

Genomes Project, where a set of experimentally validated CNV calls from microarrays

and other sources are used to assess performance. Results here show that CODEX2

markedly improve both sensitivity and specificity over existing methods. The improvement

for common variants is the most substantial, from 40% recall rate to >80% recall rate

according to two out of the three validation sets used, while simultaneously improving

precision from 60% to 90%. In the second evaluation, we apply CODEX2 to targeted

sequencing data of melanoma cancer cell lines, where CODEX2 detects CNVs with

recurrence rates that are highly concordant with those obtained from TCGA. Finally, we

perform extensive simulations benchmarking existing methods and elucidating how key

variables, such as population frequency, influence detection sensitivity. In combination,

these results establish the improved accuracy of CODEX2 over existing state-of-the-art
approaches, and the utility of the software under varying study designs.

Risso et al. [24] propose remove unwanted variation (RUV) for normalizing RNA
sequencing data and detecting differential expression, which adopts factor analysis based
on sets of control genes or samples. CODEX2 resembles RUV but comes with additional
distinguishing features. First, RUV is designed for a case-control setting to identify
differentially expressed genes whereas CODEX2 can be applied with and without
negative control samples. Second, when estimating the latent factors that correspond to
the control genes or samples, RUV adopts SVD with Gaussian assumption, while
CODEX2 is completely off-the-shelf with Poisson generalized linear modeling.
Furthermore, CODEX2 directly models the GC content bias, which cannot be fully
captured by a linear principal component [6, 11]. CODEX also adjusts for library size
factor and exonic lengths, all of which can be directly quantified/modeled.

CODEX2 normalizes the read depth data for CNV detection via a Poisson latent
factor model, which can be well adapted to other settings within the genomics domain.
Lee et al. [25] applies this to the non-normalized microRNA sequencing data. Chen et al.
[26] estimates allele-specific copy number under tumor-normal setting using the Poisson
latent factor model to remove biases and artifacts that cannot be fully captured by
comparing to the normal.

In this paper, we show application results of CODEX2 to WES and targeted
sequencing data. For WGS, user-defined consecutive bins can be treated as 'targets' in
the WES setting, with normalization and segmentation procedures carried out in the same
fashion. Method based on this has been integrated in a pipeline to detect CNV using both
sequencing and microarray data (Zhou et al., https://doi.org/10.1101/172700). Notably,
exome sequencing with its low cost and fast turnover is still being preferred as the method
of choice in large-scale genomic studies, where the priority goal is to identify variants
within protein coding regions. The sequencing capacity has also increased exponentially
over the past few years. CODEX2 is currently being applied to 12,000 blood WES
samples in the Penn Medicine BioBank and over 10,000 WES samples in the Alzheimer's
Disease Sequencing Project. This tremendous amount of data opens up great
opportunities and yet at the same time cautions should be made with regard to running

efficiency and method scalability. CODEX2 processes each chromosome within each batch separately and can thus be highly parallelized. With increasing sequencing capacity, and increasing need to profile CNVs as a non-negligible source of genetic variation, we believe that CODEX2 can be a useful tool for the genetics and genomics community.

Abbreviations

Copy number variation: CNV, whole-genome sequencing: WGS, whole-exome sequencing: WES, singular value decomposition (SVD), the Cancer Genome Atlas (TCGA), Akaike information criterion (AIC), Bayesian information criterion (BIC), expectation-maximization (EM), remove unwanted variation (RUV).

Declarations

Ethics Approval and consent to participate

Not applicable.

Consent for publication

Not applicable.

Availability of data and material

CODEX2 is an open-source R package available at https://github.com/yuchaojiang/CODEX2 with license GPL-2.0.

Competing interests

The authors declare no conflict of interest.

Funding

This work was supported by the National Institutes of Health (NIH) grant R01 HG006137 to NRZ and P01 CA142538 to YJ.

Authors' contributions

NRZ initiated and envisioned the study. YJ and NRZ formulated the model. YJ developed

and implemented the algorithm. YJ, KLN, and NRZ conducted the analysis. YJ and NRZ

wrote the manuscript. All authors read and approved the final manuscript.

Acknowledgements

We thank Bradley Garman, Ioannis N. Anastopoulos, and Bradley Wubbenhorst for

providing the case-control melanoma dataset and Xiaoqi Geng, Xiangwei Zhong, and Dr.

Jingshu Wang for helpful comments and discussions.

References

1.   Cancer Genome Atlas N: **Genomic Classification of Cutaneous Melanoma.** *Cell* 2015, **161:**1681-
1696.
2.   Sudmant PH, Rausch T, Gardner EJ, Handsaker RE, Abyzov A, Huddleston J, Zhang Y, Ye K, Jun G,
Hsi-Yang Fritz M, et al: **An integrated map of structural variation in 2,504 human genomes.**
Nature 2015, **526:**75-81.
3.   Harismendy O, Schwab RB, Bao L, Olson J, Rozenzhak S, Kotsopoulos SK, Pond S, Crain B, Chee MS,
Messer K, et al: **Detection of low prevalence somatic mutations in solid tumors with ultra-deep**
targeted sequencing. *Genome Biol* 2011, **12:**R124.
4.   Wagle N, Berger MF, Davis MJ, Blumenstiel B, Defelice M, Pochanard P, Ducar M, Van Hummelen
P, Macconaill LE, Hahn WC, et al: **High-throughput detection of actionable genomic alterations**
in clinical tumor samples by targeted, massively parallel sequencing. *Cancer Discov* 2012, **2:**82-
93.
5.   O'Roak BJ, Vives L, Fu W, Egertson JD, Stanaway IB, Phelps IG, Carvill G, Kumar A, Lee C, Ankenman
K, et al: **Multiplex targeted sequencing identifies recurrently mutated genes in autism spectrum**
disorders. *Science* 2012, **338:**1619-1622.
6.   Benjamini Y, Speed TP: **Summarizing and correcting the GC content bias in high-throughput**
sequencing. *Nucleic Acids Res* 2012, **40:**e72.
7.   Sims D, Sudbery I, Ilott NE, Heger A, Ponting CP: **Sequencing depth and coverage: key**
considerations in genomic analyses. *Nat Rev Genet* 2014, **15:**121-132.
8.   Teo SM, Pawitan Y, Ku CS, Chia KS, Salim A: **Statistical challenges associated with detecting copy**
number variations with next-generation sequencing. *Bioinformatics* 2012, **28:**2711-2718.
9.   Krumm N, Sudmant PH, Ko A, O'Roak BJ, Malig M, Coe BP, Project NES, Quinlan AR, Nickerson DA,
Eichler EE: **Copy number variation detection and genotyping from exome sequence data.**
Genome Res 2012, **22:**1525-1532.
10. Fromer M, Moran JL, Chambert K, Banks E, Bergen SE, Ruderfer DM, Handsaker RE, McCarroll SA,
O'Donovan MC, Owen MJ, et al: **Discovery and statistical genotyping of copy-number variation**
from whole-exome sequencing depth. *Am J Hum Genet* 2012, **91:**597-607.
11. Jiang Y, Oldridge DA, Diskin SJ, Zhang NR: **CODEX: a normalization and copy number variation**
detection method for whole exome sequencing. *Nucleic Acids Res* 2015, **43:**e39.
12. Koboldt DC, Zhang Q, Larson DE, Shen D, McLellan MD, Lin L, Miller CA, Mardis ER, Ding L, Wilson
RK: **VarScan 2: somatic mutation and copy number alteration discovery in cancer by exome**
sequencing. *Genome Res* 2012, **22:**568-576.

13. Magi A, Tattini L, Cifola I, D'Aurizio R, Benelli M, Mangano E, Battaglia C, Bonora E, Kurg A, Seri M,
et al: **EXCAVATOR: detecting copy number variants from whole-exome sequencing data.**
Genome Biol 2013, **14:**R120.
14. Plagnol V, Curtis J, Epstein M, Mok KY, Stebbings E, Grigoriadou S, Wood NW, Hambleton S, Burns
SO, Thrasher AJ, et al: **A robust model for read count data in exome sequencing experiments**
and implications for copy number variant calling. *Bioinformatics* 2012, **28:**2747-2754.
15. Sathirapongsasuti JF, Lee H, Horst BA, Brunner G, Cochran AJ, Binder S, Quackenbush J, Nelson SF:
Exome sequencing-based copy-number variation and loss of heterozygosity detection:
ExomeCNV. *Bioinformatics* 2011, **27:**2648-2654.
16. Tattini L, D'Aurizio R, Magi A: **Detection of Genomic Structural Variants from Next-Generation**
Sequencing Data. *Front Bioeng Biotechnol* 2015, **3:**92.
17. D'Aurizio R, Pippucci T, Tattini L, Giusti B, Pellegrini M, Magi A: **Enhanced copy number variants**
detection from whole-exome sequencing data using EXCAVATOR2. *Nucleic Acids Res* 2016,
44:e154.
18. Sanders SJ, Murtha MT, Gupta AR, Murdoch JD, Raubeson MJ, Willsey AJ, Ercan-Sencicek AG,
DiLullo NM, Parikshak NN, Stein JL, et al: **De novo mutations revealed by whole-exome**
sequencing are strongly associated with autism. *Nature* 2012, **485:**237-241.
19. Shi H, Moriceau G, Kong X, Lee MK, Lee H, Koya RC, Ng C, Chodon T, Scolyer RA, Dahlman KB, et
al: **Melanoma whole-exome sequencing identifies (V600E)B-RAF amplification-mediated**
acquired B-RAF inhibitor resistance. *Nat Commun* 2012, **3:**724.
20. Witkiewicz AK, McMillan EA, Balaji U, Baek G, Lin WC, Mansour J, Mollaee M, Wagner KU, Koduru
P, Yopp A, et al: **Whole-exome sequencing of pancreatic cancer defines genetic diversity and**
therapeutic targets. *Nat Commun* 2015, **6:**6744.
21. McCarroll SA, Kuruvilla FG, Korn JM, Cawley S, Nemesh J, Wysoker A, Shapero MH, de Bakker PI,
Maller JB, Kirby A, et al: **Integrated detection and population-genetic analysis of SNPs and copy**
number variation. *Nat Genet* 2008, **40:**1166-1174.
22. Conrad DF, Pinto D, Redon R, Feuk L, Gokcumen O, Zhang Y, Aerts J, Andrews TD, Barnes C,
Campbell P, et al: **Origins and functional impact of copy number variation in the human genome.**
Nature 2010, **464:**704-712.
23. International HapMap C, Altshuler DM, Gibbs RA, Peltonen L, Altshuler DM, Gibbs RA, Peltonen L,
Dermitzakis E, Schaffner SF, Yu F, et al: **Integrating common and rare genetic variation in diverse**
human populations. *Nature* 2010, **467:**52-58.
24. Risso D, Ngai J, Speed TP, Dudoit S: **Normalization of RNA-seq data using factor analysis of**
control genes or samples. *Nat Biotechnol* 2014, **32:**896-902.
25. Lee S, Chugh PE, Shen H, Eberle R, Dittmer DP: **Poisson factor models with applications to non-**
normalized microRNA profiling. *Bioinformatics* 2013, **29:**1105-1111.
26. Chen H, Jiang Y, Maxwell KN, Nathanson KL, Zhang N: **Allele-specific copy number estimation by**
whole exome sequencing. *The Annals of Applied Statistics* 2017, **11:**1169-1192.

Figure legends

Figure 1. CODEX2 can be applied under two experimental designs to identify

common and rare, germline and somatic CNVs. (A) CODEX2 with negative control

samples. The goal is to recover both rare and common CNV signals present

disproportionately in the case samples. (B) CODEX2 without negative control samples.

The goal is to identify all CNVs in all samples, e.g., to detect germline CNVs in healthy
individuals without prior knowledge of disease status.

Figure 2. Outline of analysis framework with benchmark against SVD-based
methods. Results are based on *in silico* simulations where the ground truth with one-
dimensional latent factor is known. One CNV signal is correlated with batch effect; the
other is not. CODEX2 utilizes negative control samples and negative control regions and
outperforms SVD-based methods.

Figure 3. Assessment of CNV calls on WES data from the 1000 Genomes Project
by array-based methods. CNV calls by XHMM, EXCAVATOR, CODEX and CODEX2
are validated against genotyping calls from (A) HapMap 3 Consortium [23], (B) Conrad et
al. [22], and (C) McCarroll et al. [21]. Grey contours show F-measures as harmonic
means of precision and recall rates. CODEX2 has significantly improved precision and
recall for common CNVs and has the highest F-measure among all methods.

Figure 4. Heatmap of CODEX and CODEX2 normalization/segmentation results for
the melanoma cohort. Each column is one target in the gene panel; each row is one
sample, with the first 16 towards the bottom in the heatmap being normal. Profiled CNVs
are categorized as high gain, gain, diploid (null), one-copy heterozygous deletion, and
two-copy homozygous deletion based on the estimated copy numbers. Only part of the
oncogenes and tumor suppressors with greater than 30 targets are shown.

Figure 5. Assessment of profiled CNVs in the melanoma cohort with comparison
to TCGA. CNVs are separated by states: losses on the left panels and gains on the right
panel. Each dot corresponds to one gene in the targeted sequencing panel. CNV
frequencies detected by (A) CODEX and (B) CODEX2 from the melanoma cohort is
compared to the TCGA cohort with CODEX2 having drastically higher correlation.

Figure 6. Performance assessment by spike-in experiment. CNV signals are *in silico*
spiked in with increasing population frequencies. (A) Ground truth, and normalization

results by CODEX, CODEX2, and SVD based method. (B) Histogram of normalized z-

scores as $\log{(Y/\hat{\lambda})}$ in CNV (red) and diploid (grey) regions. The z-scores returned by

XHMM are on a different scale with a much wider range and significant overlap between

the null and non-null. (C) Segmentation results where CODEX2 has the highest

concordance with the ground truth among the methods being compared.

Figure 7. Assessment of precision and recall rates with different CNV frequencies

and correlations between CNV state and batch effect. CODEX2 has nearly perfect

performance compared to CODEX and XHMM. The latter two suffer from low recall and

precision rates, especially for common CNV signals that are highly correlated with the

batch effects.

Figure 1

Figure 2

Figure 3

CODEX   CODEX2

High gain   Gain   Diploid   one-copy deletion   two-copy deletion

Figure 4

Figure 5

Figure 6

Figure 7

Supplement to "CODEX2: full-spectrum copy number variation detection by high-throughput DNA sequencing"

Yuchao Jiang[*]   Katherine L Nathanson[†]   Nancy R Zhang [‡]

List of Supplementary Tables

List of Supplementary Algorithms

List of Supplementary Figures

[*]Department of Biostatistics, Gillings School of Public Health, University of North Carolina at Chapel Hill; Department of Genetics, School of Medicine, University of North Carolina at Chapel Hill. Corresponding author: (+1) 919/843-4822; yuchaoj@email.unc.edu.

[†]Department of Medicine, Division of Translational Medicine and Human Genetics, Perelman School of Medicine, University of Pennsylvania; Abramson Cancer Center, Perelman School of Medicine, University of Pennsylvania.

[‡]Department of Statistics, The Wharton School, University of Pennsylvania. Corresponding author: (+1) 215/898-8222; nzh@wharton.upenn.edu.

Supplementary Algorithm 1 Parameter estimation algorithm for CODEX.

Initialization:
$\beta^{old} = 1^n$, $g = 0^{n \times K}$, $h = 0^{m \times K}$.

Iteration:

1. For each sample j, fit a smoothing spline $Y_{\cdot j}/N_j \beta^{old} \exp(g \times h_{j\cdot}^T) \sim GC$ to get $f_j(GC)$.

2. For each exon i, update β_i as $\beta_i^{new} = \text{median}\left([Y/Nf(GC)\exp(g \times h^T)]_{i\cdot}\right)$.

3. Denote $Z = Nf(GC)\beta^{new}$. Apply SVD to row-centered $\log(Y/Z)$ to obtain the K right singular vectors and use as h^{old}.

   (a) For each i, fit Poisson log-linear regression with $Y_{i\cdot}$ as response, h^{old} as covariates, $\log(Z_{i\cdot})$ as fixed offset to obtain updated estimates as $\{g_{i1}, \cdots, g_{iK}\}$.

   (b) For each j, fit Poisson log-linear regression with $Y_{\cdot j}$ as response, g as covariates, $\log(Z_{\cdot j})$ as fixed offset to obtain updated estimates as $\{h_{j1}^{new}, \cdots, h_{jK}^{new}\}$.

   (c) Center each row of $g \times (h^{new})^T$ and apply SVD to the row-centered matrix to obtain the K right singular vectors to update h^{new}.

   (d) Repeat steps (a) to (c) with $h^{old} = h^{new}$ till convergence to obtain h, g.

4. Repeat steps 1 to 3 with $\beta^{old} = \beta^{new}$ till convergence.

Supplementary Algorithm 2 Parameter estimation algorithm for CODEX2 with negative control samples.

Let J_c be the indices of the control samples.

1. Apply CODEX to the null regions $Y_{:J_c}$ and GC using Supplementary Algorithm 1 to get an estimate of $h_{J_c:}, g, \beta$ and $f_{J_c}(GC)$.

2. For case sample $j \notin J_c$, initiate $h_{j1}^{old} = \cdots = h_{jK}^{old} = 0$.

   (a) Fit a smoothing spline $Y_{:j}/N_j\beta \exp(g \times h_{j:}^{old^T}) \sim GC$ to get $f_j(GC)$.

   (b) Denote $Z = Nf(GC)\beta$. Fit Poisson log-linear regression with $Y_{:j}$ as response, g as covariates, $\log(Z_{:j})$ as fixed offset to obtain updated estimates as $\{h_{j1}^{new}, \cdots, h_{jK}^{new}\}$.

   (c) Repeat steps (a) to (b) with $h_{j:}^{old} = h_{j:}^{new}$ till convergence to obtain $h_{j:}, f_j(GC)$.

Supplementary Algorithm 3 Parameter estimation algorithm for CODEX2 without negative control samples.

Let I^* be the indices of exons with CNVs with high population frequencies.

1. Apply CODEX to the null regions $Y_{-I^*:}$ and GC_{-I^*} using Supplementary Algorithm 1 to get an estimate of $h, g_{-I^*}, \beta_{-I^*}$ and $f(GC_{-I^*})$.

2. Use the estimated non-parametric smooth spline function to estimate the GC content bias in the non-null regions $f(GC_{I^*})$ with the corresponding GC_{I^*}.

3. For each $i^* \in I^*$, adopt an EM algorithm to estimate β_{i^*} and $\{g_{i^*1}, \cdots, g_{i^*K}\}$.

   (a) E-step:

   $$
   \begin{aligned}
   p_1 &= P\big(Y_{i^*j} \mid N_j, f_j(GC_{i^*}), Z_{i^*j} = 1, \hat{\mu}_{i^*}\big)\hat{\pi}_{i^*}, \\
   p_0 &= P\big(Y_{i^*j} \mid N_j, f_j(GC_{i^*}), Z_{i^*j} = 0, \hat{\mu}_{i^*}\big)(1 - \hat{\pi}_{i^*}), \\
   \hat{Z}_{i^*j} &= p_1/(p_1 + p_0),
   \end{aligned}
   $$

   where $\hat{\mu}_{i^*}$ and $\hat{\pi}_{i^*}$ are from the previous M-step and $P(Y_{i^*j} \mid \lambda_{i^*j})$ is the probability for Poisson distribution with λ_{i^*j} calculated based on the given parameters.

   (b) M-step:

   $$
   \hat{\pi}_{i^*} = \frac{1}{m} \sum_{j=1}^{m} \hat{Z}_{i^*j},
   $$

   where $\hat{Z}_{i^*j}$ is from the previous E-step. Run Poisson log-linear regression with $Y_{i^*:}$ as response, h and $\hat{Z}_{i^*:}$ as covariates, and $\log(N \times f(GC))_{i^*:}$ as fixed offsets to obtain estimates of $\hat{\beta}_{i^*}$ as intercept, $\{\hat{g}_{i^*1}, ..., \hat{g}_{i^*K}\}$ and $\hat{\mu}_{i^*}$ as coefficients.

Supplementary Table 1: Performance of CODEX and CODEX2 with different number of latent factors. CODEX and CODEX2 are applied to the melanoma targeted sequencing data set with the number of latent factors K ranging from 0 to 10. Correlations of the profiled losses and gains (r_{loss} and r_{gain} respectively) by CODEX and CODEX2 with those reported by TCGA, as well as the number of *BRAF* gains and *PTEN* losses out of 334 tumor samples are used as measurements. CNV profiles by CODEX2 are consistent since only the negative control samples (16 normal samples) are used to estimate the target-specific bias and artifacts. For CODEX, true CNV signals are attenuated with a large K resulting in less CNV events and lower correlations.

K	CODEX2				CODEX			
	r_{loss}	r_{gain}	*BRAF* gains	*PTEN* losses	r_{loss}	r_{gain}	*BRAF* gains	*PTEN* losses
0	0.787	0.859	288	256	0.571	0.112	170	146
1	0.840	0.841	297	230	0.589	-0.039	163	138
2	0.837	0.839	296	228	0.580	-0.003	161	133
3	0.841	0.830	296	227	0.567	0.013	160	117
4	0.837	0.839	292	229	0.581	0.034	158	113
5	0.842	0.848	302	229	0.556	0.046	158	110
6	0.845	0.845	301	229	0.546	0.033	155	108
7	0.842	0.853	298	231	0.520	0.049	142	107
8	0.838	0.859	295	237	0.453	0.027	130	97
9	0.831	0.858	299	234	0.435	0.042	128	95
10	0.835	0.859	297	237	0.442	0.039	125	98

Supplementary Figure 1: Poisson latent factor model to normalize read depth data by whole-exome and targeted sequencing. h^T is shown for illustration purpose.

Supplementary Figure 2: Parameter estimation by CODEX when the null data is mixed with alternatives with different frequencies. Here we focus on a specific exon i^* and try to estimate g_{i^*1} from Poisson generalized linear model taking h_1 as known from previous iteration.

Supplementary Figure 3: Model selection and parameter estimation in spike-in studies. (A) Number of latent factors is determined by variance reduction and BIC based on the null read depth after quality control procedures and is kept the same throughout the spike-in studies. (B-D) True underlying parameters and estimated parameters by CODEX and CODEX2. CODEX biasedly estimates the exon-specific latent factor $\{g_1, g_2, g_3\}$ for the exons, where common CNV signals are *in silico* added.

Supplementary Figure 4: Assessment of precision and recall rates with different CNV lengths. CODEX2 has nearly perfect performance compared to CODEX and SVD-based method, which suffer from low recall and precision rates for large and common CNV singals.

Supplementary Figure 5: Relationship between CNV state and batch effect. (A) The null read depth from the 1000 Genomes Project after quality control procedures show distinct batch effect between two centers, where the samples were sequenced. An example spike-in run where the CNVs are mostly added to the samples from one center. The CNV state and the batch effect are highly correlated. (B) An example of Poisson log-linear regression to estimate the exon-specific latent factor for a specific exon in a common CNV region. The vertical axis is Y (in this case the spike-in read depth) while the horizontal axis is the λ (estimated null read depth by CODEX and CODEX2). If there is no CNV, these two quantities should be approximately equal along the diagonal line. CODEX's fitted results separate the carriers and non-carriers at two sides of the diagonal line. CODEX2 adopts the EM algorithm with the non-carriers lying along the diagonal line as expected and the carriers below the diagonal line called as deletions. (C) Heatmap of the normalization results in all non-null exons across all samples. CODEX suffers from low sensitivity for detecting true deletions in carriers and false positives as deletions in non-carriers.