TITLE: Enhanced JBrowse plugins for epigenomics data visualization

AUTHORS

Brigitte T. Hofmeister[1] and Robert J. Schmitz[2]

[1] Institute of Bioinformatics, University of Georgia, Athens, GA 30602, U.S.A.

[2] Department of Genetics, University of Georgia, Athens, GA 30602, U.S.A.

CORRESPONDING AUTHOR: Brigitte T. Hofmeister, bth29393@uga.edu and Robert

J. Schmitz, schmitz@uga.edu

KEYWORDS: Epigenomics, genomics, genome browser, visualization

ABSTRACT

New sequencing techniques require new visualization strategies, as is the case for

epigenomics data such as DNA base modifications, small non-coding RNAs, and

histone modifications. We present a set of plugins for the genome browser JBrowse that

are targeted for epigenomics visualizations. Specifically, we have focused on visualizing

DNA base modifications, small non-coding RNAs, stranded read coverage, and

sequence motif density. Additionally, we present several plugins for improved user

experience such as configurable, high-quality screenshots. In visualizing epigenomics

with traditional genomics data, we see these plugins improving scientific communication

and leading to discoveries within the field of epigenomics.

BACKGROUND

As next-generation sequencing techniques for detecting and quantifying DNA nucleotide

variants, histone modifications and RNA transcripts become widely implemented, it is

imperative that graphical tools such as genome browsers are able to properly visualize

these specialized data sets. Current genome browsers such as UCSC genome browser

[1], AnnoJ [2], IGV [3], IGB [4], and JBrowse [5], have limited capability to visualize

these data sets effectively, hindering the visualization and potential discoveries with

new sequencing technologies. JBrowse is used by numerous scientific resources, such

as Phytozome [6], CoGe [7], WormBase [8], and Araport [9], because it is highly

customizable and adaptable with modular plugins [5].

Epigenomics is an emerging area of research that generates a significant amount of

specialized sequencing data which cannot be efficiently visualized using standard

genome browsers. New sequencing technologies such as whole-genome bisulfite

sequencing (WGBS) [2, 10], Tet-assisted bisulfite sequencing (TAB-seq) [11], single-

molecule real-time sequencing (SMRT) [12], chromatin immunoprecipitation sequencing

(ChIP-seq) [13], assay for transposase-accessible chromatin sequencing (ATAC-seq)

[14], RNA-seq [15–17], and small RNA-seq [18] have been instrumental in advancing

the field of epigenomics. Epigenomic data sets generated from these techniques

typically include: DNA base modifications, mRNAs, small RNAs, histone modifications

and variants, chromatin accessibility, and DNA sequence motifs. These techniques

have allowed researchers to map the epigenomic landscape at high resolution, greatly

advancing our understanding of gene regulation. DNA methylation (4-methylcytosine,

4mC; 5-methylcytosine, 5mC; 5- hydroxylmethylcytosine, 5hmC; and 6-methyladenine,

6mA) and small non-coding RNAs (smRNAs) are modifications often found in

epigenomic data sets, and function to regulate DNA repair and transcription by

localizing additional chromatin marks or inducing post-transcriptional gene regulation

[19–21].

We have developed several JBrowse plugins to address the current limitations of

visualizing epigenomics data, which include visualizing base modifications and small

RNAs as well as stranded-coverage tracks and sequence motif density. Additionally, we

have developed several plugins that add features for improved user experience with

JBrowse, including high-resolution browser screenshots. These plugins are freely

available and can be used together or independently as needed. In visualizing

epigenomics with traditional genomics data, we see these plugins improving scientific

communication and leading to discoveries within the field of epigenomics.

IMPLEMENTATION

Plugins are implemented to work with JBrowse's modular plugin system. Client-side

logic, such as visualization, fetching data, and interaction, are written in Javascript

relying on the Dojo library [22]. This includes JavaScript classes for viewing data and

storing data. Raw data files are standard in genomics, including BAM files for next-

generation sequencing reads [23] and BigWig files for quantitative coverage tracks [24].

Python scripts are included to convert output from analysis pipelines to BigWig files

needed by JBrowse. Additional styling for each plugin is provided using CSS. Wherever

possible, colorblind safe colors were used to improve accessibility.

RESULTS

Base modifications. We have developed a plugin to visualize the quantity of 4mC,

5mC, 5hmC, and 6mA at single base-pair resolution. When studying 5mC, the

modification is split into two (CG and CH; where H is any nucleotide expect G)

sequence contexts for animals or three (CG, CHG, and CHH) sequence contexts for

plants, as each context is established and/or maintained by different pathways with

different functional roles [20]. Our plugin visualizes the quantity of methylation at each

cytosine or adenine using a bar plot (Fig. 1), where values are positive or negative to

signify the DNA strand. In most genome browsers, each sequence context must be

shown as a different track (Fig. 1a). This is cumbersome when viewing multiple samples

and makes it more difficult to determine overlap between context or samples. Our plugin

is advantageous because, we color-code 4mC, 5mC, 5hmC, and 6mA sequence

contexts and display them on a single track (Fig. 1b, Additional file 1: Fig. S1). However,

focusing on a single context or modification can be important, thus our plugin offers

several filtering options including by sequence context and base modification.

Small RNAs. Currently, JBrowse represents each sequenced RNA as a single read and

is colored by sequenced strand (Fig. 2a). When analyzing smRNAs, strand alone does

not always provide sufficient information; the size (nucleotides [nt]) of smRNA and

strandedness indicate potential function [19]. For example, in plants, 21nt microRNAs

can be aligned to single strand and 24nt small interfering RNAs can be aligned to both

strands [25]. Products of RNA degradation, however, have varying sizes and align to

one strand. To improve smRNA visualization, we color-code reads by smRNA size and

retain strand information by placement of smRNAs within the track relative to the y-axis

(Fig. 2b). This plugin also includes the ability to filter the reads in a track or multiple

tracks by size, strand, and read quality.

Stranded read coverage. Quantitative coverage tracks are necessary for any

worthwhile genome browser. It is important for visualizing DNA-protein interactions via

ChIP-seq and chromatin accessibility via ATAC-seq where coverage is computed in a

strand-independent manner. However, for strand-dependent data types, such as 5mC,

small RNAs, and mRNAs, read coverage can greatly vary for opposite strands. The

default coverage tracks are unable to handle this, thus we developed a plugin which

shows stranded read coverage. For example, WGBS can have uneven coverage on

both strands which can make only one strand seem methylated (Fig. 3a).

Motif density. Sequence motifs not only have important roles for protein binding, i.e.

binding motifs, but can also impact chromatin formation [26] and recombination hotspots

[27]. When correlating the frequency of a sequence motif with another characteristic, i.e.

5mC or histone modification localization, it is preferred to visualize motif density over

larger regions compared to single base-pair resolution. To address this, we developed a

plugin which visualizes sequence motif density across the genome as a heatmap (Fig.

3b). Users can input multiple motifs in a single track and IUPAC degenerate nucleotides

are supported. We also include several options for heatmap coloring and density

computation configuration options.

Exporting browser images. One of the most difficult tasks working with any genome

browser is obtaining high-quality screenshots for presentations or publications. We have

developed a plugin for JBrowse, which allows the user to take high quality and highly

configurable screenshots without installing additional software. A dialog window allows

users to set general, output, and track-specific configuration options (Fig. 4).

Additionally, our plugin is able to create the screenshot with vector graphic objects,

which is preferred for publication-quality screenshots, without needing to change the

underlying track configuration parameters.

Customization. To improve user experience, we have developed several additional

JBrowse plugins. These plugins include: (i) Selecting or deselecting all tracks in a

category from a hierarchical track list; (ii) An easily customizable y-scale range and

location; and (iii) An option to force a track to stay in "feature" view or "histogram" view

regardless of the zoom.

CONCLUSIONS

With these plugins, we aim to improve epigenomics visualization using JBrowse, a user-

friendly genome browser familiar to the research community. All the plugins described

can be used together or independently as needed. All plugins are freely available for

download and additional customization.

AVAILABILITY AND REQUIREMENTS

Project name: Epigenomics in JBrowse

Project home page: http://github.com/bhofmei/bhofmei-jbplugins

Operating systems(s): Platform independent

Programming language: Javascript, Python

Other requirements: JBrowse 1.11.6+

License: Apache License, Version 2.0

Any restrictions to use by non-academics: none

DECLARATIONS

Ethics approval and consent to participate

Not applicable

Consent for publication

Not applicable

Availability of data and material

See Additional file 1 for availability and description of data processing for samples used

in the figures.

Competing interests

Not applicable

Funding

This work was supported by the National Institute of General Medical Sciences of the

National Institutes of Health (T32GM007103) to BTH, the National Science Foundation

(IOS-1546867) to RJS., and the Office of Research at the University of Georgia to BTH

and RJS.

Authors' contributions

183   Conceptualization and design: BTH and RJS; Implementation and testing: BTH; Writing:

184   BTH; Review and editing: RJS. All authors read and approved the final manuscript.

Acknowledgements

We would like to thank Adam Bewick, Lexiang Ji, William Jordan, and Melissa Shockey

for comments and discussions. We would like to thank Eric Lyons and Colin Diesh for

open-source software code that influenced these plugins early in development. We

would like to thank all members of the Schmitz lab for using the plugins during

development and suggesting additional features. Additionally, we would like to thank

Scott Cain and Mathew Lewsey for being early adopters.

FIGURES

Fig 1. Visualizing DNA base modifications. Top track shows gene models in gold and

transposable element models in purple. a) Viewing 5mC in three *A. thaliana* samples

without the plugin. b) Viewing 5mC in the same samples with the plugin. For all tracks,

height and direction of bar indicates methylation level and strand, respectively. Bars are

colored by 5mC sequence context.

Fig 2. Visualizing small RNAs. Top track shows gene models in gold and transposable

element models in purple. a) Viewing smRNA reads, 18 nt - 30 nt, in an *A. thaliana*

sample using the general JBrowse alignments track. Color indicates strand; red,

forward; blue, reverse. b) Viewing the same smRNA reads using the smRNA alignments

track provided by the plugin. Color indicates read length. Position above and below the

y-axis origin indicates forward and reverse strand, respectively.

Fig 3. Visualizing stranded coverage and sequence motif density. Top track shows

gene models in gold and transposable element models in purple. a) Stranded read

coverage for sample used in the methylation track. Asterisk (*) indicates uneven strand

coverage which affects the perceived methylation level. b) Dinucleotide sequence motif

density in *A. thaliana*. Darker color indicates higher density.

Fig. 4. Screenshot dialog window. The dialog window that opens when taking

screenshots with our plugin. There are numerous configuration options for general

visualization, image output, and track-specific settings. This includes exporting each

track using vector objects.

SUPPLEMENTARY FILES

Additional file 1. Supplementary figure S1 and supplementary methods. PDF.

Additional-file.pdf (103 KB)

REFERENCES

1. Kent WJ, Sugnet CW, Furey TS, Roskin KM, Pringle TH, Zahler AM et al. The human genome browser at UCSC. Genome research. 2002; 12: 996-1006.

2. Lister R, O'Malley RC, Tonti-Filippini J, Gregory BD, Berry CC, Millar AH et al. Highly integrated single-base resolution maps of the epigenome in Arabidopsis. Cell. 2008 May 2; doi:10.1016/j.cell.2008.03.029.

3. Robinson JT, Thorvaldsdóttir H, Winckler W, Guttman M, Lander ES, Getz G et al. Integrative genomics viewer. Nature biotechnology. 2011; 29: 24-26.

4. Freese NH, Norris DC, Loraine AE. Integrated genome browser: visual analytics platform for genomics. Bioinformatics. 2016 Jul 15; doi:10.1093/bioinformatics/btw069.

5. Buels R, Yao E, Diesh CM, Hayes RD, Munoz-Torres M, Helt G et al. JBrowse: a dynamic web platform for genome visualization and analysis. Genome Biol. 2016; doi:10.1186/s13059-016-0924-1.

6. Goodstein DM, Shu S, Howson R, Neupane R, Hayes RD, Fazo J et al. Phytozome: a comparative platform for green plant genomics. Nucleic Acids Res. 2012; 40: D1178-D1186.

7. Lyons E, Freeling M. How to usefully compare homologous plant genes and chromosomes as DNA sequences. Plant J. 2008 Feb; doi:10.1111/j.1365-313X.2007.03326.x.

8. Howe KL, Bolt BJ, Cain S, Chan J, Chen WJ, Davis P et al. WormBase 2016:

expanding to enable helminth genomic research. Nucleic Acids Res. 2016 Jan 04;

doi:10.1093/nar/gkv1217.

9. Krishnakumar V, Hanlon MR, Contrino S, Ferlanti ES, Karamycheva S, Kim M et

al. Araport: the Arabidopsis information portal. Nucleic Acids Res. 2015 Jan;

doi:10.1093/nar/gku1200.

10. Cokus SJ, Feng S, Zhang X, Chen Z, Merriman B, Haudenschild CD et al. Shotgun

bisulphite sequencing of the Arabidopsis genome reveals DNA methylation

patterning. Nature. 2008; 452: 215-219.

11. Yu M, Hon GC, Szulwach KE, Song C-X, Zhang L, Kim A et al. Base-resolution

analysis of 5-hydroxymethylcytosine in the mammalian genome. Cell. 2012 Jun 08;

doi:10.1016/j.cell.2012.04.027.

12. Flusberg BA, Webster DR, Lee JH, Travers KJ, Olivares EC, Clark TA et al. Direct

detection of DNA methylation during single-molecule, real-time sequencing. Nat

Methods. 2010 Jun; doi:10.1038/nmeth.1459.

13. Johnson DS, Mortazavi A, Myers RM, Wold B. Genome-wide mapping of in vivo

protein-DNA interactions. Science. 2007; 316: 1497-1502.

14. Buenrostro JD, Giresi PG, Zaba LC, Chang HY, Greenleaf WJ. Transposition of

native chromatin for fast and sensitive epigenomic profiling of open chromatin,

DNA-binding proteins and nucleosome position. Nat Methods. 2013 Dec;

doi:10.1038/nmeth.2688.

15. Nagalakshmi U, Wang Z, Waern K, Shou C, Raha D, Gerstein M et al. The

transcriptional landscape of the yeast genome defined by RNA sequencing.

Science. 2008 Jun 06; doi:10.1126/science.1158441.

16.   Cloonan N, Forrest AR, Kolle G, Gardiner BB, Faulkner GJ, Brown MK et al. Stem

cell transcriptome profiling via massive-scale mRNA sequencing. Nat Methods.

2008 Jul; doi:10.1038/nmeth.1223.

17.   Mortazavi A, Williams BA, McCue K, Schaeffer L, Wold B. Mapping and quantifying

mammalian transcriptomes by RNA-Seq. Nat Methods. 2008 Jul;

doi:10.1038/nmeth.1226.

18.   Morin RD, O'Connor MD, Griffith M, Kuchenbauer F, Delaney A, Prabhu AL et al.

Application of massively parallel sequencing to microRNA profiling and discovery

in human embryonic stem cells. Genome Res. 2008 Apr; doi:10.1101/gr.7179508.

19.   Ghildiyal M, Zamore PD. Small silencing RNAs: an expanding universe. Nat Rev

Genet. 2009 Feb; doi:10.1038/nrg2504.

20.   Law JA, Jacobsen SE. Establishing, maintaining and modifying DNA methylation

patterns in plants and animals. Nat Rev Genet. 2010 Mar; doi:10.1038/nrg2719.

21.   Marinus MG, Løbner-Olesen A. DNA Methylation. EcoSal Plus. 2014 May;

doi:10.1128/ecosalplus.ESP-0003-2013.

22.   Dojo Toolkit: Reference Guide. https://dojotoolkit.org/reference-guide/1.10/.

Accessed 15 July 2017.

23.   Li H, Handsaker B, Wysoker A, Fennell T, Ruan J, Homer N et al. The sequence

alignment/map format and SAMtools. Bioinformatics. 2009;

doi:10.1093/bioinformatics/btp352.

24. Kent WJ, Zweig AS, Barber G, Hinrichs AS, Karolchik D. BigWig and BigBed:

enabling browsing of large distributed datasets. Bioinformatics. 2010 Sep 1;

doi:10.1093/bioinformatics/btq351.

25. Finnegan EJ, Matzke MA. The small RNA world. J Cell Sci. 2003 Dec 01;

doi:10.1242/jcs.00838.

26. Segal E, Fondufe-Mittendorf Y, Chen L, Thåström A, Field Y, Moore IK et al. A

genomic code for nucleosome positioning. Nature. 2006 Aug 17;

doi:10.1038/nature04979.

27. Myers S, Freeman C, Auton A, Donnelly P, McVean G. A common sequence motif

associated with recombination hot spots and genome instability in humans. Nat

Genet. 2008 Sep; doi:10.1038/ng.213.

310