# Testing the Efforts Model of Simultaneous Interpreting:
# An ERP Study

Roman Koshkin[1], Yury Shtyrov[1,3] & Alex Ossadtchi[1,2]

1 - Centre for Cognition and Decision Making, NRU Higher School of Economics, Moscow, Russia
2 - Laboratory of Control of Complex Systems, Institute of Problems of Mechanical Engineering   Russian Academy of Sciences, St. Petersburg, Russia
3 – Center of Functionally Integrative Neuroscience, Department of Clinical Medicine, Aarhus University, Aarhus, Denmark

## Abstract

We utilized the event-related potential (ERP) technique to study neural activity associated with different levels of working memory (WM) load during simultaneous interpretation (SI) in an ecologically valid setting. The amplitude of N1 and P1 elicited by task-irrelevant tone probes were significantly modulated as a function of WM load but not the direction or interpretation. The latency of the N1 increased insignificantly with WM load. P1 latency mostly did not depend on either WM load or direction of interpretation. Larger negativity under lower WM loads suggests deeper processing of the audio stimuli, providing tentative electrophysiological evidence validating Daniel Gile's Efforts Model of SI. Relationship between the direction of interpretation and median WM load are also discussed.

## I. INTRODUCTION

Unlike in monolingual communication, in simultaneous interpreting (SI) a message in one language is perceived and processed almost concurrently with the production of an equivalent message in another language. To be able to accomplish that feat, besides high proficiency in both the source and target languages, the interpreter must possess a set of specialized skills, including exceptional language switching abilities (Proverbio, Leoni, & Zani, 2004), large working memory (WM) span (Bajo, Padilla, & Padilla, 2000), ability to manipulate WM content and understand incoming discourse while producing a rendering of an earlier portion of the source message in the target language. By its nature, SI is externally paced (Lambert, 1992; Padilla, Bajo, Cañas & Padilla, 1995), indicating the need for cognitive resource management and coping strategies (Chernov, 2004; Kim, 2005; Li, 2010; Liu, Schallert & Carroll, 2004; Mizuno, 2005; Pym, 2008).

In SI an interpreter usually begins interpreting before the speaker has finished a sentence. But the speaker does not wait to move on to the next

utterance, regardless of whether the interpreter has completed the translation of the previous chunk (cf. Chernov, 2004; Signorelli & Obler, 2013). Moreover, it may not always be possible or convenient to maintain sequential linearity of the target message relative the source. For example, interpreters often reverse the order of lists. In some language combinations, e.g. German and English, one may have to wait for the final verb to construct a target sentence in English (Goldman-Eisler, 1972). Finally, the interpreter may choose to defer translating a word until a good enough equivalent comes to mind, hoping to be able to work it into the target message later. The resulting lag — also referred to as *décalage* or *ear-voice-span (EVS)* in the interpretation studies literature — between the source and the target messages highlights the critical role of WM in the SI pipeline. WM represents a mental space within which to perform the transformations needed for a coherent and accurate target message to emerge.

Under normal circumstances, when the source message is relatively easy to understand and target equivalents are quickly and automatically retrieved from long-term memory (LTM), the interpreter maintains a comfortable décalage, accurately rendering the source message with almost no omissions. But when confronted with a long-winded, dense or obscure passage, the interpreter may be forced out of the comfort zone and temporarily increase the lag to accommodate the need for more time to process it. The lag is similar to debt in that beyond a certain point it becomes difficult to handle. In extreme cases, when the interpreter gets too far behind to speaker, performance quality may be compromised: parts of the source message may get severely distorted or go missing from the translation altogether. This happens either when the interpreter shifted much of his attention away from the current chunk *being* said to finish processing the previous one stored in WM to catch up with the speaker. In sum, large lags are most likely caused by processing difficulties.

On the other hand, when the source message overall is relatively difficult to follow (i.e. when the target message is not in the interpreter's mother tongue), the interpreter may need to allocate extra effort towards understanding. This can be done by shortening the décalage, effectively limiting the amount of information to be processed in working memory. Such a strategy may result in a more literal translation that is likely to be syntactically and grammatically deficient.

In our opinion, the above considerations are best captured by Gile's Efforts Model (Gile, 1988) which conceptualizes SI in terms of three groups or mental operations, or 'efforts': listening, production and memory. Since these efforts are mostly *non-automatic* and *concurrent*, they critically depend on and compete for the limited pool of attentional resources. A major

implication of the model is that increased processing demands in one of the efforts can only be met at the expense of another.

To our knowledge, only one study has attempted to test the Effort Model of SI (Gile, 1999). But as its author himself admitted, "it cannot be said to have led to [its] systematic testing or validation" and also suggested that "precise quantitative measurement" would help to make it more useful. To partially address this concern, in the present paper we used the ERP technique to test one particular prediction of the Efforts Model, namely that increased processing demands on the 'memory' effort means less processing capacity available to the 'listening' effort. In other words, a higher WM load would create a deficit of attention to the auditory stream. In fact, this hypothesis is quite intuitive but, to our knowledge, has never been tested experimentally in an ecologically valid setting requiring the participants to interpret continuous prose overtly. Electrophysiological evidence supporting it would suggest that interpreters' brains gate part of the auditory input to be able to properly process the information backlog and reduce the associated processing pressure.

We exploited the fact that the P1 and N1 components of the ERP waveform evoked by task-irrelevant probes embedded in a speech stream are larger when the listener is fully focused on the task (cf. Coch, Sanders, & Neville, 2005; Hillyard, Hink, Schwent, & Picton, 1973; Hink & Hillyard, 1976; Teder, Alho, Reinikainen, & Näätänen, 1993; Woldorff & Hillyard, 1991; Woods, Hillyard, & Hansen, 1984). Moreover, a more recent EEG study (Pratt, Willoughby & Swick, 2011) showed that in a multitasking situation — and SI is an extreme case of multitasking (Camayd-Freixas, 2011) — increased WM load decreases attention to the targets. Therefore, the amplitude of these early ERP components can be used as a suitable and temporally precise index of interpreters' attention to the *source* message.

Our assumption that WM overload reduces attention to the auditory stream, which in turn modulates the ERP waveform, aligns well with the evidence that both WM and attention may utilize a common pool of neural resources (Sabri et al., 2014). As demonstrated by fMRI studies, attention and WM are subserved by largely the same brain areas (Awh, Vogel & Oh, 2006; Awh & Jonides, 2001; Corbetta & Shulman, 2002; Cowan, 2000; Mayer et al., 2007; Ungerleider, 2000; Zanto, Rubens, Thangavel & Gazzaley, 2011).

We also examined whether the direction of interpretation has any effect on the early ERP components and sought to identify its potential interaction with WM load. We were motivated by an informal survey conducted prior to this study. In it, out of 32 professional simultaneous interpreters, all of whom were L1 Russian speakers, 29 reported that, all else

being equal, interpreting from English into Russian was much more difficult than in the opposite direction. This is at odds with the findings of a PET study (Rinne et al., 2000) on Finnish L1 interpreters that suggested L1-L2 interpretation was more difficult. The interpreters we surveyed also said the most difficult part for them was to *understand* the source message in L2— and understanding is part of the *listening* effort according to Gile (1988, 1995, 1999). Based on these observations and the prediction of the Efforts Model we predicted that this subjective difficulty would result in a significant difference in median WM loads. Finally, we looked into a possible connection between the direction of interpretation and attention as indexed by the early ERPs.

Below we describe the design of our experiment, report its results and discuss the implications.

## II. METHOD

### Participants

Nine males (aged 25-47, *M* = 36.9, *SD* = 6.757) participated in the study. We sought to keep the age bracket of the participants as narrow as possible to minimize potential age effects. All were qualified interpreters holding a university degree in translation and interpreting, L1 Russian speakers, with an average of 10.65 (*SD* = 6.675) years of professional SI experience. None of them reported substance abuse or a neurological disorder. All signed an informed consent form.

### Procedure and materials

The participants were asked to interpret 8 speeches (4 Russian and 4 English) from the 6849[th] United Nations Security Council Meeting. The discussions at the meeting focused on the rule of law, a topic unlikely to elicit an emotional response. Our expectation was that the UN terminology would be familiar enough to the participants so that they could deliver quality translation with little or no preparation. All the speeches had been originally presented in the speaker's mother tongue (2 in French, 6 in Spanish) with simultaneous interpretation into all the six official UN languages, including Russian and English, in line with the standard UN practice. We deliberately chose speeches originally delivered in a language other than Russian or English. This was necessary to avoid a potential bias due to some subtle properties (e.g. idiosyncratic syntax) that may have been present in the translated, but not in the original texts, and vice versa. To control for a potentially confounding effect of varying delivery speed, we had the written Russian and English translations read at a slow constant rate by bilingual speaker (female) highly proficient in both Russian and English. After the

recording we used Audacity (http://audacityteam.org), open audio editing software, to stretch the audio file to ensure a constant delivery rate of 105 words per minute (wpm). This was an appropriate measure since if these texts had been read out loud within the timeframe of the original speeches, the text-to-text variance of the reader's rate of speech would have had been quite high ($M$ = 121.75 wpm, $SD$ = 30.64 wpm for Russian, $M$ = 125 wpm, $SD$ = 42.1 wpm for English). Thus we eliminated the possible effects of individual speaker's voice features such as rate, pitch, timbre, loudness, prosody and accent. The total playback time was 53 minutes (excluding periods of rest between the speeches).

The audio streams and the task-irrelevant probe stimuli were played by a custom script running under PsychoPy (Peirce, 2008). The probes were 440-Hz 52-ms pure sine tones (including a rise and fall period of 4 ms) delivered with a jittered inter-stimulus interval (ISI) of 450–750 ms ($M$ = 600 ms). These parameters were selected empirically to maximize the number of probes per second of experimental time while minimizing the effect of diminished ERP amplitude with shorter ISIs (Teder et al., 1993).

To control for order effects, the speeches were delivered to the participants in a pseudo-random fashion according to a Latin square such that for every participant the texts' order was different.

The texts were played through earbud headphones (Sennheiser MX 170, 32Ω, Germany). Before the experiment, the participants did two 30-second practice runs, in which they were asked to adjust the volume to a comfortable level and interpret an excerpt from a speech delivered at the same UNSC session, but not included in the experimental material.

Participants were seated comfortably in a reclining chair in an electrically and acoustically shielded room. To reduce oculo-motor and muscle artifacts, they were instructed to sit still, relax, minimize eye movements and articulate their translation as quietly as possible. The translation was recorded using a Boya BY-M1 capacitor microphone for subsequent offline transcription and timecoding.

*Working memory load estimation*

The most obvious and straightforward approach to estimating WM load would be to simply assume that it is proportional to the number of words that an interpreter lags behind the source message at any given time. In the time intervening between the moment of hearing a word and finishing its translation overtly, the interpreter has to store it in WM at least until it is further processed appropriate to the situational context. If we assume that the cognitive effort it takes to process the most frequent function words—

especially articles and prepositions—is negligible, we can exclude them from WM load estimation.

Obviously, this approach is an oversimplification for several reasons. First, it is predicated on the assumption that each word strains WM capacity equally. More frequent words must have stronger mental representations and a larger network of associations than relatively rare ones. In what is known as the *word frequency effect* (Gardner, Rothkopf, Lapan & Lafferty, 1987; Rubenstein, Lewis, & Rubenstein 1971; Scarborough, Cortese & Scarborough, 1977) more frequent words are processed faster. Therefore, they must be translated more easily and cleared from working memory relatively quickly to make room for processing the next chunk of the source message. Conversely, words that are less familiar take more time and effort to process, which delays the retrieval of equivalents from LTM and increases WM load. Second, such an approach does not take into account that words in the source message are never chunked together such that they are stored in WM as a single mental object. Third, it assumes that WM load is reduced at the moment when a word has been translated overtly. This is not always the case because interpreters continue to post-process their own translation, in a phenomenon known as self-monitoring (Gerver, 1974, 1975; Gile, 1995, 2008; Setton, 1999). This means that after a word (or, more generally, a chunk) is translated overtly, it is not cleared from WM immediately, but at a later time, when the interpreter is satisfied with his or her translation. An opposite situation may happen—and this is the fourth reason—when the interpreter can use informational redundancy of the source message to predict an idea *before* it is fully uttered by the speaker (Chernov, 2004). For example, if the source message has multiple references to the United Nations Organization, it is easy to finish the translation before the offset of the phrase *the United Nations Organization*, in other words get ahead of the speaker. The above considerations mean that WM load estimates will be inherently noisy. To mitigate this error of measurement, we sought to maximize the sample and explored several alternative methods of WM load estimation, which we describe below.

A potentially more precise way of estimating WM load would be to scale every word in the source texts by its min-max normalized log-transformed frequency, $\hat{f}$, in a representative corpus. Min-max normalization maps a word's log-transformed absolute frequency in the corpus, $f$, to a value in the range between 0 and 1, while log-transformation helps ensure a better fit for the linear model describing the relationship between a word's rank and frequency in the corpus. For example, the WM load associated with the word 'peace', $\hat{f}_{"peace"}$, after controlling for its frequency in the corpus is given by:

$$\hat{f}_{"peace"} = \frac{\log(f_{"peace"}) - \log(F_{min})}{\log(F_{max}) - \log(F_{min})},$$

where $F_{max}$ and $F_{min}$ are the absolute frequencies, respectively, of the most and the least frequent word in a given corpus, and $f_{"peace"}$ is the absolute frequency of the word 'peace' in the corpus. Estimating WM load this way seems appropriate since word frequency is a major factor determining word recognition (Burgess & Livesay, 1998). More frequent words elicit quicker responses than less frequent ones (Dobbs, Friedman, & Lloyd, 1985; Gernsbacher, 1984). In fact, Whaley (1978) argued that word frequency was "by far the most powerful predictor" in a lexical decision task. For Russian source texts we chose the ruTenTen (14.5 billion words) and the British National Corpus (112.2 million words) accessed through Sketchengine (https://www.sketchengine.co.uk/). Before looking up a word's frequency in the corpus, we used the NLTK package (Bird, Klein, & Loper, 2009) to lemmatize each word.

Finally, to be able to compare the distributions of frequency-weighted lags by direction of interpretation, we ensured that for each participant the sum of WM load estimates were equal for both English-Russian and Russian-English interpretation. This was accomplished by multiplying all the WM load estimates, $e_{mki}$, in the Russian-English interpretations by the quotient of the sums of WM load estimates in the English-Russian and Russian-English directions for each participant. Thus, the $k$-th corrected WM load estimate for the $m$-th participant in the $i$-th Russian-English text, $\hat{e}_{mki}$, is given by

$$\hat{e}_{mki} = e_{mki} \frac{\sum_{j=1}^{J} e_{mj}}{\sum_{i=1}^{I} e_{mi}},$$

for $j = 1, \ldots, J;\ i = 1, \ldots, I;\ k = 1, \ldots, K; m = 1, \ldots, M$

where $J, I, K, M$ are, respectively, the total numbers of English-Russian texts, Russian-English texts, WM estimates (in a given text for a given participant) and participants.

The first method described above is based on the number of content words only. However, it can be extended by scaling each word according to its length in syllables. This should give a more precise estimate of WM load taking account of the words' syllabic length, a potential factor influencing the speed of processing. This extension makes sense since the phonological loop — an essential component of auditory WM (Baddeley, 1992; Baddeley & Hitch, 1974) — has a capacity of about 2 s unless the information stored in it is constantly rehearsed and/or processed.

Finally, we wanted to explore a way to estimate WM load only in terms of the words that were explicitly translated, excluding the ones that were

omitted or mistranslated. The omissions may occur for several reasons. First, words can be lost because the interpreter may fail to find a satisfactory equivalent in the target language. Second, some omissions may be strategic, i.e. aimed to reduce the overall processing load (Cheung, 2012; Pym, 2008). This kind of omission happens quite naturally when a word or phrase is redundant. Examples of such redundancies range from the conjunction *that* to discourse markers *as we know, which I'll get to in a moment* etc. Finally, in rare cases the interpreter may simply fail to attend to a word or phrase while processing earlier information in WM or due to an attention lapse. In the latter case, it can be assumed that the word or phrase neither increased nor decreased WM load. We expected this method to perform similarly to the first method that took into account all the words.

In summary, we assessed the performance of five different methods to estimate WM load, specifically in the number of (a) all content words[1] (CWall); (b) content words excluding those omitted in translation (CW); (c) content words multiplied by their respective syllabic length (SYL); (d) all the words (both function and content) weighted by their frequency in the language (CLall), (e) translated words only, weighted by their respective frequency (CL). Changes in WM load have been assumed to occur at the time of word offset. Since the probes were delivered at random intervals not corresponding to word offsets, we used linear interpolation to estimate WM load at probe onsets (see Figure 1).

## Transcript time coding and WM load estimation

After all the participants' EEG data were recorded, we made transcripts of both the original and translation. Then these transcripts were manually time-stamped and reformatted to allow us to calculate the different WM load estimates as described above. This work was partially automated using several custom functions in VBA running under Microsoft Excel. Figure 2 illustrates the resulting data.

| onset | offset | text | WM load estimate | | |
|---|---|---|---|---|---|
| | | | CW | SYL | CLall |
| 00:39:16.760 | 00:39:17.090 | we | 1 | 1 | 0.172 |
| 00:39:17.090 | 00:39:18.100 | thank | 2 | 2 | 0.567 |
| 00:39:18.100 | 00:39:18.672 | the presidency | 3 | 7 | 1.115 |
| 00:39:18.672 | 00:39:19.400 | Мы | 2 | 6 | 0.943 |
| 00:39:19.400 | 00:39:20.441 | of Guatemala | 3 | 11 | 1.613 |
| 00:39:20.441 | 00:39:20.540 | благодарим | 2 | 10 | 1.217 |
| 00:39:20.540 | 00:39:20.880 | for convening | 3 | 14 | 1.939 |
| 00:39:20.880 | 00:39:20.980 | today's | 4 | 16 | 2.288 |
| 00:39:20.980 | 00:39:21.387 | Гватемалу | 3 | 11 | 1.618 |
| 00:39:21.387 | 00:39:21.730 | страну | 3 | 11 | 1.618 |
| 00:39:21.730 | 00:39:22.177 | meeting | 4 | 13 | 1.979 |
| 00:39:22.177 | 00:39:22.760 | председателя | 3 | 8 | 1.432 |
| 00:39:22.760 | 00:39:23.092 | chile | 4 | 9 | 2.024 |
| 00:39:23.092 | 00:39:23.440 | за созыв | 3 | 5 | 1.303 |
| 00:39:23.440 | 00:39:23.638 | attaches | 4 | 8 | 1.76 |
| 00:39:23.638 | 00:39:23.830 | этого | 3 | 6 | 1.411 |
| 00:39:23.830 | 00:39:24.573 | great | 4 | 7 | 1.722 |
| 00:39:24.573 | 00:39:24.670 | заседания | 3 | 5 | 1.361 |
| 00:39:24.670 | 00:39:25.650 | importance | 4 | 8 | 1.774 |
| 00:39:25.650 | 00:39:25.836 | to the debate | 5 | 12 | 2.242 |
| 00:39:25.836 | 00:39:26.380 | Чили | 4 | 11 | 1.649 |
| 00:39:26.380 | 00:39:26.973 | on peace | 5 | 13 | 2.204 |

**Figure 2.** *Illustration of a time-coded transcript with WM load estimates.*

## EEG data acquisition and pre-processing

The electroencephalogram (EEG) was continuously recorded using the ActiCHamp recording system and BrainVision PyCorder software (Brain Products GmbH) at the sampling rate of 2000 Hz from 32 scalp sites with active electrodes seated in an elastic cap. The EEG signal was re-referenced offline to the average mastoid.

EEG preprocessing and analysis and was carried out using the EEGlab toolbox (Delorme & Makeig, 2004) for MATLAB (The Mathworks, Natick). Raw datasets were downsampled offline to 250 Hz, converted to a linked-mastoids reference (TP9 and TP10) and bandpass-filtered from 0.25

to 30 Hz (6 db/oct) using a zero-phase FIR filter. At the next step we ran independent component analysis (ICA) using the *binica* algorithm in EEGlab to remove the two most dominant independent components corresponding to oculomotor artifacts. Then, to address the issue of muscle noise produced by constant articulation in the experiment, we cleaned continuous data with the artifact subspace reconstruction (ASR) algorithm (Mullen et al., 2015) with the burst parameter set to 4 standard deviations[2].

To ensure the possibility of averaging the data epochs within specific WM load (*low*, *medium* or *high)*, we changed event codes in the EEG dataset to reflect WM load at the probe onset latency estimated with the five different methods described above.

The continuous EEG was then chunked into epochs of 500 ms post-stimulus onset including a 100 ms pre-stimulus baseline, yielding about 5840 epochs per subject. The epochs were screened for any residual artifacts that may have survived the ASR- and ICA-based cleaning stage. Then we averaged the epochs within direction of interpretation and WM load estimated at time zero, i.e. the moment of probe onset, using each of the five methods.

*Data Analysis*

Once we had the clean EEG datasets, we performed several statistical tests to test our hypotheses. First, we wanted to check for possible main effects (and interaction) of WM load and interpretation direction on the average ERP amplitude in the N1 and P1 range. The N1 and P1 component amplitudes and latencies were computed for 20-ms and 80-ms windows around the observed P1 and N1 grand average peaks, respectively. We used a 2-way repeated measures analysis of variance (ANOVA) with Direction (Russian-English, English-Russian) and WM Load (Low, Medium, High) as factors. The Kolmogorov-Smirnov test of the mean P1 ($D$ = 0.047213, $p < 2.2e\text{-}16$ P1) and N1 ($D$ = 0.041403, $p < 2.2e\text{-}16$ N1) indicated a violation of normality. To address this, we used the Johnson transformation[3] (after the transformation $D$ = 0.0037101*, p* = 0.121 for P1; $D$ = 0.0032198, $p$ = 0.2799 for N1). In the second analysis, we submitted the same data to a linear mixed effects model with WM Load and Direction as fixed factors and Subject as a random effect. Unless stated otherwise, all the statistical tests were done in R (R Development Core Team 2016) using the *ez* and *lme4* libraries. Finally, as an additional safeguard against spurious significant results, we re-analyzed our data using a non-parametric randomization test to obtain Monte Carlo estimates of the permutation p-

---

[2] According the authors of the ASR algorithm implementation, 4 sigma ensures mild cleaning.
3 implemented in the *jtrans* library for R.

values (cf. Maris & Oostenveld, 2007). The resampling for the null distribution was performed over all the cells as described by Manly (2006).

## III. RESULTS

### WM load estimates from behavioral data

Figure 3 shows the distributions of WM loads by participant and direction of interpretation. We first consider the distributions of WM load estimated by the most straightforward methods CW and SYL described above. All the participants' median WM loads estimated with the CW and SYL methods were smaller in the English-Russian than in the opposite direction. A Wilcoxon [4] signed rank test showed this difference to be significant: $V$ = 45, $p$ = 0.003906. However, the difference between WM loads calculated using the other methods did not reach statistical significance: $V$ = 35, $p$ = 0.1641 (CL and CWall), $V$ = 6, $p$ = 0.05469 (CLall).

As expected, WM load distributions were far from flat suggesting that the majority of data points representing the interpreters' WM load during the task performance were close to a certain medium value.

*Figure 3. Distributions of WM load estimates by subject and direction of translation calculated using the five different methods.*

---

4 Since all the WM load distributions were clearly right-skewed, a non-parametric test was in order.

*Electrophysiological Results*

To obtain an equal number of observations within each cell of our fully crossed experimental design, the boundaries between the high, medium and low WM load conditions should have been set at the 33[rd] and 66[th] quantiles of each subject's WM load distributions (both for English-Russian and Russian-English). However, as can be inferred from Figure 3, there is a certain 'zone of comfort' that interpreters keep to (or are forced to keep by the very conditions of the interpretation task) most of the time. Therefore, splitting the epochs into three equal WM load groups is not likely to capture a potential effect on the neural activity due to the associated WM load.

With that in mind, we labeled an epoch as *low* if the WM load at the probe onset was below the 10th quantile, *medium* if the WM load fell between the 10[th] and 90[th] quantile, and *high* if it exceeded the 90[th] quantile in the corresponding WM load distribution. Although such a choice may seem arbitrary, it was a tradeoff between maximizing the effect size and sacrificing statistical power due to inflated error in the *low* and *high* WM condition. Mindful of large between-subject and between-language variance in the WM load distributions, we calculated the boundary quantiles for each participant and direction of translation individually obtaining 18 pairs (9 participants x 2 source language) of subject- and direction-specific condition boundaries.

**Figure 4.** *Grand average ERPs for English-Russian (A) and Russian-English (B) at Cz. The ERPs are plotted for the five different methods of estimating WM load.*

Figure 4 shows grand average ERPs at the vertex electrode (Cz) elicited by the probes as a function of WM load. The ANOVA results are summarized in Table 1. In the N1 range, the main effect of WM load achieved significance except with the CW and CL methods. The effect of WM load was also significant in the P1 range (for CWall and CLall methods). The fact that no significant effect of WM load was achieved with the CW and

CL methods (that disregard the omitted words) strongly suggests that even if a word or phrase is not translated, it is processed and contributes to WM load. Therefore, they should be taken into account in WM load estimation.

| | **N1** (120-140 ms) | | | **P1** (50-70 ms) | | |
|---|---|---|---|---|---|---|
| **CLall** | $F$[5] | $p$ | $\eta_p^2$ | $F$ | $p$ | $\eta_p^2$ |
| WM load | 5.48 | 0.015* | 0.41 | 5.80 | 0.013* | 0.42 |
| Direction | 0.28 | 0.614 | 0.03 | 0.051 | 0.497 | 0.06 |
| WM load * Direction | 0.04[6] | 0.884 | 0.01 | 1.67[7] | 0.232 | 0.17 |
| | | | | | | |
| **CWall** | | | | | | |
| WM load | 7.82 | 0.004* | 0.49 | 3.97 | 0.040* | 0.33 |
| Direction | 1.28 | 0.290 | 0.14 | 0.15 | 0.707 | 0.02 |
| WM load * Direction | 0.39 | 0.684 | 0.05 | 2.44[8] | 0.148 | 0.23 |
| | | | | | | |
| **SYL** | | | | | | |
| WM load | 9.65 | 0.002* | 0.55 | 0.27 | 0.764 | 0.03 |
| Direction | 1.36 | 0.277 | 0.14 | 0.01 | 0.906 | <0.01 |
| WM load * Direction | 1.03 | 0.380 | 0.11 | 1.83[9] | 0.124 | 0.26 |
| | | | | | | |
| **CL** | | | | | | |
| WM load | 2.25 | 0.166 | 0.22 | 1.69 | 0.215 | 0.17 |
| Direction | 1.01[10] | 0.345 | 0.11 | 3.31 | 0.107 | 0.29 |
| WM load * Direction | 0.48[11] | 0.524 | 0.06 | 1.84[12] | 0.207 | 0.19 |
| | | | | | | |
| **CW** | | | | | | |
| WM load | 2.28 | 0.135 | 0.22 | 1.12 | 0.350 | 0.12 |
| Direction | 0.88 | 0.375 | 0.10 | 0.69 | 0.430 | 0.08 |
| WM load * Direction | 0.23[13] | 0.696 | 0.03 | 0.41[14] | 0.558 | 0.05 |

*Table 1. Summary of ANOVA results obtained using the different methods of WM load estimation.*

There was neither a significant main effect of interpretation direction, nor WM load * Direction interaction, indicating that processing sensory input (at least task-irrelevant portion of it) is not sensitive to the direction of interpreting.

---

[5] Unless Greenhouse-Geisser correction was used due to violation of sphericity, $df_{load}$ = (2, 16), $df_{direction}$ = (1, 8), $df_{load \ x \ direction}$ = (2, 16). Huynh-Feldt correction was not used because ε never exceeded 0.75.
[6] Mauchly's $W$ = 0.381, $p$ = 0.034. Greenhouse-Geisser corrected df = (1.24, 9.88).
[7] Mauchly's $W$ = 0.062, $p$ < 0.001. Greenhouse-Geisser corrected df = (1.03, 8.26).
[8] Mauchly's $W$ = 0.387, $p$ = 0.036. Greenhouse-Geisser corrected df = (1.24, 9.92).
[9] Mauchly's $W$ = 0.266, $p$ = 0.009. Greenhouse-Geisser corrected df = (1.15, 9.23).
[10] Mauchly's $W$ = 0.319, $p$ = 0.018. Greenhouse-Geisser corrected df = (1.19, 9.52).
[11] Mauchly's $W$ = 0.170, $p$ = 0.002. Greenhouse-Geisser corrected df = (1.09, 8.75).
[12] Mauchly's $W$ = 0.405, $p$ = 0.042. Greenhouse-Geisser corrected df = (1.25, 10.03).
[13] Mauchly's $W$ = 0.420, $p$ = 0.048. Greenhouse-Geisser corrected df = (1.27, 10.13).
[14] Mauchly's $W$ = 0.184, $p$ = 0.003. Greenhouse-Geisser corrected df = (1.10, 8.81).

Figures 5 and 6 show grand average ERP amplitudes as a function of WM load. The pattern of increasing negativity with decreasing WM load was more consistent for the N1, regardless of the WM load estimation method. In the P1 range no such trend could be identified.

*Figure 5.* *Grand average N1 amplitudes as a function of WM load. Vertical bars represent standard errors of the mean.*

*Figure 6.* *Grand average P1 amplitudes as a function of WM load. Vertical bars represent standard errors of the mean.*

**Figure 7.** *Grand average ERP scalp maps.*

Figure 7 shows the scalp activations computed on grand average ERP data. It is clearly seen that the P1 peak (~60 ms post stimulus onset) was topographically centered around frontal midline electrodes (Fz and Cz), while the N1 peak is slightly offset to the right.

To provide a more sophisticated alternative to ANOVA, we also performed statistical tests using several linear mixed-effects models. Adding random by-subject slopes for Direction and WM Load led to no significant improvement in model fit either in the N1 range, (for CLall: $\chi^2(9) = 7.3739$, $p = 0.5983$; for CWall: $\chi^2(9) = 7.5919$, $p = 0.5757$; for SYL: $\chi^2(9) = 8.8749$, $p = 0.4489$; for CL: $\chi^2(9) = 7.5919$, $p = 0.5757$; for CW: $\chi^2(9) = 7.3739$, $p = 0.5983$), or in the P1 range, (for CLall: $\chi^2(9) = 1.7776$, $p = 0.9945$; for CWall: $\chi^2(9) = 2.1555$, $p = 0.9888$; for SYL: $\chi^2(9) = 2.719$, $p = 0.9744$; for CL: $\chi^2(9) = 1.6831$, $p = 0.9955$; for CW: $\chi^2(9) = 2.1862$, $p = 0.9882$). Therefore, in Table 2 we report the results of random by-subject intercept models.

Finally, to additionally check our results, we used a permutation test that unlike parametric models makes no assumption about the underlying distribution. Its alternative hypothesis was that the influence of WM load and Direction on the amplitude of N1 and P1 was stronger than would be expected due to chance. The null distribution was created by randomly permuting the data over all the cells as described by Manly (2006). The

rationale was that if our effects were indeed systematic, the proportion of F-statistics obtained by testing samples drawn from the null distribution, equal to or exceeding the corresponding parametric F-statistics, should not exceed 5%.

| | N1 (120-140 ms) | | P1 (50-70 ms) | |
|---|---|---|---|---|
| | *Likelihood Ratio Test* $(\chi2^{15}$, *p-value)* | *Permutation p-value* | *Likelihood Ratio Test* $(\chi2$, *p-value)* | *Permutation p-value* |
| **CLall** | | | | |
| WM load | 6.6657, 0.0357* | 0.021* | 5.409, 0.0669 | 0.019* |
| Direction | 1.0151, 0.3137 | 0.610 | 0.0939, 0.7592 | 0.499 |
| WM load * Dir. | 0.1228, 0.9405 | 0.957 | 2.1227, 0.346 | 0.206 |
| | | | | |
| **CWall** | | | | |
| WM load | 9.3274, 0.0094* | 0.007* | 4.2253, 0.1209 | 0.046* |
| Direction | 0.9976, 0.3179 | 0.290 | 0.0902, 0.7639 | 0.708 |
| WM load * Dir. | 0.3238, 0.8505 | 0.659 | 1.3499, 0.5092 | 0.127 |
| | | | | |
| **SYL** | | | | |
| WM load | 6.7881, 0.0336* | 0.002* | 0.3181, 0.853 | 0.757 |
| Direction | 1.0141, 0.3139 | 0.272 | 0.0937, 0.7595 | 0.917 |
| WM load * Dir. | 1.5022, 0.4718 | 0.376 | 3.8141, 0.1485 | 0.09 |
| | | | | |
| **CL** | | | | |
| WM load | 3.8036, 0.1493 | 0.138 | 2.5209, 0.2835 | 0.214 |
| Direction | 1.0115, 0.3145 | 0.335 | 0.094, 0.7592 | 0.117 |
| WM load * Dir. | 0.205, 0.9026 | 0.591 | 2.05, 0.3588 | 0.195 |
| | | | | |
| **CW** | | | | |
| WM load | 2.5362, 0.2814 | 0.137 | 2.2313, 0.3277 | 0.342 |
| Direction | 0.9442, 0.3312 | 0.387 | 0.0799, 0.7774 | 0.441 |
| WM load * Dir. | 0.6163, 0.7348 | 0.780 | 1.3077, 0.5200 | 0.658 |

*Table 2. Summary of permutation p-values and p-values obtained using a Likelihood Ratio test of linear mixed effects models. The values are reported for the different methods of WM load estimation.*

The results of the permutation test with 5000 resamples fully agreed with the parametric tests, showing a significant effect of WM load both on the N1 (in the case of the CLall, CWall and SYL methods) and P1 (in the case of the CLall and CWall methods). A complete summary of p-values estimated using the permutation test are reported in Table 2.

Peak latencies for visually identifiable ERP components, specifically P1 and N1, are reported in Table 3. The p-values for the difference between the peak latencies were calculated using a permutation test with 5000 resamples.

---

[15] The degrees of freedom for the Chi-square were 1 for the main effect of Load and 2 for the main effect of Direction and the WM load x Direction interaction.

**Russian - English**

| WM load estimation method | P1 (50-70 ms) | | | N1 (100-180 ms) | | |
|---|---|---|---|---|---|---|
| | Low WM load | High WM load | p | Low WM load | High WM load | p |
| CLall | 52 | 56 | 0.0014* | 140 | 168 | 0.2157 |
| CWall | 56 | 60 | 0.0257* | 140 | 140 | 0.8600 |
| CL | 52 | 56 | 0.1500 | 136 | 168 | 0.6542 |
| CW | 56 | 60 | 0.2471 | 136 | 176 | 0.2867 |
| SYL | 56 | 56 | 0.4886 | 140 | 168 | 0.2814 |

**English – Russian**

| WM load estimation method | P1 (50-70 ms) | | | N1 (100-180 ms) | | |
|---|---|---|---|---|---|---|
| | low WM load | High WM load | p | Low WM load | High WM load | p |
| CLall | 56 | 56 | 0.2142 | 136 | 148 | 0.2342 |
| CWall | 56 | 56 | 0.1771 | 136 | 148 | 0.4185 |
| CL | 56 | 56 | 0.1214 | 136 | 148 | 0.0242* |
| CW | 56 | 56 | 0.1401 | 132 | 156 | 0.2400 |
| SYL | 56 | 56 | 0.1042 | 136 | 152 | 0.3400 |

*Table 3. Peak latencies (in milliseconds post stimulus onset) in the P1 (50-70 ms) and N1 (100-180 ms) range for the low and high WM load conditions. The p-values are reported for the latency differences between the high and low WM load.*

A quick glance at Table 3 suggests that peak latencies in the high WM load condition tend to be greater (and are never smaller) than in the low WM load condition. However, this trend is very weak, especially for the P1 peak latency.

## IV. DISCUSSION

The present study aimed to find electrophysiological evidence in support of the Efforts Model (Gile, 1988, 1995, 1999) which predicts, in particular, that WM overload during simultaneous language interpretation should decrease the amount of processing capacity available to the 'listening effort' and therefore affect the processing of auditory stimuli. Although WM load can be conveniently estimated if we assume it to be proportional to the size of lag between the source and the target (in number of content words), getting a precise behavioral measure of attention during SI would have been problematic. However, as was previously demonstrated in non-interpreters, the amplitude of early ERP components time-locked to task-irrelevant probe stimuli could be used as an electrophysiological index of attention. Given that and based on the Efforts Model, we expected larger negativity in the N1 range at small WM loads.

Consistent with our hypothesis, we found that the amplitude of the N1 component elicited by the task-irrelevant pure tone probes was more negative at lower WM loads. Conversely, the N1 amplitude was less negative at higher WM loads suggesting that the brain temporarily attenuates or suspends the processing of auditory stimuli to more efficiently process and manipulate WM backlog, reduce the lag and cognitive load. The question whether this is controlled consciously (i.e. is a choice based on strategic judgement), or automatically (i.e. is a skill acquired though training and used unconsciously) is treated elsewhere (cf. Fukuii and Asano 1961, Oléron and Nanpon 1965, Kade and Cartellieri 1971, Daró and Fabbro 1994, Osaka 1994, Padilla 1995, Gran and Bellini 1996, Chincotta and Underwood 1998). A correlational study on a larger sample of interpreters with different levels of experience may help answer it.

A visual inspection of the ERP waveforms revealed that the effect of WM load in the P1-N1 range may not have been due only to the enhanced negativity, but also to decreased latency of the P1 and N1 peaks for low WM load. Fehér, Folyi & Horváth (2011) reported a shorter N1 latency for attended stimuli, which reinforces the case for attention acting as a latent variable mediating the effect of WM load on the N1. Although our results did suggest greater N1 latencies at larger WM load, they were not statistically significant.

As part of our second research question, we wished to establish if the subjectively greater difficulty of SI from English into Russian reported by our informal respondents, was due to direction-specific WM load management differences and, if any, to find their electrophysiological correlates. The behavioral data showed a pattern of smaller median WM loads in the English-Russian direction, which seems to be consistent with the predictions of the Efforts Model. However, further interpretation of this pattern is difficult due to no significant main effect of direction on the ERPs (P1/N1) or interaction between direction and WM load.

The fact that Russian-English and English-Russian interpretation had significantly different median WM loads may be due to several reasons. Firstly, because L2 words on average are less 'familiar' than L1 words, they have weaker mental representations than the corresponding L1 words. As a result, L2 words take more time to react to in lexical decision tasks (Gernsbacher, 1984). For our participants (Russian L1, English L2 speakers) this indicates that the perception and analysis of English speech is more difficult than Russian. Moreover, this difficulty is not offset by the relative ease of producing a meaningful target message in the mother tongue (Russian), which is evidenced by shorter lexical retrieval times for L1 words (cf. Schoonen et al., 2003). Secondly, WM in L2 is known to be slower and less efficient than in L1 (Ardila, 2003). Perhaps, when working from English

into Russian, interpreters conserve processing capacity by reducing WM load, while in the Russian-English direction they can afford to keep in WM more Russian than English content words. Thirdly, interpreting from Russian into English—again, all else being equal— appears less of a challenge because Russian words are on average syllabically longer than in English (Gurin, 2009). Thus, a source message in Russian is informationally more sparse and easier to process than a comparable English message delivered at the same rate measured in syllables per unit time. Conversely, in Russian-English interpretation the target English discourse is syllabically more compact and therefore should cause less interference due to acoustic overlap with the source message. In other words, if we assume word-for-word rendering, the interpreter has less time to 'unpack' the English message: English words are shorter than Russian requiring more time to complete the articulation of the corresponding Russian translation. Not only does this create greater and potentially disrupting acoustic interference with the process of listening to the English source, it is possible that attention is engaged longer in the self-monitoring stage of the interpretation cycle. Further research is needed to address this question. However, at least one study (Pellegrino, Coupé & Marsico, 2011) based on seven languages—unfortunately, not including Russian—found that in spoken communication the average amount of information transferred per unit time is subject to substantial, however statistically insignificant, cross-language variation. It is possible that the obvious difference in WM loads as a function of source language is due to different information densities of English and Russian.

Although it is impossible to generalize our results to situations with any other source-target language pair, our data suggest that the early sensory processing does not depend on whether the source is in the mother tongue (L1) or a foreign language (L2). We can argue, at least, that the main source of subjective difficulty in the English-Russian interpreting does not lie in the perceptual stage of processing.

It would be interesting to know if our pattern of results will replicate in language pairs other than Russian and English. Languages may have vastly different syntaxes and grammars, which means that interpreters have to change their strategies depending on the direction of interpretation. For example, when working from German, interpreters are forced to increase their décalage (Goldman-Eisler, 1972) waiting for the predicate which often appears at the end of the clause, which means larger WM loads overall.

On a practical note, our results justify a recommendation to keep WM load within reasonable limits during SI. The question about how this can be achieved is very relevant. Several studies (Bartłomiejczyk, 2006; Chernov, 1994; Li, 2010) have shown that simultaneous interpreters use a range of strategies to manage their processing load (e.g. omitting redundancies in the

source speech). None of them, however, have attempted to identify the neural states that determine—or at least bias—the choice of a particular strategy.

Further neuroimaging studies of SI are needed to validate and/or refine theoretical models of SI and will help to guide interpreters, SI instructors and the interpretation industry towards better interpretation practices, more efficient curricula and higher standards of service.

## V. REFERENCES

Ardila, A. (2003). Language representation and working memory with bilinguals. *Journal of Communication Disorders*, *36*(3), 233–240. http://doi.org/10.1016/S0021-9924(03)00022-4

Awh, E., & Jonides, J. (2001). Overlapping mechanisms of attention and spatial working memory. *Trends in Cognitive Sciences*, *5*(3), 119–126. http://doi.org/10.1016/S1364-6613(00)01593-X

Awh, E., Vogel, E. K., & Oh, S.-H. (2006). Interactions between attention and working memory. *Neuroscience*, *139*(1), 201–208. http://doi.org/10.1016/j.neuroscience.2005.08.023

Baddeley, A. (1992). Working memory. *Science*. Retrieved from http://www.sciencemag.org/content/255/5044/556.short

Baddeley, A., & Hitch, G. (1974). Working memory. *The Psychology of Learning and Motivation*, *8*, 47–89. Retrieved from https://www.google.com/books?hl=en&lr=&id=o5LScJ9ecGUC&oi=fnd&pg=PA47&dq=Working+Memory&ots=8z8G_U5gZ_&sig=c3N0a_Kl0hExGJW8aPgZIcpNG84

Bajo, M. T., Padilla, F., & Padilla, P. (2000). *Comprehension processes in simultaneous interpreting*. (A. Chesterman, N. G. S. Salvador, & Y. Gambier, Eds.)*Translation in Context: Selected papers from the EST Congress, Granada 1998*. John Benjamins Publishing Company. http://doi.org/10.1075/btl.39.15baj

Bartłomiejczyk, M. (2006). Strategies of simultaneous interpreting and directionality. *Interpreting*, *8*(2), 149–174. http://doi.org/10.1075/intp.8.2.03bar

Bird, S., Klein, E., & Loper, E. (2009). *Natural Language Processing with Python*. O'Reilly Media. Retrieved from http://books.google.com/books?id=KGIbfiiP1i4C&printsec=frontcover

Burgess, C., & Livesay, K. (1998). The effect of corpus size in predicting reaction time in a basic word recognition task: Moving on from Kučera and Francis. *Behavior Research Methods, Instruments, & Computers*, *30*(2), 272–277. http://doi.org/10.3758/BF03200655

Camayd-Freixas, E. (2011). Cognitive theory of simultaneous interpreting and training. *Proceedings of the 52nd Conference of the American Translators Association*, 13. Retrieved from http://casgroup.fiu.edu/pages/docs/2406/1320876652_Cognitive_Theory _of_Simultation_Interpreting.pdf

Chernov, G. V. (1994). Message redundancy and message anticipation in simultaneous interpreting. In S. Lambert & B. Moser-Mercer (Eds.), *Bridging the Gap: Empirical research in simultaneous interpretation* (pp. 139–153). Chapel Hill: John Benjamins Publishing Co. http://doi.org/10.1075/btl.3.13che

Chernov, G. V. (2004). *Inference and Anticipation in Simultaneous Interpreting*. (R. Setton & A. Hild, Eds.) (Vol. 57). Amsterdam: John Benjamins Publishing Company. http://doi.org/10.1075/btl.57

Cheung, A. K. (2012). Omission in Simultaneous Interpreting: Word order differences1. *FORUM*, *10*(2), 19–33. http://doi.org/10.1075/forum.10.2.02che

Coch, D., Sanders, L. D., & Neville, H. J. (2005). An Event-related Potential Study of Selective Auditory Attention in Children and Adults. *Journal of Cognitive Neuroscience*, *17*(4), 605–622.

Corbetta, M., & Shulman, G. L. (2002). Control of goal-directed and stimulus-driven attention in the brain. *Nature Reviews. Neuroscience*, *3*(3), 201–15. http://doi.org/10.1038/nrn755

Cowan, N. (2000). Processing limits of selective attention and working memory: Potential implications for interpreting. *Interpreting*, *5*(2), 117–146. http://doi.org/10.1075/intp.5.2.05cow

Delorme, A., & Makeig, S. (2004). EEGLAB: An open source toolbox for analysis of single-trial EEG dynamics including independent component

analysis. *Journal of Neuroscience Methods*, *134*(1), 9–21. http://doi.org/10.1016/j.jneumeth.2003.10.009

Dobbs, A. R., Friedman, A., & Lloyd, J. (1985). Frequency effects in lexical decisions: A test of the verification model. *Journal of Experimental Psychology: Human Perception and Performance*, *11*(1), 81–92. http://doi.org/10.1037//0096-1523.11.1.81

Fehér, B., Folyi, T., & Horváth, J. (2011). Attention decreases auditory N1 latency. In *Front. Neurosci. Conference Abstract: 13th Conference of the Hungarian Neuroscience Society* (Vol. 5). http://doi.org/10.3389/conf.fnins.2011.84.00117

Gardner, M. K., Rothkopf, E. Z., Lapan, R., & Lafferty, T. (1987). The word frequency effect in lexical decision: Finding a frequency-based component. *Memory & Cognition*, *15*(1), 24–28. http://doi.org/10.3758/BF03197709

Gernsbacher, M. A. (1984). Resolving 20 Years of Inconsistent Interactions Between Lexical Familiarity and Orthography, Concreteness, and Polysemy. *Journal of Experimental Psychology: General*, *113*(2), 256–281. http://doi.org/10.1016/j.micinf.2011.07.011.Innate

Gerver, D. (1974). THE EFFECTS OF NOISE ON THE PERFORMANCE OF SIMULTANEOUS INTERPRETERS : ACCURACY OF PERFORMANCE 1 Continuous skilled tasks involving attention switching and / or data transformation are particularly susceptible to interference from environmental noise , , 159–167.

Gerver, D. (1975). A psychological approach to simultaneous interpretation. *Meta*, *20/22*(July), 119–128. http://doi.org/10.7202/002885ar

Gile, D. (1988). Le partage de l'attention et le "modèle d'effort" en interprétation simulaneé. *The Interpreters' Newsletter*, (1), 4–22. Retrieved from http://hdl.handle.net/10077/2132

Gile, D. (1995). *Basic Concepts and Models for Interpreter and Translator Training* (Vol. 8 (1st)). Amsterdam: John Benjamins Publishing Company. http://doi.org/10.1075/btl.8(1st)

Gile, D. (1999). Testing the Effort Models' tightrope hypothesis in simultaneous interpreting-A contribution. *Hermes*, (23), 153–172.

Gile, D. (2008). Local cognitive load in simultaneous interpreting and its implications for empirical research. *Forum American Bar Association*, *6*, 59–77.

Goldman-Eisler, F. (1972). Segmentation of input in simultaneous translation. *Journal of Psycholinguistic Research*, *1*(2), 127–40. http://doi.org/10.1007/BF01068102

Gurin, I. (2009). *Priemy rechevoi kompressii pri sinkhronnom perevode c russikogo yazyka an angliiskii [Speech Compression Techniques For Simultaneous Interpetation From Russian Into English]. (PhD Thesis)*. Moscow State University.

Hillyard, S. a, Hink, R. F., Schwent, V. L., & Picton, T. W. (1973). Electrical Signs of Selective Attention in the Human Brain. *Science*, *182*(4108), 177–180. http://doi.org/10.1126/science.182.4108.177

Hink, R. F., & Hillyard, S. a. (1976). Auditory evoked potentials during selective listening to dichotic speech messages. *Perception & Psychophysics*, *20*(4), 236–242. http://doi.org/10.3758/BF03199449

Kim, H.-R. (2005). Linguistic Characteristics and Interpretation Strategy Based on EVS Analysis of Korean-Chinese, Korean-Japanese Interpretation. *Meta: Journal Des Traducteurs*, *50*(4). http://doi.org/10.7202/019846ar

Lambert, S. (1992). Shadowing. *Meta: Journal Des Traducteurs*, *37*(2), 263. http://doi.org/10.7202/003378ar

Li, C. (2010). Coping Strategies for Fast Delivery in Simultaneous Interpretation. *The Journal of Specialised Translation*, (13), 19–25.

Liu, M., Schallert, D. L., & Carroll, P. J. (2004). Working memory and expertise in simultaneous interpreting. *Interpreting*, *6*(1), 19–42. http://doi.org/10.1075/intp.6.1.04liu

Manly, B. F. J. (2006). *Randomization and Monte Carlo Methods in Biology* (3rd ed.). Chapman and Hall/CRC. http://doi.org/10.1017/CBO9781107415324.004

Maris, E., & Oostenveld, R. (2007). Nonparametric statistical testing of EEG- and MEG-data. *Journal of Neuroscience Methods*, *164*(1), 177–190. http://doi.org/10.1016/j.jneumeth.2007.03.024

Mayer, J. S., Bittner, R. a., Nikolić, D., Bledowski, C., Goebel, R., & Linden, D. E. J. (2007). Common neural substrates for visual working memory and attention. *NeuroImage*, *36*(2), 441–453. http://doi.org/10.1016/j.neuroimage.2007.03.007

Mizuno, A. (2005). Process Model for Simultaneous Interpreting and Working Memory. *Meta: Journal Des Traducteurs*, *50*(2), 739. http://doi.org/10.7202/011015ar

Mullen, T. R., Kothe, C. A. E., Chi, Y. M., Ojeda, A., Kerth, T., Makeig, S., … Cauwenberghs, G. (2015). Real-time neuroimaging and cognitive monitoring using wearable dry EEG. *IEEE Transactions on Biomedical Engineering*, *62*(11), 2553–2567. http://doi.org/10.1109/TBME.2015.2481482

Padilla, P., Bajo, M. T., Cañas, J. J., & Padilla, F. (1995). Cognitive processes of memory in simultaneous interpretation. *Topics in Interpreting Research*.

Peirce, J. W. (2008). Generating Stimuli for Neuroscience Using PsychoPy. *Frontiers in Neuroinformatics*, *2*(January), 10. http://doi.org/10.3389/neuro.11.010.2008

Pellegrino, F., Coupé, C., & Marsico, E. (2011). Across-Language Perspective on Speech Information Rate. *Language*, *87*(3), 539–558. http://doi.org/10.1353/lan.2011.0057

Proverbio, A. M., Leoni, G., & Zani, A. (2004). Language switching mechanisms in simultaneous interpreters: an ERP study. *Neuropsychologia*, *42*(12), 1636–1656. http://doi.org/10.1016/j.neuropsychologia.2004.04.013

Pym, A. (2008). On omission in simultaneous interpreting . Risk analysis of a hidden effort. *Efforts and Models in Interpreting and Translation Research*, 83–105.

Rinne, J. O., Tommola, J., Laine, M., Krause, B. J., Schmidt, D., Kaasinen, V., … Sunnari, M. (2000). The translating brain: cerebral activation patterns during simultaneous interpreting. *Neuroscience Letters*, *294*(2), 85–8. http://doi.org/10.1016/S0304-3940(00)01540-8

Rubenstein, H., Lewis, S. S., & Rubenstein, M. A. (1971). Evidence for phonemic recoding in visual word recognition. *Journal of Verbal Learning*

and *Verbal Behavior, 10*(6), 645–657. http://doi.org/10.1016/S0022-5371(71)80071-3

Sabri, M., Humphries, C., Verber, M., Liebenthal, E., Binder, J. R., Mangalathu, J., & Desai, A. (2014). Neural effects of cognitive control load on auditory selective attention. *Neuropsychologia, 61*(1), 269–279. http://doi.org/10.1016/j.neuropsychologia.2014.06.009

Scarborough, D., Cortese, C., & Scarborough, H. S. (1977). Frequency and repetition effects in lexical memory. *Journal of Experimental Psychology: General, 3*(1), 1–17. http://doi.org/10.1037/0096-1523.3.1.1

Schoonen, R., Gelderen, A. Van, Glopper, K. de, Hulstijn, J., Simis, A., Snellings, P., & Stevenson, M. (2003). First Language and Second Language Writing: The Role of Linguistic Knowledge, Speed of Processing, and Metacognitive Knowledge. *Language Learning, 53*(1), 165–202. http://doi.org/10.1111/1467-9922.00213

Setton, R. (1999). *Simultaneous interpretation: a cognitive-pragmatic analysis. Benjamins translation library*.

Signorelli, T. M., & Obler, L. (2013). Working memory in simultaneous interpreters. In *Memory, language, and bilingualism: Theoretical and applied approaches.* (pp. 95–125). Retrieved from http://search.ebscohost.com/login.aspx?direct=true&db=psyh&AN=2012-26865-004&site=ehost-live&scope=site

Teder, W., Alho, K., Reinikainen, K., & Näätänen, R. (1993). Interstimulus interval and the selective-attention effect on auditory ERPs: *Psychophysiology, 30*(1), 71–81. http://doi.org/10.1111/j.1469-8986.1993.tb03206.x

Ungerleider, S. K. and L. G. (2000). Mechanisms of Visual Attention in the Human Cortex. *Annual Review of Neuroscience, 23*(1), 315–341. http://doi.org/10.1146/annurev.neuro.23.1.315

Whaley, C. P. (1978). Word—nonword classification time. *Journal of Verbal Learning and Verbal Behavior, 17*(2), 143–154. http://doi.org/10.1016/S0022-5371(78)90110-X

Woldorff, M. G., & Hillyard, S. a. (1991). Modulation of early auditory processing during selective listening to rapidly presented tones. *Electroencephalography and Clinical Neurophysiology, 79*(3), 170–191. http://doi.org/10.1016/0013-4694(91)90136-R

Woods, D. L., Hillyard, S. a, & Hansen, J. C. (1984). Event-related brain potentials reveal similar attentional mechanisms during selective listening and shadowing. *Journal of Experimental Psychology. Human Perception and Performance*, *10*(6), 761–77. http://doi.org/10.1037/0096-1523.10.6.761

Zanto, T. P., Rubens, M. T., Thangavel, A., & Gazzaley, A. (2011). Causal role of the prefrontal cortex in top-down modulation of visual processing and working memory. *Nature Neuroscience*, *14*(5), 656–661. http://doi.org/10.1038/nn.2773