Voluntary control of illusory contour formation

William J Harrison [1,2,*] & Reuben Rideaux [1]

[1]Department of Psychology, University of Cambridge

[2]Queensland Brain Institute, The University of Queensland

*Corresponding author (willjharri@gmail.com)

SUMMARY

The visual brain is tasked with segmenting visual input into a structured scene of coherent

objects. Figures that produce the perception of illusory contours reveal minimal conditions

necessary for the visual system to perform figure-ground segmentation, but it is unclear what

role visual attention plays in such perceptual organisation. Here we tested whether illusory

contours are formed under the guidance of voluntary attention by exploiting a novel variant

of the classical Kanizsa figure in which multiple competing illusory forms are implied. We

used a psychophysical response classification technique to quantify which spatial structures

guide perceptual decisions, and generated alternative predictions about the influence of

attention using a machine classifier. We found that illusory contour formation was contingent

on attended elements of the figure even when such illusory contours conflicted with

competing illusory form. However, the strength of these illusory contours was constrained

by form implied by unattended figural elements. Our data thus reveal an interplay of top-

down and bottom-up processes in figure-ground segmentation: while attention is not

necessary for illusory contour formation, under some conditions it is sufficient.

INTRODUCTION

The clutter inherent to natural visual environments means that goal-relevant objects often

partially occlude one another. A critical function of the human visual system is to group

common parts of objects while segmenting them from distracting objects and background,

a process which requires interpreting an object's borders. Figures which produce illusory

contours, such as the classic Kanizsa triangle (Kanizsa, 1976), have provided many insights

into this problem by revealing the inferential processes made in determining figure-ground

relationships. These figures give rise to a vivid percept of a shape emerging from sparse

information, and thus demonstrate the visual system's ability to interpolate structure from

fragmented information, to perceive edges in the absence of luminance discontinuities, and

to fill-in a shape's surface properties. In the present study, we investigated whether voluntary

attention guides figure-ground segmentation of competing illusory contours.

Most objects can be differentiated from their backgrounds via a luminance-defined border.

The visual system is tasked with allocating one side of the border to an occluding object,

and the other side to the background. This computation can be performed by neurons in

macaque visual area V2 whose receptive fields fall on the edge of an object (Zhou,

Friedman, & Heydt, 2000). These "border-ownership" cells can distinguish figure from

ground even when the monkey attends elsewhere in the display (Qiu, Sugihara, & Heydt,

2007), and psychophysical adaptation aftereffects suggest such cells also exist in humans

(Heydt, Macuda, & Qiu, 2005). Further, neurophysiological work has revealed that V2 cells

also process illusory edges (Heydt, Peterhans, & Baumgartner, 1984), though it is unclear

whether those cells possess the same properties as border-ownership cells. These findings

have contributed to the claim that visual structure is computed automatically and relatively

early in the visual system, and that visual attention is guided by this pre-computed structure

(Mihalas, Dong, Heydt, & Niebur, 2011).

It is also known, however, that visual attention can modulate the perception of figure-ground

relationships of luminance-defined stimuli. In particular, psychophysical work has shown that

voluntary attention can alter perceived depth order (Driver & Baylis, 1996), as in the case of

Rubin's face-vase illusion (Wagemans et al., 2012), and surface filling-in (Tse, 2005). These

findings raise the possibility that perceptual organisation may not be as automatic as

previously hypothesized. Indeed, electrophysiological work has revealed that the activity of

some border-ownership cells is modulated by visual attention (Qiu et al., 2007).

Furthermore, visual attention has been shown to facilitate visual grouping according to

Gestalt rules at both the neurophysiological (Wannig, Stanisor, & Roelfsema, 2011) and

behavioural (Houtkamp, Spekreijse, & Roelfsema, 2003) level. However, because these

previous studies involve physically defined stimuli, it remains unclear whether visual

attention simply modulates pre-attentively computed structure as suggested by

neurophysiological work (McMains & Kastner, 2011; Qiu et al., 2007), or whether structural

computations depend on the state of attention. Rivalrous illusory figures are perfectly suited

to address this issue: if attending to one illusory figure results in illusory contours that directly

conflict with the form of another illusory figure, then structural computations must depend
on attention.

To investigate the influence of voluntary attention on visual interpolation, here we combined
a novel illusory figure with an attentionally demanding task, exploiting human observers'
propensity to use illusory edges when making perceptual decisions (Gold, Murray, Bennett,
& Sekuler, 2000). We developed a novel Kanizsa figure (**Fig. 1a**), in which "pacman" discs
are arranged at the tips of an imaginary star. This figure includes multiple Gestalt cues that
promote the segmentation of various forms. We predict that, because some of these cues
suggest competing configurations, selective attention can bias which figure elements are
assigned to figure and which to ground. Although such a hypothesis is relatively
uncontroversial, the critical question is whether grouping via selective attention promotes
illusory contour formation in direct conflict with competing implied form. For example, while
the black inducers of **Figure 1a** form part of an implied star, in isolation the black inducers
imply an illusory triangle that competes with both the star form as well as the illusory triangle
implied by the white inducers. We therefore assessed whether the figure perceived by
observers is determined by which inducers are attended.

We used a response classification technique that allowed us to simultaneously assess
where observers' attention was allocated, and whether such attentional allocation resulted
in visual interpolation of illusory edges. At the beginning of each block of testing, observers
were cued to report the relative jaw size of the inducers forming an upright (or inverted)
triangle, corresponding to the white (or black) elements in **Figure 1a**. By adding random
visual noise to the target image on each trial (**Fig. 1b**), we could use reverse correlation to
measure "classification images". An observer's classification image quantifies a correlation
between each pixel in the image and the perceptual report revealing which spatial structures
are used for perceptual decisions (Gold et al., 2000).

We generated hypotheses regarding how observers' voluntary attention may influence their
perception of this figure. We used a support vector machine (SVM) classifier to judge small
changes to a triangle image after training it on one of three different protocols. First, we
generated a prediction of the hypothesis that observers can attend to the correct inducers,
but do not perceive illusory edges, by training a model to discriminate only the jaws of the

inducers. This model is analogous to that of an ideal observer (Gold et al., 2000), and

reveals that only structure at the edges of the stimuli are used in generating a response

(**Fig. 1c**). We next generated predictions of how illusory edges could be interpolated in this

task. In one case, we assumed illusory contours would be formed between attended

inducers. We thus trained the classifier to discriminate whether a triangle's edges were bent

outward or inward, and found a classification image approximating a triangle (**Fig. 1d**). In

the other case, we assumed that, although selective attention may guide the correct

perceptual decision, the illusory form of a star may be determined pre-attentively according

to the physical structure of the entire stimulus. In this case, we trained the classifier to

discriminate whether alternating tips of a star where relatively wide or narrow. The resulting

classification image reveals edges that are interpolated beyond the inducers, but that they

do not extend beyond the alternating star tips (**Fig. 1e**). These predictions not only provide

qualitative comparisons for our empirical data, but they also allow us to formally test which

training regime produces a classification image that most closely resembles human data.

Figure 1. Novel illusory figure and design used to test the influence of attention on perceptual organisation.

a) Our variant of the classic Kanizsa figure. "Pacman" inducers are arranged such that a star appears to

occlude black and white discs. Whereas the ensemble of features may produce the appearance of a star,

grouping features by polarity leads to competing illusory triangles. We test whether attending to one set of

inducers (e.g. the white inducers) leads to interpolation of the illusory edge. b) Example trial sequence. After

an observer fixates a spot, the illusory figure with overlaid Gaussian noise is displayed for 250ms. The

observer's task was to report whether the tips of the upright or inverted triangle were narrower or wider than

an equilateral triangle. The target triangle was cued prior to, and held constant throughout, each testing

block. The observer's perceptual reports were then correlated with the noise on each trial to produce

classification images. (c - e) Support vector machine (SVM) classifier images. We had a SVM classifier

perform "narrow" vs "wide" triangle judgements after training it on three different protocols: (c) inducers, a (d)

triangle, or a (e) star (see Methods). Dashed red lines show the location of a pacman for reference, and in

(e) the tips of the star that do not influence classification.

RESULTS

To motivate observers to attend to only one possible configuration of the illusory figure, they were cued to report the relative jaw size ("narrow" or "wide") of only a subset of pacmen positioned at the tips of an imaginary star (**Fig. 1a**). Specifically, observers were instructed to report only the jaw size of inducers forming an upward (or downward) triangle within a testing block. The uncued inducer jaws varied independently of the cued inducers and thus added no information regarding the correct response. To derive the spatial structure used for perceptual decisions, we added Gaussian noise to each trial and classified each noise image according to the observers' responses (**Fig. 1b**). To create the classification image for each observer, we summed all noise images for narrow reports and subtracted the sum of all noise images for wide reports (see Methods). We collapsed across inducer polarity by inverting the noise on trials in which the white inducers were cued, and across cue direction by flipping the noise on trials in which the downward facing illusory triangle was cued. The resulting images quantify the correlation between each stimulus pixel and the observer's report. So we could analyse a single axis of emergent spatial structure, we first averaged each observer's data with itself after rotating 120° and 240° such that correlations were averaged over the three sides of the triangle. Although this step involved bilinear interpolation of neighbouring pixels, no other averaging or smoothing was performed.

Classification images for three observers and their mean are shown in **Figure 2a** (see **Supp. Fig. 1a** for unrotated classification images). There are two obvious patterns that emerge. First, it is clear that observers based their reports on pixels within the jaws of the cued inducers, indicating that only some regions of the image – those aligned with the attended inducers – influenced perceptual decisions. Note the difference in the sign of the correlation between the edges and tips of the triangle - noise pixels in these regions have the opposite influence on narrow/wide decisions, which is likely due to an illusory widening of the jaw centre which is not registered by the SVM (cf. **Fig. 1d**). Second, the edges clearly extend beyond the inducers, revealing observers' reports were influenced by illusory contours. However, it is also apparent that the spatial structure is non-uniform, with weaker correlations in the centre of the illusory edges than in the corners of the inducers. We therefore quantitatively test the extent of illusory contour formation below.

To test whether the illusory edge interpolation extended into the region of the implied competing figure, we performed two analyses. First, we used Bayesian and Students' one-sampled t-tests to assess the pixel values along the edge of the triangle implied by the attended inducers (see red line in **Fig. 2a**). We selected only pixels that fell within the bounds of the competing implied triangle (see Methods and **Fig. 2b**), but nonetheless found that these 18 pixels were below zero for the naïve participant (mean and sem: -3 ± .9 x 10^{-3}, BF_{10}=18.37, t(17)=3.59, p=0.002), observer A2 (mean and sem: -5 ± .7 x 10^{-3}, BF_{10}=8141.36, t(17)=6.94, p<0.001), and the group (mean and sem: -3 ± .4 x 10^{-3}, BF_{10}=16580, t(17) = 7.38, p<0.001), but not for A1 (mean and sem: -1 ± 1 x 10^{-3}, BF_{10}=0.42, t(17)=1.15, p=0.27).

Figure 2. Classification image results. a) The individual and average classification images. Black and white pixels in this image are correlated with "narrow" and "wide" perceptual reports, respectively, after 9984 trials per participant. Data have not been smoothed, but were first averaged across triangle edges and cropped to be 122x122 pixels. In the mean image, a pacman outline is shown for reference, and a red line indicates the spatial range over which we tested the pixel values aligned with the implied triangle edge (from which data in (b) are shown). b) Pixel values along the illusory edge. The grey shaded region corresponds to a conservative estimate of the extent of the gap that would appear if observers necessarily saw a star shape (e.g. Fig. 1e). The blue shaded region in the mean plot shows ±one standard error; asterisks indicate differences from zero ($BF_{10} > 10$ and p < 0.05). N1 is the naïve participant; A1 and A2 are authors. c) Comparison of SVM models. Distributions show comparisons of the mean classification image to the output of each SVM prediction, repeated 200 times. Data points and error bars represent the mean and 95% confidence intervals, respectively, for each SVM training regime. Model error has been normalised relative to the model with the least error, which is the model in which the SVM is trained to perceive a triangle.

We next quantified the spatial structure content of the classification image by testing which prediction generated by the SVM was most similar to the human data (see Fig. 1c-e). For each model, we generated 200 predictions, each with a unique distribution of noise, and computed the sum of squared errors between predictions and the mean classification image produced by the human observers. The resulting distributions of error, normalised to the

best model, are shown in Figure 2c, and reveal that the model in which we trained the

classifier to perceive a complete triangle is the best fit to the data (z-test comparing the

mean error for the star SVM versus the distribution of error for the triangle or inducer SVM:

p's < 0.0001). Taken together, these analyses thus reveal illusory contour formation

between attended visual elements, and this interpolation occurred despite the contour

conflicting with equally plausible implied spatial structure.

We next tested the spatial specificity of illusory contour formation. For the two participants

who showed a clear effect, we tested how spatially specific visual interpolation was by

repeating the same analysis as above but for the row of pixels above and below the triangle

boundary implied by the geometry of the attended inducers. Quite surprisingly, we found

good evidence that there was an absence of illusory contour formation for the pixels below

the implied triangle boundary (N1: $BF_{01} = 3.19$; A2: $BF_{01} = 3.31$), and equivocal evidence for

the pixels above the implied triangle boundary (N1: $BF_{10} = 1.05$; A2: $BF_{01} = 1.83$). These

results thus reveal that the strength of illusory contours was highly precisely aligned to the

geometry of the triangle implied by the inducers. Consistent with this observation,

psychophysical thresholds for identifying the relative inducer jaw size were reliably highly

precise across testing sessions (see **Supp. Fig. 1b**).

Our data further address the extent to which the unattended figural elements were grouped.

In our experiment, the uncued inducer jaw size was independent of the cued inducer jaw

size, and was thus uninformative of the correct report. Indeed, we found no evidence in the

classification image that observers attended to these task-irrelevant cues. We modelled the

possibility that these unattended cues were nonetheless grouped: the SVM prediction of

pre-attentive figure-ground segmentation shows gaps in the sides of the classification image

triangle (**Fig 1e**). Note that this model is equivalent to observers perceiving a whole star, but

focussing their attention on only some regions of the figure. Because we designed our

illusory figure to be geometrically invertible, the extent of the illusory star form is pronounced

if we sum the classification image with a flipped version of itself (**Fig. 3a**). In **Figure 3b**, we

show the result of performing this step with the observers' average classification image.

Very similar patterns of results were found for all individual images (**Supp. Fig. 2**). This

result is strikingly similar to the SVM prediction, revealing that the changes in strength of

edges of the illusory form are near-perfectly aligned with the geometry of the implied star.

The reduction in pixel intensity along the triangle edge reported above (**Fig. 2b**) can thus
likely be explained by the illusory star form constraining voluntary interpolation of the illusory
triangle edge.

224
225 **Figure 3**. Pre-attentive grouping. a) Geometric form prediction of unattended grouping. The classification
226 image derived from our SVM was summed with a flipped version of itself. Note that the inner corners of the
227 star are well aligned due to the design of our original Kanizsa figure. b) Geometric form in observers' data.
228 The mean classification image was summed with a flipped version of itself, and reveals the strength of
229 illusory edges are well aligned to the implied star.
230

DISCUSSION
We used classification images to quantify which spatial structure guides perceptual
decisions when attention is directed to only some elements of a scene. Our main findings
are twofold. First, we found that voluntarily attending to a subset of Gestalt cues leads to
visual interpolation between those cues, and the resulting illusory edges inform perceptual
decisions. Second, the strength of visual interpolation is constrained by the grouping of
unattended elements. Our study thus reveals that figure-ground segmentation of illusory
form is determined by both top-down (cognition-contingent) and bottom-up (stimulus-driven)
processes.
240

Unlike previous studies that show visual attention modulates the appearance of physically
defined surfaces (e.g., attending to different surfaces of the Necker cube), our study shows
a rich interaction between attention and perception. The illusory edges of the triangle implied
by the attended inducers directly conflict with the regions of the competing implied figures
(i.e., the star and inverted triangle). Our finding that illusory edges were interpolated between
attended inducers reveals that attention can determine depth order, even when figures and
ground are illusory. Spatial structure is thus computed by neural regions whose operations
can be contingent on the voluntary state of the observers. The precision of illusory contours
were nonetheless tightly aligned to the geometry of luminance defined structure, indicating

these inferential processes are also highly contingent on scene or task context. Indeed,

observers' psychophysical thresholds for the inducer task reveal a correspondence between

their precise objective psychophysical performance and subjective classification image.

We were able to quantify the influence of unattended stimuli on perception by measuring a

classification image across the entire stimulus. We found that changes in the strength of

illusory contour formation between attended inducers were aligned with form implied by the

unattended inducers. Measuring perceived form in the absence of visual attention is

notoriously difficult (Wagemans et al., 2012), which is perhaps one reason why many studies

of figure-ground organisation rely on single-unit recordings. Whereas neurophysiological

recordings have revealed the brain regions involved in perceptual organisation, they have

left open the question of perceptual phenomena. Our data show that the influence of

attention on perception is constrained by task-irrelevant information, providing yet further

evidence that visual experience is the combination of both bottom-up and top-down

processes. This conclusion sheds light on previous work in which competing colour

adaptation after-effects are biased according to alternating illusory contours at a similar

location (van Lier, Vergeer, & Anstis, 2009). In these demonstrations, the onset of inducer

elements likely attracts an observer's attention, resulting in perceptual completion processes

specific to only the implied shape of attended elements. Surface filling-in would then follow

the contours of the implied form (Poort et al., 2012). Indeed, other recent research from our

lab reveals similar interactions may occur between attention and surface filling-in (Harrison,

Ayeni, & Bex, 2017).

The influence of attention on figure-ground segmentation may be explained by feedback

signals from the lateral occipital complex (M. M. Murray et al., 2002; Stanley & Rubin, 2003)

that could act as early as V1 (Wannig et al., 2011), but also may involve modulating

responses of border-ownership cells in V2 (Qiu et al., 2007). Border-ownership cells indicate

which side of a border is an object versus ground. Previous work showing the activity of

border-ownership cells is modulated by visual attention (Qiu et al., 2007) has been limited

to luminance-defined borders. Our finding that information inferred by the visual system is

influenced by voluntary attention suggests that attentional modulation of border-ownership

may similarly apply to illusory contours (Heydt et al., 1984). Early psychophysical work

suggested that illusory contours are perceived in the absence of attention (Davis & Driver,

1994; Mattingley, Davis, & Driver, 1997), but did not address the question of whether illusory

contours can be formed *because* of voluntary attention, which we have shown here. Our

findings are also distinct from other recent work that found attention can influence the

appearance of existing surfaces (Tse, 2005). In our study, visual attention had a causal role

in forming the structure from which perceptual decisions were made.

METHODS

Observers. Three healthy subjects, one naïve (N1) and two authors (A1 & A2 corresponding

to authors RR and WH, respectively), gave their informed written consent to participate in

the project, which was approved by the University of Cambridge Psychology Research

Ethics Committee. All procedures were in accordance with approved guidelines. Simulations

were run to determine an appropriate number of trials per participant to ensure sufficient

statistical power, and our total sample is similar to those generally employed for

classification images. All participants had normal vision.

Apparatus. Stimuli were generated in MATLAB (The MathWorks, Inc., Matick, MA) using

Psychophysics Toolbox extensions (Brainard, 1997; Cornelissen, Peters, & Palmer, 2002;

Pelli, 1997). Stimuli were presented on a calibrated ASUS LCD monitor (120Hz,

1920×1200). The viewing distance was 57 cm and participants' head position was stabilized

using a head and chin rest (43 pixels per degree of visual angle). Eye movement was

recorded at 500Hz using an EyeLink 1000 (SR Research Ltd., Ontario, Canada).

Stimuli and task. The stimulus was a modified version of the classic Kanisza triangle. Six

pacman discs (radius = 1°) were arranged at the tips of an imaginary star centred on a

fixation spot. The six tips of the star were equally spaced, and the distance from the centre

of the star to the centre of each pacman was 2.1°. The fixation spot was a white circle (0.1°

diameter) and a black cross hair (stroke width = 1 pixel). The stimulus was presented on a

grey background (77.5 cd/m^2). The polarity of the inducers with respect to the background

alternated across star tips. For half the trials, the three inducers forming an upright triangle

were white, while the others were black, and for half the trials this was reversed. Inducers

had a Weber contrast of .75.

We added Gaussian noise to the stimulus on each trial to measure classification images.
Noise was 250 x 250 independently drawn luminance values with a mean of 0 and standard
deviation of 1. Each noise image was scaled without interpolation to occupy 500 x 500
pixels, such that each randomly drawn luminance value occupied 2 x 2 pixels (.05° x .05°).
The amplitude of these luminance values was then scaled to have an effective contrast of
0.125 on the display background, and were then added to the Kanizsa figure. Finally, a
circular aperture was applied to the noise to ensure the edges of the inducers were equally
spaced from the noise edge (**Fig. 1b**).

The jaw size of inducers was manipulated such that they were wider or narrower than an
equilateral triangle, which would have exactly 60° of jaw angle for all inducers. The
observer's task was to indicate whether the jaws of the attended inducers was consistent
with a triangle that was narrower or wider than an equilateral triangle. Prior to the first trial
of a block, a message on the screen indicated which set of inducers framed the "target"
triangle, and this was held constant within a block but alternated across blocks. The polarity
of the target inducers and whether the triangles were narrow or wide was pseudorandomly
assigned across trials such that an equal number of all trial types were included in each
block. The relative jaw size of attended inducers was independent of the unattended
inducers; thus, the identity of the non-target triangle was uncorrelated with the correct
response.

Each trial began with the onset of the fixation spot and a check of fixation compliance for
250 ms. Following an additional random interval (0-500 ms uniformly distributed), the
stimulus was presented for 250 ms, after which only the background was presented while
observers were given unlimited duration to report the jaw size using a button press. The
next trial would immediately follow a response. Throughout the experiment, eye tracking
was used to ensure observers did not break fixation during stimulus presentation. If gaze
position strayed from fixation by more than 2° the trial was aborted and a message was
presented instructing them to maintain fixation during stimulus presentation, and then the
trial was repeated. Such breaks in fixation were extremely rare for all participants.

A three-down one-up staircase procedure was used to progress the difficulty of the task by
varying the difference of the jaw size from 60° (i.e., from what would form an equilateral

triangle). On each trial an additional angle was randomly added or subtracted to the standard 60° inducers. The initial difference was 2°. Following three correct responses, this difference would decrease by a step size of 0.5°, or would increase by the same amount following a single error. When an incorrect response was followed by three correct responses (i.e., a reversal), the step size halved. If two incorrect responses were made in a row, the step size would double. If the step size fell below 0.05°, it would be reset to 0.2°. Blocks consisted of 624 trials which took approximately 20 minutes including a forced break. Each observer completed 16 blocks for a total of 9984 trials, which took a total of approximately five hours duration spread over multiple days and testing sessions. To familiarize observers with the task, they underwent two training blocks of 624 trials each with no noise. They then were shown the stimulus with noise, and completed as many trials as they felt was required before starting the experimental blocks.

Support vector machine models. Support vector machine (SVM) classifiers were trained and tested in MATLAB. We generated (3) hypotheses by training SVM classifiers on images of the *i*) inducers, *ii*) a triangle, or *iii*) a star. We trained the classifiers using a quadratic kernel function and a least squares method of hyperplane separation. The training images consisted of two exemplars ("narrow" and "wide") with no noise. To generate hypotheses in the form of classification images, we used each of the classifiers to perform narrow/wide triangle judgements (trials = 9984), with an equilateral triangle; thus, classification was exclusively influenced by the noise in the image.

Data and statistical analysis. The 9984 noise images for a participant were separated according to perceptual report ("narrow" or "wide"). To collapse across inducer polarity, we reflected the distribution of noise on trials in which the cued inducers were white (i.e., we inverted the sign). We also collapsed across upright and inverted cue conditions by spatially flipping the noise on inverted trials. The noise values were then summed within each report type. The difference of these summed images is the raw classification image. To average across emergent triangle edges, we further summed the image with itself two times after rotating 120° and 240° using Matlab's "imrotate" function using bilinear interpolation. This procedure results in a classification image that is invariant across edges such that analysis of one edge summarises all three edges. Note that this is a conservative estimate of the classification image and any spurious structure will only be diminished. To test for correlated

pixels along the illusory edge of the classification image, we extracted 18 pixels along the

bottom edge of the implied triangle, but within the bounds of the implied star tip (see bottom

right panel of **Fig. 2a**). To ensure that these pixels were not contaminated by averaging of

nearest-neighbour pixels during rotation, described above, we excluded the three pixels

closest to the inner corners of the star. We conducted a one-sample, two-tailed Bayesian

and Students' T-Test on these pixel values using JASP software (JASP Team, 2017). We

performed the model comparisons in Figure 2c by first normalising the noise of the mean

classification image and each SVM prediction such that the sum of squared error of each

image equalled 1. We then subtracted the mean classification image from each prediction,

and found the sum of squared error of the resulting difference. Finally, we normalised the

difference scores to the model with the least error by subtracting from each distribution the

mean of the distribution with the lowest error. This process was repeated for 200 repetitions

of each SVM prediction.

Data availability. The data that support the findings of this study are available from the

corresponding author upon request.

REFERENCES

Brainard, D. H. (1997). The Psychophysics Toolbox. *Spatial Vision*, *10*(4), 433–436.

Cornelissen, F. W., Peters, E. M., & Palmer, J. (2002). The Eyelink Toolbox: eye tracking with MATLAB and the Psychophysics Toolbox. *Behavior Research Methods, Instruments & Computers*, *34*(4), 613–617.

Davis, G., & Driver, J. (1994). Parallel detection of Kanizsa subjective figures in the human visual system. *Nature*, *371*(6500), 791–793. http://doi.org/10.1038/371791a0

Driver, J., & Baylis, G. C. (1996). Edge-assignment and figure-ground segmentation in short-term visual matching. *Cognitive Psychology*, *31*(3), 248–306. http://doi.org/10.1006/cogp.1996.0018

Gold, J. M., Murray, R. F., Bennett, P. J., & Sekuler, A. B. (2000). Deriving behavioural receptive fields for visually completed contours. *Current Biology*, *10*(11), 663–666. http://doi.org/10.1016/S0960-9822(00)00523-6

Harrison, W. J., Ayeni, A. J., & Bex, P. J. (2017). Selective attention modulates surface filling-in. *bioRxiv*. http://doi.org/10.1101/221150

Heydt, von der, R., Macuda, T., & Qiu, F. T. (2005). Border-ownership-dependent tilt aftereffect. *Journal of the Optical Society of America. a, Optics, Image Science, and Vision*, *22*(10), 2222–2229. http://doi.org/10.1364/JOSAA.22.002222

Heydt, von der, R., Peterhans, E., & Baumgartner, G. (1984). Illusory contours and cortical neuron responses. *Science*, *224*(4654), 1260–1262. http://doi.org/10.1126/science.6539501

Houtkamp, R., Spekreijse, H., & Roelfsema, P. R. (2003). A gradual spread of attention during mental curve tracing. *Perception and Psychophysics*, *65*(7), 1136–1144.

Kanizsa, G. (1976). Subjective contours. *Scientific American*, *234*(4), 48–52.

Mattingley, J. B., Davis, G., & Driver, J. (1997). Preattentive filling-in of visual surfaces in parietal extinction. *Science*, *275*(5300), 671–674.

McMains, S., & Kastner, S. (2011). Interactions of Top-Down and Bottom-Up Mechanisms in Human Visual Cortex. *Journal of Neuroscience*, *31*(2), 587–597. http://doi.org/10.1523/JNEUROSCI.3766-10.2011

Mihalas, S., Dong, Y., Heydt, von der, R., & Niebur, E. (2011). Mechanisms of perceptual organization provide auto-zoom and auto-localization for attention to objects. *Proceedings of the National Academy of Sciences of the United States of America*, *108*(18), 7583–7588. http://doi.org/10.1073/pnas.1014655108

Murray, M. M., Wylie, G. R., Higgins, B. A., Javitt, D. C., Schroeder, C. E., & Foxe, J. J. (2002). The spatiotemporal dynamics of illusory contour processing: combined high-density electrical mapping, source analysis, and functional magnetic resonance imaging. *Journal of Neuroscience*, *22*(12), 5055–5073.

Pelli, D. G. (1997). The VideoToolbox software for visual psychophysics: Transforming numbers into movies. *Spatial Vision*, *10*(4), 437–442.

Poort, J., Raudies, F., Wannig, A., Lamme, V. A. F., Neumann, H., & Roelfsema, P. R. (2012). The role of attention in figure-ground segregation in areas V1 and V4 of the visual cortex. *Neuron*, *75*(1), 143–156. http://doi.org/10.1016/j.neuron.2012.04.032

Qiu, F. T., Sugihara, T., & Heydt, von der, R. (2007). Figure-ground mechanisms provide structure for selective attention. *Nature Neuroscience*, *10*(11), 1492–1499. http://doi.org/10.1038/nn1989

Stanley, D. A., & Rubin, N. (2003). fMRI activation in response to illusory contours and salient regions in the human lateral occipital complex. *Neuron*, *37*(2), 323–331.

Tse, P. U. (2005). Voluntary attention modulates the brightness of overlapping transparent

surfaces. *Vision Research*, *45*(9), 1095–1098.
http://doi.org/10.1016/j.visres.2004.11.001
van Lier, R., Vergeer, M., & Anstis, S. (2009). Filling-in afterimage colors between the
lines. *Current Biology*, *19*(8), R323–4. http://doi.org/10.1016/j.cub.2009.03.010
Wagemans, J., Elder, J. H., Kubovy, M., Palmer, S. E., Peterson, M. A., Singh, M., &
Heydt, von der, R. (2012). A century of Gestalt psychology in visual perception: I.
Perceptual grouping and figure-ground organization. *Psychological Bulletin*, *138*(6),
1172–1217. http://doi.org/10.1037/a0029333
Wannig, A., Stanisor, L., & Roelfsema, P. R. (2011). Automatic spread of attentional
response modulation along Gestalt criteria in primary visual cortex. *Nature*
Neuroscience, *14*(10), 1243–1244. http://doi.org/10.1038/nn.2910
Zhou, H., Friedman, H. S., & Heydt, von der, R. (2000). Coding of border ownership in
monkey visual cortex. *The Journal of Neuroscience, 20*(17), 6594–6611.
459
460

ACKNOWLEDGEMENTS

We are indebted to Peter Bex who developed the novel Kanizsa figure with us and

provided helpful feedback on our study design and results. This research was supported

by funding to W.J.H. from King's College Cambridge and the National Health and Medical

Research Council of Australia (APP1091257).

AUTHOR CONTRIBUTIONS

Both authors designed the experiment and collected the data. WJH analysed the

experimental data, and RR performed the SVM analyses. Both authors contributed equally

to the writing of the manuscript.

We declare we have no competing interests.

SUPPLEMENTARY FIGURES

Supplementary Figure 1. Raw classification images and psychophysical performance. a)
Classification images without rotation of the image with itself. b) Threshold performance
across blocks shown separately for each observer. Thresholds were the midpoint of a
cumulative Gaussian fit to accuracy data for each session.

Supplementary Figure 2. Individual classification images revealing grouping of
unattended structure. These images were created by summing each classification image
with a flipped version of itself. Note that the emergent structure aligns to the geometry of
the star implied by our Kanizsa figure (Fig. 1a).