Title: Voluntary control of visual appearance

Authors and affiliations: William J Harrison [1,2,] & Reuben Rideaux [1]

[1] Department of Psychology, University of Cambridge
Downing Street, Cambridge CB2 3EB, UK
[2] Queensland Brain Institute, The University of Queensland
QBI Building #79, St Lucia QLD 4072, Australia

Corresponding author: William Harrison (willjharri@gmail.com)

Classification: Biological Sciences; Psychological and Cognitive Sciences

ABSTRACT

The extent to which visual appearance is shaped by attentional goals is controversial. Voluntary attention may simply modulate the priority with which information is accessed by higher cognitive functions involved in perceptual decision making. Alternatively, voluntary attention may influence fundamental visual processes, such as those involved in segmenting an incoming retinal signal into a structured scene of coherent objects, thereby determining visual appearance. Here we tested whether the segmentation and integration of visual form can be determined by an observer's goals by exploiting a novel variant of the classical Kanizsa figure. We generated predictions about the influence of attention with a machine classifier, and tested these predictions with a psychophysical response classification technique. Despite seeing the same image on each trial, observers' perception of illusory spatial structure depended on their attentional goals. These attention-contingent illusory contours directly conflicted with equally plausible visual form implied by the geometry of the stimulus, revealing that attentional selection can determine the perceived layout of a fragmented scene. Attentional goals, therefore, not only select pre-computed features or regions of space for prioritised processing, but, under certain conditions, also greatly influence perceptual organisation and thus visual appearance.

SIGNIFICANCE STATEMENT

The extent to which higher cognitive functions can influence perceptual experience is hotly debated. The role of voluntary spatial attention, the ability to focus on only some parts of a scene, has been particularly controversial among neuroscientists and psychologists who aim to uncover the basic neural computations involved in grouping image features into coherent objects. To address this issue, we repeatedly presented the same novel ambiguous image to observers and changed their attentional goals by having them make fine spatial judgements about only some elements of the image. We found that observers' attentional goals determine the perceived organisation of multiple illusory shapes. We thus reveal that voluntary spatial attention can control the fundamental processes that determine visual experience.

INTRODUCTION

The clutter inherent to natural visual environments means that goal-relevant objects often partially occlude one another. A critical function of the human visual system is to group common parts of objects while segmenting them from distracting objects and background, a process which requires interpreting an object's borders. Figures which produce illusory contours, such as the classic Kanizsa triangle (1), have provided many insights into this problem by revealing the inferential processes made in determining figure-ground relationships. These figures give rise to a vivid percept of a shape emerging from sparse information, and thus demonstrate the visual system's ability to interpolate structure from fragmented information, to perceive edges in the absence of luminance discontinuities, and to fill-in a shape's surface properties. In the present study, we exploit these figures to investigate whether voluntary attention influences visual appearance.

Most objects can be differentiated from their backgrounds via a luminance-defined border. The visual system is tasked with allocating one side of the border to an occluding object, and the other side to the background. This computation can be performed by neurons in macaque visual area V2 whose receptive fields fall on the edge of an object (2). These "border-ownership" cells can distinguish figure from ground even when the monkey attends elsewhere in the display (3), and psychophysical adaptation aftereffects suggest such cells also exist in humans (4). Further, neurophysiological work has revealed that V2 cells also process illusory edges (5), though it is unclear whether those cells possess the same properties as border-ownership cells. These findings have contributed to the claim that visual structure is computed automatically and relatively early in the visual system, and that visual attention is guided by this pre-computed structure (6).

It is also known, however, that visual attention can modulate the perception of figure-ground relationships of luminance-defined stimuli. As early as 1832, Necker described his ability to alter the apparent depth of an engraved crystalline form, now referred to as a Necker cube, via an overt shift of attention (7). More recent psychophysical work has shown that voluntary attention can alter perceived depth order (8) as in the case of Rubin's face-vase illusion (9)(10), and can also alter apparent surface transparency (11). Furthermore, visual attention has been shown to facilitate visual grouping according to Gestalt rules at both the neurophysiological (12) and behavioural (13) level. These findings raise the possibility that,

regardless of whether it is necessary, visual attention may play a determining role in visual

appearance under certain conditions. However, because these previous studies involved

physically defined stimuli, it remains unclear whether visual attention simply modulates pre-

attentively computed structure as suggested by neurophysiological work (3, 14), or whether

structural computations depend on the state of attention. Rivalrous illusory figures are

perfectly suited to address this issue: if attending to one illusory figure results in illusory

contours that directly conflict with the form of another illusory figure, then structural

computations must depend on attention.

To investigate the influence of voluntary attention on visual appearance, here we combined

a novel illusory figure with an attentionally demanding task, exploiting human observers'

propensity to use illusory edges when making perceptual decisions (15). We developed a

novel Kanizsa figure (**Fig. 1a**), in which "pacman" discs are arranged at the tips of an

imaginary star. This figure includes multiple Gestalt cues that promote the segmentation and

integration of various forms not defined by the physics of the stimulus. We predict that,

because some of these cues suggest competing configurations, selective attention can bias

which figure elements are assigned to figure and which to ground. Although such a

hypothesis is relatively uncontroversial, the critical question is whether grouping via

selective attention promotes illusory contour formation in direct conflict with competing

implied form. For example, while the black inducers of **Figure 1a** form part of an implied

star, in isolation the black inducers imply an illusory triangle that competes with both the star

form as well as a second illusory triangle implied by the white inducers. The dependence of

such perceptual organisation on voluntary attentional selection thus can reveal the extent of

top-down processing on visual appearance. We therefore assessed whether the apparent

organisation of the figure is determined by which inducers are attended.

Figure 1. Novel illusory figure and design used to test the influence of attention on perceptual organisation. a)

Our variant of the classic Kanizsa figure. "Pacman" inducers are arranged such that a star appears to occlude

black and white discs. Whereas the ensemble of features may produce the appearance of a star, grouping

features by polarity leads to competing illusory triangles. We test whether attending to one set of inducers (e.g.

the white inducers) leads to interpolation of the illusory edge. b) Example trial sequence. After an observer

fixates a spot, the illusory figure with overlaid Gaussian noise is displayed for 250ms. The observer's task was

to report whether the tips of the upright or inverted triangle were narrower or wider than an equilateral triangle.

The target triangle was cued prior to, and held constant throughout, each testing block. The observer's

perceptual reports were then correlated with the noise on each trial to produce classification images. (c - e)

Support vector machine (SVM) classifier images. We had a SVM classifier perform "narrow" vs "wide" triangle

judgements after training it on three different protocols: (c) inducers, a (d) triangle, or a (e) star (see Methods).

Dashed red lines show the location of a pacman for reference, and in (e) the tips of the star that do not influence

classification.

RESULTS

We used a response classification technique that allowed us to simultaneously assess

where observers' attention was allocated, and whether such attentional allocation resulted

in visual interpolation of illusory edges. At the beginning of each block of testing, observers

were cued to report the relative jaw size of the inducers forming an upright (or inverted)

triangle, corresponding to the white (or black) elements in **Figure 1a**. By adding random

visual noise to the target image on each trial (**Fig. 1b**), we could use reverse correlation to

measure "classification images". An observer's classification image quantifies a correlation

between each pixel in the image and the perceptual report revealing which spatial structures
are used for perceptual decisions (15).

We generated hypotheses regarding how observers' voluntary attention may influence their
perception of this figure. We used a support vector machine (SVM) classifier to judge small
changes to a triangle image after training it on one of three different protocols. First, we
generated a prediction of the hypothesis that observers can attend to the correct inducers,
but do not perceive illusory edges, by training a model to discriminate only the jaws of the
inducers. This model is analogous to that of an ideal observer and reveals that only structure
at the edges of the stimuli are used in generating a response (**Fig. 1c**). We next generated
predictions of how illusory edges could be interpolated in this task. In one case, we assumed
illusory contours would be formed between attended inducers. We thus trained the classifier
to discriminate whether a triangle's edges were bent outward or inward, and found a
classification image approximating a triangle (**Fig. 1d**). In the other case, we assumed that,
although selective attention may guide the correct perceptual decision, the illusory form of
a star may be determined pre-attentively according to the physical structure of the entire
stimulus. In this case, we trained the classifier to discriminate whether alternating tips of a
star where relatively wide or narrow. The resulting classification image reveals edges that
are interpolated beyond the inducers, but that they do not extend beyond the alternating star
tips (**Fig. 1e**). These predictions not only provide qualitative comparisons for our empirical
data, but they also allow us to formally test which training regime produces a classification
image that most closely resembles human data.

To motivate observers to attend to only one possible configuration of the illusory figure, they
were cued to report the relative jaw size ("narrow" or "wide") of only a subset of pacmen
positioned at the tips of an imaginary star (**Fig. 1a**). Specifically, observers were instructed
to report only the jaw size of inducers forming an upward (or downward) triangle within a
testing block. The non-cued inducer jaws varied independently of the cued inducers and
thus added no information regarding the correct response. To derive the spatial structure
used for perceptual decisions, we added Gaussian noise to each trial and classified each
noise image according to the observers' responses (**Fig. 1b**). To create the classification
image for each observer, we summed all noise images for narrow reports and subtracted
the sum of all noise images for wide reports (see Methods). We collapsed across inducer

polarity by inverting the noise on trials in which the white inducers were cued, and across

cue direction by flipping the noise on trials in which the downward facing illusory triangle

was cued. The resulting images quantify the correlation between each stimulus pixel and

the observer's report. In order to analyse a single axis of emergent spatial structure, we first

averaged each observer's data with itself after rotating 120° and 240° such that correlations

were averaged over the three sides of the triangle. Although this step involved bilinear

interpolation of neighbouring pixels, no other averaging or smoothing was performed, and

this averaging is therefore most likely to only reduce the strength of emergent illusory

structure.

Classification images for three observers and their mean are shown in **Figure 2a** (see **Supp.**

Fig. 1a for unrotated classification images). Images are normalised to the "attend upright"

condition. There are two obvious patterns that emerge. First, it is clear that observers based

their reports on pixels within the jaws of the cued inducers, indicating that only some regions

of the image – those aligned with the attended inducers – influenced perceptual decisions.

Note the difference in the sign of the correlation between the edges and tips of the triangle

– noise pixels in these regions have the opposite influence on narrow/wide decisions, which

is likely due to an illusory widening of the jaw centre which is not registered by the SVM (cf.

Fig. 1d). Second, the edges clearly extend beyond the red inducer outline shown in the

mean image, revealing observers' reports were influenced by illusory contours. However, it

is also apparent that the spatial structure is non-uniform, with weaker correlations in the

centre of the illusory edges than in the corners of the inducers. We therefore quantitatively

test the extent of illusory contour formation below.

To test whether the illusory edge interpolation extended into the region of the implied

competing figure, we performed two analyses. First, we used Bayesian and Students' one-

sampled t-tests to assess the pixel values along the edge of the triangle implied by the

attended inducers (see red line in **Fig. 2a**). We selected only pixels that fell within the bounds

of the competing implied triangle (see Methods and grey shaded regions of **Fig. 2b**), and

found that these 18 pixels were below zero for the naïve participant (mean and sem: $-3 \pm .9$

$\times 10^{-3}$, $BF_{10}=18.365$, $t(17)=3.585$, $p=0.002$, $d = 0.845$), observer A2 (mean and sem: $-5 \pm .7$

$\times 10^{-3}$, $BF_{10}=8,141.356$, $t(17)=6.944$, $p<0.001$, $d = 1.637$), and the group (mean and sem: -

$3 \pm .4 \times 10^{-3}$, $BF_{10}=16{,}580$, $t(17) = 7.38$, $p<0.001$, $d = 1.738$), but not for A1 (mean and sem:

$-1 \pm 1 \times 10^{-3}$, $BF_{10}=0.431$, $t(17)=1.15$, $p=0.266$, $d = 0.204$).

Figure 2. Classification image results. a) The individual and average classification images. Black and white pixels in this image are correlated with "narrow" and "wide" perceptual reports, respectively, after 9984 trials per participant. Data have not been smoothed, but were first averaged across triangle edges and cropped to be 122x122 pixels. In the mean image, a pacman outline is shown for reference, and a red line indicates the spatial range of the implied triangle edge (from which data in (b) are shown). b) Pixel values along the illusory edge. The grey shaded region corresponds to a conservative estimate of the extent of a gap in the edge that would appear if observers necessarily saw a star shape (e.g. Fig. 1e). The blue shaded region in the mean plot shows ±one standard error; asterisks indicate differences from zero ($BF_{10} > 10$ and $p < 0.05$; see text). N1 is the naïve participant; A1 and A2 are authors. c) Comparison of SVM models. Distributions show comparisons of the mean classification image to the output of each SVM prediction, repeated 200 times. Data points and error bars represent the mean and 95% confidence intervals, respectively, for each SVM training regime. Model error has been normalised relative to the model with the least error, which is the model in which the SVM is trained to perceive a triangle within the attended inducers.

We next quantified the spatial structure content of the classification image by testing which prediction generated by the SVM was most similar to the human data (see **Fig. 1c-e**). For each model, we generated 200 predictions, each with a unique distribution of noise, and computed the sum of squared errors between predictions and the mean classification image produced by the human observers (see Materials and Methods). The resulting distributions of error, normalised to the best model, are shown in **Figure 2c**, and reveal that the model in which we trained the classifier to perceive a complete triangle is the best fit to the data (z-test comparing the mean error for the star SVM versus the distribution of error for the triangle or inducer SVM: p's < 0.0001). Taken together, these analyses thus reveal illusory contour formation between attended visual elements, and this interpolation occurred despite the contour conflicting with equally plausible implied spatial structure.

We next tested the spatial specificity of illusory contour formation. For the two participants who showed a clear effect, we tested how spatially specific visual interpolation was by repeating the same analysis as above but for the row of pixels above and below the triangle boundary implied by the geometry of the attended inducers. Quite surprisingly, we found good evidence that there was an absence of illusory contour formation for the pixels below the implied triangle boundary (N1: $BF_{01} = 3.19$; A2: $BF_{01} = 3.31$), and equivocal evidence for the pixels above the implied triangle boundary (N1: $BF_{10} = 1.05$; A2: $BF_{01} = 1.83$). These results thus reveal that the strength of illusory contours was highly precisely aligned to the geometry of the triangle implied by the attended inducers. Consistent with this observation, psychophysical thresholds for identifying the relative inducer jaw size were reliably highly precise across testing sessions (see **Supp. Fig. 1b**).

Our data further address the extent to which the non-cued figural elements may have influenced perceptual judgements. In our experiment, the non-cued inducer jaw size was independent of the cued inducer jaw size, and was thus uninformative of the correct report. Indeed, we found no evidence in the classification image that observers' perceptual decisions were guided by these task-irrelevant cues. We modelled the possibility that these non-cued elements were nonetheless grouped: the SVM prediction of pre-attentive figure-ground segmentation shows gaps in the sides of the classification image triangle (**Fig 1e**). Note that this model is equivalent to observers having perceived a whole star, but with a later stage attentional signal focussed on only some regions of the pre-computed figure. Because we designed our illusory figure to be geometrically invertible, the extent of the illusory star form is pronounced if we sum the classification image with a flipped version of itself (**Fig. 3a**). In **Figure 3b**, we show the result of performing this step with the observers' average classification image. Very similar patterns of results were found for all individual images (**Supp. Fig. 2**). This result is strikingly similar to the SVM prediction, revealing that the changes in strength of edges of the illusory form are near-perfectly aligned with the geometry of the implied star or non-cued illusory triangle (**Fig. 1e**).

Figure 3. Pre-attentive grouping. a) Geometric form prediction of unattended grouping. The classification
image derived from our SVM was summed with a flipped version of itself. Note that the inner corners of the
star are well aligned due to the design of our original Kanizsa figure. b) Geometric form in observers' data.
The mean classification image was summed with a flipped version of itself, and reveals the strength of
illusory edges are well aligned to the implied star. c) Results of mixture modelling used to explore the
correspondence between fluctuations of illusory edge strength and implied figure geometry. The best fitting
model for each observer was one in which attention determined perceptual outcome in 84% of trials. The
dashed line indicates the proportion expected from a purely stochastic process. Error bars show 95%
confidence intervals.

There are at least three possible explanations for the near-perfect alignment of changes in

illusory edge strength with the implied star figure (**Fig. 3b**). First, a similar classification

image would have been obtained had observers perceived a star on every trial, a

possibility which we discounted in the results described above. Second, this qualitative

result could be generated if trial-by-trial perceptual organisation was stochastic, such that

observers perceived each possible configuration approximately equally often across trials.

Under this hypothesis, the resulting illusory contours shown in **Figure 2a** are incidental

rather than being determined by observers' attentional goals. The third possible

explanation is that observers' voluntary allocation of attention determined the outcome on

most, but not all, trials. To distinguish between the two latter possibilities, we used mixture

modelling to quantify the proportion of trials in which observers' percept depended on

attentional instructions (see Materials and Methods). A purely stochastic process would be

implied were the proportion of trials accounted for by the triangle template no different from

0.33 (i.e. the apparent top-most surface was equally often a star, the cued triangle, or the

non-cued triangle, see **Fig. 1c-e**). However, in the best fitting model, the attention-

contingent triangle template contributed to 84% of trials on average, which is much greater

than expected by a stochastic process (**Fig. 3c**). This mixture modelling is thus consistent

with observers' attentional goals determining illusory contour interpolation on the vast

majority of trials.

DISCUSSION

We used classification images to address whether voluntary attention determines a scene's

apparent visual structure. Using a psychophysical response classification paradigm we

tested which of three competing model predictions best describes the influence of attention

on illusory contour formation. Our results clearly show that voluntary attention can guide

the fundamental processes involved in perceptual organisation, thus determining visual

appearance.

Unlike previous studies that show visual attention modulates the appearance of physically

defined surfaces (e.g., attending to different surfaces of the Necker cube (7)), our study

shows a rich interaction between attention and endogenously generated percepts. The

illusory edges of the triangle implied by the attended inducers directly conflict with the

regions of the competing implied figures (i.e., the star and inverted triangle). Our finding that

illusory edges were interpolated between attended inducers reveals that attention can

determine depth order, even when figures and ground are illusory. Spatial structure is thus

computed by neural operations that are at least partially contingent on the voluntary state of

the observer. The precision of illusory contours was nonetheless tightly aligned to the

geometry of luminance defined structure, indicating these inferential processes are also

highly contingent on scene or task context. Indeed, observers' psychophysical thresholds

for the inducer task reveal a correspondence between their precise objective psychophysical

performance and subjective classification image.

We were able to quantify the influence of non-cued stimuli on perception by measuring a

classification image across the entire stimulus. We found that changes in the strength of

illusory contour formation between attended inducers were aligned with form implied by the

non-cued inducers. Our mixture modelling suggests that the non-cued stimuli influenced

performance on approximately 16% of trials. Such a contribution of task-irrelevant features

on perceptual decisions could be attributed to lapses in attentional allocation, or variability

in the feed-forward processing of the incoming signal. Measuring perceived form in the

absence of visual attention is notoriously difficult (10), which is perhaps one reason why

many studies of figure-ground organisation rely on single-unit recordings. Whereas
neurophysiological recordings have revealed the brain regions involved in perceptual
organisation, they have left open the question of perceptual phenomena. Our data show that
the influence of attention on perception is constrained by task-irrelevant information,
providing yet further evidence that visual experience is the combination of both bottom-up
and top-down processes. This conclusion sheds light on previous work in which competing
colour adaptation after-effects are biased according to alternating illusory contours at a
similar location (16). In these demonstrations, the onset of inducer elements likely attracts
an observer's attention, resulting in perceptual completion processes specific to only the
implied shape of attended elements. Surface filling-in would then follow the contours of the
implied form (17). Indeed, other recent research from our lab reveals similar interactions
may occur between attention and surface filling-in (18).

The influence of attention on figure-ground segmentation may be explained by feedback
signals from the lateral occipital complex (19, 20) that could act as early as V1 (12), but also
may involve modulating responses of border-ownership cells in V2 (3). Border-ownership
cells indicate which side of a border is an object versus ground. Previous work showing the
activity of border-ownership cells is modulated by visual attention (3) has been limited to
luminance-defined borders. Our finding that information inferred by the visual system is
influenced by voluntary attention suggests that attentional modulation of border-ownership
may similarly apply to illusory contours (5). Early psychophysical work suggested that
illusory contours are perceived in the absence of attention (21, 22), but did not address the
question of whether illusory contours can be formed *because* of voluntary attention, which
we have shown here. Our findings are also distinct from other recent work that found
attention can influence the appearance of existing surfaces (11). In our study, visual
attention had a causal role in forming the structure from which perceptual decisions were
made. We anticipate that our simple stimulus and task design may prove to be a useful
neurophysiological assay to test further the neural substrates governing the interaction
between voluntary attention and perceptual organisation.

MATERIALS AND METHODS

Observers. Three healthy subjects, one naïve (N1) and two authors (A1 & A2 corresponding
to authors RR and WH, respectively), gave their informed written consent to participate in

the project, which was approved by the University of Cambridge Psychology Research
Ethics Committee. All procedures were in accordance with approved guidelines. Simulations
were run to determine an appropriate number of trials per participant to ensure sufficient
statistical power, and our total sample is similar to those generally employed for
classification images. All participants had normal vision.

Apparatus. Stimuli were generated in MATLAB (The MathWorks, Inc., Matick, MA) using
Psychophysics Toolbox extensions (23–25). Stimuli were presented on a calibrated ASUS
LCD monitor (120Hz, 1920×1200). The viewing distance was 57 cm and participants' head
position was stabilized using a head and chin rest (43 pixels per degree of visual angle).
Eye movement was recorded at 500Hz using an EyeLink 1000 (SR Research Ltd., Ontario,
Canada).

Stimuli and task. The stimulus was a modified version of the classic Kanisza triangle. Six
pacman discs (radius = 1°) were arranged at the tips of an imaginary star centred on a
fixation spot. The six tips of the star were equally spaced, and the distance from the centre
of the star to the centre of each pacman was 2.1°. The fixation spot was a white circle (0.1°
diameter) and a black cross hair (stroke width = 1 pixel). The stimulus was presented on a
grey background (77.5 cd/m^2). The polarity of the inducers with respect to the background
alternated across star tips. For half the trials, the three inducers forming an upright triangle
were white, while the others were black, and for half the trials this was reversed. Inducers
had a Weber contrast of .75.

We added Gaussian noise to the stimulus on each trial to measure classification images.
Noise was 250 x 250 independently drawn luminance values with a mean of 0 and standard
deviation of 1. Each noise image was scaled without interpolation to occupy 500 x 500
pixels, such that each randomly drawn luminance value occupied 2 x 2 pixels (.05° x .05°).
The amplitude of these luminance values was then scaled to have an effective contrast of
0.125 on the display background, and were then added to the Kanizsa figure. Finally, a
circular aperture was applied to the noise to ensure the edges of the inducers were equally
spaced from the noise edge (**Fig. 1b**).

The jaw size of inducers was manipulated such that they were wider or narrower than an
equilateral triangle, which would have exactly 60° of jaw angle for all inducers. The
observer's task was to indicate whether the jaws of the attended inducers was consistent
with a triangle that was narrower or wider than an equilateral triangle. Prior to the first trial
of a block, a message on the screen indicated which set of inducers framed the "target"
triangle, and this was held constant within a block but alternated across blocks. The polarity
of the target inducers and whether the triangles were narrow or wide was pseudorandomly
assigned across trials such that an equal number of all trial types were included in each
block. The relative jaw size of attended inducers was independent of the unattended
inducers; thus, the identity of the non-target triangle was uncorrelated with the correct
response.

Each trial began with the onset of the fixation spot and a check of fixation compliance for
250 ms. Following an additional random interval (0-500 ms uniformly distributed), the
stimulus was presented for 250 ms, after which only the background was presented while
observers were given unlimited duration to report the jaw size using a button press. The
next trial would immediately follow a response. Throughout the experiment, eye tracking
was used to ensure observers did not break fixation during stimulus presentation. If gaze
position strayed from fixation by more than 2° the trial was aborted and a message was
presented instructing them to maintain fixation during stimulus presentation, and then the
trial was repeated. Such breaks in fixation were extremely rare for all participants.

A three-down one-up staircase procedure was used to progress the difficulty of the task by
varying the difference of the jaw size from 60° (i.e., from what would form an equilateral
triangle). On each trial an additional angle was randomly added or subtracted to the standard
60° inducers. The initial difference was 2°. Following three correct responses, this difference
would decrease by a step size of 0.5°, or would increase by the same amount following a
single error. When an incorrect response was followed by three correct responses (i.e., a
reversal), the step size halved. If two incorrect responses were made in a row, the step size
would double. If the step size fell below 0.05°, it would be reset to 0.2°. Blocks consisted of
624 trials which took approximately 20 minutes including a forced break. Each observer
completed 16 blocks for a total of 9984 trials, which took a total of approximately five hours
duration spread over multiple days and testing sessions. To familiarize observers with the

task, they underwent two training blocks of 624 trials each with no noise. They then were shown the stimulus with noise, and completed as many trials as they felt was required before starting the experimental blocks.

Support vector machine models. Support vector machine (SVM) classifiers were trained and tested in MATLAB. We generated (3) hypotheses by training SVM classifiers on images of the *i*) inducers, *ii*) a triangle, or *iii*) a star. We trained the classifiers using a quadratic kernel function and a least squares method of hyperplane separation. The training images consisted of two exemplars ("narrow" and "wide") with no noise. To generate hypotheses in the form of classification images, we used each of the classifiers to perform narrow/wide triangle judgements (trials = 9984), with an equilateral triangle; thus, classification was exclusively influenced by the noise in the image.

Data and statistical analysis. The 9984 noise images for a participant were separated according to perceptual report ("narrow" or "wide"). To collapse across inducer polarity, we reflected the distribution of noise on trials in which the cued inducers were white (i.e., we inverted the sign). We also collapsed across upright and inverted cue conditions by spatially flipping the noise on inverted trials. The noise values were then summed within each report type. The difference of these summed images is the raw classification image. To average across emergent triangle edges, we further summed the image with itself two times after rotating 120° and 240° using Matlab's "imrotate" function using bilinear interpolation. This procedure results in a classification image that is invariant across edges such that analysis of one edge summarises all three edges. Note that this is a conservative estimate of the classification image and any spurious structure will only be diminished. To test for correlated pixels along the illusory edge of the classification image, we extracted 18 pixels along the bottom edge of the implied triangle, but within the bounds of the implied star tip (see bottom right panel of **Fig. 2a**). To ensure that these pixels were not contaminated by averaging of nearest-neighbour pixels during rotation, described above, we excluded the three pixels closest to the inner corners of the star. We conducted a one-sample, two-tailed Bayesian and Students' T-Test on these pixel values using JASP software (JASP Team, 2017). Reported effect sizes are Cohen's d.

We performed the model comparisons in **Figure 2c** by first normalising the noise of the
mean classification image and each SVM prediction such that the sum of squared error of
each image equalled 1. We then subtracted the mean classification image from each
prediction, and found the sum of squared error of the resulting difference. Finally, we
normalised the difference scores to the model with the least error by subtracting from each
distribution the mean of the distribution with the lowest error. This process was repeated for
200 repetitions of each SVM prediction. The mixture modelling (**Fig. 3c**) was performed
similarly, but we further used Monte Carlo simulations to estimate the proportion of trials in
which a triangle was perceived. In this case, each set of 200 simulated experiments included
a proportion of triangle template trials, ranging from 0.33 (chance) to 1. We validated this
model fitting procedure by generating a simulated classification image with a known
generative template, or with proportional mixtures of templates, and then verified the model
fitting returned results that approximated the ground truth. The Monte Carlo simulations were
highly accurate for a range of simulated proportions, but slightly overestimated the
contribution of the triangle template when the ground truth contribution was close to 0.33,
and, conversely, slightly underestimated its contribution when the triangle was the only
contributor.

Data availability. The data that support the findings of this study are available from the
corresponding author upon request.

ACKNOWLEDGEMENTS
We are indebted to Peter Bex who developed the novel Kanizsa figure with us and
provided helpful feedback on our study design and results. We also thank Tom Wallis for
feedback on an earlier draft which led to the mixture modelling and overall improvements
in the manuscript. This research was supported by funding to W.J.H. from King's College
Cambridge and the National Health and Medical Research Council of Australia
(APP1091257).

AUTHOR CONTRIBUTIONS
Both authors designed the experiment and collected the data. WJH analysed the
experimental data, RR performed the SVM analyses, and both authors performed the
model comparisons. Both authors contributed equally to the writing of the manuscript.

We declare we have no competing interests.

REFERENCES

1. Kanizsa G (1976) Subjective contours. *Sci Am* 234(4):48–52.

2. Zhou H, Friedman HS, von der Heydt R (2000) Coding of border ownership in monkey visual cortex. *J Neurosci* 20(17):6594–6611.

3. Qiu FT, Sugihara T, von der Heydt R (2007) Figure-ground mechanisms provide structure for selective attention. *Nat Neurosci* 10(11):1492–1499.

4. von der Heydt R, Macuda T, Qiu FT (2005) Border-ownership-dependent tilt aftereffect. *J Opt Soc Am A Opt Image Sci Vis* 22(10):2222–2229.

5. von der Heydt R, Peterhans E, Baumgartner G (1984) Illusory contours and cortical neuron responses. *Science* 224(4654):1260–1262.

6. Mihalas S, Dong Y, von der Heydt R, Niebur E (2011) Mechanisms of perceptual organization provide auto-zoom and auto-localization for attention to objects. *Proc Natl Acad Sci U S A* 108(18):7583–7588.

7. Necker LA (1832) LXI. Observations on some remarkable optical phænomena seen in Switzerland; and on an optical phænomenon which occurs on viewing a figure of a crystal or geometrical solid. *Lond Edinb Dublin Philos Mag J Sci* 1(5):329–337.

8. Driver J, Baylis GC (1996) Edge-assignment and figure-ground segmentation in short-term visual matching. *Cognit Psychol* 31(3):248–306.

9. Rubin E (1915) *Synsoplevede Figurer. Studier i psykologisk Analyse /Visuell wahrgenommene Figuren. Studien in psychologischer Analyse [Visually perceived figures: Studies in psychological analysis]* (Gyldendalske Boghandel, Copenhagen, Denmark).

10. Wagemans J, et al. (2012) A century of Gestalt psychology in visual perception: I. Perceptual grouping and figure-ground organization. *Psychol Bull* 138(6):1172–1217.

11. Tse PU (2005) Voluntary attention modulates the brightness of overlapping transparent surfaces. *Vision Res* 45(9):1095–1098.

12. Wannig A, Stanisor L, Roelfsema PR (2011) Automatic spread of attentional response modulation along Gestalt criteria in primary visual cortex. *Nat Neurosci* 14(10):1243–1244.

13. Houtkamp R, Spekreijse H, Roelfsema PR (2003) A gradual spread of attention during mental curve tracing. *Percept Psychophys* 65(7):1136–1144.

14. McMains S, Kastner S (2011) Interactions of Top-Down and Bottom-Up Mechanisms in Human Visual Cortex. *J Neurosci* 31(2):587–597.

15. Gold JM, Murray RF, Bennett PJ, Sekuler AB (2000) Deriving behavioural receptive fields for visually completed contours. *Curr Biol* 10(11):663–666.

16. van Lier R, Vergeer M, Anstis S (2009) Filling-in afterimage colors between the lines. *Curr Biol* 19(8):R323–4.

17. Poort J, et al. (2012) The role of attention in figure-ground segregation in areas V1 and V4 of the visual cortex. *Neuron* 75(1):143–156.

18. Harrison WJ, Ayeni AJ, Bex PJ (2017) Selective attention modulates surface filling-in. *bioRxiv*. doi:10.1101/221150.

19.   Murray MM, et al. (2002) The spatiotemporal dynamics of illusory contour processing:
combined high-density electrical mapping, source analysis, and functional magnetic
resonance imaging. *J Neurosci* 22(12):5055–5073.

20.   Stanley DA, Rubin N (2003) fMRI activation in response to illusory contours and
salient regions in the human lateral occipital complex. *Neuron* 37(2):323–331.

21.   Davis G, Driver J (1994) Parallel detection of Kanizsa subjective figures in the human
visual system. *Nature* 371(6500):791–793.

22.   Mattingley JB, Davis G, Driver J (1997) Preattentive filling-in of visual surfaces in
parietal extinction. *Science* 275(5300):671–674.

23.   Brainard DH (1997) The Psychophysics Toolbox. *Spat Vis* 10(4):433–436.

24.   Cornelissen FW, Peters EM, Palmer J (2002) The Eyelink Toolbox: eye tracking with
MATLAB and the Psychophysics Toolbox. *Behav Res Methods Instrum Comput*
34(4):613–617.

25.   Pelli DG (1997) The VideoToolbox software for visual psychophysics: Transforming
numbers into movies. *Spat Vis* 10(4):437–442.

SUPPLEMENTARY FIGURES

523 **Supplementary Figure 1**. Raw classification images and psychophysical performance. a)

524 Classification images without averaging of edges via rotation. b) Threshold performance

525 across blocks shown separately for each observer. Thresholds were the midpoint of a

526 cumulative Gaussian fit to accuracy data for each session.

531 **Supplementary Figure 2**. Individual classification images revealing a potential influence

532 of non-cued structure. These images were created by summing each classification image

533 with a flipped version of itself. Note that the emergent structure aligns to the geometry of

534 the star implied by our Kanizsa figure (**Fig. 1a**).