Title: Voluntary control of illusory contour formation

Authors and affiliations: William J Harrison [1,2] & Reuben Rideaux [1]

[1] Department of Psychology, University of Cambridge
Downing Street, Cambridge CB2 3EB, UK
[2] Queensland Brain Institute, The University of Queensland
QBI Building #79, St Lucia QLD 4072, Australia

Corresponding author: William Harrison (willjharri@gmail.com)

Classification: Biological Sciences; Psychological and Cognitive Sciences

ABSTRACT

The extent to which visual appearance is shaped by attentional goals is controversial. Voluntary attention may simply modulate the priority with which information is accessed by higher cognitive functions involved in perceptual decision making. Alternatively, voluntary attention may influence fundamental visual processes, such as those involved in segmenting an incoming retinal signal into a structured scene of coherent objects, thereby determining visual appearance. Here we tested whether the segmentation and integration of visual form can be determined by an observer's goals by exploiting a novel variant of the classical Kanizsa figure. We generated predictions about the influence of attention with a machine classifier, and tested these predictions with a psychophysical response classification technique. Despite seeing the same image on each trial, observers' perception of illusory spatial structure depended on their attentional goals. These attention-contingent illusory contours directly conflicted with equally plausible visual form implied by the geometry of the stimulus, revealing that attentional selection can determine the perceived layout of a fragmented scene. Attentional goals, therefore, not only select pre-computed features or regions of space for prioritised processing, but, under certain conditions, also greatly influence perceptual organisation and thus visual appearance.

SIGNIFICANCE STATEMENT

The extent to which higher cognitive functions can influence perceptual experience is hotly debated. The role of voluntary spatial attention, the ability to focus on only some parts of a scene, has been particularly controversial among neuroscientists and psychologists who aim to uncover the basic neural computations involved in grouping image features into coherent objects. To address this issue, we repeatedly presented the same novel ambiguous image to observers and changed their attentional goals by having them make fine spatial judgements about only some elements of the image. We found that observers' attentional goals determine the perceived organisation of multiple illusory shapes. We thus reveal that voluntary spatial attention can control the fundamental processes that determine visual experience.

INTRODUCTION

The clutter inherent to natural visual environments means that goal-relevant objects often partially occlude one another. A critical function of the human visual system is to group common parts of objects while segmenting them from distracting objects and background, a process which requires interpreting an object's borders. Figures which produce illusory contours, such as the classic Kanizsa triangle (Kanizsa, 1976), have provided many insights into this problem by revealing the inferential processes made in determining figure-ground relationships. These figures give rise to a vivid percept of a shape emerging from sparse information, and thus demonstrate the visual system's ability to interpolate structure from fragmented information, to perceive edges in the absence of luminance discontinuities, and to fill-in a shape's surface properties. In the present study, we exploit these figures to investigate whether voluntary attention influences visual appearance.

Most objects can be differentiated from their backgrounds via a luminance-defined border. The visual system is tasked with allocating one side of the border to an occluding object, and the other side to the background. This computation can be performed by neurons in macaque visual area V2 whose receptive fields fall on the edge of an object (Zhou, Friedman, & von der Heydt, 2000). These "border-ownership" cells can distinguish figure from ground even when the monkey attends elsewhere in the display (Qiu, Sugihara, & von der Heydt, 2007), and psychophysical adaptation aftereffects suggest such cells also exist in humans (von der Heydt, Macuda, & Qiu, 2005). Further, neurophysiological work has revealed that V2 cells also process illusory edges (von der Heydt, Peterhans, & Baumgartner, 1984), though it is unclear whether those cells possess the same properties as border-ownership cells. These findings have contributed to the claim that visual structure is computed automatically and relatively early in the visual system, and that visual attention is guided by this pre-computed structure (Mihalas, Dong, von der Heydt, & Niebur, 2011).

It is also known, however, that visual attention can modulate the perception of figure-ground relationships of luminance-defined stimuli. As early as 1832, Necker described his ability to alter the apparent depth of an engraved crystalline form, now referred to as a Necker cube, via an overt shift of attention (Necker, 1832). More recent psychophysical work has shown that voluntary attention can alter perceived depth order (Driver & Baylis, 1996) as in the case of Rubin's face-vase illusion (Rubin, 1915)(Wagemans et al., 2012), surface transparency

(Tse, 2005), speed (Anton-Erxleben, Henrich, & Treue, 2007; Turatto, Vescovi, & Valsecchi,

2007), contrast (Carrasco, Ling, & Read, 2004; Liu, Abrams, & Carrasco, 2009; Stormer,

McDonald, & Hillyard, 2009) and spatial frequency (Abrams, Barbot, & Carrasco, 2010;

Gobell & Carrasco, 2005). Furthermore, visual attention has been shown to facilitate visual

grouping according to Gestalt rules at both the neurophysiological (Wannig, Stanisor, &

Roelfsema, 2011) and behavioural (Barbot, Liu, Kimchi, & Carrasco, 2018; Houtkamp,

Spekreijse, & Roelfsema, 2003) level. For instance, Barbot et al. (2018) found that the

apparent perceptual organization of luminance defined multielement arrays is either

intensified or attenuated by the presence or absence of covert attention, respectively. These

findings raise the possibility that, regardless of whether it is necessary, visual attention may

play a determining role in visual appearance under certain conditions. However, because

these previous studies involved physically defined stimuli, it remains unclear whether visual

attention simply modulates pre-attentively computed structure as suggested by

neurophysiological work (McMains & Kastner, 2011; Qiu et al., 2007), or whether structural

computations depend on the state of attention. Rivalrous illusory figures are perfectly suited

to address this issue: if attending to one illusory figure results in illusory contours that directly

conflict with the form of another illusory figure, then structural computations must depend

on attention.

To investigate the influence of voluntary attention on visual appearance, here we combined

a novel illusory figure with an attentionally demanding task, exploiting human observers'

propensity to use illusory edges when making perceptual decisions (Gold, Murray, Bennett,

& Sekuler, 2000). We developed a novel Kanizsa figure (**Fig. 1a**), in which "pacman" discs

are arranged at the tips of an imaginary star. This figure includes multiple Gestalt cues that

promote the segmentation and integration of various forms not defined by the physics of the

stimulus. We predict that, because some of these cues suggest competing configurations,

selective attention can bias which figure elements are assigned to figure and which to

ground. Although such a hypothesis is relatively uncontroversial, the critical question is

whether grouping via selective attention promotes illusory contour formation in direct conflict

with competing implied form. For example, while the black inducers of **Figure 1a** form part

of an implied star, in isolation the black inducers imply an illusory triangle that competes with

both the star form as well as a second illusory triangle implied by the white inducers. The

dependence of such perceptual organisation on voluntary attentional selection thus can

reveal the extent of top-down processing on visual appearance. We therefore assessed
whether the apparent organisation of the figure is determined by which inducers are
attended.
99

Figure 1. Novel illusory figure and design used to test the influence of attention on perceptual organisation. a)
Our variant of the classic Kanizsa figure. "Pacman" inducers are arranged such that a star appears to occlude
black and white discs. Whereas the ensemble of features may produce the appearance of a star, grouping
features by polarity leads to competing illusory triangles. We test whether attending to one set of inducers (e.g.
the white inducers) leads to interpolation of the illusory edge. b) Example trial sequence. After an observer
fixates a spot, the illusory figure with overlaid Gaussian noise is displayed for 250ms. The observer's task was
to report whether the tips of the upright or inverted triangle were narrower or wider than an equilateral triangle.
The target triangle was cued prior to, and held constant throughout, each testing block. The observer's
perceptual reports were then correlated with the noise on each trial to produce classification images. (c - e)
Support vector machine (SVM) classifier images. We had a SVM classifier perform "narrow" vs "wide" triangle
judgements after training it on three different protocols: (c) inducers, a (d) triangle, or a (e) star (see Methods).
Dashed red lines show the location of a pacman for reference, and in (e) the tips of the star that do not influence
classification.
114

RESULTS
We used a response classification technique that allowed us to simultaneously assess
where observers' attention was allocated, and whether such attentional allocation resulted
in visual interpolation of illusory edges. At the beginning of each block of testing, observers

were cued to report the relative jaw size of the inducers forming an upright (or inverted)

triangle, corresponding to the white (or black) elements in **Figure 1a**. By adding random

visual noise to the target image on each trial (**Fig. 1b**), we could use reverse correlation to

measure "classification images". An observer's classification image quantifies a correlation

between each pixel in the image and the perceptual report revealing which spatial structures

are used for perceptual decisions (Abbey, Eckstein, & Bochud, 1999; A. J. . J. Ahumada,

Beard, & Ellis, 1997; A. J. Ahumada, 1996; A. Ahumada & Lovell, 1971; Beard & Ahumada,

Jr., 1998; Gold et al., 2000).

We generated hypotheses regarding how observers' voluntary attention may influence their

perception of this figure. We used a support vector machine (SVM) classifier to judge small

changes to a triangle image after training it on one of three different protocols (**Supp. Fig.**

1). First, we generated a prediction of the hypothesis that observers can attend to the correct

inducers, but do not perceive illusory edges, by training a model to discriminate only the

jaws of the inducers. This model is analogous to that of an ideal observer and reveals that

only structure at the edges of the stimuli are used in generating a response (**Fig. 1c**). We

next generated predictions of how illusory edges could be interpolated in this task. In one

case, we assumed illusory contours would be formed between attended inducers. We thus

trained the classifier to discriminate whether a triangle's edges were bent outward or inward,

and found a classification image approximating a triangle (**Fig. 1d**). In the other case, we

assumed that, although selective attention may guide the correct perceptual decision, the

illusory form of a star may be determined pre-attentively according to the physical structure

of the entire stimulus. In this case, we trained the classifier to discriminate whether

alternating tips of a star, i.e., the tips corresponding to a set of cued inducers, were relatively

wide or narrow. The resulting classification image reveals edges that are interpolated

beyond the inducers, but that they do not extend beyond the alternating star tips (**Fig. 1e**).

These predictions not only provide qualitative comparisons for our empirical data, but they

also allow us to formally test which training regime produces a classification image that most

closely resembles human data.

To motivate observers to attend to only one possible configuration of the illusory figure, they

were cued to report the relative jaw size ("narrow" or "wide") of only a subset of pacmen

positioned at the tips of an imaginary star (**Fig. 1a**). Specifically, observers were instructed

to report only the jaw size of inducers forming an upward (or downward) triangle within a
testing block. The non-cued inducer jaws varied independently of the cued inducers and
thus added no information regarding the correct response. To derive the spatial structure
used for perceptual decisions, we added Gaussian noise to each trial and classified each
noise image according to the observers' responses (**Fig. 1b**). To create the classification
image for each observer, we summed all noise images for narrow reports and subtracted
the sum of all noise images for wide reports (see Methods). We collapsed across inducer
polarity by inverting the noise on trials in which the white inducers were cued, and across
cue direction by flipping the noise on trials in which the downward facing illusory triangle
was cued. The resulting images quantify the correlation between each stimulus pixel and
the observer's report. In order to analyse a single axis of emergent spatial structure, we first
averaged each observer's data with itself after rotating 120° and 240° such that correlations
were averaged over the three sides of the triangle. Although this step involved bilinear
interpolation of neighbouring pixels, no other averaging or smoothing was performed, and
this averaging is therefore most likely to only reduce the strength of emergent illusory
structure.

Classification images for three observers and their mean are shown in **Figure 2a** (see **Supp.**
Fig. 2a for unrotated classification images). Images are normalised to the "attend upright
black inducers" condition; black pixels indicate locations where dark and light noise was
correlated with narrow and wide judgements, respectively, and white pixels indicate the
opposite relationship. There are two obvious patterns that emerge. First, it is clear that
observers based their reports on pixels within the jaws of the cued inducers, indicating that
only some regions of the image – those aligned with the attended inducers – influenced
perceptual decisions. Note the difference in the sign of the correlation between the edges
and tips of the triangle – noise pixels in these regions have the opposite influence on
narrow/wide decisions, which is likely due to an illusory widening of the jaw centre which is
not registered by the SVM (cf. **Fig. 1d**). Second, the edges clearly extend beyond the red
inducer outline shown in the mean image, revealing observers' reports were influenced by
illusory contours. However, it is also apparent that the spatial structure is non-uniform, with
weaker correlations in the centre of the illusory edges than in the corners of the inducers.
We therefore quantitatively test the extent of illusory contour formation below.

To test whether the illusory edge interpolation extended into the region of the implied

competing figure, we performed two analyses. First, we used Bayesian and Students' one-

sampled t-tests to assess the pixel values along the edge of the triangle implied by the

attended inducers (see red line in **Fig. 2a**). We selected only pixels that fell within the bounds

of the competing implied triangle (see Methods and grey shaded regions of **Fig. 2b**), and

found that these 18 pixels were below zero for the naïve participant (mean and sem: $-3 \pm .9$

x 10^{-3}, BF_{10}=18.365, $t(17)$=3.585, p=0.002, d = 0.845), observer A2 (mean and sem: $-5 \pm .7$

x 10^{-3}, BF_{10}=8,141.356, $t(17)$=6.944, p<0.001, d = 1.637), and the group (mean and sem: -

$3 \pm .4$ x 10^{-3}, BF_{10}=16,580, $t(17)$ = 7.38, p<0.001, d = 1.738), but not for A1 (mean and sem:

-1 ± 1 x 10^{-3}, BF_{10}=0.431, $t(17)$=1.15, p=0.266, d = 0.204). The lack of a difference in

observer A1 may be due to a difference in task related strategy and or increased lapse rate.

Figure 2. Classification image results. a) The individual and average classification images, normalized to the "attend upright black inducers" condition. Black pixels indicate locations where dark and light noise was correlated with narrow and wide judgements, respectively, and white pixels indicate the opposite relationship, after 9984 trials per participant. Data have not been smoothed, but were first averaged across triangle edges and cropped to be 122x122 pixels. In the mean image, a pacman outline is shown for reference, and a red line indicates the spatial range of the implied triangle edge (from which data in (b) are shown). b) Pixel values along the illusory edge. The grey shaded region corresponds to a conservative estimate of the extent of a gap in the edge that would appear if observers necessarily saw a star shape (e.g. Fig. 1e). The blue shaded region in the mean plot shows ±one standard error; asterisks indicate differences from zero ($BF_{10} > 10$ and $p < 0.05$; see text). N1 is the naïve participant; A1 and A2 are authors. c) Comparison of SVM models for averaged data. Distributions show comparisons of the mean classification image to the output of each SVM prediction, repeated 200 times. Data points and error bars represent the mean and 95% confidence intervals, respectively, for each SVM training regime. Model error has been normalised relative to the model with the least error, which is the model in which the SVM is trained to perceive a triangle within the attended inducers. d) Comparison of SVM models for each observer. Colours are as per panel (c).

We next quantified the spatial structure content of the classification image by testing which prediction generated by the SVM was most similar to the human data (see **Fig. 1c-e**). For each model, we generated 200 predictions, each with a unique distribution of noise, and

computed the sum of squared errors between predictions and the mean classification image produced by the human observers (see Materials and Methods). The resulting distributions of error, normalised to the best model, are shown in **Figure 2c**, and reveal that the model in which we trained the classifier to perceive a complete triangle is the best fit to the data (z-test comparing the mean error for the star SVM versus the distribution of error for the triangle or inducer SVM: p's < 0.0001). The pattern of results was the same for all observers (Fig. 2d), though there was no significant difference between the triangle and star models for A1. Taken together, these analyses thus reveal illusory contour formation between attended visual elements, and this interpolation occurred despite the contour conflicting with equally plausible implied spatial structure.

We next tested the spatial specificity of illusory contour formation. For the two participants who showed a clear effect, we tested how spatially specific visual interpolation was by repeating the same analysis as above but for the row of pixels above and below the triangle boundary implied by the geometry of the attended inducers. Quite surprisingly, we found good evidence that there was an absence of illusory contour formation for the pixels below the implied triangle boundary (N1: $BF_{01} = 3.19$; A2: $BF_{01} = 3.31$), and equivocal evidence for the pixels above the implied triangle boundary (N1: $BF_{10} = 1.05$; A2: $BF_{01} = 1.83$). These results thus reveal that the strength of illusory contours was highly precisely aligned to the geometry of the triangle implied by the attended inducers. Consistent with this observation, psychophysical thresholds for identifying the relative inducer jaw size were reliably highly precise across testing sessions (see **Supp. Fig. 2b**). Across sessions, the mean thresholds (±one standard error) for observer N1, A1, and A2, were 0.86 ± .03, 0.84 ± .02, and 0.66 ± .03.

Our data further address the extent to which the non-cued figural elements may have influenced perceptual judgements. In our experiment, the non-cued inducer jaw size was independent of the cued inducer jaw size, and was thus uninformative of the correct report. Indeed, we found no evidence in the classification image that observers' perceptual decisions were guided by these task-irrelevant cues. We modelled the possibility that these non-cued elements were nonetheless grouped to form a star. In such a case where a star was perceived, the task could still be performed accurately were observers to base their reports on only the edges shared by the star and the triangle implied by the cued inducers.

As expected, the SVM prediction of pre-attentive figure-ground segmentation shows gaps

in the sides of the classification image triangle (**Fig 1e**). Note that this model is equivalent

to observers having perceived a whole star, but with a later stage attentional signal focussed

on only some regions of the pre-computed figure. Because we designed our illusory figure

to be geometrically invertible, the extent of the illusory star form is pronounced if we sum

the model's classification image with a flipped version of itself (**Fig. 3a**). In **Figure 3b**, we

show the result of performing this step with the observers' average classification image.

Very similar patterns of results were found for all individual images (**Supp. Fig. 3**). This

result is strikingly similar to the SVM prediction, revealing that the changes in strength of

edges of the illusory form are near-perfectly aligned with the geometry of the implied star or

non-cued illusory triangle, i.e., the strength of the lines appears to reduce precisely at the

point of intersection (**Fig. 1e**). These qualitative results, however, are in contrast to the SVM

analysis, presented above, in which we found that correlated noise in observers'

classification images is best explained by observers having attended to the cued triangle.

Thus, a remaining critical question, which we address below, is whether we can quantify the

proportion of trials in which observers relied on different forms implied by the inducers.

Figure 3. Pre-attentive grouping. a) Geometric form prediction of unattended grouping. The classification

image derived from our SVM was summed with a flipped version of itself. Note that the inner corners of the

star are well aligned due to the design of our original Kanizsa figure. b) Geometric form in observers' data.

The mean classification image was summed with a flipped version of itself, and reveals the strength of

illusory edges are well aligned to the implied star. c) Results of mixture modelling used to explore the

correspondence between fluctuations of illusory edge strength and implied figure geometry. The best fitting

model for each observer was one in which attention determined perceptual outcome in 84% of trials. The

dashed line indicates the proportion expected from a purely stochastic process. Error bars show 95%

confidence intervals.

There are at least three possible explanations for the near-perfect alignment of changes in

illusory edge strength with the implied star figure (**Fig. 3b**). First, a similar classification

image would have been obtained had observers perceived a star on every trial, a possibility

which we discounted in the results described above. Second, this qualitative result could be

generated if trial-by-trial perceptual organisation was stochastic, such that observers

perceived each possible configuration approximately equally often across trials. Under this

hypothesis, the resulting illusory contours shown in **Figure 2a** are incidental rather than

being determined by observers' attentional goals. The third possible explanation is that

observers' voluntary allocation of attention determined the outcome on most, but not all,

trials. To distinguish between the two latter possibilities, we used mixture modelling to

quantify the proportion of trials in which observers' percept depended on attentional

instructions (see Materials and Methods). A purely stochastic process would be implied were

the proportion of trials accounted for by the triangle template no different from 0.33 (i.e. the

apparent top-most surface was equally often a star, the cued triangle, or the non-cued

triangle, see **Fig. 1c-e**). However, in the best fitting model, the attention-contingent triangle

template contributed to 84% of trials on average, which is much greater than expected by a

stochastic process (**Fig. 3c**). At the individual level, the triangle contributions (and 95%

confidence intervals) for N1, A1, and A2 were 88% (45% - 100%), 79% (39% - 99.5%), and

86% (50.5% - 100%), respectively. This mixture modelling is thus consistent with observers'

attentional goals determining illusory contour interpolation on the vast majority of trials.

DISCUSSION

We used classification images to address whether voluntary attention determines a scene's

apparent visual structure. Using a psychophysical response classification paradigm we

tested which of three competing model predictions best describes the influence of attention

on illusory contour formation. Our results clearly show that voluntary attention can guide

the fundamental processes involved in perceptual organisation, thus determining visual

appearance.

Unlike previous studies that show visual attention modulates the appearance of physically

defined surfaces (e.g., attending to different surfaces of the Necker cube (Necker, 1832)),

our study shows a rich interaction between attention and endogenously generated percepts.

Classification images reveal the spatial location of noise elements that influence observers'

responses, whereas interpreting subjective phenomenology is more difficult. However, given

that the illusory edges of the triangle implied by the attended inducers directly conflict with

the regions of the competing implied figures (i.e., the star and inverted triangle), our finding

that illusory edges were interpolated between attended inducers reveals that attention can

determine depth order, even when figures and ground are illusory. Spatial structure is thus

computed by neural operations that are at least partially contingent on the voluntary state of

the observer. The precision of illusory contours was nonetheless tightly aligned to the

geometry of luminance defined structure, indicating these inferential processes are also

highly contingent on scene or task context. Indeed, observers' psychophysical thresholds

for the inducer task reveal a correspondence between their precise objective psychophysical

performance and subjective classification image.

We were able to quantify the influence of non-cued stimuli on perception by measuring a

classification image across the entire stimulus. We found that changes in the strength of

illusory contour formation between attended inducers were aligned with form implied by the

non-cued inducers. Our mixture modelling suggests that the non-cued stimuli influenced

performance on approximately 16% of trials. Such a contribution of task-irrelevant features

on perceptual decisions could be attributed to lapses in attentional allocation, or variability
in the feed-forward processing of the incoming signal. Measuring perceived form in the
absence of visual attention is notoriously difficult (Wagemans et al., 2012), which is perhaps
one reason why many studies of figure-ground organisation rely on single-unit recordings.
Whereas neurophysiological recordings have revealed the brain regions involved in
perceptual organisation, they have left open the question of perceptual phenomena. Our
data show that the influence of attention on perception is constrained by task-irrelevant
information, providing yet further evidence that visual experience is the combination of both
bottom-up and top-down processes. This conclusion sheds light on previous work in which
competing colour adaptation after-effects are biased according to alternating illusory
contours at a similar location (van Lier, Vergeer, & Anstis, 2009). In these demonstrations,
the onset of inducer elements likely attracts an observer's attention, resulting in perceptual
completion processes specific to only the implied shape of attended elements. Surface
filling-in would then follow the contours of the implied form (Poort et al., 2012). Indeed, other
recent research from our lab reveals similar interactions may occur between attention and
surface filling-in (Harrison, Ayeni, & Bex, 2017).
344
The influence of attention on figure-ground segmentation may be explained by feedback
signals from the lateral occipital complex (Murray et al., 2002; Stanley & Rubin, 2003) that
could act as early as V1 (Wannig et al., 2011), but also may involve modulating responses
of border-ownership cells in V2 (Qiu et al., 2007). Border-ownership cells indicate which side
of a border is an object versus ground. Previous work showing the activity of border-
ownership cells is modulated by visual attention (Qiu et al., 2007) has been limited to
luminance-defined borders. Our finding that information inferred by the visual system is
influenced by voluntary attention suggests that attentional modulation of border-ownership
may similarly apply to illusory contours (von der Heydt et al., 1984). Early psychophysical
work suggested that illusory contours are perceived in the absence of attention (Davis &
Driver, 1994; Mattingley, Davis, & Driver, 1997), but did not address the question of whether
illusory contours can be formed *because* of voluntary attention, which we have shown here.
Our findings are also distinct from other recent work that found attention can influence the
appearance of existing surfaces (Tse, 2005). In our study, visual attention had a causal role
in forming the structure from which perceptual decisions were made. We anticipate that our
simple stimulus and task design may prove to be a useful neurophysiological assay to test

further the neural substrates governing the interaction between voluntary attention and
perceptual organisation.

MATERIALS AND METHODS

Observers. Three healthy subjects, one naïve (N1) and two authors (A1 & A2 corresponding
to authors RR and WH, respectively), gave their informed written consent to participate in
the project, which was approved by the University of Cambridge Psychology Research
Ethics Committee. All procedures were in accordance with approved guidelines. Simulations
were run to determine an appropriate number of trials per participant to ensure sufficient
statistical power, and our total sample is similar to those generally employed for
classification images. All participants had normal vision.

Apparatus. Stimuli were generated in MATLAB (The MathWorks, Inc., Matick, MA) using
Psychophysics Toolbox extensions (Brainard, 1997; Cornelissen, Peters, & Palmer, 2002;
Pelli, 1997). Stimuli were presented on a calibrated ASUS LCD monitor (120Hz,
1920×1200). The viewing distance was 57 cm and participants' head position was stabilized
using a head and chin rest (43 pixels per degree of visual angle). Eye movement was
recorded at 500Hz using an EyeLink 1000 (SR Research Ltd., Ontario, Canada).

Stimuli and task. The stimulus was a modified version of the classic Kanisza triangle. Six
pacman discs (radius = 1°) were arranged at the tips of an imaginary star centred on a
fixation spot. The six tips of the star were equally spaced, and the distance from the centre
of the star to the centre of each pacman was 2.1°. The fixation spot was a white circle (0.1°
diameter) and a black cross hair (stroke width = 1 pixel). The stimulus was presented on a
grey background (77.5 cd/m^2). The polarity of the inducers with respect to the background
alternated across star tips. For half the trials, the three inducers forming an upright triangle
were white, while the others were black, and for half the trials this was reversed. Inducers
had a Weber contrast of .75.

We added Gaussian noise to the stimulus on each trial to measure classification images.
Noise was 250 x 250 independently drawn luminance values with a mean of 0 and standard
deviation of 1. Each noise image was scaled without interpolation to occupy 500 x 500
pixels, such that each randomly drawn luminance value occupied 2 x 2 pixels (.05° x .05°).

The amplitude of these luminance values was then scaled to have an effective contrast of 0.125 on the display background, and were then added to the Kanizsa figure. Finally, a circular aperture was applied to the noise to ensure the edges of the inducers were equally spaced from the noise edge (**Fig. 1b**).

The jaw size of inducers was manipulated such that they were wider or narrower than an equilateral triangle, which would have exactly 60° of jaw angle for all inducers. The observer's task was to indicate whether the jaws of the attended inducers was consistent with a triangle that was narrower or wider than an equilateral triangle. Prior to the first trial of a block, a message on the screen indicated which set of inducers framed the "target" triangle, and this was held constant within a block but alternated across blocks. The polarity of the target inducers and whether the triangles were narrow or wide was pseudorandomly assigned across trials such that an equal number of all trial types were included in each block. The relative jaw size of attended inducers was independent of the unattended inducers; thus, the identity of the non-target triangle was uncorrelated with the correct response.

Each trial began with the onset of the fixation spot and a check of fixation compliance for 250 ms. Following an additional random interval (0-500 ms uniformly distributed), the stimulus was presented for 250 ms, after which only the background was presented while observers were given unlimited duration to report the jaw size using a button press. The next trial would immediately follow a response. Throughout the experiment, eye tracking was used to ensure observers did not break fixation during stimulus presentation. If gaze position strayed from fixation by more than 2° the trial was aborted and a message was presented instructing them to maintain fixation during stimulus presentation, and then the trial was repeated. Such breaks in fixation were extremely rare for all participants.

A three-down one-up staircase procedure was used to progress the difficulty of the task by varying the difference of the jaw size from 60° (i.e., from what would form an equilateral triangle). On each trial an additional angle was randomly added or subtracted to the standard 60° inducers. The initial difference was 2°. Following three correct responses, this difference would decrease by a step size of 0.5°, or would increase by the same amount following a single error. When an incorrect response was followed by three correct responses (i.e., a

reversal), the step size halved. If two incorrect responses were made in a row, the step size
would double. If the step size fell below 0.05°, it would be reset to 0.2°. Blocks consisted of
624 trials which took approximately 20 minutes including a forced break. Each observer
completed 16 blocks for a total of 9984 trials, which took a total of approximately five hours
duration spread over multiple days and testing sessions. To familiarize observers with the
task, they underwent two training blocks of 624 trials each with no noise. They then were
shown the stimulus with noise, and completed as many trials as they felt was required before
starting the experimental blocks.

Support vector machine models. Support vector machine (SVM) classifiers were trained
and tested in MATLAB. We generated (3) hypotheses by training SVM classifiers on images
of the *i*) inducers, *ii*) a triangle, or *iii*) a star. We trained the classifiers using a quadratic
kernel function and a least squares method of hyperplane separation. The training images
consisted of two exemplars ("narrow" and "wide") with no noise (**Supp. Fig. 1**). To generate
hypotheses in the form of classification images, we used each of the classifiers to perform
narrow/wide triangle judgements (trials = 9984), with an equilateral triangle; thus,
classification was exclusively influenced by the noise in the image.

Data and statistical analysis. The 9984 noise images for a participant were separated
according to perceptual report ("narrow" or "wide"). To collapse across inducer polarity, we
reflected the distribution of noise on trials in which the cued inducers were white (i.e., we
inverted the sign). We also collapsed across upright and inverted cue conditions by spatially
flipping the noise on inverted trials. The noise values were then summed within each report
type. The difference of these summed images is the raw classification image. Thus, images
are normalised to the "attend upright black inducers" condition; black pixels indicate
locations where dark and light noise was correlated with narrow and wide judgements,
respectively, and white pixels indicate the opposite relationship. To average across
emergent triangle edges, we further summed the image with itself two times after rotating
120° and 240° using Matlab's "imrotate" function using bilinear interpolation. This procedure
results in a classification image that is invariant across edges such that analysis of one edge
summarises all three edges. Note that this is a conservative estimate of the classification
image and any spurious structure will only be diminished. To test for correlated pixels along
the illusory edge of the classification image, we extracted 18 pixels along the bottom edge

of the implied triangle, but within the bounds of the implied star tip (see bottom right panel of **Fig. 2a**). To ensure that these pixels were not contaminated by averaging of nearest-neighbour pixels during rotation, described above, we excluded the three pixels closest to the inner corners of the star. We conducted a one-sample, two-tailed Bayesian and Students' T-Test on these pixel values using JASP software (JASP Team, 2017). Reported effect sizes are Cohen's d.

We performed the model comparisons in **Figure 2c** by first normalising the noise of the mean classification image and each SVM prediction such that the sum of squared error of each image equalled 1. We then subtracted the mean classification image from each prediction, and found the sum of squared error of the resulting difference. Finally, we normalised the difference scores to the model with the least error by subtracting from each distribution the mean of the distribution with the lowest error. This process was repeated for 200 repetitions of each SVM prediction. The mixture modelling (**Fig. 3c**) was performed similarly, but we further used Monte Carlo simulations to estimate the proportion of trials in which a triangle was perceived. In this case, each set of 200 simulated experiments included a proportion of triangle template trials, ranging from 0.33 (chance) to 1. We validated this model fitting procedure by generating a simulated classification image with a known generative template, or with proportional mixtures of templates, and then verified the model fitting returned results that approximated the ground truth. The Monte Carlo simulations were highly accurate for a range of simulated proportions, but slightly overestimated the contribution of the triangle template when the ground truth contribution was close to 0.33, and, conversely, slightly underestimated its contribution when the triangle was the only contributor.

Data availability. The data that support the findings of this study are available from the corresponding author upon request.

ACKNOWLEDGEMENTS

We are indebted to Peter Bex who developed the novel Kanizsa figure with us and provided helpful feedback on our study design and results. We also thank Tom Wallis for feedback on an earlier draft which led to the mixture modelling and overall improvements in the manuscript. This research was supported by funding to W.J.H. from King's College

Cambridge and the National Health and Medical Research Council of Australia
(APP1091257).

AUTHOR CONTRIBUTIONS

Both authors designed the experiment and collected the data. WJH analysed the

experimental data, RR performed the SVM analyses, and both authors performed the model

comparisons. Both authors contributed equally to the writing of the manuscript.

We declare we have no competing interests.

REFERENCES

1. Kanizsa G (1976) Subjective contours. *Sci Am* 234(4):48–52.

2. Zhou H, Friedman HS, von der Heydt R (2000) Coding of border ownership in monkey visual cortex. *J Neurosci* 20(17):6594–6611.

3. Qiu FT, Sugihara T, von der Heydt R (2007) Figure-ground mechanisms provide structure for selective attention. *Nat Neurosci* 10(11):1492–1499.

4. von der Heydt R, Macuda T, Qiu FT (2005) Border-ownership-dependent tilt aftereffect. *J Opt Soc Am A Opt Image Sci Vis* 22(10):2222–2229.

5. von der Heydt R, Peterhans E, Baumgartner G (1984) Illusory contours and cortical neuron responses. *Science* 224(4654):1260–1262.

6. Mihalas S, Dong Y, von der Heydt R, Niebur E (2011) Mechanisms of perceptual organization provide auto-zoom and auto-localization for attention to objects. *Proc Natl Acad Sci U S A* 108(18):7583–7588.

7. Necker LA (1832) LXI. Observations on some remarkable optical phænomena seen in Switzerland; and on an optical phænomenon which occurs on viewing a figure of a crystal or geometrical solid. *Lond Edinb Dublin Philos Mag J Sci* 1(5):329–337.

8. Driver J, Baylis GC (1996) Edge-assignment and figure-ground segmentation in short-term visual matching. *Cognit Psychol* 31(3):248–306.

9. Rubin E (1915) *Synsoplevede Figurer. Studier i psykologisk Analyse /Visuell wahrgenommene Figuren. Studien in psychologischer Analyse [Visually perceived figures: Studies in psychological analysis]* (Gyldendalske Boghandel, Copenhagen, Denmark).

10. Wagemans J, et al. (2012) A century of Gestalt psychology in visual perception: I. Perceptual grouping and figure-ground organization. *Psychol Bull* 138(6):1172–1217.

11. Tse PU (2005) Voluntary attention modulates the brightness of overlapping transparent surfaces. *Vision Res* 45(9):1095–1098.

12. Wannig A, Stanisor L, Roelfsema PR (2011) Automatic spread of attentional response modulation along Gestalt criteria in primary visual cortex. *Nat Neurosci* 14(10):1243–1244.

13. Houtkamp R, Spekreijse H, Roelfsema PR (2003) A gradual spread of attention during mental curve tracing. *Percept Psychophys* 65(7):1136–1144.

14. McMains S, Kastner S (2011) Interactions of Top-Down and Bottom-Up Mechanisms in Human Visual Cortex. *J Neurosci* 31(2):587–597.

15. Gold JM, Murray RF, Bennett PJ, Sekuler AB (2000) Deriving behavioural receptive fields for visually completed contours. *Curr Biol* 10(11):663–666.

16. van Lier R, Vergeer M, Anstis S (2009) Filling-in afterimage colors between the lines. *Curr Biol* 19(8):R323–4.

17. Poort J, et al. (2012) The role of attention in figure-ground segregation in areas V1 and V4 of the visual cortex. *Neuron* 75(1):143–156.

18. Harrison WJ, Ayeni AJ, Bex PJ (2017) Selective attention modulates surface filling-in. *bioRxiv*. doi:10.1101/221150.

19. Murray MM, et al. (2002) The spatiotemporal dynamics of illusory contour processing:
combined high-density electrical mapping, source analysis, and functional magnetic
resonance imaging. *J Neurosci* 22(12):5055–5073.

20. Stanley DA, Rubin N (2003) fMRI activation in response to illusory contours and
salient regions in the human lateral occipital complex. *Neuron* 37(2):323–331.

21. Davis G, Driver J (1994) Parallel detection of Kanizsa subjective figures in the human
visual system. *Nature* 371(6500):791–793.

22. Mattingley JB, Davis G, Driver J (1997) Preattentive filling-in of visual surfaces in
parietal extinction. *Science* 275(5300):671–674.

23. Brainard DH (1997) The Psychophysics Toolbox. *Spat Vis* 10(4):433–436.

24. Cornelissen FW, Peters EM, Palmer J (2002) The Eyelink Toolbox: eye tracking with
MATLAB and the Psychophysics Toolbox. *Behav Res Methods Instrum Comput*
34(4):613–617.

25. Pelli DG (1997) The VideoToolbox software for visual psychophysics: Transforming
numbers into movies. *Spat Vis* 10(4):437–442.

SUPPLEMENTARY FIGURES

Supplementary Figure 1. Support vector machine (SVM) images. From left to right, the

first two columns show examples of wide and narrow exemplar images used to train the

SVM in the inducers, triangle, and star protocols. The column on the right shows examples

of the test image for each protocol.

Supplementary Figure 2. Raw classification images and psychophysical performance. a)

Classification images without averaging of edges via rotation. Note that the individual

images show varying degrees of a complete triangle. One explanation for this is that

observers perceived a partial shape, e.g., a single or pair of unconnected lines between

the cued inducers. Given the strength of the Kanizsa illusion in producing the percept of a

triangle, rather than a partial shape, a more likely explanation is that observers perceived a

triangle, but only used part of this triangle to perform the task. b) Threshold performance

across blocks shown separately for each observer. Thresholds were the midpoint of a

cumulative Gaussian fit to accuracy data for each session.

Supplementary Figure 3. Individual classification images revealing a potential influence
of non-cued structure. These images were created by summing each classification image
with a flipped version of itself. Note that the emergent structure aligns to the geometry of
the star implied by our Kanizsa figure (**Fig. 1a**).