GrandPrix: Scaling up the Bayesian GPLVM for single-cell data

Sumon Ahmed[1], Magnus Rattray[1] and Alexis Boukouvalas[1]

[1]Division of Informatics, Imaging and Data Sciences Faculty of Biology, Medicine and Health
University of Manchester
December 1, 2017

Abstract

Motivation: The Gaussian Process Latent Variable Model (GPLVM) is a popular approach for dimensionality reduction of single-cell data and has been used for pseudotime estimation with capture time information. However current implementations are computationally intensive and will not scale up to modern droplet-based single-cell datasets which routinely profile many tens of thousands of cells.
Results: We provide an efficient implementation which allows scaling up this approach to modern single-cell datasets. We also generalize the application of pseudotime inference to cases where there are other sources of variation, such as branching dynamics. We applied our method on microarray, nCounter, RNA-seq, qPCR and droplet-based datasets from different organisms. The model converges an order of magnitude faster compared to existing methods whilst achieving similar levels of estimation accuracy. Further, we demonstrate the flexibility of our approach by extending the model to higher-dimensional latent spaces that can be used to simultaneously infer pseudotime and other structure such as branching. Thus, the model has the capability of producing meaningful biological insights about cell ordering as well as cell fate regulation.
Availability: Software available at github.com/ManchesterBioinference/GrandPrix.

1 Introduction

The analysis of single-cell genomics data promises to reveal novel states of complex biological processes, but is challenging due to inherent biological and technical noise. It is often useful to reduce high-dimensional single-cell gene expression profiles into a low-dimensional latent space capturing major sources of inter-cell variation in the data. Popular methods for dimensionality reduction applied to single-cell data include linear methods such as Principal and Independent Components Analysis (P/ICA) (Trapnell *et al.*, 2014; Ji and Ji, 2016) and nonlinear techniques such as t-stochastic neighborhood embedding (t-SNE) (Becher *et al.*, 2014), diffusion maps (Haghverdi *et al.*, 2015, 2016) and the Gaussian Process Latent Variable Model (GPLVM) (Buettner and Theis, 2012; Buettner *et al.*, 2015). In some cases the dimension is reduced to a single *pseudotime* dimension representing the trajectory of cells undergoing some dynamics process such as differentiation or cell division. The pseudotemporal ordering of cells is based on the principle that cells represent a time series where each cell corresponds to distinct time points along the pseudotime trajectory, corresponding to progress through a process of interest. The trajectory may be linear or branching depending on the underlying process.

Different formalisms can be used to represent a pseudotime trajectory. In graph-based methods such as Monocle (Trapnell *et al.*, 2014), Wanderlust (Bendall *et al.*, 2014), Waterfall (Shin *et al.*, 2015) and TSCAN (Ji and Ji, 2016), a simplified graph or tree is estimated. By using different path-finding algorithms, these methods try to find a path through a series of nodes. These nodes can correspond to individual cells (Trapnell *et al.*, 2014; Bendall *et al.*, 2014) or group of cells (Shin *et al.*, 2015; Ji and Ji, 2016) in the graph. SCUBA (Marco *et al.*, 2014) uses curve fitting to characterize the pseudotime trajectory. Principal curves are used to model the trajectory and each cell is assigned a pseudotime according to its low-dimensional projection on the principal curves. On the other hand, in the diffusion pseudotime (DPT) framework (Haghverdi *et al.*, 2016), there is no initial dimension reduction. DPT uses random walk based inference where all the diffusion components are used to infer pseudotime.

One major drawback of the above methods is the absence of an explicit probabilistic framework. They only provide a single point estimate of pseudotime, concealing the impact of biological and technical variability. Thus, the inherent uncertainty associated with pseudotime estimation is not propagated to the downstream analysis and its consequences remain unknown. However, the robustness of the estimated pseudotime for these models can be examined by re-estimating the pseudotimes multiple times under different initial conditions, parameter settings or samples of the original data. Campbell and Yau (2016) have examined the pseudotime estimation of Monocle where they have taken multiple random subsets of data and re-estimated the pseudotimes for each of them. They have shown that the pseudotime points assigned by Monocle for the same cell can vary significantly across the random subsets taken. This uncertainty in pseudotime assignment motivates the use of probabilistic analysis techniques. The GPLVM is a non-linear probabilistic model for dimension reduction and has been used extensively to analyze single-cell data. Buettner and Theis (2012) used the GPLVM as a tool of non-linear dimension reduction to analyze the complex interactions among differentiating cells. Buettner *et al.* (2015) used the GPLVM to identify subpopulations of cells where the algorithm was also dealt with confounding factors such as cell cycle. More recently, Bayesian versions of the GPLVM have been used to model pseudotime uncertainty. Campbell and Yau (2016) have proposed a method using the GPLVM to model pseudotime trajectories as latent variables. They used Markov Chain Monte Carlo (MCMC) to draw samples from the posterior pseudotime distribution, where each sample corresponds to one possible pseudotime ordering for the cells with associated uncertainties. Zwiessele and Lawrence (2016) have used the Bayesian GPLVM framework to estimate the Waddington landscape using single-cell transcriptomic data; the probabilistic nature of the model allows for more robust estimation of the topology of the estimated epigenetic landscape.

As well as allowing for uncertainty in inferences, Bayesian methods have the advantage of allowing the incorporation of additional covariates which can inform useful dimensionality reduction through the prior. In particular, pseudotime estimation methods may usefully incorporate capture times which may be available from a single-cell time series experiment. For example, in the

immune response after infection, gene expression profiles show a cyclic behaviour which makes it challenging to estimate a single pseudotime. Reid and Wernisch (2016) have developed a Bayesian approach that uses a GPLVM with a prior structure on the latent dimension. The latent dimension in their model is a one-dimensional pseudotime and the prior relates it to the cell capture time. This helps to identify specific features of interest such as cyclic behaviour of cell cycle data. The pseudotime points estimated by their model are in proximity to the actual capture time and use the same scale. Further, Lönnberg *et al.* (2017) have adopted this approach and used sample capture time as prior information to infer pseudotime in the their trajectory analysis.

However, although the Bayesian GPLVM provides an appealing approach for pseudotime estimation with prior information, existing implementations are too computationally inefficient for application to large single-cell datasets, e.g. from droplet-based RNA-Seq experiments. In this contribution, we develop a new efficient implementation of the Bayesian GPLVM with an informative prior which allows for application to much larger datasets than previously considered. Furthermore, we show how extending the pseudotime model to include additional latent dimensions allows for improved pseudotime estimation in the case of branching dynamics. Our model is based on the variational sparse approximation of the Bayesian GPLVM (Titsias and Lawrence, 2010) that can generate a full posterior using only a small number of inducing points and is implemented within a flexible architecture (Matthews *et al.*, 2017) that uses TensorFlow to perform computation across a number of CPU cores and GPU.

2 Methods

Our model is motivated by the DeLorean approach (Reid and Wernisch, 2016) and uses cell capture time to specify a prior over the pseudotime. The probabilistic nature of the model can be used to quantify the uncertainty associated with pseudotime estimation. The GPLVM uses Gaussian processes (GP) to define a stochastic mapping from the latent pseudotime space to the observed gene expression space. A Gaussian process is an infinite dimensional multivariate normal distribution characterized by a mean function and a covariance function (Rasmussen and Williams, 2006). In the GPLVM, the mean function defines

the expected mapping from the latent dimension to the observed data and the covariance function describes the associated covariance between the mapping function evaluated at any two arbitrary points in the latent space. Thus, the covariance function controls the second order statistics and a suitable choice is encouraged by second order features such as smoothness and periodicity.

2.1 Model

The challenge is to develop scalable models that can handle both biological and technical noise inherent in the data. Our preference for the sparse Bayesian approach offers a principled yet pragmatic answer to these challenges. The core of the model is the Gaussian process which has been used extensively to model uncertainty in regression, classification and dimension reduction tasks. The model uses a sparse variational approximation which requires only a small number of inducing points to efficiently produce a full posterior distribution.

The model we use is similar to the Bayesian GPLVM DeLorean model (Reid and Wernisch, 2016); the main differences in our two approaches lie in how model inference is accomplished which is discussed in Section 2.2. The primary latent variables in our method are the pseudotimes associated with each cell. The method expects the technical variability is sufficiently described by a Gaussian distribution which is often accomplished by taking a logarithmic transformation of the gene expression data. The critical assumption is that the cell capture times are informative for the biological dynamics of interest. The expression profile of each gene y_g is modeled as a non-linear transformation of pseudotime which is corrupted by some noise ϵ

$$y_g = f_g(t) + \epsilon, \qquad (1)$$

where $\epsilon \sim N\left(0, \sigma_{noise}^2\right)$ is a Gaussian distribution with variance σ_{noise}^2. We place a Gaussian process prior on the mapping function

$$f_g(t) \sim GP\left(0, \sigma^2 k(t, t^*)\right), \qquad (2)$$

where σ^2 the process variance and $k(t, t^*)$ is the covariance function between two distinct pseudotime points t and t^*. Thus, the expression profiles are functions of pseudotime and the covariance function imposes a smoothness constraint that is shared by all genes.

The pseudotime t_c of cell c is given as prior and drawn from a normal distribution which is centered on the capture time τ_c of cell c.

$$t_c = \mathcal{N}\left(\tau_c, \sigma_t^2\right). \qquad (3)$$

Here σ_t^2 describes the variance over the pseudotime trajectory.

To identify a non-periodic smooth pseudotime trajectory we have used the Radial Basis Function (RBF) and Matern$_{3/2}$ kernels:

$$\mathrm{RBF}(t_1, t_2) = \exp\left(-r^2\right), \qquad (4)$$

$$\mathrm{Matern}_{3/2}(t_1, t_2) = \left(1 + \sqrt{3}r\right)\exp\left(-\sqrt{3}r\right) \qquad (5)$$

where $r = \frac{|t_1 - t_2|}{l}$ and l the process length scale.

For cell cycle data, we have used the periodic kernel described in MacKay (1998). For a known period λ

$$\mathrm{Periodic}(t_1, t_2) = \exp\left(-\frac{1}{2}\left(\frac{\sin\left(\frac{\pi}{\lambda}(t_1 - t_2)\right)}{l}\right)^2\right), \qquad (6)$$

which limits the GP prior to periodic functions.

We have exploited the model's flexibility by extending it to higher dimensional latent spaces. If the x represents the extra latent dimensions, then the expression profile of each gene is modeled as

$$y_g = f_g(t, x) + \epsilon, \qquad (7)$$

where

$$f_g(t, x) \sim GP\left(0, \sigma^2 k\left((t, x), (t, x)^*\right)\right). \qquad (8)$$

This generalization takes the model beyond the estimation of pseudotime. It alleviates the model to a proper probabilistic non-linear dimension reduction technique for large datasets.

2.2 Inference

The computation of the log marginal likelihood is mathematically intractable and MCMC methods (Campbell and Yau, 2016; Reid and Wernisch, 2016) have been employed for inference. Reid and Wernisch (2016) also use black box variational approaches that rely on sampling to increase inference efficiency. However for the Bayesian GPLVM an analytic exact bound exists (Titsias and Lawrence, 2010; Damianou *et al.*, 2016) but the original derivation and all currently available

packages such as GPy (2012) assume an uninformative prior. We modify the exact bound to allow for informative priors

$$\log p\left(Y\right) \geq \mathbb{E}_{q(t)}\left[\log p\left(Y|t\right)\right] - KL\left[q\left(t\right)||p\left(t\right)\right] \tag{9}$$

where $q\left(t\right)$ is the variational distribution and

$$p\left(t\right) = \prod_{n=1}^{N} \mathcal{N}\left(t_n|\tau_n, \sigma_t^2\right), \tag{10}$$

is the modified prior centered at the capture time τ_n of cell n with prior variance σ_t^2.

The modified lower bound on the model marginal likelihood is used to optimize all model parameters including the kernel hyperparameters (process variance, length scale, noise model variance) and the pseudotime locations.

The most notable practical limitation of GPs in practice is the computation required for inference; for each optimisation step the algorithm requires $\mathcal{O}(n^3)$ time and $\mathcal{O}(n^2)$ memory, where n is the number of training examples. Campbell and Yau (2016) have incorporated an MCMC implementation of Bayesian GPLVM without an approximation in their model and hence their approach does not scale for large datasets.

The Bayesian GPLVM has computational complexity of $\mathcal{O}(GC^3)$, where G is the number of genes and C is the number of cells. To make the model computationally tractable for large datasets, a variety of sparse approximations have been proposed (Quiñonero-Candela and Rasmussen, 2005). Sparse GP approximations reduce the complexity to $\mathcal{O}(GCM^2)$ where $M \ll C$ is the number of auxiliary or inducing points. These inducing points may or may not coincide with actual points. As M is chosen much smaller than C, sparse approximations can result in significant reductions in computational requirements.

To reduce computational complexity Reid and Wernisch (2016) use the Fully Independent Training Conditional (FITC) approximation (Snelson and Ghahramani, 2006). This is a simple approach where a specific type of kernel is used to reduce the computational requirement. The approach is attractive because only the kernel is affected; the bound on the marginal likelihood is not affected and is therefore simple to derive. However as Bauer *et al.* (2016) have shown, this approach is prone to overfitting as it does not penalize model complexity. Titsias (2009) derived a Variational Free Energy (VFE) approximation for the Bayesian GPLVM where the bound of the marginal likelihood is modified to include such a penalty term.

Both methods can be succinctly summarized by a different parametrization of the marginal likelihood bound:

$$F = -\frac{N}{2}\log(2\pi) - \underbrace{\frac{1}{2}\log|Q_{NN} + G|}_{\text{complexity penalty}} \tag{11}$$

$$-\underbrace{\frac{1}{2}\mathbf{y}^{\mathrm{T}}\left(Q_{NN} + G\right)^{-1}\mathbf{y}}_{\text{data fit}} - \underbrace{\frac{\beta}{2}tr(T)}_{\text{trace term}},$$

For the VFE approximation we have

$$Q_{NN} = K_{NM}K_{MM}^{-1}K_{MN}, \tag{12}$$

$$G_{\text{VFE}} = \beta^{-1}I_N, \tag{13}$$

$$T_{\text{VFE}} = K_{NN} - Q_{NN}. \tag{14}$$

Here, Q_{NN} is approximating the true covariance matrix K_{NN}, but only involves the inversion of a $M \times M$ matrix K_{MM}. K_{MM} is the covariance matrix on the inducing inputs Z; K_{NM} is the cross covariance matrix between the training and inducing inputs, i.e. between X and Z and $K_{MN} = K_{NM}^{\mathrm{T}}$.

The objective function of Equation (11) consists of three terms: the data fit term imposes a penalty on data not well explained by the model; the complexity term characterizes the volume of probable datasets which are compatible with data fit term and therefore penalizes complex models fitting well on only a small ratio of datasets. Finally, the trace term measures the additional error due to the sparse approximation. Without this term VFE may overestimate the marginal likelihood like previous methods of sparse approximation such as FITC. In fact, the objective function of the FITC can be obtained from Equation (11) by using the same expression for Q_{NN} and taking

$$G_{\text{FITC}} = \text{diag}\left[K_{NN} - Q_{NN}\right] + \beta^{-1}I_N, \tag{15}$$

$$T_{\text{FITC}} = 0, \tag{16}$$

which clearly shows that the objective function of the FITC can be obtained by modifying the GP prior

$$p(\mathbf{f}_d|U) = \mathcal{N}\left(\mathbf{f}_d|\mathbf{0}, Q_{NN} + \text{diag}\left[K_{NN} - Q_{NN}\right]\right). \tag{17}$$

Here the inducing points are acting as an extra set of hyperparameters to parametrize the covariance matrix Q_{NN}. As this approach changes the prior, the continuous optimization of the latent variable $\mathbf{f}_d$ with respect to the inducing points U does

not guarantee to approximate the full GP posterior (Titsias, 2009). Moreover, as $\mathbf{f}_d$ is heavily parametrized because of the extra hyperparameter U and the trace term is 0, overfitting may arise at the time of jointly estimating the inducing points and hyperparameters. For detailed derivation of the bound see the supplement and for a comprehensive comparison of FITC and VFE see Bauer *et al.* (2016). For both the VFE and FITC approximations, the inducing points may be chosen randomly from the training inputs or optimized with respect to the marginal likelihood bound.

Lastly, we have implemented our model in the GPflow package whose flexible architecture allows to perform the computation across multiple CPU cores and GPUs (Matthews *et al.*, 2017).

The source of the scalability of our approach compared to DeLorean is therefore three-fold: model estimation using an exact variational bound, a robust sparse approximation (VFE vs FITC) and implementation on a scalable software architecture.

3   Results and discussion

The performance of our model has been investigated by applying it on a number of datasets of varying sizes collected from different organisms using different techniques. First we have compared our method with the DeLorean model (Reid and Wernisch, 2016) in terms of model fitting as well as the time required to fit the model on all the datasets used in Reid and Wernisch (2016); this encompasses the whole-leaf microarrays of *Arabidopsis thaliana* (Windram *et al.*, 2012); single-cell RNA-Seq libraries of mouse dendritic cells (Shalek *et al.*, 2014) and single-cell expression profiles of a human prostate cancer cell line (McDavid *et al.*, 2014). Unlike the approach taken in Reid and Wernisch (2016) where the variational approximation is computed numerically, our approach provides an exact analytical bound which, as we show, results in robust parameter estimation. Moreover, our method converges quickly by using a small number of inducing points even for large data. Overall, our model outperforms the DeLorean model in both robustness and computational scalability aspects.

We also apply our approach on more recent droplet-based single-cell data. We apply the model on mouse embryo single-cell RNA-seq (Klein *et al.*, 2015) and compare the predicted pseudotime with the diffusion pseudotime (DPT) (Haghverdi *et al.*, 2016). We find that the pseudotime estimated by our model is in good agreement with the DPT demonstrating the robustness of the model. Then we apply the model on a large single-cell dataset of $3^{'}$ mRNA counting data of peripheral blood mononuclear cells (Zheng *et al.*, 2017) to demonstrate scalability to tens of thousands of cells.

Finally, we demonstrate the flexibility of the model by applying it on single-cell qPCR data of early development stages collected from mouse blastocyst (Guo *et al.*, 2010). We infer a two-dimensional latent space and show that the capture time used as an informative prior helps to disambiguate pseudotime from branching structure.

3.1   Comparison with the DeLorean model

We have applied our model on three different datasets from three different organisms which have been also used in Reid and Wernisch (2016). The results produced by our model are similar to the DeLorean model, but our model converges significantly faster. All the experiments have been carried out by using the same experimental setup, that is the same model structure and initial conditions.

Windram *et al.* (2012) examined the effects of *Botrytis cinera* infection on *Arabidopis thaliana*. Among the 150 genes described by Windram *et al.* (2012), we have used 100 genes for the inference process. The remaining 50 genes were left out as held-out genes and used further to validate the model as in Reid and Wernisch (2016). Fig. 1 shows the comparison of our method to the DeLorean model. We have used 20 different initializations for this experiment. Fig. 1(**a**) shows the best and average Spearman correlation between the actual capture time and the estimated pseudotime as the number of inducing points is increased. Both the best and average correlation values show that our method has faster convergence for a smaller number of inducing points than the DeLorean method. Fig. 1(**b**) depicts the fitting time required by both models for different number of inducing points. As our model uses the VFE approximation with an exact bound, it converges an order of magnitude faster than the DeLorean model which requires a sampling process. The problem with the sampling approach is that it requires initial burn-in time to fit the model which makes the inference slower and therefore problematic for larger datasets.

Reid and Wernisch (2016) defined the roughness statistic R_g as the difference of consecutive expression measurements under the ordering given by pseudotime. Our model estimates smooth pseudotime trajectories which have close correspondence with the actual capture time points. To verify the smoothness of our predicted trajectory, we calculated the roughness statistics for the 50 held out genes. The average R_g for all experiments in Fig. 1 is the same for both the DeLorean and Bayesian GPLVM approaches (0.71), reflecting the pseudotime similarity. For details, see supplementary.

Figure 1: *Arabidopis thaliana* microarray data (Windram *et al.*, 2012): A comparison of performance and fitting time between the proposed method and DeLorean method. (**a**): Spearman correlation between the actual capture time and the estimated pseudotime for different number of inducing points. (**b**): Fitting time required by the models for the same experimental setups.

Shalek *et al.* (2014) investigated the primary bone-marrow-derived dendritic cells of mouse in three different conditions. The time course data were collected using single-cell RNA-seq technology. They described several modules of genes which show different temporal expression patterns through the lipopolysaccharide stimulated (LPS) time course. Fig. 2(**a**) shows that our model correctly assigns two precocious cells to later pseudotime as in the DeLorean approach (see supplementary). Fig. 2(**b**) depicts the fitting time required by the both models for different number of inducing points and in all the cases the Bayesian GPLVM model converges significantly faster than the DeLorean model.

McDavid *et al.* (2014) examined the effect of cell cycle on single-cell gene expression across three human prostate cancer cell lines. To model the cyclic nature of the cell cycle, we have used a periodic kernel (Equation (6)). The DeLorean model

Figure 2: Mouse dendritic cells (Shalek *et al.*, 2014): (**a**): The module score of core antiviral cells over pseudotime. The two precocious cells (plotted as triangles) have been placed in later pseudotimes than the other cells captured at 1 hour. A Loess curve (solid blue line) has been plotted thorough the data. (**b**): Comparison of fitting time required by both the DeLorean and our models for different number of inducing points while using the same experimental setups.

requires 7h 31m to fit the model while our method uses 20 inducing points and takes only 4m 45s to converge whilst achieving similar error in recovering the cell cycle peak times (see supplementary). The DeLorean approach uses samples from 40 model initialisations to generate a full posterior GP whilst the BGPLVM only requires a single initialization as an analytic bound of the marginal likelihood is available. We also attempted to compare the fitting time required for different number of inducing points for this dataset but the sparse kernel used in the DeLorean packages results into non-invertible covariance matrices. Therefore the sparse approximation followed in the DeLorean package appears more fragile in cases of non-standard kernels such as the periodic kernel. The estimated pseudotimes are in good agreement with the cyclic behavior of the data. The model also predicts the cell cycle peak time of each gene with similar accuracy level of the DeLorean approach. See supplementary for the details of these results.

3.2 Scaling up the model to droplet-based single-cell data

To investigate the robustness and scalability of our method, we have applied it on droplet-based single-cell data. First, we have applied the model on single-cell RNA-seq data from mouse embryonic stem cells (ESC) generated using droplet barcoding (Klein *et al.*, 2015). Klein *et al.* (2015) developed a method termed inDrop (indexing

droplet) based on droplet microfluidics. They assayed the gene expression profiles and differentiation heterogeneity of mouse stem cells after leukemia inhibitory factor (LIF) withdrawal. They captured the cells at $t = 0, 2, 4$ and 7 days and used their protocol to profile 2717 cells with 24175 observed transcripts. Haghverdi *et al.* (2016) have used this dataset for their analysis of diffusion pseudotime (DPT). They have applied their model on the cell cycle normalized data to infer DPT. We have used this cell cycle normalized data to assess the quality of the Bayesian GPLVM inferred pseudotime.

(a) No prior   (b) With prior

Figure 3: Mouse embryonic stem cells (Klein *et al.*, 2015): pseudotime estimation without and with prior capture time. The points are colored according to the actual cell capture times. Both approaches show similar rank correlation (0.93 vs 0.94) with DPT but the model using prior information also shows similar pseudotime density to DPT.

The inference process uses 2717 cells and 2047 genes. The model uses a RBF kernel (Equation (4)) to identify a smooth pseudotime trajectory. We have used empirical estimates of the kernel hyperparameters $l = 1$ and $\sigma^2 = 1$ and set the capture time prior variance to $\sigma_t^2 = 0.1$. In Fig. 3 we contrast the DPT and Bayesian GPLVM pseudotimes using both non-informative and informative priors. Although the Spearman correlation between estimated pseudotime and diffusion pseudotime have similar values for both non-informative and informative priors, the latter shows a closer correspondence to DPT.

As memory is a crucial resource when analyzing large volumes of data, we also examine the effect of lower precision computations. We have examined the performance of our model under both 64 and 32 bits floating point precision. In both cases we observe a strong correlation with DPT (0.94) but note a significant reduction in fitting time when

using 32 bits precision. For 64 bits precision the algorithm take 32 seconds to converge, whilst it takes only 11 seconds to converge for 32 bits precision.

Figure 4: PBMCs with ˜68k cells (Zheng *et al.*, 2017): Time per iteration using 1, 2, 4, 8, 16 CPU cores. The algorithm has been applied using both 32 and 64 bit floating point precision.

We also apply our method on a larger single-cell RNA-seq data to further demonstrate its scalability. Zheng *et al.* (2017) have presented a droplet-based technology that enables $3'$ messenger RNA (mRNA) digital counting to encapsulate tens of thousands of single cells per sample. In their method, reverse transcription takes place within each droplet and barcoded complementary DNAs (cDNAs) have been amplified in bulk. The resulting libraries are then used for Illumina short-read sequencing. Their method has 50% cell capture efficiency and can process a maximum of 8 cells simultaneously in each run. Zheng *et al.* (2017) have assayed ˜68k peripheral blood mononuclear cells (PBMCs) demonstrating the suitability of single-cell RNA-seq technology to characterize large immune cell populations.

We have applied our method using the top 1000 variably expressed genes ranked by their normalized dispersion (Zheng *et al.*, 2017). The GPLVM model uses an RBF kernel (Equation (4)). For simplicity only the pseudotime latent positions are optimized, using fixed values for the kernel hyperparameters $l = 1$ and $\sigma^2 = 1$ and the inducing points. The algorithm takes ˜6m to converge using 16 CPU cores[1]. In Fig. 4 we show the time required per iteration when using different number of CPU cores for both 32 and 64 bit precision. The computational benefits of lower precision are reduced as the number of cores is increased. We also note the diminishing returns of increasing the number of CPU cores; we see an approximately doubling of performance when increasing the number of cores from 2 to 4 but a reduced benefit when increasing from 8 to 16. We recommend a small number of cores is assigned to an individual model fitting, with any remaining resources

---

[1]The hardware used was a 16-core Intel Ivy Bridge CPUs (E5-2650 v2, 2.60GHz) with 512 GB memory.

assigned to perform multiple model fittings using different initial conditions. The latter is needed to alleviate the local minima problem inherent when fitting a Bayesian GPLVM model. We have also run our model on a simple desktop machine[2] for this dataset and it takes ~10m to converge.

3.3 Extending the model to infer Pseudotime-branching

To demonstrate the flexibility of our approach, we extend the model to 2-D latent spaces and apply it on single-cell qPCR data of early developmental stages in mouse (Guo *et al.*, 2010). The gene expression profiles of 48 genes were measured across 437 cells. Cells differentiate from the single-cell stage into three different cell states in the 64 cell stage: trophectoderm (TE), epiblast (EPI), and primitive endoderm (PE).

Models with both informative and non-informative priors are examined. Both models use an RBF kernel (Equation (4)) with fixed hyperparameters $l = 1$ and $\sigma^2 = 1$. Both models are initialized with identical values. For the informative prior, we set the capture time variance to $\sigma_t^2 = 0.1$. The informative prior (Fig. 5(**Bottom**)) on capture time helps with the identifiability of the model as it aligns the first latent dimension (horizontal axis) with pseudotime and the second latent dimension (vertical axis) with the branching structure.

Figure 5: Single-cell qPCR of early developmental stages (Guo *et al.*, 2010): Latent space reconstruction without and with prior. The bottom captures both developmental time and branching structure. The cell stage and type labels are also shown.

To investigate how the branching dynamics affect the estimation of pseudotime points, we have used our model to infer the 1-D pseudotimes with

informative prior and compared it with the pseudotimes from the 2-D informative prior model (Fig. 6(a) and (b)). Both models were run from multiple initial conditions to ensure a good likelihood optimum was obtained. The 2-D model estimate of the pseudotime is found to have better correspondence with the actual capture time (correlation 0.84 vs 0.95), suggesting that the 1-D model is less able to align all variation with a pseudotime axis.

In Fig. 6(c) and (d), we have plotted the expression profiles of two marker genes against our estimated pseudotime points. $Id2$ is a known marker gene for TE, thus it behaves differently in TE cells from the other two differentiation stages. It differentially expressed between the stages (TE and EPI) as well as between (TE and PE). Similarly, Fig. 6 (d) shows that $Gata4$ is differentially expressed between the stages (PE and EPI) and between the stages (TE and PE). To see the expression profiles of the other differentially expressed genes across the differentiation stages, see the accompanying notebook.

Figure 6: (a) and (b): The actual capture times against the estimated pseudotimes from the 2-D and 1-D model with informative prior. (c) and (d): The expression profiles of the two known markers genes against the estimated pseudotime shows the time series experiments describing how the genes behaves differentially across the differentiation stages.

---

4   Conclusion

Pseudotime estimation on single-cell genomics faces a number of challenges as the structure of the expression data is complex and non-linear. Many sources of variability, both biological and technical, introduce a significant amount of statistical uncertainty in the inference process. Here, we have used the Bayesian GPLVM model with informative priors to perform pseudotime estimation within a probabilistic framework. The model uses cell capture times as priors over pseudotime. Experimental results show that the properties of pseudotime ordering do not only depend on the data but also on the prior assumptions about the trajectory such as proximity to capture time, smoothness and periodicity.

The Bayesian GPLVM framework allows us to predict a number of latent dimensions along with associated uncertainty. A sampling-based Markov Chain Monte Carlo implementation of the Bayesian GPLVM is impractical for large number of cells because of its high computational complexity. We have developed our model on the basis of a sparse approximation that can generate a full posterior using only a small number of inducing points. Among a number of sparse approximation techniques, we have used the Variational Free Energy (VFE) approximation which has an exact bound to the marginal likelihood and avoids overfitting unlike the FITC approximation used by Reid and Wernisch (2016). To validate these claims, our approach has been tested on a variety of datasets from different organisms collected using different protocols. While producing results with a similar level of accuracy across all datasets used in Reid and Wernisch (2016), our model converges considerably faster than the De-Lorean model. The sources of the speed up are threefold: an analytic rather a numerically assessed variational bound, a more robust sparse approximation (VFE vs FITC) requiring fewer inducing points, and a scalable software implementation (Matthews *et al.*, 2017) allowing for lower precision and GPU computation.

We have applied our model on droplet-based datasets to examine the robustness and scalability of our approach on much larger datasets. Our model successfully estimates pseudotimes for single-cell RNA-seq data of mouse embryonic stem cells (ESC) generated using the inDrop protocol. The Bayesian GPLVM estimated pseudotimes are in good agreement with DPT whilst providing all the benefits of a fully probabilistic model; namely quantification of uncertainty in the pseudotime estimation which has been shown to be of biological relevance (Campbell and Yau, 2016). To demonstrate our models scalability, we have measured its performance on a ~68k single-cell data of peripheral blood mononuclear cells and the model converges in 6 minutes on this large dataset.

Finally, we have applied the model on single-cell qPCR of early developmental stages to demonstrating its flexibility. We extended the model to higher dimensional latent spaces where the interaction of pseudotime with other factors, such as cell type differentiation, can be captured. We demonstrated the importance of this additional flexibility using a two-dimensional latent space where pseudotime is estimated jointly with the developmental branching structure.

The model performs well across varying floating point precisions. For droplet-based datasets we have run the model using both 32 and 64 bit floating point precision and the algorithm produces similar estimation of pseudotime. We expect that in most cases, low precision will be sufficient to understand the behavior of the system offering a way to further scale up our approach without the need for more expensive hardware. Mixed precision computations would also be possible with higher-precision computations performed only on the most numerically critical parts of the algorithm maintaining high accuracy whilst being significantly faster (Baboulin *et al.*, 2009).

The analysis of single-cell data creates the opportunity to examine the temporal dynamics of complex biological processes where the generation of time course experiments is challenging or technically impossible. As single-cell data are becoming increasingly available in larger volumes, we believe scalable yet rigorous approaches such as the Bayesian GPLVM we have presented, will become ever more relevant. The flexibility of our approach can also reveal interesting biological facts such as identifying branching points in the differentiation pathways.

Acknowledgements

We wish to thank John Reid for his help with the DeLorean code and data. We also thank James Hensman and all GPflow contributors for their help with the GPflow package.

Funding

SA is a Commonwealth Scholar, funded by the UK government. MR and AB were supported by MRC award MR/M008908/1.

References

Baboulin, M., Buttari, A., Dongarra, J., Kurzak, J., Langou, J., Langou, J., Luszczek, P., and Tomov, S. (2009). Accelerating scientific computations with mixed precision algorithms. *Computer Physics Communications*, **180**(12), 2526–2533.

Bauer, M., van der Wilk, M., and Rasmussen, C. E. (2016). Understanding probabilistic sparse gaussian process approximations. In *Advances in Neural Information Processing Systems*, pages 1533–1541.

Becher, B., Schlitzer, A., Chen, J., Mair, F., Sumatoh, H. R., Teng, K. W. W., Low, D., Ruedl, C., Riccardi-Castagnoli, P., Poidinger, M., *et al.* (2014). High-dimensional analysis of the murine myeloid cell system. *Nature immunology*, **15**(12), 1181–1189.

Bendall, S. C., Davis, K. L., Amir, E.-a. D., Tadmor, M. D., Simonds, E. F., Chen, T. J., Shenfeld, D. K., Nolan, G. P., and Peer, D. (2014). Single-cell trajectory detection uncovers progression and regulatory coordination in human b cell development. *Cell*, **157**(3), 714–725.

Buettner, F. and Theis, F. J. (2012). A novel approach for resolving differences in single-cell gene expression patterns from zygote to blastocyst. *Bioinformatics*, **28**(18), i626–i632.

Buettner, F., Natarajan, K. N., Casale, F. P., Proserpio, V., Scialdone, A., Theis, F. J., Teichmann, S. A., Marioni, J. C., and Stegle, O. (2015). Computational analysis of cell-to-cell heterogeneity in single-cell rna-sequencing data reveals hidden subpopulations of cells. *Nature biotechnology*, **33**(2), 155–160.

Campbell, K. and Yau, C. (2016). Order under uncertainty: robust differential expression analysis using probabilistic models for pseudotime inference. *PLoS Computational Biology*, **12**(11).

Damianou, A. C., Titsias, M. K., and Lawrence, N. D. (2016). Variational inference for latent variables and uncertain inputs in gaussian processes. *The Journal of Machine Learning Research*, **17**(1), 1425–1486.

GPy (since 2012). GPy: A gaussian process framework in python. http://github.com/SheffieldML/GPy.

Guo, G., Huss, M., Tong, G. Q., Wang, C., Sun, L. L., Clarke, N. D., and Robson, P. (2010). Resolution of cell fate decisions revealed by single-cell gene expression analysis from zygote to blastocyst. *Developmental cell*, **18**(4), 675–685.

Haghverdi, L., Buettner, F., and Theis, F. J. (2015). Diffusion maps for high-dimensional single-cell analysis of differentiation data. *Bioinformatics*, **31**(18), 2989–2998.

Haghverdi, L., Buettner, M., Wolf, F. A., Buettner, F., and Theis, F. J. (2016). Diffusion pseudonyme robustly reconstructs lineage branching. *Nature Methods*, **13**(10), 845–848.

Ji, Z. and Ji, H. (2016). TSCAN: Pseudo-time reconstruction and evaluation in single-cell rna-seq analysis. *Nucleic acids research*, **44**(13).

Klein, A. M., Mazutis, L., Akartuna, I., Tallapragada, N., Veres, A., Li, V., Peshkin, L., Weitz, D. A., and Kirschner, M. W. (2015). Droplet barcoding for single-cell transcriptomics applied to embryonic stem cells. *Cell*, **161**(5), 1187–1201.

Lönnberg, T., Svensson, V., James, K. R., Fernandez-Ruiz, D., Sebina, I., Montandon, R., Soon, M. S., Fogg, L. G., Nair, A. S., Liligeto, U., *et al.* (2017). Single-cell rna-seq and computational analysis using temporal mixture modelling resolves th1/tfh fate bifurcation in malaria. *Science immunology*, **2**(9).

MacKay, D. J. (1998). Introduction to gaussian processes. *NATO ASI Series F Computer and Systems Sciences*, **168**, 133–166.

Marco, E., Karp, R. L., Guo, G., Robson, P., Hart, A. H., Trippa, L., and Yuan, G.-C. (2014). Bifurcation analysis of single-cell gene expression data reveals epigenetic landscape. *Proceedings of the National Academy of Sciences*, **111**(52), E5643–E5650.

Matthews, A. G. d. G., van der Wilk, M., Nickson, T., Fujii, K., Boukouvalas, A., León-Villagrá, P., Ghahramani, Z., and Hensman, J. (2017). GPflow: A Gaussian process library using TensorFlow. *Journal of Machine Learning Research*, **18**(40), 1–6.

McDavid, A., Dennis, L., Danaher, P., Finak, G., Krouse, M., Wang, A., Webster, P., Beechem, J., and Gottardo, R. (2014). Modeling bi-modality improves characterization of cell cycle on gene expression in single cells. *PLoS Comput Biol*, **10**(7), e1003696.

Quiñonero-Candela, J. and Rasmussen, C. E. (2005). A unifying view of sparse approximate gaussian process regression. *Journal of Machine Learning Research*, **6**(Dec), 1939–1959.

Rasmussen, C. and Williams, C. (2006). *Gaussian processes for machine learning*. MIT Press, Cambridge, Mass.

Reid, J. E. and Wernisch, L. (2016). Pseudotime estimation: deconfounding single cell time series. *Bioinformatics*, **32**(19), 2973–2980.

Shalek, A. K., Satija, R., Shuga, J., Trombetta, J. J., Gennert, D., Lu, D., Chen, P., Gertner, R. S., Gaublomme, J. T., Yosef, N., *et al.* (2014). Single-cell rna-seq reveals dynamic paracrine control of cellular variation. *Nature*, **510**(7505), 363–369.

Shin, J., Berg, D. A., Zhu, Y., Shin, J. Y., Song, J., Bonaguidi, M. A., Enikolopov, G., Nauen, D. W., Christian, K. M., Ming, G.-l., *et al.* (2015). Single-cell rna-seq with waterfall reveals molecular cascades underlying adult neurogenesis. *Cell Stem Cell*, **17**(3), 360–372.

Snelson, E. and Ghahramani, Z. (2006). Sparse gaussian processes using pseudo-inputs. In *Advances in neural information processing systems*, pages 1257–1264.

Titsias, M. K. (2009). Variational learning of inducing variables in sparse gaussian processes. In *International Conference on Artificial Intelligence and Statistics*, pages 567–574.

Titsias, M. K. and Lawrence, N. D. (2010). Bayesian gaussian process latent variable model. In *International Conference on Artificial Intelligence and Statistics*, pages 844–851.

Trapnell, C., Cacchiarelli, D., Grimsby, J., Pokharel, P., Li, S., Morse, M., Lennon, N. J., Livak, K. J., Mikkelsen, T. S., and Rinn, J. L. (2014). The dynamics and regulators of cell fate decisions are revealed by pseudotemporal ordering of single cells. *Nature biotechnology*, **32**(4), 381–386.

Windram, O., Madhou, P., McHattie, S., Hill, C., Hickman, R., Cooke, E., Jenkins, D. J., Penfold, C. A., Baxter, L., Breeze, E., *et al.* (2012). Arabidopsis defense against botrytis cinerea: chronology and regulation deciphered by high-resolution temporal transcriptomic analysis. *The Plant Cell*, **24**(9), 3530–3557.

Zheng, G. X., Terry, J. M., Belgrader, P., Ryvkin, P., Bent, Z. W., Wilson, R., Ziraldo, S. B., Wheeler, T. D., McDermott, G. P., Zhu, J., *et al.* (2017). Massively parallel digital transcriptional profiling of single cells. *Nature communications*, **8**, 14049.

Zwiessele, M. and Lawrence, N. D. (2016). Topslam: Waddington landscape recovery for single cell experiments. *bioRxiv*.