1
2
3
4 # The ventral visual pathway represents animal appearance over animacy,
5 ## unlike human behavior and deep neural networks
6
7
8
9

Stefania Bracci[1], Ioannis Kalfas[2], and Hans Op de Beeck[1]

(1) Laboratory of Biological Psychology, KU Leuven, Leuven, 3000, Belgium

(2) Laboratory of Neuro- and Psychophysiology, Department of Neurosciences,

KU Leuven, Leuven, 3000, Belgium

Corresponding author:

Stefania Bracci

stefania.bracci@kuleuven.be

Laboratory for Biological Psychology

Tiensestraat 102 - box 3714

3000 Leuven

Tel. +32 16 37 77 44

Running Title: DNNs predict perception, not brain representations

Abstract

Recent studies showed agreement between how the human brain and neural networks represent objects, suggesting that we might start to understand the underlying computations. However, we know that the human brain is prone to biases at many perceptual and cognitive levels, often shaped by learning history and evolutionary constraints. Here we explore one such bias, namely the bias to perceive animacy, and used the performance of neural networks as a benchmark. We performed an fMRI study that dissociated object appearance (how an object looks like) from object category (animate or inanimate) by constructing a stimulus set that includes animate objects (e.g., a cow), typical inanimate objects (e.g., a mug), and, crucially, inanimate objects that look like the animate objects (e.g., a cow-mug). Behavioral judgments and deep neural networks categorized images mainly by animacy, setting all objects (lookalike and inanimate) apart from the animate ones. In contrast, activity patterns in ventral occipitotemporal cortex (VTC) were strongly biased towards object appearance: animals and lookalikes were similarly represented and separated from the inanimate objects. Furthermore, this bias interfered with proper object identification, such as failing to signal that a cow-mug is a mug. The bias in VTC to represent a lookalike as animate was even present when participants performed a task requiring them to report the lookalikes as inanimate. In conclusion, VTC representations, in contrast to neural networks, fail to veridically represent objects when visual appearance is dissociated from animacy, probably due to a biased processing of visual features typical of animate objects.

Keywords

fMRI, MVPA, deep neural networks, object representations, animacy, ventral occipitotemporal cortex.

Introduction

A fundamental goal in visual neuroscience is to reach a deep understanding of the neural code underlying object representations; how does the brain represent objects we perceive around us? Over the years, research has characterized object representations in the primate brain in terms of their content for a wide range of visual and semantic object properties such as shape, size, or animacy (Konkle and Oliva, 2012; Nasr et al., 2014; Bracci and Op de Beeck, 2016; Kalfas et al., 2017). More recently, our understanding of these multidimensional object representations has been lifted to a higher level by the advent of so-called deep-convolutional neural networks (DNNs) that do not only reach human behavioral performance in image categorization (Russakovsky et al., 2014; He et al., 2015; Kheradpisheh et al., 2016a), but also appear to develop representations that share many of the properties of primate object representations (Cadieu et al., 2014; Guclu and van Gerven, 2014; Khaligh-Razavi and Kriegeskorte, 2014; Yamins et al., 2014; Guclu and van Gerven, 2015; Kubilius et al., 2016). This correspondence extends to the representation of several object dimensions, such as shape properties (Kubilius et al., 2016), and the distinction between animate and inanimate objects (Khaligh-Razavi and Kriegeskorte, 2014). Hence, the availability of computational models that can mimic human recognition behavior and neural information processing in its full complexity offers exciting possibilities for understanding human object vision (Kriegeskorte, 2015). Here, we provide an important test of this similarity between artificial and biological brain representations by focusing upon a particularly challenging organizing principle of human ventral visual cortex: object animacy.

Perception of animacy has played an essential role through the evolution and survival of our species. This animacy bias is evident in both bottom-up perceptually driven contexts (Gao et al., 2009; Gao et al., 2010; Scholl and Gao, 2013), even after controlling for stimulus low-level visual properties (New et al., 2007), as well as more high-level cognitive phenomena such as pareidolia, where – most often – animate objects (faces or animals) are perceived in meaningless, random noise images (e.g., clouds). At the neural level, our visual system includes specific neural mechanisms with selectivity for animate entities, such as animals and humans, relative to inanimate objects (Kanwisher et al., 1997; Downing et al., 2001). What are the dimensions underlying animacy percepts? One proposal suggests that animacy representations in visual cortex reflect the psychological dimension of perceiving something as being a living entity (Caramazza and Shelton, 1998; Tremoulet and Feldman, 2000; Gao et al., 2009). Alternatively, animacy representations might be "not aware" of object animacy per se but instead reflect stimulus visual aspects such as appearance – whether something looks like a living entity or not. Here we test these two alternatives and compare whether the representation of animacy converges across artificial and biological brains.

We explicitly dissociated object appearance (how an object looks like) from object category (what the object really is) – two dimensions that are typically correlated in natural images, to test whether (1) both biological and artificial brains represent animacy in the same way, and whether (2) animacy percepts reflect object appearance or object category. We show that activity patterns in visual cortex were confused by animal appearance: a cow-shaped mug was more similar to a cow as opposed to a mug. In contrast, DNNs correctly categorized a cow-mug as an inanimate object. As a consequence, rather surprisingly, deep neural networks, which were never explicitly trained on animacy, outperform ventral occipitotemporal cortex representations in categorizing objects as being animate or inanimate.

Materials and Methods

Participants

The study included 16 adult volunteers (9 males; mean age, 30 years). Informed consent to take part in the fMRI experiment was signed by all participants. The ethics committee of the KU Leuven approved the study. For the fMRI experiment, due to excessive head motion, all data from one participant was excluded. In addition, one run was excluded in two participants, and two runs were excluded in two other participants. The head motion exclusion criterion was set to +/- 3 mm (equal to 1 voxel size) and defined before data collection. For behavioral ratings, two participants were excluded due to technical problems during data collection.

Stimuli

The stimulus set included nine different triads (27 stimuli in total), each containing: (1) one animal (e.g., a cow), (2) one object (e.g., a mug), and (3) one lookalike object, which resembled the animal (e.g., a cow-shaped mug; Figure 1A). Critically, to dissociate object appearance from object identity, each stimulus in the lookalike condition was matched to the inanimate objects in terms of object identity, and to the animals in terms of animal appearance. That is, the lookalike and object conditions shared the same object identity, size, and other object properties such as function and usage (e.g., the mug and the cow-mug). At the same time, the lookalike and animal conditions shared animal appearance, but differed in animacy; the cow-mug it an object whereas the cow depicts a living animal. This stimulus set was used to acquire behavioral, deep neural network, and neuroimaging data.

Experimental Design

Behavioral Data

Each participant rated all images (Figure 1A) based on their general similarity. Images were simultaneously rated on a screen within a circle arena following the procedure of Kriegeskorte and Mur (2012). Participants were asked to ''arrange the objects according to how similar they are'', thus letting them free to choose what they considered to be the most relevant dimension/s to judge. The object dissimilarity space for behavioral judgments was constructed by averaging results across participants. Only the upper triangle of the dissimilarity matrix was used for subsequent analyses.

Deep Neural Network Data

To create the object dissimilarity space of our stimulus set, we used the stimuli features that were extracted for the last processing stage (last fully connected layer) of two Deep Neural Networks (DNNs), VGG-19 (Simonyan and Zisserman, 2014) and GoogLeNet (Szegedy et al., 2015). As for behavioral data, only the upper triangle of the dissimilarity matrix was used for subsequent analyses. These DNNs are deep convolutional neural networks, which have been very successful for object recognition tasks in the last few years. They consist of various processing stages, which are often termed as 'layers' either individually or in groups, in a feedforward manner that nonlinearly transform an input image volume (width, height, RGB value) into a 1-dimensional vector holding the class scores.

These processing stages include: i) convolutional layers, where a neuron outputs the dot product

between a kernel (its weights) and a small region in the input it is connected to, ii) rectified linear unit activation

functions, such that the activations of a previous weight layer are thresholded at zero (max(0,x)), iii) max

pooling layers performing a downsampling operation along the width and height of the input and lastly, iv) fully

connected layers (resembling a multilayer perceptron) that flatten the previous stage's volume and end up in a

1-dimensional vector with the same size as the number of classes. A softmax function is then typically applied

to this last fully connected layer's unit activations to retrieve class probability scores for the classification task. In

our experiments, we used the last fully connected layer as the upper layer of the network and not the

probability scores from applying the softmax function.

The two networks were trained on ~1.2 million natural images, belonging to 1000 classes for the

ImageNet Large Scale Visual Recognition Challenge 2012 (ILSVRC2012). The classes include ~40% animals and

~60% objects, but the networks are not specifically trained to detect animacy. We used the pre-trained models

from MatConvNet (http://www.vlfeat.org/matconvnet/)(Vedaldi and Lenc, 2016) toolbox in MATLAB. Before

feature extraction, the mean of the ILSVRC2012 training images was subtracted from each image, as to the

standards of training both these DNNs. Furthermore, all stimuli were scaled to 224x224 pixels, in accordance

with the requirements of the two networks.

VGG-19. This deep neural network from Simonyan and Zisserman (2014) incorporates 16

convolutional layers, in 2 blocks of 2 convolutional layers and 3 blocks of 4 convolutional layers, followed by

three fully connected layers. A max pooling operation is applied after each of these five convolutional layer

blocks. All, except for the last (fc8), of these weight layers are followed by a RELU function, where the

activations are thresholded at zero. A softmax function is then applied to the last fully connected layer (fc8).

The top-5 error rate performance of this pre-trained MatConvNet model on the ILSVRC2012 validation data

was 9.9%.

GoogLeNet. Google's entry to ILSVRC2014 (Szegedy et al., 2015). It made use of the 'Inception' module,

which is a technique used in early versions of Deep Neural Networks for pattern recognition, where a DNN

uses several sizes of kernels along with pooling concatenated within one layer, which is similar to integrating all

information about parts of the image (size, location, texture etc.). In addition, there is a softmax operation in

multiple stages of GoogLeNet, assisting the classification procedure during training along the depth levels of the

network. This MatConvNet pretrained model was imported from the Princeton version, not by the Google

team, thus there is some difference in performance to other versions probably due to parameter settings during

training. The top-5 error rate performance of this model on the ILSVRC2012 validation data was 12.9%.

fMRI Data

Experimental Design: We acquired neuroimaging data by means of an event-related design in two separated

sessions, each performed in separated days with no more than 7 days between the first and second session.

Each session included six experimental runs as well as additional runs with unrelated stimuli for another

experiment (not reported here). The stimuli presentation was controlled by a PC running the Psychophysics

Toolbox package (Brainard, 1997) in MATLAB (The MathWorks). Pictures from the stimulus set were

projected onto a screen and were viewed through a mirror mounted on the head coil.

Each experimental run (12 in total) lasted 7 min and 14 ms (230 volumes per run). For each subject

and for each run, a fully randomized sequence of 27 image trials (repeated 4 times) and 9 fixation trials

(repeated 4 times) was presented. Each trial was presented for 1500 ms, followed by a fixation screen for 1500

ms. Each run started and ended with 14 sec of fixation. During the whole experiment, each stimulus was

repeated 48 times. While scanning participants performed two different tasks (Figure 1B) counterbalanced

across runs. During the animacy task, participants judged animacy ("does this image depict a living animal?").

During the appearance task, participants judged object appearance ("does this image look like an animal?").

Participants responded 'yes' or 'no' with the index and middle finger. Response-finger associations were

counterbalanced across runs.

Acquisition Parameters: Imaging data was acquired on a 3T Philips scanner with a 32-channel coil at the

Department of Radiology of the University Hospitals Leuven. MRI volumes were collected using echo planar

(EPI) T2*-weighted scans. Acquisition parameters were as follows: repetition time (TR) of 2 s, echo time (TE)

of 30 ms, flip angle (FA) of 90°, field of view (FoV) of 216 mm, and matrix size of 72 × 72. Each volume

comprised 37 axial slices (covering the whole brain) with 3 mm thickness and no gap. The T1- weighted

anatomical images were acquired with an MP-RAGE sequence, with 1×1×1 mm resolution.

Preprocessing: Imaging data were preprocessed and analyzed with the Statistical Parametrical Mapping software

package (SPM 12, Welcome Department of Cognitive Neurology) and MATLAB. Before statistical analysis,

functional images underwent a standard preprocessing procedure to align, co-register and normalize to an MNI

(Montreal Neurological Institute) template. Functional images were spatially smoothed by convolution of a

Gaussian kernel of 4 mm full width at half-maximum (Op de Beeck, 2010). For each participant, a general linear

model (GLM) for both tasks was created to model the 27 conditions of interest and the 6 motion correction

parameters (x, y, z for translation and for rotation). Each predictor's time course was modelled for 3 sec

(stimulus presentation + fixation) by a boxcar function convolved with the canonical hemodynamic response

function in SPM. We also analyzed data for each task separately, for which purpose a general linear model

(GLM) was created for each task separately.

Regions of Interest (ROIs) definition: ROIs were defined at the group level with a combination of functional and

anatomical criteria. First, we selected all visually active voxels (all stimuli versus baseline) that exceeded the

statistical uncorrected threshold $p < 0.001$. Subsequently, we selected all spatially continuous voxels within

anatomical ROIs defined with the Neuromorphometrics atlas in SPM. The following ROIs were defined: V1, and

ventro-temporal cortex (VTC) divided into its posterior (post VTC) and anterior (ant VTC) sectors. These

ROIs were chosen based on the important role played by VTC in object representation and categorization

(Grill-Spector and Weiner, 2014).

Statistical Analyses

Multivariate analyses were used to investigate the extent to which the two experimental dimensions (object

animacy and object appearance) explain representational content in behavioral, DNNs, and brain data (this

latter under different task conditions). For statistical tests, we took the following approach. For DNNs models,

given that only one similarity matrix for each model was available, statistical significance in the different analyses

(e.g., representational similarity analysis) was tested across stimuli with permutation tests (Figure 2) or pairwise

t-tests (Figure 3). To be consistent, this approach was also applied to the behavioral data (i.e., these two
datasets were directly compared in Figure 2 and 3). For neural data, instead, given that individual subject data
was available, we tested significance across subjects with ANOVAs and pairwise t-tests (e.g., Figure 4). Whereas
corrections for multiple comparisons were applied for all analyses, for transparency, throughout the text
uncorrected p-values are reported. However, when p-values did not survive correction, we noted it in the text.
For all statistical tests we report exact p-values up to p = 0.00001, for lower p-values we report p < 0.00001.

ROI-based RSA: As before (Op de Beeck et al., 2010), for each voxel within a given ROI, parameter estimates
for each condition (relative to baseline) were extracted for each participant and each run and normalized by
subtracting the mean response across all conditions. Subsequently, the data set was divided 100 times into 2
random subsets of runs (set-1 and set-2) and the voxel response patterns for each object pair were correlated
across these independent data sets. Correlations were averaged across the 100 iterations, thus resulting in an
asymmetric 27×27 correlation matrix for each task, participant and ROI. For each correlation matrix, cells
above and below the diagonal were averaged and only the upper triangle of the resulting symmetric matrix was
used in the subsequent analyses (Ritchie et al., 2017). Correlation matrices were converted into dissimilarities
matrices (1 minus Pearson's r) and used as neural input for subsequent analyses. Resulting correlations were
Fisher transformed $\{0.5 * \log[(1 + r)/(1 - r)]\}$ and tested with ANOVAs and pairwise t-tests.
For each ROI we computed an estimate of the reliability of the dissimilarity matrices (Op de Beeck et
al., 2008), which indicates the highest expected correlation in a region given its signal-to-noise ratio. For each
subject and each ROI, the 27×27 correlation matrix was correlated with the averaged correlation matrix of
the remaining participants. The resulting correlation values (averaged across participants) capture noise inherent
to a single subject as well as noise caused by inter-subject variability.

Whole-brain RSA: In addition to ROI-based RSA, we performed a whole-brain RSA correlating the two models
(appearance, animacy) with neural patterns throughout the brain. The whole-brain RSA performed using the
volume-based searching approach (Kriegeskorte et al., 2006) was implemented with CoSMo MVPA (Oosterhof
et al., 2016). Parameter estimates for each condition (relative to baseline) were extracted for each participant
and each run and normalized by subtracting the mean response across all conditions. Resulting values were then
averaged across all runs. For each voxel in the brain, a searchlight was defined using a spherical neighborhood
with a variable radius, including the 100 voxels nearest to the center voxel. For each searchlight, the neural
dissimilarity matrix was computed for the 27 stimuli. The neural dissimilarity matrix (upper triangle) was then
correlated with the dissimilarity matrices derived from the two predictive models (Figure 1C). The output
correlation values were Fisher transformed and assigned to the center voxel of the sphere. Resulting whole-
brain correlation maps for each of the models were directly contrasted and differences were tested using
random-effects whole-brain group analysis and corrected with the Threshold-Free Cluster Enhancement (TFCE;
Smith and Nichols, 2009) method. Voxel-wise corrected statistical maps (z =1.64; p < 0.05, one-sided t-test)
are highlighted with dotted lines were displayed on a brain template by means of BrainNet Viewer (Xia et al.,
2013).
238

Data and software availability

All types of brain images and statistics data are available from the authors upon request. The data used for final
statistics are made available through the Open Science Framework.

Results

We constructed a stimulus set to intentionally separate object appearance from object identity, including: 9

animals (e.g., a cow), 9 objects (e.g., a mug), and 9 lookalike objects, which consisted of objects (e.g., a cow-

mug) that were matched to the inanimate objects in terms of object identity, and to the animals in terms of

appearance. This resulted in a stimulus set of 9 closely matched triads -- 27 stimuli in total (Figure 1A). The mug

and the cow-mug represent the same inanimate object, identical in many respects (e.g., function, size, material,

and manipulability) but their appearance. Conversely, relative to the cow-mug, the cow is a living animal and

despite shared visual features typical of animals, such as eyes, mouth and limbs, differs in all the above semantic

and functional properties. With this stimulus design, we dissociate the conceptual animate-inanimate distinction

from visual appearance (Fig. 1C).

Figure 1. The experimental design. (A) The stimulus set was specifically designed to dissociate object appearance from object
identity. We included 9 different object triads. Each triad included an animal (e.g., butterfly), an inanimate object (e.g., earring), and a
lookalike object closely matched to the inanimate object in terms of object identity and to the living animal in terms of object appearance
(e.g., a butterfly-shaped earring). (B) During fMRI acquisition, participants performed two different tasks counterbalanced across runs. During
the *animacy task*, participants judged animacy: "does this image depict a living animal?" During the *animal appearance task*, participants
judged animal resemblance: "does this image look like an animal?" Participants responded 'yes' or 'no' with the index and middle finger.
Responses were counterbalanced across runs. (C) Model predictions represent the required response similarity in the two tasks. The
animacy model predicts high similarity among images that share semantic living/animate properties, thus predicting all inanimate objects
(objects and lookalikes) to cluster together and separately from living animals. On the contrary, the animal appearance model predicts
similarities based on visual appearance despite differences in object identity and animacy, thus predicting lookalikes and animals to cluster
together and separately from inanimate objects. The two models are independent (r = 0.07).

Deep neural networks and human perception privilege object animacy over appearance

To test whether DNNs predict human perception on object animacy and appearance, we compared similarity

judgments on the stimulus set (Materials and Methods) to the stimulus representation for two recent DNNs

(VGG-19: Simonyan and Zisserman, 2014; and GoogLeNet: Szegedy et al., 2015) that were chosen based on

their human-like performance in object categorization (Russakovsky et al., 2014; He et al., 2015; Kheradpisheh

et al., 2016b). The object dissimilarity for each image pair (1 minus Pearson's r) was computed for human

similarity ratings (Materials and Methods), and for the output vectors of the DNNs' last fully connected layer,

and resulting dissimilarity matrices were correlated with the two independent models. Results revealed

similarities but also differences between human judgments and DNNs representations (Figure 2). A significant

positive correlation of both models (appearance: r =0.41; p < 0.0001; animacy: r= 0.66; p < 0.0001) with

behavioral judgments showed that participants perceived both dimensions, with a significant bias for the

animacy percept (p = 0.0006). This bias was particularly strong in DNNs' representations, with a highly

significant correlation with the animacy model (VGG-19: r = 0.73; p < 0.0001; GoogLeNet: r = 0.55; p <

0.0001), but no significant correlation with the appearance model (VGG-19: r = -0.04; GoogLeNet: r = -0.01; p

> 0.5, for both DNNs). These results are also evident when inspecting dissimilarity matrices and comparing

them to the model matrices (Figure 3 A); animals appear to be separated from objects and lookalikes in both

behavioral and DNNs dissimilarity matrices. In addition, animals cluster together in behavioral data with some

additional similarities to the lookalike objects, which was absent in DNNs representations.

287
288 **Figure 2. DNNs predict human perception of object animacy but not appearance.** Representational similarity analysis (RSA;
289 Kriegeskorte et al., 2008a) results for the appearance model (dark gray) and the animacy model (light gray) are shown for human judgments
290 (left panel), and DNNs (right panel). Asterisks indicate significant values computed with permutation tests (10,000 randomizations of
291 stimulus labels), and error bars indicate SE computed by bootstrap resampling of the stimuli. *** p < 0.0001, ** p < 0.001, * p < 0.01.
292
Despite being orthogonal (r=0.07), both models predict animals and objects being separated from each other.

Therefore, in the next analysis we directly test whether lookalikes are represented more similar to animals or

other inanimate objects by computing two distance measures (Figure 3C-D): (1) the *appearance* distance (light

blue), reflects correlation distance between each animal (e.g., cow) and its matching lookalike object (e.g., cow-

mug), and (2) the *animate* distance (dark blue), reflects correlation distance between each object (e.g., mug)

and its matching lookalike object (cow-mug).

Confirming the above results, human judgments privilege animacy over object appearance; a test

across all object triads showed that the appearance distance (mean = 0.36, SEM = 0.001) was significantly

larger than the object distance (mean = 0.019, SEM = 0.001; $t_{(8)}$ = 18.73, p < 0.00001; Figure 3C). Similarly,

DNNs are not deceived by animal appearance and represent a cow-mug as being more similar to a mug

(animacy distance: VGG-19: mean 0.27, SEM 0.03; GoogLeNet: mean 0.35, SEM 0.05) as oppose to a living cow

(appearance distance: VGG-19: mean 0.27, SEM 0.03, $t_{(8)}$ = 4.93, p = 0.001; GoogLeNet: mean 0.35, SEM 0.05,

$t_{(8)}$ = 4.65, p = 0.002; Figure 3D). Taken together, these data show that both humans and DNNs set apart

animate from inanimate objects in accordance with one of the most reported divisions in ventral occipito-

temporal cortex (VTC) (Kriegeskorte et al., 2008b; Grill-Spector and Weiner, 2014).

308
309
310

311
312
Figure 3. Deep neural networks and human perception predict a representation based on object animacy, over
appearance. (A-B) Dissimilarities matrices (upper panel) show stimuli pairwise distances for behavioral judgments (A) and DNNs (B). (C-
D) The appearance distance (light blue: animals and lookalikes) and the animacy distance (dark blue: objects and lookalikes) are shown for
each object triad (n = 9), for human similarity judgments (C), and DNNs (D). Values are shown on segments, each indicating an object
triad. The length of the segments reflects the whole dissimilarity space. Thus, for each chart, the center and the outer points represent the
smaller and the largest dissimilarity value, respectively. The closer the value is to the center, the smaller the distance between stimuli within
a pair.
320

321
Animal appearance explains representational content in the human visual cortex

The above results, from DNNs and human behavior, point to the animacy model as the representational

structure to sustain object representations even with a stimulus set that sets object animacy apart from object

visual appearance. Based on previous studies, we would expect this organizational principle to have its neural

correlate in VTC (Kriegeskorte et al., 2008b; Grill-Spector and Weiner, 2014), possibly accompanied by a

further effect of visual appearance (Bracci and Op de Beeck, 2016). We collected human functional

neuroimaging (fMRI) data in an event-related design (Materials and Methods). All 27 images were presented in

a random order while participants performed two orthogonal tasks (matching the models) counterbalanced

across runs (Figure 1B). During the *animacy task*, participants judged whether the image on the screen depicted

a living animal (yes or no). During the *appearance task*, participants judged whether the image on the screen

looked like an animal (yes or no). In this way, we forced participants to group the lookalike condition in two

different ways depending on their properties (Figure 1C): either similarly to the object condition (as in the

animacy model) or similarly to the animal condition (as in the appearance model). Thus, in addition to test the

two independent predictive models, we can assess any task-related modulation.

We correlated the dissimilarity values predicted by the two models with the dissimilarity matrices derived from

neural activity patterns elicited in target regions of interest (ROIs; Figure 4A) in visual cortex. Our main ROI was

VTC, divided into its anterior portion (ant VTC) and posterior portion (post VTC). In addition, we included V1

as a control ROI. Analyses were performed separately for each task (Figure 4 C-D), but when no task-related

effects were observed, we mostly focus on results for the combined dataset.

To investigate the role of animacy and animal appearance in driving the VTC organization, correlation

values were tested in a 3x2 ANOVA with ROI (V1, post VTC, ant VTC) and Model (appearance, animacy) as

within-subject factors. Results revealed a significant ROI x Model interaction ($F_{(2,30)}$ = 9.40, p = 0.001; Figure

4B), thus highlighting differences in the relation between the two models and representational content in the

three ROIs. No positive correlations were found in V1 (lookalike: t <1; animacy: t < 1), suggesting that our

stimulus set was constructed appropriately to investigate neural representations without trivial confounds with

low-level visual features. Unexpectedly, and differently from DNNs and behavioral results, neural

representations in anterior and posterior VTC were significantly more correlated with the appearance model

than the animacy model (post VTC: $t_{(15)}$ = 3.85, p = 0.002; ant VTC: $t_{(15)}$ = 4.00, p = 0.001). In addition, we

also observed differences between the anterior and posterior portion of VTC. Whereas in anterior VTC both

models were significantly correlated with the neural data (appearance: $t_{(15)}$ = 8.70, p < 0.00001; animacy: $t_{(15)}$ =

5.36, p < 0.00001), in posterior VTC, only correlations with the appearance model significantly differed from

baseline (lookalike: $t_{(15)}$ = 4.56, p = 0.0004; animacy: t < 1.5). Replicating results within subjects, data analyzed

for the two tasks separately did not reveal any task effect in VTC (Figure 4C-D). In both tasks, the appearance

model was significantly more correlated with the neural data as oppose to the animacy model in post VTC

(animacy task: $t_{(15)}$ = 3.83, p = 0.002; appearance task : $t_{(15)}$ = 3.05, p = 0.008) and ant VTC (animacy task: $t_{(15)}$

= 2.97, p = 0.009; appearance task: $t_{(15)}$ = 3.44, p = 0.004). Furthermore, none of the ROIs showed an effect of

task in a direct statistical comparison (ant VTC: F < 1; post VTC: F < 1). To visualize the representational

structure in each ROI in more detail, dissimilarities matrices (averaged across tasks) are shown in Figure 6 A.

Findings from the ROI-based analysis were backed up by a whole-brain searchlight analysis, which

showed a significant preference for the appearance model over the animacy model in (right) VTC (p < 0.05,

one-tail t-test, TFCE corrected; Figure 5). The opposite contrast (animacy > appearance) revealed a non-

significant trend in the occipito-parietal cortex.

Figure 4. Animal appearance better explains representational content in human visual cortex. (A) Group averaged ROIs
(V1, post VTC, ant VTC) are shown on an inflated human brain template in BrainNet Viewer (Xia et al., 2013). (B-D) Representational
similarity analysis (RSA; Kriegeskorte et al., 2008) results for the appearance model (dark gray) and the animacy model (light gray) are
shown for the data combined across the two tasks (B), and for each task separately (C-D). Individual participant's (n =16) correlation values
are shown in purple. Purple-shaded backgrounds represent reliability values of the correlational patterns taking into account the noise in the
data (Materials and Methods). These values give an estimate of the highest correlation we can expect in each ROI. Error bars indicate SEM.
Asterisks indicate significant difference between the two models (*** p < 0.001; ** p < 0.01).

Figure 5 Whole-brain representational similarity analysis. Results of random-effects whole-brain RSA, for the direct contrast
between the two predictive models (appearance and animacy) corrected with the Threshold-Free Cluster Enhancement (TFCE; Smith and
Nichols, 2009) method. Voxel-wise corrected statistical maps (z =1.64; p < 0.05, one-sided t-test) are highlighted with dotted lines and
displayed on a brain template by means of BrainNet Viewer (Xia et al., 2013).
379

380 To further quantify these results, as for behavior and DNNs data, we computed the appearance

381 distance (light blue) and the animacy distance (dark blue) for each object triad. A test across subjects showed

382 that in anterior VTC (Figure 6B), across all triads, the appearance distance (between each animal and its

383 matching lookalike) was significantly smaller (mean: 0.94, SEM: 0.02, $t_{(15)}$ = 3.97, p = 0.001) relative to the

animacy distance (between each object and its matching lookalike; mean: 1.02, SEM: 0.01). Converging results where observed when the data were analyzed for the two tasks separately (animacy task: $t_{(15)}$ = 2.62, p = 0.019; appearance task: $t_{(15)}$ = 3.78, p = 0.002), thus highlighting the robustness of these findings. Results did not reach significance in posterior VTC (animacy distance: mean 1.0, SEM: 0.02; appearance distance: mean 0.94, SEM: 0.02; $t_{(15)}$ = 1.94, p = 0.07). Instead, in V1 we observed the opposite trend – smaller distance between neural patterns for lookalikes and objects (animacy distance: mean 0.52, SEM: 0.01; appearance distance: mean 1.01, SEM: 0.01; $t_{(15)}$ = 4.81, p = 0.0002); thus, suggesting that results in ant VTC cannot be explained by confounds between appearance and low-level visual properties.

Figure 6. The neural similarity space in VTC reflects animal appearance. (A) The neural dissimilarity matrices (1 minus Person's r) derived from the neural data (averaged across subjects and tasks) show pairwise dissimilarities among stimuli in the three ROIs (data averaged across tasks). (B) For the three ROIs, the appearance distance (light blue: between animals and lookalikes) and the animacy distance (dark blue: between objects and lookalikes) are shown for each object triad (n = 9). Values are averaged across subjects (n =16) and tasks (animacy and appearance) and shown on segments, each referring to an object triad. The length of the segments reflects the whole dissimilarity space. Thus, for each chart, the inner and outer points represent the smaller and the largest dissimilarity value, respectively. The closer values are to the center, the smaller the distance between stimuli within pairs.

Together these results show that the animacy organization reported in VTC is largely explained by animal appearance rather than object animacy per se. Inanimate objects (e.g., cow-mug) that share with animals neither functional properties nor animacy, are represented closer to living animals than to other inanimate objects with which they share object category (e.g., a mug), and functional/semantic properties. The animal appearance might relate to high-level visual features such as faces, eyes, limbs, and bodies, which are not generally present in inanimate objects. This result, replicated across tasks, is particularly striking in light of the aforementioned results from human judgments and DNNs, which privilege object animacy over appearance.

Do VTC representations distinguish between lookalikes and real animals?

In anterior VTC the two (independent) models both differ from baseline. Therefore, although the lookalikes were closer to animals than to objects, lookalikes and animals might be encoded separately in VTC. Another

possibility is that the positive correlation with the animacy model is fully driven by the distinction between

animals and (non-lookalike) objects (which both predictive models share), without any representation of the

lookalikes as being different from real animals (on which the two predictive models make opposite predictions).

In other words, does VTC discriminate between animals and objects that look like animals or is it largely blind

to this category distinction? If VTC does not distinguish between animals and objects that have animal

appearance then there should be no difference between within- and between-condition correlations for these

two categories. In what follows we investigated this hypothesis.

To this aim, we computed the *category index*, which reflects the extent to which representations for

two conditions can be discriminated from each other. That is, for each subject and condition, the average

within-condition correlation (e.g., comparing an animal with other animals) and between-condition correlation

(e.g., comparing animals with lookalikes or objects) were calculated. For each condition pair (i.e., animal-

lookalike, animal-object, and lookalike-object), the *category index* was computed as follows: first averaging the

two within-condition correlations (for animals and lookalikes) and then subtracting the between-condition

correlation for the same two categories (animals-lookalikes). For between-condition correlations, diagonal

values (e.g., duck and duck-kettle) were excluded from this computation to avoid intrinsic bias between

conditions that share either animal appearance (i.e., duck and duck-kettle) or object category (i.e., kettle and

duck-kettle). Category indexes above baseline indicate that two category representations are separated. In both

VTC regions, the category index could distinguish between animals and objects (ant VTC: $t_{(15)} = 6.00$, p =

0.00002; post VTC: $t_{(15)} = 4.03$, p = 0.001; Figure 7, left panel), and objects and lookalikes (ant VTC: $t_{(15)} = 7.40$,

p < 0.00001; post VTC: $t_{(15)} = 4.02$, p = 0.001). The category index between animals and lookalikes was

significant in ant VTC ($t_{(15)} = 5.38$, p = 0.00007) but did not differ from baseline (after correcting for multiple

comparisons: p 0.05/9 = p < 0.005) in post VTC ($t_{(15)} = 2.34$, p = 0.03). Furthermore, in both ROIs, the

category index for animals and lookalikes was significantly smaller than the other two category indexes (ant

VTC: $t_{(15)} > 3.49$, p < 0.004, for both indexes; post VTC: $t_{(15)} > 3.45$, p < 0.005, for both indexes). In V1 none

of the conditions could be distinguished (t < 1, for all condition pairs). As for previous analyses, these results

were replicated when data were analyzed for each task separately (the category index for animals vs. lookalikes

was significantly smaller than the other two indexes: animacy task: p < 0.004; appearance task: p < 0.01). Thus,

VTC representations reflect animal appearance much more than animacy, with a small remaining difference

between animals and lookalikes in the anterior part of VTC (but not posterior VTC).

442
443
444   **Figure 7. VTC representations differ in category discriminability from DNNs and human behavior.** The *category index*
445   reflects representational discriminability among the three stimulus categories (animals, lookalikes, and objects) and is computed for each
446   condition pair by subtracting the average of between-condition correlations (e.g., for animals and lookalikes), from the average of within-
447   condition correlations (e.g., for animals and lookalikes). Results are reported for neural data (left panel), behavior (middle panel), and DNNs

Different results were observed for behavioral judgments and DNNs. In both cases, category indexes

distinguished between animals and objects (behavior: $p = 0.0001$; VGG-19: $p < 0.00001$; GoogLeNet: $p <$

0.00001), between animals and lookalikes (behavior: $p = 0.0006$; VGG-19: $p < 0.00001$; GoogLeNet: $p =$

0.0005), but did not differ between lookalikes and objects (behavior: $p = 0.03$ − num. comparisons: p 0.05/3 =

$p < 0.01$; VGG-19: $p = 0.46$; GoogLeNet: $p = 0.15$). This suggests that differently from VTC representations,

human judgments and convolutional neural network take object category into account; two mugs belong to the

same object category regardless of their shape.

Together, these results show that representations in VTC are not predicted either by convolutional

neural networks or human judgments. Whereas the former privileges the role of animal appearance, the latter

favours the role of superordinate object category such as objects versus animals.

The coding for animal appearance in VTC interferes with invariant object identification.

Previous studies have shown that VTC contains information about object identity, with a high degree of

invariance for a variety of image transformations (Gross et al., 1972; Desimone et al., 1984; Grill-Spector et al.,

1998; Grill-Spector et al., 1999). Despite the reported finding that a lookalike object is represented very

differently from other objects, VTC representations might still allow for object identity identification (e.g.

recognizing that a cow-mug is a mug). To allow this, the representation of a lookalike object should be more

similar to another object from the same basic category (e.g., a cow-mug and a regular mug) than to other

objects. We operationalize this as the prediction that the within-triad correlation between each lookalike and its

corresponding non-lookalike object would be significantly higher than the average of correlation of this same

lookalike to objects from other triads. We call this the *identity index*. That is, for each subject and for each

lookalike object, we took the on-diagonal correlation (e.g., between the cow-mug and the mug) and subtracted

the average of off-diagonal correlations (e.g., between the cow-mug and the remaining objects). We computed

the *identity index* separately for animals (*animal identity index*: is a cow-mug closer to a cow relative to other

animals?) and objects (*object identity index*: is a cow-mug closer to a mug relative to other objects?). Figure 8

shows results for the dataset combined across the two tasks.

Figure 8. VTC representations sustain animal identity, but not object identity, categorization **(A)** The *identity index* reflects information for individual object ad animal pairs (e.g., the cow-mug and the mug represent the same object; the cow-mug and the cow represent the same animal) and is computed separately for each condition (animals and objects). For each lookalike object (n= 9) we took the on-diagonal correlation (e.g., between the cow-mug and the mug) and subtracted the average off-diagonal correlations (e.g., between the cow-mug and the remaining objects). The identity index for animals and objects was computed for the brain data (V1, post VTC, and ant VTC), behavioral data (similarity judgments), DNNs (VGG-19, GoogLeNet), and the image pixelwise data. Light gray: animal identity index; dark gray: object identity index. Asterisks (**** p < 0.00001, *** < p < 0.0001, ** < p < 0.001, * p < 0.01) indicate significant values relative to baseline, and error bars indicate SEM. (B) For each dataset, dissimilarity matrices used to compute the identity index are shown separately for animals and objects.

For brain data, a test across all conditions (Figure 8, left panel) revealed differences in the amount of stimulus identity information carried in the three ROIs. In V1 there was significant identity information for objects ($t_{(8)}$ = 4.76, p = 0.001) but not for animals (t < 1). This result can be explained considering differences in image low-level visual properties across conditions; objects and lookalikes were more similar to each other relative to animals and lookalikes. Confirming this interpretation, the same trend was observed for image pixelwise information (Figure 8A, right panel), where we observed significant identity information for objects ($t_{(8)}$ = 3.16, p = 0.01) but not for animals (t < 1). In posterior VTC, neither identity index survived correction for multiple comparisons (p 0.05/6 = p < 0.008; animals: $t_{(8)}$ = 2.82, p = 0.02; objects $t_{(8)}$ = 3.09, p = 0.01). In anterior VTC object identity information decreased and animal identity information increased; here only the animal identity index was significantly above baseline (animals: $t_{(8)}$ = 3.88, p = 0.005; objects: $t_{(8)}$ = 1.93, p = 0.09). Results were replicated when data were analyzed separately for the two tasks (ant VTC: animals, p < 0.009; objects, p > 0.4, for both tasks). Together, these results suggest that representational content in anterior VTC is differently biased to represent animal and object's identity, containing more information for the former.

In line with previous analyses, different results were observed for behavioral judgments and DNNs. For human similarity judgments, a test across conditions revealed significant identity information for both animals ($t_{(8)}$ = 17.98, p < 0.00001) and objects ($t_{(8)}$ = 24.44, p < 0.00001; Figure 8A, middle panel). Similarly, DNNs were able to discriminate individual stimulus identities for animals (VGG-19: $t_{(8)}$ = 3.84, p = 0.005; GoogLeNet:

$t_{(8)}$ = 5.42, p = 0.0006) as well as objects (VGG-19: $t_{(8)}$ = 5.67, p = 0.0005; GoogLeNet: $t_{(8)}$ = 5.04, p = 0.001;

Figure 8A, right panel).

Strikingly, after years of searching for models that would match the tolerance in the most advanced

category representations in primate ventral visual cortex, we have now found an object transformation for

which neural networks sustain invariant object recognition to a higher degree than anterior VTC

representations.

Discussion

With a stimulus set that specifically dissociates object appearance from object category, we investigated the

characteristics of the previously reported organization of object representations in the superordinate distinction

of animate versus inanimate in the human brain, deep neural networks, and behavior. Human behavioral

judgments and neural networks privilege animacy over appearance. Conversely, representations in ventral

occipitotemporal cortex mostly reflect object appearance. Thus, although deep neural networks can largely

predict human behavior, representations in ventral occipitotemporal cortex deviate from behavior and neural

network representations.

Our results can be summarized as follows. First, representational content in VTC reflects animal

appearance more than object identity and animacy; even though the mug and the cow-mug share many high-

level properties (e.g., object identity, size, function, manipulation), as well as low-level properties (e.g., shape and

texture), VTC represents a cow-mug closer to a real cow than to a mug. Second, VTC representations are not

explained by either human perception or DNNs, which were not deceived by object appearance, and judged a

cow-mug being closer to a mug as opposed to a real cow. Third, given its bias in favor of animal appearance,

VTC representations are remarkably poor in providing information about object identity, that is, to reflect that a

cow-mug is a mug. This is not a desirable property for a 'what' pathway that, according to uniformly held views

in visual neuroscience (e.g., DiCarlo et al., 2012), builds up representations that sustain reliable and

transformation-invariant object identification and categorization. Fourth, VTC representations are not

modulated by task demand, and the similarity in responses to animals and lookalike objects persists even when

participants performed a task requiring focusing on object animacy.

The animacy division is considered one of the main organizational principles in visual cortex (e.g., Grill-

Spector and Weiner, 2014), but information content underlying this division is highly debated (Baldassi et al.,

2013; Grill-Spector and Weiner, 2014; Nasr et al., 2014; Bracci and Op de Beeck, 2016; Bracci et al., 2017b;

Kalfas et al., 2017). Animacy and other category distinctions are often correlated with a range of low- and

higher-level visual features such as the spatial frequency spectrum (Nasr et al., 2014; Rice et al., 2014) and shape

(Cohen et al., 2014; Jozwik et al., 2016), but the animacy structure remains even when dissociated from such

features (Bracci and Op de Beeck, 2016). Here we question what we imply with animacy. Previous reports

suggest that the extent to which an object is perceived as being alive and animate is reflected in VTC

representations, giving rise to a continuum where those animals perceived more animate (e.g., primates) are

closely represented to humans, whereas those animals perceived less animate (e.g., bugs) are represented away

from humans and closer to inanimate objects (Connolly et al., 2012; Sha et al., 2015). Contrary to this

prediction, our results suggest that information content underlying the animacy organization does not relate to

the animacy concept: whether an object is perceived as being alive and animate is close to irrelevant. Instead,

what mostly matters is animal appearance; that is, whether an inanimate object lookalikes and shares high-level

visual features with animals. Indeed, in VTC, inanimate objects such as a mug, a water kettle, or a pair of slippers

with animal features (e.g., eyes, mouth, tail) are represented close to living animals (Figure 4,6).

Does this mean that it is all about animal appearance? Probably not: our results showed that VTC

representational content can be explained by both models, though uncorrelated (r = 0.07; Figure 4), and carries

enough information to distinguish between real animals and lookalikes (Figure 7). What we suggest is that

information about animals in VTC is overrepresented relative to information about objects – to the extent that

even inanimate objects, if having animal appearance, are represented similarly to animate entities. A VTC bias

towards animal representations was further supported by results showing significant information for animal's

identity, which was not observed for objects; that is, VTC representations contain information to discriminate

that a duck-shaped water kettle represents a duck, but not to discriminate that it is a kettle (Figure 8). An

everyday life example of this bias is our strong predisposition to perceive faces (and animals) in meaningless

patterns such as toast or clouds (pareidolia), which results in face-like activations in the fusiform face area

(Hadjikhani et al., 2009). To our knowledge, similar effects reported for inanimate objects are rare. We could

speculate that having a system devoted to detecting animate entities and biased to represent similarly animals

and inanimate objects that resemble animals, might have been beneficial from an evolutionary perspective. The

chance for our ancestors to survive in the wild necessitated fast and successful detection of predators. Such a

biased system would have been advantageous: better mistaking a bush for a lion than the other way around.

Thus, the VTC bias to represent lookalikes similarly to real animals might be the result of an evolution-long

"training", similarly to the way, in artificial intelligence, neural networks, trained to recognize animals, start to

detect animals in random-noise images (Szegedy et al., 2015).

This speculation points to one possible explanation for a particularly surprising aspect of our findings,

namely the discrepancy in representations between VTC at one hand and artificial DNN at the other hand.

Indeed, whereas DNNs were able to predict aspects of human perception such as setting apart animals from

inanimate objects (Figure 6), and discriminating both animal and object identity (Figure 8), contrary to recent

findings (Cadieu et al., 2014; Guclu and van Gerven, 2014; Khaligh-Razavi and Kriegeskorte, 2014; Yamins et al.,

2014) our results show that DNNs representations (at the higher processing layers) do not predict human

visual cortex representations. Here it is noteworthy that the training history of the DNNs was focused upon

the categorization of a large number of categories and was not specifically biased towards e.g. animate objects.

This training history might explain why DNNs are very good, and even better than human visual cortex, at

identifying a cow-mug as being a mug – not a cow.

Our results show that, across all analyses, human behavior was better predicted by DNNs than human

VTC, privileging what an object is (two mugs), as opposed to its visual appearance. Information from DNNs

and behavioral judgments did not show a category distinction between lookalikes and inanimate objects (e.g., all

objects; Figure 7), yet allowed object identification across changes in appearance (e.g., a cow-mug is a mug;

Figure 8). These results differ from previous studies reporting some degree of correspondence between

behavior and visual cortex information content (Williams et al., 2007; Carlson et al., 2014; van Bergen et al.,

2015). This discrepancy might relate to the choice of task used to obtain the behavioral results that were

compared to neural data; here we used a cognitive task (similarity judgments), while a categorization task based

on reaction times (e.g., visual search task) might have been a better predictor for visual cortex representations

(Proklova et al., 2016; Cohen et al., 2017).

Finally, visual cortex representations were not modulated by tasks. Despite the different focus on

object appearance in one case (appearance task), and on object identity in the other case (animacy task), the

neural data was striking similar across task sessions revealing no difference in any of the performed analyses.

These results confirm, and add to, recent findings showing that task demand appears not to have much

influence on the representational structure of ventral visual cortex (Harel et al., 2014; Bracci et al., 2017a;

Bugatus et al., 2017; Hebart et al., 2018).

The mere observation that a stimulus that looks like an animal or part of it, such as a face, can elicit
animal- or face-like responses in ventral visual cortex is not novel, with studies on face pareidolia being the
most relevant example (Hadjikhani et al., 2009). What makes our study novel and our results striking, is the
availability of behavioral and neural network data that makes a very different prediction; the systematic
comparison and dissociation of neural, behavioral, and DNN representations; the quantification of the degree of
bias towards representing appearance rather than animacy; the persistence of this bias in VTC even when
performing a task requiring to report animacy; and the detrimental effect of this bias upon the informational
content about object identity.

To summarize, these results highlight substantial differences in the way categorical representations in
the human brain, human judgments, and deep neural networks characterize objects. Whereas DNN
representations resemble human behavior and heavily weight object identity, representations in ventral visual
cortex are very much constrained by object appearance. Based on these findings, we might have to reconsider
the traditional view of the human visual cortex as a general object recognition machine like the artificial neural
networks are trained to be.

Author Contributions

S.B. and H.O.B designed research; S.B. performed research; S.B. and I.K. analyzed data; S.B., I.K. and H.O.B.

wrote the paper.

Acknowledgements

S.B. was funded by FWO (Fonds Wetenschappelijk Onderzoek) through a postdoctoral fellowship (12S1317N)

and a Research Grant (1505518N). H.O.B. was supported by the European Research Council (ERC- 2011-StG-

284101), a federal research action (IUAP-P7/11), the KU Leuven Research Council (C14/16/031), and a

Hercules grant ZW11_10.

References

Baldassi C, Alemi-Neissi A, Pagan M, Dicarlo JJ, Zecchina R, Zoccolan D (2013) Shape
similarity, better than semantic membership, accounts for the structure of visual object
representations in a population of monkey inferotemporal neurons. PLoS computational
biology 9:e1003167.

Bracci S, Op de Beeck H (2016) Dissociations and Associations between Shape and
Category Representations in the Two Visual Pathways. The Journal of neuroscience : the
official journal of the Society for Neuroscience 36:432-444.

Bracci S, Daniels N, Op de Beeck H (2017a) Task Context Overrules Object- and Category-
Related Representational Content in the Human Parietal Cortex. Cerebral cortex 27:310-
321.

Bracci S, Ritchie JB, de Beeck HO (2017b) On the partnership between neural
representations of object categories and visual features in the ventral visual pathway.
Neuropsychologia 105:153-164.

Brainard DH (1997) The Psychophysics Toolbox. Spatial vision 10:433-436.

Bugatus L, Weiner KS, Grill-Spector K (2017) Task alters category representations in
prefrontal but not high-level visual cortex. NeuroImage 155:437-449.

Cadieu CF, Hong H, Yamins DL, Pinto N, Ardila D, Solomon EA, Majaj NJ, DiCarlo JJ (2014)
Deep neural networks rival the representation of primate IT cortex for core visual object
recognition. PLoS computational biology 10:e1003963.

Caramazza A, Shelton JR (1998) Domain-specific knowledge systems in the brain the
animate-inanimate distinction. Journal of cognitive neuroscience 10:1-34.

Carlson TA, Ritchie JB, Kriegeskorte N, Durvasula S, Ma J (2014) Reaction time for object
categorization is predicted by representational distance. Journal of cognitive neuroscience
26:132-142.

Cohen MA, Alvarez GA, Nakayama K, Konkle T (2017) Visual search for object categories is
predicted by the representational architecture of high-level visual cortex. Journal of
neurophysiology 117:388-402.

Cohen MA, Konkle T, Rhee JY, Nakayama K, Alvarez GA (2014) Processing multiple visual
objects is limited by overlap in neural channels. Proceedings of the National Academy of
Sciences of the United States of America 111:8955-8960.
665
666   Connolly AC, Guntupalli JS, Gors J, Hanke M, Halchenko YO, Wu YC, Abdi H, Haxby JV
667   (2012) The representation of biological classes in the human brain. The Journal of
668   neuroscience : the official journal of the Society for Neuroscience 32:2608-2618.
669
670   Desimone R, Albright TD, Gross CG, Bruce C (1984) Stimulus-selective properties of
671   inferior temporal neurons in the macaque. The Journal of neuroscience : the official journal
672   of the Society for Neuroscience 4:2051-2062.
673
674   Downing PE, Jiang Y, Shuman M, Kanwisher N (2001) A cortical area selective for visual
675   processing of the human body. Science 293:2470-2473.
676
677   Gao T, Newman GE, Scholl BJ (2009) The psychophysics of chasing: A case study in the
678   perception of animacy. Cogn Psychol 59:154-179.
679
680   Gao T, McCarthy G, Scholl BJ (2010) The wolfpack effect. Perception of animacy irresistibly
681   influences interactive behavior. Psychol Sci 21:1845-1853.
682
683   Grill-Spector K, Weiner KS (2014) The functional architecture of the ventral temporal
684   cortex and its role in categorization. Nature reviews Neuroscience 15:536-548.
685
686   Grill-Spector K, Kushnir T, Edelman S, Itzchak Y, Malach R (1998) Cue-invariant activation in
687   object-related areas of the human occipital lobe. Neuron 21:191-202.
688
689   Grill-Spector K, Kushnir T, Edelman S, Avidan G, Itzchak Y, Malach R (1999) Differential
690   processing of objects under various viewing conditions in the human lateral occipital
691   complex. Neuron 24:187-203.
692
693   Gross CG, Rocha-Miranda CE, Bender DB (1972) Visual properties of neurons in
694   inferotemporal cortex of the Macaque. Journal of neurophysiology 35:96-111.
695
696   Guclu U, van Gerven MA (2014) Unsupervised feature learning improves prediction of
697   human brain activity in response to natural images. PLoS computational biology
698   10:e1003724.
699
Guclu U, van Gerven MA (2015) Deep Neural Networks Reveal a Gradient in the
Complexity of Neural Representations across the Ventral Stream. The Journal of
neuroscience : the official journal of the Society for Neuroscience 35:10005-10014.

Hadjikhani N, Kveraga K, Naik P, Ahlfors SP (2009) Early (M170) activation of face-specific
cortex by face-like objects. Neuroreport 20:403-407.

Harel A, Kravitz DJ, Baker CI (2014) Task context impacts visual object processing
differentially across the cortex. Proceedings of the National Academy of Sciences of the
United States of America 111:E962-971.

He K, Zhang X, Ren S, Sun J (2015) Delving Deep into Rectifiers: Surpassing Human-Level
Performance on ImageNet Classification. arXiv 1502.01852v1.

Hebart MN, Bankson BB, Harel A, Baker CI, Cichy RM (2018) The representational dynamics
of task and object processing in humans. Elife 7.

Jozwik KM, Kriegeskorte N, Mur M (2016) Visual features as stepping stones toward
semantics: Explaining object similarity in IT and perception with non-negative least squares.
Neuropsychologia 83:201-226.

Kalfas I, Kumar S, Vogels R (2017) Shape Selectivity of Middle Superior Temporal Sulcus
Body Patch Neurons. eNeuro 4.

Kanwisher N, McDermott J, Chun MM (1997) The fusiform face area: a module in human
extrastriate cortex specialized for face perception. The Journal of neuroscience : the official
journal of the Society for Neuroscience 17:4302-4311.

Khaligh-Razavi SM, Kriegeskorte N (2014) Deep supervised, but not unsupervised, models
may explain IT cortical representation. PLoS computational biology 10:e1003915.

Kheradpisheh SR, Ghodrati M, Ganjtabesh M, Masquelier T (2016a) Deep Networks Can
Resemble Human Feed-forward Vision in Invariant Object Recognition. Scientific reports
6:32672.

Kheradpisheh SR, Ghodrati M, Ganjtabesh M, Masquelier T (2016b) Humans and Deep
Networks Largely Agree on Which Kinds of Variation Make Object Recognition Harder.
Frontiers in computational neuroscience 10:92.

Konkle T, Oliva A (2012) A real-world size organization of object responses in
occipitotemporal cortex. Neuron 74:1114-1124.

Kriegeskorte N (2015) Deep Neural Networks: A New Framework for Modeling Biological
Vision and Brain Information Processing. Annual review of vision science 1:417-446.

Kriegeskorte N, Goebel R, Bandettini P (2006) Information-based functional brain mapping.

Proceedings of the National Academy of Sciences of the United States of America

103:3863-3868.

Kriegeskorte N, Mur M, Bandettini P (2008a) Representational similarity analysis -

connecting the branches of systems neuroscience. Frontiers in systems neuroscience 2:4.

Kriegeskorte N, Mur M, Ruff DA, Kiani R, Bodurka J, Esteky H, Tanaka K, Bandettini PA

(2008b) Matching categorical object representations in inferior temporal cortex of man and

monkey. Neuron 60:1126-1141.

Kubilius J, Bracci S, Op de Beeck HP (2016) Deep Neural Networks as a Computational

Model for Human Shape Sensitivity. PLoS computational biology 12:e1004896.

Nasr S, Echavarria CE, Tootell RB (2014) Thinking outside the box: rectilinear shapes

selectively activate scene-selective cortex. The Journal of neuroscience : the official journal

of the Society for Neuroscience 34:6721-6735.

New J, Cosmides L, Tooby J (2007) Category-specific attention for animals reflects ancestral

priorities, not expertise. Proceedings of the National Academy of Sciences of the United

States of America 104:16598-16603.

Oosterhof NN, Connolly AC, Haxby JV (2016) CoSMoMVPA: Multi-Modal Multivariate

Pattern Analysis of Neuroimaging Data in Matlab/GNU Octave. Frontiers in neuroinformatics

10:27.

Op de Beeck HP (2010) Against hyperacuity in brain reading: spatial smoothing does not

hurt multivariate fMRI analyses? NeuroImage 49:1943-1948.

Op de Beeck HP, Torfs K, Wagemans J (2008) Perceived shape similarity among unfamiliar

objects and the organization of the human object vision pathway. The Journal of

neuroscience : the official journal of the Society for Neuroscience 28:10111-10123.

Op de Beeck HP, Brants M, Baeck A, Wagemans J (2010) Distributed subordinate specificity

for bodies, faces, and buildings in human ventral visual cortex. NeuroImage 49:3414-3425.

Proklova D, Kaiser D, Peelen MV (2016) Disentangling Representations of Object Shape and

Object Category in Human Visual Cortex: The Animate-Inanimate Distinction. Journal of

cognitive neuroscience 28:680-692.

Rice GE, Watson DM, Hartley T, Andrews TJ (2014) Low-level image properties of visual
objects predict patterns of neural response across category-selective regions of the ventral
visual pathway. The Journal of neuroscience : the official journal of the Society for
Neuroscience 34:8837-8844.
789
790 Ritchie JB, Bracci S, Op de Beeck H (2017) Avoiding illusory effects in representational
791 similarity analysis: What (not) to do with the diagonal. NeuroImage 148:197-200.
792
793 Russakovsky O, Deng J, Su H, Krause J, Satheesh S, Ma S, Huang Z, Karpathy A, Khosla A,
794 Bernstein M, Berg A, Fei-Fei L (2014) ImageNet Large Scale Visual Recognition Challenge.
795 arXiv 1409.0575v3.
796
797 Scholl BJ, Gao T (2013) Perceiving Animacy and Intentionality: Visual Processing or Higher-
798 Level Judgment? In MD Rutherford and Valerie A Kuhlmeier (Eds) Social Perception:
799 Detection and Interpretation of Animacy, Agency, and Intention (197-229.
800
801 Sha L, Haxby JV, Abdi H, Guntupalli JS, Oosterhof NN, Halchenko YO, Connolly AC (2015)
802 The animacy continuum in the human ventral vision pathway. Journal of cognitive
803 neuroscience 27:665-678.
804
805 Simonyan K, Zisserman A (2014) Very deep convolutional networks for large-scale image
806 recognition. arXiv 1409.1556.
807
808 Smith SM, Nichols TE (2009) Threshold-free cluster enhancement: addressing problems of
809 smoothing, threshold dependence and localisation in cluster inference. NeuroImage 44:83-
810 98.
811
812 Szegedy C, Liu W, Jia Y, Sermanet P, Reed S, Anguelov D, Erhan D, Vanhoucke V,
813 Rabinovich A (2015) Going Deeper With Convolutions. arXiv 1409.4842v1
814
815 Tremoulet PD, Feldman J (2000) Perception of animacy from the motion of a single object.
816 Perception 29:943-951.
817
818 van Bergen RS, Ma WJ, Pratte MS, Jehee JF (2015) Sensory uncertainty decoded from visual
819 cortex predicts behavior. Nature neuroscience 18:1728-1730.
820
821 Vedaldi A, Lenc K (2016) MatConvNet: Convolutional Neural Networks for MATLAB.
822 arXiv:14124564v3.
823
Williams MA, Dang S, Kanwisher NG (2007) Only some spatial patterns of fMRI response
are read out in task performance. Nature neuroscience 10:685-686.

Xia M, Wang J, He Y (2013) BrainNet Viewer: a network visualization tool for human brain

connectomics. PloS one 8:e68910.

Yamins DL, Hong H, Cadieu CF, Solomon EA, Seibert D, DiCarlo JJ (2014) Performance-

optimized hierarchical models predict neural responses in higher visual cortex. Proceedings

of the National Academy of Sciences of the United States of America 111:8619-8624.