# Visual recency bias is explained by a mixture model of short term memory

Kristjan Kalm,* Dennis Norris

MRC Cognition and Brain Sciences Unit, University of Cambridge

15 Chaucer Road, Cambridge, CB2 7EF, UK

* E-mail: kristjan.kalm@mrc-cbu.cam.ac.uk.

## Abstract

Human bias towards more recent events is a common and well-studied phenomenon. However, recent studies in a wide range of sensory domains have shown that this recency bias persists even when past events contain no information about the future. Reasons for this suboptimal behaviour are not well understood and the internal model that leads people to exhibit recency bias is unknown. Here we use a well-known orientation estimation task to frame the human recency bias in terms of incremental Bayesian inference. We show that the only Bayesian model capable of explaining the recency bias relies on a weighted mixture of past states. Furthermore, we suggest that this mixture model is a consequence of participants' failure to infer a model for data in visual short term memory, and reflects the nature of the internal representations used in the task.

## Significance statement

Human bias towards more recent events is a common and well-studied phenomenon which occurs even when past events contain no information about the future. In this paper we investigate why such suboptimal behaviour should occur and what it tells us about the underlying mechanisms of perception and memory. Our results reveal that the internal model underlying the recency bias is a weighted mixture of past events. We suggest that this reflects the nature of representations in visual short term memory.

# Introduction

In a rapidly changing world our model of the environment needs to be continuously updated. Often recent information is a better predictor of the environment than the more distant past [1, 2]: for example, the location of a moving object is better predicted by its location one second ago than a minute ago. However, human observers seem to rely on recent experience even when it provides no information about the future at all [3, 4, 5, 6, 7]. Such recency bias seems to be domain-general and not constrained to a particular task or feature dimension [8]. Why should this be so, and what can it tell us about the mechanisms of perception and memory?

The most extensive quantitative data on the human recency bias comes from a study of visual orientation estimation by Fischer and Whitney [3]. In that study participants were presented with a randomly oriented grating (Gabor) on each trial and asked to report the orientation by adjusting a bar using the arrow keys (Fig 1A). Participants' error distributions

**Fig 1: Orientation estimation task [3].** (A) Participants observed randomly oriented Gabor stimuli and reported the orientation of each Gabor by adjusting a response bar. Stimuli were presented for 500 ms and separated in time by 5s. (B) Single subject's errors (red dots) as a function of the relative orientation of the previous trial. Gray line is average error; red line shows a first derivative of a Gaussian (DoG) curve fit to the data. (C) Average recency bias amplitude across participants computed for stimuli presented one, two and three trials back from the present. Error bars represent ±1 standard deviation of the bootstrapped distribution.

revealed that although responses were centred on the correct orientations over the course of the entire experiment, on a trial-by-trial basis the reported orientation was systematically (and precisely) biased in the direction of the orientation seen on the previous trial. For example, when the Gabor on the previous trial was oriented more clockwise than the Gabor on the present trial, participants perceived the present Gabor as being tilted more clockwise than its

true orientation (Fig 1B).

Since the orientations of the stimuli were generated randomly in this task the recency bias indicates that participants are not behaving optimally. In other words, the previous trial contained no information about the next trial and hence the optimal model would consider all orientations as equally likely in the future. In such case the participants' error distributions would simply be proportional to the sensory noise and always centred around the true stimulus value (Fig 2A, top row). However, here participants assume a model of the environment where past states are informative about the future (Fig 2A, bottom row), which is clearly false.

In the current study we use the Fischer and Whitney task [3] to investigate what is the participants' model of the environment that gives rise to the recency bias. We frame this question in terms of sequential Bayesian inference which allows us to test hypotheses about the participant's model of the environment at any trial given sensory information (orientation of the Gabor) and the recorded response (Fig 2, see also *Bayesian orientation estimation* in *Supporting Information*). We test three alternative hypotheses about the model behind the recency bias which are all formulated as sequential Bayesian inference models so that they can be directly compared to each other.

**Fig 2: Bayesian orientation estimation and recency bias.** Participant's estimate of the orientation ($p(z|y)$, green line) combines sensory evidence ($p(y|z)$, blue line) with prior expectation ($p(z)$, red line). Participant's response can be thought of as a sample from the posterior distribution. All distributions are Von Mises since orientation is a circular variable. (A) Top row: for optimal behaviour participant's prior should be flat and posterior equal to the sensory evidence. Bottom row: Recency bias occurs when information about previous stimuli (orientation estimate at trial $n-1$, green line in top row) is transferred to the prior expectation about the next stimulus (red line, bottom row). Here the prior for trial $t$ is just the posterior from previous trial $t-1$. (B) Natural prior model. Top row: participants prior is based on the statistics of the natural environment [9]. Bottom row: participants prior is a mixture of the previous stimulus and the natural statistics.

**Von Mises filter**

First, we test the hypothesis that participants assume that the current state of the environment is the best guess about it's future. This *identity model* is the simplest Bayesian incremental updating model (a Bayesian filter) that can plausibly represent the orientation estimation task. Bayesian filters (such as the Kalman filter [10]) are widely used in explaining human behaviour and have been previously proposed to explain the temporal continuity effects in perception [5, 11, 12].

Here we use the circular approximation of the Kalman filter called the Von Mises filter (VMF) where the latent state and measurement noise are distributed according to Von Mises and not Gaussian distributions [13, 14]. An example of a simple VMF is depicted on Fig 2A, where the prediction $p(z_t)$ at the bottom row is derived from the previously estimated posterior distribution $p(z_{t_1}|y_{t-1})$, or in other words, the latent state transition model is identity. See *Von Mises filter* in *Methods* for details.

**Natural prior model**

A simple identity model as outlined above ignores the fact that people's orientation judgements are more accurate at cardinal orientations, reflecting the statistics of contours in natural environment [9]. Such bias suggests that the observer's internal model matches the environment, a hallmark of Bayesian optimality. Fig 3 depicts orientation statistics of a natural image and participants' orientation sensitivity extracted from a behavioural task [9]. Hence we can supplement the identity model with a *natural prior* so that participants modulate the identity prediction by taking into account the natural statistics of orientations in the environment.

Since the size of the recency bias in the task was independent of stimulus orientation [3] we can rule out a static natural prior in advance. Instead, we assume here that the prior is a mixture of the stimulus on the previous trial and the natural prior distribution. An illustration of a single step in the natural prior model is depicted on Fig 2B, where the prediction $z_t$ is equal to the mixture of the previous stimulus and a static natural prior. See *Natural prior model* in *Methods* for details.

**Mixture model**

Last, we test the hypothesis that participants' predictions incorporate information from multiple past trials. Such a *mixture model* assumes that the participant's model of the environment is a mixture of multiple past states so that more recent states contribute more than older ones. The two previous hypotheses both assume that the model of the environment $p(z)$ is inferred only based on the previous latent state. Contrastingly, the human recency bias clearly extends beyond the previous state – it is greatest for the most recent state and decays for each further

**Fig 3: Natural prior for orientation [9].** (A) A natural image (left) and a distribution of contour orientations extracted from the image. (B) Average prior distribution of orientations across all participants estimated with a noisy orientation judgement task. The grey error region shows ±1 standard deviation of 1,000 bootstrapped estimated priors.

state into the past (Fig 1C). In order to model such time-decaying recency bias over several past states we modify the VMF so that its prior distribution reflects a time-decaying mixture of information from multiple previous trials. Fig 4 illustrates the evolution of the latent state $p(z)$ in a mixture model over 4 trials. Importantly, such mixture distribution is computed by a fixed sampling step [15] which results in a computationally first-order Markovian model which has the same number of parameters and model complexity as the natural prior model described above. See *Mixture model* in *Methods* for details.

Note that we can a priori rule out approaches which track the average orientation or some other summary statistic [16, 17] since with random stimuli they would all be uninformative about the past.

**Fig 4: Mixture model.** Evolution of the mixture latent state over five trials.

# Results

We used all three models to simulate participants' responses using the stimuli and experimental structure provided by the authors (824 trials with fully randomised stimuli). We sought to replicate three statistical effects observed in the behavioural experiments: zero-mean distribution of the errors, DoG-like fit of the recency bias (Fig 1B), and significant recency bias over multiple past trials (Fig 1C). See *Statistical effects of interest* in *Methods* for details.

**Von Mises Filter (VMF)**

The best fitting VMF could not successfully replicate any of the three statistical effects. The distribution of errors was centred around zero but its concentration was significantly different from human data (Fig 5A-VMF, $p = 0.026$). Similarly, the maximum of the simulated recency bias was significantly removed from the human data (ca 0.35 rad or 20 deg for humans; ca 0.79 rad or 45 deg for the VMF; Fig 5B-VMF). Furthermore, it can be shown that the VMF cannot even theoretically have a maximum of the bias at less than $\pi/4$ radians (or 45 deg), which means it is incapable of replicating the DoG-like curve of the human recency bias (see *Von Mises filter properties* in *Supporting Information*). The VMF also could not replicate recency biases for stimuli presented 2 or 3 trials ago (Fig 5C-VMF) In sum, the VMF can simulate a recency bias but it is qualitatively different from human bias and only extends one trial back.

**Natural prior model (NPM)**

The NPM could only partially replicate the behavioural effects. The error distribution was centred around zero but significantly different from participants' data (Fig 5A-NPM, $p < 0.001$). However, because NPM's prior and posterior distributions are not Von Mises it was able to capture the DoG shaped curve of the recency bias (Fig 5B-NPM). The NPM was still not able to capture either the amplitude of the recency bias or extend it back more than one previous

**Fig 5: Results.** Comparison of model simulation results (black) with human data from Experiment 1 (red, [3]). (A) Error histograms: black – model simulation, red – average human participant. Solid lines depict Von Mises fits to error distributions. (B) Recency bias: black circles show errors of the simulated responses. Solid black line shows a DoG curve fit to the simulated errors, red line shows the human recency bias (average DoG fit to human errors). Dotted vertical lines show the location of the maxima of the recency biases (black – model; red – human participants). (C) Average recency bias amplitude computed for stimuli presented one, two and three trials back from the present. Grey bars – model; red bars – human participants. Error bars represent ±1 standard deviation of the bootstrapped distribution.

trial (Fig 5C-NPM). This was to be expected since the NPM, like the VMF, also predicts the next state based only on the previous one (first order Markovian). In sum, the NPM was able to replicate the DoG shaped recency bias curve but only for stimuli one trial back. Furthermore, the error distributions simulated by the NPM were significantly different from participants' average with variance of the response reduced by approximately twofold.

### Mixture model

The mixture model was able to successfully simulate all three statistical effects of interest: the distribution of errors was not significantly different from the participants' data (Fig 5A-MM, $p = 0.23$); the recency bias fit the DoG-shaped curve (Fig 5B-MM), and a significant recency bias was evident over multiple past states (Fig 5C-MM). Importantly, the best-fitting $\beta$ parameter value for the mixture model was $\beta = 0.75$, which effectively sets the time window for the mixture distribution at 3-4 past states (see Fig 8A, column 2, $\beta = 0.7$). This corresponds to robust and well-replicated estimates of visual short term memory capacity [18, 19].

## Discussion

In this paper we investigated the internal model of the environment which leads people to show a recency bias.

First, we showed that participants cannot be using a simple Bayesian filter that predicts the orientation on the current trial based only on the previous one. Furthermore, we showed that a first-order identity model is theoretically incapable of producing the recency bias observed in the orientation estimation task. This suggests that previous proposals that a simple first-order Bayesian model (such as Kalman or Von Mises filters) could explain the temporal continuity over trials and hence the recency bias [5, 11, 12] are misplaced. Second, we showed that a more complex model, where participants use the natural statistics of the environment in addition to the previous stimulus, is similarly incapable of simulating the recency bias. Although such an approach is significantly better at replicating the DoG like shape of the recency bias curve it still lacks a mechanism to extend the bias beyond the most recent state. Finally, we showed that a model where the prediction about the next stimulus incorporates information from multiple past orientations can successfully simulate all aspects of the recency bias. Specifically, the participant's model of the environment is assumed to be a mixture of multiple past states so that more recent states contribute more than older ones.

The success of the mixture model shows that the task utilises visual short-term memory (STM) since participants' inference is based on multiple past trials, each several seconds apart. Notably, the best fitting mixture model had an effective time window of 3-4 past states (Fig 5B,C-MM, $\beta = 0.75$) corresponding to robust estimates of visual STM core capacity [18, 19].

The classical Bayesian interpretation of our results suggests that the recency bias is a result of model mismatch: people infer an incorrect model for data resulting in suboptimal inference. This view posits that people are either incapable of recognising randomness or inevitably assume a model for the data since it is an efficient strategy for the natural environment, where random data is rare [20]. Specifically, if a recency-weighted prediction works well in the natural environment, where temporal continuity prevails, people would also wrongly apply that model to random data. However, a more parsimonious explanation exists. Perhaps, rather than inferring the wrong model (out of many models that might be inferred), the recency bias may simply be a consequence of the way STM represents a mixture of past states – people may not infer a model at all.

This can be made explicit in the framework of Bayesian filtering: the prediction for the next state is calculated by applying a state transition function $a(\cdot)$ to $m$ past states:

$$z_t = a(z_{t-1}, \ldots, z_{t-m}) + q,$$

where $q$ is state noise. According to the model mismatch explanation the state transition function $a(\cdot)$ is the recency-weighed mixture function (Eq 7). Importantly, this assumes that all data from past $m$ states is potentially available for the state transition function $a(\cdot)$ to generate a prediction. That is, there are no constraints on the capacity of STM. Participants suboptimal behaviour is hence caused by applying the mixture model to data representing past $m$ states. However, exactly the same prediction would be generated if the state transition function $a(\cdot)$ would not perform any transform at all – is identity – but the data from the past $m$ states is itself a recency weighed mixture.

Consider what happens when the model of the environment is unknown and needs to be inferred in real time: for random data, such model inference is always bound to end in failure as no model can explain, compress, or more efficiently represent random input. The most efficient representation of a random latent variable in human STM/WM is the data itself and not data plus model. In other words, people might not be applying the wrong model to the data, rather they may be failing to apply any model at all. The recency-weighted bias over multiple past states instead reflects the contents of visual STM. This is in agreement with previous proposals that human visual STM works by partially 'overwriting' previous representations with newer ones [21] and a general observation that information in STM decays with time [22]. Note that abandoning Bayesian inference altogether by simply ignoring the previous states would actually result in optimal performance in the task with random data. However, this strategy would immediately run into trouble should a pattern begin emerge in data which is initially random.

Therefore we propose that instead of having the data and just applying a 'wrong' model to

it – a classic case of Bayesian model mismatch - the recency bias emerges because participants are continuously and unsuccessfully attempting to infer a model based on previous states. In formal terms, the state transition model contains no information (it is identity) and hence the predictive prior distribution simply reflects the contents of vSTM.

In sum, our results indicate that the recency bias that appears when participants are confronted with random data must be driven by a mixture of past states. We suggest that the most parsimonious explanation of the data is that participants fail to infer a model for the data and fall back on treating the contents of visual STM as the best prediction for the future.

# Methods

## Von Mises filter

Here we use the circular approximation of the Kalman filter called the Von Mises filter (VMF) where the latent state and measurement noise are distributed according to Von Mises and not Gaussian distributions,

$$z_t = a(z_{t-1}) + q_t \qquad\qquad q_t \sim VM(0, \kappa_{Q_t}) \qquad\qquad (1)$$

$$y_t = h(z_t) + r_t \qquad\qquad r_t \sim VM(0, \kappa_{L_t}) \qquad\qquad (2)$$

where $\kappa_Q$ and $\kappa_L$ are latent state and measurement noise concentration terms respectively. An example of a simple VMF is depicted on Fig 2B, where both state transition and measurement models are identity functions and state noise is zero, resulting in a model where the predicted state $z_t$ is equal to the previously estimated posterior distribution $p(z_{t_1}|y_{t-1})$. The posterior distribution, being a product of two Von Mises distributions and representing participant's estimate, therefore also approximates Von Mises (see *Product of two von Mises distributions* in *Supporting Information* for details):

$$p(z_t|y_t) \propto VM(\mu_{E_t}, \kappa_{E_t}). \qquad\qquad (3)$$

This allows us to define recency bias at any trial $t$ as the distance which posterior mean $\mu_{E_t}$ has moved away from the presented stimulus $y_t$ towards some previous stimulus value $y_{t-n}$. Such estimation error represents the systematic shift in participants' responses since the internal estimate of the perceived orientation (Eq 3) is not centred around the presented stimulus $y_t$ (Fig 2). The value of the estimation error, as a distance between the posterior mean and stimulus

value, can be easily derived from the properties of Von Mises product:

$$y_t - \mu_{E_t} = \arctan \frac{\kappa_{Q_t} \sin y_t}{\kappa_{Q_t} \cos y_t + \kappa_{L_t}} \tag{4}$$

Importantly, this estimation error function (Eq 4) allows us to describe the possible space of recency biases by mapping the systematic shift of the estimation error towards previously observed orientations (Fig 6).

**Fig 6: Recency bias with Von Mises distributions.** (A) Example of Von Mises recency bias with fixed prior and likelihood parameters ($\kappa_L = 1.5$, $\kappa_Q = 1$, Eq 4). Recency bias is greatest when the distance between the prior mean and stimulus (x-axis) is ca 1.15 radians (black dotted line). (B) The shape of the recency bias depends on the ratio of likelihood to prior concentration $\kappa_{L_t}/\kappa_{Q_t}$ (differently coloured lines). See *Von Mises filter properties* in *Supporting Information* for details.

Such mapping of all possible shapes of the recency bias (Fig 6B) reveals that when Von Mises distributions are used for Bayesian inference the recency bias always peaks more than halfway through the x-axis (Fig 6, for a proof, see *Von Mises filter properties* in *Supporting Information*). This property means that the VMF cannot even theoretically yield a DoG-like recency bias shape as observed with human participants (Fig 1B).

**Model parameters**

To model the perceptual noise around the stimulus value (Eq 2) we used a fixed concentration parameter for the likelihood function ($\kappa_L$), which was chosen so as to produce the just noticeable difference (JND) values matching human data from Fischer and Whitney [3] (average JND was 5.39°, hence $\sigma = 3.8113°$ and $\kappa_L = 0.0688$). The concentration parameter for the state noise $\kappa_Q$

was a free parameter optimised to minimise the distance between the simulated data and the average observed subjects' response (see *Model fitting and parameter optimisation* in *Supporting Information*).

## Natural prior model

We modified the VMF so that instead of predicting the next state based on the current one (identity model) we assume that everything else being equal, cardinal orientations are more likely than oblique ones and reflect this in our prediction. We can do this by using the natural prior distribution function as the state transition model which changes the predictive prior distribution $p(z_t|z_{t-1})$ on trial $t$ from unimodal Von Mises to bimodal non-parametric distribution. For this purpose we model the average observers' prior as reported by [9] as a mixture of two Von Mises distributions, which has two components peaking at cardinal orientations (solid blue line on Fig 3C):

$$a(z) \sim \beta_1 VM(z, 0, \kappa_1) + \beta_2 VM(z, \pi, \kappa_2) = \frac{\exp(\kappa_1 \cos(z))}{2\pi I_0(\kappa_1)} + \frac{\exp(\kappa_2 \cos(z - \pi))}{2\pi I_0(\kappa_2)} \qquad (5)$$

We can now specify the equations for the Bayesian filter (Eq 1,2) with the natural prior with a state transition model $a(z_{t-1})$ is a bimodal mixture peaking at cardinal orientations (Eq 5, Fig 3C), the measurement model is identity, and the noise for both is additive Von Mises.

However, if the prior would always always predict cardinals over obliques, we would only observe recency bias for the trials which were preceded by orientations close to cardinal angles. Since the size of the recency bias in the behavioural experiment was independent of stimulus orientation [3] we can rule out a fixed natural prior (Eq 5) in advance. Instead, we assume here that the prior is a mixture of the natural prior and the previous posterior.

$$a(z_{t-1}) \sim \overbrace{\beta_1 p(z_{t-1}|y_{t-1})}^{previous\ posterior} + \overbrace{\beta_2 VM(z, 0, \kappa_1) + \beta_3 VM(z, \pi, \kappa_2)}^{natural\ prior} \qquad (6)$$

This leads to a prediction which is still biased towards the previous trial but mixed with the natural prior (Fig 7). In general terms, we assume here that participants have both a bias towards previous orientations and natural statistics of the environment (Fig 3). Importantly, such multi-modal prior means that participants estimates (posterior distribution) are also not Von Mises which allows for recency bias curves qualitatively different from Von Mises ones.

**Fig 7: Prior distribution as a mixture between the previous posterior** $p(z_{t-1}|y_{t-1})$ **and the natural prior distribution (Eq 5).** Depicted are two mixtures of the same components. (A) Equal mixture (solid blue line) of 50% previous posterior (dotted red line) and 50% natural prior (dotted green line). (B) Mixture (solid blue line) of 10% previous posterior (dotted red line) and 90% natural prior (dotted green line).

## Model parameters

For the natural prior model (NPM) we used the same perceptual noise parameter ($\kappa_L$) as in the VMF described above. Here we used an additional free parameter – the proportion of the previous posterior ($\beta_1$) in the prior distribution (Eq 6). Importantly, when $\beta_1 > 0.5$ (Fig 7A) the previous posterior would dominate the resulting prior and hence the model would start to approximate the VMF. Similarly, as $\beta_1$ approaches zero (Fig 7B) the natural prior component will dominate the prior distribution. As in our previous simulations we chose the free parameter values ($\kappa_Q$, $\beta_1$) to minimise the distance between the simulation and behavioural results observed by [3] (see *Model fitting and parameter optimisation* in *Supporting Information* for details).

Since the predictive prior distribution resulting from the mixture components is non-parametric we used a discrete circular filter to approximate the distributions in this simulation. The discrete filter is based on a grid of weighted Dirac components equally distributed along the circle [13, 23] and was implemented with *libDirectional* toolbox for Matlab [24]. Because in the unidimensional circular state space of orientations the quality of approximation is only given by the number of components, we felt that 10,000 Dirac components can adequately approximate a distribution of a circular variable. For details on the implementation of the filter algorithms see *Discrete circular filter with Dirac components* in *Supporting Information*.

## Mixture model

In order to model a time-decaying recency bias over several past states we modify the basic VMF so that the state transition model ($a(\cdot)$, Eq 1) predicts the next state based on a recency-

weighted mixture of $m$ past states:

$$a(z_{t-1}, \ldots, z_{t-m}) \sim \theta_1 p(z_t|z_{t-1}) + \cdots + \theta_m p(z_t|z_{t-m}) = \sum_{m=1}^{M} \theta_m p(z_t|z_{t-m}). \qquad (7)$$

Here $\theta_m$ is a mixing coefficient for the $m$-th past state. We can control the individual contribution of a past state $z_m$ to the resulting mixture distribution by defining how the mixing coefficient $\theta$ decays over the past states:

$$\theta_m = \alpha\theta_0(1 - \beta)^m. \qquad (8)$$

Here $\beta$ is the rate of decrease of the mixing coefficient over the past $m$ states and $\alpha$ is a normalising constant. As a result we have an decaying time window into the past $m$ states defined by the rate parameter $\beta$ controlling the decrease of the mixing coefficient $\theta$ over past states. Fig 8A illustrates the relationship between the $\beta$ and $\theta$ parameters: the bigger the $\beta$ the faster the contribution of past states decreases and greater the proportion of most recent states to the mixture distribution (Eq 7). As $\beta$ approaches 1, the mixture begins to resemble $z_{t-1}$ and approximate the first-order VMF described above:

$$\lim_{\beta \to 1}, p(z_t|z_{t-1}, \ldots, z_{t-m}) \sim p(z_t|z_{t-1}).$$

Conversely, as $\beta$ approaches zero, all past states contribute equally to the mixture. Intuitively, $\beta$ could be interpreted as the bias towards more recent states. Fig 8B illustrates the evolution of the latent state distribution $p(z)$ when $\beta = 0.5$ and the mixing coefficient decays over the previous states.

Importantly, the mixture distribution is computed by a fixed sampling step (for details of the mixture sampling algorithm see [15] and *Mixture model* in *Supporting Information*). Hence the mixture model is computationally first-order Markovian and has the same number of parameters and model complexity as the NPM described above.

In sum, we have a circular Bayesian filter where the state transition model $a(\cdot)$ is a mixture function over past $m$ states (Eq 7). The proportion of the individual past states in the mixture – and therefore the effective extent of the window into the past – is controlled by the $\beta$ parameter. Like in previous models, the measurement model is identity, and both state and measurement noise ($\kappa_Q$ and $\kappa_L$) is additive Von Mises.

## Model parameters

We used the same perceptual noise parameter ($\kappa_L$) as in the VMF and NPM simulations described above. The free parameters in the mixture model (MM) were the mixing coefficient hyper-parameter $\beta$ (Eq 8) and state noise ($\kappa_Q$). As with previous simulations, the free parame-

**Fig 8: Mixture model.** (A) Values of the mixing coefficient $\theta$ over past states $(z_{t-1}, \ldots, z_{t-m})$ based on different $\beta$ values. $\theta$ represents the proportion of a past state $z_t$ in the mixture distribution (Eq 7). (B) Evolution of the latent state $p(z)$ over 4 trials.

ters were chosen to minimise the distance between the simulated data and the average observed subjects' response (see *Model fitting and parameter optimisation* in *Supporting Information*).

## Statistical effects of interest

In each trial, we simulated the participant's response $k_t$ by taking a random sample from the posterior distribution: $k_t \sim p(z_t|y_t)$. We then calculated three statistical effects as follows:

(1) Distribution of errors – we fit a Von Mises distribution to the simulated errors yielding mean ($\mu$) and concentration values ($\kappa_E$). We then calculated the similarity between our simulated error distribution and participants average distribution by assessing the probability of simulated $\mu$ and $\kappa_E$ given the distribution of participants bootstrapped $\overline{\mu}$ and $\overline{\kappa_E}$.

(2) DoG recency bias curve – we fit the simulated errors with a first derivative of a Gaussian curve (DoG, see *Recency bias amplitude as measured by fitting the derivative of Gaussian* in *Supporting Information* for details), and as above, calculated the probability of the curve parameters arising from the distribution of participants' bootstrapped parameter distributions.

(3) DoG recency bias over past three trials – we calculated the amplitude of the DoG curve peak for stimuli presented one, two and three trials back. We sought to replicate a positive but decaying recency bias over three previous stimuli.

# 1 Supporting Information

## 1.1 Bayesian orientation estimation

We can model participants behaviour on the orientation estimation task (Fig 1) as probabilistic inference by combining their prior expectations about the orientation of the Gabors with immediate sensory evidence on a given trial. Hence, we can model the participants internal representation ($z_t$) given the orientation of the presented Gabor ($y_t$) on trial $t$ as Bayesian inference:

$$\overbrace{p(z_t|y_t)}^{posterior} \propto \overbrace{p(y_t|z_t)}^{likelihood} \cdot \overbrace{p(z_t)}^{prior}$$

The posterior distribution $p(z_t|y_t)$ represents a participant's estimate of the orientation on trial $t$ and their response can be thought of as a sample from the posterior distribution. Since orientation is a circular variable we need to use a probability distribution wrapped on a circle to represent variables of interest (here we use a Von Mises distribution, Fig 2A). We model the sensory evidence, or the likelihood distribution, as Von Mises noise around the value of the stimulus $y_t$ on trial:

$$p(y_t|z_t) \sim VM(y_t, \kappa_L).$$

We fix the value of the likelihood noise parameter $\kappa_L$ for every trial and derive it from the participants' average just noticeable difference (JND) as derived with Experiment 3 in [3] (see *Measurement noise concentration parameter* in *Supporting Information* for details).

### 1.1.1 Bayesian filtering

We assume that at every time-step $t$ observation $y_t$ corresponds to a latent variable $z_t$ (internal representation of orientation), which over time forms a Markov chain, giving rise to the latent state space model. Hence, the state of the latent variable $z_t$ is inferred at every time step $t$ using the Bayes theorem based on the previous state $z_{t-1}$ and current observation (sensory information) $y_t$:

$$p(z_t|y_t) \propto p(y_t|z_t) \cdot p(z_t|z_{t-1})$$

Assuming that noise in the internal representation and observation is additive, then the evolution of the latent variable $z$ is predicted by the state transition model and the likelihood of the observations $y$ are given by the measurement model:

$$z_t = a(z_{t-1}) + q_t \tag{9}$$

$$y_t = h(z_t) + r_t \tag{10}$$

Assuming that the state transition and measurement models ($a$ and $h$) are arbitrary but known functions and $q_t$ and $r_t$ are additive noise, we can carry out Bayesian inference at every time step by first predicting the next state of the latent variable given the past state (Eq 9) and then updating this prediction when observable data is measured (Eq 10) to give us a Bayesian posterior distribution of the latent variable (see [25, 26] for a detailed description of state space models).

This two-step process is called *Bayesian filtering.* If the evolution of the state-space is linear and the noise is Gaussian then the optimal probabilistic state space model is the Kalman filter [10]. Kalman filters have been extensively used for problems where the future state of the environment can be predicted from just the previous few states with sufficient accuracy, such as in object tracking or phoneme recognition. An in-depth mathematical explanation of the Kalman Filter, and how it is derived from the Bayesian estimation problem can be found in any good book covering digital signal processing, for example in Sarkka [25]. However, Gaussian distributions are not appropriate when the latent state space is wrapped on a circle. A circular analogue of the Kalman filter is the Von Mises filter.

## 1.2   Measurement noise concentration parameter

Participants' psychometric functions were estimated in Fischer and Whitney [3] as just noticeable differences (JND) by using a two-interval forced-choice task (Experiment 3 in [3]). We converted the JND values ($\sigma_P$) to the measurement concentration parameter $\kappa_L$ as JND relates to the standard deviation ($\sigma$) of the normal distribution:

$$\sigma = \frac{\sigma_P}{\sqrt{2}} \tag{11}$$

and since the concentration of the Von Mises distribution can be approximated as $\kappa = 1/\sigma^2$ we get

$$\kappa = \frac{2}{\sigma_P^2} \tag{12}$$

The mean JND ($\sigma_P$) across subjects was $5.39°$ [3], so we used $\sigma = 3.8113°$ and $\kappa_L = 0.0688$.

## 1.3   Product of two von Mises distributions

Given two von Mises probability density distributions $p(x; \mu_1, \kappa_1)$ and $p(x; \mu_2, \kappa_2)$ the resulting product is an unnormalised von Mises distribution [27]:

$$p(x; \mu, \kappa) = \frac{\exp(\kappa \cos(x - \mu))}{4\pi^2 I_0(\kappa_1) I_0(\kappa_2)} \tag{13}$$

where the mean $\mu$ and concentration $\kappa$ are respectively:

$$\mu = \mu_1 + \mathrm{atan2}(-\sin(\mu_1 - \mu_2), \frac{\kappa_1}{\kappa_2} + \cos(\mu_1 - \mu_2)) \tag{14}$$

$$\kappa = (\kappa_1^2 + \kappa_2^2 + 2\kappa_1\kappa_2 \cos(\mu_1 - \mu_2))^{-1} \tag{15}$$

## 1.4   Von Mises filter properties

In the Von Mises filter (VMF) the recency bias at any trial $t$ is given as the distance which posterior mean $\mu_{E_t}$ has moved away from the presented stimulus $y_t$ towards some previous stimulus value $y_{t-n}$. Since the posterior in VMF is a product of two individual VM distributions (likelihood and prior) it follows that the estimation error (Eq 4) is only dependent on two parameters: (1) distance between the prior mean and stimulus ($\mu_{Q_t} - y_t$, x-axis on Fig 6); and (2) ratio of likelihood to prior concentration ($\kappa_{L_t}/\kappa_{Q_t}$, differently coloured lines on Fig 6B). Such mapping of all possible shapes of the recency bias reveals several interesting findings.

First, in order to observe a recency bias the concentration of the likelihood has to be greater than the concentration of the prior: $\kappa_{L_t} > \kappa_{Q_t}$. Conversely, when $\kappa_{L_t} < \kappa_{Q_t}$ the posterior mean will be closer to the prior mean than to the stimulus and the bias curves on Fig 6 will be inverted. In other words, likelihood concentration has to be on the average greater than prior for a participant's response error distribution to be centred around zero. In general terms this means that perceptual noise in the task has to be smaller than uncertainty about the next stimulus.

Second, one would intuitively expect the estimation error ($y_t - \mu_{E_t}$, y-axis), and hence the recency bias, to be greatest when the distance between the prior and stimulus ($\mu_{Q_t} - y_t$) is greatest (x-axis maxima and minima on Fig 6B). However, as shown in Fig 6B for various values of $\kappa_{L_t}/\kappa_{Q_t}$, this is not the case because of the circular nature of Von Mises. As the distance between the prior mean and stimulus approaches maximum (antipodean angle) the influence of the prior decreases so that the mean of the posterior tends back towards the stimulus. At maximum distance ($\pm\pi/2$ on the x-axis on Fig 6B) the influence of the prior is zero and the posterior mean is equal to the stimulus.

Finally, and most importantly, no value of $\kappa_{L_t}/\kappa_{Q_t}$ can even theoretically yield a DoG-like recency bias shape as observed in [3] (Fig 1B): the Von Mises recency bias cannot have maxima or minima between $-\pi/4$ and $\pi/4$ (see *Minima and maxima of the recency bias in Von Mises filter* below for details). In other words, when Von Mises distributions are used for Bayesian inference the recency bias always peaks more than halfway through the x-axis. Contrastingly, DoG curves fitted to participant data in [3] peak close to zero and between $\pm\pi/4$ (Fig 1B). In sum, a DoG-shaped recency bias is not even theoretically possible if participants use Bayesian

inference and Von Mises distributions for orientation estimation.

## 1.5 Minima and maxima of the recency bias in Von Mises filter

We find the extrema of Eq 4 by setting its first derivative to zero:

$$\frac{\kappa_{Q_t}^2 + \kappa_{L_t}\cos(x)\kappa_{Q_t}}{\kappa_{L_t}^2 + 2\cos(x)\kappa_{L_t}\kappa_{Q_t} + \kappa_{Q_t}^2} = 0 \tag{16}$$

which gives us maximum and minimum at

$$\pi \pm \arccos(\kappa_{Q_t}/\kappa_{L_t}). \tag{17}$$

In order to observe a positive recency bias the likelihood concentration has to be greater than prior's ($\kappa_{Q_t}/\kappa_{L_t} \leq 1$) and therefore $\arccos(\kappa_{Q_t}/\kappa_{L_t})$ can only take values between $[0, \pi/2]$.

Finally, we need to convert this result to the stimulus space used in the behavioural experiments – the Von Mises distribution is wrapped on a full circle $[0, 2\pi]$, whilst in the orientation estimation task stimulus values were wrapped on the top half of the circle $[-\pi/2, \pi/2]$ [3]. Eq 17 wrapped between $\pm\pi/2$ gives $\pm\pi/4$ as the new limits to the extrema.

## 1.6 Recency bias amplitude as measured by fitting the derivative of Gaussian

The errors as a function of between-trial orientation distance (Fig 1B) were fitted with a first derivative of a Gaussian curve (DoG) as given by Fischer and Whitney [3]:

$$y = x\alpha wce^{-wx^2} \tag{18}$$

where $x$ is the relative orientation of the previous trial, $\alpha$ is the amplitude of the curve peaks, $w$ scales the curve width, and $c$ is the constant $\sqrt{2/e^{-0.5}}$ which rescales the curve so that the $\alpha$ parameter numerically matches the height of the positive peak of the curve for ease of interpretation: the amplitude of serial dependence ($\alpha$) is the number of radians that perceived orientation was pulled in the direction of the previous stimulus.

## 1.7 Model fitting and parameter optimisation

To evaluate how well the simulated recency bias fit with the observed behavioural data we measured the distance between the simulated recency bias DoG curve to the one observed in the behavioural experiments [3]. The distance between the simulated and observed curves was measured as the sum of squared errors (SSE) across orientations bins. Fig 9 displays the average

DoG curve recency bias fit across the participants. To find the value of free parameters (latent state noise and mixing coefficient) that yielded recency biases most similar to behavioural results we performed a grid search across parameter space. We used state noise $\kappa_Q$ values from 48 to 480 (step size $log(x)$) and $\beta$ values from 0.2 to 0.9 (step size 0.05). We used the parameter values which yielded the lowest SSE to the average participants DoG curve (Fig 9).

**Fig 9: Parameter search grid results.** Sum of squared errors (SSE) between simulated recency bias curves and the observed human bias. SSE is displayed as a function of state noise concentration parameter ($\kappa_Q$, y-axis) and mixture coefficient ($\beta$, x-axis). (A) Natural prior mixture. (B) Von Mises mixture.

## 1.8 Natural prior

Here we used the average participants' prior as reported in [9] as the natural prior distribution. This was modelled as a mixture of two von Mises distributions with means fixed at 0 and $\pi$ radians respectively.

$$\beta_1 VM(z, 0, \kappa_1) + \beta_2 VM(z, \pi, \kappa_2) = \frac{\exp(\kappa_1 \cos(z))}{2\pi I_0(\kappa_1)} + \frac{\exp(\kappa_2 \cos(z - \pi))}{2\pi I_0(\kappa_2)} \tag{19}$$

We used Matlab's nonlinear and derivative-free model fitting function *fminsearch* with $10^8$ iterations and an ordinary least squares cost function to estimate the values of mixing coefficients ($\beta_1 = 0.0215$, $\beta_2 = 0.0178$) and von Mises concentrations ($\kappa_1 = 0.8365$ $\kappa_2 = 0.8728$). The resulting mixture and its fit with data from [9] is depicted on Fig 3C.

## 1.9 Discrete circular filter with Dirac components

A detailed derivation of the circular filter using Dirac mixtures can be found in [23, 13]. Briefly, a wrapped Dirac mixture with $L$ components and Dirac positions $\beta_1, \ldots, \beta_L \in [0, 2\pi]$ is defined

as:

$$f(x) = \sum_{j=1}^{L} \omega_j \delta(x - \beta_j), \tag{20}$$

where $\omega_j$ are weighting coefficients and $\sum_{j=1}^{L} \omega_j = 1$. A Von Mises distribution can be approximated by a wrapped Dirac mixture

$$f^d(x) = \delta(x - (\mu - \alpha))1/3 + \delta(x - \mu)1/3 + \delta(x - (\mu + \alpha))1/3$$

by calculating $\mu$ as the circular mean

$$\mu = \mathrm{atan2}(\sum_{j=1}^{L} \sin(\beta_j), \sum_{j=1}^{L} \cos(\beta_j))$$

i. e., the argument of the first circular moment, and by matching the first circular moment to obtain $\kappa$.

## 1.10 Mixture model

A detailed derivation of the mixture model and the sampling algorithm can be found in [15, 28]. What follows is a brief overview of the approach.

The latent state $z$ can be modelled as the mixture of it's past states by using a mixture state transition function (see [29, 28] for details). This method considers the effect of the each of the past $m$ states separately. Specifically, the conditional probability distribution $p(z_t|z_{t-1}, \ldots, z_{t-m})$ is modelled by a mixture distribution of past $m$ states:

$$p(z_t|z_{t-1}, \ldots, z_{t-m}) = \theta_1 f(z_t|z_{t-1}) + \cdots + \theta_m f(z_t|z_{t-m}) = \sum_{m=1}^{M} \theta_m \sim f(z_t|z_{t-m}), \tag{21}$$

where $\theta$ is a mixing coefficient so that

$$0 < \theta_m \leq 1, \text{ and } \sum_{m=1}^{M} \theta_m = 1.$$

We assume that the mixing coefficient $\theta$, declines over $m$ time steps as given by some decay function $\phi$ and the rate of decay parameter $\beta$:

$$\theta_m = \phi(m, \beta)$$

Here we use an exponential decay function $\phi$, so that:

$$\theta_m = \phi(m, \beta) = \alpha\theta_0(1 - \beta)^m \tag{22}$$

where $\beta$ is the rate of decrease ($0 \leq \beta < 1$) and $\alpha$ normalising constant. Substituting $\theta_m$ into Eq 21 gives:

$$p(z_t|z_{t-1}, \ldots, z_{t-m}) = \sum_{m=1}^{M} \alpha\theta_0(1-\beta)^m \sim f(z_t|z_{t-m}) \tag{23}$$

In order to limit the computational cost of performing inference at every time step we represent the distribution of latent variable $z$ with a fixed number of samples $L$. As a result the proportion of samples assigned to a particular component of the mixture distribution (representing a past state) is determined by the mixing coefficient $\theta$:

$$p(z_t|z_{t-1}, \ldots, z_{t-m}) = \sum_{m=1}^{M} \theta_m \sim f(z_t|z_{t-m}) \simeq \sum_{m=1}^{M} \sum_{l=1}^{\theta L} \{f(z_t|z_{t-m})\}^l \tag{24}$$

where $L$ is the total number of samples, $\theta L$ is rounded to the nearest integer, and $\{f(z_t|z_{t-m})\}^l$ is a set of $l$ samples drawn from $p(z_t|z_{t-m})$.

The property of constant number of samples $l$ for every $m$-th component of the mixture at any time-step ($\{z_t|z_{t-m}\}^l$) is important since it greatly simplifies the approximation of the mixture distribution (Eq 23) algorithmically. If at every time-step $t$ we take a fixed proportion $\beta$ from the existing mixture distribution and reassign those samples to represent the most recent component, then after $m$ steps we end up with the same proportion of components as given by (Eq 23). It follows that a mixture distribution of past $m$ states with exponentially decaying proportions of past $m$ components can be approximated by sampling from just $f(z_t|z_{t-1})$ and the previous state of the mixture $\{\mathbf{z}_{t-1}\}$ at every time step $t$.

# References

[1] John R Anderson and Robert Milson. Human memory: An adaptive perspective. *Psychological Review*, 96(4):703, 1989.

[2] John R Anderson and Lael J Schooler. Reflections of the environment in memory. *Psychological science*, 2(6):396–408, 1991.

[3] Jason Fischer and David Whitney. Serial dependence in visual perception. *Nature Neuroscience*, 17(5):738–743, mar 2014. ISSN 1097-6256. doi: 10.1038/nn.3689. URL `http://www.nature.com/doifinder/10.1038/nn.3689`.

[4] Guido Marco Cicchini, Giovanni Anobile, and David C Burr. Compressive mapping of number to space reflects dynamic encoding mechanisms, not static logarithmic transform. *Proceedings of the National Academy of Sciences of the United States of America*, 111(21): 7867–72, 2014. ISSN 1091-6490. doi: 10.1073/pnas.1402785111.

[5] David Burr and Guido Marco Cicchini. Vision: Efficient adaptive coding. *Current Biology*, 24(22):R1096–R1098, 2014. ISSN 09609822. doi: 10.1016/j.cub.2014.10.002. URL `http://dx.doi.org/10.1016/j.cub.2014.10.002`.

[6] Matthias Fritsche, Pim Mostert, and Floris P de Lange. Opposite effects of recent history on perception and decision. *Current Biology*, 27(4):590–595, 2017.

[7] Alina Liberman, Jason Fischer, and David Whitney. Serial dependence in the perception of faces. *Current Biology*, 24(21):2569–2574, 2014. ISSN 09609822. doi: 10.1016/j.cub.2014.09.025. URL `http://dx.doi.org/10.1016/j.cub.2014.09.025`.

[8] Anastasia Kiyonaga, Jason M. Scimeca, Daniel P. Bliss, and David Whitney. Serial Dependence across Perception, Attention, and Memory. *Trends in Cognitive Sciences*, 21(7):493–497, 2017. ISSN 1879307X. doi: 10.1016/j.tics.2017.04.011. URL `http://dx.doi.org/10.1016/j.tics.2017.04.011`.

[9] A Girshick, M Landy, and E Simoncelli. Cardinal rules: visual orientation perception reflects knowledge of environmental statistics. *Nature neuroscience*, 14(7):926–932, jun 2011. ISSN 1546-1726. doi: 10.1038/nn.2831.

[10] R Kalman and R Bucy. New Results in Linear Filtering and Prediction Theory, 1961. ISSN 00219223.

[11] D. M. Wolpert and Z. Ghahramani. Computational principles of movement neuroscience. *Nature neuroscience*, 3 Suppl(november):1212–7, nov 2000. ISSN 1097-6256. doi: 10.1038/81497. URL `http://www.ncbi.nlm.nih.gov/pubmed/11127840`.

[12] R P Rao. An optimal estimation approach to visual perception and learning. *Vision research*, 39(11):1963–89, jun 1999. ISSN 0042-6989. doi: 10.1016/S0042-6989(98)00279-X. URL `http://www.ncbi.nlm.nih.gov/pubmed/10343783`.

[13] Gerhard Kurz, Igor Gilitschenski, and Uwe D. Hanebeck. Recursive Bayesian filtering in circular state spaces. *IEEE Aerospace and Electronic Systems Magazine*, 31(3):70–87, 2016. ISSN 08858985. doi: 10.1109/MAES.2016.150083.

[14] Ivan Marković and Ivan Petrović. Speaker Localization and Tracking in Mobile Robot Environment Using a Microphone Array. *Proceedings book of 40th International Symposium on Robotics*, (2):283–288, 2009. ISSN 09218890. doi: 10.1016/j.robot.2010.08.001.

[15] Kristjan Kalm. Recency-weighted Markovian inference. *arXiv*, nov 2017. URL `http://arxiv.org/abs/1711.03038`.

[16] Bjorn Hubert-Wallander and Geoffrey M Boynton. Not all summary statistics are made equal: Evidence from extracting summaries across time. *Journal of vision*, 15(4):5, 2015. ISSN 1534-7362. doi: 10.1167/15.4.5.

[17] Chad Dubé, Feng Zhou, Michael J. Kahana, and Robert Sekuler. Similarity-based distortion of visual short-term memory is due to perceptual averaging. *Vision Research*, 96: 8–16, 2014. ISSN 00426989. doi: 10.1016/j.visres.2013.12.016.

[18] N Cowan. The magical number 4 in short-term memory: a reconsideration of mental storage capacity. *The Behavioral and brain sciences*, 24(1):87–114; discussion 114–85, 2001. ISSN 0140-525X.

[19] Nelson Cowan. The magical mystery four: How is working memory capacity limited, and why? *Current directions in psychological science*, 19(1):51–57, 2010.

[20] Maya Bar-Hillel and Willem A. Wagenaar. The perception of randomness. *Advances in Applied Mathematics*, 12(4):428–454, 1991. ISSN 10902074. doi: 10.1016/0196-8858(91)90029-I.

[21] Loic Matthey, Paul M Bays, and Peter Dayan. A Probabilistic Palimpsest Model of Visual Short-term Memory. *PLOS Computational Biology*, 11(1):e1004003, jan 2015. ISSN 1553-7358. doi: 10.1371/journal.pcbi.1004003.

[22] T Brady, T Konkle, and G Alvarez. A review of visual memory capacity: Beyond individual items and toward structured representations. *Journal of vision*, 11(5):4, jan 2011. ISSN 1534-7362. doi: 10.1167/11.5.4. URL `http://www.ncbi.nlm.nih.gov/pubmed/21617025`.

[23] Gerhard Kurz, Igor Gilitschenski, and Uwe D. Hanebeck. Recursive Nonlinear Filtering for Angular Data Based on Circular Distributions. *American Control Conference (ACC)*, pages 5439–5445, 2013. ISSN 07431619. doi: 10.1109/ACC.2013.6580688. URL `http://ieeexplore.ieee.org/lpdocs/epic03/wrapper.htm?arnumber=6580688`.

[24] Gerhard Kurz, Igor Gilitschenski, Florian Pfaff, and Lukas Drude. libDirectional, 2015. URL `https://github.com/libDirectional`.

[25] Simo Sarkka. 04 Bayesian filtering equations and exact solutions. In *Bayesian Filtering and Smoothing*. Cambridge University Press, 2013.

[26] Christopher M. Bishop. 13 Sequential Data. In *Pattern Recognition and Machine Learning*, pages 605–652. Cambridge University Press, 2006.

[27] Richard F Murray and Yaniv Morgenstern. Cue combination on the circle and the sphere. *Journal of vision*, 10(11):15, jan 2010. ISSN 1534-7362. doi: 10.1167/10.11.15. URL `http://www.ncbi.nlm.nih.gov/pubmed/20884510`.

[28] A Raftery. A Model for High-order Markov Chains. *Journal of the Royal Statistical Society. Series B (Methodological)*, 47(3):528–539, 1985.

[29] A Berchtold and A Raftery. The Mixture Transition Distribution Model for High-Order Markov Chains and Non-Gaussian Time Series. *Statistical Science*, 17(3):328–356, 2002. ISSN 0883-4237. doi: 10.1214/ss/1042727943.