MEG sensor patterns reflect perceptual but not categorical similarity of animate

and inanimate objects

Abbreviated title: MEG patterns reflect perceptual similarity

Daria Proklova[1], Daniel Kaiser[2], Marius V. Peelen[3]

[1]The Brain and Mind Institute, The University of Western Ontario, London, ON N6A 5B7, Canada

[2]Department of Education and Psychology, Freie Universität Berlin, 14195 Berlin-Dahlem, Germany

[3]Donders Institute for Brain, Cognition and Behaviour, Radboud University, 6525 HR Nijmegen, The

Netherlands

Corresponding author:

Marius V. Peelen

Donders Institute for Brain, Cognition, and Behaviour

Radboud University

Montessorilaan 3

6525 HR Nijmegen

The Netherlands

Email: m.peelen@donders.ru.nl

Acknowledgements: The research was supported by the Autonomous Province of Trento, Call

"Grandi Progetti 2012", project "Characterizing and improving brain mechanisms of attention –

ATTEND". This project has received funding from the European Research Council (ERC) under the

European Union's Horizon 2020 research and innovation programme (grant agreement No

725970). D.K. is supported by a DFG grant (KA4683-2/1).

Abstract

Human high-level visual cortex shows a distinction between animate and inanimate objects, as

revealed by fMRI. Recent studies have shown that object animacy can similarly be decoded from

MEG sensor patterns. Which object properties drive this decoding? Here, we disentangled the

influence of perceptual and categorical object properties by presenting perceptually matched

objects (e.g., snake and rope) that were nonetheless easily recognizable as being animate or

inanimate. In a series of behavioral experiments, three aspects of perceptual dissimilarity of these

objects were quantified: overall dissimilarity, outline dissimilarity, and texture dissimilarity. Neural

dissimilarity of MEG sensor patterns was modeled using regression analysis, in which perceptual

dissimilarity (from the behavioral experiments) and categorical dissimilarity served as predictors of

neural dissimilarity. We found that perceptual dissimilarity was strongly reflected in MEG sensor

patterns from 80ms after stimulus onset, with separable contributions of outline and texture

dissimilarity. Surprisingly, when controlling for perceptual dissimilarity, MEG patterns did not carry

information about object category (animate vs inanimate) at any time point. Nearly identical

results were found in a second MEG experiment that required basic-level object recognition.

These results suggest that MEG sensor patterns do not capture object animacy independently of

perceptual differences between animate and inanimate objects. This is in contrast to results

observed in fMRI using the same stimuli, task, and analysis approach: fMRI showed a highly

reliable categorical distinction in visual cortex even when controlling for perceptual dissimilarity.

Results thus point to a discrepancy in the information contained in multivariate fMRI and MEG

patterns.

Introduction

Since their successful application in fMRI research, multivariate analysis methods have recently been applied to MEG and EEG data to gain insight into the temporal dynamics of visual and cognitive processing. A replicable finding in this rapidly growing literature is the finding that MEG sensor patterns carry information about object category (e.g., animacy), peaking around 150-250 ms after stimulus onset (for review, see Contini et al., 2017). Similar category distinctions have been observed in high-level visual cortex using fMRI (Grill-Spector and Weiner, 2014). What are the object properties that drive this decoding, and are these the same in fMRI and MEG?

Animate objects differ from inanimate objects in terms of their characteristic shapes and other category-associated visual features. These feature differences are reflected in behavioral measures of perceptual similarity, such that within- and between-category perceptual similarity can be used to accurately predict the time it takes observers to categorize an object as animate or inanimate (Mohan and Arun, 2012). These perceptual differences likely contribute to categorical distinctions in MEG, considering that object shape and perceptual similarity are strongly reflected in MEG and EEG patterns (Isik et al., 2014; Coggan et al., 2016; Wardle et al., 2016). Furthermore, MEG animacy decoding strength is closely related, at the exemplar level, to categorization reaction time (Ritchie et al., 2015), likely reflecting the exemplar's perceptual typicality of the category it belongs to (Mohan and Arun, 2012). Together, these studies raise the possibility that category information in MEG patterns primarily reflects perceptual differences between animate and inanimate objects.

However, animate and inanimate objects also differ in other aspects. For example, animals are agents capable of moving by themselves, a property that we rapidly associate with animals even when these are viewed as static pictures. Additionally, we perceive (most) animals as entities with goals, intentions, beliefs, and desires. Animate and inanimate objects also invite different actions on the part of the observer. For example, unlike animals, inanimate objects are often things with specific functions and manipulation patterns, such as tools, musical instruments, or clothing. Animate and inanimate objects are thus associated with different actions, functions, and other higher-order properties. fMRI studies have provided evidence that category selectivity in visual cortex, for example for tools, partly reflects these higher-order associations (for reviews, see Amedi et al., 2017; Peelen and Downing, 2017). This raises the possibility that category information in MEG patterns similarly reflects non-perceptual differences between animate and inanimate objects.

One way to dissociate between these accounts is to compare neural responses to animate
and inanimate objects that are perceptually matched in terms of their 2D shape profile (e.g., snake
and rope). Recent fMRI studies adopting this approach revealed that category-specific responses
in parts of ventral temporal cortex (VTC) are not fully reducible to perceptual differences
(Macdonald and Culham, 2015; Bracci and Op de Beeck, 2016; Bryan et al., 2016; Proklova et al.,
2016). In a previous fMRI study (Proklova et al., 2016), we found that activity in large parts of the
visual cortex reflected the perceptual similarity of the objects, independent of object category. But
importantly, the animacy distinction in parts of VTC was preserved for objects that were closely
matched in terms of perceptual similarity. If MEG activity in the 150-250 ms time window
corresponds to category-selective fMRI activity in these VTC regions, animacy information should
be preserved in MEG as well.

In contrast to this prediction, we report here that the matching for perceptual similarity of
objects abolished animacy information in MEG: while representational similarity in MEG sensor
patterns strongly reflected the perceptual similarity between the objects, as well as similarity in
their outline and texture properties, it did not reflect the categorical distinction between animate
and inanimate objects at any time point.

Materials and Methods

Participants

Twenty-nine participants with normal or corrected-to-normal vision took part in one of two
experiments, including 14 volunteers who participated in Experiment 1 (5 females, mean age =
25.6 years, SD = 4 years) and 15 volunteers who participated in Experiment 2 (8 females, mean age
= 25.2 years, SD = 3.1 years). All participants provided informed consent and received monetary
compensation for their participation. The experimental protocols were approved by the Ethical
Committee of the University of Trento, Italy.

Stimuli

The stimulus set in both experiments was identical to the one used in an earlier fMRI study
(Proklova et al., 2016) and consisted of 16 objects (8 animate and 8 inanimate) divided into 4
shape sets (Figure 1A). Each shape set consisted of 2 animals and 2 inanimate objects that were
matched for overall shape features (e.g. snake-rope). In addition, four exemplars of each stimulus

were used, resulting in a total of 64 stimuli (see Figure 1C for the full stimulus set). In all analyses,

we averaged across the 4 exemplars of each stimulus conditions (i.e., there were 16 conditions in

total). In Experiment 1, one additional visual stimulus (a hammer, see Figure 1B) was used to serve

as an oddball target. All stimuli were matched for luminance and contrast using the SHINE toolbox

(Willenbockel et al., 2010).

Experiment 1 and 2: Procedure

Participants viewed the visual stimuli while sitting in the dimly lit magnetically shielded room. The

stimuli were projected on a translucent screen located 150 cm from the participant. The stimuli

were presented centrally on the uniformly gray background and approximately spanned a visual

angle of 8 degrees. Stimulus presentation was controlled using the Psychophysics Toolbox

(Brainard, 1997). Participants completed 12 experimental runs, with each of the 64 stimuli

appearing exactly twice in each run, in random order. The stimuli were presented for 500 ms,

followed by a variable inter-stimulus interval ranging from 1.5 s to 2 s.

In Experiment 1, participants were instructed to maintain fixation and to press the

response button and blink each time they saw a picture of a hammer. This target appeared on 20%

of trials (32 target trials, randomly distributed over the run), resulting in 160 trials in total per run.

Target trials were not analyzed. In Experiment 2, participants were asked to perform a one-back

task, pressing the response button whenever an image of the same object type appeared on two

consecutive trials (e.g. two different snakes). Twelve repetition trials were inserted at random

points within each run, resulting in 140 trials per run. Repetition trials were not analyzed.

MEG acquisition and preprocessing

Electrophysiological recordings were obtained using an Elekta Neuromag 306 MEG system (Elekta

Neuromag systems, Helsinki, Finland) equipped with 204 gradiometers and 102 magnetometers.

Signals were sampled continuously at 1000 Hz rate and band-pass filtered online between 0.1 and

330 Hz. The data were then preprocessed offline using MATLAB and the Fieldrip Toolbox

(Oostenveld et al., 2011). Data from all runs were concatenated and trials were epoched from 100

ms before to 500 ms after stimulus onset (for one follow-up analysis, trials were epoched from

100 ms before to 800 ms after stimulus onset). Trials containing eye-blinks and other movement-

related artifacts were discarded from further analysis based on visual inspection. The signal was

baseline-corrected with respect to the pre-stimulus window and downsampled to 100 Hz to

reduce the processing time and increase the signal-to-noise ratio (Grootswagers et al., 2017).

Figure 1. Stimuli and MEG paradigms. (A) Example stimuli of the 16 conditions, grouped in shape clusters. (B) In

Experiment 1, individual stimuli were presented centrally for 500 ms, followed by a variable ISI of 1.5 – 2 s. Participants

were asked to press the response button and blink whenever they saw a hammer. In Experiment 2, the procedure was

largely identical to Experiment 1, except that participants performed a one-back task, pressing the button when two

images of the same object type (e.g., two different planes) appeared on two consecutive trials. (C) Full stimulus set

used in the experiments.

Pairwise decoding analysis

For each time point, we trained linear discriminant analysis (LDA) classifiers on response patterns

across sensors to discriminate between all possible pairs of stimuli. For the classification analysis,

trials were randomly assigned to four independent chunks, with an equal number of trials for each

condition per chunk. Classifiers were trained on data from three chunks and tested on the fourth

chunk; this analysis was repeated four times, with each chunk serving as the test set once. To

reduce trial-to-trial noise and increase the reliability of data supplied to the classifier, new,

"synthetic" trials were created by averaging individual trials (Grootswagers et al., 2017): for every

condition and chunk we randomly picked 25% of the original trials and averaged the data across

them. This procedure was repeated 500 times (with the constraint that no trial was used more

than one time more often than any other trial), producing 500 new "synthetic" trials (with each

one being an average of up to 12 trials, depending on trial numbers left after preprocessing) for

each condition and chunk that were then supplied to the classifier. The resulting decoding

accuracy time course was smoothed with an averaging filter spanning 3 time points (i.e., 30 ms).

The pair-wise decoding analysis yielded a time course of classification accuracies for each pair of
stimuli, reflecting the neural dissimilarity of each pair at every time point.

Representational similarity analysis

In order to investigate the independent contributions of perceptual properties and object category
to the MEG signal, we used representational similarity analysis (RSA; Kriegeskorte et al., 2008).
Following the analysis approach used in a previous fMRI study (Proklova et al., 2016), the neural
dissimilarity (measured with MEG) at each time point was modeled as a linear combination of
category and perceptual dissimilarity. The procedures used to obtain the neural dissimilarity
matrices as well as category and perceptual dissimilarity matrices are described below.

Category dissimilarity

A category dissimilarity matrix was constructed by assigning zeroes (minimum dissimilarity) to
elements of the matrix that corresponded to pairs of objects belonging to the same category and
ones (maximum dissimilarity) for pairs of objects from different categories.

Perceptual dissimilarity

To be able to measure the contribution of perceptual dissimilarity to the MEG signal, we created
predictor matrices that reflected the perceived similarity of the objects for a set of independent
observers. In separate behavioral visual search experiments (see Proklova et al., 2016 for a
detailed reporting of these experiments), three perceptual dissimilarity matrices were obtained. In
one experiment, overall perceptual dissimilarity was quantified using the stimuli used in the MEG
experiment. In two other experiments, we sought to dissociate the influence of outline and
texture properties of the stimuli by using outline silhouettes and texture patches as stimuli (Figure
2). In all three experiments, participants detected an oddball target among an array of identical
distractors (Figure 2) by indicating whether the target was on the right or on the left of the
midline. In this task, the identity or category of the target is irrelevant; the task of the participants
is simply to indicate where the different-looking stimulus is located (Mohan and Arun, 2012). This
was done for all possible target-distractor pairs among the stimuli. For each pair of stimuli, the
corresponding entry in the perceptual dissimilarity matrix is given as the inverse reaction time
(1/RT) in the visual search task, using one of the stimuli as a target and another as a distractor
(Figure 2). For perceptually similar target and distractor pairs, the reaction times will be slower

(such as when searching for a snake among ropes), while for perceptually dissimilar target and
distractor pairs the reaction times will be faster (such as when looking for a snake among planes).
201

Figure 2. Perceptual dissimilarity measures. *Three behavioral visual search experiments were used to measure*
different aspects of pairwise perceptual dissimilarity of the stimuli. In each experiment, participants had to locate the
target among an array of identical distractors. The inverse reaction time in this task is taken as a measure of
perceptual dissimilarity between the target and distractor. Dissimilarity matrices are shown for the three behavioral
experiments, quantifying overall perceptual dissimilarity (left panel), outline dissimilarity (center), and texture
dissimilarity (right panel).

Relationship between the predictor matrices

Prior to the RSA, we assessed dependencies among the different predictor matrices. Correlating
the perceptual dissimilarity matrices with the category dissimilarity matrix revealed that category
dissimilarity was not related to the other three predictors (r=-0.08, r=-0.07, and r=-0.06 for overall,
outline, and texture dissimilarity, respectively), indicating that the matching of visual properties
between animate and inanimate objects was successful. As expected, the three perceptual
dissimilarity predictors were related to each other: Overall perceptual dissimilarity correlated with
both outline dissimilarity (r=0.82) and texture dissimilarity (r=0.32). Outline and texture
dissimilarity were comparably less correlated (r=0.18), suggesting that they capture different
aspects of overall perceptual dissimilarity. Interestingly, a linear combination of outline
dissimilarity (75% weighting) and texture dissimilarity (25% weighting) closely resembled the

overall perceptual dissimilarity (see Proklova et al., 2016, for details). Considering this inter-
dependency between the perceptual dissimilarity matrices, we performed two separate
regression analyses: one with category and overall perceptual dissimilarity as predictors, and one
with category dissimilarity, outline dissimilarity and texture dissimilarity as predictors.

Neural dissimilarity

Following the approach used in previous MEG studies, we used pairwise decoding accuracy as a
measure of neural dissimilarity, where higher decoding accuracy corresponds to greater neural
dissimilarity (Cichy et al., 2014; Wardle et al., 2016). Classifier details are described in the Pairwise
decoding analyses section. The classifier accuracy at each time point was assessed as the
percentage of correctly classified trials (with chance performance being 50%) and was used as a
measure of neural dissimilarity between the two conditions. This classification procedure was
performed for all pairs of conditions, resulting in a 16 x 16 neural dissimilarity matrix for each time
point.

In addition, as an alternative neural dissimilarity measure we used linear discriminant t-
value (LD-t), a version of cross-validated Mahalanobis distance (Nili et al., 2014; Walther et al.,
2016). To obtain an LD-t value for each pair of stimuli, the data were divided into two parts
(training and testing set), and an LDA classifier was trained to discriminate between the two
stimuli (see above). The testing set was then projected on the discriminant dimension, and the t-
value was computed describing how well the two stimuli are discriminated. This measure was
calculated using the RSA toolbox (Nili et al., 2014). The 16 x 16 LD-t neural dissimilarity matrix was
obtained for each time point.

Neural dissimilarity was computed for magnetometers and gradiometers separately, and
all subsequent analyses are reported for both sensor types. Previous MEG studies on visual
category decoding have either used both sensor types together (e.g., Cichy et al., 2014), only
magnetometers (e.g., Kaiser et al., 2016a; 2016b), or only gradiometers (e.g., Ritchie et al., 2015).
Here, we decided to report data from magnetometers and gradiometers separately to
demonstrate consistency of the results across sensor types (similar results were obtained when
analyzing all sensors together).

Modelling the neural dissimilarity

After constructing neural dissimilarity matrices for each time point, as well as category and

perceptual dissimilarity matrices, we performed two regression-based representational similarity

analyses (RSA) to determine the contribution of category dissimilarity and different aspects of

perceptual dissimilarity to the MEG signal. All dissimilarity matrices were z-scored before

estimating the regression coefficients. In the first analysis, the neural dissimilarity at each time

point was modeled as a linear combination of category and overall perceptual dissimilarity (Figure

3A). This analysis was performed separately for each participant, resulting in two regression

weights for each time point per participant. In the second analysis, the neural dissimilarity at each

time point was modeled as a linear combination of category, outline, and texture dissimilarity

(Figure 3B). This produced three beta weights per participant for each time point. The time

courses of the resulting beta estimates for each predictor were then tested against zero.

Figure 3. Representational similarity analysis. *(A) For the first RSA, at each time point, the neural dissimilarity matrix*

was constructed by calculating the pairwise decoding accuracy for all pairs of stimuli. This neural dissimilarity matrix

was then modeled as a linear combination of overall perceptual dissimilarity and category dissimilarity. (B) For the

second RSA, the neural dissimilarity at each time point was modeled using outline, texture and category dissimilarity as

predictors.

Sensor-space searchlight analysis

To identify time periods and sensors in which the contribution of category or perceptual

dissimilarity to neural dissimilarity was significant, we performed a sensor-space searchlight

analysis. Using the same approach as in the previous analyses, we ran two representational

similarity searchlights. For these analyses, the pairwise decoding analysis was repeated for local sensor neighborhoods of ten sensors each. For each sensor location, neighborhoods were defined by selecting the sensor and its nine nearest neighboring sensors in the MEG gradiometer configuration; individual neighborhoods were thus overlapping in sensor space. For each sensor neighborhood the neural dissimilarity was computed for every post-stimulus time point. Then, to reduce the number of statistical comparisons, the neural dissimilarity matrices for each neighborhood were averaged in time bins of 50 ms, ranging from stimulus onset to 500 ms post-stimulus (resulting in 10 time bins).

The resulting neural dissimilarity matrices were then modeled at each time window as (1) a linear combination of category dissimilarity and overall perceptual dissimilarity, resulting in two beta estimate maps, and (2) a linear combination of category dissimilarity, outline dissimilarity, and texture dissimilarity, producing three beta estimate maps. The resulting beta estimates were mapped onto a scalp representation. The scalp maps for each predictor were then averaged across participants and tested against zero.

Statistical analysis

For all tests, statistical significance was assessed using the threshold-free cluster enhancement procedure (TFCE) (Smith and Nichols, 2009) with default parameters, using multiple-comparison correction based on a sign-permutation test (with null distributions created from 10,000 bootstrapping iterations) as implemented in the CoSMoMVPA toolbox (Oosterhof et al., 2016). The threshold was set at $Z > 1.64$ (i.e., $p < 0.05$, one-tailed), as further clarified in the individual sections. Significance in the searchlight analysis was assessed separately for each time window using the TFCE procedure to reveal the sensors in which the contribution of a particular predictor to the neural dissimilarity was significantly above chance.

Results

Behavioral results

Participants were very accurate in the oddball detection task of Experiment 1 (mean = 97%, SD = 2%) and the one-back repetition detection task of Experiment 2 (mean = 94%, SD = 1%). Responses were faster in Experiment 1 (mean = 0.47 s, SD = 0.06 s) than Experiment 2 (mean = 0.73 s, SD = 0.12 s).

Decoding stimulus conditions

To assess the quality of the MEG data and evaluate whether stimulus condition could be decoded from the MEG sensor patterns, we averaged the off-diagonal elements of the MEG dissimilarity matrix for each time point. This was done separately for Experiments 1 and 2, as well as for each of the two sensor types (magnetometers and gradiometers), producing four time courses of average pairwise stimulus decodability (Figure 4). In both experiments, and for both sensor types, decoding was at chance until about 50 ms, after which the decoding curve rose sharply, becoming significant at 60 ms (or at 70 ms for magnetometers in Experiment 2) and peaking at 120 ms. This pattern is similar to the pattern observed in previous studies (for review, see Contini et al., 2017). For both sensor types, average pairwise decoding accuracy was higher in Experiment 2, suggesting that the demands of a one-back task (e.g., enhanced attention to the objects, deeper object processing, and involvement of working memory) increases neural discriminability. Overall, these results replicate earlier MEG decoding studies and show that the individual stimuli could be decoded successfully from the MEG signal.

Figure 4. Time courses of average decodability of all stimulus pairs. Average pairwise stimulus decodability in Experiment 1 (left panel) and Experiment 2 (right panel), shown separately for two sensor types (solid line for gradiometers and dashed line for magnetometers). Circles indicate time bins where decoding accuracy was significantly greater than chance (0.5), with filled circles showing significant time points for gradiometers and empty circles for magnetometers.

Representational similarity analysis

To examine the separate contribution of overall perceptual dissimilarity (based on RTs in the visual search task) and category dissimilarity to neural dissimilarity, we performed a representational

similarity analysis (RSA) modelling the neural dissimilarity at each time point as the linear

combination of these two predictors (see Materials and Methods; Figure 3A). This analysis

produced one beta estimate time course for each predictor. The results of this analysis for both

experiments are shown in Figure 5A, separately for the two types of sensors. For both

magnetometers and gradiometers, the beta estimate for overall perceptual dissimilarity (shown in

red) reached significance at 80 ms, peaking at 130 ms. The beta estimate for category dissimilarity

(shown in blue) did not reach significance at any time point. In a second analysis, the neural

dissimilarity was modeled as a combination of category, outline, and texture dissimilarity (Figure

3B). This analysis produced three time courses that are shown in Figure 5B. The outline predictor

contributed significantly to neural dissimilarity, starting at 80 ms and peaking at 150 ms, followed

by a smaller peak at 250 ms. The time course of the texture predictor was significantly above

chance starting from 90 ms, with a peak at 130 ms. The beta estimate for category dissimilarity did

not reach significance at any time point.

Nearly identical results were obtained in Experiment 2, in which subject performed a one-

back task (Figure 5, right column). The first RSA again revealed a strong contribution of overall

perceptual dissimilarity, peaking at 120 ms for magnetometers and at 130 ms for gradiometers

(Figure 5A, right column). In the second RSA, the outline dissimilarity significantly contributed to

the neural dissimilarity with a peak at 150 ms for both magnetometers and gradiometers (Figure

5B, right column). Texture (shown in orange) peaked at 110 ms for both types of sensors. In both

analyses the category predictor again did not reach significance at any time point, confirming the

results of Experiment 1 with a different and more engaging task that required attention to object

identity.

Figure 5. RSA results using decoding accuracy. *(A) The time courses of regression weights for two sensor types (solid line for gradiometers and dashed line for magnetometers) showing the contributions of category dissimilarity (in blue) and overall perceptual dissimilarity (in red) to neural dissimilarity for Experiment 1 (left column) and Experiment 2 (right column). (B) The time courses of regression weights reflecting the contributions of category dissimilarity (in blue), outline dissimilarity (in green) and texture dissimilarity (in orange). Circles indicate time bins where beta estimates were significantly greater than zero, with filled circles showing significant time points for gradiometers and empty circles for magnetometers.*

It is possible that the previously described measure of neural dissimilarity (i.e., pairwise decoding accuracy) was not sensitive to reveal category effects. fMRI studies have suggested that the cross-validated Mahalanobis distance may be a more reliable measure of neural dissimilarity (Walther et al., 2016). Thus, we repeated all analyses using the neural dissimilarity matrices constructed using this measure (see Materials and Methods). The RSA results using this alternative neural dissimilarity measure are shown in Figure 6. The pattern of results was nearly identical to the one obtained using decoding accuracy.

Figure 6. RSA results using cross-validated Mahalanobis distance. *(A) Contributions of category dissimilarity (in blue) and perceptual dissimilarity (in red) to neural dissimilarity for two sensor types (solid line for gradiometers and dashed line for magnetometers). Results of Experiment 1 (left panel) and Experiment 2 (right panel). (B) The same analysis for three predictors (outline dissimilarity, texture dissimilarity, category dissimilarity). Circles indicate time bins where beta estimates were significantly greater than zero, with filled circles showing significant time points for gradiometers and empty circles for magnetometers.*

Finally, to maximize statistical power to detect category information, we combined the data of the two experiments, resulting in N=29. Moreover, to explore the possibility that category information emerges after 500 ms, we repeated the analysis for a longer time window, until 800 ms after stimulus onset. The results of these analyses are shown in Figure 7. In the first RSA (Figure 7A), the overall perceptual dissimilarity beta estimate peaked at 130 ms for both types of sensors and for both decoding accuracy (left column) and cross-validated Mahalanobis distance (right column) as measures of neural dissimilarity. In the second RSA (Figure 7B), the regression weights for outline dissimilarity peaked at 140 ms for magnetometers and at 150 ms for gradiometers for both dissimilarity measures. Texture dissimilarity beta estimates peaked at 120 ms for both sensor types. Category dissimilarity was not significant at any time point.

Figure 7. RSA results for both experiments combined (N=29). *(A) Contributions of category dissimilarity (in blue) and*

perceptual dissimilarity (in red) to neural dissimilarity for two sensor types (solid line for gradiometers and dashed line

for magnetometers). Results of both experiments combined using decoding accuracy as the measure of neural

dissimilarity (left panel), and cross-validated Mahalanobis distance (right panel). (B) The same analysis for three

predictors (outline dissimilarity, texture dissimilarity, category dissimilarity). Circles indicate time bins where beta

estimates were significantly greater than zero, with filled circles showing significant time points for gradiometers and

empty circles for magnetometers.

Representational similarity searchlight

The absence of category information in the previous analyses could in principle be due to

differences in the spatial scales of perceptual and category processing: perhaps perceptual

properties are well reflected in coarse patterns across all sensors, whereas more subtle categorical

responses are only reflected in localized patterns emerging across a few sensors. We therefore

performed a sensor-space representational similarity searchlight analysis. This analysis was done

using the data from gradiometers, because these sensors have greater spatial specificity and

showed numerically greater pairwise discriminability (e.g., Figure 4). Given that the pattern of

results in Experiments 1 and 2 was highly similar we pooled data from Experiments 1 and 2 for the

searchlight analysis to maximize power.

For each channel, we defined a neighborhood of ten adjacent channels and computed the

neural dissimilarity matrix for this neighborhood (see Materials and Methods). We then used the

RSA approach described earlier, modelling the neural dissimilarity for each channel as a

combination of category and perceptual dissimilarity. This procedure was repeated for each 50 ms

time window (see Materials and Methods), resulting in 10 searchlight maps showing the

contribution of perceptual and category dissimilarity to neural dissimilarity at different sensor

locations. In accordance with the previous analyses, this analysis did not reveal any sensors or

time windows in which the contribution of category dissimilarity to neural dissimilarity was

significantly above zero (Figure 8A). In contrast, the contribution of perceptual dissimilarity again

reached significance in the 50-100 ms time window and stayed significant throughout all

subsequent time windows, starting in a group of posterior sensors and progressing to more

anterior sensors at 100-250 ms, peaking at 150-200 ms and gradually receding towards the

posterior sensors again (Figure 8B). These results suggest that the MEG neural dissimilarity across

multiple channel locations predominantly reflects perceptual, but not category dissimilarity, also

when looking at more localized sensor patterns.

Figure 8. RSA searchlight results: category and perceptual dissimilarity. *(A) Searchlight maps showing the regression*

weights reflecting the contribution of category dissimilarity to MEG patterns across channels (gradiometers) and ten

time windows. The beta estimates for category were not significantly above zero in any of the sensors for all time

 windows. (B) Searchlight maps showing the perceptual dissimilarity regression weights across gradiometers for ten

time windows. Asterisks indicate sensor locations where beta estimates were significantly greater than zero.

Finally, we ran a second RSA searchlight, using category, outline and texture dissimilarity as

predictors of neural dissimilarity. The results of this analysis are shown in Figure 9. As in the

previous analysis, no sensors in any time window exhibited a significant contribution of category

dissimilarity to MEG neural dissimilarity (Figure 9A). By contrast, the outline dissimilarity beta

estimates reached significance at 50-100 ms after stimulus onset in a group of left posterior

sensors, spreading to more anterior sensors at 100-150 ms and peaking at 150-200 ms, staying

significant in posterior channels throughout all time windows (Figure 9B). Similarly, texture

dissimilarity beta estimates reached significance in a cluster of central posterior sensors at 50-100

ms and stayed significant at multiple channel locations in all the next time windows, peaking at

150-200 ms (Figure 9C).

 Figure 9. *RSA searchlight results: category, outline and texture dissimilarity.* *(A) Beta estimate maps showing the*

447 *contribution of category dissimilarity to MEG patterns across channels (gradiometers) and ten 50-ms time windows.*

448 *The beta estimates for category did not reach significance in any of the sensors or time windows. (B) Beta estimate*

449 *maps showing the contribution of outline dissimilarity to the MEG signal across gradiometers for ten time windows. (C)*

450 *Beta estimates reflecting contribution of texture dissimilarity to neural dissimilarity. Asterisks indicate sensor locations*

451 *where beta estimates were significantly greater than zero.*

Discussion

In this study, we used a carefully designed stimulus set to disentangle categorical from perceptual

properties in driving MEG sensor patterns. Replicating previous reports, MEG sensor patterns

carried information about individual objects (Carlson et al., 2011; Carlson et al., 2013; van de

Nieuwenhuijzen et al., 2013; Cichy et al., 2014; Isik et al., 2014; Clarke et al., 2015; Ritchie et al.,

2015; Coggan et al., 2016; Kaiser et al., 2016a). Using representational similarity analysis, we then

related MEG neural similarity to the objects' perceptual and categorical similarity. This analysis

revealed the time course of the objects' overall perceptual similarity as well as the separate

contributions of outline shape and inner texture; each of these independently contributed to MEG

neural similarity but with overlapping time courses. Contrary to our prediction, there was no

category information in the MEG patterns even though participants easily recognized the objects

at the basic level, as evidenced by behavioral performance in Experiment 2 and post-experiment

debriefing.

These results can be directly compared with those of a recent fMRI study using the same

stimulus set, task, and analysis approach (Proklova et al., 2016). Similar to the current MEG

findings, outline shape and texture also contributed independently to multi-voxel fMRI patterns in

visual cortex, with these regions partly overlapping. However, unlike the current MEG results,

fMRI showed a highly reliable contribution of object category to neural similarity in anterior VTC.

Our results therefore show that the representation of animacy for shape-matched objects in VTC

does not give rise to distinct scalp-level patterns as observed with MEG. It should be noted,

however, that considering the fact that the animacy of our stimuli during this task *is* represented

in the brain (Proklova et al., 2016), it remains a possibility that other types of analysis (e.g.,

decoding in source-space; van de Nieuwenhuijzen et al., 2013) or additional preprocessing of the

MEG data (e.g., principal component analysis; Grootswagers et al., 2017) could still retrieve this

information. Nevertheless, our results suggest that any such information is likely to be very weak

relative to information about visual properties.

Our results show that MEG sensor patterns in the 150-250 ms range reflect perceptual

properties, including outline shape and inner texture, derived from response times in a visual

search task. Previous behavioral work has shown that this perceptual similarity measure can be

used to predict animate-inanimate categorization times when using stimuli that naturally

confound visual features and category (Mohan and Arun, 2012). For example, a side-view picture

of a cow is quickly categorized as animate because it is perceptually relatively similar to other

animals (e.g., sheep, horse, dog) and relatively dissimilar from inanimate objects. These findings,

combined with our current results, suggest that previous MEG reports of animacy decoding in the

150-250 ms range likely reflected the perceptual differences between animate and inanimate

objects. In the current stimulus set, the perceptual similarity measure no longer reflects

categorical influences (Proklova et al., 2016), allowing us to dissociate these two components and

reveal that MEG sensory patterns at 150-250 ms reflect perceptual object properties rather than

object category *per se*.

It should be noted that previous studies provided some evidence for a contribution of

semantic object properties to the MEG signal even at relatively early latencies (<250 ms; Clarke et

al., 2015; Coggan et al., 2016; Kaiser et al., 2016b). These studies differed from the current study

in several important ways. First, none of these studies controlled for perceptual similarity using

human judgments or task performance. It is likely that the semantic factors in these studies (e.g.,

the property "has legs"; Clarke et al., 2015) would still express in perceptual similarity differences

in tasks like the visual search task used here. Second, two of these studies included human faces

(Coggan et al., 2016) or bodies (Kaiser et al., 2016b). The human visual system is particularly

sensitive to such stimuli (Stein et al., 2012), showing highly selective and localized face- and body-

selective responses in fMRI (Kanwisher, 2010).

Notably, these face- and body-selective responses are right lateralized in most participants

(Willems et al., 2010), thus resulting in distinct scalp topographies (Thierry et al., 2006) that are

likely more easily decodable than the bilateral animate-inanimate organization investigated here

(no significant lateralization of animacy was observed in Proklova et al., 2016, see their Figure 3B).

Similarly, the animate stimuli used in the current study (birds, reptiles, insects) give a lower

response than mammals in right-lateralized face- and body-selective regions (Downing et al.,

2006), which may reflect their lower score on a proposed animacy continuum (Sha et al., 2015).

These considerations leave open the possibility that MEG sensor patterns contain information
about more human-like animals (e.g., mammals), even after shape matching. Future studies
should test the decoding of other shape-matched categories to investigate whether lateralization
is indeed required for MEG to reveal categorical representations in high-level visual cortex.

To conclude, the current study shows that MEG sensor patterns are highly sensitive to two
independent perceptual features (outline shape and texture) of visually presented objects,
quantified using behavioral perceptual similarity measures. By contrast, MEG sensor patterns
appear insensitive to the conceptual-level distinction between animate and inanimate objects,
unlike fMRI voxel patterns in ventral temporal cortex (Proklova et al., 2016). The discrepancy
between the information contained in MEG and fMRI patterns may need to be considered when
integrating these methods, for example using RSA (Cichy et al., 2016).

References

Amedi A, Hofstetter S, Maidenbaum S, Heimler B (2017) Task Selectivity as a Comprehensive
525   Principle for Brain Organization. Trends Cogn Sci 21:307-310.

526   Bracci S, Op de Beeck H (2016) Dissociations and Associations between Shape and Category
527   Representations in the Two Visual Pathways. J Neurosci 36:432-444.

528   Brainard DH (1997) The Psychophysics Toolbox. Spat Vis 10:433-436.

529   Bryan PB, Julian JB, Epstein RA (2016) Rectilinear Edge Selectivity Is Insufficient to Explain the
530   Category Selectivity of the Parahippocampal Place Area. Front Hum Neurosci 10:137.

531   Carlson T, Tovar DA, Alink A, Kriegeskorte N (2013) Representational dynamics of object vision: the
532   first 1000 ms. J Vis 13.

533   Carlson TA, Hogendoorn H, Kanai R, Mesik J, Turret J (2011) High temporal resolution decoding of
534   object position and category. J Vis 11.

535   Cichy RM, Pantazis D, Oliva A (2014) Resolving human object recognition in space and time. Nat
536   Neurosci 17:455-462.

537   Cichy RM, Pantazis D, Oliva A (2016) Similarity-Based Fusion of MEG and fMRI Reveals Spatio-
538   Temporal Dynamics in Human Cortex During Visual Object Recognition. Cereb Cortex
539   26:3563-3579.

540   Clarke A, Devereux BJ, Randall B, Tyler LK (2015) Predicting the Time Course of Individual Objects
541   with MEG. Cereb Cortex 25:3602-3612.

542   Coggan DD, Baker DH, Andrews TJ (2016) The Role of Visual and Semantic Properties in the
543   Emergence of Category-Specific Patterns of Neural Response in the Human Brain. eNeuro
544   3.

545   Contini EW, Wardle SG, Carlson TA (2017) Decoding the time-course of object recognition in the
546   human brain: From visual features to categorical decisions. Neuropsychologia 105:165-176.

547   Downing PE, Chan AW, Peelen MV, Dodds CM, Kanwisher N (2006) Domain specificity in visual
548   cortex. Cereb Cortex 16:1453-1461.

549   Grill-Spector K, Weiner KS (2014) The functional architecture of the ventral temporal cortex and its
550   role in categorization. Nat Rev Neurosci 15:536-548.

551   Grootswagers T, Wardle SG, Carlson TA (2017) Decoding Dynamic Brain Patterns from Evoked
552   Responses: A Tutorial on Multivariate Pattern Analysis Applied to Time Series
553   Neuroimaging Data. J Cogn Neurosci 29:677-697.

554   Isik L, Meyers EM, Leibo JZ, Poggio T (2014) The dynamics of invariant object recognition in the
555   human visual system. J Neurophysiol 111:91-102.

556   Kaiser D, Oosterhof NN, Peelen MV (2016a) The Neural Dynamics of Attentional Selection in
557   Natural Scenes. J Neurosci 36:10522-10528.

558   Kaiser D, Azzalini DC, Peelen MV (2016b) Shape-independent object category responses revealed
559   by MEG and fMRI decoding. J Neurophysiol 115:2246-2250.

560   Kanwisher N (2010) Functional specificity in the human brain: a window into the functional
561   architecture of the mind. Proc Natl Acad Sci U S A 107:11163-11170.

562   Kriegeskorte N, Mur M, Bandettini P (2008) Representational similarity analysis - connecting the
563   branches of systems neuroscience. Front Syst Neurosci 2:4.

564   Macdonald SN, Culham JC (2015) Do human brain areas involved in visuomotor actions show a
565   preference for real tools over visually similar non-tools? Neuropsychologia 77:35-41.

566   Mohan K, Arun SP (2012) Similarity relations in visual search predict rapid visual categorization. J
567   Vis 12:19.

568   Nili H, Wingfield C, Walther A, Su L, Marslen-Wilson W, Kriegeskorte N (2014) A toolbox for
569   representational similarity analysis. PLoS Comput Biol 10:e1003553.

570   Oostenveld R, Fries P, Maris E, Schoffelen JM (2011) FieldTrip: Open source software for advanced
571   analysis of MEG, EEG, and invasive electrophysiological data. Comput Intell Neurosci
572   2011:156869.

Oosterhof NN, Connolly AC, Haxby JV (2016) CoSMoMVPA: Multi-Modal Multivariate Pattern
Analysis of Neuroimaging Data in Matlab/GNU Octave. Front Neuroinform 10:27.

Peelen MV, Downing PE (2017) Category selectivity in human visual cortex: Beyond visual object
recognition. Neuropsychologia 105:177-183.

Proklova D, Kaiser D, Peelen MV (2016) Disentangling Representations of Object Shape and Object
Category in Human Visual Cortex: The Animate-Inanimate Distinction. J Cogn Neurosci
28:680-692.

Ritchie JB, Tovar DA, Carlson TA (2015) Emerging Object Representations in the Visual System
Predict Reaction Times for Categorization. PLoS Comput Biol 11:e1004316.

Sha L, Haxby JV, Abdi H, Guntupalli JS, Oosterhof NN, Halchenko YO, Connolly AC (2015) The
animacy continuum in the human ventral vision pathway. J Cogn Neurosci 27:665 -678.

Smith SM, Nichols TE (2009) Threshold-free cluster enhancement: addressing problems of
smoothing, threshold dependence and localisation in cluster inference. Neuroimage 44:83-
98.

Stein T, Sterzer P, Peelen MV (2012) Privileged detection of conspecifics: evidence from inversion
effects during continuous flash suppression. Cognition 125:64-79.

Thierry G, Pegna AJ, Dodds C, Roberts M, Basan S, Downing P (2006) An event-related potential
component sensitive to images of the human body. Neuroimage 32:871-879.

van de Nieuwenhuijzen ME, Backus AR, Bahramisharif A, Doeller CF, Jensen O, van Gerven MA
(2013) MEG-based decoding of the spatiotemporal dynamics of visual category perception.
Neuroimage 83:1063-1073.

Walther A, Nili H, Ejaz N, Alink A, Kriegeskorte N, Diedrichsen J (2016) Reliability of dissimilarity
measures for multi-voxel pattern analysis. Neuroimage 137:188-200.

Wardle SG, Kriegeskorte N, Grootswagers T, Khaligh-Razavi SM, Carlson TA (2016) Perceptual
similarity of visual patterns predicts dynamic neural activation patterns measured with
MEG. Neuroimage 132:59-70.

Willems RM, Peelen MV, Hagoort P (2010) Cerebral lateralization of face-selective and body-
selective visual areas depends on handedness. Cereb Cortex 20:1719-1725.

Willenbockel V, Sadr J, Fiset D, Horne GO, Gosselin F, Tanaka JW (2010) Controlling low-level
image properties: the SHINE toolbox. Behav Res Methods 42:671-684.