ClassificalO: machine learning for classification graphical user interface

Raeuf Roushangar [1, 2], George I. Mias [1, 2*]

[1] Department of Biochemistry and Molecular Biology,

[2] Institute for Quantitative Health Science and Engineering,

Michigan State University, East Lansing MI 48824, USA

*Corresponding author

E-mail: gmias@msu.edu (GM)

Abstract

Machine learning methods are being used routinely by scientists in many research areas, typically requiring significant statistical and programing knowledge. Here we present ClassificaIO, an open-source Python graphical user interface for machine learning classification for the scikit-learn Python library. ClassificaIO provides an interactive way to train, validate, and test data on a range of classification algorithms. The software enables fast comparisons within and across classifiers, and facilitates uploading and exporting of trained models, and both validation and testing data results. ClassificaIO aims to provide not only a research utility, but also an educational tool that can enable biomedical and other researchers with minimal machine learning background to apply machine learning algorithms to their research in an interactive point-and-click way. The ClassificaIO package is available for download and installation through the Python Package Index (PyPI) (http://pypi.python.org/pypi/ClassificaIO) and it can be deployed using the "import" function in Python once the package is installed. The application is distributed under an MIT license and the source code is publicly available for download (for Mac OS X, Linux and Microsoft Windows) through PyPI and GitHub (http://github.com/gmiaslab/ClassificaIO, and https://doi.org/10.5281/zenodo.1320465).

Introduction

Recent advances in high-throughput technologies, especially in genomics, have led to an explosion of large-scale structured data (e.g. RNA-sequencing and microarray

data) (1). Machine learning methods (classification, regression, clustering, etc.) are routinely used in mining such big data to extract biological insights in a range of areas within genetics and genomics (2). For example, using unsupervised machine learning classification methods to predict the sex of gene expression microarrays donor samples (3), using genome sequencing data to train machine learning models to identify transcription start sites (4), splice sites (5), transcriptional promoters and enhancers regions (6). Recent examples of using machine learning classification methods include their use to detect neurofibromin 1 tumor suppressor gene inactivation in glioblastoma (7), and to identify reliable gene markers for drug sensitivity in acute myeloid leukemia (8). Many advanced machine learning algorithms have been developed in the recent years. Scikit-learn (9) is one of the most popular machine learning libraries in Python with a plethora of thoroughly tested and well-maintained machine learning algorithms. However, these algorithms are primarily aimed at users with computational and statistical backgrounds, which may discourage many biologists, biomedical scientists or beginning students (who may have minimal machine learning background but still want to explore its application in their research) from using machine learning. Ching et al (2018) recently highlighted the role of deep learning (a class of machine learning algorithms) currently plays in biology, and how such algorithms present new opportunities and obstacles for a data-rich field such as biology (10).

Several open source machine learning applications, such as KNIME (11) and Weka (12) written in Java and Orange (13) written in Python, have been developed with graphical user interfaces. The dataflow process for most of these applications is generally graphically constructed by the user, in the form of placing and connecting

widgets by drag-and-drop. Such graphical workflow and representation of data input, processing and output is visually appealing, but can be computationally demanding (memory, storage, processing, etc.) and limiting in algorithm comparison, since each machine learning algorithm can have many different parameters. These tools are very mature with numerous algorithms, and well documented. However, they can be intimidating for machine learning beginners and students that want to preform simple tasks such as data classification. Also, scikit-learn has comprehensive documentation (14), and many online resources, including though Kaggle (15) and Stack Overflow (16), and a large online user base, which make scikit-learn a very popular package for machine learning beginners learning using Python.

Here, we present ClassificaIO, an open-source Python graphical user interface (GUI) for supervised machine learning classification for the scikit-learn library. To the best of our knowledge, no standalone GUI exists for the scikit-learn library. ClassificaIO's core aim is to provide a, machine learning research, teaching and educational tool that is visually minimalistic and computationally light interactive interface, that can give access to a range of state-of-the-art classification algorithms to machine learning beginners with some basic knowledge of Python and using a terminal, and with broad background in machine learning, allowing them to use machine learning and apply it to their research. What distinguishes ClassificaIO from other similar applications is:

- Cross-platform implementation for Mac OS X, Linux, and Windows operating systems

- Interactive point-and-click GUI to 25 supervised classification algorithms in scikit-learn

- Accessible clickable links, to scikit-learn's well-written online documentation for each implemented classification algorithms

- Simple upload of all data files with dedicated buttons; with robust CSV reader, and a displayed history-log to track uploaded files, files names and directories

- Fast comparisons within and across classifiers to train, validate, and test data

- Upload and export of ClassificaIO trained models (for future of a trained model without the need to retrain), and export of both validated, and tested data results

- Small application footprint in terms of disk space usage (<2 MB)

Materials and methods

ClassificaIO implementation

ClassificaIO has been developed using the standard Python interface Tkinter module to the Tk GUI toolkit (17), for Mac OS X (using High Sierra $\geq$ 10.13), Linux (using Ubuntu 18.04-64 bit), and Windows (using Windows 10 64-bit), Table 1. It uses external packages including: Tkinter, Pillow, Pandas (18), NumPy (19), scikit-learn and SciPy (20). To avoid any system errors, crashes, and crude fonts, we recommend not to install ClassificaIO using integrated environment package installers – instead, native

installation of ClassificaIO and dependencies (using pip for Mac and Windows, and pip3

and apt-get for Linux) is encouraged. Once installed, ClassificaIO can be deployed

using the 'import' function. A ClassificaIO user manual uploaded as supplementary file

S1_Manual (hereafter referred to as S1) is also distributed with ClassificaIO GUI and

can be accessed directly through the 'HELP' button at the upper left of the GUI, that

points the user's default browser to ClassificaIO's online user manual on GitHub. Some

basic knowledge of Python and accessing it through a terminal are required for

installation and running the software. Additional ClassificaIO software information is

provided in Table 1.

Table 1. ClassificaIO software information

Current ClassificaIO Version	1.1.5
Public Links to Executables	PyPI: https://pypi.org/project/ClassificaIO/ GitHub: https://github.com/gmiaslab/ClassificaIO
Distribution License	MIT license (MIT)
Operating Systems	Mac OS X, Linux, and Microsoft Windows
Software Installation Dependencies	Python 3 and Python libraries: Tkinter, Pillow, Pandas, NumPy, scikit-learn and SciPy
ClassificaIO Online User Manual	https://github.com/gmiaslab/manuals/blob/master/ClassificaIO /ClassificaIO_UserManual.pdf
Supplementary Data Online Availability	https://github.com/gmiaslab/manuals/tree/master/ClassificaIO/ Supplementary%20Files
Contact E-mail	gmiaslab@gmail.com

112 ClassificaIO is provided as open source software, and distributed on GitHub and PyPI. Up-to-
113 date code, manuals and supplementary example material will be maintained on GitHub.

ClassificaIO backend

ClassificaIO implements 25 scikit-learn classification algorithms for supervised

machine learning. A list of all these algorithms, their corresponding scikit-learn

functions, and immutable (unchangeable) parameters with their default values are

presented in S1 Table 1, and ClassificaIO's workflow is outlined in Fig 1. Once training

and testing data are uploaded to the front-end as described below, a classifier selection

is made and submitted, ClassificaIO's backend calls the scikit-learn selected classifier,

including any values from manually set parameters to create the model. Otherwise, the

default parameters values are used instead. For example, for "LogisticRegression", the

model is defined in the scikit-learn library as a class, in terms of Python code used in

the backend, the details are outlined in the scikit-learn documentation:

sklearn.linear_model.LogisticRegression(penalty='l2', dual=False, tol=0.0001, C=1.0, fit

_intercept=True, intercept_scaling=1, class_weight=None, random_state=None, solver=

'liblinear', max_iter=100, multi_class='ovr', verbose=0, warm_start=False, n_jobs=1)

Fig1. ClassificaIO workflow. The diagram summarizes the graphical user interface

and backend functionality/workflow for ClassificaIO Use My Own Training Data and

Already Trained My Model windows.

The inputs to the class, within the parentheses, such as "penalty", "dual", "tol",

etc., correspond to the model parameters, followed by an equal sign assigning the

default values for these parameters. Rather than typing the values, the ClassificaIO GUI

displays these parameters with input fields and radio buttons, for each classifier, initially

populated by the default values. More information is available for all the parameters in

the GUI, through a link for each classifier in the interface named "Learn More". The link

directs the default browser to the scikit-learn online documentation of the selected classifier, and connects to the underlying backend documentation, and online parameter descriptions. The details and code complexity of the backend implementation are effectively hidden from the user, who can interact with the ClassificaIO GUI to set the relevant parameters, or leave them unchanged as default values. On the training data, ClassificaIO fits the estimator for classification using the scikit-learn 'fit' method, e.g. fit(x_train, y_train), to train (learn from the model), and uses the scikit-learn 'predict' method, e.g. predict(x_validation), to validate the model. Finally, ClassificaIO predicts new values using the scikit-learn 'predict' method again but on the testing data, e.g. predict(testing_X), for implementing the model on new data that have not been used in model training.

ClassificaIO functionalities

ClassificaIO's GUI consists of three windows: 'Main', 'Use My Own Training Data', and 'Already Trained My Model'. Each window is actually implemented within the code as a class with several functions/methods that are dynamically connected to provide the GUI. ClassificaIO's Main window, Fig 2, has two buttons: (i) the 'Use My Own Training Data' button, which when clicked allows the user to train and test classifiers using their own training and testing data, (ii) the 'Already Trained My Model' button, which when clicked allows the user to use their own already ClassificaIO trained model and testing data.

Fig 1. ClassificaIO main window. The main window appears on the screen after typing 'ClassificaIO.gui()' in a terminal or a Python interpreter.

Data input

For the 'Use My Own Training Data' window, Fig 3a, by clicking the

corresponding buttons in the 'UPLOAD TRAINING DATA FILES' and 'UPLOAD

TESTING DATA FILE' panels, a file selector directs the user to upload all required

comma-separated values (CSV) data files ('Dependent and Target' or 'Dependent,

Target and Features' and 'Testing Data') (S1 Fig 1). Briefly, the dependent data

represent the data on which the model will depend on for learning, and the target data is

the annotation, i.e. what is going to be predicted. The dependent data have attributes

(also known as features) that take values (measurements/results) for each contained

object (i.e. each sample). Further details on data files formats and examples are

provided in the S1 Figs 3(a, b) and S2-S5. A history of all uploaded data files (file name

and directory) is automatically saved in the 'CURRENT DATA UPLOAD' panel (S1 Figs

2 and 7(c)).

Fig 3. ClassificaIO user interface (Mac OS shown). As described in ClassificaIO

implementation section, (a) an example 'Use My Own Training Data' window with

uploaded training and testing data files, selected logistic regression classifier, populated

classifier parameters, and output classification results. (b) A corresponding 'Already

Trained My Model' window with uploaded logistic regression ClassificaIO trained model

and testing data file, and output classification result.

Classifier selection

After the data is uploaded, the user can select between all 25 different widely

used classification algorithms (including logistic regression, perceptron, support vector

machines, k-nearest neighbors, decision tree, random forest, neural network multi-layer

perceptron, and more). The algorithms are integrated from the scikit-learn library, and

allow the user to train and test models using their own uploaded data. Each classifier

can be easily selected by clicking the corresponding classifier name in the 'CLASSIFER

SELECTION' panel (see S1 'Classifier selection' section). Once classifier selection is

completed, a brief description for the classifier with an underlined clickable link that

reads "Learn more" right next to the classifier name (S1 Fig 4(a)) and the classifier

parameters will populate (S1 Fig 4(c)). If "Learn more" is clicked, the link directs the

default web browser to open scikit-learn's online well-written documentation that

explains the specific classifier parameters, with explanation for each parameter and its

use, and how to tune/optimize each parameter to get the best performance. ClassificaIO

provides the user with an interactive point-and-click interface to set, modify, and test the

influence of each parameter on their data. The user can switch between classifiers and

parameters through point-and-click, which enables fast comparisons within and across

classifier models.

Model training

199   Both train-validate split and cross-validation methods (which are necessary to

200 prevent/minimize overfitting) will populate with each classifier that can be used for data

201 training (S1 Fig 4(b)). Training, validating and testing are all performed after pressing

202 the submit button (middle of Fig. 3(a)).

Results output

After model training and testing is completed, the confusion matrix, classifier accuracy and error are displayed in the 'CONFUSION MATRIX, MODEL ACCURACY & ERROR' panel, bottom of Fig 3(a) and S1 Fig 5(a). Model validation data results are displayed in the 'TRAINING RESULT: ID – ACTUAL – PREDICTION' panel, S1 Fig 5(b), and testing data results are displayed in the 'TESTING RESULT: ID – PREDICTION' panel, S1 Fig 6(b).

Model export

By clicking on the 'Export Model' button (see Fig 3(a) bottom left and S1 Fig 5(a)), the user can export trained models to save for future use without having to retrain. A previously exported ClassificaIO model can then be used for testing of new data in the 'Already Trained My Model' window, Fig 3(b), by clicking the 'Model file' button in the 'UPLOAD TRAINING MODEL FILE' panel (S1 Fig 7(a)).

Results export

Full results (trained models, both validated and tested data, and uploaded files names and directories) for both windows, Fig 3(a and b), can be exported as CSV files for further analysis for publication, sharing, or later use (for more details on the exported trained model and data file formats, see S7 and S8).

Results: Illustrative examples and data used

To illustrate the use of the interface and classification, we have used in this manuscript

the following two examples (also see the S1 for more details).

(i). Iris prediction using Iris dataset. To demonstrate the interface and classification,

we used the so-called Fisher/Anderson iris dataset (21, 22). This dataset is used widely

as a prototype to illustrate classification algorithms, not only of biological data but in

general machine learning implementations. The dataset consists of fifty samples each

for three different species of iris flowers (Setosa, Versicolor and Viginica), with sepal

length and width, and petal length and width provided as measurements. For more

details on the iris data files format, see S1 Fig 3(a,b) and S2-S5.

(ii). Sex prediction using microarray gene expression data. In this example,

provided in ClassificaIO user manual (S1), we used raw microarray gene expression

data, from Gene Expression Omnibus (GEO) (23) to predict each sample donor's sex.

This is often necessary in metadata analyses, using publicly available gene expression

datasets for reanalysis, as samples annotations on GEO may be missing information,

including sample donor's sex. To illustrate the classification/sex prediction we used two

datasets, GSE99039 (24) (training data) and GSE18781 (25) (testing data). In both

GSE99039 and GSE18781 datasets, we used 121 and 25 samples respectively, for

which RNA from peripheral blood mononuclear cells was assayed using Affymetrix

Human Genome U133 Plus 2.0 Array (accession GPL570). The Y chromosome gene

expression values were used in ClassificaIO as training and testing data to predict

samples donor's sex. Using the 'Linear SVC' model with "k-fold cross validation" (10-

fold), resulted into a model with 99% accuracy for sample donor's sex prediction (in the

displayed example). For more details on the pre-processing of the raw gene expression

data, files format, and Y chromosome probes ids, and final result, see S1 'Additional

Examples: Ex2' section and Figs 9 and 10.

Discussion

We have presented ClassificaIO, a GUI that implements the scikit-learn

supervised machine learning classification algorithms. The scikit-learn package is one

of the most popular in Python with well-written documentation, and many of its machine

leaning algorithms are currently used for analyzing large and complex data sets in

genomics. Our interface aims to provide an interactive machine learning research,

teaching and educational tool to do machine learning analysis without the requirement

of advanced computational and machine learning knowledge using scikit-learn.

ClassificaIO is provided as an open source software, and its back-end classes and

functions allow for rapid development. We anticipate further development, aided by the

scikit-learn library developer community to integrate additional classification algorithms,

and extend ClassificaIO to include other machine leaning methods such as regression,

clustering, and anomaly detection, to name but a few.

Acknowledgements

265 None

References

1. Mias GI, Snyder M. Personal genomes, quantitative dynamic omics and personalized medicine. Quant Biol. 2013;1(1):71-90.

2. Libbrecht MW, Noble WS. Machine learning applications in genetics and genomics. Nat Rev Genet. 2015;16(6):321-32.

3. Buckberry S, Bent SJ, Bianco-Miotto T, Roberts CT. massiR: a method for predicting the sex of samples in gene expression microarray datasets. Bioinformatics. 2014;30(14):2084-5.

4. Ohler U, Liao GC, Niemann H, Rubin GM. Computational analysis of core promoters in the Drosophila genome. Genome Biol. 2002;3(12):RESEARCH0087.

5. Degroeve S, De Baets B, Van de Peer Y, Rouze P. Feature subset selection for splice site prediction. Bioinformatics. 2002;18 Suppl 2:S75-83.

6. Heintzman ND, Stuart RK, Hon G, Fu Y, Ching CW, Hawkins RD, et al. Distinct and predictive chromatin signatures of transcriptional promoters and enhancers in the human genome. Nat Genet. 2007;39(3):311-8.

7. Way GP, Allaway RJ, Bouley SJ, Fadul CE, Sanchez Y, Greene CS. A machine learning classifier trained on cancer transcriptomes detects NF1 inactivation signal in glioblastoma. BMC Genomics. 2017;18(1):127.

8. Lee SI, Celik S, Logsdon BA, Lundberg SM, Martins TJ, Oehler VG, et al. A machine learning approach to integrate big data for precision medicine in acute myeloid leukemia. Nat Commun. 2018;9(1):42.

9. Pedregosa F, Varoquaux G, Gramfort A, Michel V, Thirion B, Grisel O, et al. Scikit-learn: Machine Learning in Python. J Mach Learn Res. 2011;12:2825-30.

10. Ching T, Himmelstein DS, Beaulieu-Jones BK, Kalinin AA, Do BT, Way GP, et al. Opportunities and obstacles for deep learning in biology and medicine. J R Soc Interface. 2018;15(141).

11. Berthold MR, Cebron N, Dill F, Gabriel TR, Kotter T, Meinl T, et al. KNIME: The Konstanz Information Miner. Stud Class Data Anal. 2008:319-26.

12. Frank E, Hall M, Trigg L, Holmes G, Witten IH. Data mining in bioinformatics using Weka. Bioinformatics. 2004;20(15):2479-81.

13. Demsar J, Curk T, Erjavec A, Gorup C, Hocevar T, Milutinovic M, et al. Orange: Data Mining Toolbox in Python. J Mach Learn Res. 2013;14:2349-53.

14. Scikit Learn Documentation. Scikit learn online documentation. 2018.

15. Help KDa. How to use kaggle 2018 [Available from: https://www.kaggle.com/docs.]

16. Stack Overflow. The stack overflow python online comunity. 2018.

17. Ousterhout JK. Tcl and the Tk toolkit. Reading, Mass.: Addison-Wesley; 1994. xx, 458 p. p.

18. McKinney W, editor Data structures for statistical computing in python. Proceedings of the 9th Python in Science Conference; 2010.

19. Oliphant TE. A guide to NumPy: Trelgol Publishing USA; 2006.

20.   Olivier BG, Rohwer JM, Hofmeyr JHS. Modelling cellular processes with Python
and Scipy. Mol Biol Rep. 2002;29(1-2):249-54.
21.   Fisher RA. The use of multiple measurements in taxonomic problems. Ann
Eugenic. 1936;7:179-88.
22.   Anderson E. The Irises of the Gaspe peninsula. Bulletin of American Iris Society.
1935;59:2-5.
23.   Edgar R, Domrachev M, Lash AE. Gene Expression Omnibus: NCBI gene
expression and hybridization array data repository. Nucleic Acids Res. 2002;30(1):207-
10.
24.   Shamir R, Klein C, Amar D, Vollstedt EJ, Bonin M, Usenovic M, et al. Analysis of
blood-based gene expression in idiopathic Parkinson disease. Neurology.
2017;89(16):1676-83.
25.   Sharma SM, Choi D, Planck SR, Harrington CA, Austin CR, Lewis JA, et al.
Insights in to the pathogenesis of axial spondyloarthropathy based on gene expression
profiles. Arthritis Res Ther. 2009;11(6):R168.

Supporting information

S1 Fig 1. Graphical control element dialog box. (a) Dependent data file selected for

upload. (b) Selected target data file to upload. N.B. each file selection has to be done

one at a time.

S1 Fig 2. Current data upload panel. Both dependent and target data file names

shown (red boxes). Scroll down for uploaded data files directories.

S1 Fig 3(a) Dependent data. Example of partial dependent data file format. Testing

data (not shown) uses the same format.

S1 Fig 3(b) Target data. Example of partial target data file format where the targets

correspond to setosa = 0, versicolor = 1, and virginica = 2. Versicolor and virginica are

not visible in this screenshot.

S1 Fig 4. Selected logistic regression classifier. The interface for each selected

classifier, has uniform features. (a) Classifier definition is displayed, together with an

underlined clickable link that reads "Learn more" next to the classifier name. (b) Training

methods with 'Train Sample Size (%)' method selected. (c) The classifier parameters

set to their default values.

S1 Fig 5. Trained logistic regression classifier. (a) Trained model using 78 data

points (75% of 105 data points), classifier evaluation (confusion matrix, model accuracy

and error). (b) Model validated using 27 data points (25% of 105 data points).

S1 Fig 6. Tested logistic regression classifier. (a) Upload testing data panel. (b)

Model tested using 45 data points.

S1 Fig 7. 'Already Trained My Model' window. (a) Upload ClassificaIO trained model

panel. (b) Upload testing data panel. (c) Current data upload panel with both model and

testing data files names shown (red boxes). (d) Model preset parameters. (e) Trained

model result and model evaluation (confusion matrix, model accuracy and error). (f)

Model testing result.

S1 Fig 8. Training and testing using gene expression data. (a) selected k-nearest

neighbors classifier with trained and tested the data using the default parameters

values, (b) Same classifier selected with trained and tested data but using different

parameters values.

S1 Fig 9. Trained linear support vector machine classifier. Trained model using

GSE99039 121 data points and k-fold cross validation, classifier evaluation (confusion

matrix, model accuracy and error). Model validated and tested model using GSE18781

25 data points.

S1 Fig 10. Features data. Example of partial features data file format where each

Affymetrix probe id correspond to a Y chromosome gene.

S1_Manual. ClassificaIO user manual. User manual for ClassificaIO, including all

supplementary Figs 1-10 as well as working examples implementing using

supplementary files S2-S8.

S2_Iris_Dependent_DataSet.csv. Iris dependent data set (105 data points).

S3_Iris_Target.csv. Iris Target data set (105 labels).

S4_Iris_Testing_DataSet.csv. Iris testing data set (45 data points).

S5_Iris_FeatureNames.csv. Example Iris features (2 features: sepal length and

petal width).

S6_LogisticRegression_IrisTrainedModel.pkl. Example ClassificaIO trained model

using logistic regression.

S7_IrisTrainValidationResult.csv. Example ClassificaIO testing result using

logistic regression.

S8_IrisTestingResult.csv. Example ClassificaIO validation result using logistic

regression.

ClassificalO System Diagram

HOME   HELP   EXIT PYTHON

ClassificalO

Machine Learning for Classification

Use My Own Training Data

Already Trained My Model

a)

ClassificaIO

HOME   HELP   EXIT PYTHON

UPLOAD TRAINING DATA FILES
- ○ Dependent, target and features
- ● Dependent and target

Dependent
Target

CLASSIFIER SELECTION
I. Linear_model
1: LogisticRegression
2: PassiveAggressiveClassifier
3: Perceptron
4: RidgeClassifier
5: Stochastic Gradient Descent (SGD

UPLOAD TESTING DATA FILE
Testing Data

CURRENT DATA UPLOAD
#Use My Own Training Data Uploade
Dependent Data: S1_Iris_Dependent_
Target Data: S2_Iris_Target.csv
Features Data: Not Uploaded
Test Data: S3_Iris_Testing_DataSet.c

1: LogisticRegression Learn more.

"Logistic regression, despite its name, is a linear model for classification rather than regression. Logistic regression is also known in the literature as logit regression, maximum-entropy classification (MaxEnt) or the log-linear classifier."

Train Sample Size (%): 75   5 50 95

random_state:
○ Integer: 0
● None

multi_class: ovr
penalty: l2
solver: liblinear

intercept_scaling: 1
max_iter: 100
tol: 1.0E-4

verbose: 0
n_jobs: 1
C: 1

fit_intercept:
● True
○ False

dual:
○ True
● False

warm_start:
○ True
● False

K-fold Cross-Validation: 10

Submit

{PARAMETERS: } {random_state = None} {shuffle = True} {penalty = l2} {multi_class = ovr} {solver = liblinear} {max_iter = 100} {tol = 0.0001} {intercept_scaling = 1.0} {verbose = 0} {n_jobs = 1} {C = 1.0} {fit_intercept = True} {dual = False} {warm_start = False} {class_weight = None}

CONFUSION MATRIX, MODEL ACCURACY & ERROR
```
        Predicted Class
True  | 0    1    2
Class -------------------
0     | 7    0    0
1     | 0    10   1
2     | 0    0    9
```
Classification Accuracy: 96.3 %
Classification Error (MR):   3.7 %

Export Model

TRAINING RESULT: ID — ACTUAL — PREDICTION
Total objects predicted: 27
50 — 0 — 0
102 — 2 — 2
137 — 2 — 2
37 — 0 — 0
20 — 0 — 0
83 — 1 — 1
119 — 2 — 2
58 — 1 — 1
108 — 2 — 2

Export Training

TESTING RESULT: ID — PREDICTION
Total objects tested: 45
— 0
— 0
— 0
— 0
— 0
— 0
— 0
— 0
— 0

Export Testing

---

b)

ClassificaIO

HOME   HELP   EXIT PYTHON

UPLOAD TRAINING MODEL FILE
Model File

UPLOAD TESTING DATA FILE
Testing Data

CURRENT DATA UPLOAD

#Already Trained My Model Uploade
Model: S5_LogisticRegression_IrisTra
Test Data: S3_Iris_Testing_DataSet.c

#Upload History

Submit

CLASSIFIER: ('PARAMETERS: ', 'random_state = None', 'shuffle = True', 'penalty = l2', 'multi_class = ovr', 'solver = liblinear', 'max_iter= 100', 'tol = 0.0001', 'intercept_scaling = 1.0', 'verbose = 0', 'n_jobs = 1', 'C = 1.0', 'fit_intercept = True', 'dual = False', 'warm_start = False', 'class_weight = None')

CONFUSION MATRIX, MODEL ACCURACY & ERROR
```
        Predicted Class
True  | 0    1    2
Class -------------------
0     | 7    0    0
1     | 0    10   1
2     | 0    0    9
```
Classification Accuracy: 96.3 %
Classification Error (MR):   3.7 %

TESTING RESULT: ID — PREDICTION
Total objects tested: 45
— 0
— 0
— 0
— 0
— 0
— 0
— 0
— 0
— 0

Export Testing