Large-scale, high-resolution comparison of the core visual object recognition behavior of humans, monkeys, and state-of-the-art deep artificial neural networks

Abbreviated title: Comparing object recognition between primates and models

Rishi Rajalingham*, Elias B. Issa*, Pouya Bashivan, Kohitij Kar, Kailyn Schmidt, and James J. DiCarlo

McGovern Institute for Brain Research and Department of Brain and Cognitive Sciences
Massachusetts Institute of Technology, Cambridge, Massachusetts 02139

*R.R. and E.B.I. contributed equally to this work.

Correspondence should be addressed to James J. DiCarlo, McGovern Institute for Brain Research, Department of Brain and Cognitive Sciences, Massachusetts Institute of Technology, 77 Massachusetts Institute of Technology, 46-6161, Cambridge, MA 02139. E-mail: dicarlo@mit.edu

E. Issa's present address: Department of Neuroscience, Zuckerman Mind Brain Behavior Institute, Columbia University, New York, NY 10027

____

Targeting *Journal of Neuroscience*
Title 19 words
Abbreviated Title 50 characters
Abstract 242 words
Significance Statement 97 words
Introduction 649 words
Discussion 1188 words
Figures 6
*All word limits include citations
____

AUTHOR CONTRIBUTIONS
E.B.I., R.R., and J.J.D designed the experiments. E.B.I., K.S., R.R., and K.K. carried out the experiments. R.R., E.B.I., and P.B. performed the data analysis and modeling. R.R., E.B.I., and J.J.D. wrote the manuscript.

ACKNOWLEDGEMENTS
This research was supported by US National Eye Institute grants R01-EY014970 (J.J.D.) and K99-EY022671 (E.B.I.), Office of Naval Research MURI-114407 (J.J.D), IARPA Contract D16PC00002 (J.J.D), Engineering Research Council of Canada (R.R.), and The McGovern Institute for Brain Research

COMPETING FINANCIAL INTERESTS
The authors declare no competing financial interests.

ABSTRACT

Primates—including humans—can typically recognize objects in visual images at a glance even in the face of naturally occurring identity-preserving image transformations (e.g. changes in viewpoint). A primary neuroscience goal is to uncover neuron-level mechanistic models that quantitatively explain this behavior by predicting primate performance for each and every image. Here, we applied this stringent behavioral prediction test to the leading mechanistic models of primate vision (specifically, deep, convolutional, artificial neural networks; ANNs) by directly comparing their behavioral signatures against those of humans and rhesus macaque monkeys. Using high-throughput data collection systems for human and monkey psychophysics, we collected over one million behavioral trials for 2400 images over 276 binary object discrimination tasks. Consistent with previous work, we observed that state-of-the-art deep, feed-forward convolutional ANNs trained for visual categorization (termed $DCNN_{IC}$ models) accurately predicted primate patterns of object-level confusion. However, when we examined behavioral performance for individual images within each object discrimination task, we found that all tested $DCNN_{IC}$ models were significantly non-predictive of primate performance, and that this prediction failure was not accounted for by simple image attributes, nor rescued by simple model modifications. These results show that current $DCNN_{IC}$ models cannot account for the image-level behavioral patterns of primates, and that new ANN models are needed to more precisely capture the neural mechanisms underlying primate object vision. To this end, large-scale, high-resolution primate behavioral benchmarks—such as those obtained here—could serve as direct guides for discovering such models.

SIGNIFICANCE STATEMENT

Recently, specific feed-forward deep convolutional artificial neural networks (ANNs) models have dramatically advanced our quantitative understanding of the neural mechanisms underlying primate core object recognition. In this work, we tested the limits of those ANNs by systematically comparing the behavioral responses of these models with the behavioral responses of humans and monkeys, at the resolution of individual images. Using these high-resolution metrics, we found that all tested ANN models significantly diverged from primate behavior. Going forward, these high-resolution, large-scale primate behavioral benchmarks could serve as direct guides for discovering better ANN models of the primate visual system.

INTRODUCTION

Primates—both human and non-human—can typically recognize objects in visual images at a glance, even in the face of naturally occurring identity-preserving transformations such as changes in viewpoint. This view-invariant visual object recognition ability is thought to be supported primarily by the primate ventral visual stream (DiCarlo et al., 2012). A primary neuroscience goal is to construct computational models that quantitatively explain the neural mechanisms underlying this ability. That is, our goal is to discover artificial neural networks (ANNs) that accurately predict neuronal firing rate responses at all levels of the ventral stream and its behavioral output. To this end, specific models within a large family of deep, convolutional neural networks (DCNNs), optimized by supervised training on large-scale category-labeled image-sets (ImageNet) to match human-level categorization performance (Krizhevsky et al., 2012; LeCun et al., 2015), have been put forth as the leading ANN models of the ventral stream (Yamins and DiCarlo, 2016). We refer to this sub-family as $DCNN_{IC}$ models (IC to denote ImageNet-categorization pre-training), so as to distinguish them from all possible models in the DCNN family, and more broadly, from the super-family of all ANNs. To date, it has been shown that $DCNN_{IC}$ models display internal feature representations similar to neuronal representations along the primate ventral visual stream (Yamins et al., 2013; Cadieu et al., 2014; Khaligh-Razavi and Kriegeskorte, 2014; Yamins et al., 2014), and they exhibit behavioral patterns similar to the behavioral patterns of pairwise object confusions of primates (Rajalingham et al., 2015). Thus, $DCNN_{IC}$ models may provide a quantitative account of the neural mechanisms underlying primate core object recognition behavior.

However, several studies have shown that $DCNN_{IC}$ models can diverge drastically from humans in object recognition behavior, especially with regards to particular images optimized to be adversarial to these networks (Goodfellow et al., 2014; Nguyen et al., 2015). Related work has shown that specific image distortions are disproportionately challenging to current DCNNs, as compared to humans (RichardWebster et al., 2016; Dodge and Karam, 2017; Geirhos et al., 2017; Hosseini et al., 2017). Such image-specific failures of the current ANN models would likely not be captured by "object-level" behavioral metrics (e.g. the pattern of pairwise object confusions mentioned above) that are computed by pooling over hundreds of images and thus are

not sensitive to variation in difficulty across images of the same object. To overcome this

limitation of prior work, we here aimed to use scalable behavioral testing methods to precisely

characterize primate behavior at the resolution of individual images and to directly compare

leading DCNN models to primates over the domain of core object recognition behavior at this

high resolution.

We focused on *core invariant object recognition*—the ability to identify objects in visual

images in the central visual field during a single, natural viewing fixation (DiCarlo et al., 2012).

We further restricted our behavioral domain to *basic-level* object discriminations, as defined

previously (Rosch et al., 1976). Within this domain, we collected large-scale, high-resolution

measurements of human and monkey behavior (over a million behavioral trials) using high-

throughput psychophysical techniques—including a novel home-cage behavioral system for

monkeys. These data enabled us to systematically compare all systems at progressively higher

resolution. At lower resolutions, we replicated previous findings that humans, monkeys, and

$DCNN_{IC}$ models all share a common pattern of object-level confusion (Rajalingham et al., 2015).

However, at the higher resolution of individual images, we found that the behavior of all tested

$DCNN_{IC}$ models was significantly different from human and monkey behavior, and this model

prediction failure could not be easily rescued by simple model modifications. These results show

that current $DCNN_{IC}$ models do not fully account for the image-level behavioral patterns of

primates, suggesting that new ANN models are needed to more precisely capture the neural

mechanisms underlying primate object vision. To this end, large-scale high-resolution behavioral

benchmarks, such as those obtained here, could serve as a strong top-down constraint for

efficiently discovering such models.

MATERIALS & METHODS

Visual images

We examined basic-level, core object recognition behavior using a set of 24 broadly-

sampled objects that we previously found to be reliably labeled by independent human subjects,

based on the definition of basic-level proposed by (Rosch et al., 1976). For each object, we

generated 100 naturalistic synthetic images by first rendering a 3D model of the object with

randomly chosen viewing parameters (2D position, 3D rotation and viewing distance), and then

placing that foreground object view onto a randomly chosen, natural image background. To do

this, each object was first assigned a canonical position (center of gaze), scale (~2 degrees) and

pose, and then its viewing parameters were randomly sampled uniformly from the following

ranges for object translation ([-3,3] degrees in both h and v), rotation ([-180,180] degrees in all

three axes) and scale ([x0.7, x1.7]. Background images were sampled randomly from a large

database of high-dynamic range images of indoor and outdoor scenes obtained from Dosch

Design (www.doschdesign.com). This image generation procedure enforces invariant object

recognition, rather than image matching, as it requires the visual recognition system (human,

animal or model) to tackle the "invariance problem," the computational crux of object

recognition (Ullman and Humphreys, 1996; Pinto et al., 2008). Using this procedure, we

previously generated 2400 images (100 images per object) rendered at 1024x1024 pixel

resolution with 256-level gray scale and subsequently resized to 256x256 pixel resolution for

human psychophysics, monkey psychophysics and model evaluation (Rajalingham et al., 2015).

In the current work, we focused our analyses on a randomly subsampled, and then fixed, sub-set

of 240 images (10 images per object; here referred to as the "primary test images"). Figure 1A

shows the full list of 24 objects, with two example images of each object.

Because all of the images were generated from synthetic 3D object models, we had

explicit knowledge of the viewpoint parameters (position, size, and pose) for each object in each

image, as well as perfect segmentation masks. Taking advantage of this feature, we characterized

each image based on these high-level attributes, consisting of size, eccentricity, relative pose and

contrast of the object in the image. The size and eccentricity of the object in each image were

computed directly from the corresponding viewpoint parameters, under the assumption that the

entire image would subtend 6° at the center of visual gaze (+/-3° in both azimuth and elevation;

see below). For each synthetic object, we first defined its "canonical" 3D pose vector, based on

independent human judgments. To compute the relative pose attribute of each image, we

estimated the difference between the object's 3D pose and its canonical 3D pose. Pose

differences were computed as distances in unit quaternion representations: the 3D pose (r_{xy}, r_{xz},

r_{yz}) was first converted into unit quaternions, and distances between quaternions q_1, q_2 were

estimated as $\cos^{-1}|q_1 \cdot q_2|$ (Huynh, 2009). To compute the object contrast, we measured the

absolute difference between the mean of the pixel intensities corresponding to the object and the

mean of the background pixel intensities in the vicinity of the object (specifically, within 25

pixels of any object pixel, analogous to computing the local foreground-background luminance

difference of a foreground object in an image). Figure 5C shows example images with varying

values for the four image attributes.

Core object recognition behavioral paradigm

Core object discrimination is defined as the ability to discriminate between two or more

objects in visual images presented under high view uncertainty in the central visual field (~10°),

for durations that approximate the typical primate, free-viewing fixation duration (~200 ms)

(DiCarlo and Cox, 2007; DiCarlo et al., 2012). As in our previous work (Rajalingham et al.,

2015), the behavioral task paradigm consisted of a interleaved set of binary discrimination tasks.

Each binary discrimination task is an object discrimination task between a pair of objects (e.g.

elephant vs. bear). Each such binary task is balanced in that the test image is equally likely

(50%) to be of either of the two objects. On each trial, a test image is presented, followed by a

choice screen showing canonical views of the two possible objects (the object that was not

displayed in the test image is referred to as the "distractor" object, but note that objects are

equally likely to be distractors and targets). Here, 24 objects were tested, which resulted in 276

binary object discrimination tasks. To neutralize feature attention, these 276 tasks are randomly

interleaved (trial by trial), and the global task is referred to as a basic-level, core object

recognition task paradigm.

Testing human behavior

All human behavioral data presented here were collected from 1476 human subjects on

Amazon Mechanical Turk (MTurk) performing the task paradigm described above. Subjects

were instructed to report the identity of the foreground object in each presented image from

among the two objects presented on the choice screen (Fig 1B). Because all 276 tasks were

interleaved randomly (trial-by-trial), subjects could not deploy feature attentional strategies

specific to each object or specific to each binary task to process each test image.

Figure 1B illustrates the time course of each behavioral trial, for a particular object
discrimination task (zebra versus dog). Each trial initiated with a central black point for 500 ms,
followed by 100 ms presentation of a test image containing one foreground object presented
under high variation in viewing parameters and overlaid on a random background, as described
above (see *Visual images* above). Immediately after extinction of the test image, two choice
images, each displaying a single object in a canonical view with no background, were shown to
the left and right. One of these two objects was always the same as the object that generated the
test image (i.e., the correct object choice), and the location of the correct object (left or right) was
randomly chosen on each trial. After clicking on one of the choice images, the subject was
queued with another fixation point before the next test image appeared. No feedback was given;
human subjects were never explicitly trained on the tasks. Under assumptions of typical
computer ergonomics, we estimate that images were presented at 6–8° of visual angle at the
center of gaze, and the choice object images were presented at ±6–8° of eccentricity along the
horizontal meridian.
220
We measured human behavior using the online Amazon MTurk platform (see Figure 1C),
which enables efficient collection of large-scale psychophysical data from crowd-sourced
"human intelligence tasks" (HITs). The reliability of the online MTurk platform has been
validated by comparing results obtained from online and in-lab psychophysical experiments
(Majaj et al., 2015; Rajalingham et al., 2015). We pooled 927,296 trials from 1472 human
subjects to characterize the aggregate human behavior, which we refer to as the "pooled" human
(or "archetypal" human). Each human subject performed only a small number of trials (~150) on
a subset of the images and binary tasks. All 2400 images were used for behavioral testing, but in
some of the HITs, we biased the image selection towards the 240 primary test images (1424±70
trials/image on this subsampled set, versus 271±93 trials/image on the remaining images, mean ±
SD) to efficiently characterize behavior at image level resolution. Images were randomly drawn
such that each human subject was exposed to each image a relatively small number of times
(1.5±2.0 trials/image per subject, mean ± SD), in order to mitigate potential alternative
behavioral strategies (e.g. "memorization" of images) that could arise from a finite image set.
Behavioral signatures at the object-level (B.O1, B.O2, see *Behavioral metrics and signatures*)
were measured using all 2400 test images, while image-level behavioral signatures (B.I1n, B.I2n,

see *Behavioral metrics and signatures*) were measured using the 240 primary test images. (We

observed qualitatively similar results using those metrics on the full 2400 test images, but we

here focus on the primary test images as the larger number of trials leads to lower noise levels).

Five other human subjects were separately recruited on MTurk to each perform a large

number of trials on the same images and tasks (53,097±15,278 trials/subject, mean ± SD).

Behavioral data from these five subjects was not included in the characterization of the pooled

human described above, but instead aggregated together to characterize a distinct held-out

human pool. For the scope of the current work, this held-out human pool—which largely

replicated all behavioral signatures of the larger archetypal human (see Figures 2 and 3)—served

as an independent validation of our human behavioral measurements.

Testing monkey behavior

Five adult male rhesus macaque monkeys (*Macaca mulatta, subjects M, Z, N, P, B*) were

tested on the same basic-level, core object recognition task paradigm described above, with

minor modification as described below. All procedures were performed in compliance with

National Institutes of Health guidelines and the standards of the Massachusetts Institute of

Technology Committee on Animal Care and the American Physiological Society. To efficiently

characterize monkey behavior, we used a novel home-cage behavioral system developed in our

lab (termed MonkeyTurk, see Fig. 1C). This system leveraged a tablet touchscreen (9" Google

Nexus or 10.5" Samsung Galaxy Tab S) and used a web application to wirelessly load the task

and collect the data (code available at https://github.com/dicarlolab/mkturk). Analogous to the

online Amazon Mechanical Turk, which allows for efficient psychophysical assays of a large

number (hundreds) of human users in their native environments, MonkeyTurk allowed us to test

many monkey subjects simultaneously in their home environment. Each monkey voluntarily

initiated trials, and each readily performed the task a few hours each day that the task apparatus

was made available to it. At an average rate of ~2,000 trials per day per monkey, we collected a

total of 836,117 trials from the five monkey subjects over a period of ~3 months.

Monkey training is described in detail elsewhere (Rajalingham et al., 2015). Briefly, all

monkeys were initially trained on the match-test-image-to-object rule using other images and

were also trained on discriminating the particular set of 24 objects tested here using a separate set
of training images rendered from these objects, in the same manner as the main testing images.
Two of the monkeys subjects (Z and M) were previously trained in the lab setting, and the
remaining three subjects were trained using MonkeyTurk directly in their home cages and did
not have significant prior lab exposure. Once monkeys reached saturation performance on
training images, we began the behavioral testing phase to collect behavior on test images.
Monkeys did improve throughout the testing phase, exhibiting an increase in performance
between the first and second half of trials of 4%±0.9% (mean ± SEM over five monkey subjects).
However, the image-level behavioral signatures obtained from the first and the second halves of
trials were highly correlated to each other (B.I1 noise-adjusted correlation of 0.85±0.06, mean ±
SEM over five monkey subjects, see *Behavioral metrics and signatures* below), suggesting that
monkeys did not significantly alter strategies (e.g. did not "memorize" images) throughout the
behavioral testing phase.

The monkey task paradigm was nearly identical to the human paradigm (see Figure 1B),
with the exception that trials were initiated by touching a white "fixation" circle horizontally
centered on the bottom third of the screen (to avoid occluding centrally-presented test images
with the hand). This triggered a 100ms central presentation of a test image, followed
immediately by the presentation of the two choice images (Fig. 1B, location of correct choice
randomly assigned on each trial, identical to the human task). Unlike the main human task,
monkeys responded by directly touching the screen at the location of one of the two choice
images. Touching the choice image corresponding to the object shown in the test image resulted
in the delivery of a drop of juice through a tube positioned at mouth height (but not obstructing
view), while touching the distractor choice image resulted in a three second timeout. Because
gaze direction typically follows the hand during reaching movements, we assumed that the
monkeys were looking at the screen during touch interactions with the fixation or choice targets.
In both the lab and in the home cage, we maintained total test image size at ~6 degrees of visual
angle at the center of gaze, and we took advantage of the retina-like display qualities of the tablet
by presenting images pixel matched to the display (256 x 256 pixel image displayed using 256 x
256 pixels on the tablet at a distance of 8 inches) to avoid filtering or aliasing effects.

As with Mechanical Turk testing in humans, MonkeyTurk head-free home-cage testing
enables efficient collection of reliable, large-scale psychophysical data but it likely does not yet
achieve the level of experimental control that is possible in the head-fixed laboratory setting.
However, we note that when subjects were engaged in home-cage testing, they reliably had their
mouth on the juice tube and their arm positioned through an armhole. These spatial constraints
led to a high level of head position trial-by-trial reproducibility during performance of the task
paradigm. Furthermore, when subjects were in this position, they could not see other animals as
the behavior box was opaque, and subjects performed the task at a rapid pace 40 trials/minute
suggesting that they were not frequently distracted or interrupted. The location of the upcoming
test image (but not the location of the object within that test image) was perfectly predictable at
the start of each behavioral trial, which likely resulted in a reliable, reproduced gaze direction at
the moment that each test image was presented. The relatively short—but natural and high
performing (Cadieu et al., 2014)—test image duration (100 ms) ensured that saccadic eye
movements were unlike to influence test image performance (as they generally take ~200 ms to
initiate in response to the test image, and thus well after the test image has been extinguished).
314

Testing model behavior

We tested a number of different deep convolutional neural network (DCNN) models on
the exact same images and tasks as those presented to humans and monkeys. Importantly, our
core object recognition task paradigm is closely analogous to the large-scale ImageNet 1000-way
object categorization task for which these networks were optimized and thus expected to perform
well. We focused on publicly available DCNN model architectures that have proven highly
successful with respect to this computer vision benchmark over the past five years: AlexNet
(Krizhevsky et al., 2012), NYU (Zeiler and Fergus, 2014), VGG (Simonyan and Zisserman,
2014), GoogleNet (Szegedy et al., 2013), Resnet (He et al., 2016), and Inception-v3 (Szegedy et
al., 2013). As this is only a subset of possible DCNN models, we refer to these as the $DCNN_{IC}$
(to denote ImageNet-Categorization) visual system model sub-family. For each of the publicly
available model architectures, we first used ImageNet-categorization-trained model instances,
either using publicly available trained model instances or training them to saturation on the 1000-
way classification task in-house. Training took several days on 1-2 GPUs.
329

We then performed psychophysical experiments on each ImageNet-trained DCNN model
to characterize their behavior on the exact same images and tasks as humans and monkeys. We
first adapted these ImageNet-trained models to our 24-way object recognition task by re-training
the final class probability layer (initially corresponding to the probability output of the 1000-way
ImageNet classification task) while holding all other layers fixed. In practice, this was done by
extracting features from the penultimate layer of each $DCNN_{IC}$ (i.e. top-most prior to class
probability layer), on the same images that were presented to humans and monkeys, and training
back-end multi-class logistic regression classifiers to determine the cross-validated output class
probability for each image. This procedure is illustrated in Figure 1C. To estimate the hit rate of
a given image in a given binary classification task, we renormalized the 24-way class
probabilities of that image, considering only the two relevant classes, to sum to one. Object-level
and image-level behavioral metrics were computed based on these hit rate estimates (as
described in *Behavioral metrics and signatures* below). Importantly, this procedure assumes that
the model "retina" layer processes the central 6 degrees of the visual field. It also assumes that
linear discriminants ("readouts") of the model's top feature layer are its behavioral output (as
intended by the model designers). Manipulating either of these choices (e.g. resizing the input
images such that they span only part of the input layer, or building linear discriminates for
behavior using a different model feature layer) would result in completely new, testable ANN
models that we do not test here.

From these analyses, we selected the most *human-consistent* $DCNN_{IC}$ architecture
(Inception-v3, see *Behavioral consistency* below), fixed that architecture, and then performed
post-hoc analyses in which we varied: the input image sampling, the initial parameter settings
prior to training, the filter training images, the type of classifiers used to generate the behavior
from the model features, and the classifier training images. To examine input image sampling,
we re-trained the Inception-v3 architecture on images from ImageNet that were first spatially
filtered to match the spatial sampling of the primate retina (i.e. an approximately exponential
decrease in cone density away from the fovea) by effectively simulating a fish-eye
transformation on each image. These images were at highest resolution at the "fovea" (i.e. center
of the image) with gradual decrease in resolution with increasing eccentricity. To examine the
analog of "inter-subject variability", we constructed multiple trained model instances

("subjects"), where the architecture and training images were held fixed (Inception-v3 and
ImageNet, respectively) but the model filter weights initial condition and order of training
images were randomly varied for each model instance. Importantly, this procedure is only one
possible choice for simulating inter-subject variability for DCNN models, a choice that is an
important open research direction that we do not address here. To examine the effect of model
training, we fine-tuned an ImageNet-trained Inception-v3 model on a synthetic image set
consisting of ~6.9 million images of 1049 objects (holding out 50,000 images for model
validation). These images were generated using the same rendering pipeline as our test images,
but the objects were non-overlapping with the 24 test objects presented here. As expected, fine-
tuning on synthetic images led to an overall increase in performance of ~5%. We tested the effect
of different classifiers to generate model behavior by testing both multi-class logistic regression
and support vector machine classifiers. Additionally, we tested the effect of varying the number
of training images used to train those classifiers (20 versus 50 images per class).

Behavioral metrics and signatures

To characterize the behavior of any visual system, we here introduce four behavioral (B)
metrics of increasing richness, requiring increasing amounts of data to measure reliably. Each
behavioral metric computes a pattern of unbiased behavioral performance, using a sensitivity
index: $d' = Z(HitRate) - Z(FalseAlarmRate)$, where Z is the inverse of the cumulative
Gaussian distribution. The various metrics differ in the resolution at which hit rates and false
alarm rates are computed. Table 1 summarizes the four behavioral metrics, varying the hit-rate
resolution (object-level or image-level) and the false-alarm resolution (one-versus-all or one-
versus-other). When each metric is applied to the behavioral data of a visual system—biological
or artificial—we refer to the result as one behavioral "signature" of that system. Note that we do
not consider the signatures obtained here to be the final say on the behavior of these biological or
artificial systems—in the terms defined here, new experiments using new objects/images but the
same metrics would produce additional behavioral signatures.

The four behavioral metrics we chose are as follows: First, the one-versus-all object-level
performance metric (termed B.O1) estimates the discriminability of each object from all other
objects, pooling across all distractor object choices. Since we here tested 24 objects, the resulting

B.O1 signature has 24 independent values. Second, the one-versus-other object-level
performance metric (termed B.O2) estimates the discriminability of each specific pair of objects,
or the pattern of pairwise object confusions. Since we here tested 276 interleaved binary object
discrimination tasks, the resulting B.O2 signature has 276 independent values (the off-diagonal
elements on one half of the 24x24 symmetric matrix). Third, the one-versus-all image-level
performance metric (termed B.I1) estimates the discriminability of each image from all other
objects, pooling across all possible distractor choices. Since we here focused on the primary
image test set of 240 images (10 per object, see above), the resulting B.I1 signature has 240
independent values. Fourth, the one-versus-other image-level performance metric (termed B.I2)
estimates the discriminability of each image from each distractor object. Since we here focused
on the primary image test set of 240 images (10 per object, see above) with 23 distractors, the
resulting B.I2 signature has 5520 independent values.

Naturally, object-level and image-level behavioral signatures are tightly linked. For
example, images of a particularly difficult-to-discriminate object would inherit lower
performance values on average as compared to images from a less difficult-to-discriminate
object. To isolate the behavioral variance that is specifically driven by image variation and not
simply predicted by the objects (and thus already captured by B.O1 and B.O2), we defined
normalized image-level behavioral metrics (termed B.I1n, B.I2n) by subtracting the mean
performance values over all images of the same object and task. This process is schematically
illustrated in Figure 3A. We note that the resulting normalized image-level behavioral signatures
capture a significant proportion of the total image-level behavioral variance in our data (e.g.
52%, 58% of human B.I1 and B.I2 variance is driven by image variation, independent of object
identity). In this study, we use these normalized metrics for image-level behavioral comparisons
between models and primates (see Results).

Behavioral Consistency

To quantify the similarity between a model visual system and the human visual system
with respect to a given behavioral metric, we used a measure called the "*human-consistency*" as
previously defined (Johnson et al., 2002). *Human-consistency* ($\tilde{\rho}$) is computed, for each of the
four behavioral metrics, as a noise-adjusted correlation of behavioral signatures (DiCarlo and

Johnson, 1999). For each visual system, we randomly split all behavioral trials into two equal

halves and applied each behavioral metric to each half, resulting in two independent estimates of

the system's behavioral signature with respect to that metric. We took the Pearson correlation

between these two estimates of the behavioral signature as a measure of the reliability of that

behavioral signature given the amount of data collected, i.e. the split-half internal reliability. To

estimate the *human-consistency*, we computed the Pearson correlation over all the independent

estimates of the behavioral signature from the model (**m**) and the human (**h**), and we then divide

that raw Pearson correlation by the geometric mean of the split-half internal reliability of the

same behavioral signature measured for each system: $\tilde{\rho}(\boldsymbol{m}, \boldsymbol{h}) = \frac{\rho(\boldsymbol{m},\boldsymbol{h})}{\sqrt{\rho(\boldsymbol{m},\boldsymbol{m})\rho(\boldsymbol{h},\boldsymbol{h})}}$.

Since all correlations in the numerator and denominator were computed using the same

amount of trial data (exactly half of the trial data), we did not need to make use of any prediction

formulas (e.g. extrapolation to larger number of trials using Spearman-Brown prediction

formula). This procedure was repeated 10 times with different random split-halves of trials. Our

rationale for using a reliability-adjusted correlation measure for *human-consistency* was to

account for variance in the behavioral signatures that arises from "noise," i.e., variability that is

not replicable by the experimental condition (image and task) and thus that no model can be

expected to predict (DiCarlo and Johnson, 1999; Johnson et al., 2002). In sum, if the model (m)

is a replica of the archetypal human (h), then its expected human-consistency is 1.0, regardless of

the finite amount of data that are collected.

Characterization of Residuals

In addition to measuring the similarity between the behavioral signatures of primates and

models (using *human-consistency* analyses, as described above), we examined the corresponding

differences, termed "residual signatures." Each candidate visual system model's residual

signature was estimated as the residual of a linear least squares regression of the model's

signature on the corresponding human signature and a free intercept parameter. This procedure

effectively captures the differences between human and model signatures after accounting for

overall performance differences. Residual signatures were estimated on disjoint split-halves of

trials, repeating 10 times with random trial permutations. Residuals were computed with respect

to the normalized one-versus-all image-level performance metric (B.I1n) as this metric showed a

clear difference between DCNN$_{IC}$ models and primates, and the behavioral residual can be

interpreted based only the test images (i.e. we can assign a residual per image).

To examine the extent to which the difference between each model and the archetypal

human is reliably shared across different models, we measured the Pearson correlation between

the residual signatures of pairs of models. Residual similarity was quantified as the proportion of

shared variance, defined as the square of the noise-adjusted correlation between residual

signatures (the noise-adjustment was done as defined in equation above). Correlations of residual

signatures were always computed across distinct split-halves of data, to avoid introducing

spurious correlations from subtracting common noise in the human data. We measured the

residual similarity between all pairs of tested models, holding both architecture and optimization

procedure fixed (between instances of the ImageNet-categorization trained Inception-v3 model,

varying in filter initial conditions), varying the architecture while holding the optimization

procedure fixed (between all tested ImageNet-categorization trained DCNN architectures), and

holding the architecture fixed while varying the optimization procedure (between ImageNet-

categorization trained Inception-v3 and synthetic-categorization fine-tuned Inception-v3

models). This analysis addresses not only the reliability of the failure of DCNN$_{IC}$ models to

predict human behavior (deviations from humans), but also the relative importance of the

characteristics defining similarities within the model sub-family (namely, the architecture and the

optimization procedure). We first performed this analysis for residual signatures over the 240

primary test images, and subsequently zoomed in on subsets of images that humans found to be

particularly difficult. This image selection was made relative to the distribution of image-level

performance of held-out human subjects (B.I1 metric from five subjects); difficult images were

defined as ones with performance below the 25th percentile of this distribution.

To examine whether the difference between each model and humans can be explained by

simple human-interpretable stimulus attributes, we regressed each DCNN$_{IC}$ model's residual

signature on image attributes (object size, eccentricity, pose, and contrast). Briefly, we

constructed a design matrix from the image attributes (using individual attributes, or all

attributes), and used multiple linear least squares regression to predict the image-level residual

signature. The multiple linear regression was tested using two-fold cross-validation over trials.

The relative importance of each attribute (or groups of attributes) was quantified using the

proportion of explainable variance (i.e. variance remaining after accounting for noise variance)

explained from the residual signature.

Primate behavior zone

In this work, we are primarily concerned with the behavior of an "archetypal human",

rather than the behavior of any given individual human subject. We operationally defined this

concept as the common behavior over many humans, obtained by pooling together trials from a

large number of individual human subjects and treating this human pool as if it were acquired

from a single behaving agent. Due to inter-subject variability, we do not expect any given human

or monkey subject to be perfectly consistent with this archetypal human (i.e. we do not expect it

to have a *human-consistency* of 1.0). Given current limitations of monkey psychophysics, we are

not yet able to measure the behavior of very large number of monkey subjects at high resolution

and consequently cannot directly estimate the *human-consistency* of the corresponding

"archetypal monkey" to the human pool. Rather, we indirectly estimated this value by first

measuring *human-consistency* as a function of number of individual monkey subjects pooled

together (n), and extrapolating the *human-consistency* estimate for pools of very large number of

subjects (as n approaches infinity). Extrapolations were done using least squares fitting of an

exponential function $\tilde{\rho}(n) = a + b \cdot e^{-cn}$ (see Figure 4).

For each behavioral metric, we defined a "primate zone" as the range of *human-*

consistency values delimited by estimates $\tilde{\rho}_{M\infty}$ and $\tilde{\rho}_{H\infty}$ as lower and upper bounds respectively.

$\tilde{\rho}_{M\infty}$ corresponds to the extrapolated estimate of *human-consistency* of a large (i.e. infinitely

many) pool of rhesus macaque monkeys; $\tilde{\rho}_{H\infty}$ is by definition equal to 1.0. Thus, the primate

zone defines a range of *human-consistency* values that correspond to models that accurately

capture the behavior of the human pool, at least as well as an extrapolation of our monkey

sample. In this work, we defined this range of *human-consistency* values as the criterion for

success for computational models of primate visual object recognition behavior.

To make a global statistical inference about whether models sampled from the DCNN$_{IC}$

sub-family meet or fall short of this criterion for success, we attempted to reject the hypothesis

that, for a given behavioral metric, the *human-consistency* of DCNN$_{IC}$ models is within the primate zone. To test this hypothesis, we estimated the empirical probability that the distribution of *human-consistency* values, estimated over different model instances within this family, could produce *human-consistency* values within the primate zone. Specifically, we estimated a p-value for each behavioral metric using the following procedure: We first estimated an empirical distribution of Fisher-transformed *human-consistency* values for this model family (i.e. over all tested DCNN$_{IC}$ models and over all trial-resampling of each DCNN$_{IC}$ model). From this empirical distribution, we fit a Gaussian kernel density function, optimizing the bandwidth parameter to minimize the mean squared error to the empirical distribution. This kernel density function was evaluated to compute a p-value, by computing the cumulative probability of observing a *human-consistency* value greater than or equal to the criterion of success (i.e. the Fisher transformed $\tilde{\rho}_{M\infty}$ value). This p-value indicates the probability that *human-consistency* values sampled from the observed distribution would fall into the primate zone, with smaller p-values indicating stronger evidence against the hypothesis that the *human-consistency* of DCNN models is within the primate zone.

RESULTS

In the present work, we systematically compared the basic level core object recognition behavior of primates and state-of-the-art artificial neural network models using a series of behavioral metrics ranging from low to high resolution within a two-alternative forced choice match-to-sample paradigm. The behavior of each visual system, whether biological or artificial, was tested on the same 2400 images (24 objects, 100 images/object) in the same 276 interleaved binary object recognition tasks. Each system's behavior was characterized at multiple resolutions (see *Behavioral metrics and signatures* in Methods) and directly compared to the corresponding behavioral metric applied on the archetypal human (defined as the average behavior of a large pool of human subjects tested; see Methods). The overarching logic of this study was that, if two visual systems are equivalent, they should produce statistically indistinguishable behavioral signatures with respect to these metrics. Specifically, our goal was to compare the behavioral signatures of visual system models with the corresponding behavioral signatures of primates.

Object-level behavioral comparison

We first examined the pattern of one-versus-all object-level behavior (termed "B.O1

metric") computed across all images and possible distractors. Since we tested 24 objects here, the

B.O1 signature was 24 dimensional. Figure 2A shows the B.O1 signatures for the pooled human

(pooling n=1472 human subjects), pooled monkey (pooling n=5 monkey subjects), and several

$DCNN_{IC}$ models as 24-dimensional vectors using a color scale. Each element of the vector

corresponds to the system's discriminability of one object against all others that were tested (i.e.

all other 23 objects). The color scales span each signature's full performance range, and warm

colors indicate lower discriminability. For example, red indicates that the tested visual system

found the object corresponding to that element of the vector to be very challenging to

discriminate from other objects (on average over all 23 discrimination tests, and on average over

all images). Figure 2B directly compares the B.O1 signatures computed from the behavioral

output of two visual system models—a pixel model (top panel) and a $DCNN_{IC}$ model (Inception-

v3, bottom panel)—against that of the human B.O1 signature. We observe a tighter

correspondence to the human behavioral signature for the $DCNN_{IC}$ model visual system than for

the baseline pixel model visual system. We quantified that similarity using a noise-adjusted

correlation between each pair of B.O1 signatures (termed *human-consistency,* following

(Johnson et al., 2002)); the noise adjustment means that a visual system that is identical to the

human pool will have an expected *human-consistency* score of 1.0, even if it has irreducible trial-

by-trial stochasticity; see Methods). Figure 2C shows the B.O1 *human-consistency* for each of

the tested model visual systems. We additionally tested the behavior of a held-out pool of five

human subjects (black dot) and a pool of five macaque monkey subjects (gray dot), and we

observed that both yielded B.O1 signatures that were highly human-consistent (*human-*

consistency $\tilde{\rho} = 0.90, 0.97$ for monkey pool and held-out human pool, respectively). We defined

a range of *human-consistency* values, termed the "primate zone" (shaded gray area), delimited by

extrapolated *human-consistency* estimates of large pools of macaques (see Methods, Figure 4).

We found that the baseline pixel visual system model and the low-level V1 visual system model

were not within this zone ($\tilde{\rho} = 0.40, 0.67$ for pixels and V1 models, respectively), while all tested

$DCNN_{IC}$ visual system models were either within or very close to this zone. Indeed, we could not

reject the hypothesis that $DCNN_{IC}$ models are primate-like (p = 0.54, exact test, see Methods).

Next, we compared the behavior of the visual systems at a slightly higher level of
resolution. Specifically, instead of pooling over all discrimination tasks for each object, we
computed the mean discriminability of each of the 276 pairwise discrimination tasks (still
pooling over images within each of those tasks). This yielded a symmetric matrix that is referred
to here as the B.O2 signature. Figure 2D shows the B.O2 signatures of the pooled human, pooled
monkey, and several DCNN$_{IC}$ visual system models as 24x24 symmetric matrices. Each bin (i,j)
corresponds to the system's discriminability of objects i and j, where warmer colors indicate
lower performance; color scales are not shown but span each signature's full range. We observed
strong qualitative similarities between the pairwise object confusion patterns of all of the high
level visual systems (e.g. camel and dog are often confused with each other by all three systems).
This similarity is quantified in Figure 2E, which shows the *human-consistency* of all examined
visual system models with respect to this metric. Similar to the B.O1 metric, we observed that
both a pool of macaque monkeys and a held-out pool of humans are highly *human-consistent*
with respect to this metric ($\tilde{\rho} = 0.77$, 0.94 for monkeys, humans respectively). Also similar to the
B.O1 metric, we found that all DCNN$_{IC}$ visual system models are highly *human-consistent* ($\tilde{\rho} >$
0.8) while the baseline pixel visual system model and the low-level V1 visual system model were
not ($\tilde{\rho} = 0.41$, 0.57 for pixels, V1 models respectively). Indeed, all DCNN$_{IC}$ visual system
models are within the defined "primate zone" of *human-consistency*, and we could not falsify the
hypothesis that DCNN$_{IC}$ models are primate-like (p = 0.99, exact test).

Taken together, humans, monkeys, and current DCNN$_{IC}$ models all share similar patterns
of object-level behavioral performances (B.O1 and B.O2 signatures) that are not shared with
lower-level visual representations (pixels and V1). However, object-level performance patterns
do not capture the fact that some images of an object are more challenging than other images of
the same object because of interactions of the variation in the object's pose and position with the
object's class. To overcome this limitation, we next examined the patterns of behavior at the
resolution of individual images on a subsampled set of images where we specifically obtained a
large number of behavioral trials to accurately estimate behavioral performance on each image.
Note that, from the point of view of the subjects, the behavioral tasks are identical to those
already described. We simply aimed to measure and compare their patterns of performance at
much higher resolution.

Image-level behavioral comparison

To isolate purely image-level behavioral variance, i.e. variance that is not predicted by

the object and thus already captured by the B.O1 signature, we computed the normalized image-

level signature. This normalization procedure is schematically illustrated in Figure 3A which

shows that the one-versus-all image-level signature (240-dimensional, 10 images/object) is used

to obtain the normalized one-versus-all image-level signature (termed B.I1n, see *Behavioral*

metrics and signatures). Figure 3B shows the B.I1n signatures for the pooled human, pooled

monkey, and several DCNN$_{IC}$ models as 240 dimensional vectors. Each bin's color corresponds

to the discriminability of a single image against all distractor options (after subtraction of object-

level discriminability, see Figure 3A), where warmer colors indicate lower values; color scales

are not shown but span each signature's full range. Figure 3D shows the *human-consistency* with

respect to the B.I1n signature for all tested models. Unlike with object-level behavioral metrics,

we now observe a divergence between DCNN$_{IC}$ models and primates. Both the monkey pool and

the held-out human pool remain highly *human-consistent* ($\tilde{\rho}$ = 0.77, 0.96 for monkeys, humans

respectively), but all DCNN$_{IC}$ models were significantly less *human-consistent* (Inception-

v3: $\tilde{\rho}$ = 0.62) and well outside of the defined "primate zone" of B.I1n *human-consistency*.

Indeed, the hypothesis that the *human-consistency* of DCNN$_{IC}$ models is within the primate zone

is strongly rejected (p = 6.16e-8, exact test, see Methods).

We can zoom in further by examining not only the overall performance for a given image

but also the object confusions for each image, i.e. the additional behavioral variation that is due

not only to the test image but to the interaction of that test image with the alternative (incorrect)

object choice that is provided after the test image (see Fig. 1B). This is the highest level of

behavioral accuracy resolution that our task design allows. In raw form, it corresponds to one-

versus-other image-level confusion matrix, where the size of that matrix is the total number of

images by the total number of objects (here, 240x24). Each bin (i,j) corresponds to the behavioral

discriminability of a single image i against distractor object j. Again, we isolate variance that is

not predicted by object-level performance by subtracting the average performance on this binary

task (mean over all images) to convert the raw matrix B.I2 above into the normalized matrix,

referred to as B.I2n. Figure 3D shows the B.I2n signatures as 240x24 matrices for the pooled

human, pooled monkey and top DCNN$_{IC}$ visual system models. Color scales are not shown but

span each signature's full range; warmer colors correspond to images with lower performance in

a given binary task, relative to all images of that object in the same task. Figure 3E shows the

human-consistency with respect to the B.I2n metric for all tested visual system models.

Extending our observations using B.I1n, we observe a similar divergence between primates and

DCNN$_{IC}$ visual system models on the matrix pattern of image-by-distractor difficulties (B.I2n).

Specifically, both the monkey pool and held-out human pool remain highly *human-consistent*

($\tilde{\rho}$ = 0.75, 0.77 for monkeys, humans respectively), while all tested DCNN$_{IC}$ models are

significantly less *human-consistent* (Inception-v3: $\tilde{\rho}$ = 0.53) falling well outside of the defined

"primate zone" of B.I2n *human-consistency* values. Once again, the hypothesis that the *human-*

consistency of DCNN$_{IC}$ models is within the primate zone is strongly rejected (p = 3.17e-18,

exact test, see Methods).

Natural subject-to-subject variation

For each behavioral metric (B.O1, BO2, B.I1n, BI2n), we defined a "primate zone" as the

range of consistency values delimited by *human-consistency* estimates $\tilde{\rho}_{M\infty}$ and $\tilde{\rho}_{H\infty}$ as lower

and upper bounds respectively. $\tilde{\rho}_{M\infty}$ corresponds to the extrapolated estimate of the *human-*

consistency of a large (i.e. infinitely many subjects) pool of rhesus macaque monkeys. Thus, the

fact that a particular tested visual system model falls outside of the primate zone can be

interpreted as a failure of that visual system model to accurately predict the behavior of the

archetypal human at least as well as the archetypal monkey.

However, from the above analyses, it is not yet clear whether a visual system model that

fails to predict the archetypal human might nonetheless accurately correspond to one or more

individual human subjects found within the natural variation of the human population. Given the

difficulty of measuring individual subject behavior at the resolution of single images for large

numbers of human and monkey subjects, we could not yet directly test this hypothesis. Instead,

we examined it indirectly by asking whether an archetypal model—that is a pool that includes an

increasing number of model "subjects"—would approach the human pool. We simulated model

inter-subject variability by retraining a fixed DCNN architecture with a fixed training image set

with random variation in the initial conditions and order of training images. This procedure

results in models that can still perform the task but with slightly different learned weight values.

We note that this procedure is only one possible choice of generating inter-subject variability

within each visual system model type, a choice that is an important open research direction that

we do not address here. From this procedure, we constructed multiple trained model instances

("subjects") for a fixed DCNN architecture, and asked whether an increasingly large pool of

model "subjects" better captures the behavior of the human pool, at least as well as a monkey

pool. This post-hoc analysis was conducted for the most *human-consistent* DCNN architecture

(Inception-v3).

Figure 4A shows, for each of the four behavioral metrics, the measured *human-*

consistency of subject pools of varying size (number of subjects *n*) of rhesus macaque monkeys

(black) and ImageNet-trained Inception-v3 models (blue). The *human-consistency* increases with

growing number of subjects for both visual systems across all behavioral metrics. To estimate

the expected *human-consistency* for a pool of infinitely many monkey or model subjects, we fit

an exponential function mapping *n* to the mean *human-consistency* values and obtained a

parameter estimate for the asymptotic value (see Methods). We note that estimated asymptotic

values are not significantly beyond the range of the measured data—the *human-consistency* of a

pool of five monkey subjects reaches within 97% of the *human-consistency* of an estimated

infinite pool of monkeys for all metrics—giving credence to the extrapolated *human-consistency*

values. This analysis suggests that under this model of inter-subject variability, a pool of

Inception-v3 subjects accurately capture archetypal human behavior at the resolution of objects

(B.O1, B.O2) by our primate zone criterion (see Figure 4A, first two panels). In contrast, even a

large pool of Inception-v3 subjects still fails at its final asymptote to accurately capture human

behavior at the image-level (B.I1n, B.I2n) (Figure 4A, last two panels).

Modification of visual system models to try to rescue their human-consistency

Next, we wondered if some relatively simple changes to the $DCNN_{IC}$ visual system

models tested here could bring them into better correspondence with the primate visual system

behavior (with respect to B.I1n and B.I2n metrics). Specifically, we considered and tested the

following modifications to the most *human-consistent* $DCNN_{IC}$ model visual system (Inception-

v3): we (1) changed the input to the model to be more primate-like in its retinal sampling

(Inception-v3 + retina-like), (2) changed the transformation (aka "decoder") from the internal
model feature representation into the behavioral output by augmenting the number of decoder
training images or changing the decoder type (Inception-v3 + SVM, Inception-v3 +
classifier_train), and (3) modified all of the internal filter weights of the model (aka "fine
tuning") by augmenting its ImageNet training with additional images drawn from the same
distribution as our test images (Inception-v3 + synthetic-fine-tune). While some of these
modifications (e.g. fine-tuning on synthetic images and increasing the number of classifier
training images) had the expected effect of increasing mean overall performance (not shown, see
Methods), we found that none of these modifications led to a significant improvement in its
human-consistency on the behavioral metrics (Figure 4B). Thus, the failure of current $DCNN_{IC}$
models to accurately capture the image-level signatures of primates cannot be rescued by simple
modifications on a fixed architecture.

Looking for clues: Image-level comparisons of models and primates

Taken together, Figures 2, 3 and 4 suggest that current $DCNN_{IC}$ visual system models fail
to accurately capture the image-level signatures of humans and monkeys. To further examine this
failure in the hopes of providing clues for model improvement, we examined the image-level
residual signatures of all the visual system models, relative to the pooled human. For each model,
we computed its residual signature as the difference (positive or negative) of a linear least
squares regression of the model signature on the corresponding human signature. For this
analysis, we focused on the B.I1n metric as it showed a clear divergence of $DCNN_{IC}$ models and
primates, and the behavioral residual can be interpreted based only on the test images (whereas
B.I2n depends on the interaction between test images and distractor choice).

We first asked to what extent the residual signatures are shared between different visual
system models. Figure 5A shows the similarity between the residual signatures of all pairs of
models; the color of bin (*i,j*) indicates the proportion of explainable variance that is shared
between the residual signatures of visual systems *i* and *j*. For ease of interpretation, we ordered
visual system models based on their architecture and optimization procedure and partitioned this
matrix into four distinct regions. Each region compares the residuals of a "source" model group
with fixed architecture and optimization procedure (five Inception-v3 models optimized for

733 categorization on ImageNet, varying only in initial conditions and training image order) to a

734 "target" model group. The target groups of models for each of the four regions are: 1) the pooled

735 monkey, 2) other $DCNN_{IC}$ models from the source group, 3) $DCNN_{IC}$ models that differ in

736 architecture but share the optimization procedure of the source group models and 4) $DCNN_{IC}$

737 models that differ slightly using an augmented optimization procedure but share the architecture

738 of the source group models. Figure 5B shows the mean (±SD) variance shared in the residuals

739 averaged within these four regions for all images (black dots), as well as for images that humans

740 found to be particularly difficult (gray dots, selected based on held-out human data, see

741 Methods). First, consistent with the results shown in Figure 3, we note that the residual

742 signatures of this particular $DCNN_{IC}$ model are not well shared with the pooled monkey (r^2=0.39

743 in region 1), and this phenomenon is more pronounced for the images that humans found most

744 difficult (r^2=0.17 in region 1). However, this relatively low correlation between model and

745 primate residuals is not indicative of spurious model residuals, as the model residual signatures

746 were highly reliable between different instances of this fixed $DCNN_{IC}$ model, across random

747 training initializations (region 2: r^2=0.79, 0.77 for all and most difficult images, respectively).

748 Interestingly, residual signatures were still largely shared with other $DCNN_{IC}$ models with vastly

749 different architectures (region 3: r^2=0.70, 0.65 for all and most difficult images, respectively).

750 However, residual signatures were more strongly altered when the visual training diet of the

751 same architecture was altered (region 4: r^2=0.57, 0.46 for all and most difficult images

752 respectively, cf. region 3). Taken together, these results indicate that the images where $DCNN_{IC}$

753 visual system models diverged from humans (and monkeys) were not spurious but were rather

754 highly reliable across different model architectures, demonstrating that current $DCNN_{IC}$ models

755 systematically and similarly diverge from primates.

757   To look for clues for model improvement, we asked what, if any, characteristics of

758 images might account for this divergence of models and primates. We regressed the residual

759 signatures of $DCNN_{IC}$ models on four different image attributes (corresponding to the size,

760 eccentricity, pose, and contrast of the object in each image). We used multiple linear regressions

761 to predict the model residual signatures from all of these image attributes, and also considered

762 each attribute individually using simple linear regressions. Figure 6A shows example images

763 (sampled from the full set of 2400 images) with increasing attribute value for each of these four

image attributes. While the DCNN$_{IC}$ models were not directly optimized to display primate-like

performance dependence on such attributes, we observed that the Inception-v3 visual system

model nonetheless exhibited qualitatively similar performance dependencies as primates (see

Figure 6B). For example, humans (black), monkeys (gray) and the Inception-v3 model (blue) all

performed better, on average, for images in which the object is in the center of gaze (low

eccentricity) and large in size. Furthermore, all three systems performed better, on average, for

images when the pose of the object was closer to the canonical pose (see Figure 6B); this

sensitivity to object pose manifested itself as a non-linear dependence due to the fact that all

tested objects exhibited symmetry in at least one axis. The similarity of the patterns in Figure 6B

between primates and the DCNN$_{IC}$ visual system models is not perfect but is striking,

particularly in light of the fact that these models were not optimized to produce these patterns.

However, this similarity is analogous to the similarity in the B.O1 and B.O2 metrics in that it

only holds on average over many images. Looking more closely at the image-by-image

comparison, we again found that the DCNN$_{IC}$ models failed to capture a large portion of the

image-by-image variation (Figure 3). In particular, Figure 6C shows the proportion of variance

explained by specific image attributes for the residual signatures of monkeys (black) and

DCNN$_{IC}$ models (blue). We found that, taken together, all four of these image attributes

explained only ~10% of the variance in DCNN$_{IC}$ residual signatures, and each individual

attribute could explain at most a small amount of residual variance (<5% of the explainable

variance). In sum, these analyses show that some behavioral effects that might provide intuitive

clues to modify the DCNN$_{IC}$ models are already in place in those models (e.g. a dependence on

eccentricity). But the quantitative image-by-image analyses of the remaining unexplained

variance (Figure 6C) argue that the DCNN$_{IC}$ visual system models' failure to capture primate

image-level signatures cannot be further accounted for by these simple image attributes and

likely stem from other factors.

DISCUSSION

The current work was motivated by the broad scientific goal of discovering models that

quantitatively explain the neuronal mechanisms underlying primate invariant object recognition

behavior. To this end, previous work had shown that specific artificial neural network models

(ANNs), drawn from a large family of deep convolutional neural networks (DCNNs) and
optimized to achieve high levels of object categorization performance on large-scale image-sets,
capture a large fraction of the variance in primate visual recognition behaviors (Rajalingham et
al., 2015; Jozwik et al., 2016; Kheradpisheh et al., 2016; Kubilius et al., 2016; Peterson et al.,
2016; Wallis et al., 2017), and the internal hidden neurons of those same models also predict a
large fraction of the image-driven response variance of brain activity at multiple stages of the
primate ventral visual stream (Yamins et al., 2013; Cadieu et al., 2014; Khaligh-Razavi and
Kriegeskorte, 2014; Yamins et al., 2014; Güçlü and van Gerven, 2015; Cichy et al., 2016; Hong
et al., 2016; Seibert et al., 2016; Cadena et al., 2017; Wen et al., 2017). For clarity, we here
referred to this sub-family of models as $DCNN_{IC}$ (to denote ImageNet-Categorization training),
so as to distinguish them from all possible models in the DCNN family, and more broadly, from
the super-family of all ANNs. In this work, we directly compared leading $DCNN_{IC}$ models to
primates (humans and monkeys) with respect to their behavioral signatures at both object and
image level resolution in the domain of core object recognition. In order to do so, we measured
and characterized primate behavior at larger scale and higher resolution than previously possible.
We first replicate prior work (Rajalingham et al., 2015) showing that, at the object level,
$DCNN_{IC}$ models produce statistically indistinguishable behavior from primates, and we extend
that work by showing that these models also match the *average* primate sensitivities to object
contrast, eccentricity, size, and pose, a noteworthy similarity in light of the fact that these models
were not optimized to produce these performance patterns. However, our primary novel result is
that, examining behavior at the higher resolution of individual images, all leading $DCNN_{IC}$
models failed to replicate the image-level behavioral signatures of primates. An important related
claim is that rhesus monkeys are more consistent with the archetypal human than any of the
tested $DCNN_{IC}$ models (at the image-level).
819

While it had previously been shown that $DCNN_{IC}$ models can diverge from human
behavior on specifically chosen adversarial images (Szegedy et al., 2013), a strength of our work
is that we did not optimize images to induce failure but instead randomly sampled the image
generative parameter space broadly. As such, our results highlight a *general*, rather than
adversarial-induced, failure of $DCNN_{IC}$ models to fully capture the neural mechanisms
underlying primate core object recognition behavior. Furthermore, we showed that this failure of

current DCNN$_{IC}$ models cannot be explained by simple image attributes and cannot be rescued

by simple model modifications (input image sampling, model training, and classifier variations).

Taken together, these results suggest that new ANN models are needed to more precisely capture

the neural mechanisms underlying primate object vision.

With regards to new ANN models, we can attempt to make prospective inferences about

future possible DCNN$_{IC}$ models from the data presented here. Based on the observed distribution

of image-level *human-consistency* values for the DCNN$_{IC}$ models tested here, we infer that yet

untested model instances sampled identically (i.e. from the DCNN$_{IC}$ model sub-family) are very

likely to have similarly inadequate image-level *human-consistency*. While we cannot rule out the

possibility that at least one model instance within the DCNN$_{IC}$ sub-family would fully match the

image-level behavioral signatures, the probability of sampling such a model is vanishingly small

($p<10^{-17}$ for B.I2n *human-consistency*, estimated using exact test using Gaussian kernel density

estimation, see Methods, Results). An important caveat of this inference is that we may have a

biased estimate of the *human-consistency* distribution of this model sub-family, as we did not

exhaustively sample the sub-family. In particular, if the model sampling process is non-

stationary over time (e.g. increases in computational power over time allows larger models to be

successfully trained), the *human-consistency* of new (i.e. yet to be sampled) models may lie

outside the currently estimated distribution. Consistent with the latter, we observed that current

DCNN$_{IC}$ cluster into two distinct "generations" separated in time (before/after the year 2015; e.g.

Inception-v3 improves over AlexNet though both lie outside the primate zone in Figure 3). Thus,

following this trend, it is possible that the evolution of "next-generation" models within the

DCNN$_{IC}$ sub-family could meet our criteria for successful matching primate-like behavior.

Alternatively, it is possible—and we think likely—that future DCNN$_{IC}$ models will also

fail to capture primate-like image-level behavior, suggesting that either the architectural

limitations (e.g. convolutional, feed-forward) and/or the optimization procedure (including the

diet of visual images) that define this model sub-family are fundamentally limiting. Thus, ANN

model sub-families utilizing different architectures (e.g. recurrent neural networks) and/or

optimized for different behavioral goals (e.g. loss functions other than object classification

performance, and/or images other than category-labeled ImageNet images) may be necessary to

accurately capture primate behavior. To this end, we propose that testing even individual
changes to the $DCNN_{IC}$ models—each creating a new ANN model sub-family—may be the best
way forward, because $DCNN_{IC}$ models currently offer the best explanations (in a predictive
sense) of both the behavioral and neural phenomena of core object recognition.

To reach that goal of finding a new ANN model sub-family that is a better mechanistic
model of the primate ventral visual stream, we propose that even larger-scale, high-resolution
behavioral measurements, such as expanded versions of the patterns of image-level performance
presented here, could serve as a useful top-down optimization guides. Not only do these high-
resolution behavioral signatures have the statistical power to reject the currently leading ANN
models, but they can also be efficiently collected at very large scale, in contrast to other guide
data (e.g. large-scale neuronal measurements). Indeed, current technological tools for high-
throughput psychophysics in humans and monkeys (e.g. Amazon Mechanical Turk for humans,
Monkey Turk for rhesus monkeys) enable time- and cost-efficient collection of large-scale
behavioral datasets, such as the ~1 million behavioral trials obtained for the current work. These
systems trade off an increase in efficiency with a decrease in experimental control. For example,
we did not impose experimental constraints on subjects' acuity and we can only infer likely head
and gaze position. Previous work has shown that patterns of behavioral performance on object
recognition tasks from in-lab and online subjects were equally reliable and virtually identical
(Majaj et al., 2015), but it is not yet clear to what extent this holds at the resolution of individual
images, as one might expect that variance in performance across images is more sensitive to
precise head and gaze location. For this reason, we here refrain from making strong inferences
from small behavioral differences, such as the small difference between humans and monkeys.
Nevertheless, we argue that this sacrifice in exact experimental control while retaining sufficient
power for model comparison is a good tradeoff for efficiently collecting large behavioral datasets
toward the goal of constraining future models of the primate ventral visual stream.

REFERENCES

Cadena SA, Denfield GH, Walker EY, Gatys LA, Tolias AS, Bethge M, Ecker AS (2017) Deep convolutional models improve predictions of macaque V1 responses to natural images. bioRxiv:201764.

Cadieu CF, Hong H, Yamins DL, Pinto N, Ardila D, Solomon EA, Majaj NJ, DiCarlo JJ (2014) Deep neural networks rival the representation of primate IT cortex for core visual object recognition. PLoS computational biology 10:e1003963.

Cichy RM, Khosla A, Pantazis D, Torralba A, Oliva A (2016) Comparison of deep neural networks to spatio-temporal cortical dynamics of human visual object recognition reveals hierarchical correspondence. Scientific reports 6:27755.

DiCarlo JJ, Johnson KO (1999) Velocity invariance of receptive field structure in somatosensory cortical area 3b of the alert monkey. Journal of Neuroscience 19:401-419.

DiCarlo JJ, Cox DD (2007) Untangling invariant object recognition. Trends in cognitive sciences 11:333-341.

DiCarlo JJ, Zoccolan D, Rust NC (2012) How does the brain solve visual object recognition? Neuron 73:415-434.

Dodge S, Karam L (2017) A Study and Comparison of Human and Deep Learning Recognition Performance Under Visual Distortions. arXiv preprint arXiv:170502498.

Geirhos R, Janssen DH, Schütt HH, Rauber J, Bethge M, Wichmann FA (2017) Comparing deep neural networks against humans: object recognition when the signal gets weaker. arXiv preprint arXiv:170606969.

Goodfellow IJ, Shlens J, Szegedy C (2014) Explaining and harnessing adversarial examples. arXiv preprint arXiv:14126572.

Güçlü U, van Gerven MA (2015) Deep neural networks reveal a gradient in the complexity of neural representations across the ventral stream. Journal of Neuroscience 35:10005-10014.

He K, Zhang X, Ren S, Sun J (2016) Deep residual learning for image recognition. In: Proceedings of the IEEE conference on computer vision and pattern recognition, pp 770-778.

Hong H, Yamins DL, Majaj NJ, DiCarlo JJ (2016) Explicit information for category-orthogonal object properties increases along the ventral stream. Nature neuroscience 19:613.

Hosseini H, Xiao B, Jaiswal M, Poovendran R (2017) On the Limitation of Convolutional Neural Networks in Recognizing Negative Images. human performance 4:6.

Huynh DQ (2009) Metrics for 3D rotations: Comparison and analysis. Journal of Mathematical Imaging and Vision 35:155-164.

Johnson KO, Hsiao SS, Yoshioka T (2002) Neural coding and the basic law of psychophysics. The Neuroscientist 8:111-121.

Jozwik KM, Kriegeskorte N, Mur M (2016) Visual features as stepping stones toward semantics: Explaining object similarity in IT and perception with non-negative least squares. Neuropsychologia 83:201-226.

Khaligh-Razavi S-M, Kriegeskorte N (2014) Deep supervised, but not unsupervised, models may explain IT cortical representation. PLoS computational biology 10:e1003915.

Kheradpisheh SR, Ghodrati M, Ganjtabesh M, Masquelier T (2016) Deep networks can resemble human feed-forward vision in invariant object recognition. Scientific reports 6:32672.

Krizhevsky A, Sutskever I, Hinton GE (2012) Imagenet classification with deep convolutional neural networks. In: Advances in neural information processing systems, pp 1097-1105.

Kubilius J, Bracci S, de Beeck HPO (2016) Deep neural networks as a computational model for human shape sensitivity. PLoS computational biology 12:e1004896.

LeCun Y, Bengio Y, Hinton G (2015) Deep learning. Nature 521:436-444.

Majaj NJ, Hong H, Solomon EA, DiCarlo JJ (2015) Simple Learned Weighted Sums of Inferior
Temporal Neuronal Firing Rates Accurately Predict Human Core Object Recognition
Performance. The Journal of Neuroscience 35:13402-13418.
Nguyen A, Yosinski J, Clune J (2015) Deep neural networks are easily fooled: High confidence
predictions for unrecognizable images. In: Proceedings of the IEEE Conference on Computer
Vision and Pattern Recognition, pp 427-436.
Peterson JC, Abbott JT, Griffiths TL (2016) Adapting deep network features to capture
psychological representations. arXiv preprint arXiv:160802164.
Pinto N, Cox DD, DiCarlo JJ (2008) Why is real-world visual object recognition hard? PLoS
computational biology 4:e27.
Rajalingham R, Schmidt K, DiCarlo JJ (2015) Comparison of Object Recognition Behavior in
Human and Monkey. The Journal of Neuroscience 35:12127-12136.
RichardWebster B, Anthony SE, Scheirer WJ (2016) PsyPhy: A Psychophysics Driven
Evaluation Framework for Visual Recognition. arXiv preprint arXiv:161106448.
Rosch E, Mervis CB, Gray WD, Johnson DM, Boyes-Braem P (1976) Basic objects in natural
categories. Cognitive psychology 8:382-439.
Seibert D, Yamins DL, Ardila D, Hong H, DiCarlo JJ, Gardner JL (2016) A performance-
optimized model of neural responses across the ventral visual stream. bioRxiv:036475.
Simonyan K, Zisserman A (2014) Very deep convolutional networks for large-scale image
recognition. arXiv preprint arXiv:14091556.
Szegedy C, Zaremba W, Sutskever I, Bruna J, Erhan D, Goodfellow I, Fergus R (2013)
Intriguing properties of neural networks. arXiv preprint arXiv:13126199.
Ullman S, Humphreys GW (1996) High-level vision: Object recognition and visual cognition: MIT
press Cambridge, MA.
Wallis TS, Funke CM, Ecker AS, Gatys LA, Wichmann FA, Bethge M (2017) A parametric
texture model based on deep convolutional features closely matches texture appearance for
humans. Journal of vision 17:5-5.
Wen H, Shi J, Zhang Y, Lu K-H, Cao J, Liu Z (2017) Neural encoding and decoding with deep
learning for dynamic natural vision. Cerebral Cortex:1-25.
Yamins DL, DiCarlo JJ (2016) Using goal-driven deep learning models to understand sensory
cortex. Nature neuroscience 19:356-365.
Yamins DL, Hong H, Cadieu C, DiCarlo JJ (2013) Hierarchical modular optimization of
convolutional networks achieves representations similar to macaque IT and human ventral
stream. In: Advances in neural information processing systems, pp 3093-3101.
Yamins DL, Hong H, Cadieu CF, Solomon EA, Seibert D, DiCarlo JJ (2014) Performance-
optimized hierarchical models predict neural responses in higher visual cortex. Proceedings of
the National Academy of Sciences:201403112.
Zeiler MD, Fergus R (2014) Visualizing and understanding convolutional networks. In: Computer
Vision–ECCV 2014, pp 818-833: Springer.

971
972

Behavioral Metric	Hit Rate	False Alarm Rate
One-versus all object-level performance (B.O1) ($N_{objects}$ x 1) $$O_1(i) = Z\big(HR(i)\big) - Z\big(FAR(i)\big),$$ $$i = 1,2,\dots,N_{objects}$$	Proportion of trials when images of object i were correctly labeled as object i.	Proportion of trials when any image was incorrectly labeled as object i.
One-versus-other object-level performance B.O2 ($N_{objects}$ x $N_{objects}$) $$O_2(i,j) = Z\big(HR(i,j)\big) - Z\big(FAR(i,j)\big),$$ $$i = 1,2,\dots,N_{objects}$$ $$j = 1,2,\dots,N_{objects}$$	Proportion of trials when images of object i were correctly labeled as i, when presented against distractor object j.	Proportion of trials when images of object j were incorrectly labeled as object i
One-versus-all image-level performance B.I1 (N_{images} x 1) $$I_1(ii) = Z\big(HR(ii)\big) - Z\big(FAR(ii)\big),$$ $$ii = 1,2,\dots,N_{images}$$	Proportion of trials when image ii was correctly classified as object i.	Proportion of trials when any image was incorrectly labeled as object i.
One-versus-other image-level performance B.I2 (N_{images} x $N_{objects}$) $$I_2(ii,j) = Z\big(HR(ii,j)\big) - Z\big(FAR(ii,j)\big),$$ $$ii = 1,2,\dots,N_{images}$$ $$j = 1,2,\dots,N_{objects}$$	Proportion of trials when image ii was correctly classified as object i, when presented against distractor object j.	Proportion of trials when images of object j were incorrectly labeled as object i

976 **Table 1: Definition of behavioral performance metrics.** The first column provides the name,

977 abbreviation, dimensions, and equations for each of the raw performance metrics. The next two

978 columns provide the definitions for computing the hit rate (HR) and false alarm rate (FAR)

979 respectively.

 FIGURE LEGENDS

Figure 1. Images and behavioral task. (A) Two (out of 100) example images for each of the 24
basic-level objects. To enforce true invariant object recognition behavior, we generated
naturalistic synthetic images, each with one foreground object, by rendering a 3D model of each
object with randomly chosen viewing parameters and placing that foreground object view onto a
randomly chosen, natural image background. **(B)** Time course of example behavioral trial (zebra
versus dog) for human psychophysics. Each trial initiated with a central fixation point for 500
ms, followed by 100 ms presentation of a square test image (spanning 6-8° of visual angle).
After extinction of the test image, two choice images were shown to the left and right. Human
participants were allowed to freely view the response images for up to 1000 ms and responded
by clicking on one of the choice images; no feedback was given. To neutralize top-down feature
attention, all 276 binary object discrimination tasks were randomly interleaved on a trial-by-trial
basis. The monkey task paradigm was nearly identical to the human paradigm, with the
exception that trials were initiated by touching a fixation circle horizontally centered on the
bottom third of the screen, and successful trials were rewarded with juice while incorrect choices
resulted in timeouts of 1–2.5s. **(C)** Large-scale and high-throughput psychophysics in humans
(top left), monkeys (top right), and models (bottom). Human behavior was measured using the
online Amazon MTurk platform, which enabled the rapid collection ~1 million behavioral trials
from 1472 human subjects. Monkey behavior was measured using a novel custom home-cage
behavioral system (MonkeyTurk), which leveraged a web-based behavioral task running on a
tablet to test many monkey subjects simultaneously in their home environment. Deep
convolutional neural network models were tested on the same images and tasks as those
presented to humans and monkeys by extracting features from the penultimate layer of each
visual system model and training back-end multi-class logistic regression classifiers. All
behavioral predictions of each visual system model were for images that were not seen in any
phase of model training.

Figure 2. Object-level comparison to human behavior. (A) One-versus-all object-level (B.O1)
signatures for the pooled human (n=1472 human subjects), pooled monkey (n=5 monkey
subjects), and several DCNN$_{IC}$ models. Each B.O1 signature is shown as a 24-dimensional
vector using a color scale; each colored bin corresponds to the system's discriminability of one

object against all others that were tested. The color scales span each signature's full performance range, and warm colors indicate lower discriminability. **(B)** Direct comparison of the B.O1 signatures of a pixel visual system model (top panel) and a $DCNN_{IC}$ visual system model (Inception-v3, bottom panel) against that of the human B.O1 signature. **(C)** *Human-consistency* of B.O1 signatures, for each of the tested model visual systems. The black and gray dots correspond to a held-out pool of five human subjects and a pool of five macaque monkey subjects respectively. The shaded area corresponds to the "primate zone," a range of consistencies delimited by the estimated *human-consistency* of a pool of infinitely many monkeys (see Figure 4A). **(D)** One-versus-other object-level (B.O2) signatures for pooled human, pooled monkey, and several $DCNN_{IC}$ models. Each B.O2 signature is shown as a 24x24 symmetric matrices using a color scale, where each bin (i,j) corresponds to the system's discriminability of objects i and j. Color scales similar to (A). **(E)** Human-consistency of B.O2 signatures for each of the tested model visual systems. Format is identical to (C).

Figure 3. Image-level comparison to human behavior. (A) Schematic for computing B.I1n. First, the one-versus-all image-level signature (B.I1) is shown as a 240-dimensional vector (24 objects, 10 images/object) using a color scale, where each colored bin corresponds to the system's discriminability of one image against all distractor objects. From this pattern, the normalized one-versus-all image-level signature (B.I1n) is estimated by subtracting the mean performance value over all images of the same object. This normalization procedure isolates behavioral variance that is specifically image-driven but not simply predicted by the object. **(B)** Normalized one-versus-all object-level (B.I1n) signatures for the pooled human, pooled monkey, and several $DCNN_{IC}$ models. Each B.I1n signature is shown as a 240-dimensional vector using a color scale, formatted as in (A). Color scales similar to Figure 2A. **(C)** *Human-consistency* of B.I1n signatures for each of the tested model visual systems. Format is identical to Figure 2C. **(D)** Normalized one-versus-other image-level (B.I2n) signatures for pooled human, pooled monkey, and several $DCNN_{IC}$ models. Each B.I2n signature is shown as a 240x24 matrix using a color scale, where each bin (i,j) corresponds to the system's discriminability of image i against distractor object j. Color scales similar to Figure 2A. **(E)** Human-consistency of B.I2n signatures for each of the tested model visual systems. Format is identical to Figure 2C.

Figure 4. Effect of subject pool size and DCNN model modifications on consistency with
human behavior. **(A)** Accounting for natural subject-to-subject variability. For each of the four
behavioral metrics, the *human-consistency* distributions of monkey (blue markers) and model
(black markers) pools are shown as a function of the number of subjects in the pool (mean ± SD,
over subjects). The human consistency increases with growing number of subjects for all visual
systems across all behavioral metrics. The dashed lines correspond to fitted exponential
functions, and the parameter estimate (mean ± SE) of the asymptotic value, corresponding to the
estimated *human-consistency* of a pool of infinitely many subjects, is shown at the right most
point on each abscissa. **(B)** Model modifications that aim to rescue the $DCNN_{IC}$ models. We
tested several simple modifications (see Methods) to the most *human-consistent* $DCNN_{IC}$ visual
system model (Inception-v3). Each panel shows the resulting *human-consistency* per modified
model (mean ± SD over different model instances, varying in random filter initializations) for
each of the four behavioral metrics.

1054

Figure 5. Analysis of unexplained human behavioral variance. **(A)** Residual similarity
between all pairs of human visual system models. The color of bin (*i,j*) indicates the proportion
of explainable variance that is shared between the residual signatures of visual systems *i* and *j*.
For ease of interpretation, we ordered visual system models based on their architecture and
optimization procedure and partitioned this matrix into four distinct regions. **(B)** Summary of
residual similarity. For each of the four regions in Figure 5A, the similarity to the residuals of
Inception-v3 (region 2 in (A)) is shown (mean ± SD, within each region) for all images (black
dots), and for images that humans found to be particularly difficult (gray dots, selected based on
held-out human data).

1064

Figure 6. Dependence of primate and DCNN model behavior on image attributes. **(A)**
Example images with increasing attribute value, for each of the four pre-defined image attributes
(see Methods). **(B)** Dependence of performance (B.I1n) as a function of four image attributes, for
humans, monkeys and a $DCNN_{IC}$ model (Inception-v3). **(C)** Proportion of explainable variance
of the residual signatures of monkeys (black) and $DCNN_{IC}$ models (blue) that is accounted for by
each of the pre-defined image attributes. Error-bars correspond to SD over trial re-sampling for
monkeys, and over different models for $DCNN_{IC}$ models.

Figure 1

A

100 testing images/object

Elephant Shorts Bird Tank Camel Leg Rhino Wrench

Bear Guitar Fork Zebra Hammer Pen Hanger House

Knife Gun Calculator Table Truck Spider Dog Watch

B

Fixation
(500ms/100ms)

Test Image
(100ms)

Choice Screen
(1000ms)

C

Human Behavior (Mechanical Turk)
n=1472 human subjects

Monkey Behavior (Monkey-Turk)
Arduino controller Android Tablet Juice reward tube n=5 monkey subjects

Model Behavior
Input Image

Feature Representation

Linear classifier

Output Class Probability

Figure 2

A B.O1 Signatures (~object difficulties)

Primates: Human, Monkey

DCNNs: ALEXNET, NYU, VGG, GOOGLENET, RESNET, INCEPTION-v3

Objects: CAMEL, DOG, RHINO, ELEPHANT, WRENCH, KNIFE, HANGER, FORK, GUITAR, PEN, TANK, TRUCK, BIRD, HAMMER, GUN, TABLE, CALCULATOR, SPIDER, LEG, ZEBRA, HOUSE, BEAR, SHORTS, WATCH

B

Pixels (d'): ρ̃ = 0.40, n = 24 objects, Human Pool (d')

Inception-v3 (d'): ρ̃ = 0.89, n = 24 objects, Human Pool (d')

C Primate Zone — Heldout Human Pool (n=5 subjects), Monkey Pool (n=5 subjects)

Human-Consistency (of B.O1 Signatures)

PIXELS, V1, ALEXNET, NYU, VGG, GOOGLENET, RESNET, INCEPTION-v3

D B.O2 Signatures (~object confusions)

Primates: Human, Monkey

DCNNs: ALEXNET, NYU, VGG, GOOGLENET, RESNET, INCEPTION-v3

E Primate Zone — Heldout Human Pool (n=5 subjects), Monkey Pool (n=5 subjects)

Human-Consistency (of B.O2 Signatures)

PIXELS, V1, ALEXNET, NYU, VGG, GOOGLENET, RESNET, INCEPTION-v3

Figure 3

A **B.I1n Signatures**
(~normalized image difficulties)

B.I1 (image-level one-versus-all performance)

mean per object

B.I1n

B

Primates

CAMEL
DOG
RHINO
ELEPHANT
WRENCH
KNIFE
HANGER
FORK
GUITAR
PEN
TANK
TRUCK
BIRD
HAMMER
GUN
TABLE
CALCULATOR
SPIDER
LEG
ZEBRA
HOUSE
BEAR
SHORTS
WATCH

Human Monkey

DCNNs

ALEXNET NYU VGG GOOGLENET RESNET INCEPTION-v3

C

Primate Zone

Heldout Human Pool (n=5 subjects)
Monkey Pool (n=5 subjects)

Human-Consistency (of B.I1n Signatures)

1.0

0.0

PIXELS | V1 | ALEXNET | NYU | VGG | GOOGLENET | RESNET | INCEPTION-v3

D **B.I2n Signatures** (~normalized image confusions)

Primates

CAMEL
DOG
RHINO
ELEPHANT
WRENCH
KNIFE
HANGER
FORK
GUITAR
PEN
TANK
TRUCK
BIRD
HAMMER
GUN
TABLE
CALCULATOR
SPIDER
LEG
ZEBRA
HOUSE
BEAR
SHORTS
WATCH

Human Monkey

DCNN (ex.)

INCEPTION-v3

E

Primate Zone

Heldout Human Pool (n=5 subjects)
Monkey Pool (n=5 subjects)

Human-Consistency (of B.I2n Signatures)

1.0

0.0

PIXELS | V1 | ALEXNET | NYU | VGG | GOOGLENET | RESNET | INCEPTION-v3

Figure 4

A — B.O1, B.O2, B.I1n, B.I2n

Human-Consistency

Monkey Pool
Model Pool

Extrapolation to infinitely many subjects

Subjects   ∞

B — Model Variations

Human-Consistency

INCEPTION-v3
INCEPTION-v3 + retina
INCEPTION-v3 + SVM
INCEPTION-v3 + classifier_train
INCEPTION-v3 + synthetic_train

Figure 5

Figure 6