Learning optimal decisions with confidence

Jan Drugowitsch[1,*], André G. Mendonça[2], Zachary F. Mainen[2], Alexandre Pouget[3]

[1] Department of Neurobiology, Harvard Medical School, 220 Longwood Avenue, Boston, MA 02115, USA
[2] Champalimaud Neuroscience Programme, Champalimaud Centre for the Unknown, Avenida de Brasilia, s/n, 1400-038 Lisbon, Portugal
[3] Department of Basic Neuroscience, University of Geneva, Rue Michel Servet 1, CH-1211 Geneva, Switzerland

[*] Corresponding author:
Jan Drugowitsch
Department of Neurobiology
Harvard Medical School
220 Longwood Avenue
Boston, MA 02115
Telephone: +1 (617) 432 5026
E-Mail: jan_drugowitsch@hms.harvard.edu

Abstract

Diffusion decision models (DDMs) are immensely successful models for decision-making under

uncertainty and time pressure. In the context of perceptual decision making, these models

typically start with two input units, organized in a neuron-antineuron pair. In contrast, in the brain,

sensory inputs are encoded through the activity of large neuronal populations. Moreover, while

DDMs are wired by hand, the nervous system must learn the weights of the network through trial

and error. There is currently no normative theory of learning in DDMs and therefore no theory of

how decision makers could learn to make optimal decisions in this context. Here, we derive the

first such rule for learning a near-optimal linear combination of DDM inputs based on trial-by-trial

feedback. The rule is Bayesian in the sense that it learns not only the mean of the weights but

also the uncertainty around this mean in the form of a covariance matrix. In this rule, the rate of

learning is proportional (resp. inversely proportional) to confidence for incorrect (resp. correct)

decisions. Furthermore, we show that, in volatile environments, the rule predicts a bias towards

repeating the same choice after correct decisions, with a bias strength that is modulated by the

previous choice's difficulty. Finally, we extend our learning rule to cases for which one of the

choices is more likely a priori, which provides new insights into how such biases modulate the

mechanisms leading to optimal decisions in diffusion models.

Significance Statement

Popular models for the tradeoff between speed and accuracy of everyday decisions usually assume fixed, low-dimensional sensory inputs. In contrast, in the brain, these inputs are distributed across larger populations of neurons, and their interpretation needs to be learned from feedback. We ask how such learning could occur and demonstrate that efficient learning is significantly modulated by decision confidence. This modulation predicts a particular dependency pattern between consecutive choices, and provides new insight into how a priori biases for particular choices modulate the mechanisms leading to efficient decisions in these models.

Introduction

Decisions are a ubiquitous component of every-day behavior. To be efficient, they require handling the uncertainty arising from the noisy and ambiguous information that the environment provides (1). This is reflected in the trade-off between speed and accuracy of decisions. Fast choices rely on little information and may therefore sacrifice accuracy. In contrast, slow choices provide more opportunity to accumulate evidence and thus may be more likely to be correct, but are more costly in terms of attention or effort and lost time and opportunity. Therefore, efficient decisions require not only a mechanism to accumulate evidence, but also one to trigger a choice once enough evidence has been collected. *Drift-diffusion models* (or *diffusion decision models*; DDMs) are a widely-used model family (2) that provides both mechanisms. Not only do DDMs yield surprisingly good fits to human and animal behavior (3–5), but they are also known to achieve a Bayes-optimal decision strategy under a wide range of circumstances (4, 6–10).

DDMs assume a particle that drifts and diffuses until it reaches one of two boundaries, each triggering a different choice (**Fig. 1a**). The particle's drift reflects the net surplus of evidence towards one of two choices. This is exemplified by the random-dot motion task, in which the motion direction and coherence set the drift sign and magnitude. The particle's stochastic diffusion reflects the uncertainty in the momentary evidence and is responsible for the variability in decision times and choices widely observed in human and animal decisions (3, 5). A standard assumption underlying DDMs is that the noisy momentary evidence that is accumulated over time is one-dimensional — an abstraction of the momentary decision-related evidence of some stimulus. In reality, however, evidence would usually be distributed across a larger number of inputs, such as a neural population in the brain, rather than individual neurons (or neuron/anti-neuron pairs; **Fig. 1a**). Furthermore, the brain would not know a priori how this distributed encoding provides information about the correctness of either choice. As a consequence, it needs to learn how to interpret neural population activity from the success and failure of previous choices. How such an

interpretation can be efficiently learned over time, both normatively and mechanistically, is the
focus of this work.

The multiple existing computational models for how humans and animals might learn to
improve their decisions from feedback (e.g., 11–14) do not address the question we are asking,
as they all assume that all evidence for each choice is provided at once, without considering the
temporal aspect of evidence accumulation. This is akin to fixed-duration experiments, in which
the evidence accumulation time is determined by the environment rather than the decision maker.
We, instead, address a more general and natural case in which decision times are under the
decision maker's control. In this setting, commonly studied using "reaction time" paradigms, the
temporal accumulation of evidence needs to be treated explicitly, and – as we will show – the
time it took to accumulate this evidence impacts how the decision strategy is updated after
feedback. Some models for both choice and reaction times have addressed the presence of high-
dimensional inputs (e.g., 15–17). However, they usually assumed as many choices as inputs,
were mechanistic rather than normative, and did not consider how interpreting the input could be
learned. We furthermore extend on previous work by considering the effect of a priori biases
towards believing that one option is more correct than the other, and how such biases can be
learned. This yields a new theoretical understanding of how choice biases impact optimal
decision-making in diffusion models. Furthermore, it clarifies of how different implementations of
this bias result in different diffusion model implementations, like the one proposed by Hanks et al.
(18).

Results

75
76 **Figure 1. Learning the input weights from feedback in diffusion models.** In diffusion models, the input(s) provide at each point in
77 time noisy evidence about the world's true state, here given by the drift μ. The decision maker accumulates this evidence over time
78 (e.g., black example traces) to form a belief about μ. Bayes-optimal decisions choose according to the sign of the accumulated

- 3 -

evidence, justifying the two decision boundaries that trigger opposing choices. (**a**) In standard diffusion models, the momentary
evidence either arises directly from noisy samples of μ, or, as illustrated here, from a neuron/anti-neuron pair that codes for opposing
directions of evidence. The illustrated example assumes a random dot task, in which the decision maker needs to identify if most of
the dots that compose the stimulus are moving either to the left or to the right. The two neurons (or neural pools) are assumed to
extract motion energy of this stimulus towards the right (top) and left (bottom), such that their difference forms the momentary evidence
towards rightward motion. A decision is made once the accumulated momentary evidence reaches one of two decision boundaries,
triggering opposing choices. (**b**) Our setup differs from that in (**a**) in that we assume the input information $\delta x(t)$ to be encoded in a
larger neural population whose activity is linearly combined with weights w to yield the one-dimensional momentary evidence, and
that the decision maker aims to learn these weights from feedback about the correctness of her choices. (**c**) Decision confidence (i.e.,
the belief that the made choice was correct) in this kind of diffusion model drop as a function of time (horizontal axis) and with increased
uncertainty about the input weights (different shades of blue). (**d**) For near-optimal learning, the learning rate (the term ξ_w in Eq. (6))
is modulated by decision confidence (top left). High-confidence decisions lead to little learning if correct (green, right), and strong
learning if incorrect (red, left). Low-confidence decisions result in a moderate confidence-related learning rate term (top, center). The
learning rate in 1000 simulated trials (bottom) shows that the overall learning rate preserves this trend, with an additional suppression
of learning for low-confidence decisions. Other learning heuristics (e.g., the delta rule, right) do not modulate their learning by
confidence.
95

Bayes-optimal decision-making with diffusion models

A standard way (8, 10, 19) to interpret diffusion models as mechanistic implementations of Bayes-
optimal decision-making is to assume that, in each trial, an unobservable latent state μ (called
drift rate in diffusion models) is drawn from a prior distribution, $\mu \sim \mathrm{N}(0, \sigma_\mu^2)$, with zero mean and
variance σ_μ^2. The decision maker's aim is to infer whether this latent state is positive or negative
(e.g., rightward vs. leftward motion in the random dot motion task), irrespective of its magnitude
(e.g., the dot coherence level). The latent state itself is not directly observed, but is indirectly
conveyed via a stream of noisy, momentary evidence values $\delta z_1, \delta z_2, ...,$ that, in each small time
step of size δt, provide independent and identically distributed noisy information about μ through
$\delta z_i | \mu \sim \mathrm{N}(\mu \delta t, \delta t)$. Here, we have chosen a unit variance, scaled by δt. Any re-scaling of this
variance by an additional parameter would result in a global re-scaling of the evidence that can
be factored out (4, 8, 20), thus making such a re-scaling unnecessary.

Having after some time $t \equiv n\delta t$ observed n pieces of such evidence, $\delta z_{1:n}$, the decision
maker's posterior belief about μ, $p(\mu|\delta z_{1:n})$, turns out to be fully determined by the accumulated
evidence, $z(t) = \sum_{i=1}^{n} \delta z_i$, and time t (see Methods). Then, the posterior belief about μ being
positive (e.g., leftward motion) results in (8)
112

$$p(\mu \geq 0 | z(t), t) = \int_0^\infty p(\mu|\delta z_{1:n})\mathrm{d}\mu = \Phi\left(\frac{z(t)}{\sqrt{t + \sigma_\mu^{-2}}}\right), \tag{1}$$

where $\Phi(\cdot)$ is the cumulative function of a standard Gaussian. The opposite belief about μ being

negative is simply $p(\mu < 0|z(t), t) = 1 - p(\mu \geq 0|z(t), t)$ (**Fig. 3a**). The accumulated evidence

follows a diffusion process, $z(t)|\mu \sim N(\mu t, t)$, and thus can be interpreted as the location of a

drifting and diffusing particle with drift μ and unit diffusion variance (**Fig. 1a**). By Eq. (1), the

posterior belief about $\mu \geq 0$ is $> 1/2$ for positive $z(t)$, and $< 1/2$ for negative $z(t)$. To make Bayes-

optimal decisions, Bayesian decision theory (21) requires that these decisions are chosen to

maximize the expected associated reward (or, more formally, to minimize the expected loss).

Assuming equally-rewarding correct choices, this implies choosing the option that is considered

more likely correct. Given the above posterior belief, this makes $y = \text{sign}(z(t)) \in \{-1,1\}$ the

Bayes-optimal choice, which can be implemented mechanistically by (possibly time-varying)

boundaries $\pm\theta(t)$ on $z(t)$, associated with the two choices. At these boundaries, the posterior

belief about having made the correct choice, or decision confidence (22), is then given by Eq. (1)

with $z(t)$ replaced by $\theta(t)$. The sufficient statistics, $z(t)$ and t, of this posterior remain unchanged

by the introduction of such decision boundaries, such that Eq. (1) remains valid even in the

presence of these boundaries (8). Thus, under the above assumptions of prior and evidence,

diffusion models implement the Bayes-optimal decision strategy (**Fig. 3b**).

Note that $|\mu|$ (i.e., the momentary evidence's signal-to-noise ratio) controls the amount of

information provided about the sign of μ, and thus the difficulty of individual decisions. Thus, the

used prior $\mu \sim \text{N}(0, \sigma_\mu^2)$, which has more mass on small $|\mu|$, reflects that the difficulty of decisions

varies across trials, and that harder decisions are more frequent than easier ones. The prior width,

σ_μ^2 determines the spread of μ's across trials, and therefore the overall difficulty of the task (larger

σ_μ^2 = overall easier task). We chose a Gaussian prior for mathematical convenience, and also

because hard trials are more frequent than easy ones in many experiments (e.g. (20)), even

though they don't commonly use Gaussian priors. In general, the important assumption is that the

difficulty varies across trials, but not exactly how it does so, which is to say that the shape of the

prior distribution is not critical (8). Different prior choice will not qualitatively change our results,

but would make it hard or impossible to derive interpretable closed-form expressions. Model

predictions would change qualitatively if we assume the difficulty to be fixed, or known a-priori

(see 8), but we will not consider this case, as it rarely if ever occurs in the real world.

Using high-dimensional diffusion model inputs

To extend diffusion models to multi-dimensional momentary evidence, we assume it to be given

the a k-dimensional vector $\delta \boldsymbol{x}_i$. This evidence might represent inputs from multiple sensors, or

the (abstract) activity of a neuronal population (**Fig. 1b**). As the activity of neurons in a population

that encodes limited information about the latent state μ is likely correlated across neurons (23,

24), we chose the momentary evidence statistics to also feature such correlations (see Methods).

In general, we choose these statistics such that $\boldsymbol{w}^T \delta \boldsymbol{x}_i = \delta z_i$, where the vector $\boldsymbol{w}$ denote the k

input weights (for now assumed known). Defining the high-dimensional accumulated evidence by

$\boldsymbol{x}(t) = \sum_{i=1}^n \delta \boldsymbol{x}_i$, this implies $z(t) = \boldsymbol{w}^T \boldsymbol{x}(t)$, such that it is again Bayes-optimal to trigger decisions

as soon as $\boldsymbol{w}^T \boldsymbol{x}(t)$ equals one of two decision boundaries $\pm\theta(t)$. Furthermore, the posterior belief

about $\mu \geq 0$ is, similar to Eq. (1), given by

$$p(\mu \geq 0 | \boldsymbol{w}, \boldsymbol{x}(t), t) = \Phi(\boldsymbol{w}^T \tilde{\boldsymbol{x}}(t)), \tag{2}$$

where we have defined the time-attenuated accumulated evidence $\tilde{\boldsymbol{x}}(t) = \boldsymbol{x}(t)/\sqrt{t + \sigma_\mu^{-2}}$. As a

consequence, the decision-confidence for either choice, is, as before, given by Eq. (2), with

$\boldsymbol{w}^T \tilde{\boldsymbol{x}}(t)$ replaced by $\theta(t)/\sqrt{t + \sigma_\mu^{-2}}$. For time-independent decision bounds, $\theta(t) = \theta$, this

confidence decreases over time (**Fig. 1c**), reflecting the uncertainty about μ, and that late choices

are likely due to a low μ, which is associated with a hard trial, and thus low decision confidence.

This counter-intuitive drop in confidence with time has been previously described for diffusion

models with one-dimensional inputs (8, 25), and is a consequence of a trial difficulty that varies

across trials. Specifically, it arises from a mixture of easy trials associated with large $|\mu|$ that lead

to rapid, high-confidence choice, and hard trials associated with small $|\mu|$ that lead to slow, low-

confidence choices. Therefore, it doesn't depend on our choice of Gaussian prior, but is present

for any choice of symmetric prior over μ (see SI). The confidence remains constant over time only

when the difficulty is fixed across trials (i.e., $\mu \in \{-\mu_0, \mu_0\}$ for some fixed μ_0).

Using feedback to find the posterior weights

So far we have assumed the decision maker knows the linear input weights $\boldsymbol{w}$ to make Bayes-

optimal choices. If they were not known, how could they be learned? Traditionally, learning has

been considered an optimization problem, in which the decision maker tunes some decision-

making parameters (here, the input weights $\boldsymbol{w}$) to maximize their performance. Here we will

instead consider it as an inference problem in which the decision maker aims to identify the

decision-making parameters that are most compatible with the provided observations. These two

views are not necessarily incompatible. For example, minimizing the mean squared error of a

linear model (an optimization problem) yields the same solution as sequential Bayesian linear
regression (an inference problem) (26). In fact, as we show in the SI, our learning problem can
also be formulated as an optimization problem. Nonetheless, we here take the learning-by-
inference route, as it provides a statistical interpretation of the involved quantities, which provides
additional insights. Specifically, we focus on learning the weights while keeping the diffusion
model boundaries fixed. The decision maker's reward rate (i.e., average number of correct
choices per unit time), which we use as our performance measure, depends on both weights and
the chosen decision boundaries. However, to isolate the problem of weight learning, we fix the
boundaries such that a particular set of optimal weights $\boldsymbol{w}^*$ maximize this reward rate. The aim of
weight learning is to find these weights. Weight learning is a problem that needs to be solved
even if the decision boundaries are optimized at the same time. We have addressed how to best
tune these boundaries elsewhere (8, 27).

To see how learning can be treated as inference, consider the following scenario. Before
having observed any evidence, the decision maker has some belief, $p(\boldsymbol{w})$, about the input
weights, either as a prior or formed through previous experience. They now observe new
evidence, $\delta\boldsymbol{x}_1, \delta\boldsymbol{x}_2, ...$ and use the mean of the belief over weights, $\langle\boldsymbol{w}\rangle$ (or any other statistics), to
combine this evidence and to trigger a choice y once the combined evidence reaches one of the
decision boundaries. Upon this choice, they receive feedback y^* about which choice was the
correct one. Then, the best way to update the belief about $\boldsymbol{w}$ in light of this feedback is by Bayes'
rule,
198

$$p(\boldsymbol{w}|\boldsymbol{x}(t), t, y^*) \propto p(y^*|\boldsymbol{w}, \boldsymbol{x}(t), t)p(\boldsymbol{w}), \qquad (3)$$

199
where we have replaced the stream of evidence $\delta\boldsymbol{x}_1, \delta\boldsymbol{x}_2, ...$ by the previously established
sufficient statistics $\boldsymbol{x}(t)$ and t.

The likelihood $p(y^*|\boldsymbol{w}, \boldsymbol{x}(t), t)$ expresses for any hypothetical weight vector $\boldsymbol{w}$ the
probability that the observed evidence makes y^* the correct choice. To find its functional form,
consider that, for a known weight vector, we have shown that $p(\mu \geq 0|\boldsymbol{w}, \boldsymbol{x}(t), t)$, given by Eq. (2),
expresses the probability that $y = 1$ (associated with $\mu \geq 0$) is the correct choice. Therefore, $1 -$
$p(\mu \geq 0|\boldsymbol{w}, \boldsymbol{x}(t), t)$ corresponds to the probability that $y = -1$ (associated with $\mu < 0$) is the correct
choice. Therefore, it can act as the above likelihood function, which, by Eq.(2), is given by
$p(y^*|\boldsymbol{w}, x(t), t) = \Phi(y^*\boldsymbol{w}^T\widetilde{\boldsymbol{x}}(t))$, where we have used $1 - \Phi(a) = \Phi(-a)$. In summary, the decision
maker's belief is optimally updated after each choice by
210

$$p(\boldsymbol{w}|\boldsymbol{x}(t), t, y^*) \propto \Phi\big(y^* \boldsymbol{w}^T \widetilde{\boldsymbol{x}}(t)\big)p(\boldsymbol{w}). \tag{4}$$

This update equation only requires knowing the accumulated evidence $\boldsymbol{x}(t)$, decision time t, and
feedback y^*, but is independent of the chosen option y, and how the decision maker came to this
choice. As a matter of fact, the decision maker could make random choices, irrespective of the
accumulated evidence, and still learn $\boldsymbol{w}$ according to the above update equation, as long as they
keep track of $\boldsymbol{x}(t)$ and t, and acknowledge the feedback y^*. Therefore, learning and decision-
making aren't necessarily coupled. Nonetheless, we assume for all simulations that decision
makers perform decisions by using the mean estimate $\langle \boldsymbol{w} \rangle$, which is an intuitively sensible choice
if the decision maker's aim is to maximize their reward rate (see SI).

As in Eq. (4) the likelihood parameters, $\boldsymbol{w}$, are linear within a cumulative Gaussian
function, such problems are known as *Probit Regression* and don't have a closed-form expression
for the posterior. We could proceed by sampling from the posterior by Markov Chain Monte Carlo
methods, but that would not provide much insight into the different factors that modulate learning
the posterior weights. Instead, we proceed by deriving a closed-form approximation to this
posterior to provide such insight, as well as a potential mechanistic implementation.

Confidence controls the learning rate

To find an approximation to the posterior in Eq. (4), let us assume the prior to be given by the
Gaussian distribution, $p(\boldsymbol{w}) = N(\boldsymbol{w}|\boldsymbol{\mu}_w, \boldsymbol{\Sigma}_w)$, with mean $\boldsymbol{\mu}_w$ and covariance $\boldsymbol{\Sigma}_w$, which is the
maximum entropy distribution that specifies the mean and covariance (28). First, we investigated
how knowing $\boldsymbol{w}$ with limited certainty, as specified by $\boldsymbol{\Sigma}_w$, impacts the decision confidence.
Marginalizing over all possible $\boldsymbol{w}$'s (see Methods) resulted in the choice confidence to be given
by

$$p(y|x(t), t) = \Phi\left(\frac{y \boldsymbol{\mu}_w^T \widetilde{\boldsymbol{x}}(t)}{\sqrt{1 + \widetilde{\boldsymbol{x}}^T \boldsymbol{\Sigma}_w \widetilde{\boldsymbol{x}}}}\right). \tag{5}$$

Compared to Eq. (2), the choice confidence is additionally attenuated by $\boldsymbol{\Sigma}_w$. Specifically, higher
weight uncertainty (i.e., an overall larger covariance $\boldsymbol{\Sigma}_w$) results in a lower decision confidence,
as one would intuitively expect (**Fig. 1c**).

Next, we found a closed-form approximation to the posterior, Eq. (4). For repeated
learning across consecutive decisions, the posterior over the weights after the previous decision

becomes the prior for the new decision. Unfortunately, a direct application of this principle would
lead to a posterior that changes its functional form after each update, making it intractable. We
instead used *Assumed Density Filtering* (ADF) (26, 29) that posits a fixed functional form
$q(\boldsymbol{w}|y^*, \boldsymbol{x}(t), t) = \mathrm{N}(\boldsymbol{w}|\boldsymbol{\mu}_w^*, \boldsymbol{\Sigma}_w^*)$ of the posterior density – in our case Gaussian for consistency with
the prior – and then finds the posterior parameters $\boldsymbol{\mu}_w^*$ and $\boldsymbol{\Sigma}_w^*$ that make this approximate
posterior best match the "true" posterior $p(\boldsymbol{w}|y^*, \boldsymbol{x}(t), t)$, Eq. (4). Performing this match by
minimizing the Kullback-Leiber divergence $\mathrm{KL}(p|q)$ results in the posterior mean (30, 31)
248

$$\boldsymbol{\mu}_w^* = \boldsymbol{\mu}_w + \frac{\xi_w}{\sqrt{1 + \widetilde{\boldsymbol{x}}^T \boldsymbol{\Sigma}_w \widetilde{\boldsymbol{x}}}} y^* \boldsymbol{\Sigma}_w \widetilde{\boldsymbol{x}}, \tag{6}$$

and a similar expression for the posterior covariance (see Methods). Choosing $KL(p|q)$ to
measure the distance between p and q is to some degree arbitrary, but has beneficial properties,
such as that it causes the first two moments of q to match those of p (see SI). In Eq. (6), the factor
ξ_w modulates how strongly this mean is updated towards $y^* \boldsymbol{\Sigma}_w \widetilde{\boldsymbol{x}}$, and turns out to be a
monotonically decreasing function of decision confidence (**Fig. 1d**, top; see Methods for
mathematical expression). For incorrect choices, for which the decision confidence is
$p(y^*|\boldsymbol{x}(t), t) < 1/2$, ξ_w is largest for choices made with high confidence, promoting significant
weight adjustments. For low-confidence choices it only promotes moderate adjustments, notably
irrespective of whether the choice was correct or incorrect. High-confidence, correct choices yield
a low ξ_w, and thus an intuitively minor strategy update. The update of the posterior covariance
follows a similar confidence-weighted learning rate modulation (**Fig. S1**; Methods).
Decision confidence is not the only factor that impacts the learning rate in Eq. (6). For
instance, $\widetilde{\boldsymbol{x}}$ shrinks for longer, less confidence choices (because it is inversely proportional to
time) and results in overall less learning. Less certain weights, associated with larger magnitudes
of $\boldsymbol{\Sigma}_w$, have a similar effect. To investigate the overall impact of all of these factors combined on
the learning rate, we simulated a long sequence of consecutive choices and plotted the learning
rate for a random subset of these trials against the decision confidence (**Fig. 1d**, bottom). This
plot revealed a slight down-weighting of the learning rate for low-confidence choices when
compared to ξ_w, but left the overall dependency on ξ_w otherwise unchanged.

Performance comparison to optimal inference and to simpler heuristics

The intuitions provided by near-optimal ADF learning are only informative if its approximations do not cause a significant performance drop. We quantified this drop by comparing ADF performance to that of the Bayes-optimal rule, as found by Gibbs sampling (see Methods). Gibbs sampling is biologically implausible as it requires a complete memory of inputs and feedbacks for past decisions and is intractable for longer decision sequences, but nonetheless provides an optimal baseline to compare against. We furthermore tested the performance of two additional approximations. One was an ADF variant that assumes a diagonal covariance matrix Σ_w, yielding a local learning rule that could be implemented by the nervous system. This variant furthermore reduced the number of parameters from quadratic to linear in the size of w. The second was a second-order Taylor expansion of the log-posterior, resulting in a learning rule similar to ADF, but with a lower impact of weight uncertainty on the learning rate (see Methods).

Furthermore, we tested if simpler learning heuristics can match ADF performance. We focused on three rules of increasing complexity. The *delta rule*, which can be considered a variant of temporal-difference learning, or reinforcement learning (32), updates its weight estimate after the nth decision by

$$w_{n+1} = w_n + \frac{\alpha}{2\theta(0)}(y_n^*\theta(t) - x_n(t)^T w_n)x_n(t), \qquad (7)$$

where $y_n^* \in \{-1,1\}$ is the feedback about the correct choice provided after this decision, and we have chosen to normalize the learning rate α by the initial bound height $\theta(0)$ to make it less sensitive to this chosen height. As decisions are triggered at one of the two boundaries, $x_n(t)^T w_n \in \{-\theta(t), \theta(t)\}$, the residual in brackets is zero for correct choices, and $\pm 2\theta(t)$ for incorrect choices. As a result, and in contrast to ADF, weight adjustments are only performed after incorrect choices, and with a fixed learning rate α rather than one modulated by confidence (**Fig. 1d**; right). Our simulations revealed that the delta rule excessively and suboptimally decrease in the weight size $\|w\|$ over time, leading to unrealistically long reaction times and equally unrealistic near-zero weights. To counteract this problem, we designed a *normalized delta rule*, that updates the weight estimates as the delta rule, but thereafter normalizes them by $w \leftarrow w \|w^*\|/\|w\|$ to ensure that its size matches that of the true weights w^*. Access to these true weights, w^*, makes it an omniscient learning rule that can't be implemented by a decision maker

300   in practice. Lastly, we tested a learning rule that performs stochastic gradient ascent on the
301   feedback log-likelihood,

$$\boldsymbol{w}_{n+1} = \boldsymbol{w}_n + \alpha \nabla_w \log p(y_n^* | \boldsymbol{w}_n, \boldsymbol{x}_n(t), t) = \boldsymbol{w}_n + \alpha y_n^* \xi_w \tilde{\boldsymbol{x}}_n(t). \tag{8}$$

This rule introduces decision confidence weighting through ξ_w, but differs from ADF in that it does
not take the weight uncertainty (Σ_w in ADF) into account, and requires tuning of the learning rate
parameter α.

We evaluated the performance of these learning rules by simulating weight learning
across 1,000 consecutive decisions (called *trials*; see Methods for details) in a task in which use
of the optimal weight vector maximizes the reward rate. This reward rate was the average reward
for correct choices minus some small cost for accumulating evidence over the average time
across consecutive trials and is a measure we would expect rational decision makers to optimize.
For each learning rule we found its reward rate relative to random behavior and optimal choices.

Figure 2. Input weight learning and tracking performance of different learning rules. All plots show the relative reward rate (0 =
immediate, random choices, 1 = optimal) averaged over 5,000 simulations with different true, underlying weights, and for 2 (top) and
50 (bottom) inputs. (**a**) The relative reward rate for probabilistic and heuristic learning rules. The probabilistic learning rules include
the optimal rule (Gibbs sampling), assumed density filtering (ADF), ADF with a diagonal covariance matrix (ADF (diag)), and a learning
rule based on a second-order Taylor expansion of the log-posterior (Taylor exp.). For both 2 and 50 inputs, all rules perform roughly
equally. For the heuristic rules, different color shadings indicate different learning rates. The initial performance shown is that *after* the
first application of the learning rule, such that initial performances can differ across learning rule. (**b**) The steady-state performance
across different heuristic rule learning rates. Steady state performance was measured as an average across 5,000 simulations,
averaging over the last 100 of 1000 simulated trials in which the true weights slowly change across consecutive trials. An optimal
relative reward rate of one corresponds to knowing the true weight in each trial, which, due to the changing weight, is not achievable
in this setup. The color scheme is the same as in (**a**), but the vertical axis has a different scale. The delta rule did not converge and
was not included in (**b**).

Figure 2a shows this relative reward rate for all learning rules and different numbers of
inputs. As can be seen, the performance of ADF and the other probabilistic learning rules is

indistinguishable from Bayes-optimal weight learning for all tested numbers of inputs. Surprisingly,

the ADF variant that ignores off-diagonal covariance entries even outperformed Bayes-optimal

learning for a large number of inputs (**Fig. 2a**, yellow line for 50 inputs). That reason that a simpler

learning rule could outperform the rule deemed optimal by Bayesian decision theory is that this

simpler rule has less parameters and a simpler underlying model that was nonetheless good

enough to learn the required weights. Learning fewer parameters with the same data resulted in

initially better parameter estimates, and better associated performance. Conceptually, this is

similar to a linear model outperforming a quadratic model when fitting a quadratic function if little

data is available, and if the function is sufficiently close to linear (as illustrated in Fig. S2). Once

more data is available, the quadratic model will outperform the linear one. Similarly, the Bayes-

optimal learning rule will outperform the simpler one once more feedback has been observed. In

our simulation, however, this does not occur within the 1000 simulated trials.

All other learning heuristics performed significantly worse. For low-dimensional input, the

delta rule initially improved its reward rate but worsens it again at a later stage across all learning

rates. The normalized delta rule avoided such performance drops for low-dimensional input, but

both delta rule variants were unable to cope with high-dimensional inputs. Only stochastic

gradient ascent on the log-likelihood provided a stable learning heuristic for high dimensional

inputs, but with the downside of having to choose a learning rate. Small learning rates lead to

slow learning, and an associated slower drop in angular error. Overall, the probabilistic learning

rules significantly outperformed all tested heuristic learning rules and matched (and in one case

even exceeded) the weight learning performance of the Bayes-optimal estimator.

Tracking non-stationary input weights

So far, we have tested how well our weight learning rule is able to learn the true, underlying

weights from binary feedback about the correctness of the decision maker's choices. For this we

assumed that the true weights remained constant across decisions. What would happen if these

weights change slowly over time? Such a scenario could occur if, for example, the world around

us changes slowly, or if the neural representation of this world changes slowly through neural

plasticity or similar. In this case, the true weights would become a moving target that we would

never be able to learn perfectly. Instead, we would after some initial transient expect to reach

steady-state performance that remains roughly constant across consecutive decisions. We

compared this steady-state performance of Bayes-optimal learning (now implemented by a

particle filter) to that of the probabilistic and heuristic learning rules introduced in the previous

section. The probabilistic rules were updated to take into account such a trial-by-trial weight

change, as modeled by a first-order autoregressive process (see Methods). The heuristic rules

remained unmodified, as their use of a constant learning rate already encapsulates the

assumption that the true weights change across decisions.

Figure 2b illustrates the performance of the different learning rules. First, it shows that,

for low-dimensional inputs the various probabilistic models yield comparable performances, but

for high-dimensional inputs the approximate probabilistic learning rules outperform Bayes-optimal

learning. In case of the latter, these approximations weren't actually harmful, but instead

beneficial, for the same reason discussed further above. In particular, the more neurally-realistic

ADF variant that only tracked the diagonal of the covariance matrix again outperformed all other

probabilistic models. Second, only the heuristic learning rule that performed gradient ascent on

the log-likelihood achieved steady-state performance comparable to the approximate probabilistic

rules, and then only for high input dimensionality and a specific choice of learning rate. This should

come as no surprise, as its use of the likelihood function introduces more task structure

information than the other heuristics use. The delta rule did not converge and therefore never

achieved steady-state performance. Overall, the ADF variant that focused only on the diagonal

covariance matrix achieved the best overall performance.

Learning both weights and a latent state prior bias

Our learning rule can be generalized to learn prior biases in addition to the input weights. The

prior we have used so far for the latent variable, $\mu \sim \mathrm{N}\!\left(0, \sigma_\mu^2\right)$, is unbiased, as both $\mu \geq 0$ and $\mu <$

0 are equally likely. To introduce a prior bias, we instead used $\mu \sim \mathrm{N}\!\left(m, \sigma_\mu^2\right)$, where m controls

the bias through $P^+ \equiv p(\mu \geq 0) = \Phi\!\left(m/\sigma_\mu\right)$. A positive (or negative) m causes $P^+ > 1/2$ (or $<$

$1/2$), thus making $y = 1$ (or $y = -1$) the more likely correct choice even before evidence is

accumulated. After evidence accumulation, such a prior results in the posterior

$$p(\mu \geq 0 | \boldsymbol{w}, \boldsymbol{x}(t), t) = \Phi\left(\frac{\boldsymbol{w}^T\boldsymbol{x}(t) + \sigma_\mu^{-2}m}{\sqrt{t + \sigma_\mu^{-2}}}\right). \tag{9}$$

390   Comparing this to the unbiased posterior Eq. (2) reveals the additional term $\sigma_\mu^{-2}m$ whose relative

391   influence wanes over time.

393
Figure 3. Decision confidence, prior biases, and the relation between decision boundary and choice. (**a**) For an unbiased prior
(i.e., $P^+ \equiv p(\mu \geq 0) = 1/2$), the decision confidence (color gradient) is symmetric around $z = 0$ for each fixed time t. The associated
posterior belief $p(\mu \geq 0|z(t), t)$ (numbers above/below "time" axis label; constant along white lines; ½ along light blue line) promote
choosing $y = 1$ and $y = -1$ above (blue area in (**b**)) and below (red area in (**b**)) $z = 0$. (**b**) As a result, different choices are Bayes-
optimal at the blue/red decision boundaries, as long as they are separated by $z = 0$, irrespective of the boundary separation (solid vs.
dashed blue red lines). (**c**) If the prior is biased by an overall shift, the decision confidence is counter-shifted by the same constant
across all t. In this case, both decision boundaries might promote the same choice, which can be counter-acted by a time-invariant
shift of z by $C_1(P^+)$. (**d**) If the prior is biased by boosting one side while suppressing the other, the decision confidence shift becomes
time-dependent, such that the optimal choice at a time-invariant boundary might change over time. Counteracting this effect requires
a time-dependent shift of z by $C_2(P^+, t)$. In both (**c**) and (**b**) we have chosen $P^+ = 0.6$, for illustration.

This additional term has two consequences. First, appending the elements m and σ_μ^{-2} to
the vectors $\boldsymbol{w}$ and $\boldsymbol{x}(t)$, respectively, shows that $\boldsymbol{w}$ and m can be learned jointly by the same
learning rule we have derived before (Methods). Second, the term requires us to rethink the
association between decision boundaries and choices. As **Fig. 3c** illustrates, such a prior causes
a time-invariant shift in the association between the accumulated evidence, $z(t) = \boldsymbol{w}^T \boldsymbol{x}(t)$, and
the posterior belief of $\mu \geq 0$ and corresponding decision confidence. This shift makes it possible
to have the same Bayes-optimal choice at both decision boundaries (**Fig. 3c**, blue/red decision
areas). Hence, we have lost the mechanistically convenient unique association between decision
boundaries and choices. We recover this association by a boundary counter-shift, such that these
boundaries come to lie at the same decision confidence levels for opposite choices, making them
asymmetric around $z = 0$. Mathematically, this is equivalent to shifting the evidence accumulation
starting point, $\tilde{z}(0)$ away from zero in the opposite direction (**Fig. 3c**, shift by $C_1(P^+) = \sigma_\mu^{-2}m$; SI).
Therefore, a prior bias is implemented by a bias-dependent simple shift of the accumulation

- 14 -

starting point, leading to a mechanistically straight-forward implementation of Bayes-optimal
decision-making with biased priors.

A consequence of the shifted accumulation starting point is that, for some fixed decision
time t, the decision confidence at both boundaries is the same (**Fig. 3c** right). This seems at odds
with the intuition that a biased prior ought to bias the decision confidence in favor of the more
likely option. However, this mechanism does end up assigning higher average confidence to the
more likely option because of reactions times. As the starting point is now further away from the
less likely correct boundary, it will on average take longer to reach this boundary, which lowers
the decision confidence since confidence decreases with elapsed time. Therefore, even though
the decision confidence at both boundaries is the same for the given decision time, it will on
average across decision times be lower for the a-priori non-preferred boundary, faithfully
implementing this prior (see SI for a mathematical demonstration).

Our finding that a simple shift in the accumulation starting point is the Bayes-optimal
strategy appears at odds with previous work that suggested that the optimal shift of the
accumulator variable $z(t)$ varies with time (18). This difference stems from a different
implementation of the bias. While we have chosen an overall shift in the prior by its mean (**Fig.
3c**), an alternative implementation is to multiply $p(\mu \geq 0)$ by P^+, and $p(\mu < 0)$ by $1 - P^+$ (**Fig. 3d**),
again resulting in $P^+ = p(\mu \geq 0)$. A consequence of this difference is that the associated shift of
the posterior belief of $\mu \geq 0$ in the evidence accumulation space becomes time-dependent. Then,
the optimal choice at a time-invariant boundary in that space might change over time (**Fig. 3d**).
Furthermore, un-doing this shift to regain a unique association between boundaries and choices
not only requires a shifted accumulation starting point, but additionally a time-dependent additive
signal ($C_2(P^+, t)$ in **Fig. 3d**; SI), as was proposed in (18). Which of the two approaches is more
adequate depends on how well it matches the prior implicit in the task design. Our approach has
the advantage of a simpler mechanistic implementation, as well as yielding a simple extension to
the previously derived learning rule. How learning prior biases in the framework of (18) could be
achieved remains unclear (but see (33)).

Sequential choice dependencies due to continuous weight tracking

Figure 4. Sequential choice dependencies due to continuous learning, and effects of noisy feedback. Bayes-optimal learning in a slowly changing environment predicts sequential choice dependencies with the following pattern. (**a**) After hard, correct choices (low prev. $|\mu|$; light colors), the psychometric curve is shifted towards repeating the same choice (blue/red = choice $y = 1/-1$). This shift decreases after easier, correct choices (high prev. $|\mu|$; dark colors). (**b**) We summarize these tuning curve shifts in the repetition bias, which is the probability of repeating the same choice to a $\mu = 0$ stimulus (example green arrow for $\mu = -0.38$ in (**a**)). After correct/incorrect choices (green/red curve), this leads to a win-stay/lose-switch strategy. Only the win-stay strategy is shown in (**a**). (**c**) If choice feedback is noisy (inverted with probability β), the learning rate becomes overall lower. In particular for high-confidence choices with "incorrect" feedback, the learning rate becomes zero, as the learner trusts her choice more than the feedback.

In every-day situations, no two decisions are made under the exact same circumstances. Nonetheless, we need to be able to learn from the outcome of past choices to improve future ones. A common assumption is that past choices become increasingly less informative about future choices over time. One way to express this formally is to assume that the world changes slowly over time – and that our aim is to track these changes. By 'slow' we mean that we can consider it constant over a single trial but that it is unstable over the course of an hour-long session. We implemented this tracking of the moving world, as in **Fig. 2b**, by slowly allowing the weights mapping evidence to decisions to change. With such continuously changing weights, weight learning never ends. Rather, the input weights are continuously adjusted to make correct choices more likely in the close future. After correct choices, this means that weights will be adjusted to repeat the same choice upon observing a similar input in the future. After incorrect choices, the aim is to adjust the weights to perform the opposite choice, instead. Our model predicts that, after an easy correct choice, in which confidence can be expected to be high, the weight adjustments are lower than after hard correct choices (see **Fig. 1d** top, green line). As a consequence, we would expect the model to be more likely to repeat the same choices after correct and hard, than after correct and easy trials.

To test this prediction, we relied on the same simulation to generate **Fig. 2b** to measured how likely the model repeated the same choice after correct decisions. **Figure 4a** illustrates that this repetition bias manifests itself in a shift of the psychometric curve that makes it more likely to repeat the previous choice. Furthermore, and as predicted, this shift is modulated by the difficulty of the previous choice and is stronger if the previous choice was easy (i.e., associated with a large $|\mu|$; **Fig. 4b**). Therefore, if the decision maker expects to operate in a volatile, slowly changing world, our model predicts a repetition bias to repeat the same choices after correct decisions, and that this bias is stronger if the previous choice was easy.

Unreliable feedback reduces learning

What would occur if choice feedback is less-than-perfectly reliable? For example, the feedback

itself might not be completely trustworthy, or hard to interpret. We simulated this situation by

assuming that the feedback is inverted with probability β. Here, $\beta = 0$ implies the so far assumed

perfectly reliable feedback, and $\beta = 1/2$ makes the feedback completely uninformative. This

change impacts how decision confidence modulates the learning rate (**Fig. 4c**) as follows. First,

it reduces the overall magnitude of the correction, with weaker learning for higher feedback noise.

Second, it results in no learning for highly confident choices that we are told are incorrect. In this

case, one's decision confidence overrules the unreliable feedback. This stands in stark contrast

to the optimal learning rule for perfectly reliable feedback, in which case the strongest change to

the current strategy ought to occur.

Discussion

Diffusion models are applicable to model decisions that require some accumulation of evidence

over time, which is almost always the case in natural decisions. We extended previous work on

the normative foundations of these models to more realistic situations in which the sensory

evidence is encoded by a population of neurons, as opposed to just two neurons, as has been

typically assumed in previous studies. We have focused on normative and mechanistic models

for learning the weights from the sensory neurons to the decision integrator without additionally

adjusting the decision boundaries, as weight learning is a problem that needs to be solved even

if the decision boundaries are optimized at the same time.

From the Bayesian perspective, weight learning corresponds to finding the weight

posterior given the provided feedback, and resulted in an approximate learning rule whose

learning rate was strongly modulated by decision confidence. It suppressed learning after high-

confidence correct decisions, supported learning for uncertain decisions irrespective of their

correctness, and promoted strong change of the combination weights after wrong decisions that

were made with high confidence (**Fig. 1d**). Evidence for such confidence-based learning has

already been identified in human experiments (34), but not in a task that required the temporal

accumulation of evidence in individual trials. Indeed, as we have previously suggested (22), such

a modulation by decision confidence should arise in all scenarios of Bayesian learning in N-AFC

tasks in which the decision maker only receives feedback about the correctness of their choices,

rather than being told which choice would have been correct. In the 2-AFC task we have

considered, being told that one's choice was incorrect automatically reveals that the other choice

was correct, making the two cases coincide. Moving from one-dimensional to higher-dimensional

inputs requires performing the accumulation of evidence for each input dimension separately (**Fig.**

1b; Eqs. (6) & (12) require $\boldsymbol{x}(t)$ rather than only $\boldsymbol{w}^T\boldsymbol{x}(t)$), even if triggering choices only requires

a linear combination of $\boldsymbol{x}(t)$. This is because uncertain input weights require keeping track of how

each input dimension contributed to the particle crossing the decision boundary in order to

correctly improve these weights upon feedback (i.e., proper credit assignment). The multi-

dimensional evidence accumulation predicted by our work arises naturally if inputs encode full

distributions across the task-relevant variables, such as in linear probabilistic population codes

(35) that trigger decisions by bounding the pooled activity of all units that represent the

accumulated evidence (36).

Continual weight learning predicts sequential choice dependencies that make the

repetition of a previous, correct choice more likely, in particular if this choice was difficult (**Fig. 4**).

Thus, based on assuming a volatile environment that promotes a continual adjustment of the

decision-making strategy, we provide a rational explanation for sequential choice dependencies

that are frequently observed in both humans and animals (e.g., 37, 38). In rodents making

decisions in response to olfactory cues we have furthermore confirmed that these sequential

dependencies are modulated by choice difficulty, and that the exact pattern of this modulation

depends on the stimulus statistics, as predicted by our theory (39) (but consistency with (40)

unclear).

Lastly, we have clarified how prior biases ought to impact Bayes-optimal decision-making

in diffusion models. Extending the work of Hanks et al. (18), we have demonstrated that the exact

mechanisms to handle these biases depend on the specifics of how these biases are introduced

through the task design. Specifically, we have suggested a variant that simplifies these

mechanisms and the learning of this bias. This variant predicts that the evidence accumulation

offset, that has previously been suggested to be time-dependent, to become independent of time,

and it would be interesting to see if LIP activity of monkeys performing the random-dot motion

task, as recorded by Hanks et al. (but see (41)), would change accordingly.

Materials and Methods

We here provide an outline of the framework and its results. Detailed derivations are provided in

the SI.

Bayesian decision-making with one and multi-dimensional diffusion models

We assume the latent state to be drawn from $\mu \sim N(m, \sigma_\mu^2)$, and the momentary evidence in each

time step δt to provide information about this latent state by $\delta z_i | \mu \sim N(\mu \delta t, \delta t)$. The aim is to infer

the sign of μ, and choose $y = 1$ if $\mu \geq 0$, and $y = -1$ otherwise. After having observed this

evidence for some time $t \equiv n\delta t$, the posterior μ given all observed evidence $\delta z_{1:n}$ is by Bayes'

rule given by

$$p(\mu | \delta z_{1:n}) \propto N(\mu | m, \sigma_\mu^2) \prod_{i=1}^{n} N(\delta z_i | \mu \delta t, \delta t) \propto N\left(\mu \Big| \frac{\sigma_\mu^{-2} m + z(t)}{\sigma_\mu^{-2} + t}, \frac{1}{\sigma_\mu^{-2} + t}\right). \qquad (11)$$

In the above, all proportionalities are with respect to μ, and we have defined $z(t) = \sum_{i=1}^{n} \delta z_i$ and

have used $t = \sum_{i=1}^{n} \delta t$. How to find the posterior belief for about μ's sign with $m = 0$ is described

around Eq. (1).

We extend diffusion models to multi-dimensional inputs with momentary evidence

$\delta x_i | \mu, w \sim N((a\mu + b)\delta t, \Sigma \delta t)$, with a, b and Σ chosen such that $w^T x(t) | \mu = z(t) | \mu \sim N(\mu t, t)$, as

before. The posterior over μ and $\mu \geq 0$ is the same as for the one-dimensional case, with $z(t)$

replaced by $w^T x(t)$. Definining $\widetilde{x}(t) = x(t)/\sqrt{\sigma_\mu^{-2} + t}$, we find $p(\mu \geq 0 | w, x(t), t) = \Phi(w^T \widetilde{x}(t))$. As

$y = 1$ and $y = -1$ correspond to $\mu \geq 0$ and $\mu < 0$, and $y = 1$ is only chosen if $p(\mu \geq 0 | w, x(t), t) \geq$

$1/2$, the decision confidence for $m = 0$ at some boundary $w^T x(t) = \pm\theta(t)$ is given by

$\Phi\left(\theta(t)/\sqrt{\sigma_\mu^{-2} + t}\right)$. If input weights are unknown, and the decision maker holds belief $w \sim$

$N(\mu_w, \Sigma_w)$ about these weights, the decision confidence needs to additionally account for weight

uncertainty by marginalizing over w, resulting in Eq. (5).

Probabilistic and heuristic learning rules

We find the approximate posterior $q(w) = N(w | \mu_w^*, \Sigma_w^*)$ that approximates the target posterior p

Eq. (4) by Assumed Density Filter (ADF). This requires minimizing the Kullback-Leiber divergence

$KL(p|q)$ (26, 29), resulting in Eq. (6) for the posterior mean, and

$$\Sigma_w^* = \Sigma_w + \xi_{cov}(\gamma)((\Sigma_w^{-1} + \widetilde{x}\widetilde{x}^T)^{-1} - \Sigma_w), \qquad (12)$$

with learning rate modulators $\xi_w(\gamma) = N(\gamma | 0,1)/\Phi(\gamma)$ and $\xi_{cov}(\gamma) = \xi_w(\gamma)^2 + \xi_w(\gamma)\gamma$, and where

we have defined $\gamma \equiv y^* \mu_w^T \widetilde{x}/\sqrt{1 + \widetilde{x}^T \Sigma_w \widetilde{x}}$, which is monotonic in the decision confidence, Eq. (5).

Noisy choice feedback (**Fig. 4c**) changes the likelihood to assume reversed feedback with

probability β, and follow the same procedure as above to derive the posterior moments (see SI).

The ADF variant that only tracks the diagonal covariance elements assumes Σ_w to be diagonal,

and only computes the diagonal elements of Σ_w^*. A second-order Taylor expansion of the log of

Eq. (4) leads to update equations similar to Eqs. (6) and (12), but without the normalization by

weight uncertainty (see SI for details). All heuristic learning rules are described in the main text.

We modeled non-stationary input weights by $w_n|w_{n-1} \sim N(Aw_{n-1} + b, \Sigma_d)$ after a

decision in trial $n - 1$. This weight transition is taken into account by the probabilistic learning

rules by setting the parameter priors to $\mu_{w,n} = A\mu_{w,n-1}^* + b$ and $\Sigma_{w,n} = A\Sigma_{w,n-1}^* A^T + \Sigma_d$. For

stationary weights we have $A = I$, $b = 0$, and $\Sigma_d = 0$.

Bayes-optimal weight inference was for stationary weights performed by Gibbs sampling

for Probit models, and for non-stationary weights by particle filtering (see SI).

Simulation details

We used parameters $a = w/\|w\|^2$ and $b = 0$ for the momentary evidence δx. Its covariance Σ

was generated to feature eigenvalues that drop exponentially from $\sigma_x^2 = 2/\|w\|^2$ to zero until it

reaches a constant $\sigma_0^2 = 0.001/\|w\|^2$ noise baseline, as qualitatively observed in neural

populations. It additionally contains an eigenvector w with eigenvalue set to guarantee $w^T\Sigma w =$

1, limiting the information that δx provides about μ. For non-stationary weights, all momentary

evidence parameters are adjusted after each weight change (see SI). The diffusion model bounds

$\pm\theta$ were time-invariant and tuned to maximize the reward rate when using the correct weights.

The reward rate is given by $(p(correct) - c_{accum}\langle t \rangle)/(t_{iti} + \langle t \rangle)$, where averages where across

trials, and we used evidence accumulation cost $c_{accum} = 0.01$ and inter-trial interval $t_{iti} = 2s$. We

used $\sigma_\mu^2 = 3^2$ to draw μ in each trial, and drew w from $w \sim N(1, I)$ before each trial sequence. For

non-stationary weights, we re-sampled weight after each trial according to $w_n|w_{n-1} \sim N(\lambda w_{n-1} +$

$(1 - \lambda), \sigma_d^2 I)$, with decay factor $\lambda = 1 - 0.01$ and $\sigma_d^2 = 1 - \lambda^2$ to achieve steady-state mean **1** and

identity covariance.

To compare the weight learning performance of ADF to alternative models (**Fig. 2a**), we

simulated 1,000 learning trials 5,000 times, and reported the reward rate per trial averaged across

these 5,000 repetitions. To assess steady-state performance (**Fig. 2b**), we performed the same

procedure with non-stationary weights, and reported reward rate averaged over the last 100 trials,

and over 5,000 repetitions. The same 100 trials were used to compute the sequential choice

dependencies in **Fig. 4a/b**. To simulate decision-making with diffusion models and uncertain

weights, we used the current mean estimate $\langle w \rangle$ of the input weights to linearly combine the

momentary evidence. The probabilistic learning rules were all independent of the specific choice

of this estimate. The learning rate in **Fig. 1d** shows the pre-factor to $y^* \Sigma_w \widetilde{x}$ in Eq. (6) over decision

confidence for a subsample of the last 10,000 trials of a single 15,000 trial simulation with non-

stationary weights. For the Gibbs sampler, we drew 10 burn-in samples, followed by 200 samples

in each trial. For the particle filter we simulated 1,000 particles.

Acknowledgments

This work was supported by a James S. McDonnell Foundation Scholar Award (#220020462,

JD), and grants from the NIMH (R01MH115554, JD), the Swiss National Science Foundation,

www.snf.ch, (#31003A_143707 and #31003A_165831, AP), Champalimaud Foundation (ZFM),

European Research Council (Advanced Investigator Grant 250334 & 67125, ZFM), Human

Frontier Science Program (Grant RGP0027/2010, ZFM & AP), Simons Foundation (Grant

325057, ZFM & AP), and Fundação para a Ciência e a Tecnologia (AGM).

References

1. Doya K, Ishii S, Pouget A, Rao RPN (2006) *Bayesian Brain: Probabilistic Approaches to*
Neural Coding (MIT Press).

2. Ratcliff R (1978) A theory of memory retrieval. *Psychol Rev* 85(2):59–108.

3. Ratcliff R, McKoon G (2008) The diffusion decision model: theory and data for two-choice
decision tasks. *Neural Comput* 20(4):873–922.

4. Bogacz R, Brown E, Moehlis J, Holmes P, Cohen JD (2006) The physics of optimal
decision making: A formal analysis of models of performance in two-alternative forced-
choice tasks. *Psychol Rev* 113(4):700–765.

5. Ratcliff R, Smith PL (2004) A Comparison of Sequential Sampling Models for Two-Choice
Reaction Time. *Psychol Rev* 111(2):333–367.

6. Frazier PI, Yu AJ (2008) Sequential hypothesis testing under stochastic deadlines. *Adv*
Neural Inf Process Syst:1–8.

7. Tajima S, Drugowitsch J, Pouget A (2016) Optimal policy for value-based decision-making.
Nat Commun 7:12400.

8. Drugowitsch J, Moreno-Bote R, Churchland AK, Shadlen MN, Pouget A (2012) The cost of
accumulating evidence in perceptual decision making. *J Neurosci* 32(11):3612–3628.

9. Gold JI, Shadlen MN (2002) Banburismus and the brain: Decoding the relationship
between sensory stimuli, decisions, and reward. *Neuron* 36(2):299–308.

10.   Drugowitsch J, Deangelis GC, Klier EM, Angelaki DE, Pouget A (2014) Optimal
641   multisensory decision-making in a reaction-time task. *Elife* 2014(3):1–19.

642   11.   Dayan P, Kakade S, Montague PR (2000) Learning and selective attention. *Nat Neurosci*
643   3 Suppl(november):1218–1223.

644   12.   Dayan P, Yu AJ (2003) Uncertainty and learning. *IETE J Res* 49(2–3):171–181.

645   13.   Körding KP, Wolpert DM (2004) Bayesian integration in sensorimotor learning. *Nature*
646   427(6971):244–7.

647   14.   Courville AC, Daw ND, Touretzky DS (2006) Bayesian theories of conditioning in a
648   changing world. *Trends Cogn Sci* 10(7):294–300.

649   15.   Ratcliff R (1981) A theory of order relations in perceptual matching. *Psychol Rev*
650   88(6):552–572.

651   16.   Gomez P, Ratcliff R, Perea M (2008) The overlap model: A model of letter position coding.
652   *Psychol Rev* 115(3):577–600.

653   17.   Ratcliff R, Starns JJ (2013) Modeling confidence judgments, response times, and multiple
654   choices in decision making: Recognition memory and motion discrimination. *Psychol Rev*
655   120(3):697–719.

656   18.   Hanks TD, Mazurek ME, Kiani R, Hopp E, Shadlen MN (2011) Elapsed decision time
657   affects the weighting of prior probability in a perceptual decision task. *J Neurosci*
658   31(17):6339–6352.

659   19.   Moreno-Bote R (2010) Decision confidence and uncertainty in diffusion models with
660   partially correlated neuronal integrators. *Neural Comput* 22(7):1786–1811.

661   20.   Palmer J, Huk AC, Shadlen MN (2005) The effect of stimulus strength on the speed and
662   accuracy of a perceptual decision. *J Vis* 5(5):376–404.

663   21.   Berger JO (1993) *Statistical Decision Theory and Bayesian Analysis* (Springer). 2nd Editio.

664   22.   Pouget A, Drugowitsch J, Kepecs A (2016) Confidence and certainty: distinct probabilistic
665   quantities for different goals. *Nat Neurosci* 19(3):366–374.

666   23.   Averbeck BB, Latham PE, Pouget A (2006) Neural correlations, population coding and
667   computation. *Nat Rev Neurosci* 7(5):358–366.

668   24.   Moreno-Bote R, et al. (2014) *Information-limiting correlations* (Nature Publishing Group)
669   doi:10.1038/nn.3807.

670   25.   Kiani R, Shadlen MN (2009) Representation of Confidence Associated with a Decision by
671   Neurons in the Parietal Cortex. *Science (80-)* 324(5928):759–764.

26.   Bishop C (2006) *Pattern Recognition and Machine Learning* (Springer).

27.   Drugowitsch J, Deangelis GC, Angelaki DE, Pouget A (2015) Tuning the speed-accuracy

trade-off to maximize reward rate in multisensory decision-making. *Elife* 4(JUNE2015):1–
11.

28.   Cover TM, Thomas JA (2006) *Elements of Information Theory* (Wiley). 2nd Editio.

29.   Murphy KP (2012) *Machine Learning: a Probabilistic Perspective* (MIT Press).

30.   Graepel T, Quiñonero-Candela J, Borchert T, Herbrich R (2010) Web-Scale Bayesian
Click-Through Rate Prediction for Sponsored Search Advertising in Microsoft's Bing
Search Engine. *Proceedings of the 27th International Conference on Machine Learning*
(ICML-10)   Available   at:
http://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.165.5644&rep=rep1&
type=pdf%5Cnhttp://machinelearning.wustl.edu/mlpapers/paper_files/icml2010_GraepelC
BH10.pdf.

31.   Chu W, Zinkevich M, Li L, Thomas A, Tseng B (2011) Unbiased online active learning in
data streams. *Proceedings of the 17th ACM SIGKDD International Conference on*
Knowledge Discovery and Data Mining - KDD '11 (ACM Press, New York, New York, USA),
p 195.

32.   Sutton RS, Barto AG (2018) *Reinforcement learing: an introduction* (MIT Press). 2nd editio.

33.   Zylberberg A, Wolpert DM, Shadlen MN (2018) Counterfactual Reasoning Underlies the
Learning of Priors in Decision Making. *Neuron* 99(5):1083-1097.e6.

34.   Meyniel F, Dehaene S (2017) Brain networks for confidence weighting and hierarchical
inference during probabilistic learning. *Proc Natl Acad Sci* 114(19):E3859–E3868.

35.   Ma WJ, Beck JM, Latham PE, Pouget A (2006) Bayesian inference with probabilistic
population codes. *Nat Neurosci* 9(11):1432–8.

36.   Beck JM, et al. (2008) Probabilistic Population Codes for Bayesian Decision Making.
Neuron 60(6):1142–1152.

37.   Busse L, et al. (2011) The Detection of Visual Contrast in the Behaving Mouse. *J Neurosci*
31(31):11351–11361.

38.   Yu AJ, Cohen JD (2009) Sequential effects: Superstition or rational behavior? *Adv Neural*
Inf Process Syst 21:1873–80.

39.   Mendonça AG, et al. (2019) The impact of learning on perceptual decisions and its
implication for speed-accuracy tradeoffs. *bioRxiv*:1–64.

40.   Urai AE, Braun A, Donner TH (2017) Pupil-linked arousal is driven by decision uncertainty
and alters serial choice bias. *Nat Commun* 8:14637.

41.   Rao V, DeAngelis GC, Snyder LH (2012) Neural correlates of prior expectations of motion
in the lateral intraparietal and middle temporal areas. *J Neurosci* 32(29):10063–74.

Figure legends

Figure 1. Learning the input weights from feedback in diffusion models. In diffusion models, the input(s) provide at each point in time noisy evidence about the world's true state, here given by the drift μ. The decision maker accumulates this evidence over time (e.g., black example traces) to form a belief about μ. Bayes-optimal decisions choose according to the sign of the accumulated evidence, justifying the two decision boundaries that trigger opposing choices. (a) In standard diffusion models, the momentary evidence either arises directly from noisy samples of μ, or, as illustrated here, from a neuron/anti-neuron pair that codes for opposing directions of evidence. The illustrated example assumes a random dot task, in which the decision maker needs to identify if most of the dots that compose the stimulus are moving either to the left or to the right. The two neurons (or neural pools) are assumed to extract motion energy of this stimulus towards the right (top) and left (bottom), such that their difference forms the momentary evidence towards rightward motion. A decision is made once the accumulated momentary evidence reaches one of two decision boundaries, triggering opposing choices. (b) Our setup differs from that in (a) in that we assume the input information $\delta\boldsymbol{x}(t)$ to be encoded in a larger neural population whose activity is linearly combined with weights $\boldsymbol{w}$ to yield the one-dimensional momentary evidence, and that the decision maker aims to learn these weights from feedback about the correctness of her choices. (c) Decision confidence (i.e., the belief that the made choice was correct) in this kind of diffusion model drop as a function of time (horizontal axis) and with increased uncertainty about the input weights (different shades of blue). (d) For near-optimal learning, the learning rate (the term ξ_w in Eq. (6)) is modulated by decision confidence (top left). High-confidence decisions lead to little learning if correct (green, right), and strong learning if incorrect (red, left). Low-confidence decisions result in a moderate confidence-related learning rate term (top, center). The learning rate in 1000 simulated trials (bottom) shows that the overall learning rate preserves this trend, with an additional suppression of learning for low-confidence decisions. Other learning heuristics (e.g., the delta rule, right) do not modulate their learning by confidence.

Figure 2. Input weight learning and tracking performance of different learning rules. All plots show the relative reward rate (0 = immediate, random choices, 1 = optimal) averaged over 5,000 simulations with different true, underlying weights, and for 2 (top) and 50 (bottom) inputs. (a) The relative reward rate for probabilistic and heuristic learning rules. The probabilistic learning rules include the optimal rule (Gibbs sampling), assumed density filtering (ADF), ADF with a diagonal covariance matrix (ADF (diag)), and a learning rule based on a second-order Taylor

expansion of the log-posterior (Taylor exp.). For both 2 and 50 inputs, all rules perform roughly

equally. For the heuristic rules, different color shadings indicate different learning rates. The initial

performance shown is that after the first application of the learning rule, such that initial

performances can differ across learning rule. (b) The steady-state performance across different

heuristic rule learning rates. Steady state performance was measured as an average across 5,000

simulations, averaging over the last 100 of 1000 simulated trials in which the true weights slowly

change across consecutive trials. An optimal relative reward rate of one corresponds to knowing

the true weight in each trial, which, due to the changing weight, is not achievable in this setup.

The color scheme is the same as in (a), but the vertical axis has a different scale. The delta rule

did not converge and was not included in (b).

Figure 3. Decision confidence, prior biases, and the relation between decision boundary

and choice. (a) For an unbiased prior (i.e., $P^+ \equiv p(\mu \geq 0) = 1/2$), the decision confidence (color

gradient) is symmetric around $z = 0$ for each fixed time t. The associated posterior belief $p(\mu \geq$

$0|z(t), t)$ (numbers above/below "time" axis label; constant along white lines; ½ along light blue

line) promote choosing $y = 1$ and $y = -1$ above (blue area in (b)) and below (red area in (b)) $z =$

0. (b) As a result, different choices are Bayes-optimal at the blue/red decision boundaries, as long

as they are separated by $z = 0$, irrespective of the boundary separation (solid vs. dashed blue

red lines). (c) If the prior is biased by an overall shift, the decision confidence is counter-shifted

by the same constant across all t. In this case, both decision boundaries might promote the same

choice, which can be counter-acted by a time-invariant shift of z by $C_1(P^+)$. (d) If the prior is biased

by boosting one side while suppressing the other, the decision confidence shift becomes time-

dependent, such that the optimal choice at a time-invariant boundary might change over time.

Counteracting this effect requires a time-dependent shift of z by $C_2(P^+, t)$. In both (c) and (b) we

have chosen $P^+ = 0.6$, for illustration.

Figure 4. Sequential choice dependencies due to continuous learning, and effects of noisy

feedback. Bayes-optimal learning in a slowly changing environment predicts sequential choice

dependencies with the following pattern. (a) After hard, correct choices (low prev. $|\mu|$; light colors),

the psychometric curve is shifted towards repeating the same choice (blue/red = choice $y =$

$1/-1$). This shift decreases after easier, correct choices (high prev. $|\mu|$; dark colors). (b) We

summarize these tuning curve shifts in the repetition bias, which is the probability of repeating the

same choice to a $\mu = 0$ stimulus (example green arrow for $\mu = -0.38$ in (a)). After correct/incorrect

choices (green/red curve), this leads to a win-stay/lose-switch strategy. Only the win-stay strategy

is shown in (a). (c) If choice feedback is noisy (inverted with probability β), the learning rate

becomes overall lower. In particular for high-confidence choices with "incorrect" feedback, the

learning rate becomes zero, as the learner trusts her choice more than the feedback.