Finding decodable information that is read out in behaviour

Tijl Grootswagers[1,2,3,*] (tijl.grootswagers@sydney.edu.au)

Radoslaw M. Cichy[4] (rmcichy@zedat.fu-berlin.de)

Thomas A. Carlson[1,2] (thomas.carlson@sydney.edu.au)

*corresponding author

[1]School of Psychology, University of Sydney, NSW 2006, Australia

[2]ARC Centre of Excellence in Cognition and its Disorders, NSW 2109, Australia

[3]Department of Cognitive Science, Macquarie University, NSW 2109, Australia

[4]Department of Education and Psychology, Freie Universität Berlin, 14195 Berlin, Germany

Acknowledgements

This research was supported by an Australian Research Council Future Fellowship (FT120100816)

and an Australian Research Council Discovery project (DP160101300) awarded to T.A.C., and

a German Research Foundation grant (CI-241/1-1) awarded to R.M.C. The authors acknowledge

the University of Sydney HPC service for providing High Performance Computing resources. The

authors declare no competing financial interests.

Abstract

Multivariate decoding methods applied to neuroimaging data have become the standard in

cognitive neuroscience for unravelling statistical dependencies between brain activation patterns

and experimental conditions. The current challenge is to demonstrate that information decoded

as such by the experimenter is in fact used by the brain itself to guide behaviour. Here we

demonstrate a promising approach to do so in the context of neural activation during object

perception and categorisation behaviour. We first localised decodable information about visual

objects in the human brain using a spatially-unbiased multivariate decoding analysis. We then

related brain activation patterns to behaviour using a machine-learning based extension of signal

detection theory. We show that while there is decodable information about visual category

throughout the visual brain, only a subset of those representations predicted categorisation

behaviour, located mainly in anterior ventral temporal cortex. Our results have important

implications for the interpretation of neuroimaging studies, highlight the importance of relating

decoding results to behaviour, and suggest a suitable methodology towards this aim.

1 Introduction

Multivariate pattern analysis (MVPA), also called brain decoding, are a powerful tool to establish statistical dependencies between experimental conditions and brain activation patterns (Carlson, Schrater, & He, 2003; Cox & Savoy, 2003; Haxby et al., 2001; Haynes, 2015; Kamitani & Tong, 2005; Kriegeskorte, Goebel, & Bandettini, 2006). In these analyses, an implicit assumption often made by experimenters is that if information can be decoded, then this information is used by the brain in behaviour (de-Wit, Alexander, Ekroll, & Wagemans, 2016; Ritchie, Kaplan, & Klein, 2017). However, the decoded information could be different (e.g., epiphenomenal) from the signal that is relevant for the brain (de-Wit et al., 2016; Williams, Dang, & Kanwisher, 2007), highlighting the need to relate decoded information to behaviour. To address this, previous work has correlated decoding performances to behavioural accuracies (e.g., Bouton et al., 2018; Freud, Culham, Plaut, & Behrmann, 2017; Naselaris, Kay, Nishimoto, & Gallant, 2011; Raizada, Tsao, Liu, & Kuhl, 2010; van Bergen, Ji Ma, Pratte, & Jehee, 2015; Walther, Caddigan, Fei-Fei, & Beck, 2009; Williams et al., 2007). However, this does link decoding and behaviour at the level of individual experimental conditions. Another approach has been to compare neural and behavioural similarity structures (e.g., Bracci & op de Beeck, 2016; Cohen, Dennett, & Kanwisher, 2016; Grootswagers, Kennedy, Most, & Carlson, 2017; Haushofer, Livingstone, & Kanwisher, 2008; Mur et al., 2013; Proklova, Kaiser, & Peelen, 2016; Wardle, Kriegeskorte, Grootswagers, Khaligh-Razavi, & Carlson, 2016). While this approach allows to link behaviour and brain patterns at the level of single experimental conditions, it is unclear how this link carries over to decision making behaviour such as categorisation.

Recently, a novel methodological approach, called the distance-to-bound approach (Ritchie & Carlson, 2016), has been proposed to connect brain activity directly to perceptual decision-making behaviour at the level of individual experimental conditions. The rationale behind this approach

(Carlson, Ritchie, Kriegeskorte, Durvasula, & Ma, 2014; Kiani, Cueva, Reppas, & Newsome, 2014;

Philiastides & Sajda, 2006; Ritchie & Carlson, 2016) is that for decision-making tasks, the brain

applies a decision boundary to a neural activation space (DiCarlo & Cox, 2007). Similarly, MVPA

classifiers fit multi-dimensional hyperplanes to separate a neural activation space. The distance of

the input to a decision boundary reflects the ambiguity of the evidence for the decision (Green &

Swets, 1966) and thus predicts reaction times (Ashby, 2000; Ashby & Maddox, 1994). If for a

decision task (e.g., categorisation), the brain uses the same information as the MVPA classifier,

then the classifier's hyperplane reflects the brain's decision boundary. This in turn predicts that

distance to the classifier's hyperplane negatively correlates with reaction times for the decision

task. Carlson et al. (2014) demonstrated the promise of the distance-to-bound approach in a

region of interest based analysis using fMRI. Here we go beyond this work by using the distance-

to-bound method and a spatially unbiased approach to create maps of where in the brain

information can be used to guide behaviour.

2 Materials and Methods

In this study, we separately localised information that is decodable, and information that is

suitably formatted to guide behaviour in the context of decodable information about visual

objects and object categorisation behaviour. To ensure robustness and generality of our results,

we analysed in parallel two independent fMRI datasets (Cichy et al., 2014, 2016), with different

stimulus sets, and in relation to partly overlapping categorisation behaviours. Overall, this allowed

us to investigate the relationship between decodable information from brain activity and

categorisation behaviour for six different distinctions: animate versus inanimate, faces versus

bodies, human versus animal, tools versus not tools, food versus not food, and transport versus

not food. Note that the negative 'not-X' category was defined as all stimuli that did fall into one of

the aforementioned classes. Categorisation reaction times for those stimuli were collected on

Amazon's Mechanical Turk. In this section, we describe the two-step searchlight procedure used

to create decoding and correlation maps of areas involved in visual object categorisation.

2.1 Experimental design

Stimuli

Stimuli for experiment 1 consisted of 92 visual objects, segmented on a white background (Figure

1A). Stimuli consisted of animate and inanimate objects. The animate objects could be further

divided into faces, bodies, humans and animals. Inanimate objects consisted of natural (e.g.,

plants or fruits) and man-made items (e.g., tools or houses). The stimulus set for experiment 2

consisted of 118 visual objects on natural backgrounds (Figure 1C). A small proportion of the

objects (27) were animate. The inanimate objects included subcategories such as tools, or food

items. In both experiments, participants were presented with the visual object stimuli while

performing an orthogonal task at fixation. Stimuli were displayed at 2.9° (Experiment 1) and 4.0°

(Experiment 2) visual angle with 500 ms duration. Images were displayed (overlaid with a grey

fixation cross) for 500 ms in random order.

fMRI recordings

The first experiment (Cichy et al., 2014) had high resolution fMRI coverage of the ventral visual

stream (Figure 1B) from 15 participants with a 2 mm isotropic voxel resolution. The second

experiment (Cichy et al., 2016) had whole brain from 15 participants with a 3 mm isotropic voxel

resolution. In both experiments, at the start of a session, structural images were obtained using a

standard T_1-weighted sequence. fMRI data were aligned and coregistered to the T1 structural

image, and then normalized to a standard MNI template. General linear models were used to

compute t-values for each stimulus (92 and 118, respectively) against baseline.

Reaction time data

We obtained reaction times for the stimuli in multiple different categorisation contrasts (Figure 1A&B). For experiment 1, these were animate versus inanimate, face versus body, and human versus animal. For experiment 2, we tested animate versus inanimate, tool versus not tool, food versus not food, and transport versus not transport. The RTs were collected using Amazons Mechanical Turk (MTurk). For each of the categorisation contrasts, 50 unique participants performed a categorisation task using the same stimuli as were used in collecting the fMRI data. Participants were instructed to "Categorise the images as fast and accurate as possible using the following keys: (z for X, m for Y)", where X and Y would be replaced with the relevant categories (e.g., animate and inanimate) for the contrast. On each trial, an image was presented for 500ms, followed by a black screen until the participant's response (Figure 1C). The presentation order of the stimuli was randomized and stimuli did not repeat. This resulted in 50 reaction time values per exemplar (one for each participant). Each participant's reaction times were z-scored. Next, we computed the median reaction time (across participants) for each exemplar. his resulted in one reaction time value per exemplar, which were used in the rest of the study.

2.2 Statistical Analysis

Searchlight procedure

For each categorisation contrast and subject, we used a searchlight approach (Haynes et al., 2007; Kriegeskorte et al., 2006) to create maps of decoding accuracy and of correlations between distance to the classifier boundary and categorisation reaction times. In contrast to pre-defined ROI's, which are used to test a-priori hypotheses about the spatial origin of information in the brain, the searchlight results in a spatially unbiased map of decodable information. An overview of the approach is presented in Figure 1D.

To create the decoding accuracy maps, we used a standard searchlight decoding approach

(Grootswagers, Wardle, & Carlson, 2017; Haynes, 2015; Kriegeskorte et al., 2006; Pereira, Mitchell,

& Botvinick, 2009), as implemented in the CoSMoMVPA decoding toolbox (Oosterhof, Connolly, &

Haxby, 2016). In detail, at each spatial location (voxel) in an fMRI image, a support vector machine

(SVM) was used to classify visual object category based on local brain patterns, resulting in a map

of classification accuracies. We then determined the subset of the locations at which brain

patterns were suitably formatted for read-out by the brain using the distance-to-bound approach

(Ritchie & Carlson, 2016) in a second searchlight analysis. Analogous to the decoding analysis, at

each voxel, an SVM was trained to classify visual objects. Diverging at this point from the decoding

approach we did not test the classifier, but rather obtained the distance for each exemplar to the

hyperplane set by the SVM. We then correlated those distances to reaction times acquired in

separate categorisation tasks. The contribution of each category was assessed individually, by

performing the correlations separately for the two sides of the categorisation (e.g., one

correlation for animate and one for inanimate exemplars). For each categorisation task this

resulted in two correlation maps per subject. The maps of decoding accuracy and correlations

were assessed for significance at the group level using sign-rank tests for random-effects

inference. The results were thresholded at $p<0.05$, using the false discovery rate (FDR; (Benjamini

& Hochberg, 1995)) to correct for multiple comparisons at the voxel level.

Relating the results to topographical locations of the visual system

For each of the categorisation contrasts, we identified the locations of the significant voxels with

respect to ROIs of the visual system. The significant voxels in the decoding maps and correlation

maps were compared to probabilistic topographic maps of visual processing areas (Wang,

Mruczek, Arcaro, & Kastner, 2015), which represent for each voxel the visual area with the highest

probability. A percentage score for each ROI was then computed, reflecting the percentage of

voxels in this ROI that were significant at the group level. We obtained a bootstrapped distribution

of percentage scores for each ROI by repeating this procedure 10,000 times, while randomly

sampling the subjects with replacement and recomputing the group level statistics. We report the

5^{th}, 50^{th} and 95^{th} percentiles of this distribution. This approach allows quantifying the difference

between the number of decoding voxels and correlation voxels per visual ROI.

Figure 1. General experimental rationale. Stimuli (**A,C**) used to map fMRI brain responses and
brain coverage (**B,C**) for fMRI study 1 and 2 respectively. **E**. Acquisition of reaction times on object
categorisation tasks. Reaction times for categorisation contrasts were collected in a different pool
of participants than the ones participating in the fMRI experiment. On each trial, a stimulus was
displayed for 250ms, and participants categorised it into two categories (exemplarily here:
animate vs inanimate) by pressing one of two keys. **F.** The two-partite approach to separately
localize decodable information and information that is suitable for read out in behaviour. For both
parts, a local cluster of neighbouring voxels (i.e., searchlight) was used to train a linear support
vector machine (SVM) on an image category classification task (e.g., animacy). To localize
decodable information, the classifier was tested on left-out data, storing the classification
accuracy at the centre voxel of the searchlight. To localise information that was suitably formatted
for read-out in a categorisation task, the distances of objects to the classifier hyperplane were
correlated with the reaction times for the same object images on the same classification task.
Repeated for every voxel, this resulted for each subject in one map of decoding accuracies and
one of correlations. For visualisation, significant correlation voxels were superimposed on
significant decoding accuracy voxels, each showing group average values in significant voxels.

3 Results

We examined the relationship between decodable information and information that is suitably

formatted for read-out by the brain in the context of decodable information about visual objects

and object categorisation behaviour. We determined the relationship between decodable

information and behaviour separately. First, we determined where information about objects is

present in brain patterns using decoding in a standard fMRI searchlight decoding analysis (Haynes

et al., 2007; Kriegeskorte et al., 2006). We then determined the subset of the locations at which

brain patterns were suitably formatted for read-out by the brain using the distance-to-bound

approach (Ritchie & Carlson, 2016) in a second searchlight analysis. The subject-specific

searchlight results were subjected to inference statistics at the group level using one-sided sign

rank tests and thresholded at p < 0.05 (fdr-corrected for multiple comparisons across voxels).

3.1 A subset of locations that have decodable information about animacy also had information suitably formatted for animacy categorisation behaviour

Animacy is a pervasive and basic object property according to which any object can be classified as animate or inanimate (Caramazza & Shelton, 1998). Previous studies have shown that the division of animate versus inanimate objects is reflected in the large-scale architecture of high-level visual areas such as the ventral temporal cortex (VTC) (Caramazza & Shelton, 1998; Grill-Spector & Weiner, 2014; Kriegeskorte et al., 2008), However, it has also been shown that animacy can be decoded not only from VTC, but from the whole ventral visual stream (Cichy et al., 2016; Grill-Spector & Weiner, 2014; Long, Yu, & Konkle, 2017). Furthermore, categorical object responses have also been found in the dorsal visual stream (Bracci, Daniels, & op de Beeck, 2017; Freedman & Assad, 2006; Konen & Kastner, 2008) and in frontal areas (Freedman, Riesenhuber, Poggio, & Miller, 2001, 2003). This prompts the question of where in the visual system object representations are suitably formatted for read-out by the brain for animacy decisions.

Corroborating previous studies, we found decodable information about animacy in the entire ventral visual stream from the occipital pole to anterior ventral temporal cortex (Figure 2AB, Table 1AD, N = 15, one-sided sign-rank test, $p < 0.05$ fdr-corrected). In addition, we found decodable information in dorsal and prefrontal cortex (Figure 2B) in experiment 2 which had full brain coverage. Localising the brain representations suitable to guide animacy categorisation behaviour (using the distance-to-bound approach) revealed convergent evidence across experiments that only a subset of voxels containing decodable information fulfilled this criterion. In detail, distance-RT-correlations for animate objects were strongest in the high-level regions of the ventral and the dorsal stream. For inanimate objects, we found no voxels with significant distance-RT-correlations (Carlson et al., 2014; Grootswagers, Ritchie, Wardle, Heathcote, & Carlson, 2017).

A   Experiment 1: animate - inanimate

B   Experiment 2: animate - inanimate

Figure 2. Relationship between decodable information and categorisation behaviour for animacy. A. In experiment 1, decodable animacy information (hot colours) was found throughout the ventral stream. A correlation between distance to the classifier boundary and reaction time for

animate stimuli (cool colours) was found in a subset of these areas. **B.** The results of the analysis
for experiment 2 corroborated these findings, and showed decodable information in prefrontal
areas and in the dorsal visual stream. Correlations between distance and reaction time were also
present in the dorsal stream. Visualizations show average results across subjects in significant
voxels (N=15, sign-rank test, $p<0.05$ fdr-corrected) projected onto axial slices of a standard T_1
image in MNI space.

Contrast	#significant voxels	Max/min	uncorr. p-value	X	Y	Z
A) decoding 'animate' vs 'inanimate' (exp 1)	11745	0.80	0.0000	36	-52	-15
Distance-RT-correlation 'animate'	6410	-0.38	0.0000	38	-58	-19
Distance-RT-correlation 'inanimate'	0	-0.16	0.0021	-48	-58	5
B) decoding 'human' vs 'animal'	4863	0.69	0.0000	22	-90	-13
Distance-RT-correlation 'human'	0	-0.29	0.0002	30	-58	-15
Distance-RT-correlation 'animal'	0	-0.17	0.0072	48	-46	-4
C) decoding 'face' vs 'body'	10661	0.84	0.0000	44	-78	-10
Distance-RT-correlation 'face'	226	-0.32	0.0000	40	-76	-15
Distance-RT-correlation 'body'	0	-0.20	0.0000	-54	-68	16
D) decoding 'animate' vs 'inanimate' (exp 2)	8824	0.80	0.0000	36	-55	-11
Distance-RT-correlation 'animate'	2015	-0.34	0.0000	51	-73	-2
Distance-RT-correlation 'inanimate'	0	-0.12	0.0002	-21	-43	-2
E) decoding 'tool' vs 'not tool'	0	0.58	0.0002	-30	-94	7
Distance-RT-correlation 'tool'	0	-0.25	0.0013	-33	-13	19
Distance-RT-correlation 'not tool'	0	-0.24	0.0001	-33	-52	-17
F) decoding 'transport' vs 'not transport'	0	0.59	0.0001	33	-94	1
Distance-RT-correlation 'transport'	0	-0.32	0.0003	15	50	4
Distance-RT-correlation 'non-transport'	0	-0.18	0.0000	-33	-55	-14
G) decoding 'food' vs 'not food'	1092	0.62	0.0002	36	-55	-14
Distance-RT-correlation 'food'	0	-0.16	0.0177	-18	26	-5
Distance-RT-correlation 'not food'	154	-0.13	0.0002	27	-40	-14

231 **Table 1. Results for all categorisation contrasts.** For all categorisation contrasts, we report the
232 number of significant voxels (after correction for multiple comparisons), its peak value (maximum
233 for decoding or minimum for distance-RT-correlation) and uncorrected p-value, and the peak's
234 location in MNI-XYZ coordinates.

3.2 The proportion of region-specific representations suitably formatted for behaviour increases along the ventral stream and decreases along the dorsal stream

We next explicitly determined the degree to which representations in single brain regions within the ventral and dorsal streams are suitably formatted for behaviour. For this we parcellated the cortex (Figure 3A) using a probabilistic topographic map of visual processing areas (Wang et al., 2015). For each region, we calculated the ratio between the number of significant voxels in the decoding analysis and the total number of voxels, so that a high ratio indicates that a large part of a region contains object representations with categorical information. Similarly, we calculated the ratio between the number of significant voxels in the distance-to-bound analysis and the total number of voxels. Here, a high ratio indicates that a large part of a region contains object representations that are suitably formatted for read out in a categorisation task.

In the ventral stream, we observed a systematic increase in ratio with processing stage, from early visual areas to high-level visual areas, with highest ratios in ventral occipital (VO) and parahippocampal (PHC) cortex (Figure 3 B&C). In contrast, in the dorsal stream we observed a systematic decrease of the correlation ratio with processing stage. In addition, significant animacy decoding information was found in similar proportions in the ventral-temporal areas as in lateral-occipital areas, however, the proportion of voxels with information suitable for categorisation was lower in lateral-occipital areas. This is consistent with the notion that while both these regions contain object representations, the VTC contains location-invariant representations which are essential for object categorisation (Cichy et al., 2013; Haushofer et al., 2008; Schwarzlose, Swisher, Dang, & Kanwisher, 2008; Williams et al., 2007).

In sum, these results show that representations along the ventral stream are shaped for optimal read-out of categorical information (Cichy et al., 2013; Grill-Spector & Weiner, 2014). In contrast,

representations in the dorsal stream might be shaped for the read-out in different tasks (Bracci et

al., 2017; Freud et al., 2017). These results also suggest that intermediate stages along the ventral

and dorsal streams may be similar or partly shared, as suggested by the similar ratios of

information suitable for read-out.

Figure 3. Quantifying the decodable information in visual areas and their contribution to

categorisation behaviour. A. Locations of topographical ROIs of the visual system (Wang et al.,

2015), containing early visual cortex (EVC) areas V1 and V2, mid-level areas V3 and hV4, high level

ventral occipital (VO) and parahippocampal cortex (PHC), temporal occipital (TO) and lateral

occipital (LO) areas, areas in the intra-parietal sulcus (IPS), the superior parietal lobule (SPL), and

the frontal eye fields (FEF). **B-C.** The ratio between significant voxels in an ROI and the size of the

ROI. Orange points show the ratio of voxels within the ROI that had significant animacy decoding

performance. Blue points show the ratio of voxels with a significant correlation between distance

to the hyperplane and RT for 'animate'. The lower, middle and upper points on these lines indicate

5^{th}, 50^{th}, and 95^{th} percentiles (bootstrapping of participants 10,000 times). These results quantify

the increasing contribution of early to late areas in the ventral visual stream to animacy

categorisation behaviour.

3.3 Decodable information about subordinate categorisation tasks is also suitably formatted for

categorisation behaviour

While animacy categorisation may be based on large-scale representational differences in the

visual brain (Carlson, Tovar, Alink, & Kriegeskorte, 2013; Downing, Chan, Peelen, Dodds, &

Kanwisher, 2006; Grill-Spector & Weiner, 2014; Kriegeskorte et al., 2008), subordinate

categorisation tasks (e.g., faces, bodies, tools) may depend more on fine grained patterns in focal

brain regions (Downing, Jiang, Shuman, & Kanwisher, 2001; Downing & Peelen, 2016; Kanwisher,

McDermott, & Chun, 1997). Here, we tested whether decodable information about subordinate

category membership is also suitably formatted for read out in respective categorisation tasks. We

tested two subordinate contrasts for experiment 1: face versus body, and human versus animal

using the same general procedure as for animacy. We found that both contrasts were decodable

(Table 1B-C). We found a significant correlation between distance to the classifier hyperplane and

reaction time for faces in the face versus body task (Figure 4A). Of the subordinate categorisation

contrasts in experiment 2 (food, transport or tool versus everything else), transport and tool

versus everything else were not significantly decodable information nor had they significant

correlations (Table 1E-F). Food versus not food resulted in significant decodable information, and

significant distance-RT correlations were present for this contrast in the 'not food' category

(Figure 4B, Table 1G). Taken together, for some subordinate categorisation contrasts that were

decodable, we were successful in localising brain patterns suitably formatted for read-out in behaviour.

A   Experiment 1: face - body

B   Experiment 2: food - not food

Figure 4. Relationship between decodable information and behaviour for subordinate categorisation tasks. A. In experiment 1, decodable face versus body information (hot colours) was found in the entire ventral stream. A distance-RT-correlation for the face stimuli (cool colours) was found in a subset of these areas. **B.** In experiment 2, food versus not food was decodable in some areas in the ventral visual stream. A distance-RT-correlation for the 'not food' stimuli was found in a subset of these areas. Visualisations show average results across subjects in significant voxels (N=15, sign-rank test, p<0.05 fdr-corrected) projected onto axial slices of a standard T_1 image in MNI space.

4 Discussion

4.1 Dissociating between decodable information and information that is used in behaviour

The aim of this study was to examine where in the brain decodable information is suitably formatted for read-out by the brain in behaviour. We found that only a subset of information that is decodable could be related to behaviour using the distance-to-bound approach, which argues for a partial dissociation between decodable information and information that is relevant for behaviour. This speaks to a current challenge in neuroimaging, which is to show that information visible to the experimenter is in fact used by the brain (de-Wit et al., 2016; Ritchie et al., 2017). To illustrate, consider the question about what regions are used by the brain to perform an object animacy categorisation task (DiCarlo, Zoccolan, & Rust, 2012; Grill-Spector & Weiner, 2014). On its own, the result of the animacy decoding searchlight might be interpreted as the brain using animacy information from anywhere in the ventral stream. However, when investigating this interpretation directly using the distance-RT-correlation results, it becomes clear that object animacy information is represented for read-out in mid- and high-level visual areas only.

It is important to note that not finding a correlation between distance to the classifier hyperplane and RT does not imply that the information revealed using the decoding approach is irrelevant or epiphenomenal. The distance-to-bound approach taken here makes specific assumptions about

the brain's read-out process, such as distance in representational space as the measure for

evidence, and a rank-order relationship between distance and reaction time (Ritchie & Carlson,

2016). Other assumptions follow from those imposed by the decoding approach, such as the

binary classification, the size of the searchlight radius, and the choice of classifier. For example, it

could be that the representations are relevant in a different task (Grootswagers, Ritchie, et al.,

2017; Ritchie & Carlson, 2016), or that read-out involves pooling over larger spatial scales or

multiple brain areas. Therefore, the current approach only allows the positive inference on the

level of suitability of decoded information for behaviour in the context of the current task and

decoding parameters. On the other hand, a correlation with behaviour still does not prove that

the information is used by the brain, but it shows that the information is at least formatted in a

way that is suitable to be used by the brain for decisions. Future work can use causal measures

(e.g., TMS) targeting the areas highlighted in the current results.

4.2 The contribution of ventral and dorsal visual regions to categorisation behaviour

We found that neural representations suitably formatted for behaviour in categorisation were

most prominently located in the anterior regions of the VTC. This corroborates previous studies

(Afraz, Kiani, & Esteky, 2006; Carlson et al., 2014; Hong, Yamins, Majaj, & DiCarlo, 2016; Hung,

Kreiman, Poggio, & DiCarlo, 2005), and reinforces the tight link between VTC and visual

categorisation behaviour. In these areas, our results provide converging evidence for the (implicit)

assumption made in neuroimaging studies, which is that information that is available to the

experimenter is also available for read out by the brain in behaviour (cf. de-Wit et al., 2016).

However, we found that correlations between distance to boundary and RT were not restricted to

anterior regions of the VTC, but were also prominent in V3 and hV4. This is consistent with the

view that lower level visual features encoded in mid-level visual regions could aid faster read-out

of category information. V4 is thought of as an intermediate stage of visual processing that

aggregates lower level visual features into invariant representations (Riesenhuber & Poggio,

1999). It has been proposed that direct pathways from V4 to decision areas allow the brain to

exploit visual feature cues for fast responses to ecologically important stimuli (Hong et al., 2016;

Kirchner & Thorpe, 2006; Thorpe, Fize, & Marlot, 1996), such as identifying faces (Crouzet,

Kirchner, & Thorpe, 2010; Honey, Kirchner, & VanRullen, 2008). An alternative possibility is that

read out is not happening directly from V4, but its representational structure is shaped by the low-

level feature differences in animacy. This structure is then largely preserved when it is

communicated to more anterior areas, leading to similar distance-RT-correlations. Both of these

accounts are also consistent with recent findings that show differential responses for object

categories in mid-level visual areas (Long et al., 2017; Proklova et al., 2016). The extent to which

visual features contribute to the read-out process could be further investigated by using the

approach from this study with different stimulus sets that control for these features (Kaiser,

Azzalini, & Peelen, 2016; Long et al., 2017; Proklova et al., 2016).

We found that distance-RT-correlations were also present in early parietal areas. The classical

view is that the ventral and dorsal visual streams are recruited for different function (Ungerleider

& Mishkin, 1982). However, areas in the ventral and dorsal streams have been found to exhibit

similar object-selective responses (Freud et al., 2017; Konen & Kastner, 2008; Sereno & Maunsell,

1998; Silver & Kastner, 2009). Consistent with this, we found similar RT-distance-correlations in

mid-level areas in the ventral and dorsal streams. However, our results also showed that the

proportion of correlations decreased along the dorsal stream, while they increased along the

ventral stream. This suggests that representations in the ventral and dorsal streams undergo

similar transformations at first, and then diverge for different goals.

4.3 Without a task, neural object representations in the VTC are formatted for read-out in categorisation decisions

Here, the fMRI participants performed an orthogonal task, and were not actively categorising. Despite this, categorisation reaction times could still be predicted from representations in the visual stream. This highlights that, without a categorisation task, information in the visual system is represented in a way that is suitable for read out in behaviour (Carlson et al., 2014; Ritchie, Tovar, & Carlson, 2015). In addition, the orthogonal task in the scanner has the advantage that it avoids RT- and difficulty confounds (see e.g., Hebart & Baker, 2017; Woolgar, Golland, & Bode, 2014). Future studies might use the distance-to-bound approach with participants actively performing the same task in the scanner, where we predict that areas involved in the decision making and execution processes would contain information that correlates with reaction time. For example, some areas preferentially represent task-relevant information, such as areas in the prefrontal cortex (Duncan, 2001; Jackson, Rich, Williams, & Woolgar, 2016; Woolgar, Jackson, & Duncan, 2016), and in the parietal stream (Bracci et al., 2017; Freedman & Assad, 2016; Jeong & Xu, 2016). In the absence of an animacy categorisation task, one would predict that animacy information would not be strongly represented in these areas. Yet, our results showed that animacy information can be decoded from prefrontal and parietal areas when participants perform an orthogonal task. However, our results also showed that the animacy information in these areas was not predictive of reaction time. This again highlights the dissociation between information that can be decoded, and information that is suitable for read out in behaviour. A prediction that follows from this is that performing an active object categorisation task in the scanner would change the representations in these task-relevant areas so that they become predictive of reaction time (Bugatus, Weiner, & Grill-Spector, 2017; McKee, Riesenhuber, Miller, & Freedman, 2014).

4.4 Asymmetric distance-RT-Correlations in binary categorisation tasks

In both experiments, we found correlations between distance and reaction time for animate stimuli, but none for the inanimate stimuli. This is consistent with previous work (Carlson et al., 2014; Grootswagers, Ritchie, et al., 2017; Ritchie et al., 2015), which argued that this discrepancy might be caused by inanimate being a negatively defined category (i.e., "not animate"). Under this hypothesis the animacy categorisation task can be performed by collecting evidence for animate stimuli and responding inanimate only when not enough evidence was accumulated after a certain amount of time. Here, we tested a prediction of this hypothesis by contrasting two positively defined categories, face versus body, and found that there was a distance-RT-correlation only for faces. This goes against the notion of the negative definition of inanimate as the main reason for a lack of correlation. However, it still is possible that observers still treated these tasks as 'A' or 'NOT A', with 'A' being the category that is easiest to detect (Grootswagers, Ritchie, et al., 2017). For example, perceptual evidence for a face would be easier to obtain that evidence for a body-part, as faces share low level visual features (Crouzet & Thorpe, 2011; Honey et al., 2008; Wu, Crouzet, Thorpe, & Fabre-Thorpe, 2015). Thus, while not explicitly specified as a negative category, it could have been treated as such.

This suggest that the binary categorisation might be an unnatural way of approaching human categorisation behaviour in the real world. Other operationalisations such as picture naming or visual search may be better suited to capture the relevant behaviours (cf. Krakauer, Ghazanfar, Gomez-Marin, MacIver, & Poeppel, 2017). Still, it is important to note that the binary task matches the brain decoding task performed by the classifier. The above-chance decoding accuracy in the brain decoding task is commonly interpreted as a similar dichotomy in the brain's representation that the brain can use in a decision. However, when only the information in one of the categories

(i.e., animals or faces) can be used to predict decision behaviour, as shown here, then this

interpretation needs to be revisited.

4.5 Conclusion

In this study, we combined the distance-to-bound approach (Ritchie & Carlson, 2016) with a

searchlight decoding analysis to find brain areas with decodable information that is suitable for

read-out in behaviour. Our results showed that decodable information is not always equally

suitable for read-out by the brain in behaviour. This speaks to the current debate in neuroimaging

research about whether the information that we can decode is the same information that is used

by the brain in behaviour (de-Wit et al., 2016).

References

Afraz, S.-R., Kiani, R., & Esteky, H. (2006). Microstimulation of inferotemporal cortex influences

face categorization. *Nature*, *442*(7103), 692–695.

Ashby, F. G. (2000). A Stochastic Version of General Recognition Theory. *Journal of Mathematical

Psychology*, *44*(2), 310–329. https://doi.org/10.1006/jmps.1998.1249

Ashby, F. G., & Maddox, W. T. (1994). A Response Time Theory of Separability and Integrality in

Speeded Classification. *Journal of Mathematical Psychology*, *38*(4), 423–466.

https://doi.org/10.1006/jmps.1994.1032

Benjamini, Y., & Hochberg, Y. (1995). Controlling the False Discovery Rate: A Practical and

Powerful Approach to Multiple Testing. *Journal of the Royal Statistical Society. Series B

(Methodological)*, *57*(1), 289–300.

Bouton, S., Chambon, V., Tyrand, R., Guggisberg, A. G., Seeck, M., Karkar, S., … Giraud, A.-L. (2018).

Focal versus distributed temporal cortex activity for speech sound category assignment.

Proceedings of the National Academy of Sciences, *115*(6), E1299–E1308.

Bracci, S., Daniels, N., & Op de Beeck, H. P. (2017). Task Context Overrules Object- and Category-

Related Representational Content in the Human Parietal Cortex. *Cerebral Cortex*, 1–12.

https://doi.org/10.1093/cercor/bhw419

Bracci, S., & Op de Beeck, H. P. (2016). Dissociations and Associations between Shape and

Category Representations in the Two Visual Pathways. *Journal of Neuroscience*, *36*(2), 432–

444. https://doi.org/10.1523/JNEUROSCI.2314-15.2016

Bugatus, L., Weiner, K. S., & Grill-Spector, K. (2017). Task alters category representations in

prefrontal but not high-level visual cortex. *NeuroImage*, *155*, 437–449.

https://doi.org/10.1016/j.neuroimage.2017.03.062

Caramazza, A., & Shelton, J. R. (1998). Domain-Specific Knowledge Systems in the Brain: The

Animate-Inanimate Distinction. *Journal of Cognitive Neuroscience*, *10*(1), 1–34.

https://doi.org/10.1162/089892998563752

Carlson, T. A., Ritchie, J. B., Kriegeskorte, N., Durvasula, S., & Ma, J. (2014). Reaction Time for

Object Categorization Is Predicted by Representational Distance. *Journal of Cognitive*

Neuroscience, *26*(1), 132–142. https://doi.org/10.1162/jocn_a_00476

Carlson, T. A., Schrater, P., & He, S. (2003). Patterns of Activity in the Categorical Representations

of Objects. *Journal of Cognitive Neuroscience*, *15*(5), 704–717.

https://doi.org/10.1162/jocn.2003.15.5.704

Carlson, T. A., Tovar, D. A., Alink, A., & Kriegeskorte, N. (2013). Representational dynamics of

object vision: The first 1000 ms. *Journal of Vision*, *13*(10), 1.

https://doi.org/10.1167/13.10.1

Cichy, R. M., Pantazis, D., & Oliva, A. (2014). Resolving human object recognition in space and

time. *Nature Neuroscience*, *17*(3), 455–462. https://doi.org/10.1038/nn.3635

Cichy, R. M., Pantazis, D., & Oliva, A. (2016). Similarity-Based Fusion of MEG and fMRI Reveals

Spatio-Temporal Dynamics in Human Cortex During Visual Object Recognition. *Cerebral*

Cortex, *26*(8), 3563–3579. https://doi.org/10.1093/cercor/bhw135

Cichy, R. M., Sterzer, P., Heinzle, J., Elliott, L. T., Ramirez, F., & Haynes, J.-D. (2013). Probing

principles of large-scale object representation: Category preference and location encoding.

Human Brain Mapping, *34*(7), 1636–1651. https://doi.org/10.1002/hbm.22020

Cohen, M. A., Dennett, D. C., & Kanwisher, N. (2016). What is the Bandwidth of Perceptual

Experience? *Trends in Cognitive Sciences*, *20*(5), 324–335.

https://doi.org/10.1016/j.tics.2016.03.006

Cox, D. D., & Savoy, R. L. (2003). Functional magnetic resonance imaging (fMRI) "brain reading":

detecting and classifying distributed patterns of fMRI activity in human visual cortex.

NeuroImage, *19*(2), 261–270. https://doi.org/10.1016/S1053-8119(03)00049-1

Crouzet, S. M., Kirchner, H., & Thorpe, S. J. (2010). Fast saccades toward faces: Face detection in

just 100 ms. *Journal of Vision*, *10*(4), 16. https://doi.org/10.1167/10.4.16

Crouzet, S. M., & Thorpe, S. J. (2011). Low-Level Cues and Ultra-Fast Face Detection. *Frontiers in*

Psychology, *2*. https://doi.org/10.3389/fpsyg.2011.00342

de-Wit, L., Alexander, D., Ekroll, V., & Wagemans, J. (2016). Is neuroimaging measuring

information in the brain? *Psychonomic Bulletin & Review*, *23*(5), 1415–1428.

https://doi.org/10.3758/s13423-016-1002-0

DiCarlo, J. J., & Cox, D. D. (2007). Untangling invariant object recognition. *Trends in Cognitive*

Sciences, *11*(8), 333–341. https://doi.org/10.1016/j.tics.2007.06.010

DiCarlo, J. J., Zoccolan, D., & Rust, N. C. (2012). How Does the Brain Solve Visual Object

Recognition? *Neuron*, *73*(3), 415–434. https://doi.org/10.1016/j.neuron.2012.01.010

Downing, P. E., Chan, A. W.-Y., Peelen, M. V., Dodds, C. M., & Kanwisher, N. (2006). Domain

Specificity in Visual Cortex. *Cerebral Cortex*, *16*(10), 1453–1461.

https://doi.org/10.1093/cercor/bhj086

Downing, P. E., Jiang, Y., Shuman, M., & Kanwisher, N. (2001). A Cortical Area Selective for Visual

Processing of the Human Body. *Science*, *293*(5539), 2470–2473.

https://doi.org/10.1126/science.1063414

Downing, P. E., & Peelen, M. V. (2016). Body selectivity in occipitotemporal cortex: Causal

evidence. *Neuropsychologia*, *83*, 138–148.

https://doi.org/10.1016/j.neuropsychologia.2015.05.033

Duncan, J. (2001). An adaptive coding model of neural function in prefrontal cortex. *Nature*

Reviews Neuroscience, *2*(11), 820–829.

Freedman, D. J., & Assad, J. A. (2006). Experience-dependent representation of visual categories in

parietal cortex. *Nature*, *443*(7107), 85–88.

Freedman, D. J., & Assad, J. A. (2016). Neuronal Mechanisms of Visual Categorization: An Abstract

View on Decision Making. *Annual Review of Neuroscience*, *39*(1), 129–147.

https://doi.org/10.1146/annurev-neuro-071714-033919

Freedman, D. J., Riesenhuber, M., Poggio, T., & Miller, E. K. (2001). Categorical Representation of

Visual Stimuli in the Primate Prefrontal Cortex. *Science*, *291*(5502), 312–316.

https://doi.org/10.1126/science.291.5502.312

Freedman, D. J., Riesenhuber, M., Poggio, T., & Miller, E. K. (2003). A Comparison of Primate

Prefrontal and Inferior Temporal Cortices during Visual Categorization. *The Journal of*

Neuroscience, *23*(12), 5235–5246.

Freud, E., Culham, J. C., Plaut, D. C., & Behrmann, M. (2017). The large-scale organization of shape

processing in the ventral and dorsal pathways. *ELife*, *6*, e27576.

https://doi.org/10.7554/eLife.27576

Green, D. M., & Swets, J. A. (1966). Signal detection theory and psychophysics. *New York*.

Grill-Spector, K., & Weiner, K. S. (2014). The functional architecture of the ventral temporal cortex

and its role in categorization. *Nature Reviews Neuroscience*, *15*(8), 536–548.

https://doi.org/10.1038/nrn3747

Grootswagers, T., Kennedy, B. L., Most, S. B., & Carlson, T. A. (2017). Neural signatures of dynamic

emotion constructs in the human brain. *Neuropsychologia*.

https://doi.org/10.1016/j.neuropsychologia.2017.10.016

Grootswagers, T., Ritchie, J. B., Wardle, S. G., Heathcote, A., & Carlson, T. A. (2017). Asymmetric

Compression of Representational Space for Object Animacy Categorization under

Degraded Viewing Conditions. *Journal of Cognitive Neuroscience*, *29*(12), 1995–2010.

https://doi.org/10.1162/jocn_a_01177

Grootswagers, T., Wardle, S. G., & Carlson, T. A. (2017). Decoding Dynamic Brain Patterns from

Evoked Responses: A Tutorial on Multivariate Pattern Analysis Applied to Time Series

Neuroimaging Data. *Journal of Cognitive Neuroscience*, *29*(4), 677–697.

https://doi.org/10.1162/jocn_a_01068

Haushofer, J., Livingstone, M. S., & Kanwisher, N. (2008). Multivariate Patterns in Object-Selective

Cortex Dissociate Perceptual and Physical Shape Similarity. *PLOS Biology*, *6*(7), e187.

https://doi.org/10.1371/journal.pbio.0060187

Haxby, J. V., Gobbini, M. I., Furey, M. L., Ishai, A., Schouten, J. L., & Pietrini, P. (2001). Distributed

and Overlapping Representations of Faces and Objects in Ventral Temporal Cortex. *Science*,

293(5539), 2425–2430. https://doi.org/10.1126/science.1063736

Haynes, J.-D. (2015). A Primer on Pattern-Based Approaches to fMRI: Principles, Pitfalls, and

Perspectives. *Neuron*, *87*(2), 257–270. https://doi.org/10.1016/j.neuron.2015.05.025

Haynes, J.-D., Sakai, K., Rees, G., Gilbert, S., Frith, C., & Passingham, R. E. (2007). Reading Hidden

Intentions in the Human Brain. *Current Biology*, *17*(4), 323–328.

https://doi.org/10.1016/j.cub.2006.11.072

Hebart, M. N., & Baker, C. I. (2017). Deconstructing multivariate decoding for the study of brain

function. *NeuroImage*. https://doi.org/10.1016/j.neuroimage.2017.08.005

Honey, C., Kirchner, H., & VanRullen, R. (2008). Faces in the cloud: Fourier power spectrum biases

ultrarapid face detection. *Journal of Vision*, *8*(12), 9–9. https://doi.org/10.1167/8.12.9

Hong, H., Yamins, D. L. K., Majaj, N. J., & DiCarlo, J. J. (2016). Explicit information for category-

orthogonal object properties increases along the ventral stream. *Nature Neuroscience*,

19(4), 613–622. https://doi.org/10.1038/nn.4247

Hung, C. P., Kreiman, G., Poggio, T., & DiCarlo, J. J. (2005). Fast Readout of Object Identity from

Macaque Inferior Temporal Cortex. *Science*, *310*(5749), 863–866.

https://doi.org/10.1126/science.1117593

Jackson, J., Rich, A. N., Williams, M. A., & Woolgar, A. (2016). Feature-selective Attention in

Frontoparietal Cortex: Multivoxel Codes Adjust to Prioritize Task-relevant Information.

Journal of Cognitive Neuroscience, *29*(2), 310–321. https://doi.org/10.1162/jocn_a_01039

Jeong, S. K., & Xu, Y. (2016). Behaviorally Relevant Abstract Object Identity Representation in the

Human Parietal Cortex. *Journal of Neuroscience*, *36*(5), 1607–1619.

https://doi.org/10.1523/JNEUROSCI.1016-15.2016

Kaiser, D., Azzalini, D. C., & Peelen, M. V. (2016). Shape-independent object category responses

revealed by MEG and fMRI decoding. *Journal of Neurophysiology*, *115*(4), 2246–2250.

https://doi.org/10.1152/jn.01074.2015

Kamitani, Y., & Tong, F. (2005). Decoding the visual and subjective contents of the human brain.

Nature Neuroscience, *8*(5), 679–685. https://doi.org/10.1038/nn1444

Kanwisher, N., McDermott, J., & Chun, M. M. (1997). The Fusiform Face Area: A Module in Human

Extrastriate Cortex Specialized for Face Perception. *The Journal of Neuroscience*, *17*(11),

4302–4311.

Kiani, R., Cueva, C. J., Reppas, J. B., & Newsome, W. T. (2014). Dynamics of Neural Population

Responses in Prefrontal Cortex Indicate Changes of Mind on Single Trials. *Current Biology*,

24(13), 1542–1547. https://doi.org/10.1016/j.cub.2014.05.049

Kirchner, H., & Thorpe, S. J. (2006). Ultra-rapid object detection with saccadic eye movements:

Visual processing speed revisited. *Vision Research*, *46*(11), 1762–1776.

https://doi.org/10.1016/j.visres.2005.10.002

Konen, C. S., & Kastner, S. (2008). Two hierarchically organized neural systems for object

information in human visual cortex. *Nature Neuroscience*, *11*(2), 224–231.

https://doi.org/10.1038/nn2036

Krakauer, J. W., Ghazanfar, A. A., Gomez-Marin, A., MacIver, M. A., & Poeppel, D. (2017).

Neuroscience Needs Behavior: Correcting a Reductionist Bias. *Neuron*, *93*(3), 480–490.

https://doi.org/10.1016/j.neuron.2016.12.041

Kriegeskorte, N., Goebel, R., & Bandettini, P. A. (2006). Information-based functional brain

mapping. *Proceedings of the National Academy of Sciences of the United States of America*,

103(10), 3863–3868. https://doi.org/10.1073/pnas.0600244103

Kriegeskorte, N., Mur, M., Ruff, D. A., Kiani, R., Bodurka, J., Esteky, H., … Bandettini, P. A. (2008).

Matching Categorical Object Representations in Inferior Temporal Cortex of Man and

Monkey. *Neuron*, *60*(6), 1126–1141. https://doi.org/10.1016/j.neuron.2008.10.043

Long, B., Yu, C.-P., & Konkle, T. (2017). A mid-level organization of the ventral stream. *BioRxiv*,

213934. https://doi.org/10.1101/213934

McKee, J. L., Riesenhuber, M., Miller, E. K., & Freedman, D. J. (2014). Task dependence of visual

and category representations in prefrontal and inferior temporal cortices. *Journal of*

Neuroscience, *34*(48), 16065–16075.

Mur, M., Meys, M., Bodurka, J., Goebel, R., Bandettini, P. A., & Kriegeskorte, N. (2013). Human

Object-Similarity Judgments Reflect and Transcend the Primate-IT Object Representation.

Frontiers in Psychology, *4*. https://doi.org/10.3389/fpsyg.2013.00128

Naselaris, T., Kay, K. N., Nishimoto, S., & Gallant, J. L. (2011). Encoding and decoding in fMRI.

NeuroImage, *56*(2), 400–410. https://doi.org/10.1016/j.neuroimage.2010.07.073

Oosterhof, N. N., Connolly, A. C., & Haxby, J. V. (2016). CoSMoMVPA: Multi-Modal Multivariate

Pattern Analysis of Neuroimaging Data in Matlab/GNU Octave. *Frontiers in*

Neuroinformatics, 27. https://doi.org/10.3389/fninf.2016.00027

Pereira, F., Mitchell, T., & Botvinick, M. (2009). Machine learning classifiers and fMRI: A tutorial

overview. *NeuroImage*, *45*(1, Supplement 1), S199–S209.

https://doi.org/10.1016/j.neuroimage.2008.11.007

Philiastides, M. G., & Sajda, P. (2006). Temporal Characterization of the Neural Correlates of

Perceptual Decision Making in the Human Brain. *Cerebral Cortex*, *16*(4), 509–518.

https://doi.org/10.1093/cercor/bhi130

Proklova, D., Kaiser, D., & Peelen, M. V. (2016). Disentangling Representations of Object Shape and

Object Category in Human Visual Cortex: The Animate–Inanimate Distinction. *Journal of*

Cognitive Neuroscience, 1–13. https://doi.org/10.1162/jocn_a_00924

Raizada, R. D. S., Tsao, F.-M., Liu, H.-M., & Kuhl, P. K. (2010). Quantifying the Adequacy of Neural

Representations for a Cross-Language Phonetic Discrimination Task: Prediction of

Individual Differences. *Cerebral Cortex*, *20*(1), 1–12.

https://doi.org/10.1093/cercor/bhp076

Riesenhuber, M., & Poggio, T. (1999). Hierarchical models of object recognition in cortex. *Nature*

Neuroscience, *2*(11), 1019–1025.

Ritchie, J. B., & Carlson, T. A. (2016). Neural Decoding and "Inner" Psychophysics: A Distance-to-

Bound Approach for Linking Mind, Brain, and Behavior. *Frontiers in Neuroscience*, 190.

https://doi.org/10.3389/fnins.2016.00190

Ritchie, J. B., Kaplan, D. M., & Klein, C. (2017). Decoding the Brain: Neural Representation and the

Limits of Multivariate Pattern Analysis in Cognitive Neuroscience. *The British Journal for the*

Philosophy of Science. https://doi.org/10.1093/bjps/axx023

Ritchie, J. B., Tovar, D. A., & Carlson, T. A. (2015). Emerging Object Representations in the Visual

System Predict Reaction Times for Categorization. *PLoS Comput Biol*, *11*(6), e1004316.

https://doi.org/10.1371/journal.pcbi.1004316

Schwarzlose, R. F., Swisher, J. D., Dang, S., & Kanwisher, N. (2008). The distribution of category and

location information across object-selective regions in human visual cortex. *Proceedings of*

the National Academy of Sciences, *105*(11), 4447–4452.

https://doi.org/10.1073/pnas.0800431105

Sereno, A. B., & Maunsell, J. H. R. (1998). Shape selectivity in primate lateral intraparietal cortex.

Nature, *395*(6701), 500–503. https://doi.org/10.1038/26752

Silver, M. A., & Kastner, S. (2009). Topographic maps in human frontal and parietal cortex. *Trends*

in Cognitive Sciences, *13*(11), 488–495. https://doi.org/10.1016/j.tics.2009.08.005

Thorpe, S., Fize, D., & Marlot, C. (1996). Speed of processing in the human visual system. *Nature*,

381(6582), 520–522.

Ungerleider, L. G., & Mishkin, M. (1982). Two cortical visual systems. *Analysis of Visual Behavior*,

549–586.

van Bergen, R. S., Ji Ma, W., Pratte, M. S., & Jehee, J. F. M. (2015). Sensory uncertainty decoded

from visual cortex predicts behavior. *Nature Neuroscience*, *18*(12), 1728–1730.

https://doi.org/10.1038/nn.4150

Walther, D. B., Caddigan, E., Fei-Fei, L., & Beck, D. M. (2009). Natural Scene Categories Revealed in

Distributed Patterns of Activity in the Human Brain. *Journal of Neuroscience*, *29*(34),

10573–10581. https://doi.org/10.1523/JNEUROSCI.0559-09.2009

Wang, L., Mruczek, R. E. B., Arcaro, M. J., & Kastner, S. (2015). Probabilistic Maps of Visual

Topography in Human Cortex. *Cerebral Cortex*, *25*(10), 3911–3931.

https://doi.org/10.1093/cercor/bhu277

Wardle, S. G., Kriegeskorte, N., Grootswagers, T., Khaligh-Razavi, S.-M., & Carlson, T. A. (2016).

Perceptual similarity of visual patterns predicts dynamic neural activation patterns

measured with MEG. *NeuroImage*, *132*, 59–70.

https://doi.org/10.1016/j.neuroimage.2016.02.019

Williams, M. A., Dang, S., & Kanwisher, N. G. (2007). Only some spatial patterns of fMRI response

are read out in task performance. *Nature Neuroscience*, *10*(6), 685–686.

https://doi.org/10.1038/nn1900

Woolgar, A., Golland, P., & Bode, S. (2014). Coping with confounds in multivoxel pattern analysis:

What should we do about reaction time differences? A comment on Todd, Nystrom &

Cohen 2013. *NeuroImage*, *98*, 506–512.

https://doi.org/10.1016/j.neuroimage.2014.04.059

Woolgar, A., Jackson, J., & Duncan, J. (2016). Coding of Visual, Auditory, Rule, and Response

Information in the Brain: 10 Years of Multivoxel Pattern Analysis. *Journal of Cognitive*

Neuroscience, *28*(10), 1433–1454. https://doi.org/10.1162/jocn_a_00981

Wu, C.-T., Crouzet, S. M., Thorpe, S. J., & Fabre-Thorpe, M. (2015). At 120 msec You Can Spot the

Animal but You Don't Yet Know It's a Dog. *Journal of Cognitive Neuroscience*, *27*(1), 141–

149. https://doi.org/10.1162/jocn_a_00701