Taxonomic identification from metagenomic and metabarcoding data using any genetic marker

Johan Bengtsson-Palme[1,2,3,*], Rodney T. Richardson[4], Marco Meola[5], Christian Wurzbacher[6,7], Émilie D. Tremblay[8], Kaisa Thorell[9], Kärt Kanger[10], K. Martin Eriksson[11], Guillaume J. Bilodeau[8], Reed M. Johnson[4], Martin Hartmann[12,13], R. Henrik Nilsson[6,14]

Affiliations

[1] Department of Infectious Diseases, Institute of Biomedicine, The Sahlgrenska Academy, University of Gothenburg, Guldhedsgatan 10, SE-413 46, Gothenburg, Sweden

[2] Center for Antibiotic Resistance research (CARe) at University of Gothenburg, Box 440, SE-40530, Gothenburg, Sweden

[3] Wisconsin Institute for Discovery, University of Wisconsin-Madison, 330 N. Orchard Street, Madison, WI 53715, USA

[4] Department of Entomology, The Ohio State University–Ohio Agricultural Research and Development Center, 1680 Madison Ave., Wooster, OH 44691, USA

[5] Fermentation Organisms, Methods Development and Analytics, Agroscope, CH-3003 Bern, Switzerland

[6] Department of Biological and Environmental Sciences, University of Gothenburg, Box 461, SE-405 30 Gothenburg, Sweden

[7] Chair of Urban Water Systems Engineering, Technical University of Munich, Am Coulombwall 8, 85748 Garching, Germany

[8] Canadian Food Inspection Agency, Ottawa, ON K2H 8P9, Canada

[9] Department of Microbiology, Tumor and Cell Biology, Karolinska Institutet, Nobels Väg 16,

SE-171 77 Stockholm, Sweden

[10] Institute of Ecology and Earth Science, University of Tartu, Vanemuise 46, 51014 Tartu,

Estonia

[11] Department of Mechanics and Maritime Sciences, Chalmers University of Technology, SE-412

96 Gothenburg, Sweden

[12] Forest Soils and Biogeochemistry, Swiss Federal Research Institute WSL, CH-8903

Birmensdorf, Switzerland

[13] Sustainable Agroecosystems, Institute of Agricultural Sciences, Department of Environmental

Systems Science, ETH Zurich, CH-8092 Zurich, Switzerland

[14] Gothenburg Global Biodiversity Centre, Box 461, SE-405 30 Göteborg, Sweden

* Corresponding author: johan.bengtsson-palme@microbiology.se; +46 31 342 46 26

Correct taxonomic identification of DNA sequences is central to studies of biodiversity using both shotgun metagenomic and metabarcoding approaches. However, there is no genetic marker that gives sufficient performance across all the biological kingdoms, hampering studies of taxonomic diversity in many groups of organisms. We here present a major update to Metaxa2 (http://microbiology.se/software/metaxa2/) that enables the use of any genetic marker for taxonomic classification of metagenome and amplicon sequence data.

Sequencing of DNA has revolutionized taxonomy, providing unprecedented resolution for species identification and definition[1,2]. Similarly, the advent of large-scale sequencing techniques has opened entirely new windows on ecology, both for microbes and multicellular species[3]. In particular, high-throughput assignment of species and genus designations based on mixed samples of organisms or environmental substrates, so called DNA metabarcoding[4], has made it possible to perform fine-tuned investigations of taxonomic diversity and to understand ecological interactions in different types of environments. However, an important bottleneck in such analyses is the size and quality of the reference sequence data to which the newly generated sequence reads are compared[5,6]. Furthermore, while the ribosomal small-subunit (16S/18S/SSU) is a popular marker choice, no single genetic marker seems to be sufficient for covering all taxonomic groups with satisfactory accuracy for species or even genus assignments[7-9]. This has led to the establishment of a wide range of other genetic markers for DNA barcoding and metabarcoding in different organisms, such as *rbcL, matK, trnL,* and *trnH* for plants[10], the ITS region for fungi[11], and the COI gene for animals[12]. This broad diversity of DNA barcodes challenges sequence classification tools, which usually have been developed with the rRNA genes

in mind[13-15]. Although some of these software tools can be re-trained on other reference datasets,

or have their reference databases exchanged for datasets representing other genes, they still make

assumptions with regards to the reference data – such as global alignability – that often negatively

affect performance, or prevent software operation altogether. In addition, increasing stringency

with regards to correct taxonomic assignment often comes at the cost of lower proportions of

classified sequences[16]. This tendency has been shown for some taxonomic classifiers also when

operating on the rRNA genes[17]. The classification tool that appear least prone to show such a

relationship is Metaxa2, which is based on a combination of hidden Markov models (HMMs) and

sequence alignments[17]. Metaxa2 examines arbitrary DNA sequence datasets, such as genomes,

metagenomes, or amplicons, and extracts the SSU and/or LSU rRNA genes; classifies the

sequences to taxonomic origin; and optionally computes a range of diversity estimates for the

studied community. However, Metaxa2 has so far been strictly limited to operation on the rRNA

genes, preventing its use for other DNA barcodes. Yet, the capability of Metaxa2 to achieve high

precision for its classifications while maintaining relatively high sensitivity would be highly

desirable also for other genetic markers, particularly as these genes often are under-sampled in

terms of species coverage[16]. Against this backdrop, the aim of this study was to adapt the

Metaxa2 software for any additional DNA barcode. To this end, the paper presents an update to

Metaxa2 itself, allowing the use of custom databases. We also introduce the Metaxa2 Database

Builder – a software tool that allows users to create customized databases from DNA sequences

and their associated taxonomic affiliations – and a repository for additional reference sets to meet

the needs of the user.

The Metaxa2 Database builder has three different operating modes. The divergent mode is

adapted to deal with barcoding regions for which fairly large sequence variability occurs among

the target taxa, such as the eukaryotic ITS region[18], the *trnH* gene used in plant barcoding[16] and

the COI gene used, e.g., for insects[12]. The conserved mode, on the other hand, is suitable for

barcoding regions that are highly conserved among the target taxa, such as the SSU rRNA genes[19]

and the bacterial *rpoB* gene[20]. In addition, this mode is advisable for certain barcoding genes used

in narrower taxonomic groups, such as Oomycota. In the conserved mode, the software extracts

the barcoding regions from every input sequence and aligns them in order to determine the level

of conservation across every position in the alignment. The most conserved regions are then

extracted from the alignment and used to build HMMs that can be used to extract the barcoding

region from metagenomic data. In the divergent mode, the database builder instead clusters the

input sequences, aligns every individual cluster and builds one HMM for each cluster. The third

mode – the hybrid mode – combines the features and advantages of the two others, but also their

drawbacks. It should therefore only be used when none of those produces satisfactory results.

A key component for the high accuracy of Metaxa2 is the hand-curated classification database[17].

In the database builder, we have tried to emulate this curation by automating as much of our

procedure as possible. There are three ways in which the software attempts to improve the

taxonomic information. First, it can remove uninformative sequences from unknown specimens

or mixed environmental samples. Second, it can make an effort to standardize the input

taxonomy into seven levels. Finally, it can filter out entries without taxonomic affiliation at, for

example, the genus or species level.

We evaluated the Metaxa2 Database Builder on 11 different barcoding regions, targeting a variety

of uses (Supplementary Table 1). We first assessed the software performance on full-length

sequences using the self-evaluation function, measured in terms of sensitivity, specificity, and

error per assignment rate (Supplementary Fig. 1, see methods for details). In general, we found

that at least one of the methods produced more than 80% correct assignments at the family level

for half of the markers (Fig. 1a). However, three of the genetic markers – *rpb1*, *rpb2* and *cpn60* –

consistently showed lower performance across all groups, even at the order level. When we

multiplied the proportion of correct assignments with the total proportion of sequences assigned,

it was clear that the divergent mode consistently was the best performing setting by this measure

(Fig. 1b), mostly because the divergent mode always included the largest proportion of the input

sequences in the final database (Supplementary Fig. 2). However, since the divergent mode

includes essentially all input sequences in the classification database, it necessitates more careful

manual curation of the dataset used for database creation. Therefore, if the data at hand is of

uncertain quality, it may still be more adequate to use the conserved mode.

Fig. 1. Self-evaluated performance of the Metaxa2 Database Builder in different operating modes (conserved, divergent and hybrid) on ten different DNA barcoding regions. A) Proportion of assigned sequences classified to the correct order (circles), family (diamonds) and genera (triangles). B) Proportion of correctly assigned sequences multiplied with the proportion of sequences included in the final classification databases (see Supplementary Fig. 2). The ATP9-NAD9 genetic marker is not shown, because it only had relevant taxonomic differences at the species level.

As an additional performance assessment, we followed the procedure from the original Metaxa2 evaluation[17] and generated fragments of 150 nucleotides from each barcoding region to estimate the performance on shotgun metagenomic data. Here, we found that for most regions, the divergent mode generated the highest proportion of correct classifications (Fig. 2a). For EF1alpha, the hybrid mode performed better, for *matK* the operating modes were essentially tied, and for ATP9-NAD9 the conserved and hybrid modes performed the best. However, the divergent mode also produced higher numbers of misclassifications than the conserved mode did for ITS2, *matK* and *rbcL*, although the hybrid mode showed the largest numbers of incorrect assignments overall (Fig. 2b). Generally, the divergent mode showed the lowest levels of unclassified input sequences and over-predictions (Fig. 2c, 2d). Still, there are obvious differences in performance between different genetic markers. Particularly, it seems to be difficult to build appropriate models for the *rpb* genes and *cpn60*, at least based on the sequence data we used. Depending on what the user values the highest (comprehensiveness, stringency, precision etc.), different settings would be desirable, and several combinations of modes and filtering options should be evaluated against each other to find the optimal settings for each genetic marker and reference dataset. We furthermore compared the evaluation of the fragments to the internal software evaluation for each dataset (Supplementary Fig. 3). We found an essentially linear relationship between the proportion of sequences included in the database times the proportion

of correct sequences in the internal evaluation and the proportion of correctly assigned sequence

fragments (Supplementary Fig. 3e), and thus this may provide a robust measure of overall

database performance.

Fig. 2. Family level Metaxa2 performance on randomly generated 150 bp fragments originating from the sequence datasets used
to build the respective databases in the three different modes (Conserved, Divergent and Hybrid). A) Proportions of fragments
assigned to the correct taxonomic family. B) Proportions of fragments assigned to an incorrect family. C) Proportions of
fragments not assigned, or not recognized as belonging to the investigated barcoding region, at the family level. D) Family-level
overpredictions, i.e. the proportions of sequence fragments belonging to a family not present in the final database, which were
still assigned to a (different) family by Metaxa2. Note that the ATP9-NAD9 dataset is only used for species identification and thus
this marker would be expected to show perfect performance on the family level. Note also that the Y-axis scales are different for
B and for D compared to A and B.

We also compared the classification performance of the native Metaxa2 database to those

resulting from automated construction based on SILVA. We built databases from release 111

(which was used as a starting point for the native Metaxa2 database) and release 128 in the

conserved mode, with two versions for each release; one in which no filtering was applied and

one in which we applied the filtering designed to mimic the manual curation process. We then

classified simulated SSU fragments using Metaxa2, replacing the native database with the newly

built ones. Overall, the results were surprisingly similar (Supplementary Fig. 4), contrary to what

was previously shown when the native database was replaced with the GreenGenes database[17].

Interestingly, there were also rather small differences between the non-filtered and the

automatically filtered databases, although applying filtering increased the number of classified

sequence fragments with full taxonomic annotation and lowered the proportion of incorrect

assignments, particularly at short fragment lengths. This indicates that the automated approach to

database building is feasible, at least when the underlying sequence and taxonomy data are of

high quality.

Evaluations of which taxonomic classification tools show the most consistent performance in

terms of sensitivity and specificity are still largely incomplete[21], particularly for non-standard

barcoding regions, but commonly used software for taxonomic assignment, such as the RDP

Naïve Bayesian Classifier[13] and Rtax[14], have all been shown to perform subpar or inconsistently in

different settings[15-17]. We believe that the lack of comprehensive evaluation does not excuse the

use of methods that produce incorrect or irrelevant results. With decreasing cost of DNA

sequencing and increasing use of shotgun metagenomics for studies of biological communities,

these updates to the Metaxa2 software – vastly extending its capabilities to virtually any high-

quality DNA barcode in use – will enable a leap forward for molecular ecologists and others in

need of precise taxonomic assignment among groups of taxa that are not feasibly targeted by

traditional barcoding markers.

Methods

Software implementation. The Metaxa2 Database Builder (metaxa2_dbb) is a command-line, open source, Unix/Linux tool implemented in Perl. The software requires, on top of Perl, the Metaxa2[17], HMMER3[22], NCBI BLAST[23], and MAFFT[24] software to be installed. In addition, USEARCH[25] or VSEARCH[26] is highly recommended for full functionality. In short, the metaxa2_dbb tool creates the hidden Markov models (HMMs) and BLAST reference databases required to build a custom Metaxa2 classification database. Importantly, metaxa2_dbb can be run in three different operating modes, depending on how similar the sequences in the reference database are to each other.

In the conserved mode, used when sequences have regions of relatively high sequence similarity, the software first identifies a suitable main reference sequence, either by user selection or by clustering the sequences at 80% identity using USEARCH, and then selecting the representative sequence of the largest cluster. Next, it uses the (5') start and (3') end of the main reference sequence to define which of the other sequences in the input dataset should be considered full-length, and extracts those regions using Metaxa2. Thereafter, the identified full-length sequences are aligned using MAFFT, and the regions outside of the start and end of the main reference sequence are trimmed away before re-aligning the trimmed sequences again. This alignment is then used to determine the degree of sequence conservation across the alignment, to identify the regions of high and low conservation. The conserved regions of the alignment are extracted and aligned individually using MAFFT. Those alignments are used to build separate HMMs for each conserved region with hmmbuild of the HMMER package. The full-length input sequences matching at least half of those HMMs are then used to build the BLAST database used for

classification, and their sequence IDs are edited to be compatible with the Metaxa2 database

structure.

In the divergent mode, the input sequences are first clustered into groups with at least 20%

sequence identity using USEARCH. Each such cluster is then aligned separately using MAFFT.

The alignments are subsequently split at the mid position (including gaps), and each pair of

alignments is used to build two separate HMMs using hmmbuild. The input sequences matching

at least one of those HMMs are then used to build the BLAST database for classification, and

their sequence IDs are edited as above. The hybrid mode is a combination of the conserved and

divergent modes, in which the database builder will cluster the input sequences at 20% identity

using USEARCH, and then proceed with same approach as in the conserved mode on each

resulting cluster separately.

From this point, the analysis proceeds identically for the three modes. The software reads

taxonomy data in any of the following formats: ASN.1, NCBI XML, and INSD XML formats, as

provided by GenBank[27]; FASTA format with taxonomy data as part of the sequence headers, as

provided by the SILVA[28] and Greengenes[29] databases; and the Metaxa2 tabulated taxonomy

format. Optionally, the taxonomy data can be filtered to exclude sequences from uncultured or

unknown organisms or with low-resolution taxonomic annotation information. The sequence

data and taxonomic information are subsequently crosschecked such that entries are only

retained if both sequence and taxonomy data are present. The remaining sequences are then

compiled into a BLAST database using formatdb or makeblastdb of the BLAST/BLAST+

packages. Thereafter, unless pre-determined sequence identity cutoffs are provided by the user,

suitable identity thresholds for taxonomic assignments at different classification levels are

automatically determined. This is done by aligning the sequences in the BLAST database using

MAFFT and then calculating the pairwise percent identity within and between taxonomic groups

(intra- and inter-specific sequence identity). The identity cutoff for each taxonomic level is then

set to be below the lowest intra-specific pairwise identity and, if possible, above the highest inter-

specific pairwise identity. The cutoff can never be set to be above 99% identity for any

taxonomic level.

Finally, the metaxa2_dbb software can perform an optional database evaluation step, which is

further described below. A more thorough description of the database construction process can

be found in the software manual (Supplementary Item 1). It should also be noted that to make

the Metaxa2 classifier more reliable across a variety of barcoding regions, we have modified the

algorithm for assigning reliability scores (see the manual for details; Supplementary Item 1).

These modifications in general have very little effect on SSU and LSU classifications, but can

nevertheless result in slight differences when the same dataset is classified using this version of

Metaxa2 and versions prior to 2.2.

Automatic correction of taxonomic data. If the user chooses, metaxa2_dbb can attempt to

adjust the supplied taxonomy data in order to better match the taxonomic levels to those

proposed by the Metaxa2 software (domain, phylum/kingdom, class, order, family, genus,

species, and strain/subspecies). The phylum level is sorted out first, by checking which input

taxonomic level that corresponds to a list of recognized phyla/kingdoms. This is followed by

searching for a taxonomic level below the phylum level with an annotation ending with "-ales" to

define the order level (unless the entry seems to be of metazoan origin). Then, the class level is

defined as the level above the order level, and the family level is defined as the first level below

the order level and with an annotation ending with "-ceae" (or "-idae" for metazoans). The

species level is then identified by finding a taxonomic annotation similar to a Latin binomial

using regular expressions. The genus level is finally defined as the level containing the genus part

of the Latin binomial. This procedure can correct the vast majority of inconsistent taxonomic

annotation data, although manual curation of the output data is highly recommended to catch

exceptional cases.

Use cases and software evaluation. We evaluated the metaxa2_dbb software by providing 12

different use cases involving 11 different DNA barcodes used in different scenarios

(Supplementary Table 1). Notably, the datasets used to evaluate the software were not collected

for the specific purpose of this evaluation, but were rather typical representatives of reference

datasets used in previous or ongoing studies, thereby representing realistically relevant use cases

for the Metaxa2 Database Builder very well. For the ITS2, *matK*, *rbcL*, *trnL* and *trnH* genetic

markers, references were obtained from Richardson et al. (2017)[16]. Briefly, all NCBI nucleotide

sequences for vascular plant available on 2016-03-04 were downloaded, filtered by length, and all

sequences with more than two sequential uncalled nucleotides were removed. The datasets were

then filtered to remove duplicates and sequences from plants not present in Ohio and

surrounding states and provinces. Taxonomic information was obtained from NCBI taxonomy[30].

Sequences with undefined taxonomic information at any rank were removed. For *rpb1*, *rpb2* and

EFalpha, references were obtained from the fungal six-gene phylogeny of James et al.[31]. Sequence

data and taxonomic information were obtained from NCBI. For the 16S rRNA gene, sequences

and taxonomic data for type-strains and cultured strains were downloaded from SILVA release

128[32], and SATIVA[33] was used to remove mislabeled strains. For *cpn60*, sequences were

downloaded from the cpnDB[34] as of 2016-10-21. The complete nucleotide sequences of group I

chaperonins, i.e. *cpn60* (also known as *hsp60* or *groEL*), which is found in bacteria, some archaea,

mitochondria and plastids, were used for building the database. Two datasets were downloaded,

both the FASTA file of all group I sequences and a reduced file with only reference genome

representatives. Taxonomic classifications were transferred from the SILVA annotation of

release 111 and then manually curated. Finally, for ATP9-NAD9, we used a database assembled

from curated sequences including 140 different *Phytophthora* species/hybrids (GenBank accession

numbers JF771616.1 to JF772053.1 and JQ439009.1 to JQ439486.1, and Bilodeau and

Robideau[35]; n.b. a total of 123 species are currently described; http://www.phytophthoradb.org).

When sequence and taxonomic data had been obtained for each of these genetic markers, we ran

the metaxa2_dbb software on each data set using the conserved, divergent and hybrid modes. We

also enabled the self-evaluation option, which performs a cross-validation of the database

performance similar to that of Richardson et al.[16]. For the self-evaluation we used the default

settings, which correspond to rebuilding the database ten times, each time using 90% of the input

sequences to build the database (the training set) and then subsequently classifying the remaining

10% of input sequences (the testing set) using Metaxa2. The predicted taxonomic classifications

were then compared against the taxonomic identity of each test sequence derived from the

source databases at every taxonomic level, generating measures for sensitivity (proportion of test

sequences identified as matching the barcoding region), specificity (proportion of correctly

classified sequences at the taxonomic level in question), and the error per classification ratio

(proportion of incorrectly classified sequences per total classifications made).

In addition to the software self-evaluation, we also tested the classification performance of the

different databases on sequence fragments derived from the sequences used to build the

respective database. This evaluation followed the method used for the original Metaxa2 paper[17],

although we only generated fragments of a single length, viz. 150 nucleotides. The test sets were

generated by randomly selecting a stretch of 150 nucleotides from every sequence in the input

data for each barcoding region. We then used Metaxa2 version 2.2 to classify these simulated

read data sets and calculated the performance for each barcoding region in terms of accuracy

(proportion of correctly classified sequence fragments), misclassifications (incorrect assignments),

sensitivity (proportion of non-detected sequence fragments), and over-prediction (incorrect

assignment to a rank for which there is no reference belonging to the query taxa present in the

database). Sequence fragments were regarded as correctly classified if their reported taxonomy

corresponded to the known taxonomy of the input sequence that the fragment was derived from,

at every taxonomic level as reported by Metaxa2. If any incorrect taxonomic affiliations were

reported at any taxonomic level, the fragment was regarded as misclassified.

We finally compared the performance of the hand-curated Metaxa2 SSU rRNA database that is

bundled with the software to SSU rRNA databases built by metaxa2_dbb from the sequences in

SILVA release 111 and 128[28]. The native Metaxa2 database is based on SILVA release 111, which

means that the comparison between the native database and release 111 is relevant to understand

the differences between the manual and automatic database constructions. The difference to

release 128, on the other hand, is rather a test of whether the accuracy changes with the addition

of more reference sequences. The SILVA databases were created by downloading the FASTA file

representing the reference SSU sequences with 99% non-redundancy (SSURef_Nr99) with

taxonomy from SILVA. We then added the SSU sequences for the 12S rRNA used in the native

Metaxa2 database from MitoZoa[17,36]. From these, we used Metaxa2 version 2.1.2 (default settings)

to divide the SSU sequences by taxonomic domain. The resulting files were used as input for

metaxa2_dbb, which was run by retaining the HMM profiles from the native database, i.e. only

rebuilding the classification database. In all cases, taxonomy correction was used, and cutoffs

were manually set to "0,60,70,75,85,90,97"[17]. The full options were: "metaxa2_dbb -o

SSU_SILVAXXX   -g   SSU   -p   metaxa2_db/SSU/HMMs/   -t

SILVA_XXX_SSURef_Nr99_tax_silva.fasta -a archaea.fasta -b bacteria.fasta -c chloroplast.fasta

-e eukaryota.fasta -m mitochondria.fasta -n mitozoa_SSU.fasta --correct_taxonomy T --cutoffs

'0,60,70,75,85,90,97' --cpu 16". For each SILVA release, two databases were built, one with the

command above, and one in which filtering of taxonomic information was applied, adding the "--

filter_uncultured T --filter_level 6" options.

After these new SILVA-based classification databases had been constructed, we classified the

simulated SSU read fragments with high-quality taxonomic information used in the original

Metaxa2 evaluation, and ran this in the same way as in the original paper[17]. The results of the

classifications were investigated manually to make sure that errors made by Metaxa2 were due to

actual classification errors and not renaming of taxa, inconsistencies in taxonomy between

database versions, synonymous names used for one taxon, or misspellings. As in the original

Metaxa2 paper, a sequence fragment was regarded correctly classified if the reported taxonomy

corresponded to the known taxonomy of the input sequence at every taxonomic level, as

reported by Metaxa2. If the Metaxa2 classification was found to completely correspond to the

known taxonomic affiliation at all investigated taxonomic levels, the sequence fragment was

regarded as perfectly classified. If Metaxa2 reported any incorrect taxonomic affiliation at any

taxonomic level the fragment was regarded as misclassified.

Acknowledgements

The authors would like to thank Prof. Christer Erséus for input on the International Code of
Zoological Nomenclature. JBP acknowledges financial support from the Swedish Research
Council for Environment, Agricultural Sciences and Spatial Planning (FORMAS; grant 2016-
768). RTR was supported by a Project Apis m. - Costco Honey Bee Biology Fellowship. KME
acknowledges financial support from FORMAS (grant 2012-86). RHN acknowledges funding
from FORMAS (grant 215-2011-498).

Author contributions

JBP and RTR conceived and designed the study. JBP designed the software, with input from
RTR, RMJ, MH and RHN. JBP implemented the software. JBP, KME and RHN updated the
software manual. RTR, CW, EDT, MM, KT, GJB and RMJ provided and curated data for
software evaluation. JBP, RTR, CW, MM, KT and KK evaluated software performance. JBP,
KME, MH and RHN updated the classification databases. JBP drafted the manuscript, with help
from RTR and RHN. All authors contributed to and approved the final manuscript.

Competing financial interests

350 The authors declare no competing financial interests.

Figure legends

Fig. 1. Self-evaluated performance of the Metaxa2 Database Builder in different operating modes (conserved, divergent and hybrid) on ten different DNA barcoding regions. A) Proportion of assigned sequences classified to the correct order (circles), family (diamonds) and genera (triangles). B) Proportion of correctly assigned sequences multiplied with the proportion of sequences included in the final classification databases (see Supplementary Fig. 2). The ATP9-NAD9 genetic marker is not shown, because it only had relevant taxonomic differences at the species level.

Fig. 2. Family level Metaxa2 performance on randomly generated 150 bp fragments originating from the sequence datasets used to build the respective databases in the three different modes (Conserved, Divergent and Hybrid). A) Proportions of fragments assigned to the correct taxonomic family. B) Proportions of fragments assigned to an incorrect family. C) Proportions of fragments not assigned, or not recognized as belonging to the investigated barcoding region, at the family level. D) Family-level overpredictions, i.e. the proportions of sequence fragments belonging to a family not present in the final database, which were still assigned to a (different) family by Metaxa2. Note that the ATP9-NAD9 dataset is only used for species identification and thus this marker would be expected to show perfect performance on the family level. Note also that the Y-axis scales are different for B and for D compared to A and B.

References

1. Woese, C. R., Kandler, O. & Wheelis, M. L. Towards a natural system of organisms: proposal for the domains Archaea, Bacteria, and Eucarya. *Proc Natl Acad Sci USA* **87,** 4576–4579 (1990).

2. Hibbett, D. *et al.* Sequence-based classification and identification of Fungi. *Mycologia* (2016). doi:10.3852/16-130

3. Yoccoz, N. G. The future of environmental DNA in ecology. *Mol Ecol* **21,** 2031–2038 (2012).

4. Taberlet, P., Coissac, E., Pompanon, F., Brochmann, C. & Willerslev, E. Towards next-generation biodiversity assessment using DNA metabarcoding. *Mol Ecol* **21,** 2045–2050 (2012).

5. Bengtsson-Palme, J. *et al.* Strategies to improve usability and preserve accuracy in biological sequence databases. *Proteomics* **16,** 2454–2460 (2016).

6. Nilsson, R. H. *et al.* Taxonomic reliability of DNA sequences in public sequence databases: a fungal perspective. *PLoS ONE* **1,** e59 (2006).

7. Wang, X.-C. *et al.* ITS1: a DNA barcode better than ITS2 in eukaryotes? *Mol Ecol Resour* **15,** 573–586 (2015).

8. Lindahl, B. D. *et al.* Fungal community analysis by high-throughput sequencing of amplified markers - a user's guide. *New Phytol* (2013). doi:10.1111/nph.12243

9. Bruns, T. D. & Taylor, J. W. Comment on "Global assessment of arbuscular mycorrhizal fungus diversity reveals very low endemism". *Science* **351,** 826 (2016).

10. Richardson, R. T. *et al.* Rank-based characterization of pollen assemblages collected by honey bees using a multi-locus metabarcoding approach. *Appl Plant Sci* **3,** (2015).

11. Schoch, C. L. *et al.* Nuclear ribosomal internal transcribed spacer (ITS) region as a universal DNA barcode marker for Fungi. *Proc Natl Acad Sci USA* **109,** 6241–6246 (2012).

12. Hebert, P. D. N., Ratnasingham, S. & deWaard, J. R. Barcoding animal life: cytochrome c oxidase subunit 1 divergences among closely related species. *Proc Biol Sci* **270 Suppl 1,** S96–9 (2003).

13. Wang, Q., Garrity, G. M., Tiedje, J. M. & Cole, J. R. Naive Bayesian classifier for rapid assignment of rRNA sequences into the new bacterial taxonomy. *Appl Environ Microbiol* **73,** 5261–5267 (2007).

14. Soergel, D. A. W., Dey, N., Knight, R. & Brenner, S. E. Selection of primers for optimal taxonomic classification of environmental 16S rRNA gene sequences. *ISME J* **6,** 1440–1444 (2012).

15. Edgar, R. SINTAX: a simple non-Bayesian taxonomy classifier for 16S and ITS sequences. *bioRxiv* 074161 (2016). doi:10.1101/074161

16. Richardson, R. T., Bengtsson-Palme, J. & Johnson, R. M. Evaluating and optimizing the performance of software commonly used for the taxonomic classification of DNA metabarcoding sequence data. *Mol Ecol Resour* **17,** 760–769 (2017).

17. Bengtsson-Palme, J. *et al.* Metaxa2: Improved identification and taxonomic classification of small and large subunit rRNA in metagenomic data. *Mol Ecol Resour* **15,** 1403–1414 (2015).

18. Nilsson, R. H. *et al.* Five simple guidelines for establishing basic authenticity and reliability of newly generated fungal ITS sequences. *MycoKeys* **4,** 37–63 (2012).

19. Hartmann, M., Howes, C. G., Abarenkov, K., Mohn, W. W. & Nilsson, R. H. V-Xtractor:
an open-source, high-throughput software tool to identify and extract hypervariable
regions of small subunit (16S/18S) ribosomal RNA gene sequences. *J Microbiol Methods* **83,**
250–253 (2010).
20. Dahllöf, I., Baillie, H. & Kjelleberg, S. rpoB-based microbial community analysis avoids
limitations inherent in 16S rRNA gene intraspecies heterogeneity. *Appl Environ Microbiol*
66, 3376–3380 (2000).
21. Bengtsson-Palme, J. **Strategies for Taxonomic and Functional Annotation of**
Metagenomes in *Metagenomics: Perspectives, Methods, and Applications* (ed. Nagarajan, M.) 55–
79 (Academic Press, Elsevier, Oxford, 2018).
22. Eddy, S. HMMER. *http://hmmer.janelia.org* (2010).
23. Altschul, S. F. *et al.* Gapped BLAST and PSI-BLAST: a new generation of protein
database search programs. *Nucleic Acids Res* **25,** 3389–3402 (1997).
24. Katoh, K. & Standley, D. M. MAFFT multiple sequence alignment software version 7:
improvements in performance and usability. *Mol Biol Evol* **30,** 772–780 (2013).
25. Edgar, R. C. Search and clustering orders of magnitude faster than BLAST. *Bioinformatics*
26, 2460–2461 (2010).
26. Rognes, T., Flouri, T., Nichols, B., Quince, C. & Mahé, F. VSEARCH: a versatile open
source tool for metagenomics. *PeerJ* **4,** e2584 (2016).
27. Clark, K., Karsch-Mizrachi, I., Lipman, D. J., Ostell, J. & Sayers, E. W. GenBank. *Nucleic*
Acids Res **44,** D67–72 (2016).
28. Quast, C. *et al.* The SILVA ribosomal RNA gene database project: improved data
processing and web-based tools. *Nucleic Acids Res* **41,** D590–6 (2013).
29. McDonald, D. *et al.* An improved Greengenes taxonomy with explicit ranks for ecological
and evolutionary analyses of bacteria and archaea. *ISME J* **6,** 610–618 (2012).
30. Federhen, S. The NCBI Taxonomy database. *Nucleic Acids Res* **40,** D136–43 (2012).
31. James, T. Y. *et al.* Reconstructing the early evolution of Fungi using a six-gene phylogeny.
Nature **443,** 818–822 (2006).
32. Yilmaz, P. *et al.* The SILVA and 'All-species Living Tree Project (LTP)' taxonomic
frameworks. *Nucleic Acids Res* **42,** D643–8 (2014).
33. Kozlov, A. M., Zhang, J., Yilmaz, P., Glöckner, F. O. & Stamatakis, A. Phylogeny-aware
identification and correction of taxonomically mislabeled sequences. *Nucleic Acids Res* **44,**
5022–5033 (2016).
34. Hill, J. E., Penny, S. L., Crowell, K. G., Goh, S. H. & Hemmingsen, S. M. cpnDB: a
chaperonin sequence database. *Genome Res* **14,** 1669–1675 (2004).
35. Bilodeau, G. J. & Robideau, G. P. Optimization of nucleic acid extraction from field and
bulk samples for sensitive direct detection of plant pests. *Phytopathology* **104,** S3.14 (2014).
36. D'Onorio de Meo, P. *et al.* MitoZoa 2.0: a database resource and search tools for
comparative and evolutionary analyses of mitochondrial genomes in Metazoa. *Nucleic Acids*
Res **40,** D1168–72 (2012).
454