Idiosyncratic, retinotopic bias in face identification

modulated by familiarity

Abbreviated title: Retinotopic bias in face identification

Matteo Visconti di Oleggio Castello[1,*], Morgan Taylor[1], Patrick Cavanagh[1,2],

M. Ida Gobbini[1,3,*]

[1]Department of Psychological & Brain Sciences,

Dartmouth College,

Hanover NH, 03755, USA

[2]Department of Psychology

Glendon College

Toronto ON, M4N 3M6 Canada

[3]Dipartimento di Medicina Specialistica, Diagnostica, e Sperimentale,

University of Bologna,

40100 Bologna, Italy

*corresponding authors:

M. Ida Gobbini, maria.i.gobbini@dartmouth.edu, mariaida.gobbini@unibo.it

Matteo Visconti di Oleggio Castello, mvdoc.gr@dartmouth.edu

6207 Moore Hall

Dartmouth College

Hanover, NH 03755, USA

Number of pages: 29

Number of figures: 4

Number of tables: 3

Words (Abstract):   165

Words (Introduction): 632

Words (Discussion):   597

Conflict of Interest

The authors declare no competing financial interests.

Acknowledgments

We would like to thank the Marten's Family Fund for its support.

Abstract

The perception of gender and age of unfamiliar faces is reported to vary idiosyncratically across retinal locations such that, for example, the same androgynous face may appear to be male at one location but female at another. Here we test spatial heterogeneity for the recognition of the *identity* of personally familiar faces. We found idiosyncratic biases that were stable within subjects and that varied more across locations for low as compared to high familiar faces. These data suggest that like face gender and age, face identity is processed, in part, by independent populations of neurons monitoring restricted spatial regions and that the recognition responses vary for the same face across these different locations. Moreover, repeated exposure to the same face in different portions of the visual field due to repeated and varied social interactions appears to lead to adjustment of these independent face recognition neurons so that the same familiar face is eventually more likely to elicit the same recognition response across widely separated regions.

Significance statement

In this work we tested spatial heterogeneity for the recognition of personally familiar faces. We found retinotopic biases that varied more across locations for low as compared to highly familiar faces. The retinotopic biases were idiosyncratic and stable within subjects. Our data suggest that, like face gender and age, face identity is processed by independent populations of neurons

monitoring restricted spatial regions and that recognition may vary for the same

face at these different locations. Unlike previous findings, our data show how

the effect of learning modifies the representation of face identity in

retinotopically-organized visual cortex. This new perspective has broader

implications for understanding how learning optimizes visual processes for

socially salient stimuli.

Introduction

We spend most of our days interacting with acquaintances, family and close

friends. Because of these repeated and protracted interactions, the

representation of personally familiar faces is rich and complex, as reflected by

stronger and more widespread neural activation in the distributed face

processing network, as compared to responses to unfamiliar faces (Gobbini and

Haxby, 2007; Taylor et al., 2009; Gobbini, 2010; Natu and O'Toole, 2011; Bobes

et al., 2013; Sugiura, 2014; Ramon and Gobbini, 2017; Visconti di Oleggio

Castello et al., 2017a). Differences in representations of familiar as compared to

unfamiliar faces is also reflected in faster detection of familiar faces and more

robust recognition (Burton et al., 1999; Gobbini et al., 2013; Ramon et al., 2015;

Visconti di Oleggio Castello and Gobbini, 2015; Visconti di Oleggio Castello et

al., 2017b). Thus, despite the subjective feeling of expertise with faces in general

(Diamond and Carey, 1986), our visual system seems to be optimized for the

processing of familiar faces. The mechanisms underlying the prioritized

processing of familiar faces are still a matter of investigation (Guntupalli and

Gobbini, 2017; Ramon and Gobbini, 2017; Young and Burton, 2017).

The advantage for familiar faces could originate at different stages of the visual

processing stream. In a study measuring saccadic reaction time, correct and

reliable saccades to familiar faces were recorded as fast as 180 ms when

unfamiliar faces were distractors (Visconti di Oleggio Castello and Gobbini,

2015). At such short latencies it is unlikely that a viewpoint-invariant

representation of an individual face's identity drives the saccadic response. To

account for facilitated, rapid detection of familiarity, we have previously

hypothesized that personally familiar faces may be recognized quickly based on

diagnostic, idiosyncratic features, which become highly learned through

extensive personal interactions (Visconti di Oleggio Castello and Gobbini, 2015;

Visconti di Oleggio Castello et al., 2017b). In a study of perception of gaze

direction and head angle, changes in eye gaze were detected around 100ms

faster in familiar than in unfamiliar faces (Visconti di Oleggio Castello and

Gobbini, 2015). These data provide support for the hypothesis that facial

features that are diagnostic for identity are processed more efficiently for familiar

as compared to unfamiliar faces. Detection of these features may occur early in

the visual hierarchy, allowing an initial, fast differential processing for personally

familiar faces.

Processes occurring at early stages of the visual system can show idiosyncratic

retinotopic biases (Greenwood et al., 2017). Afraz et al. (2010) reported

retinotopic biases for perceiving face gender and age that vary depending on

stimulus location in the visual field and were specific to each subject. These

results suggest that neurons in higher-order face areas have restricted receptive

fields or, equivalently, that diagnostic facial features for gender and age are

encoded in retinotopic visual cortices. Here we reasoned that diagnostic visual

features that play a role in visual processes for individuating faces may show

idiosyncratic retinotopic biases and that these biases may be tuned by repeated

interactions with personally familiar faces. Such biases may affect recognition of

the identities presented in different parts of the visual field and may be

modulated by the familiarity of those identities.

We tested this hypothesis by presenting participants with morphed stimuli of

personally familiar individuals that were briefly shown at different retinal

locations. In two separate experiments we found that participants showed

idiosyncratic biases for specific identities in different visual field locations, and

these biases were stable on retesting after weeks. Importantly, the range of the

retinal biases was inversely correlated with the reported familiarity of each target

identity, suggesting that prolonged personal interactions with the target

individuals reduced retinal biases. These findings provide additional support for

the hypothesis that asymmetries in the processing of personally familiar faces

can arise at stages of the visual processing hierarchy where there is still

retinotopic coding.

Materials and Methods

Figure 1. Experimental paradigm. The left panel shows an example of the experimental paradigm, while the right panel shows the angular locations used in Experiment 1 (eight locations, top panel) and in Experiment 2 (four locations, bottom panel).

Stimuli

Pictures of the faces of individuals who were personally familiar to the participants (graduate students in the same department) were taken in a photo studio room with the same lighting condition and the same camera. Images of two individuals were used for Experiment 1, and images of three individuals were used for Experiment 2. All individuals portrayed in the stimuli signed written informed consent to use their pictures for research and in publications.

The images were converted to grayscale, resized and centered so that the eyes were aligned in the same position for the three identities, and the background was manually removed. These operations were performed using ImageMagick and Adobe Photoshop CS4. The resulting images were matched in luminance

(average pixel intensity) using the SHINE toolbox (function *lumMatch*)

(Willenbockel et al., 2010) after applying an oval mask, so that only pixels

belonging to the face were modified. The luminance-matched images were then

used to create morph continua (between two identities in Experiment 1, see

Figure 2; and among three identities in Experiment 2, see Figure 3) using

Abrosoft Fantamorph (v. 5.4.7) with seven percentages of morphing: 0, 17, 33,

50, 67, 83, 100 (see Figures 2, 3).

Experiment 1

Paradigm

The experimental paradigm was similar to that by (Afraz et al., 2010). In every

trial participants would see a briefly flashed image in one of eight locations at

the periphery of their visual field (see Figure 1). Each image was shown for 50

ms at a distance of $7°$ of visual angle from the fixation point, and subtended

approximately $4° \times 4°$ of visual angle. The images could appear in one of eight

locations evenly spaced by 45 angular degrees. For Experiment 1, only the

morph *ab* was used (see Figure 1). Participants were required to maintain fixation

on a central red dot subtending approximately $1°$ of visual angle.

After the image disappeared, participants reported which identity they saw using

the left (identity *a*) and right (identity *b*) arrow keys. There was no time limit for

responding, and participants were asked to be as accurate as possible. After

responding, participants had to press the spacebar key to continue to the next

trial.

Participants performed five blocks containing 112 trials each, for a total of 560

trials. In each block all the images appeared twice for every angular location (8

angular locations x 7 morph percentages x 2 = 112). This provided ten data

points for each percentage morphing at each location, for a total of 70 trials at

each angular location.

Before the experimental session participants were shown the identities used in

the experiment (corresponding to 0% and 100% morphing, see Figure 2), and

practiced the task with 20 trials. These data were discarded from the analyses.

Participants performed two identical experimental sessions at least four weeks

apart.

Participants sat at a distance of approximately 50 cm from the screen, with their

chin positioned on a chin-rest. The experiment was run using Psychtoolbox

(Kleiner et al., 2007) (version 3.0.12) in MATLAB (R2014b). The screen operated

at a resolution of 1920x1200 and a 60Hz refresh rate.

Subjects

We recruited six subjects for this experiment (three males, including one of the

authors, MVdOC). The sample size for Experiment 1 was not determined by

formal estimates of power, and was limited by the availability of participants

familiar with the stimulus identities. After the first experimental session, two

participants (one male, one female) were at chance level in the task, thus only

data from four subjects (two males, mean age 27.50 ± 2.08 SD) were used for

the final analyses.

All subjects had normal or corrected-to-normal vision, and provided written

informed consent to participate in the experiment. The study was approved by

the Dartmouth College Committee for the Protection of Human Subjects.

Experiment 2

Paradigm

Experiment 2 differed from Experiment 1 in the following parameters (see

Figures 1, 3): 1. three morph continua (*ab*, *ac*, *bc*) instead of one; 2. images

appeared in four angular locations (45°, 135°, 225°, 315°) instead of eight; 3.

images were shown for 100 ms instead of 50 ms to make the task easier.

All other parameters were the same as in Experiment 1. Participants had to

indicate which of the three identities they saw by pressing the left (identity *a*),

right (identity *b*), or down (identity *c*) arrow keys.

Participants performed ten blocks containing 84 trials each, for a total of 840

trials. In each block all the images appeared once for every angular location (4

angular locations x 7 morph percentages x 3 morphs = 84). We used 70 data

points at every angular location to fit the model for each pair of identities. Thus,

we used the responses to different unmorphed images for each pair of identities,

ensuring independence of the models.

Before the experimental session participants were shown the identities used in

the experiment (corresponding to 0% and 100% morphing, see Figure 3), and

practiced the task with 20 trials. These data were discarded from the analyses.

Participants performed two experimental sessions at least four weeks apart.

Subjects

Ten participants (five males, mean age 27.30 ± 1.34 SD) participated in

Experiment 2, five of which were recruited for Experiment 1 as well. No authors

participated in Experiment 2. The sample size (n = 10) was determined using

G*Power3 (Faul et al., 2007, 2009) to obtain 80% power at α = 0.05 based on

the correlation of the PSE estimates across sessions in Experiment 1, using a

bivariate normal model (one-tailed).

All subjects had normal or corrected-to-normal vision, and provided written

informed consent to participate in the experiment. The study was approved by

the Dartmouth College Committee for the Protection of Human Subjects.

Familiarity and contact scales

After the two experimental sessions, participants completed a questionnaire

designed to assess how familiar each participant was with the identities shown

in the experiment. Participants saw each target identity, and were asked to

complete various scales for that identity. The questionnaire comprised the

"Inclusion of the Other in the Self" scale (IOS) (Aron et al., 1992; Gächter et al.,

2015), the "Subjective Closeness Inventory" (SCI) (Berscheid et al., 1989), and

the "We-scale" (Cialdini et al., 1997). The IOS scale showed two circles

increasingly overlapping labeled "You" and "X", and participants were given the

following instructions: *Using the figure below select which pair of circles best*

describes your relationship with this person. In the figure "X" serves as a

placeholder for the person shown in the image at the beginning of this section,

and you should think of "X" being that person. By selecting the appropriate

number please indicate to what extent you and this person are connected (Aron

et al., 1992; Gächter et al., 2015). The SCI scale comprised the two following

questions: *Relative to all your other relationships (both same and opposite sex)*

how would you characterize your relationship with the person shown at the

beginning of this section?, and *Relative to what you know about other people's*

close relationships, how would you characterize your relationship with the person

shown at the beginning of this section? Participants responded with a number

between one *(Not close at all)* and seven *(Very close) (Berscheid et al., 1989)*.

The We-scale comprised the following question: *Please select the appropriate*

number below to indicate to what extent you would use the term "WE" to

characterize you and the person shown at the beginning of this section.

Participants responded with a number between one *(Not at all)* and seven *(Very*

much so). For each participant and each identity we created a composite

"familiarity score" by averaging the scores in the three scales.

We also introduced a scale aimed at estimating the amount of interaction or

contact between the participant and the target identity. The scale was based on

the work by (Idson and Mischel, 2001), and participants were asked to respond

Yes/No to the following six questions: *Have you ever seen him during a*

departmental event?, *Have you ever seen him during a party?*, *Have you ever*

had a group lunch/dinner/drinks with him?, *Have you ever had a one-on-one*

lunch/dinner/drinks with him?, *Have you ever texted him personally (not a group*

message)?, and *Have you ever emailed him personally (not a group email)?* The

responses were converted to 0/1 and for each participant and for each identity

we created a "contact score" by summing all the responses.

For each subject separately, to obtain a measure of familiarity and contact

related to each morph, we averaged the familiarity and contact scores of each

pair of identities (e.g., the familiarity score of morph *ab* was the average of the

scores for identity *a* and identity *b*).

Psychometric fit

For both experiments we fitted a group-level psychometric curve using Logit

Mixed-Effect models as implemented in *lme4 (Bates et al., 2015)*. For each

experiment and each session, we fitted a model of the form

252
$$y^k = \text{logit}\left(\beta_0 x + \sum_{i=1}^{n}(\beta_i + z_i^k)I_i\right)$$

where k indicates the subject, n is the number of angular locations ($n = 8$ for the

first experiment, and $n = 4$ for the second experiment), I_i is an indicator variable

for the angular location, β_i are the model fixed-effects, and z_i are the subject-

level random-effects (random intercept). From this model, we defined for each

subject the Point of Subjective Equality (PSE) as the point x such that logit(x) =

0.5, that is for each angular location

259
$$PSE_i^k = -\frac{\beta_i}{\beta_0} - \frac{z_i^k}{\beta_0} = PSE_i^p + \Delta PSE_i^k$$

Thus, the PSE for subject k at angular location i can be decomposed in a

population-level PSE and a subject-specific deviation from the population level,

indicated with PSE^p and ΔPSE^k respectively.

In Experiment 2 we fitted three separate models for each of the morph continua.

In addition, prior to fitting we removed all trials in which subjects mistakenly

reported a third identity. For example, if an image belonging to morph ab was

presented, and subjects responded with c, the trial was removed.

Code and data availability

268   Code and data for both experiments are available at [link removed: will be made

269   public after publication].

Results

Experiment 1

In this experiment, participants performed a two-alternative forced-choice (AFC)

task on identity discrimination. In each trial they saw a face presented for 50 ms,

and were asked to indicate which of the two identities they just saw. Each face

could appear in one of eight stimulus locations. Participants performed the same

experiment with the same task a second time, at least 33 days after the first

session (average 35 days ± 4 days standard deviation).

Participants showed stable and idiosyncratic retinal heterogeneity for

identification. The PSE estimates for the two sessions were significantly

correlated (see Table 1 and Figure 2B), showing stable estimates, and the within-

subject correlations of ΔPSEs (see Methods) was significantly higher than the

between-subject correlation (correlation difference: 0.87 [0.64, 1.10], 95% BCa

confidence intervals (Efron, 1987); see Table 2), showing that the biases were

idiosyncratic (see Figure 2A for example fits for two different subjects).

Table 1. Correlation of parameter estimates across sessions for the two experiments.				
Parameter	r	t	df	p
Experiment 1				
PSE	0.89 [-0.23, 1]	4.86**	6	0.002831
ΔPSE	0.71 [0.47, 0.84]	5.47***	30	6.106e-06
Experiment 2				
PSE	0.98 [0.93, 0.99]	15.22***	10	3.042e-08
ΔPSE	0.64 [0.5, 0.75]	9.02***	118	3.997e-15
Note: *All confidence intervals are 95% BCa with 10,000 repetitions.* *p < .05. ** p < .01. *** p < .001*				

Table 2. Comparison of within-subjects correlations of parameter estimates across sessions with between-subjects correlations.			
Morph	Within-subjects r	Between-subjects r	Difference
Experiment 1			
ab	0.65† [0.57, 0.8]	-0.22 [-0.41, -0.01]	0.87† [0.63, 1.1]
Experiment 2			
ab	0.32 [-0.10, 0.62]	-0.02 [-0.15, 0.11]	0.34 [-0.07, 0.69]
ac	0.62† [0.35, 0.79]	-0.07 [-0.21, 0.08]	0.68† [0.41, 0.92]
bc	0.85† [0.61, 0.95]	-0.08 [-0.27, 0.12]	0.92† [0.68, 1.15]
Note: *All confidence intervals are 95% BCa with 10,000 repetitions.* *† indicates that the CIs do not contain 0.*			

Figure 2. Stable and idiosyncratic biases in identification in Experiment 1.
A) Psychometric fit for two subjects from one of the two sessions. Colors indicate angular location; actual data (points) are shown only for the extreme locations to avoid visual clutter. B) The parameter estimates across sessions (at least 33 days apart) were stable (r = 0.71 [0.47, 0.84], see Table 1). C) Example morphs used in the experiment. Note that the morphs depicted here are shown for illustration only, and participants saw morphs of identities that were personally familiar to them.

Experiment 2

In this experiment, participants performed a similar task as in Experiment 1, with

the following differences. First, each face was presented for 100 ms instead of

50 ms in order to make the task easier; second, each face could belong to one

of three morphs, and participants were required to indicate which of three

identities the face belonged to; third, each face could appear in four retinal

locations instead of eight (see Figure 1). Each participant performed another

experimental session at least 28 days after the first session (average 33 days ±

8 days SD).

We found that participants exhibited stable biases across sessions for the three

morphs (see Table 1 and Figure 3). Interestingly, within-subjects correlations

were higher than between-subjects correlations for the two morphs that

included the identity *c* (morphs *ac* and *bc*), but not for morph *ab* (see Table 2),

suggesting stronger differences in spatial heterogeneity caused by identity *c*. To

test this further, we performed a two-way ANOVA on the PSE estimates across

sessions with participants and angular locations as factors. The ANOVA was run

for each pair of morphs containing the same identity (e.g., for identity *a* the

ANOVA was run on data from morphs *ab* and *ac*), and the PSE estimates were

transformed to be with respect to the same identity (e.g., for identity *b* we

considered PSE_{bc} and 100 - PSE_{ab}). We found significant interactions between

participants and angular locations for identity *b* ($F(27, 120) = 1.77$, $p = 0.01947$)

and identity *c* ($F(27, 120) = 3.34$, $p = 3.229e-06$), but not identity *a* ($F(27, 120) =$

1.17, p = 0.2807), confirming that participants showed increased spatial

heterogeneity for identities *b* and *c*. Moreover, inspecting the ΔPSE estimates

for each individual subjects (Figure 4A) revealed lower variance across retinal

locations of the biases for morph *ab* than the other two morphs.

The variance of the average ΔPSE estimates across sessions for each subject

was significantly correlated with the reported familiarity of the identities

(r = -0.56 [-0.71, -0.30], t(28) = -3.59, p = 0.001248), showing that the strength

of the retinal bias for identities was inversely modulated by personal familiarity

(see Figure 4B). Because the amount of personal familiarity was correlated with

the amount of contact with a target identity (r = 0.45 [0.17, 0.68], t(28) = 2.65,

p = 0.01304), we tested whether a linear model predicting ΔPSE with both

contact and familiarity as predictors could fit the data better. Both models were

significant, but the model with two predictors explained more variance as

indicated by higher R^2: R^2 = 0.45, adjusted R^2 = 0.40 for the model with both

Familiarity and Contact scores (F(2, 27) = 10.82, p = 0.0003539), and R^2 = 0.32,

adjusted R^2 = 0.29 for the model with the Familiarity score only (F(1, 28) = 12.88,

p = 0.001248). Importantly, both predictors were significant (see Table 3),

indicating that familiarity modulated the variance of the ΔPSE estimates in

addition to modulation based on the amount of contact with a person. After

adjusting for the contact score, the variance of the ΔPSE estimates and the

familiarity score were still significantly correlated (r_p = -0.42 [-0.61, -0.16], t(28) =

-2.42, p = 0.02235).

Table 3. Models predicting variance of the ΔPSE estimates across angular locations in Experiment 2.						
Model	**R^2**	**Score**	**β**	**η_p^2**	**t**	**p**
1	0.32	Familiarity	-0.0574	0.32	-3.59	0.0013
2	0.45	Familiarity	-0.0390	0.17	-2.38	0.0249
		Contact	-0.0452	0.19	-2.512	0.0183

Figure 3. Stable and idiosyncratic biases in identification in Experiment 2.
A) Psychometric fit for one subject from one of the two sessions for each of the morphs. Colors indicate angular location; actual data (points) are shown only for the extreme locations to avoid visual clutter. B) The parameter estimates across sessions (at least 28 days apart) were stable (r = 0.64 [0.5, 0.75], see Table 1). C) Example morphs used in the experiment. Note that the morphs depicted here are shown only for illustration (participants saw morphs of identities who were personally familiar).

Figure 4. The strength of idiosyncratic biases was modulated by personal familiarity. A) Individual subjects' ΔPSE for each morph, averaged across sessions. Note the difference in variance across angular locations for the three different morphs (left to right)). B) The variance across angular locations of ΔPSE estimates was inversely correlated with the reported familiarity of the identities (left panel; r = -0.56 [-0.71, -0.30]), even when adjusting for the Contact score (middle panel; r_p = -0.42 [-0.61, -0.16]). The right panel shows the scatterplot between the Contact score and the ΔPSE variance, adjusted for the Familiarity score, which were significantly correlated as well (r_p = -0.44 [-0.62, -0.17]). See Methods for definition of the Familiarity score and the Contact score.

Discussion

Afraz et al. (2010) reported spatial heterogeneity for recognition of facial attributes such as gender and age, suggesting that relatively independent neural populations tuned to facial features might sample different regions of the visual field. Prolonged social interactions with personally familiar faces lead to facilitated, prioritized processing of those faces. Here we wanted to investigate if this learning of face identity through repeated social interactions also affects these local visual processes, by measuring spatial heterogeneity of identity recognition. We measured whether face identification performance for personally familiar faces differed according to the location in the visual field where face images were presented. We found that participants exhibited idiosyncratic, retinotopic biases for different face identities that were stable across experimental sessions. Importantly, the variability of the retinotopic bias was reduced with increased familiarity with the target identities. These data support the hypothesis that familiarity entails learning visual features that affect processing in visual areas with a retinotopic organization (Visconti di Oleggio Castello et al., 2017a).

These results extend the reports of spatial heterogeneity in visual processing to face identification. Similar biases exist for high-level judgments such as face gender and age (Afraz et al., 2010), as well as shape discrimination (Afraz et al., 2010), crowding, and saccadic precision (Greenwood et al., 2017). Afraz et al. (2010) suggested that neurons in IT exhibit biases that are dependent on retinal

location because their receptive field sizes are not large enough to provide

complete translational invariance, and stimuli in different locations will activate

a limited group of neurons. In this work, we show that these perceptual biases

for face processing not only exist for gender and age judgments (Afraz et al.,

2010), but also for face identification and that these biases are affected by

learning. Retinotopic organization is stronger in earlier visual areas, suggesting

that high-level judgments of gender, age, and identity may be biased by

variability of feature detectors in visual areas such as the occipital face area, or

even earlier.

In this work, we showed that the extent of variation in biases across retinal

locations was inversely correlated with the reported familiarity with individuals,

suggesting that a history of repeated interaction with a person may tune the

responses of neurons to that individual in different retinal locations, generating

more homogeneous responses. Repeated exposure to the faces of familiar

individuals during real-life social interactions results in a detailed representation

of the visual appearance of a personally familiar face. Our results showed that

both ratings of familiarity and ratings of amount of contact were strong

predictors for reduced retinotopic bias. This supports our hypothesis that

facilitated processing might be mediated by the development or tuning of

detectors for diagnostic fragments of personally familiar faces that may exist in

the visual pathway in areas that still have localized analyses and have a

retinotopic organization (Gobbini et al., 2013; Visconti di Oleggio Castello et al.,

2014, 2017b; Visconti di Oleggio Castello and Gobbini, 2015).

Future research can investigate the mechanism that generates these biases and

how learning reduces them. However, our results suggest that prioritized

processing for personally familiar faces may exist at relatively early stages of the

visual processing hierarchy, as shown by the local biases reported here. We

hypothesize that these differences may be one of the mechanisms that underlies

the known behavioral advantages for perception of personally familiar faces

(Burton et al., 1999; Gobbini and Haxby, 2007; Gobbini, 2010; Gobbini et al.,

2013; Visconti di Oleggio Castello et al., 2014, 2017b; Ramon et al., 2015;

Visconti di Oleggio Castello and Gobbini, 2015; Chauhan et al., 2017; Ramon

and Gobbini, 2017).

References

Afraz A, Pashkam MV, Cavanagh P (2010) Spatial heterogeneity in the
perception of face and form attributes. Curr Biol 20:2112–2116.

Aron A, Aron EN, Smollan D (1992) Inclusion of Other in the Self Scale and the
structure of interpersonal closeness. J Pers Soc Psychol 63:596.

Bates D, Mächler M, Bolker B, Walker S (2015) Fitting Linear Mixed-Effects
Models Using lme4. J Stat Softw 67:1–48.

Berscheid E, Snyder M, Omoto AM (1989) The Relationship Closeness
Inventory: Assessing the closeness of interpersonal relationships. J Pers
Soc Psychol 57:792.

Bobes MA, Lage Castellanos A, Quiñones I, García L, Valdes-Sosa M (2013)
Timing and tuning for familiarity of cortical responses to faces. PLoS One
8:e76100.

Burton AM, Wilson S, Cowan M, Bruce V (1999) Face Recognition in Poor-
Quality Video: Evidence From Security Surveillance. Psychol Sci 10:243–
248.

Chauhan V, Visconti di Oleggio Castello M, Soltani A, Gobbini MI (2017) Social
Saliency of the Cue Slows Attention Shifts. Front Psychol 8:738.

Cialdini RB, Brown SL, Lewis BP, Luce C, Neuberg SL (1997) Reinterpreting
the empathy--altruism relationship: When one into one equals oneness. J
Pers Soc Psychol 73:481.

Diamond R, Carey S (1986) Why faces are and are not special: An effect of
expertise. J Exp Psychol Gen 115:107.

Efron B (1987) Better Bootstrap Confidence Intervals. J Am Stat Assoc 82:171–
185.

Faul F, Erdfelder E, Buchner A, Lang A-G (2009) Statistical power analyses
using G*Power 3.1: tests for correlation and regression analyses. Behav
Res Methods 41:1149–1160.

Faul F, Erdfelder E, Lang A-G, Buchner A (2007) G*Power 3: a flexible
statistical power analysis program for the social, behavioral, and
biomedical sciences. Behav Res Methods 39:175–191.

Gächter S, Starmer C, Tufano F (2015) Measuring the Closeness of
Relationships: A Comprehensive Evaluation of the "Inclusion of the Other
in the Self" Scale. PLoS One 10:e0129478.

Gobbini MI (2010) Distributed process for retrieval of person knowledge. Social
neuroscience: Toward understanding the underpinnings of the social
mind:40–53.

Gobbini MI, Gors JD, Halchenko YO, Rogers C, Guntupalli JS, Hughes H,
Cipolli C (2013) Prioritized Detection of Personally Familiar Faces. PLoS
One 8:e66620.

Gobbini MI, Haxby JV (2007) Neural systems for recognition of familiar faces.
Neuropsychologia 45:32–41.

Greenwood JA, Szinte M, Sayim B, Cavanagh P (2017) Variations in crowding,
saccadic precision, and spatial localization reveal the shared topology of
spatial vision. Proc Natl Acad Sci U S A 114:E3573–E3582.

Guntupalli JS, Gobbini MI (2017) Reading Faces: From Features to
Recognition. Trends Cogn Sci 21:915–916.

Idson LC, Mischel W (2001) The personality of familiar and significant people:
the lay perceiver as a social-cognitive theorist. J Pers Soc Psychol
80:585–596.

Kleiner M, Brainard D, Pelli D, Ingling A, Murray R (2007) What's new in
Psychtoolbox-3. Perception.

Natu V, O'Toole AJ (2011) The neural processing of familiar and unfamiliar
faces: A review and synopsis. Br J Psychol 102:726–747.

Ramon M, Gobbini MI (2017) Familiarity matters: A review on prioritized
processing of personally familiar faces. Vis cogn:1–17.

Ramon M, Vizioli L, Liu-Shuang J, Rossion B (2015) Neural microgenesis of
personally familiar face recognition. Proc Natl Acad Sci U S A 112:E4835–
E4844.

Sugiura M (2014) Neuroimaging studies on recognition of personally familiar
people. Front Biosci 19:672–686.

Taylor MJ, Arsalidou M, Bayless SJ, Morris D, Evans JW, Barbeau EJ (2009)
Neural correlates of personally familiar faces: parents, partner and own
faces. Hum Brain Mapp 30:2008–2020.

Visconti di Oleggio Castello M, Gobbini MI (2015) Familiar Face Detection in
180ms. PLoS One 10:e0136548.

Visconti di Oleggio Castello M, Guntupalli JS, Yang H, Gobbini MI (2014)
Facilitated detection of social cues conveyed by familiar faces. Front Hum
Neurosci 8:678.

Visconti di Oleggio Castello M, Halchenko YO, Guntupalli JS, Gors JD, Gobbini
MI (2017a) The neural representation of personally familiar and unfamiliar
faces in the distributed system for face perception. Sci Rep 7:12237.

Visconti di Oleggio Castello M, Wheeler KG, Cipolli C, Gobbini MI (2017b)
Familiarity facilitates feature-based face processing. PLoS One
12:e0178895.

Willenbockel V, Sadr J, Fiset D, Horne GO, Gosselin F, Tanaka JW (2010)
Controlling low-level image properties: The SHINE toolbox. Behav Res
Methods 42:671–684.

Young AW, Burton AM (2017) Are We Face Experts? Trends Cogn Sci.

Legends

Figure 1. Experimental paradigm. The left panel shows the experimental paradigm, while the right panel shows the angular locations used in Experiment 1 (eight locations, top panel) and in Experiment 2 (four locations, bottom panel).

Figure 2. Stable and idiosyncratic biases in identification in Experiment 1. A) Psychometric fit for two subjects from one of the two sessions. Colors indicate angular location; actual data (points) are shown only for the extreme locations to avoid visual clutter. B) The parameter estimates across sessions (at least 33 days apart) were stable (r = 0.71 [0.47, 0.84], see Table 1). C) Example morphs used in the experiment. Note that the morphs depicted here are shown for illustration only, and participants saw morphs of identities that were personally familiar to them.

Figure 3. Stable and idiosyncratic biases in identification in Experiment 2. A) Psychometric fit for one subject from one of the two sessions for each of the morphs. Colors indicate angular location; actual data (points) are shown only for the extreme locations to avoid visual clutter. B) The parameter estimates across sessions (at least 28 days apart) were stable (r = 0.64 [0.5, 0.75], see Table 1). C) Example morphs used in the experiment. Note that the morphs depicted here are shown only for illustration (participants saw morphs of identities who were personally familiar).

Figure 4. The strength of idiosyncratic biases was modulated by personal familiarity. A) Individual subjects' ΔPSE for each morph, averaged across sessions. Note the difference in variance across angular locations for the three different morphs (left to right)). B) The variance across angular locations of ΔPSE estimates was inversely correlated with the reported familiarity of the identities (left panel; r = -0.56 [-0.71, -0.30]), even when adjusting for the Contact score (middle panel; r_p = -0.42 [-0.61, -0.16]). The right panel shows the scatterplot between the Contact score and the ΔPSE variance, adjusted for the Familiarity score, which were significantly correlated as well (r_p = -0.44 [-0.62, -0.17]). See Methods for definition of the Familiarity score and the Contact score.

Table 1. Correlation of parameter estimates across sessions for the two experiments.

Table 2. Comparison of within-subjects correlations of parameter estimates across sessions with between-subjects correlations.

Table 3. Models predicting variance of the ΔPSE estimates across angular locations in Experiment 2.

512 **Tables**

Table 1.
Correlation of parameter estimates across sessions for the two experiments.

Parameter	r	t	df
Experiment 1			
PSE	0.89 [-0.23, 1]	4.86**	6
ΔPSE	0.71 [0.47, 0.84]	5.47***	30
Experiment 2			
PSE	0.98 [0.93, 0.99]	15.22***	10
ΔPSE	0.64 [0.5, 0.75]	9.02***	118

Note: *All confidence intervals are 95% BCa with 10,000 repetitions.*
* p < .05. ** p < .01. *** p < .001

Table 2.
Comparison of within-subjects correlations of parameter estimates across sessions with between-subjects correlations.

Morph	Within-subjects r	Between-subjects r	Difference
Experiment 1			
ab	$0.65^\dagger$ [0.57, 0.8]	-0.22 [-0.41, -0.01]	$0.87^\dagger$ [0.63, 1.1]
Experiment 2			
ab	0.32 [-0.10, 0.62]	-0.02 [-0.15, 0.11]	0.34 [-0.07, 0.69]
ac	$0.62^\dagger$ [0.35, 0.79]	-0.07 [-0.21, 0.08]	$0.68^\dagger$ [0.41, 0.92]
bc	$0.85^\dagger$ [0.61, 0.95]	-0.08 [-0.27, 0.12]	$0.92^\dagger$ [0.68, 1.15]

Note: *All confidence intervals are 95% BCa with 10,000 repetitions.*
† indicates that the CIs do not contain 0.

Table 3. Models predicting variance of the ΔPSE estimates across angular locations in Experiment 2.						
Model	**R^2**	**Score**	**β**	**η_p^2**	**t**	**p**
1	0.32	Familiarity	-0.0574	0.32	-3.59	0.0013
2	0.45	Familiarity	-0.0390	0.17	-2.38	0.0249
		Contact	-0.0452	0.19	-2.512	0.0183