Idiosyncratic, retinotopic bias in face identification

modulated by familiarity

Abbreviated title: Retinotopic bias in face identification

Matteo Visconti di Oleggio Castello[1,*], Morgan Taylor[1], Patrick Cavanagh[1,2],

M. Ida Gobbini[1,3,*]

[1]Department of Psychological & Brain Sciences,

Dartmouth College,

Hanover NH, 03755, USA

[2]Department of Psychology

Glendon College

Toronto ON, M4N 3M6 Canada

[3]Dipartimento di Medicina Specialistica, Diagnostica, e Sperimentale,

University of Bologna,

40100 Bologna, Italy

[*]corresponding authors:

M. Ida Gobbini, mariaida.gobbini@unibo.it

Matteo Visconti di Oleggio Castello, mvdoc.gr@dartmouth.edu

6207 Moore Hall

Dartmouth College

Hanover, NH 03755, USA

Number of pages: 50
Number of figures: 5
Number of tables: 3
Words (Abstract):   169
Words (Introduction):   1,021
Words (Discussion):   2,090

Conflict of Interest
The authors declare no competing financial interests.

Acknowledgments
We would like to thank Carlo Cipolli for helpful discussions. We would like to thank the
Martens Family Fund and Dartmouth College for their support.

Abstract

The perception of gender and age of unfamiliar faces is reported to vary idiosyncratically across retinal locations such that, for example, the same androgynous face may appear to be male at one location but female at another. Here we test spatial heterogeneity for the recognition of the *identity* of personally familiar faces in human participants. We found idiosyncratic biases that were stable within participants and that varied more across locations for low as compared to high familiar faces. These data suggest that like face gender and age, face identity is processed, in part, by independent populations of neurons monitoring restricted spatial regions and that the recognition responses vary for the same face across these different locations. Moreover, repeated and varied social interactions appear to lead to adjustments of these independent face recognition neurons so that the same familiar face is eventually more likely to elicit the same recognition response across widely separated visual field locations. We provide a mechanistic account of this reduced retinotopic bias based on computational simulations.

Significance statement

In this work we tested spatial heterogeneity for the recognition of personally familiar faces. We found retinotopic biases that varied more across locations for low as compared to highly familiar faces. The retinotopic biases were idiosyncratic and stable within participants. Our data suggest that, like face gender and age, face

identity is processed by independent populations of neurons monitoring restricted

spatial regions and that recognition may vary for the same face at these different

locations. Unlike previous findings, our data and computational simulation address

the effects of learning and show how increased familiarity modifies the representation

of face identity in face-responsive cortical areas. This new perspective has broader

implications for understanding how learning optimizes visual processes for socially

salient stimuli.

62 Introduction

We spend most of our days interacting with acquaintances, family and close friends.

Because of these repeated and protracted interactions, the representation of

personally familiar faces is rich and complex, as reflected by stronger and more

widespread neural activation in the distributed face processing network, as compared

to responses to unfamiliar faces (Gobbini and Haxby, 2007; Taylor et al., 2009;

Gobbini, 2010; Natu and O'Toole, 2011; Bobes et al., 2013; Sugiura, 2014; Ramon and

Gobbini, 2017; Visconti di Oleggio Castello et al., 2017a). Differences in

representations are also reflected in faster detection and more robust recognition of

familiar faces (Burton et al., 1999; Gobbini et al., 2013; Ramon et al., 2015; Visconti di

Oleggio Castello and Gobbini, 2015; Guntupalli and Gobbini, 2017; Visconti di Oleggio

Castello et al., 2017b).

The advantage for familiar faces could originate at different stages of the face

processing system. The classic psychological model by Bruce and Young (1986) posits

that recognition of familiar faces occurs when the structural encoding of a perceived

face matches stored representations (Bruce and Young, 1986). In this model the

stored representations of familiar faces consist of "an interlinked set of expression-

independent structural codes for distinct head angles, with some codes reflecting the

global configuration at each angle and others representing particular distinctive

features" (Bruce and Young, 1986, p. 309). Behavioral evidence supports the

hypothesis that local features are processed differentially for personally familiar faces.

For example, in a study of perception of gaze direction and head angle, changes in eye

gaze were detected around 100ms faster in familiar than in unfamiliar faces (Visconti

di Oleggio Castello and Gobbini, 2015). In another study, the advantage for personally

familiar faces was maintained after face inversion, a manipulation that is generally

thought to reduce holistic processing in favor of local processing (Visconti di Oleggio

Castello et al., 2017b).

Taken together, these results suggest that optimized processing of personally familiar

faces could rely on local features. This could be sufficient to initially drive a differential

response to personally familiar faces. In a study measuring saccadic reaction time,

correct and reliable saccades to familiar faces were recorded as fast as 180 ms when

unfamiliar faces were distractors (Visconti di Oleggio Castello and Gobbini, 2015). In

an EEG study using multivariate analyses, significant decoding of familiarity could be

detected at around 140 ms from stimulus onset (Barragan-Jason et al., 2015). At such

short latencies it is unlikely that a viewpoint-invariant representation of an individual

face's identity drives these differential responses. To account for facilitated, rapid

98   detection of familiarity, we have previously hypothesized that personally familiar

99   faces may be recognized quickly based on diagnostic, idiosyncratic features, which

100  become highly learned through extensive personal interactions (Visconti di Oleggio

101  Castello and Gobbini, 2015; Visconti di Oleggio Castello et al., 2017b). Detection of

102  these features may occur early in the face-processing system, allowing an initial, fast

103  differential processing for personally familiar faces.

104  Processes occurring at early stages of the visual system can show idiosyncratic

105  retinotopic biases (Greenwood et al., 2017). Afraz et al. (2010) reported retinotopic

106  biases for perceiving face gender and age that varied depending on stimulus location

107  in the visual field and were specific to each subject. These results suggest that

108  diagnostic facial features for gender and age are encoded in visual areas with limited

109  position invariance. Neuroimaging studies have shown that face-processing areas

110  such as OFA, pFus, and mFus have spatially restricted population receptive fields that

111  could result in retinotopic differences (Kay et al., 2015; Silson et al., 2016; Grill-Spector

112  et al., 2017b). In addition, local facial features activate the OFA (and the putative

113  monkey homologue PL, see Issa and DiCarlo, 2012): responses to face parts are

114  stronger when they are presented in typical locations (de Haas et al., 2016), and

115  population activity in the OFA codes the position and relationship between face parts

116  (Henriksson et al., 2015).

117  Here we hypothesized that detectors of diagnostic visual features that play a role in

118  identification of familiar faces may also show idiosyncratic retinotopic biases and that

these biases may be tuned by repeated interactions with personally familiar faces.

Such biases may affect recognition of the identities presented in different parts of the

visual field and may be modulated by the familiarity of those identities. We tested this

hypothesis by presenting participants with morphed stimuli of personally familiar

individuals that were briefly shown at different retinal locations. In two separate

experiments we found that participants showed idiosyncratic biases for specific

identities in different visual field locations, and these biases were stable on retesting

after weeks. Importantly, the range of the retinal biases was inversely correlated with

the reported familiarity of each target identity, suggesting that prolonged personal

interactions with the target individuals reduced retinal biases.

We hypothesized that these biases could arise because neurons in face-processing

areas have restricted receptive fields centered around the fovea (Afraz et al., 2010;

Kay et al., 2015; Silson et al., 2016), resulting in an incomplete coverage of the visual

field. Thus, identifying a particular face at different peripheral locations would rely on

independent populations tuned to that face that cover a limited portion of the visual

field biased toward the foveal region, leading to variations in identification across

locations. To test this mechanism, we created a computational simulation in which

increased familiarity with a specific identity resulted in changes of neural properties of

the units responsive to that particular face. By either increasing the number of units

responsive to a face or by increasing the receptive field size of those units, this simple

learning mechanism accounted for the reduced biases reported in the two

experiments, providing testable hypotheses for future work.

141 These findings support the hypothesis that asymmetries in the processing of

142 personally familiar faces can arise at stages of the face-processing system where there

143 is reduced position invariance and where local features are being processed, such as in

144 OFA or perhaps even earlier. Our behavioral results show that prolonged, personal

145 interactions can modify the neural representation of faces at this early level of

146 processing, and our computational simulation provides a simple account of how this

147 learning process can be implemented at the neural level.

148 ## Materials and Methods

Figure 1. Experimental paradigm. The left panel shows an example of the experimental paradigm, while the right panel shows the locations used in Experiment 1 (eight locations, top panel) and in Experiment 2 (four locations, bottom panel).

149 *Stimuli*

150 Pictures of the faces of individuals who were personally familiar to the participants

151 (graduate students in the same department) were taken in a photo studio room with

152 the same lighting condition and the same camera. Images of two individuals were

used for Experiment 1, and images of three individuals were used for Experiment 2. All

individuals portrayed in the stimuli signed written informed consent for the use of

their pictures for research and in publications.

The images were converted to grayscale, resized and centered so that the eyes were

aligned in the same position for the three identities, and the background was

manually removed. These operations were performed using ImageMagick and Adobe

Photoshop CS4. The resulting images were matched in luminance (average pixel

intensity) using the SHINE toolbox (function *lumMatch*) (Willenbockel et al., 2010)

after applying an oval mask, so that only pixels belonging to the face were modified.

The luminance-matched images were then used to create morph continua (between

two identities in Experiment 1, see Figure 2; and among three identities in Experiment

2, see Figure 3) using Abrosoft Fantamorph (v. 5.4.7) with seven percentages of

morphing: 0, 17, 33, 50, 67, 83, 100 (see Figures 2, 3).

Experiment 1

Paradigm

The experimental paradigm was similar to that by Afraz et al., (2010). In every trial

participants would see a briefly flashed image in one of eight locations at the

periphery of their visual field (see Figure 1). Each image was shown for 50 ms at a

distance of 7° of visual angle from the fixation point, and subtended approximately 4°

x 4° of visual angle. The images could appear in one of eight locations evenly spaced

by 45 angular degrees around fixation. For Experiment 1, only the morph *ab* was used

(see Figure 1). Participants were required to maintain fixation on a central red dot

subtending approximately 1° of visual angle.

After the image disappeared, participants reported which identity they saw using the

left (identity *a*) and right (identity *b*) arrow keys. There was no time limit for

responding, and participants were asked to be as accurate as possible. After

responding, participants had to press the spacebar key to continue to the next trial.

Participants performed five blocks containing 112 trials each, for a total of 560 trials.

In each block all the images appeared twice for every angular location (8 angular

locations x 7 morph percentages x 2 = 112). This provided ten data points for each

percentage morphing at each location, for a total of 70 trials at each angular location.

Before the experimental session participants were shown the identities used in the

experiment (corresponding to 0% and 100% morphing, see Figure 2), and practiced

the task with 20 trials. These data were discarded from the analyses. Participants

performed two identical experimental sessions at least four weeks apart.

Participants sat at a distance of approximately 50 cm from the screen, with their chin

positioned on a chin-rest. The experiment was run using Psychtoolbox (Kleiner et al.,

2007) (version 3.0.12) in MATLAB (R2014b). The screen operated at a resolution of

1920x1200 and a 60Hz refresh rate.

Subjects

We recruited six subjects for this experiment (three males, including one of the

authors, MVdOC). The sample size for Experiment 1 was not determined by formal

estimates of power, and was limited by the availability of participants familiar with the

stimulus identities. After the first experimental session, two participants (one male,

one female) were at chance level in the task, thus only data from four subjects (two

males, mean age 27.50 ± 2.08 SD) were used for the final analyses.

All subjects had normal or corrected-to-normal vision, and provided written informed

consent to participate in the experiment. The study was approved by the Dartmouth

College Committee for the Protection of Human Subjects.

Experiment 2

Paradigm

Experiment 2 differed from Experiment 1 in the following parameters (see Figures 1,

3): 1. three morph continua (*ab*, *ac*, *bc*) instead of one; 2. images appeared in four

locations (45°, 135°, 225°, 315°) instead of eight; 3. images were shown for 100 ms

instead of 50 ms to make the task easier.

All other parameters were the same as in Experiment 1. Participants had to indicate

which of the three identities they saw by pressing the left (identity *a*), right (identity

b), or down (identity *c*) arrow keys.

Participants performed ten blocks containing 84 trials each, for a total of 840 trials. In

each block all the images appeared once for every angular location (4 angular

locations x 7 morph percentages x 3 morphs = 84). We used 70 data points at every

angular location to fit the model for each pair of identities. Thus, we used the

responses to different unmorphed images for each pair of identities, ensuring

independence of the models.

Before the experimental session participants were shown the identities used in the

experiment (corresponding to 0% and 100% morphing, see Figure 3), and practiced

the task with 20 trials. These data were discarded from the analyses. Participants

performed two experimental sessions at least four weeks apart.

Subjects

Ten participants (five males, mean age 27.30 ± 1.34 SD) participated in Experiment 2,

five of which were recruited for Experiment 1 as well. No authors participated in

Experiment 2. The sample size (n = 10) was determined using G*Power3 (Faul et al.,

2007, 2009) to obtain 80% power at $\square$ = 0.05 based on the correlation of the PSE

estimates across sessions in Experiment 1, using a bivariate normal model (one-

tailed).

All subjects had normal or corrected-to-normal vision, and provided written informed

consent to participate in the experiment. The study was approved by the Dartmouth

College Committee for the Protection of Human Subjects.

Familiarity and contact scales

After the two experimental sessions, participants completed a questionnaire designed

to assess how familiar each participant was with the identities shown in the

experiment. Participants saw each target identity, and were asked to complete

various scales for that identity. The questionnaire comprised the "Inclusion of the

Other in the Self" scale (IOS) (Aron et al., 1992; Gächter et al., 2015), the "Subjective

Closeness Inventory" (SCI) (Berscheid et al., 1989), and the "We-scale" (Cialdini et al.,

1997). The IOS scale showed two circles increasingly overlapping labeled "You" and

"X", and participants were given the following instructions: *Using the figure below*

select which pair of circles best describes your relationship with this person. In the figure

"X" serves as a placeholder for the person shown in the image at the beginning of this

section, and you should think of "X" being that person. By selecting the appropriate

number please indicate to what extent you and this person are connected (Aron et al.,

1992; Gächter et al., 2015). The SCI scale comprised the two following questions:

Relative to all your other relationships (both same and opposite sex) how would you

characterize your relationship with the person shown at the beginning of this section?,

and *Relative to what you know about other people's close relationships, how would you*

characterize your relationship with the person shown at the beginning of this section?

Participants responded with a number between one *(Not close at all)* and seven *(Very*

close) (Berscheid et al., 1989). The We-scale comprised the following question: *Please*

select the appropriate number below to indicate to what extent you would use the term

"WE" to characterize you and the person shown at the beginning of this section.

Participants responded with a number between one *(Not at all)* and seven *(Very much*

so). For each participant and each identity we created a composite "familiarity score"

by averaging the scores in the three scales.

We also introduced a scale aimed at estimating the amount of interaction or contact

between the participant and the target identity. The scale was based on the work by

Idson and Mischel (2001), and participants were asked to respond Yes/No to the

following six questions: *Have you ever seen him during a departmental event?*, *Have you*

ever seen him during a party?, *Have you ever had a group lunch/dinner/drinks with him?*,

Have you ever had a one-on-one lunch/dinner/drinks with him?, *Have you ever texted*

him personally (not a group message)?, and *Have you ever emailed him personally (not a*

group email)? The responses were converted to 0/1 and for each participant and for

each identity we created a "contact score" by summing all the responses.

For each subject separately, to obtain a measure of familiarity and contact related to

each morph, we averaged the familiarity and contact scores of each pair of identities

(e.g., the familiarity score of morph *ab* was the average of the scores for identity *a* and

identity *b*).

Psychometric fit

For both experiments we fitted a group-level psychometric curve using Logit Mixed-

Effect models (Moscatelli et al., 2012) as implemented in *lme4* (Bates et al., 2015). For

each experiment and each session, we fitted a model of the form

$$y^k = \text{logit}\left(\beta_0 x + \sum_{i=1}^{n} (\beta_i + z_i^k) I_i\right)$$

where k indicates the subject, n is the number of angular locations ($n = 8$ for the first

experiment, and $n = 4$ for the second experiment), I_i is an indicator variable for the

angular location, β_i are the model fixed-effects, and z_i are the subject-level random-

effects (random intercept). From this model, we defined for each subject the Point of

Subjective Equality (PSE) as the point x such that logit(x) = 0.5, that is for each angular

location

$$PSE_i^k = -\frac{\beta_i}{\beta_0} - \frac{z_i^k}{\beta_0} = PSE_i^p + \Delta PSE_i^k$$

Thus, the PSE for subject k at angular location i can be decomposed in a population-

level PSE and a subject-specific deviation from the population level, indicated with

PSE^p and ΔPSE^k respectively.

In Experiment 2 we fitted three separate models for each of the morph continua. In

addition, prior to fitting we removed all trials in which subjects mistakenly reported a

third identity. For example, if an image belonging to morph ab was presented, and

subjects responded with c, the trial was removed.

To quantify the bias across locations, we computed a variance score by squaring the

ΔPSE_i, and summing them across locations, that is $bias = \sum_{i=1}^{4} (\Delta PSE_i)^2$. Because

this quantity is proportional to the variance against 0, throughout the manuscript we

refer to it as ΔPSE variance.

Computational modeling

To account for the retinotopic biases we simulated a population of neural units

activated according to the Compressive Spatial Summation model (Kay et al., 2013,

2015) and performed a model-based decoding analysis. This model was originally

developed as an encoding model (Naselaris et al., 2011) to predict BOLD responses

and estimate population receptive fields in visual areas and face-responsive areas

such as OFA, pFus, and mFus (Kay et al., 2015). We refer to activations of neural units

that can be thought as being voxels, small populations of neurons, or individual

neurons.

The CSS model posits that the response of a neural unit is equal to

$$r = g \cdot a^n$$

with $a = \int G(x, y \mid x_0, y_0, \sigma) S(x, y) dx\, dy$, and $G(x, y \mid x_0, y_0, \sigma)$ being a 2D gaussian

centered at x_0, y_0, with covariance $\Sigma = \sigma I$, and $S(x, y)$ being the stimulus converted

into contrast map. The term g represents the gain of the response, while the power

exponent n accounts for subadditive responses (Kay et al., 2013).

We reanalyzed the data from the fMRI experiments in Kay et al. (2015) (*pRF-*

*estimation experimen*t and *face-task experiment*) using the publicly available data

(http://kendrickkay.net/vtcdata)   and code (http://kendrickkay.net/socmodel/) to

obtain parameter estimates for three ROIs (Inferior Occipital Gyrus, IOG—also termed

OFA—mFus, and pFus). The simulation results were similar using parameter estimates

from both experiments, thus we describe the procedure for the face-task experiment

only because of the similarities with the behavioral experiments reported here. We

refer the reader to their paper for more details on the experiments and data

preprocessing. In the face-task experiment three participants saw medium-sized faces

(3.2°) in 25 visual field locations (5x5 grid with 1.5° spacing), and were asked to

perform a 1-back repetition detection task on face identity while fixating at the center

of the screen. The resulting 25 betas were used to fit the models. As in the original

paper, negative beta estimates were rectified (set to 0) and the power exponent was

set to n = 0.2 and not optimized because of the reduced number of stimuli. Model

fitting was performed with cross-validation. Stimuli were randomly split into ten

groups, and each group was left out in turn for testing. The parameter estimates were

aggregated across cross-validation runs taking the median value.

We simulated a population of $N = N_a + N_b$ neural units, where N_a indicates the number

of units selective to identity a, and N_b indicates the number of units selective to

identity b. For simplicity we set $N_b = 1$ and varied N_a, effectively changing the ratio of

units selective to one of the two identities. We performed additional simulations

increasing the total number of units and found consistent results, but here we report

the simulation with $N_b = 1$ for simplicity and consistency with the hypothesis of small

neural populations responsive to specific identities. The stimuli consisted of contrast

circles of diameter 4° centered at 7° from the center, and placed at an angle of 45°,

135°, 225°, and 315°, simulating Experiment 2. We simulated the activation of the units

assuming i.i.d. random noise normally distributed with mean of 0 and standard

deviation of 0.1.

Each experiment consisted of a learning phase in which we simulated the (noisy)

response to the full identities a and b in each of the four locations, with 10 trials for

each identity and location. We used these responses to train a Support Vector

Machine (Cortes and Vapnik, 1995) with linear kernel to differentiate between the two

identities based on the pattern of population responses. Then, we simulated the

actual experiment by generating responses to morphed faces. For simplicity, we

assumed a linear response between the amount of morphing and the population

response. That is, we assumed that if a morph with m percentage morphing towards b

was presented, the population response was a combination of the responses to a and

b, weighted by *(1-m, m)*. The amounts of morphing paralleled those used in the two

experiments (0, 17, 33, 50, 67, 83, 100). We simulated 10 trials for each angular location

and each amount of morphing, and recorded the responses of the trained decoder.

These responses were used to fit a logit model similar to the model used in the main

analyses (without random effects), and to estimate the Point of Subjective Equality

for each angular location. The sum of these squared estimates around 50% was

computed and stored.

We varied systematically the ratio N_a/N_b of units responsive to identity a, ranging from

1 to 9, and repeated 500 experiments for each ratio. For each experiment, parameter

values (pRF location and size) were randomly sampled without replacement from the

population of parameters previously estimated from the face-task experiment of Kay

et al., 2015. We simulated attentional modulations by modifying the gain for the units

responsive to identity a between 1 and 4 in 0.5 steps, and fixing the gain for identity b

to 1. As an alternative, we simulated the effect of increases in receptive field size for

the units responsive to identity *a* by increasing their receptive field size from 0% to

50% in 10% steps, while keeping the gain fixed to 1. We simulated receptive fields in

this way from three face-responsive ROIs (IOG, mFus, and pFus).

Code and data availability

Code for the analyses, raw data for both experiments, single subject results, and

simulations are available at [REDACTED] as well as Extended Data.

Results

Experiment 1

In this experiment, participants performed a two-alternative forced-choice (AFC) task

on identity discrimination. In each trial they saw a face presented for 50 ms, and were

asked to indicate which of the two identities they just saw. Each face could appear in

one of eight stimulus locations. Participants performed the same experiment with the

same task a second time, at least 33 days after the first session (average 35 days ± 4

days standard deviation).

Participants showed stable and idiosyncratic retinal heterogeneity for identification.

The PSE estimates for the two sessions were significantly correlated (see Table 1 and

Figure 2B), showing stable estimates, and the within-subject correlations of ΔPSEs

(see Methods) was significantly higher than the between-subject correlation

(correlation difference: 0.87 [0.64, 1.10], 95% BCa confidence intervals (Efron, 1987);

see Table 2), showing that the biases were idiosyncratic (see Figure 2A for example

fits for two different subjects).

Table 1. Correlation of parameter estimates across sessions for the two experiments.				
Parameter	r	t	df	p
Experiment 1				
PSE	0.89 [-0.23, 1]	4.86**	6	0.002831
ΔPSE	0.71 [0.47, 0.84]	5.47***	30	6.106e-06
Experiment 2				
PSE	0.98 [0.93, 0.99]	15.22***	10	3.042e-08
ΔPSE	0.64 [0.5, 0.75]	9.02***	118	3.997e-15
Note: *All confidence intervals are 95% BCa with 10,000 repetitions.* ** p < .05. ** p < .01. *** p < .001*				

Table 2. Comparison of within-subjects correlations of parameter estimates across sessions with between-subjects correlations.			
Morph	Within-subjects r	Between-subjects r	Difference
Experiment 1			
ab	$0.65^{\dagger}$ [0.57, 0.8]	-0.22 [-0.41, -0.01]	$0.87^{\dagger}$ [0.63, 1.1]
Experiment 2			
ab	0.32 [-0.10, 0.62]	-0.02 [-0.15, 0.11]	0.34 [-0.07, 0.69]
ac	$0.62^{\dagger}$ [0.35, 0.79]	-0.07 [-0.21, 0.08]	$0.68^{\dagger}$ [0.41, 0.92]
bc	$0.85^{\dagger}$ [0.61, 0.95]	-0.08 [-0.27, 0.12]	$0.92^{\dagger}$ [0.68, 1.15]
Note: *All confidence intervals are 95% BCa with 10,000 repetitions.* *† indicates that the CIs do not contain 0.*			

Figure 2. Stable and idiosyncratic biases in identification in Experiment 1. A) Psychometric fit for two subjects from both sessions. Colors indicate location (see colors in bottom left corner); actual data (points) are shown only for the extreme locations to avoid visual clutter. B) The parameter estimates across sessions (at least 33 days apart) were stable (r = 0.71 [0.47, 0.84], see Table 1). Dots represent individual parameter estimates for each location, color coded according to each subject. Correlations were performed on the data shown in this panel. C) Example morphs used in the experiment. Note that the morphs depicted here are shown for illustration only, and participants saw morphs of identities that were personally familiar to them.

Experiment 2

In Experiment 1 participants exhibited stable, retinotopic biases for face identification

that were specific to each participant. Experiment 1, however, used only two target

identities, thus it could not address the question of whether the biases were specific to

target identities or to general variations in face recognition that would be the same

for all target faces. For this reason we conducted a second experiment in which we

increased the number of target identities. In Experiment 2, participants performed a

similar task as in Experiment 1 with the following differences. First, each face was

presented for 100 ms instead of 50 ms in order to make the task easier, since some

participants could not perform the task in Experiment 1; second, each face could

belong to one of three morphs, and participants were required to indicate which of

three identities the face belonged to; third, each face could appear in four retinal

locations instead of eight (see Figure 1) to maintain an appropriate duration of the

experiment. Each participant performed another experimental session at least 28

days after the first session (average 33 days ± 8 days SD).

We found that participants exhibited stable biases across sessions for the three

morphs (see Table 1 and Figure 3). Interestingly, within-subjects correlations were

higher than between-subjects correlations for the two morphs that included the

identity *c* (morphs *ac* and *bc*), but not for morph *ab* (see Table 2), suggesting stronger

differences in spatial heterogeneity caused by identity *c*. To test this further, we

performed a two-way ANOVA on the PSE estimates across sessions with participants

and angular locations as factors. The ANOVA was run for each pair of morphs

containing the same identity (e.g., for identity a the ANOVA was run on data from

morphs ab and ac), and the PSE estimates were transformed to be with respect to the

same identity (e.g., for identity b we considered PSE_{bc} and 100 - PSE_{ab}). We found

significant interactions between participants and angular locations for identity b (F(27,

120) = 1.77, p = 0.01947) and identity c (F(27, 120) = 3.34, p = 3.229e-06), but not

identity a (F(27, 120) = 1.17, p = 0.2807), confirming that participants showed increased

spatial heterogeneity for identities b and c. The increased spatial heterogeneity for

identities b and c, but not a, can be appreciated by inspecting the ΔPSE estimates for

each participant. Figure 4A shows lower bias across retinal locations for morph ab

than the other two morphs, suggesting more similar performance across locations for

morph ab. To investigate factors explaining the difference in performance across

spatial locations between the three identities, we compared the ΔPSE estimates with

the reported familiarity of the identities.

The variance of the average ΔPSE estimates across sessions for each subject was

significantly   correlated   with   the   reported   familiarity   of   the   identities

(r = -0.56 [-0.71, -0.30], t(28) = -3.59, p = 0.001248), showing that the strength of the

retinal bias for identities was inversely modulated by personal familiarity (see Figure

4B). We estimated personal familiarity by averaging participants' ratings of the

identities on three scales (Inclusion of the Other in the Self, the We-Scale, and the

Subjective Closeness Inventory, see Methods for details). The three scales were highly

correlated (min correlation r = 0.89, max correlation r = 0.96).

Because the amount of personal familiarity was correlated with the amount of contact

with   a   target   identity   (r   =   0.45   [0.17,   0.68],   t(28)   =   2.65,

p = 0.01304), we tested whether a linear model predicting ΔPSE with both contact and

familiarity as predictors could fit the data better. Both models were significant, but

the model with two predictors provided a significantly better fit (X^2(1) = 6.30, p =

0.0121, log-likelihood ratio test), and explained more variance as indicated by higher

R^2: R^2 = 0.45, adjusted R^2 = 0.40 for the model with both Familiarity and Contact

scores (F(2, 27) = 10.82, p = 0.0003539), and R^2 = 0.32, adjusted R^2 = 0.29 for the model

with the Familiarity score only (F(1, 28) = 12.88, p = 0.001248). Importantly, both

predictors were significant (see Table 3), indicating that familiarity modulated the

variance of the ΔPSE estimates in addition to modulation based on the amount of

contact with a person. After adjusting for the contact score, the variance of the ΔPSE

estimates and the familiarity score were still significantly correlated (r_p = -0.42 [-0.61, -

0.16], t(28) = -2.42, p = 0.02235).

Table 3. Models predicting variance of the ΔPSE estimates across locations in Experiment 2.						
Model	R^2	Score	β	η_p^2	t	p
1	0.32	Familiarity	-0.0574	0.32	-3.59	0.0013
2	0.45	Familiarity	-0.0390	0.17	-2.38	0.0249
		Contact	-0.0452	0.19	-2.512	0.0183

Figure 3. Stable and idiosyncratic biases in identification in Experiment 2. A) Psychometric fit for one subject from both sessions for each of the morphs. Colors indicate location (see colors in bottom left corner); actual data (points) are shown only for the extreme locations to avoid visual clutter. B) The parameter estimates across sessions (at least 28 days apart) were stable (r = 0.64 [0.5, 0.75], see Table 1). Dots represent individual parameter estimates for each location, color coded according to each participant. Correlations were performed on the data shown in this panel. C) Example morphs used in the experiment. Note that the morphs depicted here are shown only for illustration (participants saw morphs of identities who were personally familiar).

Figure 4. The strength of idiosyncratic biases was modulated by personal familiarity. A) Individual subjects' ΔPSE for each morph, averaged across sessions. Note the difference in variance across locations for the three different morphs (left to right)). B) The variance across locations of ΔPSE estimates was inversely correlated with the reported familiarity of the identities (left panel; r = -0.56 [-0.71, -0.30]), even when adjusting for the Contact score (middle panel; r_p = -0.42 [-0.61, -0.16]). The right panel shows the scatterplot between the Contact score and the ΔPSE variance, adjusted for the Familiarity score, which were significantly correlated as well (r_p = -0.44 [-0.62, -0.17]). See Methods for definition of the Familiarity score and the Contact score. Dots represent individual participant's data, color coded according to morph type. Correlations were performed on the data shown in these panels.

Model simulation

In two behavioral experiments we found a stable, idiosyncratic bias towards specific

identities that varied according to the location in which the morphed face stimuli

appeared. The bias was reduced with more familiar identities, showing effects of

learning. To account for this effect, we hypothesized that small populations of

neurons selective to specific identities sample a limited portion of the visual field

(Afraz et al., 2010). We also hypothesized that with extended interactions with a

person, more neural units become selective to the facial appearance of the identity. In

turn, this increases the spatial extent of the field covered by the population and thus

reduces the retinotopic bias.

To quantitatively test this hypothesis, we simulated a population of neural units in

IOG (OFA), pFus, and mFus activated according to the Compressive Spatial

Summation model (Kay et al., 2013, 2015). The parameters of this model were

estimated from the publicly available data from Kay et al. (2015). We simulated

learning effects by progressively increasing the number of units selective to one of the

two identities, and measuring the response of a linear decoder trained to distinguish

between the two identities. As can be seen in Figure 5A, increasing the number of

units reduced the overall bias (expressed as variance against 0.5 of the PSE estimates,

see *Methods* for details) by increasing the spatial coverage (see Figure 5B).

Interestingly, the larger bias was found within the simulated IOG. Inspecting the pRF

coverage of the three ROIs revealed that the stimuli shown at 7° of eccentricity were

at the border of the receptive field coverage in IOG (Figure 5B) because of the smaller

RF sizes (median value across voxels of 2.98° [2.85°, 3.10°], 95% bootstrapped

confidence intervals), compared to those in pFus and mFus (3.87° [3.65°, 4.05°] and

3.55° [3.35°, 3.75°] respectively). To quantify this difference, we computed the average

proportion of units covering the stimulus locations in each ROI. As predicted from the

smaller RF sizes, fewer units in IOG covered the area where the stimuli were

presented (31.61%) compared to pFus (47.04%) and mFus (45.83%). These results

suggest that a larger retinotopic bias would be expected to originate from units in

IOG..

As alternative explanations, we tested whether differences in gain or increases in RF

size could reduce the bias to a similar extent as increasing the number of units. Figure

5C shows that modulating the gain failed to reduce the retinotopic bias in all

simulated ROIs, while Figure 5D shows that increasing RF size of the units responsive

to the more familiar identity can also reduce the retinotopic bias.

Figure 5. Simulating retinotopic biases and learning effects in face-responsive ROIs. We hypothesized that neural units (voxels, small populations of neurons, or individual neurons) cover a limited portion of the visual field, and that learning increases the number of neural units selective to a particular identity. A) Increasing the number of units selective to one identity reduces the retinotopic bias. Results of simulating 500 experiments by varying the ratio of neural units selective to one of two identities and fixing the gain to 1 for both identities. Dots represent median values with 95% bootstrapped CIs (1,000 replicates; note that for some points the CIs are too small to be seen). In all simulated ROIs the variance of the PSE around 50% decreases with increasing number of units selective to a, but remains larger in IOG because of its receptive field size. B) Population coverage of the units in each ROI estimated from the face-task data in Kay et al. (2015) and used in the simulations. Circles at the periphery show the simulated stimulus locations. Each image is normalized to the number of units in each ROI. Receptive fields are computed with radius 2σ, following the convention in Kay et al., (2015). Percentages below each image show the average proportion of units whose receptive field cover the stimulus locations. Compared to pFus and mFus, fewer units cover the stimuli in IOG resulting in a larger bias across locations. C) Increasing the gain of the response to one identity fails to reduce the retinotopic bias. D) Increasing the receptive field size of the units responsive to one

identity reduces the retinotopic bias. In both C) and D) each dot represents median values of PSE variance for 500 simulated experiments. CIs are not shown to reduce visual clutter.

Discussion

Afraz et al. (2010) reported spatial heterogeneity for recognition of facial attributes

such as gender and age, suggesting that relatively independent neural populations

tuned to facial features might sample different regions of the visual field. Prolonged

social interactions with personally familiar faces lead to facilitated, prioritized

processing of those faces. Here we wanted to investigate if this learning of face

identity through repeated social interactions also affects these local visual processes,

by measuring spatial heterogeneity of identity recognition. We measured whether

face identification performance for personally familiar faces differed according to the

location in the visual field where face images were presented. We found that

participants exhibited idiosyncratic, retinotopic biases for different face identities that

were stable across experimental sessions. Importantly, the variability of the

retinotopic bias was reduced with increased familiarity with the target identities.

These data support the hypothesis that familiarity modulates processes in visual areas

with limited position invariance (Visconti di Oleggio Castello et al., 2017a).

These results extend the reports of spatial heterogeneity in visual processing to face

identification. Similar biases exist for high-level judgments such as face gender and

age (Afraz et al., 2010), as well as shape discrimination (Afraz et al., 2010), crowding,

and saccadic precision (Greenwood et al., 2017). Afraz et al. (2010) suggested that

neurons in IT exhibit biases that are dependent on retinal location because their

receptive field sizes are not large enough to provide complete translational invariance,

and stimuli in different locations will activate a limited group of neurons. In this work,

we show that these perceptual biases for face processing not only exist for gender and

age judgments (Afraz et al., 2010), but also for face identification and that these

biases are affected by learning.

Location-dependent coding in face-responsive areas

Neurons in temporal cortex involved in object recognition are widely thought to be

invariant to object translation, that is their response to an object will not be

modulated by the location of the object in the visual field (Riesenhuber and Poggio,

1999; Hung et al., 2005). However, evidence suggests that location information is

preserved in activity of neurons throughout temporal cortex (Kravitz et al., 2008;

Hong et al., 2016). Location information can be encoded as a retinotopic map, such as

in early visual cortex, where neighboring neurons are selective to locations that are

neighboring in the visual field. In the absence of a clear cortical retinotopic map,

location information can still be preserved at the level of population responses

(Schwarzlose et al., 2008; Rajimehr et al., 2014; Henriksson et al., 2015; Kay et al.,

2015).

Areas of occipital and temporal cortices show responses to objects that are

modulated by position (Kravitz et al., 2008, 2010; Sayres and Grill-Spector, 2008). In

particular, also face-responsive areas of the ventral core system (Haxby et al., 2000;

Visconti di Oleggio Castello et al., 2017a) such as OFA, pFus, and mFus show

responses that are modulated by the position in which a face appears. Responses to a

face are stronger in these areas when faces are presented foveally rather than

peripherally (Levy et al., 2001; Hasson et al., 2002; Malach et al., 2002). In addition,

early face processing areas such as PL in monkeys or OFA in humans code specific

features of faces in typical locations. Neurons in PL are tuned to eyes in the

contralateral hemifield, with receptive fields covering the typical location of the eyes

at fixation (Issa and DiCarlo, 2012). Similarly, OFA responses to face parts are stronger

when they are presented in typical locations (de Haas et al., 2016), and OFA activity

codes the position and relationship between face parts (Henriksson et al., 2015).

The modulation of responses by object location in these areas seems to be driven by

differences in receptive field sizes. In humans, population receptive fields (pRF) can be

estimated with fMRI by modeling voxel-wise BOLD responses (Dumoulin and

Wandell, 2008; Wandell and Winawer, 2011, 2015; Kay et al., 2013). These studies

have shown that pRF centers are mostly located in the contralateral hemifield (Kay et

al., 2015; Grill-Spector et al., 2017b), corresponding to the reported preference of

these areas for faces presented contralaterally (Hemond et al., 2007). In addition, pRF

sizes increase the higher in the face processing hierarchy, favoring perifoveal regions

(Kay et al., 2015; Silson et al., 2016). The location-dependent coding of faces in these

face-processing areas might be based on population activity, since these areas do not

overlap with retinotopic maps in humans (for example, OFA does not seem to overlap

with estimated retinotopic maps, Silson et al., 2016, but see Janssens et al., 2014;

Rajimehr et al., 2014; Arcaro and Livingstone, 2017; Arcaro et al., 2017 for work in

monkeys showing partial overlap between retinotopic maps and face patches).

Cortical origin of idiosyncratic biases and effects of familiarity

Populations of neurons in visual areas and in temporal cortex cover limited portions of

the visual field, with progressively larger receptive fields centered around perifoveal

regions (Grill-Spector et al., 2017b). This property suggests that biases in high-level

judgments of gender, age, and identity may be due to the variability of feature

detectors that cover limited portions of the visual field (Afraz et al., 2010). While the

results from our behavioral study cannot point to a precise location of the cortical

origin of these biases, our computational simulation suggests that a larger bias could

arise from responses in the OFA, given the estimates of receptive field size and

eccentricity in this area (Kay et al., 2015; Grill-Spector et al., 2017b). We cannot

exclude that this bias might originate in earlier areas of the visual processing stream.

In this work, we showed that the extent of variation in biases across retinal locations

was inversely correlated with the reported familiarity with individuals, suggesting that

a history of repeated interaction with a person may tune the responses of neurons to

that individual in different retinal locations, generating more homogeneous

responses. Repeated exposure to the faces of familiar individuals during real-life social

interactions results in a detailed representation of the visual appearance of a

personally familiar face. Our computational simulation suggests a simple process for

augmenting and strengthening the representation of a face. Learning through social

interactions might cause a greater number of neural units to become responsive to a

specific identity, thus covering a larger area of the visual field and reducing the

retinotopic biases. Our results showed that both ratings of familiarity and ratings of

amount of contact were strong predictors for reduced retinotopic bias; however,

familiarity still predicted the reduced bias when accounting for amount of contact.

While additional experiments are needed to test whether pure perceptual learning is

sufficient to reduce the retinotopic biases to the same extent as personal familiarity,

these results suggest that repeated personal interactions can strengthen neural

representations to a larger extent than mere increased frequency of exposure to a

face. This idea is consistent with neuroimaging studies showing a stronger and more

widespread activation for personally familiar faces compared to unfamiliar or

experimentally learned faces (Gobbini and Haxby, 2006; Cloutier et al., 2011; Natu and

O'Toole, 2011; Leibenluft et al., 2004; Gobbini and Haxby, 2007; Bobes et al., 2013;

Ramon and Gobbini, 2017; Visconti di Oleggio Castello et al., 2017a) .

Effects of attention

Could differences in attention explain the modulation of retinotopic biases reported

here? Faces, and personally familiar faces in particular, are important social stimuli

whose correct detection and processing affects social behavior (Brothers, 2002;

Gobbini and Haxby, 2007). Behavioral experiments from our lab have shown that

personally familiar faces break through faster in a continuous flash suppression

paradigm (Gobbini et al., 2013), and hold attention more strongly than unfamiliar

faces do in a Posner cueing paradigm (Chauhan et al., 2017). These results show that

familiar faces differ not only at the level of representations, but also in allocation of

attention. At the neural level, changes in attention might be implemented as

increased gain for salient stimuli or increased receptive field size (Kay et al., 2015). In

an fMRI experiment Kay et al. (2015) reported that population receptive field (pRF)

estimates were modulated by the type of task. Gain, eccentricity, and size of the pRFs

increased during a 1-back repetition detection task on facial identity as compared to a

1-back task on digits presented foveally.

To address differences in gain in our computational simulation, we modified the

relative gain of units responsive to one of the two identities and found that it did not

influence the PSE bias across locations. This bias was more strongly modulated by the

number of units responsive to one of the identities. On the other hand, simulating

increases in receptive field size reduced the retinotopic bias almost as much as

increasing the number of units. These simulations suggest two alternative, and

possibly interacting, mechanisms that can reduce retinotopic biases in identification:

recruitment of additional units selective to an identity or changes in RF properties.

Additional experiments are needed to further characterize the differences in attention

and representations that contribute to the facilitated processing of personally familiar

faces.

Implications for computational models of vision

Many computational models of biological vision posit translational invariance:

neurons in IT are assumed to respond to the same extent, regardless of the object

position (Riesenhuber and Poggio, 1999; Serre et al., 2007; Kravitz et al., 2008). Even

the models that currently provide better fits to neural activity in IT such as

hierarchical, convolutional neural networks (Yamins et al., 2014; Kriegeskorte, 2015;

Yamins and DiCarlo, 2016) use weight sharing in convolutional layers to achieve

position invariance (LeCun et al., 2015; Schmidhuber, 2015; Goodfellow et al., 2016).

While this reduces complexity by limiting the number of parameters to be fitted,

neuroimaging and behavioral experiments have shown that translational invariance in

IT is preserved only for small displacements (DiCarlo and Maunsell, 2003; Kay et al.,

2015; Silson et al., 2016; for a review see Kravitz et al., 2008), with varying receptive

field sizes and eccentricities (Grill-Spector et al., 2017a). Our results highlight the

limited position invariance for high-level judgments such as identity, and add to the

known spatial heterogeneity for gender and age judgments (Afraz et al., 2010). Our

results also show that a higher degree of invariance can be achieved through learning,

as shown by the reduced bias for highly familiar faces. This finding highlights that to

increase biological plausibility of models of vision, differences in eccentricity and

receptive field size should be taken into account (Poggio et al., 2014), as well as more

dynamic effects such as changes induced by learning and attention (Grill-Spector et

al., 2017a).

Conclusions

Taken together, the results reported here support our hypothesis that facilitated

processing for personally familiar faces might be mediated by the development or

tuning of detectors for personally familiar faces in the visual pathway in areas that still

have localized analyses (Gobbini et al., 2013; Visconti di Oleggio Castello et al., 2014,

2017b; Visconti di Oleggio Castello and Ida Gobbini, 2015). The OFA might be a

candidate for the cortical origin of these biases as well as for the development of

detectors for diagnostic fragments. Patterns of responses in OFA (and neurons in the

monkey putative homologue PL, Issa and DiCarlo, 2012) are tuned to typical locations

of face fragments (Henriksson et al., 2015; de Haas et al., 2016). Population receptive

fields of voxels in this region cover an area of the visual field that is large enough to

integrate features of intermediate complexity at an average conversational distance

(Kay et al., 2015; Grill-Spector et al., 2017b), such as combinations of eyes and

eyebrows, which have been shown to be theoretically optimal and highly informative

for object classification (Ullman et al., 2001, 2002; Ullman, 2007).

Future research is needed to further disambiguate differences in representations or

attention that generate these biases and how learning reduces them. Nonetheless,

our results suggest that prioritized processing for personally familiar faces may exist

at relatively early stages of the face processing hierarchy, as shown by the local biases

reported here. Learning associated with repeated personal interactions modifies the

representation of these faces, suggesting that personal familiarity affects face-

processing areas well after developmental critical periods (Arcaro et al., 2017;

Livingstone et al., 2017). We hypothesize that these differences may be one of the

mechanisms that underlies the known behavioral advantages for perception of

personally familiar faces (Burton et al., 1999; Gobbini and Haxby, 2007; Gobbini, 2010;

Gobbini et al., 2013; Visconti di Oleggio Castello et al., 2014, 2017b; Ramon et al.,

2015; Visconti di Oleggio Castello and Gobbini, 2015; Chauhan et al., 2017; Ramon and

Gobbini, 2017).

References

Afraz A, Pashkam MV, Cavanagh P (2010) Spatial heterogeneity in the perception of face and form attributes. Curr Biol 20:2112–2116.

Arcaro MJ, Livingstone MS (2017) A hierarchical, retinotopic proto-organization of the primate visual system at birth. Elife 6

Arcaro MJ, Schade PF, Vincent JL, Ponce CR, Livingstone MS (2017) Seeing faces is necessary for face-domain formation. Nat Neurosci

Aron A, Aron EN, Smollan D (1992) Inclusion of Other in the Self Scale and the structure of interpersonal closeness. J Pers Soc Psychol 63:596.

Barragan-Jason G, Cauchoix M, Barbeau EJ (2015) The neural speed of familiar face recognition. Neuropsychologia 75:390–401.

Bates D, Mächler M, Bolker B, Walker S (2015) Fitting Linear Mixed-Effects Models Using lme4. J Stat Softw 67:1–48.

Berscheid E, Snyder M, Omoto AM (1989) The Relationship Closeness Inventory: Assessing the closeness of interpersonal relationships. J Pers Soc Psychol 57:792.

Bobes MA, Lage Castellanos A, Quiñones I, García L, Valdes-Sosa M (2013) Timing and tuning for familiarity of cortical responses to faces. PLoS One 8:e76100.

Brothers L (2002) The social brain: a project for integrating primate behavior and neurophysiology in a new domain. Foundations in social neuroscience:367–385.

Bruce V, Young A (1986) Understanding face recognition. Br J Psychol 77 (Pt 3):305–327.

Burton AM, Wilson S, Cowan M, Bruce V (1999) Face Recognition in Poor-Quality Video: Evidence From Security Surveillance. Psychol Sci 10:243–248.

Chauhan V, Visconti di Oleggio Castello M, Soltani A, Gobbini MI (2017) Social Saliency of the Cue Slows Attention Shifts. Front Psychol 8:738.

Cialdini RB, Brown SL, Lewis BP, Luce C, Neuberg SL (1997) Reinterpreting the empathy--altruism relationship: When one into one equals oneness. J Pers Soc Psychol 73:481.

Cloutier J, Kelley WM, Heatherton TF (2011) The influence of perceptual and
knowledge-based familiarity on the neural substrates of face perception. Soc
Neurosci 6:63–75.

Cortes C, Vapnik V (1995) Support-vector networks. Mach Learn 20:273–297.

de Haas B, Schwarzkopf DS, Alvarez I, Lawson RP, Henriksson L, Kriegeskorte N, Rees
G (2016) Perception and Processing of Faces in the Human Brain Is Tuned to
Typical Feature Locations. J Neurosci 36:9289–9302.

Diamond R, Carey S (1986) Why faces are and are not special: An effect of expertise. J
Exp Psychol Gen 115:107.

DiCarlo JJ, Maunsell JHR (2003) Anterior inferotemporal neurons of monkeys engaged
in object recognition can be highly sensitive to object retinal position. J
Neurophysiol 89:3264–3278.

Dumoulin SO, Wandell BA (2008) Population receptive field estimates in human visual
cortex. Neuroimage 39:647–660.

Efron B (1987) Better Bootstrap Confidence Intervals. J Am Stat Assoc 82:171–185.

Faul F, Erdfelder E, Buchner A, Lang A-G (2009) Statistical power analyses using
G*Power 3.1: tests for correlation and regression analyses. Behav Res Methods
41:1149–1160.

Faul F, Erdfelder E, Lang A-G, Buchner A (2007) G*Power 3: a flexible statistical power
analysis program for the social, behavioral, and biomedical sciences. Behav Res
Methods 39:175–191.

Gächter S, Starmer C, Tufano F (2015) Measuring the Closeness of Relationships: A
Comprehensive Evaluation of the "Inclusion of the Other in the Self" Scale.
PLoS One 10:e0129478.

Gobbini MI (2010) Distributed process for retrieval of person knowledge. Social
neuroscience: Toward understanding the underpinnings of the social mind:40–
53.

Gobbini MI, Gors JD, Halchenko YO, Rogers C, Guntupalli JS, Hughes H, Cipolli C
(2013) Prioritized Detection of Personally Familiar Faces. PLoS One 8:e66620.

Gobbini MI, Haxby JV (2006) Neural response to the visual familiarity of faces. Brain
Res Bull 71:76–82.

Gobbini MI, Haxby JV (2007) Neural systems for recognition of familiar faces.
Neuropsychologia 45:32–41.

Goodfellow I, Bengio Y, Courville A, Bengio Y (2016) Deep learning. MIT press
Cambridge.

Greenwood JA, Szinte M, Sayim B, Cavanagh P (2017) Variations in crowding, saccadic
precision, and spatial localization reveal the shared topology of spatial vision.
Proc Natl Acad Sci U S A 114:E3573–E3582.

Grill-Spector K, Kay K, Weiner KS (2017a) The Functional Neuroanatomy of Face
Processing: Insights from Neuroimaging and Implications for Deep Learning. In:
Deep Learning for Biometrics (Bhanu B, Kumar A, eds), pp 3–31 Advances in
Computer Vision and Pattern Recognition. Cham: Springer International
Publishing.

Grill-Spector K, Weiner KS, Kay K, Gomez J (2017b) The Functional Neuroanatomy of
Human Face Perception. Annu Rev Vis Sci 3:167–196.

Guntupalli JS, Gobbini MI (2017) Reading Faces: From Features to Recognition. Trends
Cogn Sci 21:915–916.

Hasson U, Levy I, Behrmann M, Hendler T, Malach R (2002) Eccentricity bias as an
organizing principle for human high-order object areas. Neuron 34:479–490.

Haxby JV, Hoffman EA, Gobbini MI (2000) The distributed human neural system for
face perception. Trends Cogn Sci 4:223–233.

Hemond CC, Kanwisher NG, Op de Beeck HP (2007) A Preference for Contralateral
Stimuli in Human Object- and Face-Selective Cortex. PLoS One 2:e574.

Henriksson L, Mur M, Kriegeskorte N (2015) Faciotopy-A face-feature map with face-
like topology in the human occipital face area. Cortex 72:156–167.

Hong H, Yamins DLK, Majaj NJ, DiCarlo JJ (2016) Explicit information for category-
orthogonal object properties increases along the ventral stream. Nat Neurosci
19:613–622.

Hung CP, Kreiman G, Poggio T, DiCarlo JJ (2005) Fast readout of object identity from
macaque inferior temporal cortex. Science 310:863–866.

Idson LC, Mischel W (2001) The personality of familiar and significant people: the lay
perceiver as a social-cognitive theorist. J Pers Soc Psychol 80:585–596.

Issa EB, DiCarlo JJ (2012) Precedence of the Eye Region in Neural Processing of Faces.
Journal of Neuroscience 32:16666–16682.

Janssens T, Zhu Q, Popivanov ID, Vanduffel W (2014) Probabilistic and single-subject
retinotopic maps reveal the topographic organization of face patches in the
macaque cortex. J Neurosci 34:10156–10167.

Kay KN, Weiner KS, Grill-Spector K (2015) Attention reduces spatial uncertainty in
human ventral temporal cortex. Curr Biol 25:595–600.

Kay KN, Winawer J, Mezer A, Wandell BA (2013) Compressive spatial summation in
human visual cortex. J Neurophysiol 110:481–494.

Kleiner M, Brainard D, Pelli D, Ingling A, Murray R (2007) What's new in Psychtoolbox-
3. Perception

Kravitz DJ, Kriegeskorte N, Baker CI (2010) High-level visual object representations
are constrained by position. Cereb Cortex 20:2916–2925.

Kravitz DJ, Vinson LD, Baker CI (2008) How position dependent is visual object
recognition? Trends Cogn Sci 12:114–122.

Kriegeskorte N (2015) Deep Neural Networks: A New Framework for Modeling
Biological Vision and Brain Information Processing. Annual Review of Vision
Science 1:417–446.

LeCun Y, Bengio Y, Hinton G (2015) Deep learning. Nature 521:436–444.

Leibenluft E, Gobbini MI, Harrison T, Haxby JV (2004) Mothers' neural activation in
response to pictures of their children and other children. Biol Psychiatry
56:225–232.

Levy I, Hasson U, Avidan G, Hendler T, Malach R (2001) Center–periphery
organization of human object areas. Nat Neurosci 4:533–539.

Livingstone MS, Vincent JL, Arcaro MJ, Srihasam K, Schade PF, Savage T (2017)
Development of the macaque face-patch system. Nat Commun 8:14897.

Malach R, Levy I, Hasson U (2002) The topography of high-order human object areas.
Trends Cogn Sci 6:176–184.

Moscatelli A, Mezzetti M, Lacquaniti F (2012) Modeling psychophysical data at the
population-level: the generalized linear mixed model. J Vis 12

Naselaris T, Kay KN, Nishimoto S, Gallant JL (2011) Encoding and decoding in fMRI.
Neuroimage 56:400–410.

Natu V, O'Toole AJ (2011) The neural processing of familiar and unfamiliar faces: A
review and synopsis. Br J Psychol 102:726–747.

Poggio T, Mutch J, Isik L (2014) Computational role of eccentricity dependent cortical
magnification. arXiv [csLG]

Rajimehr R, Bilenko NY, Vanduffel W, Tootell RBH (2014) Retinotopy versus Face
Selectivity in Macaque Visual Cortex. J Cogn Neurosci 22:1–10.

Ramon M, Gobbini MI (2017) Familiarity matters: A review on prioritized processing of
personally familiar faces. Vis cogn:1–17.

Ramon M, Vizioli L, Liu-Shuang J, Rossion B (2015) Neural microgenesis of personally
familiar face recognition. Proc Natl Acad Sci U S A 112:E4835–E4844.

Riesenhuber M, Poggio T (1999) Hierarchical models of object recognition in cortex.
Nat Neurosci 2:1019–1025.

Sayres R, Grill-Spector K (2008) Relating retinotopic and object-selective responses in
human lateral occipital cortex. J Neurophysiol 100:249–267.

Schmidhuber J (2015) Deep learning in neural networks: An overview. Neural Netw
61:85–117.

Schwarzlose RF, Swisher JD, Dang S, Kanwisher N (2008) The distribution of category
and location information across object-selective regions in human visual cortex.
Proc Natl Acad Sci U S A 105:4447–4452.

Serre T, Oliva A, Poggio T (2007) A Feedforward Architecture Accounts for Rapid
Categorization. Proc Natl Acad Sci U S A 104:6424–6429.

Silson EH, Groen IIA, Kravitz DJ, Baker CI (2016) Evaluating the correspondence
between face-, scene-, and object-selectivity and retinotopic organization
within lateral occipitotemporal cortex. J Vis 16:14.

Sugiura M (2014) Neuroimaging studies on recognition of personally familiar people.
Front Biosci 19:672–686.

Taylor MJ, Arsalidou M, Bayless SJ, Morris D, Evans JW, Barbeau EJ (2009) Neural
correlates of personally familiar faces: parents, partner and own faces. Hum
Brain Mapp 30:2008–2020.

Ullman S (2007) Object recognition and segmentation by a fragment-based hierarchy.
Trends Cogn Sci 11:58–64.

Ullman S, Sali E, Vidal-Naquet M (2001) A Fragment-Based Approach to Object
Representation and Classification. In: Visual Form 2001, pp 85–100. Springer,
Berlin, Heidelberg.

Ullman S, Vidal-Naquet M, Sali E (2002) Visual features of intermediate complexity
and their use in classification. Nat Neurosci

Visconti di Oleggio Castello M, Guntupalli JS, Yang H, Gobbini MI (2014) Facilitated
detection of social cues conveyed by familiar faces. Front Hum Neurosci 8:678.

Visconti di Oleggio Castello M, Halchenko YO, Guntupalli JS, Gors JD, Gobbini MI
(2017a) The neural representation of personally familiar and unfamiliar faces in
the distributed system for face perception. Sci Rep 7:12237.

Visconti di Oleggio Castello M, Ida Gobbini M (2015) Familiar Face Detection in 180ms.
PLoS One 10:e0136548.

Visconti di Oleggio Castello M, Wheeler KG, Cipolli C, Gobbini MI (2017b) Familiarity
facilitates feature-based face processing. PLoS One 12:e0178895.

Wandell BA, Winawer J (2011) Imaging retinotopic maps in the human brain. Vision
Res 51:718–737.

Wandell BA, Winawer J (2015) Computational neuroimaging and population receptive
fields. Trends Cogn Sci 19:349–357.

Willenbockel V, Sadr J, Fiset D, Horne GO, Gosselin F, Tanaka JW (2010) Controlling
low-level image properties: The SHINE toolbox. Behav Res Methods 42:671–
684.

Yamins DLK, DiCarlo JJ (2016) Using goal-driven deep learning models to understand
sensory cortex. Nat Neurosci 19:356–365.

Yamins DLK, Hong H, Cadieu CF, Solomon EA, Seibert D, DiCarlo JJ (2014)
Performance-optimized hierarchical models predict neural responses in higher
visual cortex. Proc Natl Acad Sci U S A 111:8619–8624.

Young AW, Burton AM (2017) Are We Face Experts? Trends Cogn Sci

Legends

Figure 1. Experimental paradigm. The left panel shows the experimental paradigm, while the right panel shows the locations used in Experiment 1 (eight locations, top panel) and in Experiment 2 (four locations, bottom panel).

Figure 2. Stable and idiosyncratic biases in identification in Experiment 1. A) Psychometric fit for two subjects from both sessions. Colors indicate location (see colors in bottom left corner); actual data (points) are shown only for the extreme locations to avoid visual clutter. B) The parameter estimates across sessions (at least 33 days apart) were stable (r = 0.71 [0.47, 0.84], see Table 1). Dots represent individual parameter estimates for each location, color coded according to each subject. Correlations were performed on the data shown in this panel. C) Example morphs used in the experiment. Note that the morphs depicted here are shown for illustration only, and participants saw morphs of identities that were personally familiar to them.

Figure 3. Stable and idiosyncratic biases in identification in Experiment 2. A) Psychometric fit for one subject from both sessions for each of the morphs. Colors indicate location (see colors in bottom left corner); actual data (points) are shown only for the extreme locations to avoid visual clutter. B) The parameter estimates across sessions (at least 28 days apart) were stable (r = 0.64 [0.5, 0.75], see Table 1). Dots represent individual parameter estimates for each location, color coded according to each participant. Correlations were performed on the data shown in this panel. C) Example morphs used in the experiment. Note that the morphs depicted here are shown only for illustration (participants saw morphs of identities who were personally familiar).

Figure 4. The strength of idiosyncratic biases was modulated by personal familiarity. A) Individual subjects' ΔPSE for each morph, averaged across sessions. Note the difference in variance across locations for the three different morphs (left to right)). B) The variance across locations of ΔPSE estimates was inversely correlated with the reported familiarity of the identities (left panel; r = -0.56 [-0.71, -0.30]), even when adjusting for the Contact score (middle panel; r_p = -0.42 [-0.61, -0.16]). The right panel shows the scatterplot between the Contact score and the ΔPSE variance, adjusted for the Familiarity score, which were significantly correlated as well (r_p = -0.44 [-0.62, -0.17]). See Methods for definition of the Familiarity score and the Contact score. Dots represent individual participant's data, color coded according to morph type. Correlations were performed on the data shown in these panels.

Figure 5. Simulating retinotopic biases and learning effects in face-responsive ROIs. We hypothesized that neural units (voxels, small populations of neurons, or individual neurons) cover a limited portion of the visual field, and that learning increases the number of neural units selective to a particular identity. A) Increasing the number of units selective to one identity reduces the retinotopic bias. Results of simulating 500 experiments by varying the ratio of neural units selective to one of two

identities and fixing the gain to 1 for both identities. Dots represent median values
with 95% bootstrapped CIs (1,000 replicates; note that for some points the CIs are too
small to be seen). In all simulated ROIs the variance of the PSE around 50% decreases
with increasing number of units selective to a, but remains larger in IOG because of its
receptive field size. B) Population coverage of the units in each ROI estimated from
the face-task data in Kay et al. (2015) and used in the simulations. Circles at the
periphery show the simulated stimulus locations. Each image is normalized to the
number of units in each ROI. Receptive fields are computed with radius 2σ, following
the convention in Kay et al., (2015). Percentages below each image show the average
proportion of units whose receptive field cover the stimulus locations. Compared to
pFus and mFus, fewer units cover the stimuli in IOG resulting in a larger bias across
locations. C) Increasing the gain of the response to one identity fails to reduce the
retinotopic bias. D) Increasing the receptive field size of the units responsive to one
identity reduces the retinotopic bias. In both C) and D) each dot represents median
values of PSE variance for 500 simulated experiments. CIs are not shown to reduce
visual clutter.

Table 1. Correlation of parameter estimates across sessions for the two experiments.

Table 2. Comparison of within-subjects correlations of parameter estimates across
sessions with between-subjects correlations.

Table 3. Models predicting variance of the ΔPSE estimates across angular locations in
Experiment 2.

Extended Data. The archive contains data from both experiments, as well as the
analysis scripts.

Visconti di Oleggio Castello et al.   Retinotopic bias in face identification

Tables

Table 1. Correlation of parameter estimates across sessions for the two experiments.			
Parameter	r	t	df
Experiment 1			
PSE	0.89 [-0.23, 1]	4.86**	6
ΔPSE	0.71 [0.47, 0.84]	5.47***	30
Experiment 2			
PSE	0.98 [0.93, 0.99]	15.22***	10
ΔPSE	0.64 [0.5, 0.75]	9.02***	118
Note: *All confidence intervals are 95% BCa with 10,000 repetitions.* *$p < .05$. **$p < .01$. ***$p < .001$*			

Table 2. Comparison of within-subjects correlations of parameter estimates across sessions with between-subjects correlations.			
Morph	Within-subjects r	Between-subjects r	Difference
Experiment 1			
ab	$0.65^{†}$ [0.57, 0.8]	-0.22 [-0.41, -0.01]	$0.87^{†}$ [0.63, 1.1]
Experiment 2			
ab	0.32 [-0.10, 0.62]	-0.02 [-0.15, 0.11]	0.34 [-0.07, 0.69]
ac	$0.62^{†}$ [0.35, 0.79]	-0.07 [-0.21, 0.08]	$0.68^{†}$ [0.41, 0.92]
bc	$0.85^{†}$ [0.61, 0.95]	-0.08 [-0.27, 0.12]	$0.92^{†}$ [0.68, 1.15]
Note: *All confidence intervals are 95% BCa with 10,000 repetitions.* *† indicates that the CIs do not contain 0.*			

Table 3. Models predicting variance of the ΔPSE estimates across angular locations in Experiment 2.

Model	R^2	Score	$\boldsymbol{\beta}$	η_p^2	t	p
1	0.32	Familiarity	-0.0574	0.32	-3.59	0.0013
2	0.45	Familiarity	-0.0390	0.17	-2.38	0.0249
		Contact	-0.0452	0.19	-2.512	0.0183