Transfer learning for biomedical named entity recognition with neural networks

John M Giorgi [1,2]* and Gary D Bader [1,2,3]

[1] Department of Computer Science, University of Toronto, 10 Kings College Road, Toronto, Canada M5S 3G4

[2] The Donnelly Centre, University of Toronto, 160 College Street, Toronto, Canada M5S 3E1

[3] Department of Molecular Genetics, University of Toronto, 1 King's College Circle, Toronto ON M5S 1A8

*To whom correspondence should be addressed.

Associate Editor: XXXXXXX

Abstract

Motivation: The explosive increase of biomedical literature has made information extraction an increasingly important tool for biomedical research. A fundamental task is the recognition of biomedical named entities (NER) such as genes/proteins, diseases, and species. Recently, a domain-independent method based on deep learning and statistical word embeddings, called long short-term memory network-conditional random field (LSTM-CRF), has been shown to outperform state-of-the-art entity-specific NER tools. However, this method is dependent on gold-standard corpora (GSCs) consisting of hand-labeled entities, which tend to be small but highly reliable. An alternative to GSCs are silver-standard corpora (SSCs), which are generated by harmonizing the annotations made by several automatic annotation systems. SSCs typically contain much more noise than GSCs but have the advantage of containing many more training examples. Ideally, these corpora could be combined to achieve the benefits of both, which is an opportunity for transfer learning. In this work, we analyze to what extent transfer learning improves upon state-of-the-art results for biomedical NER. We also attempt to identify the scenarios where transfer learning offers the biggest advantages.

Results: We demonstrate that transferring a deep neural network (DNN) trained on a large, noisy SSC to a smaller, but more reliable GSC improves upon state-of-the-art results for biomedical NER. Compared to a state-of-the-art baseline evaluated on 17 GSCs covering four different entity classes, transfer learning results in an average reduction in error of approximately 9%. We found transfer learning to be especially beneficial for target data sets with a small number of labels (approximately 5000 or less).

Availability and implementation: Source code for the LSTM-CRF is available at https://github.com/Franck-Dernoncourt/NeuroNER/ and links to the corpora are available at https://github.com/BaderLab/Transfer-Learning-BNER-Bioinformatics-2018/.

Contact: johnmg@cs.toronto.edu

Supplementary information: Supplementary data are available at *Bioinformatics* online.

1 Introduction

The sheer quantity of biological information deposited in literature every day leads to information overload for biomedical researchers. In 2016 alone there were 869,666 citations indexed in MEDLINE (https://www.nlm.nih.gov/bsd/index_stats_comp.html), which is greater than one paper per minute. Ideally, efficient, accurate text-mining and information extraction tools and methods could be used to help unlock structured information from this growing amount of raw text for use in computational data analysis. Text-mining has already proven useful for many types of large-scale biomedical data analysis, such as network biology (Zhou *et al.*, 2014), gene prioritization (Aerts *et al.*, 2006), drug repositioning (Wang and Zhang, 2013), and the creation of curated databases (Li *et al.*, 2015). A fundamental task in biomedical information

1

extraction is the recognition in text of biomedical named entities (NER), such as genes and gene products, chemicals, diseases, and species. Recently, a domain-independent method based on deep learning and statistical word embeddings, called long short-term memory network-conditional random field (LSTM-CRF), has been shown to outperform state-of-the-art entity-specific biomedical NER tools (Habibi *et al.*, 2017). However, as is often the case with supervised, deep neural network (DNN) based approaches, this method is dependent on large amounts of manually annotated data in the form of gold standard corpora (GSCs). The creation of a GSC is laborious: annotation guidelines must be established, domain experts must be trained, the annotation process is time-consuming and annotation disagreements must be resolved. As a consequence, GSCs in the biomedical domain tend to be small (but highly reliable) and focus on specific subdomains.

An alternative is the use of silver-standard corpora (SSCs). SSCs are generated by using multiple named entity taggers to annotate a large, unlabeled corpus. The heterogeneous results are automatically integrated, yielding a consensus-based, machine-generated ground truth. Compared to the generation of GSCs, this procedure is inexpensive, fast, and results in very large training data sets. The use of SSCs for biomedical NER has been evaluated in the Collaborative Annotation of a Large Biomedical Corpus (CALBC) project (Rebholz-Schuhmann *et al.*, 2010). The CALBC SSC was conceived as a replacement for GSCs, which would be much larger, more broadly scoped and more diversely annotated. However, Chowdhury and Lavelli compared a gene recognition system trained on an initial version of the CALBC SSC against the system trained on a BioCreative GSC. The system trained on the SSC performed considerably worse than when trained on the GSC (Chowdhury and Lavelli, 2011). While SSCs have not proven to be viable replacements for GSCs, at least for the task of biomedical NER, they do have the advantage of containing many more training examples (often in excess of 100 times more). This presents a unique transfer learning opportunity.

Transfer learning aims to perform a task on a target data set using knowledge learned from a source data set (Li, 2010; Weiss *et al.*, 2016; Pan and Yang, 2010). For DNNs, transfer learning is typically implemented by using some or all of the learned parameters of a network pre-trained on a source data set to initialize training for a second network to be trained on a target data set. Ideally, transfer learning improves generalization of the model, reduces training times on the target data set, and reduces the amount of labeled data needed to obtain high performance. The idea has been applied to many fields, such as speech recognition (Wang and Zheng, 2015), finance (Stamate *et al.*, 2015) and computer vision (Yosinski *et al.*, 2014; Oquab *et al.*, 2014; Zeiler and Fergus, 2014). Despite its popularity, few studies have been performed on transfer learning for DNN-based models in the field of natural language processing (NLP). For example, Mou *et al.* (2016) focused on transfer learning with convolutional neural networks (CNN) for sentence classification. To the best of our knowledge, there exists only one study which has analyzed transfer learning for DNN-based models in the context of NER (Dernoncourt *et al.*, 2017c), and no study which has analyzed transfer learning for DNN-based approaches to biomedical NER.

In this work, we analyze to what extent transfer learning on a source SSC to a target GSC improves performance on GSCs covering four different biomedical entity classes: chemicals, diseases, species and genes/proteins. We also attempt to identify the nature of these improvements and the scenarios where transfer learning offers the biggest advantages. The primary motivation for transfer learning from a SSC to a GSC is that we are able to expose the network to a large number of training examples while minimizing the impact of noise in the SSC on model performance.

2 Materials and methods

The following sections present a technical explanation of the DNN architecture used in this study. We first briefly describe LSTM, a specific kind of DNN, and then discuss the architecture of the hybrid LSTM-CRF model. We also describe the corpora used for evaluation and details regarding text pre-processing and evaluation metrics.

2.1 LSTM-CRF

Recurrent neural networks (RNNs) are a popular choice for sequence labeling tasks, due to their ability to use previous information in a sequence for processing of current input. Although RNNs can, in theory, learn long-range dependencies, they fail to do so in practice and tend to be biased towards their most recent inputs in the sequence (Bengio *et al.*, 1994). An LSTM is a specific RNN architecture which mitigates this issue by keeping a memory cell that serves as a summary of the preceding elements of an input sequence and is able to model dependencies between sequence elements even if they are far apart (Hochreiter and Schmidhuber, 1997). The input to an LSTM unit is a sequence of vectors $x_1, x_2, ..., x_T$ of length T, for which it produces an output sequence of vectors $h_1, h_2, ...h_T$ of equal length by applying a non-linear transformation learned during the training phase. Each h_t is called the activation of the LSTM at token t, where a token is an instance of a sequence of characters in a document that are grouped together as a useful semantic unit for processing. The formula to compute one activation of an LSTM unit in the LSTM-CRF model is provided below (Lample *et al.*, 2016):

$$i_t = \sigma(W_{xi}x_t + W_{hi}h_{t-1} + W_{ci}c_{t-1} + b_i)$$
$$c_t = (1 - i_t) \odot c_{t-1} + i_t \odot tanh(W_{xc}x_t + W_{hc}h_{t-1} + b_c)$$
$$o_t = \sigma(W_{xo}x_t + W_{ho}h_{t-1} + W_{co}c_t + b_o)$$
$$h_t = o_t \odot tanh(c_t)$$

where all Ws and bs are trainable parameters, $\sigma(\cdot)$ and $tanh(\cdot)$ denote the element-wise sigmoid and hyperbolic tangent activation functions, and $\odot$ is the element-wise product. Such an LSTM-layer processes the input in one direction and thus can only encode dependencies on elements that came earlier in the sequence. As a remedy for this problem, another LSTM-layer which processes input in the reverse direction is commonly used, which allows detecting dependencies on elements later in the text. The resulting network is called a bi-directional LSTM (Graves and Schmidhuber, 2005). The representation of a word using this model is obtained by concatenating its left and right context representations, $h_t = [\overrightarrow{h_t}; \overleftarrow{h_t}]$. These representations effectively encode a representation of a word in context. Finally, a sequential conditional random field (Lafferty *et al.*, 2001) receives as input the scores outputted by the bi-directional LSTM network to jointly model tagging decisions. LSTM-CRF (Lample *et al.*, 2016) is a domain-independent NER method which does not rely on any language-specific knowledge or resources such as dictionaries. In this study, we used NeuroNER (Dernoncourt *et al.*, 2017b), a named entity recognizer based on a bi-directional LSTM-CRF architecture. It comprises six major components:

1. **Token Embedding layer** maps each token to a token embedding.
2. **Character embedding layer** maps each character to a character embedding.
3. **Character LSTM layer** takes as input character embeddings and outputs a single vector that summarizes the information from the sequence of characters in the corresponding token.
4. **Token LSTM layer** takes as input a sequence of character-enhanced token vectors, which are formed by concatenating the outputs of the token embedding layer and the character LSTM layer.

Fig. 1. Architecture of the hybrid long short-term memory network-conditional random field (LSTM-CRF) model for named entity recognition (NER). T is the number of tokens, x_i is the i^{th} token, $\ell(i)$ is the number of characters of the i^{ith} token and $x_{i,j}$ is the j^{th} character in the i^{th} token. For transfer learning experiments, we train the parameters of the model on a source data set, and transfer all of the parameters to initialize the model for training on a target data set.

5. **Label prediction layer** Takes as input the character-enhanced token embeddings from the token LSTM layer and outputs the sequence of vectors containing the probability of each label for each corresponding token.

6. **Label sequence optimization layer** Using a CRF, outputs the most likely sequence of predicted labels based on the sequence of probability vectors from the previous layer.

Figure 1 illustrates the DNN architecture. All layers of the network are learned jointly. A detailed description of the architecture is explained in Dernoncourt *et al.* (2017a).

2.1.1 Training

The network was trained using the back-propagation algorithm to update the parameters on every training example, one at a time, using stochastic gradient descent. For regularization, dropout is applied before the token LSTM layer, and early stopping is used on the validation set with a patience of 10 epochs. While training on the source data sets, the learning rate was set to 0.0005, gradient clipping to 5.0 and the dropout rate to 0.8. These hyper-parameters were chosen to discourage convergence of the network on the source data set. While training on the target data sets, the learning rate was raised to 0.005, and the dropout rate lowered to 0.5. These are the default hyper-parameters of NeuroNER and give good performance on most NER tasks. Additionally, Lample *et al.* (2016) showed a dropout rate of 0.5 to be optimal for the task of NER.

2.2 Gold standard corpora

We performed our evaluations on four entity types: chemicals, diseases, species and genes/proteins. We relied on a total of 17 data sets (i.e., GSCs), each containing hand-labeled annotations for one of these entity types, such as the "CDR" corpus for chemicals (Li *et al.*, 2016), "NCBI Disease" for disease names (Doğan *et al.*, 2014), "S800" for species (Pafilis *et al.*, 2013) and "DECA" for genes/proteins (Wang *et al.*, 2010). Table 1 lists all corpora and their characteristics, like the number of sentences, tokens

and annotated entities per entity class (measured after text pre-processing as described in Section 2.6).

2.3 Silver standard corpora

We collected 50,000 abstracts at random from the CALBC-SSC-III-Small corpus (Rebholz-Schuhmann *et al.*, 2010) for each of the four entity types it annotates: *CHED*, chemicals, and drugs, *DISO*, diseases, *LIVB*, living beings, and *PRGE*, proteins and genes. These SSC corpora served as the source data sets for each transfer learning evaluation. For each corpus, any document that appeared in at least one of the GSCs annotated for the same entity type was excluded (e.g., if a document with PubMed ID 130845 was found in a GSC annotated for genes/proteins, it was excluded from the PRGE SSC). In an effort to reduce noise in the SSCs, a selection of entities present but not annotated in any of the GSCs of the same entity type were removed from the SSCs. For example, certain text spans such as "genes", "proteins", and "animals" are annotated in the SSCs but not annotated in any of the GSCs of the same entity type, and so were removed from the SSCs (see Supplementary Material).

2.4 Word embeddings

We utilized statistical word embedding techniques to capture functional (i.e., semantic and syntactic) similarity of words based on their surrounding words. Word embeddings are pre-trained using large unlabeled data sets typically based on token co-occurrences (Mikolov *et al.*, 2013; Collobert *et al.*, 2011; Pennington *et al.*, 2014). The learned vectors, or word embeddings, encode many linguistic regularities and patterns, some of which can be represented as linear translations. In the canonical example, the resulting vector for vec("king") − vec("man") + vec("woman") is closest to the vector associated with "queen", i.e., vec("queen"). The model used in this study, denoted *Wiki-PubMed-PMC*, was trained on a combination of PubMed abstracts (nearly 23 million abstracts) and PubMedCentral (PMC) articles (nearly 700,000 full-text articles) plus approximately four million English Wikipedia articles, and therefore mixes domain-specific texts with domain-independent ones. The model was created by Pyysalo *et al.* (2013) using Google's word2vec (Mikolov *et al.*, 2013). We chose this model because Habibi *et al.*, 2017 showed it to be optimal for the task of biomedical NER.

2.5 Character embeddings

The token-based word embeddings introduced above effectively capture distributional similarities of words (where does the word tend to occur in a corpus?) but are less effective at capturing orthographic similarities (what does the word look like?). In addition, token-based word embeddings cannot account for out-of-vocabulary tokens and misspellings. Character-based word representation models (Ling *et al.*, 2015) offer a solution to these problems by using each individual character of a token to generate its vector representation. Character-based word embeddings encode sub-token patterns such as morphemes (e.g. suffixes and prefixes), morphological inflections (e.g. number and tense) and other information not contained in the token-based word embeddings. The LSTM-CRF architecture used in this study combines character-based word representations with token-based word representations, allowing the model to learn distributional and orthographic features of words. Character embeddings are initialized randomly and learned jointly with the other parameters of the DNN.

2.6 Text pre-processing

All corpora were first converted to the Brat standoff format (http://brat.nlplab.org/standoff.html). In this format, annotations are stored separately from the annotated document text. Thus, for each text document

Table 1. Gold standard corpora used in this work.

Corpus	Text genre	Text type	Entity type	No. sentences	No. tokens	No. unique tokens	No. annotations	No. unique annotations
Arizona Disease (Leaman et al., 2009)	Scientific Article	Abstract	Diseases	2804	74346	8133	3425	1266
BioInfer (Pyysalo et al., 2007)	Scientific Article	Abstract	Genes/proteins	1147	34187	5200	4378	1041
BioSemantics (Akhondi et al., 2014)	Patent	Full-text	Chemicals	163219	6608020	173193	386110	72782
CEMP (Krallinger et al., 2015)	Patent	Full-text	Chemicals	35679	1495524	60850	65685	20630
CDR (Li et al., 2016)	Scientific Article	Abstract	Chemicals	14166	326506	22083	15915	2623
			Diseases	14166	326506	22083	12617	3113
CellFinder (Neves et al., 2012)	Scientific Article	Full-text	Species	2234	66519	7584	479	42
			Genes/proteins	2234	66519	7584	1750	734
DECA (Wang et al., 2010)	Scientific Article	Abstract	Genes/proteins	5492	139771	14053	6324	2127
FSU-PRGE (Hahn et al., 2010)	Scientific Article	Abstract	Genes/proteins	35361	914717	453634	59489	27363
IEPA (Ding et al., 2001)	Scientific Article	Abstract	Genes/proteins	241	15365	2871	1110	130
Linnaeus (Gerner et al., 2010)	Scientific Article	Full-text	Species	19048	491253	33132	4259	419
miRNA (Bagewadi et al., 2014)	Scientific Article	Abstract	Diseases	2676	66419	7638	2159	606
			Species	2676	66419	7638	722	41
			Genes/Proteins	2676	66419	7638	1058	370
NCBI Disease (Doğan et al., 2014)	Scientific Article	Abstract	Diseases	7645	173283	12534	6881	2136
S800 (Pafilis et al., 2013)	Scientific Article	Abstract	Species	8356	198091	19992	3708	1503

in the corpus, there is a corresponding annotation file. The two files are associated by the file naming convention that their base name (file name without suffix) is the same. All annotations follow the same basic structure: each line contains one annotation, and each annotation is given an identifier that appears first on the line, separated from the rest of the annotation by a single tab character.

2.7 Evaluation metrics

We randomly divided each corpus into three disjoint subsets. 60% of the samples were used for training, 10% as the development set for the training of methods, and 30% for the final evaluation. We compared all methods in terms of precision, recall, and F1-score on the test sets. Precision is computed as the percentage of predicted labels that are gold labels, recall as the percentage of gold labels that are correctly predicted, and F1-score as the harmonic mean of precision and recall.

Table 2. Macro-averaged performance values in terms of precision, recall and F1-score for baseline (B) and transfer learning (TL) over the corpora per each entity type. Baseline values are derived from training on the target data set only, while transfer learning values are derived by training on the source data set followed by training on the target data set. The macro average is computed by averaging the performance scores obtained by the classifiers for each corpus of a given entity class. The highest values for each method are represented in bold.

	Precision (%)		Recall (%)		F1-score (%)	
	B	TL	B	TL	B	TL
Chemicals	**87.10**	87.05	89.19	**89.47**	88.08	**88.21**
Diseases	78.81	**79.68**	80.82	**81.93**	79.78	**80.79**
Species	82.65	**84.71**	86.29	**89.47**	85.24	**86.91**
Gene/protein	81.76	**83.38**	79.06	**83.38**	80.02	**82.52**

3 Results

We assessed the effect of transfer learning on the performance of a state-of-the-art method for biomedical NER (LSTM-CRF) on 17 different data sets covering four different types of biomedical entity classes. In our setting, we applied transfer learning by training all parameters of the DNN on a source data set (CALBC-SSC-III) for a particular entity type (e.g., genes/proteins) and used the same DNN to retrain on a target data set (i.e., a GSC) of the same entity type. Results were compared to training the model only on the target data set using the same word embeddings.

3.1 Quantifying the impact of transfer learning

In this experiment, we determine whether transfer learning improves on state-of-the-art results for biomedical NER. Table 2 compares the macro-averaged performance metrics of the model trained only on the target data set (i.e., the baseline) against the model trained on the source data set followed by the target data set for 17 evaluation sets. Transfer learning improves the average F1-scores over the baseline for each of the four entity classes, leading to an average reduction in error of 8.98% across the GSCs. On corpora annotated for diseases, species, and genes/proteins, transfer learning (on average) improved both precision and recall, leading to sizable improvements in F1-score. For corpora annotated for chemicals, transfer learning (on average) slightly increased recall at the cost of precision for a small increase in F1-score. More generally, transfer learning appears to be

especially effective on corpora with a small number of labels. For example, transfer learning led to a 9.69% improvement in F1-score on the test set of the CellFinder corpus annotated for genes/proteins — the fifth smallest corpus overall by number of labels. Conversely, the only GSC for which transfer learning worsened the performance compared to the baseline was the BioSemantics corpora, the largest GSC used in this study.

3.2 Learning curve for select evaluation sets

Figure 2 compares learning curves for the baseline model against the model trained with transfer learning on select GSCs, one for each entity class. The number of training examples used as the target training set is reported as a percent of the overall GSC size (e.g., for a GSC of 100 documents, a target train set size of 60% corresponds to 60 documents). The performance improvement due to transfer learning is especially pronounced when a small number of labels are used as the target training set. For example, on the miRNA corpus annotated for diseases, performing transfer learning and using 10% of examples as the train set leads to similar performance as not using transfer learning and using approximately 28% of examples as the train set. The performance gains from transfer learning diminish as the number of training examples used for the target training set increases. Together, these results suggest that transfer learning is especially beneficial for data sets with a small number of labels. Figure 3 more precisely captures this trend. Large improvements in F1-score are observed for corpora with up to approximately 5000 total annotations, with improvement quickly tailing off afterward. Indeed, all corpora for which transfer learning improved the F1-score by at least 1% have 5000 annotations or less. Therefore, it appears that the expected performance improvements derived from transfer learning are largest when the number of annotations in the target data set is approximately 5000 or less.

3.3 Error analysis

We compared the errors made by the baseline and transfer learning classifiers by computing intersections of false-positives (FPs), false-negatives (FNs) and true-positives (TPs) per entity type (Figure 4). In general, there is broad agreement for baseline and transfer learning classifiers, with different strengths per entity type. For diseases, transfer learning slightly increases the number of FNs but reduces the number of FPs and TPs — trading recall for precision. For species and genes/proteins, transfer learning has the opposite effect, decreasing the number of FNs but increasing the number of FPs and TPs — trading precision for recall. Transfer learning appears to have little effect on the sets of FNs, FPs, and TPs for chemical entities — which is congruent with the minimal impact that transfer learning had on average precision and recall for chemical corpora (Table 2). This is likely explained by the much larger size of the chemical gold standard corpora, which have a median of 65,685 annotations, greater than nine times that of the next largest set of corpora (diseases).

4 Discussion

In this study, we demonstrated that transfer learning from large SSCs (source) to smaller GSCs (target) improves performance over training solely on the GSCs for biomedical NER. On average, transfer learning leads to improvements in F1-score over a state-of-the-art baseline, though the nature and degree of these improvements vary per entity type (Table 2).

The effect of transfer learning is most pronounced when the target train set size is small, with improvements diminishing as the training set size grows (Figure 2). The largest improvements in performance were observed for corpora with 5000 total annotations or less (Figure 3). We conclude that the representations learned from the source data set are

Fig. 2. Impact of transfer learning on the F1-scores. Baseline corresponds to training the model only with the target data set, and transfer learning corresponds to training on the source data set followed by training on the target data set. The number of training examples used as the target training set is reported as a percent of the overall GSC size (e.g., for a GSC of 100 documents, a target train set size of 60% corresponds to 60 documents). Error bars represent the standard deviation (SD) for $n = 3$ trials. Error bars on the order of graph point size were omitted.

Fig. 3. Box plots representing absolute F1-score improvement over the baseline after transfer learning, grouped by the total number of annotations in the target gold-standard corpora (GSCs). Points represent performance improvements over the baseline after transfer learning for each of the individual 17 GSCs.

Fig. 4. Venn diagrams demonstrating the area of overlap among the false-negative (FN), false-positive (FP), and true-positive (TP) sets of the baseline and transfer learning methods per entity class.

effectively transferred and exploited for the target data set; when transfer learning is adopted, fewer annotations are needed to achieve the same level of performance as when the source data set is not used. Thus, our results suggest that researchers and text-mining practitioners can make use of transfer learning to reduce the number of hand-labeled annotations necessary to obtain high performance for biomedical NER. We also suggest that transfer learning is likely to be a valuable tool for existing GSCs with a small number of labels.

Transfer learning had little impact on performance for chemical GSCs. This is likely explained by the much larger size of these corpora, which have a median number of annotations nine times that of the next largest set of corpora (diseases). We suspect that relatively large corpora contain enough training examples for the model to generalize well, in which case we would not expect transfer learning to improve model performance. Indeed, the largest corpora in our study, the BioSemantics corpora (annotated for chemical entities), was the only corpora for which transfer learning worsened performance over the baseline. With 386,110 total annotations (more than double the sum total of annotations in the remaining 16 GSCs) the BioSemantics corpus is an outlier. To create such a large GSC, documents were first pre-annotated and made available to four independent annotator groups each consisting of two to ten annotators (Akhondi *et al.*, 2014). This is a much larger annotation effort than usual and is not realistic for the creation of typical GSCs in most contexts.

Dernoncourt *et al.* (2017c) performed a similar set of experiments, transferring an LSTM-CRF based NER model from a large labeled data set to a smaller data set for the task of de-identification of protected health information (PHI) from electronic health records (EHR). It was demonstrated that transfer learning improves the performance over state-of-the-art results, and may be especially beneficial for a target data set with a small number of labels. Our results confirm these findings in the context biomedical NER. The study also explored the importance of each layer of the DNN in transfer learning. They found that transferring a few lower layers is almost as efficient as transferring all layers, which supports the common hypothesis that higher layers of DNN architectures contain the parameters that are more specific to the task as well as the data set used for training. We performed a similar experiment (see Supplementary Figure 1) with similar results.

Biomedical NER has recently made substantial advances in performance with the application of deep learning (Habibi *et al.*, 2017). We show that transfer learning is a valuable addition to this method. However, further work is needed to optimize this approach: for instance, by determining the optimal size of the source data set, developing robust methods of filtering noise from the source data set, and extensive hyperparameter tuning (Reimers and Gurevych, 2017; Young *et al.*, 2015).

5 Conclusion

In this work, we have studied transfer learning with DNNs for biomedical NER (specifically LSTM-CRF) by transferring parameters learned on large, noisy SSC for fine-tuning on smaller, but more reliable GSC. We demonstrated that compared to a state-of-the-art baseline evaluated on 17 GSCs, transfer learning results in an average reduction in error of approximately 9%. The largest performance improvements were observed for GSCs with a small number of labels (on the order of 5000 or less). Our results suggest that researchers and text-mining practitioners can make use of transfer learning to reduce the number of hand-labeled annotations necessary to obtain high performance for biomedical NER. We also suggest that transfer learning is likely to be a valuable tool for existing GSC with a small number of labels. We hope this study will increase interest in the development of large, broadly-scoped SSCs for the training of supervised biomedical information extraction methods.

Acknowledgements

We gratefully acknowledge the support of NVIDIA Corporation with the donation of the Titan Xp GPU used for this research.

Funding

This research was funded by the US National Institutes of Health (grant #5U41 HG006623-02).

References

Aerts, S., Lambrechts, D., Maity, S., Loo, P. V., Coessens, B., Smet, F. D., Tranchevent, L.-C., Moor, B. D., Marynen, P., Hassan, B., Carmeliet, P., and Moreau, Y. (2006). Gene prioritization through genomic data fusion. *Nature Biotechnology*, **24**(5), 537–544.

Akhondi, S. A., Klenner, A. G., Tyrchan, C., Manchala, A. K., Boppana, K., Lowe, D., Zimmermann, M., Jagarlapudi, S. A., Sayle, R., Kors, J. A., *et al.* (2014). Annotated chemical patent corpus: a gold standard for text mining. *PloS one*, **9**(9), e107477.

Bagewadi, S., Bobić, T., Hofmann-Apitius, M., Fluck, J., and Klinger, R. (2014). Detecting mirna mentions and relations in biomedical literature. *F1000Research*, **3**.

Bengio, Y., Simard, P., and Frasconi, P. (1994). Learning long-term dependencies with gradient descent is difficult. *IEEE transactions on neural networks*, **5**(2), 157–166.

Chowdhury, F. M. and Lavelli, A. (2011). Assessing the practical usability of an automatically annotated corpus. In *Proceedings of the 5th Linguistic Annotation Workshop*, pages 101–109. Association for Computational Linguistics.

Collobert, R., Weston, J., Bottou, L., Karlen, M., Kavukcuoglu, K., and Kuksa, P. (2011). Natural language processing (almost) from scratch. *Journal of Machine Learning Research*, **12**(Aug), 2493–2537.

Dernoncourt, F., Lee, J. Y., Uzuner, O., and Szolovits, P. (2017a). De-identification of patient notes with recurrent neural networks. *Journal of the American Medical Informatics Association*, **24**(3), 596–606.

Dernoncourt, F., Lee, J. Y., and Szolovits, P. (2017b). NeuroNER: an easy-to-use program for named-entity recognition based on neural networks. *Conference on Empirical Methods on Natural Language Processing (EMNLP)*.

Dernoncourt, F., Lee, J. Y., and Szolovits, P. (2017c). Transfer learning for named-entity recognition with neural networks. *CoRR*, **abs/1705.06273**.

Ding, J., Berleant, D., Nettleton, D., and Wurtele, E. (2001). Mining medline: abstracts, sentences, or phrases? In *Biocomputing 2002*, pages 326–337. World Scientific.

Doğan, R. I., Leaman, R., and Lu, Z. (2014). NCBI disease corpus: A resource for disease name recognition and concept normalization. *Journal of Biomedical Informatics*, **47**, 1–10.

Gerner, M., Nenadic, G., and Bergman, C. M. (2010). Linnaeus: a species name identification system for biomedical literature. *BMC bioinformatics*, **11**, 85.

Graves, A. and Schmidhuber, J. (2005). Framewise phoneme classification with bidirectional lstm and other neural network architectures. *Neural Networks*, **18**(5), 602–610.

Habibi, M., Weber, L., Neves, M., Wiegandt, D. L., and Leser, U. (2017). Deep learning with word embeddings improves biomedical named entity recognition. *Bioinformatics*, **33**(14), i37–i48.

Hahn, U., Tomanek, K., Beisswanger, E., and Faessler, E. (2010). A proposal for a configurable silver standard. In *Proceedings of the Fourth Linguistic Annotation Workshop*, LAW IV '10, pages 235–242, Stroudsburg, PA, USA. Association for Computational Linguistics.

Hochreiter, S. and Schmidhuber, J. (1997). Long short-term memory. *Neural computation*, **9**(8), 1735–1780.

Krallinger, M., Leitner, F., Rabal, O., Vazquez, M., Oyarzabal, J., and Valencia, A. (2015). Chemdner: The drugs and chemical names extraction challenge. *Journal of cheminformatics*, **7**(S1), S1.

Lafferty, J. D., McCallum, A., and Pereira, F. C. N. (2001). Conditional random fields: Probabilistic models for segmenting and labeling sequence data. In *Proceedings of the Eighteenth International Conference on Machine Learning*, ICML '01, pages 282–289, San Francisco, CA, USA. Morgan Kaufmann Publishers Inc.

Lample, G., Ballesteros, M., Subramanian, S., Kawakami, K., and Dyer, C. (2016). Neural architectures for named entity recognition. In *Proceedings of the 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 260–270. Association for Computational Linguistics.

Leaman, R., Miller, C., and Gonzalez, G. (2009). Enabling recognition of diseases in biomedical text with machine learning: corpus and benchmark. In *Proceedings of the 2009 Symposium on Languages in Biology and Medicine*, volume 82.

Li, G., Ross, K. E., Arighi, C. N., Peng, Y., Wu, C. H., and Vijay-Shanker, K. (2015). miRTex: A text mining system for miRNA-gene relation extraction. *PLOS Computational Biology*, **11**(9), e1004391.

Li, J., Sun, Y., Johnson, R. J., Sciaky, D., Wei, C.-H., Leaman, R., Davis, A. P., Mattingly, C. J., Wiegers, T. C., and Lu, Z. (2016). Biocreative v cdr task corpus: a resource for chemical disease relation extraction. *Database*, **2016**, baw068.

Li, Q. (2010). Literature survey: domain adaptation algorithms for natural language processing. In *Proceedings of the Fourth Linguistic Annotation Workshop*, LAW IV '10, pages 8–10, Stroudsburg, PA, USA. Association for Computational Linguistics.

Ling, W., Luís, T., Marujo, L., Astudillo, R. F., Amir, S., Dyer, C., Black, A. W., and Trancoso, I. (2015). Finding function in form: Compositional character models for open vocabulary word representation. *arXiv preprint arXiv:1508.02096*.

Mikolov, T., Sutskever, I., Chen, K., Corrado, G. S., and Dean, J. (2013). Distributed representations of words and phrases and their compositionality. In *Advances in neural information processing systems*, pages 3111–3119.

Mou, L., Meng, Z., Yan, R., Li, G., Xu, Y., Zhang, L., and Jin, Z. (2016). How transferable are neural networks in nlp applications? *arXiv preprint arXiv:1603.06111*.

Neves, M., Damaschun, A., Kurtz, A., and Leser, U. (2012). Annotating and evaluating text for stem cell research. In *Proceedings of the Third Workshop on Building and Evaluation Resources for Biomedical Text Mining (BioTxtM 2012) at Language Resources and Evaluation (LREC). Istanbul, Turkey*, pages 16–23.

Oquab, M., Bottou, L., Laptev, I., and Sivic, J. (2014). Learning and transferring mid-level image representations using convolutional neural networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1717–1724.

Pafilis, E., Frankild, S. P., Fanini, L., Faulwetter, S., Pavloudi, C., Vasileiadou, A., Arvanitidis, C., and Jensen, L. J. (2013). The SPECIES and ORGANISMS resources for fast and accurate identification of taxonomic names in text. *PLoS ONE*, **8**(6), e65390.

Pan, S. J. and Yang, Q. (2010). A survey on transfer learning. *IEEE Transactions on knowledge and data engineering*, **22**(10), 1345–1359.

Pennington, J., Socher, R., and Manning, C. (2014). Glove: Global vectors for word representation. In *Proceedings of the 2014 conference on empirical methods in natural language processing (EMNLP)*, pages 1532–1543.

Pyysalo, S., Ginter, F., Heimonen, J., Bjorne, J., Boberg, J., Jarvinen, J., and Salakoski, T. (2007). Bioinfer: a corpus for information extraction in the biomedical domain. *BMC Bioinformatics*, **8**(1), 50.

Pyysalo, S., Ginter, F., Moen, H., Salakoski, T., and Ananiadou, S. (2013). Distributional semantics resources for biomedical text processing. In *Proceedings of the 5th International Symposium on Languages in Biology and Medicine*, Tokyo, Japan. LBM.

Rebholz-Schuhmann, D., Yepes, A. J. J., van Mulligen, E., Kang, N., Kors, J., Milward, D., Corbett, M., Buyko, E., Beisswanger, E., and Hahn, U. (2010). Calbc silver standard corpus. *Journal of Bioinformatics and Computational Biology*, **8**(1), 163–179.

Reimers, N. and Gurevych, I. (2017). Optimal hyperparameters for deep lstm-networks for sequence labeling tasks. *arXiv preprint arXiv:1707.06799*.

Stamate, C., Magoulas, G. D., and Thomas, M. S. (2015). Transfer learning approach for financial applications. *arXiv preprint arXiv:1509.02807*.

Wang, D. and Zheng, T. F. (2015). Transfer learning for speech and language processing. In *Signal and Information Processing Association Annual Summit and Conference (APSIPA), 2015 Asia-Pacific*, pages 1225–1237. IEEE.

Wang, X., Tsujii, J., and Ananiadou, S. (2010). Disambiguating the species of biomedical named entities using natural language parsers. *Bioinformatics*, **26**(5), 661–667.

Wang, Z.-Y. and Zhang, H.-Y. (2013). Rational drug repositioning by medical genetics. *Nature Biotechnology*, **31**(12), 1080–1082.

Weiss, K., Khoshgoftaar, T. M., and Wang, D. (2016). A survey of transfer learning. *Journal of Big Data*, **3**(1).

Yosinski, J., Clune, J., Bengio, Y., and Lipson, H. (2014). How transferable are features in deep neural networks? In *Advances in neural information processing systems*, pages 3320–3328.

Young, S. R., Rose, D. C., Karnowski, T. P., Lim, S.-H., and Patton, R. M. (2015). Optimizing deep learning hyper-parameters through an evolutionary algorithm. In *Proceedings of the Workshop on Machine Learning in High-Performance Computing Environments*, MLHPC '15, pages 4:1–4:5, New York, NY, USA. ACM.

Zeiler, M. D. and Fergus, R. (2014). Visualizing and understanding convolutional networks. In *European conference on computer vision*, pages 818–833. Springer.

Zhou, X., Menche, J., Barabási, A.-L., and Sharma, A. (2014). Human symptoms–disease network. *Nature Communications*, **5**.