KrakenHLL: Confident and fast metagenomics classification using unique k-mer counts

Breitwieser FP[1] and Salzberg SL[1,2]

1 Center for Computational Biology, McKusick-Nathans Institute of Genetic Medicine, Johns Hopkins School of Medicine, Baltimore, MD, United States

2 Departments of Biomedical Engineering, Computer Science and Biostatistics, Johns Hopkins University, Baltimore, MD, United States

Abstract

False positive identifications are a significant problem in metagenomic classification. We present KrakenHLL, a novel metagenomic classifier that combines the fast k-mer based classification of Kraken with an efficient algorithm for assessing the coverage of unique k-mers found in each species in a dataset. On various test datasets, KrakenHLL gives better recall and F1-scores than other methods, and effectively classifies and distinguishes pathogens with low abundance from false positives in infectious disease samples. By using the probabilistic cardinality estimator HyperLogLog (HLL), KrakenHLL is as fast as Kraken and requires little additional memory.

Keywords: metagenomics, microbiome, metagenomics classification, pathogen detection, infectious disease diagnosis

Background

Metagenomic classifiers attempt to assign a taxonomic identity to each read in a data set. Because metagenomics data often contain tens of millions of reads, classification is typically

done using exact matching of short words of length k (k-mers) rather than alignment, which

would be unacceptably slow. The results contain read classifications but not their aligned

positions in the genomes [as reviewed by 1]. However, read counts can be deceiving. Sequence

contamination of the samples–introduced from laboratory kits or the environment during sample

extraction, handling or sequencing–can yield high numbers of spurious identifications [2, 3].

Having only small amounts of input material can further compound the problem of

contamination. When using sequencing for clinical diagnosis of infectious diseases, for example,

less than 0.1% of the DNA may derive from microbes of interest [4, 5]. Additional spurious

matches can result from low-complexity regions of genomes and from contamination in the

database genomes themselves [6].

Such false-positive reads typically match only small portions of a genome; e.g., if a species'

genome contains a low-complexity region, and the only reads matching that species fall in this

region, then the species was probably not present in the sample. Reads from microbes that are

truly present should distribute relatively uniformly across the genome rather than being

concentrated in one or a few locations. Genome alignment can reveal this information. However,

alignment is resource intensive, requiring the construction of indexes for every genome and a

relatively slow alignment step to compare all reads against those indexes. Some metagenomics

methods do use coverage information to improve mapping or quantification accuracy, but these

methods require results from much slower alignment methods as input [7]. Assembly-based

methods also help to avoid false positives, but these are useful only for highly abundant species

[8].

Here, we present KrakenHLL, a novel method that combines very fast k-mer based classification

with a fast k-mer cardinality estimation. KrakenHLL is based on the Kraken metagenomics

classifier [9], to which it adds a method for counting the number of unique k-mers identified for

each taxon using the efficient cardinality estimation algorithm HyperLogLog [10-12]. By

counting how many of each genome's unique k-mers are covered by reads, KrakenHLL can

often discern false positive from true positive matches. Furthermore, KrakenHLL implements

additional new features to improve metagenomics classification: (a) searches can be done against

multiple databases hierarchically, (b) the taxonomy can be extended to include nodes for strains

and plasmids, thus enabling their detection, and (c) the database build script allows the addition

of >100,000 viruses from the NCBI Viral Genome Resource [13]. KrakenHLL provides a

superset of the information provided by Kraken while running equally fast or slightly faster, and

while using very little additional memory during classification.

58 Results

KrakenHLL was developed to provide efficient k-mer count information for all taxa identified in

a metagenomics experiment. The main workflow is as follows: As reads are processed, each k-

mer is assigned a taxon from the database (Figure 1A). KrakenHLL instantiates a HyperLogLog

data sketch for each taxon, and adds the k-mers to it (Figure 1B and Supplementary

Information). After classification of a read, KrakenHLL traverses up the taxonomic tree and

merges the estimators of each taxon with its parent. In its classification report, KrakenHLL

includes the number of unique k-mers and the depth of k-mer coverage for each taxon that it

observed in the input data (Figure 1C).

68   [FIGURE 1]

Figure 1. Overview of the KrakenHLL algorithm and output. (A) An input read is shown as a

long gray rectangle, with k-mers shown as shorter rectangles below it. The taxon mappings for

each k-mer are compared to the database, shown as larger rectangles on the right. For each taxon,

a unique k-mer counter is instantiated, and the observed k-mers (K7, K8, and K9) are added to

the counters. (B) Unique k-mer counting is implemented with the probabilistic estimation

method HyperLogLog (HLL) using 16KB of memory per counter, which limits the error in the

cardinality estimate to 1% (see main text). (C) The output includes the number of reads, unique

k-mers, duplicity (average time each k-mer has been seen) and coverage for each taxon observed

in the input data.

78
79
Efficient k-mer cardinality estimation using the HyperLogLog algorithm

Cardinality is the number of elements in a set without duplicates; *e. g.* the number of distinct

words in a text. An exact count can be kept by storing the elements in a sorted list or linear

probing hash table, but that requires memory proportional to the number of unique elements.

When an accurate estimate of the cardinality is sufficient, however, the computation can be done

efficiently with very small amount of fixed memory. The HyperLogLog algorithm (HLL) [10],

which is well suited for k-mer counting [14], keeps a summary or *sketch* of the data that is

sufficient for precise estimation of the cardinality, but requires only a small amount of constant

space to estimate cardinalities up to billions. The method centers on the idea that long runs of

leading zeros, which can be efficiently computed using machine instructions, are unlikely in

random bitstrings. For example, about every fourth bitstring in a random series should start with

01_2 (one 0-bit before the first 1-bit), and about every 32^{nd} hash starts with 00001_2. Conversely, if

we know the maximum number of leading zeros k of the members of a random set, we can use

2^{k+1} as a crude estimate of its cardinality (more details in the Suppl. Methods). HLL keeps $m=2^p$

one-byte counts of the maximum numbers of leading zeros on the data (its data *sketch*), with p,

the precision parameter, typically between 10 and 18 (see Figure 2). For cardinalities up to $m/4$,

we use the sparse representation of the registers suggested by Heule et al. [11] that has the much

higher effective precision p' of 25 by encoding each index and count in a vector of four-byte

values. To add a k-mer to its taxon's sketch, the k-mer (with k up to 31) is first mapped by a hash

function to a 64-bit hash value. Note that k-mers that contain non-A, C, G or T characters (such

as ambiguous IUPAC characters) are ignored by KrakenHLL. The first p bits of the hash value

are used as index i, and the later $64-p=q$ bits for counting the number of leading zeros k. The

value of the register $M[i]$ in the sketch is updated if k is larger than the current value of $M[i]$.

When the read classification is finished, the taxon sketches are aggregated up the taxonomy tree

by taking the maximum of each register value. The resulting sketches are the same as if the k-

mers were counted at their whole lineage from the beginning. KrakenHLL then computes

cardinality estimates using the formula proposed by Ertl [12], which has theoretical and practical

advantages and does not require empirical bias correction factors [10, 11]. In our tests it

performed better than Flajolet's and Heule's methods (Suppl. Figures 1 and 2).

The expected relative error of the final cardinality estimate is approximately 1.04/sqrt(2^p) [10].

With $p=14$, the sketch uses 2^{14} one-byte registers, i.e. 16 KB of space, and gives estimates with

relative errors of less than 1% (Figure 2). An exact counter would require about 40 MB per

million distinct k-mers when implemented using an unordered set; i. e. about 40 GB for the

pathogen identification samples with an average of one billion distinct k-mers per sample.

However, unordered sets have worst case insertion time complexity linear to the container size

(and require re-hashes on resize), while it is constant for HLL.

[FIGURE 2]

p	$m=2^p$	Space (kB)	Rel. Error
10	1024	1	3.25%
11	2048	2	2.23%
12	4096	4	1.63%
13	8192	8	1.15%
14	16384	16	0.81%
15	32768	32	0.57%
16	65536	64	0.41%
17	131072	128	0.29%
18	262144	256	0.20%
25			0.02%

Figure 2: Cardinality estimation using HyperLogLog for randomly sampled k-mers from

microbial genomes. Left: standard deviations of the relative errors of the estimate with precision

p ranging from 10 to 18. No systematic biases are apparent, and, as expected, the errors decrease

with higher values of p. Up to cardinalities of about $2^p/4$, the relative error is near zero. At higher

cardinalities, the error boundaries stay near constant. Right: the size of the registers, space

requirement, and expected relative error for HyperLogLog cardinality estimates with different

values of p. For example, with a precision $p=14$, the expected relative error is 0.81% and the

counter only requires 16 KB of space, which is three orders of magnitude less than that of an

exact counter (at a cardinality of one million). Up to cardinalities of $2^p/4$, KrakenHLL uses a

sparse representation of the counter with a higher precision of 25 and an effective relative error

rate of about 0.02%.

Results on twenty-one simulated and ten biological test datasets

We assessed KrakenHLL's performance on the 34 datasets compiled by McIntyre et al. [15] (see

Suppl. Table 3). We place greater emphasis on the eleven biological datasets, which contain

more realistic laboratory and environmental contamination. In the first part of this section, we

show that unique k-mer counts provide higher classification accuracy than read counts, and in

the second part we compare KrakenHLL with the results of eleven metagenomics classifiers. We

ran KrakenHLL on three databases: 'orig', the database used by McIntyre et al., 'std', which

contains all current complete bacterial, archaeal and viral genomes from RefSeq plus viral

neighbor sequences and the human reference genome, and 'nt', which contains all microbial

sequences (including fungi and protists) in the non-redundant nucleotide collection nr/nt

provided by NCBI (see Suppl. Methods Section 2 for details). The 'std' database furthermore

includes the UniVec and EmVec sequence sets of synthetic constructs and vector sequences; and

low-complexity k-mers in microbial sequences were masked using NCBI's dustmasker with

default settings. We use two metrics to compare how well methods can separate true positives

and false positives: (a) F1 score, i. e. the harmonic mean of precision p and recall r, and (b) recall

at a maximum false discovery rate (FDR) of 5%. For each method, we compute and select the

ideal thresholds based on the read count, k-mer count or abundance calls. Precision p is defined

as the number of correctly called species (or genera) divided by the number of all called species

(or genera) at a given threshold. Recall r is the proportion of species (or genera) that are in the

test dataset and that are called at a given threshold. Higher F1 scores indicate a better separation

between true positives and false positives. Higher recall means that more true species can be

recovered while controlling the false positives.

Because the NCBI taxonomy has been updated since the datasets were published, we manually

updated the "truth" sets in several datasets (see Suppl. Methods Section 2.3 for all changes). Any

cases that might have been missed would result in a lower apparent performance of KrakenHLL.

Note that we exclude the over ten-year-old simulated datasets simHC, simMC and simLC from

Mavromatis et al. (2007), as well as the biological dataset JGI SRR033547 which has only 100

reads.

Data Type	Rank	Statistic	orig			std			nt		
			Reads	Kmers	Diff	Reads	Kmers	Diff	Reads	Kmers	Diff
Bio	Genus	Recall	0.90	0.93	**+4.0%**	0.89	0.94	**+6.2%**	0.91	0.99	**+8.9%**
		F1	0.95	0.96	**+1.8%**	0.95	0.97	**+2.6%**	0.96	0.99	**+3.4%**
	Species	Recall	0.85	0.87	**+2.6%**	0.70	0.78	**+11.8%**	0.95	0.98	**+3.1%**
		F1	0.94	0.94	**+0.7%**	0.90	0.92	**+2.5%**	0.97	0.99	**+1.6%**
Sim	Genus	Recall	0.96	0.94	-2.1%	0.95	0.97	**+2.5%**	0.98	0.99	**+0.8%**
		F1	0.98	0.98	-0.0%	0.98	0.98	**+0.3%**	0.99	0.99	**+0.3%**
	Species	Recall	0.92	0.93	**+0.6%**	0.88	0.88	**+0.3%**	0.90	0.90	-0.1%
		F1	0.97	0.97	**+0.3%**	0.94	0.94	**+0.5%**	0.96	0.96	-0.1%

161 Table 1: Performance of read count and unique k-mer thresholds on 10 biological and 21

162 simulated datasets against three databases ('orig', 'std', 'nt'). Unique k-mer count thresholds give

163 up to 10% better recall and F1 scores, particularly for the biological datasets.

Unique k-mer versus read count thresholds

We first looked at the performance of the unique k-mer count thresholds versus read count

thresholds (as would be used with Kraken). The k-mer count thresholds worked very well,

particularly for the biological datasets (Table 1 and Suppl. Table 3). On the genus level, the

average recall in the biological datasets increases by 4-9%, and the average F1 score increases 2-

3%. On the species level, the average increase in recall in the biological sets is between 3 and

12%, and the F1 score increases by 1-2%.

On the simulated datasets, the differences are less pronounced and vary between databases, even

though on average the unique k-mer count is again better. However, only in two cases (genus

recall on databases 'orig' and 'std') the difference is higher than 1% in any direction. We find

that simulated datasets often lack false positives with a decent number of reads but a lower

number of unique k-mer counts, which we see in real data. Instead, in most simulated datasets

the number of unique k-mers is linearly increasing with the number of unique reads in both true

and false positives (Suppl. Figure 4). In biological datasets, sequence contamination and lower

read counts for the true positives make the task of separating true and false positives harder.

Comparison of KrakenHLL with eleven other methods

Next, we compared KrakenHLL's unique k-mer counts with the results of eleven metagenomics

classifiers from McIntyre et al. [15], which include the alignment-based methods Blast + Megan

[16, 17], Diamond + Megan [17, 18] and MetaFlow [19], the k-mer based CLARK [20],

CLARK-S [21], Kraken [9], LMAT [22], NBC [23] and the marker-based methods GOTTCHA

[24], MetaPhlAn2 [25], PhyloSift [26]. KrakenHLL with database 'nt' has the highest average

recall and F1 score across the biological datasets, as shown in Table 2. As seen before, using

unique k-mer instead of read counts as thresholds increases the scores. While the database

selection proves to be very important (KrakenHLL with database 'std' is performing 10% worse

than KrakenHLL with database 'nt'), only Blast has higher average scores than KrakenHLL with

k-mer count thresholds on the original database. On the simulated datasets, KrakenHLL with the

'nt' database still ranks at the top, though, as seen previously there is more variation (Suppl.

Table 4). Notably CLARK is as good as KrakenHLL, but Blast has much worse scores on the

simulated datasets.

	Genus		Species		
	F1	Recall	F1	Recall	Avg
KrakenHLL nt kmers	**0.99**	**0.99**	**0.99**	**0.98**	**0.99**
KrakenHLL nt reads	0.96	0.91	0.97	0.95	0.95
BlastMeganFilteredLiberal	0.97	0.94	0.97	0.89	0.94
BlastMeganFiltered	0.97	0.93	0.96	0.87	0.93
KrakenHLL orig kmers	0.96	0.93	0.94	0.87	0.93
ClarkM4Spaced	0.95	0.90	0.94	0.88	0.92
KrakenHLL orig reads	0.95	0.90	0.94	0.85	0.91
Kraken	0.95	0.90	0.94	0.84	0.91
KrakenHLL std kmers	0.97	0.94	0.92	0.78	0.90
DiamondMegan_sensitive	0.98	0.93	0.92	0.74	0.89
KrakenFiltered	0.95	0.91	0.90	0.75	0.88
ClarkM1Default	0.94	0.85	0.91	0.77	0.87
KrakenHLL std reads	0.95	0.89	0.90	0.70	0.86
LMAT	0.97	0.93	0.91	0.60	0.85
DiamondMegan	0.94	0.87	0.91	0.66	0.85
Gottcha	0.91	0.84	0.87	0.67	0.82
NBC	0.87	0.76	0.85	0.73	0.80
Metaphlan	0.94	0.89	0.83	0.55	0.80
MetaFlow	0.66	0.53	0.65	0.51	0.59
PhyloSift	0.68	0.29	0.78	0.54	0.57
PhyloSift90pct	0.68	0.30	0.77	0.52	0.57

198   Table 2: Performance of KrakenHLL (with unique k-mer count thresholds) compared to

199   metagenomic classifiers [15] on the biological datasets (n=10). F1 and Recall show the average

200   values over the datasets. Note that 'KrakenHLL reads' would be equivalent to standard Kraken.

202   **Generating a better test dataset, and selecting an appropriate k-mer threshold**

203   In the previous section we demonstrated that KrakenHLL gives better recall and F1-scores than

204   other classifiers on the test datasets, given the correct thresholds. How can the correct thresholds

205   be determined on real data with varying sequencing depths and complex communities? The test

206   datasets are not ideal for that: The biological datasets lack complexity with a maximum of 25

207   species in some of the samples, while the simulated samples lack the features of biological

208   datasets.

209

210   We thus generated a third type of test dataset by sampling reads from real bacterial isolate

211   sequencing runs, of which there are tens of thousands in the Sequence Read Archive (SRA). That

212   way we created a complex test dataset for which we know the ground truth, with all the features

213   of real sequencing experiments, including lab contaminants and sequencing errors. We selected

214   280 SRA datasets from 280 different bacterial species that are linked to complete RefSeq

215   genomes (see Suppl. Methods Section 2.4). We randomly sampled between one hundred and one

216   million reads (logarithmically distributed) from each experiment, which gave 34 million read

217   pairs in total. Furthermore, we sub-sampled five read sets with between one to twenty million

218   reads. All read sets were classified with KrakenHLL using the 'std' database.

219

220   [FIGURE 3]

221   Figure 3: Unique k-mer count separates true and false positives better than read counts in a

222   complex dataset with ten million reads sampled from SRA experiments. Each dot represents a

223   species, with true species in orange and false species in black. The dashed and dotted lines show

224   the k-mer thresholds for the ideal F1 score and recall at a maximum of 5% FDR, respectively. In

this dataset, a unique k-mer count in the range 10000–20000 would give the best threshold for

selecting true species.

Consistent with the results of the previous section, we found that unique k-mer counts provide

better thresholds than read counts both in terms of F1 score and recall in all test datasets (e.g.

Figure 3 on ten million reads – species recall using k-mers is 0.85, recall using reads 0.76). With

higher sequencing depth, the recall increased slightly - from 0.80 to 0.85 on the species level,

and from 0.87 to 0.89 on the genus level. The ideal values of the unique k-mer count thresholds,

however, vary widely with different sequencing depths. We found that the ideal thresholds

increase by about 2000 unique k-mers per one million reads (see Figure 4). McIntyre et al. [15]

found that k-mer based methods show a positive relationship between sequencing depths and

misclassified reads. Our analysis also shows that with deeper sequencing depths higher

thresholds are required to control the false-positive rate.

239   [FIGURE 4]

No. of reads	Fraction	Genus		Species	
		Threshold	Recall	Threshold	Recall
1 million	0.03	2555	0.87	3682	0.80
2 million	0.06	4483	0.86	6152	0.81
5 million	0.15	12723	0.87	10459	0.85
10 million	0.3	21896	0.88	21201	0.85
20 million	0.6	43417	0.88	43417	0.84
34.3 million	1	69847	0.89	688842	0.85

Figure 4: Deeper sequencing depths require higher unique k-mer count thresholds to control

false-positive rate and achieve the best recall. A minimum threshold of about 2000 unique k-mer

per a million reads gives the best results in this dataset (solid line in plot).

In general, we find that for correctly identified species, we obtain up to approximately L-k

unique k-mers per each read, where L is the read length, because each read samples a different

location in the genome. (Note that once the genome is completely covered, no more unique k-

mers can be detected.) Thus the k-mer threshold should always be several times higher than the

read count threshold. For the discovery of pathogens in human patients, discussed in the next

section, a read count threshold of 10 and unique k-mer count threshold of 1000 eliminated many

background identifications while preserving all true positives, which were discovered from as

few as 15 reads.

Results on biological samples for infectious disease diagnosis

Metagenomics is increasingly used to find species of low abundance. A special case is the

emerging use of metagenomics for the diagnosis of infectious diseases [27, 28]. In this

application, infected human tissues are sequenced directly to find the likely disease organism.

Usually, the vast majority of the reads match (typically 95-99%) the host, and sometimes fewer

than 100 reads out of many millions of reads are matched to the target species. Common skin

bacteria from the patient or lab personnel and other contamination from sample collection or

preparation can easily generate a similar number of reads, and thus mask the signal from the

pathogen.

To assess if the unique k-mer count metric in KrakenHLL could be used to rank and identify

pathogen from human samples, we reanalyzed ten patient samples from a previously described

series of neurological infections [4]. That study sequenced spinal cord mass and brain biopsies

from ten hospitalized patients for whom routine tests for pathogens were inconclusive. In four of

the ten cases, a likely diagnosis could be made with the help of metagenomics. To confirm the

metagenomics classifications, the authors in the original study re-aligned all pathogen reads to

individual genomes.

Table 3 shows the results of our reanalysis of the confirmed pathogens in the four patients,

including the number of reads and unique k-mers from the pathogen, as well as the number of

bases covered by re-alignment to the genomes. Even though the read numbers are very low in

two cases, the number of unique k-mers suggests that each read matches a different location in

the genome. For example, in PT8, 15 reads contain 1570 unique k-mers, and re-alignment shows

2201 covered base pairs. In contrast, Table 4 shows examples of identifications from the same

datasets that are not well-supported by k-mer counts. We also examined the likely source of the

false positive identifications by blasting the reads against the full nt database, and found rRNA of

environmental bacteria, human RNA and PhiX-174 mis-assignments (see Suppl. Methods for

details). Notably, the common laboratory and skin contaminants PhiX-174, *Escherichia coli*,

Cutibacterium acnes and *Delftia* were detected in most of the samples, too (see Suppl. Table 6).

However, those identifications are solid in terms of their k-mer counts - the bacteria and PhiX-

174 are present in the sample, and the reads cover their genomes rather randomly. To discount

them, comparisons against a negative control or between multiple samples is required (e.g. with

Pavian [29]).

Table 3: Validated pathogen identifications in patients with neurological infections have high

numbers of unique k-mers per read. The pathogens were identified with as few as 15 reads, but

the high number of unique k-mers indicates distinct locations of the reads along their genomes.

Re-alignment of mapped reads to their reference genomes (column "Covered Bases")

corroborates the finding of the unique k-mers (see also Suppl. Figure 5). Interestingly, the k-mer

count in PT5 indicates that there might be multiple strains present in the sample since the k-mers

cover more than one genome. Read lengths were 150-250 bp.

295
296

Sample	Matched microorganism	Reads	K-mers	Covered Bases
PT5	Human polyomavirus 2	9,650	7,129	5,130 / 5,130
PT7	*Elizabethkingia genomosp. 3*	403	20,724	53,256 / 4,433,522
PT8	*Mycobacterium tuberculosis*	15	1,570	2,227 / 4,411,532
PT10	Human gammaherpesvirus 4	20	2,084	2,822 / 172,764

298   Table 4: False positive identifications have few unique k-mers. Using an extended taxonomy, the

299   identifications in PT4 and PT10 were matched to single accessions (instead of to the species

300   level). The likely true source of the mapped sequences was determined by subsequent BLAST

301   searches and included 16S rRNA present in many uncultured bacteria, human small nucleolar

302   RNAs (snRNAs), and phiX174.

Sample	Matched microorganism	Reads	K-mers	Source
PT3	*Clostridioides difficile*	122	126	16S rRNA
PT4	Hepatitis C virus JF343788.1 Recombinant Hepatitis C virus	101	3	Human snRNA
PT5	*Akkermansia muciniphila*	936	136	16S rRNA
PT10	Human betaherpesvirus 5 JN379815.1 Human herpesvirus 5 strain U04, partial genome	63	5	phiX174

Further extensions in KrakenHLL

KrakenHLL adds three further notable features to the classification engine.

1. Enabling strain identification by extending the taxonomy: The finest level of granularity for Kraken classifications are nodes in the NCBI taxonomy. This means that many strains cannot be resolved, because up to hundreds of strains share the same taxonomy ID. KrakenHLL allows extending the taxonomy with virtual nodes for genomes, chromosomes and plasmids, and thus enabling identifications at the most specific levels (see Suppl. Methods Section 3)

2. Integrating 100,000 viral strain sequences: RefSeq includes only one reference genome for most viral species, which means that a lot of the variation of viral strain is not covered in a standard RefSeq database. KrakenHLL sources viral strain sequences from the NCBI Viral Genome Resource that are validated as 'neighbors' of RefSeq viruses, which leads to up to 20% more read classifications (see Suppl. Methods Section 4).

3. Hierarchical classification with multiple databases. Researcher's may want to include additional sequence sets, such as draft genomes, in some searches. KrakenHLL allows to chain databases and match each k-mer hierarchically, stopping when it found a match. For example, to mitigate the problem of host contamination in draft genomes, a search may use the host genome as first database, then complete microbial genomes, then draft microbial genomes. More details are available in Suppl. Method Section 5.

Timing and memory requirements

The additional features of KrakenHLL come without a runtime penalty and very limited additional memory requirements. In fact, due to code improvements, KrakenHLL often runs

faster than Kraken, particularly when most of the reads come from one species. On the test

dataset, the mean classification speed in million base-pairs per minute increased slightly from

410 to 421 Mbp/m (see Suppl. Table 3). When factoring in the time needed to summarize

classification results by kraken-report, which is required for Kraken but part of the classification

binary of KrakenHLL, KrakenHLL is on average 50% faster. The memory requirements increase

on average by 0.5 GB from 39.5 GB to 40 GB.

On the pathogen Id patient data, where in most cases over 99% of the reads were either assigned

to human or synthetic reads, KrakenHLL was significantly faster than Kraken (Suppl. Table 5).

The classification speed increased from 467 to 733 Mbp/m. The average wall time was about

44% lower, and the average additional memory requirements were less than 1GB, going from

118.0 to 118.4 GB. All timing comparisons were made after preloading the database and running

with 10 parallel threads.

Discussion

In our comparison, KrakenHLL performed better in classifying metagenomics data than many

existing methods, including the alignment-based methods Blast [16], Diamond [30], and

MetaFlow [19]. Blast and Diamond results were post-processed by Megan [31], which assigns

reads to the lowest-common ancestor (LCA), but ignores coverages when computing the

resulting taxonomic profile. Thus, the taxonomic profile (with read counts as abundance

measures) is sensitive to over-representing false positives that have coverage spikes in parts of

the genome in the same way as non-alignment based methods. Coverage spikes may appear due

to wrongly matched common sequences (e.g. 16S rRNA), short amplified sequences floating in

the laboratory, and contamination in database sequences. MetaFlow, on the other hand,

implements coverage-sensitive mapping, which should give better abundance calls, but it did not

perform very well in our tests. Going from alignments to a good taxonomic profile is difficult

because coverage information cannot be as easily computed for the LCA taxon and summarized

for higher levels in the taxonomic tree. In comparison, reads and unique k-mer counts can be

assigned to the LCA taxa, and summed to higher levels. Notably, KrakenHLL's k-mer counting

is affected by GC biases in the sequencing data the same way as other read classifiers and

aligners [32], and may underreport GC-rich or GC-poor genomes.

360   Conclusions

KrakenHLL is a novel method that combines fast k-mer based classification with an efficient

algorithm for counting the number of unique k-mers found in each species in a metagenomics

dataset. When the reads from a species yield many unique k-mers, one can be more confident

that the taxon is truly present, while a low number of unique k-mers suggests a possible false

positive identification. We demonstrated that using unique k-mer counts provides improved

accuracy for species identification, and that k-mer counts can help greatly in identifying false

positives. In our comparisons with multiple other metagenomics classifiers on multiple

metagenomics datasets, we found that KrakenHLL consistently ranked at the top. The strategy of

counting unique k-mer matches allows KrakenHLL to detect that reads are spread across a

genome, without the need to align the reads. By using a probabilistic counting algorithm,

KrakenHLL is able to match the exceptionally fast classification time of the original Kraken

program with only a very small increase in memory. The result is that KrakenHLL gains many of

the advantages of alignment at a far lower computational cost.

Declarations

Availability of data and material

KrakenHLL 🐙 is implemented in C++ and Perl. Its source code is available at

https://github.com/fbreitwieser/krakenhll, licensed under GPL3. The version used in the

manuscript is permanently available under https://doi.org/10.5281/zenodo.1252385. Analysis

scripts for the results of this manuscript are available at

https://github.com/fbreitwieser/krakenhll-manuscript-code.

The datasets of McIntyre et al. are available at https://ftp-private.ncbi.nlm.nih.gov/nist-

immsa/IMMSA. The sequencing datasets of Salzberg et al. are available under the BioProject

accession PRJNA314149 (https://www.ncbi.nlm.nih.gov/bioproject/PRJNA314149). Note that

human reads have been filtered. The test datasets generated by sampling reads from bacterial

isolate SRA experiments are available at

ftp://ftp.ccb.jhu.edu/pub/software/krakenhll/SraSampledDatasets.

Funding

This work was supported in part by grants R01-GM083873 and R01-HG006677 from the

National Institutes of Health, and by grant number W911NF-14-1-0490 from the U. S. Army

Research Office.

Acknowledgements

Thanks to Jen Lu, Ales Varabyou, Thomas Mehoke, David Karig, Sharon Bewick and Peter

Thielen for valuable discussions on the general method and its applicability. Thanks to Alexa

McIntyre and Rachid Ounit for providing very quick answers, scripts and data to their

benchmarking paper. Thanks to Daniel Baker for suggestions on the HyperLogLog algorithm,

and to Jessica Atwell for proofreading the manuscript.

Authors' contributions

FPB conceived and implemented the method. FPB and SLS wrote the manuscript. All authors

read and approved the final manuscript.

Ethics approval and consent to participate

Not applicable.

Consent for publication

Not applicable.

Competing interests

The authors declare that they have no competing interests.

References

1.   Breitwieser FP, Lu J, Salzberg SL: **A review of methods and databases for**
metagenomic classification and assembly. *Brief Bioinform* 2017.
2.   Salter SJ, Cox MJ, Turek EM, Calus ST, Cookson WO, Moffatt MF, Turner P, Parkhill J,
Loman NJ, Walker AW: **Reagent and laboratory contamination can critically impact**
sequence-based microbiome analyses. *BMC Biol* 2014, **12:**87.
3.   Thoendel M, Jeraldo P, Greenwood-Quaintance KE, Yao J, Chia N, Hanssen AD, Abdel
MP, Patel R: **Impact of Contaminating DNA in Whole-Genome Amplification Kits**
Used for Metagenomic Shotgun Sequencing for Infection Diagnosis. *J Clin Microbiol*
2017, **55:**1789-1801.

4.   Salzberg SL, Breitwieser FP, Kumar A, Hao H, Burger P, Rodriguez FJ, Lim M,
Quinones-Hinojosa A, Gallia GL, Tornheim JA, et al: **Next-generation sequencing in**
neuropathologic diagnosis of infections of the nervous system. *Neurol Neuroimmunol*
Neuroinflamm 2016, **3:**e251.
5.   Brown JR, Bharucha T, Breuer J: **Encephalitis diagnosis using metagenomics:**
application of next generation sequencing for undiagnosed cases. *Journal of Infection*
2018.
6.   Mukherjee S, Huntemann M, Ivanova N, Kyrpides NC, Pati A: **Large-scale**
contamination of microbial isolate genomes by Illumina PhiX control. *Stand*
Genomic Sci 2015, **10:**18.
7.   Dadi TH, Renard BY, Wieler LH, Semmler T, Reinert K: **SLIMM: species level**
identification of microorganisms from metagenomes. *PeerJ* 2017, **5:**e3138.
8.   Quince C, Walker AW, Simpson JT, Loman NJ, Segata N: **Shotgun metagenomics,**
from sampling to analysis. *Nat Biotechnol* 2017, **35:**833-844.
9.   Wood DE, Salzberg SL: **Kraken: ultrafast metagenomic sequence classification using**
exact alignments. *Genome Biol* 2014, **15:**R46.
10.   Flajolet P, Fusy É, Gandouet O, Meunier F: **HyperLogLog: the analysis of a near-**
optimal cardinality estimation algorithm. In *AofA: Analysis of Algorithms*; *2007-06-*
17; Juan les Pins, France. Discrete Mathematics and Theoretical Computer Science;
2007: 137-156.
11.   Heule S, Nunkesser M, Hall A: **HyperLogLog in practice.** 2013**:**683.
12.   Ertl O: **New Cardinality Estimation Methods for HyperLogLog Sketches.**
arXiv:170607290 2017.
13.   Brister JR, Ako-adjei D, Bao Y, Blinkova O: **NCBI Viral Genomes Resource.** *Nucleic*
Acids Research 2015, **43:**D571-D577.
14.   Irber Junior LC, Brown CT: **Efficient cardinality estimation for k-mers in large DNA**
sequencing data sets. *bioRxiv* 2016.
15.   McIntyre ABR, Ounit R, Afshinnekoo E, Prill RJ, Hénaff E, Alexander N, Minot SS,
Danko D, Foox J, Ahsanuddin S, et al: **Comprehensive benchmarking and ensemble**
approaches for metagenomic classifiers. *Genome Biology* 2017, **18**.
16.   Altschul SF, Gish W, Miller W, Myers EW, Lipman DJ: **Basic local alignment search**
tool. *J Mol Biol* 1990, **215:**403-410.
17.   Huson DH, Auch AF, Qi J, Schuster SC: **MEGAN analysis of metagenomic data.**
Genome Res 2007, **17:**377-386.
18.   Buchfink B, Xie C, Huson DH: **Fast and sensitive protein alignment using**
DIAMOND. *Nat Methods* 2015, **12:**59-60.
19.   Sobih A, Tomescu AI, Mäkinen V: **MetaFlow: Metagenomic Profiling Based on**
Whole-Genome Coverage Analysis with Min-Cost Flows. In *Research in*
Computational Molecular Biology. 2016: 111-121: *Lecture Notes in Computer Science*].
20.   Ounit R, Wanamaker S, Close TJ, Lonardi S: **CLARK: fast and accurate classification**
of metagenomic and genomic sequences using discriminative k-mers. *BMC Genomics*
2015, **16:**236.
21.   Ounit R, Lonardi S: **Higher classification sensitivity of short metagenomic reads with**
CLARK-S. *Bioinformatics* 2016, **32:**3823-3825.

22.   Ames SK, Hysom DA, Gardner SN, Lloyd GS, Gokhale MB, Allen JE: **Scalable**
467   **metagenomic taxonomy classification using a reference genome database.**
468   *Bioinformatics* 2013, **29:**2253-2260.
469   23.   Rosen GL, Reichenberger ER, Rosenfeld AM: **NBC: the Naive Bayes Classification**
470   **tool webserver for taxonomic classification of metagenomic reads.** *Bioinformatics*
471   2010, **27:**127-129.
472   24.   Freitas Tracey Allen K, Li P-E, Scholz MB, Chain Patrick SG: **Accurate read-based**
473   **metagenome characterization using a hierarchical suite of unique signatures.**
474   *Nucleic Acids Research* 2015, **43:**e69-e69.
475   25.   Truong DT, Franzosa EA, Tickle TL, Scholz M, Weingart G, Pasolli E, Tett A,
476   Huttenhower C, Segata N: **MetaPhlAn2 for enhanced metagenomic taxonomic**
477   **profiling.** *Nat Methods* 2015, **12:**902-903.
478   26.   Darling AE, Jospin G, Lowe E, Matsen FAt, Bik HM, Eisen JA: **PhyloSift: phylogenetic**
479   **analysis of genomes and metagenomes.** *PeerJ* 2014, **2:**e243.
480   27.   Simner PJ, Miller S, Carroll KC: **Understanding the Promises and Hurdles of**
481   **Metagenomic Next-Generation Sequencing as a Diagnostic Tool for Infectious**
482   **Diseases.** *Clinical Infectious Diseases* 2017.
483   28.   Zhang C, Cleveland K, Schnoll-Sussman F, McClure B, Bigg M, Thakkar P, Schultz N,
484   Shah MA, Betel D: **Identification of low abundance microbiome in clinical samples**
485   **using whole genome sequencing.** *Genome Biology* 2015, **16**.
486   29.   Breitwieser FP, Salzberg SL: **Pavian: Interactive analysis of metagenomics data for**
487   **microbiomics and pathogen identification.** *BioRxiv* 2016.
488   30.   Buchfink B, Xie C, Huson DH: **Fast and sensitive protein alignment using**
489   **DIAMOND.** *Nature Methods* 2014, **12:**59-60.
490   31.   Huson DH, Auch AF, Qi J, Schuster SC: **MEGAN analysis of metagenomic data.**
491   *Genome Research* 2007, **17:**377-386.
492   32.   Xu Y, Chen Y-C, Liu T, Yu C-H, Chiang T-Y, Hwang C-C: **Effects of GC Bias in Next-**
493   **Generation-Sequencing Data on De Novo Genome Assembly.** *PLoS ONE* 2013, **8**.
494
495

A Read k-mers are looked-up in the database and assigned to taxa:

...TAGTACAGTAGAGCCTTCACCGGCATTCT...

K7 TAGTACAGTAGAGCCTTCACCGGCATT
K8 AGTACAGTAGAGCCTTCACCGGCATTC
K9 GTACAGTAGAGCCTTCACCGGCATTCT

Taxon[K7] = T1
Taxon[K8] = T1
Taxon[K9] = T2

B For each taxon a data sketch records its k-mers for cardinality estimation

h: kmer → $\{0,1\}^{p+q}$

01000101110000100101000111101011

p upper bits assign index i

Record number of leading zeros +1 in q lower bits as z

The maximum number of leading zeros are recorded in registers M

Estimated number of unique values for register $M[i]$: ~ $2^{M[i]}$

C K-mer count and coverage in taxonomic report show evidence behind classifications:

reads	kmers	dup	cov	taxID	rank	name
122	112	144	0.0004	11855	species	*Clostridioides difficile*
9650	7129	74.5	0.192	10632	species	Human polyomavirus 2
15	1570	1	0.0002	7643	species group	*Mycobacterium tb* complex

Bad classification with few k-mers

Good classification, reads cover genome

Number of distinct k-mers for taxon, and coverage of the taxon's k-mers