KrakenHLL: Confident and fast metagenomics classification using

unique k-mer counts

Breitwieser FP[1] and Salzberg SL[1,2]

1 Center for Computational Biology, McKusick-Nathans Institute of Genetic Medicine, Johns

Hopkins School of Medicine, Baltimore, MD, United States

2 Departments of Biomedical Engineering, Computer Science and Biostatistics, Johns Hopkins

University, Baltimore, MD, United States

Abstract

Motivation: False positive identifications are a significant problem in metagenomics. When

matching sequencing reads to a database of genomes, low-complexity regions and contaminants

in genome assemblies can attract many reads to the wrong genomes. Alignment information may

be used to recognize that many reads are piling up in a small number of locations, but fast k-mer

based metagenomic classifiers do not provide alignments, and re-alignment is expensive. We

propose using k-mer coverage, which can be computed during classification, as a proxy for

genome base coverage.

Results: We present KrakenHLL, a sequence classifier that records the number of unique k-mers

observed in each taxon in a metagenomics data set. KrakenHLL is based on the ultra-fast

classification engine Kraken, which it combines with a cardinality estimator known as

HyperLogLog (HLL). We demonstrate that many false-positive identifications can be identified

using unique k-mer counts, especially when looking at species present in low abundance.

KrakenHLL's database includes over 100,000 additional viral strain sequences not used in the

standard Kraken database, and it also has the ability to map against multiple databases and

identify plasmids and strains using an extended taxonomy. KrakenHLL's run time is similar to

that of Kraken, and it requires only a very modest increase in memory.

Availability and Implementation: KrakenHLL is implemented in C++ and Perl, and available

under the GPL v3 license at https://github.com/fbreitwieser/krakenhll.

Contact: florian.bw@gmail.com.

29 Introduction

Metagenomic classifiers attempt to assign a taxonomic identity to each read in a data set.

Because metagenomics data often contain tens of millions of reads, classification is typically

done using exact matching of short words of length k (k-mers) rather than alignment, which

would be unacceptably slow. The results contain read classifications but not their aligned

positions in the genomes (as reviewed by Breitwieser, et al., 2017). However, read counts can be

deceiving. Sequence contamination of the samples–introduced from laboratory kits or the

environment during sample extraction, handling or sequencing–can yield high numbers of

spurious identifications (Salter, et al., 2014; Thoendel, et al., 2017). Having only small amounts

of input material can further compound the problem of contamination. When using sequencing

for clinical diagnosis of infectious diseases, for example, less than 0.1% of the DNA may derive

from microbes of interest (Brown, et al., 2018; Salzberg, et al., 2016). Additional spurious

matches can result from low-complexity regions of genomes and from contamination in the

database genomes themselves (Mukherjee, et al., 2015).

Such false-positive reads typically match only small portions of a genome; e.g., if a species'

genome contains a low-complexity region, and the only reads matching that species fall in this

region, then the species was probably not present in the sample. Reads from microbes that are

truly present should distribute relatively uniformly across the genome rather than being

concentrated in one or a few locations. Genome alignment can reveal this information. However,

alignment is resource intensive, requiring the construction of indexes for every genome and a

relatively slow alignment step to compare all reads against those indexes. Some metagenomics

methods do use coverage information to improve mapping or quantification accuracy, but these

methods require results from much slower alignment methods as input (Dadi, et al., 2017).

Assembly-based methods also help to avoid false positives, but these are useful only for highly

abundant species (Quince, et al., 2017).

Here, we present KrakenHLL, a novel method that combines very fast k-mer based classification

with a fast k-mer cardinality estimation. KrakenHLL is based on the Kraken metagenomics

classifier (Wood and Salzberg, 2014), to which it adds a method for counting the number of

unique k-mers identified for each taxon using the efficient cardinality estimation algorithm

HyperLogLog (Ertl, 2017; Flajolet, et al., 2007; Heule, et al., 2013). By counting how many of

each genome's unique k-mers are covered by reads, KrakenHLL can often discern false positive

from true positive matches. Furthermore, KrakenHLL implements additional new features to

improve metagenomics classification: (a) searches can be done against multiple databases

hierarchically, (b) the taxonomy can be extended to include nodes for strains and plasmids, thus

enabling their detection, and (c) the database build script allows the addition of >100,000 viruses

from the NCBI Viral Genome Resource (Brister, et al., 2015). KrakenHLL provides a superset of

the information provided by Kraken while running equally fast or slightly faster, and while using

very little additional memory during classification.

69 Results

KrakenHLL was developed to provide efficient k-mer count information for all taxa identified in

a metagenomics experiment. The main workflow is as follows: As reads are processed, each k-

mer is assigned a taxon from the database (Figure 1A). KrakenHLL instantiates a HyperLogLog

data sketch for each taxon, and adds the k-mers to it (Figure 1B and Supplementary

Information). After classification of a read, KrakenHLL traverses up the taxonomic tree and

merges the estimators of each taxon with its parent. In its classification report, KrakenHLL

includes the number of unique k-mers and the depth of k-mer coverage for each taxon that it

observed in the input data (Figure 1C).

Figure 1. Overview of the KrakenHLL algorithm and output. (A) An input read is shown as a

long gray rectangle, with k-mers shown as shorter rectangles below it. The taxon mappings for

each k-mer are compared to the database, shown as larger rectangles on the right. For each taxon,

a unique k-mer counter is instantiated, and the observed k-mers (K7, K8, and K9) are added to

the counters. (B) Unique k-mer counting is implemented with the probabilistic estimation

method HyperLogLog (HLL) using 16KB of memory per counter, which limits the error in the

cardinality estimate to 1% (see main text). (C) The output includes the number of reads, unique

k-mers, duplicity (average time each k-mer has been seen) and coverage for each taxon observed

in the input data.

89
90
Efficient k-mer cardinality estimation using the HyperLogLog algorithm

Exact counting of the number of unique values (cardinality) of a string (for example, the number

of instances of each word in a document) in the presence of duplicates requires memory

proportional to the cardinality. Very accurate *estimation* of the cardinality, however, can be

achieved using only a small, constant amount of space. The HyperLogLog algorithm (HLL),

originally described by (Flajolet, et al., 2007), is currently one of the most efficient cardinality

estimators and has recently been used to count k-mers in DNA sequences (Irber Junior and

Brown, 2016). The main idea behind the method is that long runs of leading zeros are unlikely in

random bitstrings. E.g., in a series of random bitstrings (or hashes) we expect to see every fourth

bitstring start with exactly one 0-bit before the first 1-bit (01_2), and every 32nd hash starts with

00001_2. The HLL algorithm saves a "sketch" of observed data based on hashes of the k-mers in

2^p one-byte registers (in our implementation), where p is the precision parameter. The relative

error of the estimate is $1/\text{sqrt}(2^p)$. With $p=14$, the sketch uses 2^{14} one-byte registers, i.e. 16 KB

of space, and has a relative error less than 1% (Figure 2).

Generating the sketch. Each k-mer is first hashed into a 64-bit string H. The sketch starts out in a

sparse representation which has an effective p of 25, using 4 bytes per element. See (Heule, et

al., 2013) for more details on the encoding. Once $m/4$ distinct elements have been observed, we

switch to the standard representation of (Flajolet, et al., 2007): the first p bits of H are used as

index i into the registers M. The remaining $64\text{-}p\text{=}q$ bits are used to define the rank based on the

position of the first 1-bit (or, equivalently, the count of leading zeros plus one). If all q bits are

zero, the rank is $q\text{+}1$. The register $M[i]$ is updated if the rank is higher than the current value of

$M[i]$.

When the read classification is finished, KrakenHLL aggregates the taxon sketches up the

taxonomy tree. Each taxon's sketch is merged with its children's sketches. The cardinality

estimate is computed using a recently described method (Ertl, 2017) that does not require

empirically determined thresholds to account for biases and switching between linear counting

and the HLL estimator (Suppl. Figures 1 and 2). Figure 2 shows the performance and memory

usage of KrakenHLL's cardinality estimator for up to one million k-mers. A detailed description

of the algorithm and implementation is in the Supplementary Materials.

precision		p	m	Space (kB)	Rel. Error
10		10	1024	1	3.25%
11		11	2048	2	2.23%
12		12	4096	4	1.63%
13		13	8192	8	1.15%
14		14	16384	16	0.81%
15		15	32768	32	0.57%
16		16	65536	64	0.41%
17		17	131072	128	0.29%
18		18	262144	256	0.20%
		25			0.02%

Figure 2: Cardinality estimation using HyperLogLog for randomly sampled k-mers from

microbial genomes. Left: standard deviations of the relative errors of the estimate with precision

p ranging from 10 to 18. No systematic biases are apparent, and, as expected, the errors decrease

with higher values of p. Up to cardinalities of about $2^p/4$, the relative error is near zero. At higher

cardinalities, the error boundaries stay near constant. Right: the size of the registers, space

requirement, and expected relative error for HyperLogLog cardinality estimates with different

values of p. For example, with a precision $p=14$, the expected relative error is 0.81% and the

counter only requires 16 KB of space, which is three orders of magnitude less than that of an

exact counter (at a cardinality of one million). Up to cardinalities of $2^p/4$, KrakenHLL uses a

sparse representation of the counter with a higher precision of 25 and an effective relative error

rate of about 0.02%.

Results on twenty-one simulated and ten biological test datasets

We assessed KrakenHLL's performance on the 34 datasets compiled by (McIntyre, et al., 2017)

(see Suppl. Table 3). We place greater emphasis on the eleven biological datasets, which contain

more realistic laboratory and environmental contamination. In the first part of this section, we

show that unique k-mer counts provide classification accuracy than read counts, and in the

second part we compare KrakenHLL with the results of eleven metagenomics classifiers

described in (McIntyre, et al., 2017). We ran KrakenHLL on two databases: 'std', which includes

the human genome plus the complete bacterial, archaeal and viral genomes from RefSeq, and

'nt', which contains the microbial sequences in the BLAST nt sequence set (see Suppl. Methods

Section 2). We use two metrics to compare how well methods can separate true positives and

false positives: the maximum F1 score and maximum recall. Higher values of F1 (the harmonic

mean of precision and recall) indicate a better separation between true positives and false

positives. Higher recall (at the fixed false discovery rate of 0.05) means that more true species

can be recovered while controlling the false positives4.

Because the NCBI taxonomy has been updated since the datasets were published, we manually

updated the "truth" sets in several datasets (see Suppl. Methods Section 2.3 for all changes). Any

cases that might have been missed would result in a lower apparent performance of KrakenHLL.

Note that we exclude the over ten-year-old simulated datasets simHC, simMC and simLC from

Mavromatis et al. (2007), as well as the biological dataset JGI SRR033547 which has only 100

reads.

Data Type	Rank	Statistic	orig			std			nt		
			Reads	Kmers	Diff	Reads	Kmers	Diff	Reads	Kmers	Diff
Biological	Genus	Recall	0.90	0.93	**+4.0%**	0.89	0.94	**+6.2%**	0.91	0.99	**+8.9%**
Biological	Genus	F1	0.95	0.96	**+1.8%**	0.95	0.97	**+2.6%**	0.96	0.99	**+3.4%**
Biological	Species	Recall	0.85	0.87	**+2.6%**	0.70	0.78	**+11.8%**	0.95	0.98	**+3.1%**
Biological	Species	F1	0.94	0.94	**+0.7%**	0.90	0.92	**+2.5%**	0.97	0.99	**+1.6%**
Simulated	Genus	Recall	0.96	0.94	-2.1%	0.95	0.97	**+2.5%**	0.98	0.99	**+0.8%**
Simulated	Genus	F1	0.98	0.98	-0.0%	0.98	0.98	**+0.3%**	0.99	0.99	**+0.3%**
Simulated	Species	Recall	0.92	0.93	**+0.6%**	0.88	0.88	**+0.3%**	0.90	0.90	-0.1%
Simulated	Species	F1	0.97	0.97	**+0.3%**	0.94	0.94	**+0.5%**	0.96	0.96	-0.1%

Table 1: Performance of read count and unique k-mer thresholds on 10 biological and 21

simulated datasets against three databases ('orig', 'std', 'nt). Unique k-mer count thresholds give

up to 10% better recall and F1 scores on biological datasets.

Unique k-mer versus read count thresholds

We first looked at the performance of the unique k-mer count thresholds versus read count

thresholds (as would be used with Kraken). The k-mer count thresholds worked very well,

particularly for the biological datasets (Table 1 and Suppl. Table 3). On the genus level, the

average recall in the biological datasets increases by 4-9%, and the average F1 score increases 2-

3%. On the species level, the average increase in recall in the biological sets is between 3 and

12%, and the F1 score increases by 1-2%.

On the simulated datasets, the differences are less pronounced and vary between databases, even

though on average the unique k-mer count is again better. However, only in two cases (genus

recall on databases 'orig' and 'std') the difference is higher than 1% in any direction. We find

that simulated datasets often lack false positives with a decent number of reads but a lower

number of unique k-mer counts, which we see in real data. Instead, in most simulated datasets

the number of unique k-mers is linearly increasing with the number of unique reads in both true

and false positives (Suppl. Figure 4). In biological datasets, sequence contamination and lower

read counts for the true positives make the task of separating true and false positives harder.

Comparison of KrakenHLL with eleven other methods

Next, we compared KrakenHLL's unique k-mer counts with the results of eleven metagenomics

classifiers from (McIntyre, et al., 2017). KrakenHLL with database 'nt' has the highest average

recall and F1 score across the biological datasets, as shown in Table 2. As seen before, using

unique k-mer instead of read counts as thresholds increases the scores. While the database

selection proves to be very important (KrakenHLL with database 'std' is performing 10% worse

than KrakenHLL with database 'nt'), only Blast has higher average scores than KrakenHLL with

k-mer count thresholds on the original database. On the simulated datasets, KrakenHLL with the

'nt' database still ranks at the top, though, as seen previously there is more variation (Suppl.

Table 4). Notably CLARK is as good as KrakenHLL, but Blast has much worse scores on the

simulated datasets.

	Genus		Species		
	F1	Recall	F1	Recall	Avg
KrakenHLL nt kmers	**0.99**	**0.99**	**0.99**	**0.98**	**0.99**
KrakenHLL nt reads	0.96	0.91	0.97	0.95	0.95
BlastMeganFilteredLiberal	0.97	0.94	0.97	0.89	0.94
BlastMeganFiltered	0.97	0.93	0.96	0.87	0.93
KrakenHLL orig kmers	0.96	0.93	0.94	0.87	0.93
ClarkM4Spaced	0.95	0.90	0.94	0.88	0.92
KrakenHLL orig reads	0.95	0.90	0.94	0.85	0.91
Kraken	0.95	0.90	0.94	0.84	0.91
KrakenHLL std kmers	0.97	0.94	0.92	0.78	0.90
DiamondMegan_sensitive	0.98	0.93	0.92	0.74	0.89
KrakenFiltered	0.95	0.91	0.90	0.75	0.88
ClarkM1Default	0.94	0.85	0.91	0.77	0.87
KrakenHLL std reads	0.95	0.89	0.90	0.70	0.86
LMAT	0.97	0.93	0.91	0.60	0.85
DiamondMegan	0.94	0.87	0.91	0.66	0.85
Gottcha	0.91	0.84	0.87	0.67	0.82
NBC	0.87	0.76	0.85	0.73	0.80
Metaphlan	0.94	0.89	0.83	0.55	0.80
MetaFlow	0.66	0.53	0.65	0.51	0.59
PhyloSift	0.68	0.29	0.78	0.54	0.57
PhyloSift90pct	0.68	0.30	0.77	0.52	0.57

192 Table 2: Performance of KrakenHLL (with unique k-mer count thresholds) compared to

193 metagenomic classifiers used in (McIntyre, et al., 2017) on the biological datasets (n=10). F1 and

194 Recall show the average values over the datasets. Note that 'KrakenHLL reads' would be

195 equivalent to standard Kraken.

Generating a better test dataset, and selecting an appropriate k-mer threshold

We demonstrated that, given good thresholds, KrakenHLL performs better than other classifiers

on the test datasets. The test datasets, however, are not ideal for determining guidelines for

thresholds on real data. To establish thresholds, we'd like to use biological data, but the lab-

created microbial communities which are the basis of the datasets are usually of very low

complexity. For example, only two of the biological test datasets of the previous sections had

more than ten species. While some of the simulated test datasets have a much higher complexity,

they lack features of biological dataset.

We propose a third type of test dataset generated by mixing reads from isolate sequencing

experiments (of which there are tens of thousands). By subsampling the isolate experiments, we

can create an arbitrarily complex test dataset for which we know the ground truth. All reads are

from actual experiments, and we may contain contaminants and sequencing errors. We selected

280 SRA datasets from 280 different bacterial species that are linked to complete RefSeq

genomes (see Suppl. Methods Section 2.4). We randomly sampled between one hundred and one

million reads (logarithmically distributed) from each species, which gave 34 million read pairs in

total. To see the effect of sequencing depth, we created five sub-sampled read sets with one to

twenty million reads, too. All read sests were classified with KrakenHLL with the 'std' database.

Figure 3: Unique k-mer count separates true and false positives better than read counts in a

complex dataset with ten million reads sampled from SRA experiments. Each dot represents a

species, with true species in orange and false species in black. The dashed line shows the k-mer

threshold giving the best F1 score, and the dotted line shows the threshold for the best recall at a

maximum of 5% FDR. In this dataset, a unique k-mer count in the range 10000–20000 would

give the best threshold for selecting true species.

Consistent with the results of the results of the previous section, we found that unique k-mer

counts provide better thresholds than read counts both in terms of F1 score and recall in all test

datasets (e.g. Figure 3 on ten million reads – species recall using k-mers is 0.85, recall using

reads 0.76). With higher sequencing depth, the recall increased slightly - from 0.80 to 0.85 on the

species level, and from 0.87 to 0.89 on the genus level. The ideal values of the unique k-mer

count thresholds, however, vary widely with different sequencing depths. We found that the ideal

thresholds increase by about 2000 unique k-mers per one million reads (see Figure 4). (McIntyre,

et al., 2017) found that k-mer based methods show a positive relationship between sequencing

depths and misclassified reads. Our analysis suggest that the sequencing depth definitely should

be taken into into account. Note that Bracken may help reduce false positive identification of

similar species in the same genus, because it can redistribute reads from species at low counts to

species at higher abundance (Lu, et al., 2017).

No. of reads	Fraction	Genus Threshold	Recall	Species Threshold	Recall
1 million	0.03	2555	0.87	3682	0.80
2 million	0.06	4483	0.86	6152	0.81
5 million	0.15	12723	0.87	10459	0.85
10 million	0.3	21896	0.88	21201	0.85
20 million	0.6	43417	0.88	43417	0.84
34.3 million	1	69847	0.89	688842	0.85

Figure 4: Optimal thresholds vary with sequencing depth. A minimum threshold of about 2000

unique k-mer per a million reads gives the best results in this dataset (solid line in plot).

In general, we find that for correctly identified species, we obtain up to approximately $L\text{-}k$

unique k-mers per each read, where L is the read length, because each read samples a different

location in the genome. (Note that once the genome is completely covered, no more unique k-

mers can be detected.) Thus the k-mer threshold should always be several times higher than the

read count threshold. For the discovery of pathogens in human patients, discussed in the next

section, a read count threshold of 10 and unique k-mer count threshold of 1000 eliminated many

background identifications while preserving all true positives, which were discovered from as

few as 15 reads.

Results on biological samples for infectious disease diagnosis

Metagenomics is increasingly used to find species of low abundance. A special case is the

emerging use of metagenomics for the diagnosis of infectious diseases (Simner, et al., 2017;

Zhang, et al., 2015). In this application, infected human tissues are sequenced directly to find the

likely disease organism. Usually, the vast majority of the reads match (typically 95-99%) the

host, and sometimes fewer than 100 reads out of many millions of reads are matched to the target

species. Common skin bacteria from the patient or lab personnel and other contamination from

sample collection or preparation can easily generate a similar number of reads, and thus mask the

signal from the pathogen.

To assess if the unique k-mer count metric in KrakenHLL could be used to rank and identify

pathogen from human samples, we reanalyzed ten patient samples from a previously described

series of neurological infections (Salzberg, et al., 2016). That study sequenced spinal cord mass

and brain biopsies from ten hospitalized patients for whom routine tests for pathogens were

inconclusive. In four of the ten cases, a likely diagnosis could be made with the help of

metagenomics. To confirm the metagenomics classifications, the authors in the original study re-

aligned all pathogen reads to individual genomes.

Table 3 shows the results of our reanalysis of the confirmed pathogens in the four patients,

including the number of reads and unique k-mers from the pathogen, as well as the number of

bases covered by re-alignment to the genomes. Even though the read numbers are very low in

two cases, the number of unique k-mers suggests that each read matches a different location in

the genome. For example, in PT8, 15 reads contain 1570 unique k-mers, and re-alignment shows

2201 covered base pairs. In contrast, Table 4 shows examples of identifications from the same

datasets that are not well-supported by k-mer counts.

Table 3: Pathogen identifications in patients with neurological infections. The pathogens were

identified with as few as 15 reads, but those mapped to a high number of unique k-mers,

indicating distinct locations of the reads along their genomes. "Bases" refers to the number of

bases covered by the reads after re-alignment to a selected genome. Interestingly, the k-mer

count in PT5 reveals that there seems to be more than one viral strain present, as the k-mers

cover more than one genome. Read lengths were 150-250 bp.

Sample	Name	Reads	K-mers	Bases
PT5	Human polyomavirus 2	9650	7129*	5130
PT7	*Elizabethkingia genomosp. 3*	403	20724	52921
PT8	*Mycobacterium tuberculosis*	15	1570	2201
PT10	Human gammaherpesvirus 4	20	2084	2780

285 Table 4: False positive identifications have few unique k-mers per read. Note that the viral

286 identifications in PT4 and PT10 come from the NCBI Viral Genome Resource. Since the

287 KrakenHLL reports sequence-level matches, the source genomes are easy to find.

Sample	Name	Reads	K-mers
PT3	*Clostridioides difficile*	122	126
PT4	Hepatitis C virus JF343788.1 Recombinant Hepatitis C virus	101	3
PT5	*Akkermansia muciniphila*	936	136
PT10	Human betaherpesvirus 5 JN379815.1 Human herpesvirus 5 strain U04, partial genome	63	5

Further extensions in KrakenHLL

KrakenHLL adds three further notable features to the classification engine.

1. Enabling strain identification by extending the taxonomy: The finest level of granularity

for Kraken classifications are nodes in the NCBI taxonomy. This means that many strains

cannot be resolved, because up to hundreds of strains share the same taxonomy ID.

KrakenHLL allows extending the taxonomy with virtual nodes for genomes,

chromosomes and plasmids, and thus enabling identifications at the most specific levels

(see Suppl. Methods Section 3)

2. Integrating 100,000 viral strain sequences: RefSeq includes only one reference genome

for most viral species, which means that a lot of the variation of viral strain is not covered

in a standard RefSeq database. KrakenHLL sources viral strain sequences from the NCBI

Viral Genome Resource that are validated as 'neighbors' of RefSeq viruses, which leads

to up to 20% more read classifications (see Suppl. Methods Section 4).

3. Hierarchical classification with multiple databases. Often, we would like to include

additional sequence sets in some searches - for example draft genomes that may contain

contamination. KrakenHLL allows to chain databases in classification and matches each

k-mer hierarchically, stopping after the first match. For example, to mitigate the problem

of host contamination in draft genomes, a search may use the host genome as first

database, then the complete microbial genomes, then draft microbial genomes. More

details are available in Suppl. Method Section 5.

Timing and memory requirements

The additional features of KrakenHLL come without a runtime penalty and very limited

additional memory requirements. In fact, due to code improvements, KrakenHLL often runs

faster than Kraken, particularly when most of the reads come from one species. On the test

dataset, the mean classification speed in million base-pairs per minute increased slightly from

410 to 421 Mbp/m (see Suppl. Table 3). When factoring in the time needed to summarize

classification results by kraken-report, which is required for Kraken but part of the classification

binary of KrakenHLL, KrakenHLL is on average 50% faster. The memory requirements increase

on average by 0.5 GB from 39.5 GB to 40 GB.

On the pathogen Id patient data, where in most cases over 99% of the reads were either assigned

to human or synthetic reads, KrakenHLL was significantly faster than Kraken (Suppl. Table 5).

The classification speed increased from 467 to 733 Mbp/m. The average wall time was about

44% lower, and the average additional memory requirements were less than 1GB, going from

118.0 to 118.4 GB. All timing comparisons were made after preloading the database and running

with 10 parallel threads.

328   Conclusions

KrakenHLL is a novel method that combines fast k-mer based classification with an efficient

algorithm for counting the number of unique k-mers found in each species in a metagenomics

dataset. When the reads from a species yield many unique k-mers, one can be more confident

that the taxon is truly present, while a low number of unique k-mers suggests a possible false

positive identification. We demonstrated that using unique k-mer counts provides improved

accuracy for species identification, and that k-mer counts can help greatly in identifying false

positives. In our comparisons with multiple other metagenomics classifiers on multiple

metagenomics datasets, we found that KrakenHLL consistently ranked at the top. The strategy of

counting unique k-mer matches allows KrakenHLL to detect that reads are spread across a

genome, without the need to align the reads. By using a probabilistic counting algorithm,

KrakenHLL is able to match the exceptionally fast classification time of the original Kraken

program with only a very small increase in memory. The result is that KrakenHLL gains many of

the advantages of alignment at a far lower computational cost.

Acknowledgements

Thanks to Jen Lu, Ales Varabyou, David Karig, Susan Bewick, Peter Thielen, and Thomas

Mehoke for valuable discussions. Thanks to Daniel Baker for discussions and suggestions on

improvements regarding the HyperLogLog algorithm, and to Jessica Atwell for proofreading the

manuscript. We further would like to thank Alexa McIntyre and Rachid Ounit for providing the

scripts for their benchmarking paper, very quick answers to all my questions, and providing the

Kraken database used in the analysis.

Funding

352 This work was supported in part by grants R01-GM083873 and R01-HG006677 from the

353 National Institutes of Health, and by grant number W911NF-14-1-0490 from the U. S. Army

354 Research Office.

References

Breitwieser, F.P., Lu, J. and Salzberg, S.L. A review of methods and databases for metagenomic
classification and assembly. *Brief Bioinform* 2017.
Brister, J.R.*, et al.* NCBI Viral Genomes Resource. *Nucleic Acids Research* 2015;43(D1):D571-
D577.
Brown, J.R., Bharucha, T. and Breuer, J. Encephalitis diagnosis using metagenomics: application
of next generation sequencing for undiagnosed cases. *Journal of Infection* 2018.
Dadi, T.H.*, et al.* SLIMM: species level identification of microorganisms from metagenomes.
PeerJ 2017;5:e3138.
Ertl, O. New Cardinality Estimation Methods for HyperLogLog Sketches. *arXiv:1706.07290*
2017.
Flajolet, P.*, et al.* HyperLogLog: the analysis of a near-optimal cardinality estimation algorithm.
In, *AofA: Analysis of Algorithms*. Juan les Pins, France: Discrete Mathematics and Theoretical
Computer Science; 2007. p. 137-156.
Heule, S., Nunkesser, M. and Hall, A. HyperLogLog in practice. 2013:683.
Irber Junior, L.C. and Brown, C.T. Efficient cardinality estimation for k-mers in large DNA
sequencing data sets. *bioRxiv* 2016.
Lu, J.*, et al.* Bracken: estimating species abundance in metagenomics data. *PeerJ Computer*
Science 2017;3.
McIntyre, A.B.R.*, et al.* Comprehensive benchmarking and ensemble approaches for
metagenomic classifiers. *Genome biology* 2017;18(1).
Mukherjee, S.*, et al.* Large-scale contamination of microbial isolate genomes by Illumina PhiX
control. *Stand Genomic Sci* 2015;10:18.
Quince, C.*, et al.* Shotgun metagenomics, from sampling to analysis. *Nat Biotechnol*
2017;35(9):833-844.
Salter, S.J.*, et al.* Reagent and laboratory contamination can critically impact sequence-based
microbiome analyses. *BMC Biol.* 2014;12:87.

Salzberg, S.L.*, et al.* Next-generation sequencing in neuropathologic diagnosis of infections of
the nervous system. *Neurology(R) neuroimmunology & neuroinflammation* 2016;3(4):e251.
Simner, P.J., Miller, S. and Carroll, K.C. Understanding the Promises and Hurdles of
Metagenomic Next-Generation Sequencing as a Diagnostic Tool for Infectious Diseases.
Clinical Infectious Diseases 2017.
Thoendel, M.*, et al.* Impact of Contaminating DNA in Whole-Genome Amplification Kits Used
for Metagenomic Shotgun Sequencing for Infection Diagnosis. *J Clin Microbiol*
2017;55(6):1789-1801.
Wood, D.E. and Salzberg, S.L. Kraken: ultrafast metagenomic sequence classification using
exact alignments. *Genome Biol* 2014;15(3):R46.
Zhang, C.*, et al.* Identification of low abundance microbiome in clinical samples using whole
genome sequencing. *Genome biology* 2015;16(1).
395