babette: BEAUti 2, BEAST2 and Tracer for R

Richèl J.C. Bilderbeek[1] and Rampal S. Etienne[1]

[1]Groningen Institute for Evolutionary Life Sciences, University of
Groningen, Groningen, The Netherlands

May 7, 2018

Summary

1. In the field of phylogenetics, BEAST2 is one of the most widely
used software tools. It comes with the graphical user interfaces BEAUti
2, DensiTree and Tracer, to create BEAST2 configuration files and to in-
terpret BEAST2's output files. However, when many different alignments
or model setups are required, a workflow of graphical user interfaces is
cumbersome.

2. Here, we present a free, libre and open-source package, `babette`:
'BEAUti 2, BEAST2 and Tracer for R', for the R programming language.
`babette` creates BEAST2 input files, runs BEAST2 and parses its results,
all from an R function call.

3. We describe `babette`'s usage and the novel functionality it provides
compared to the original tools and we give some examples.

4. As `babette` is designed to be of high quality and extendable, we
conclude by describing the further development of the package.

Keywords: computational biology, evolution, phylogenetics, BEAST2, R

1 Introduction

Phylogenies are commonly used to explore evolutionary hypotheses. Not only can phylogenies show us how species (or other evolutionary units) are related to each other, but we can also estimate relevant parameters such as extinction and speciation rates from them. There are many phylogenetics tools available to obtain an estimate of the phylogeny of a given set of species. BEAST2 (Bouckaert *et al.* 2014) is one of the most widely used ones. It uses a Bayesian statistical framework to estimate the joint posterior distribution of phylogenies and model parameters, from one or more DNA, RNA or amino acid alignments (see figure 1 for an overview of the workflow).

BEAST2 has a graphical and a command-line interface, that both need a configuration file containing alignments and model parameters. BEAST2 is bundled with BEAUti 2 (Drummond *et al.* 2012) ('BEAUti' from now on), a desktop application to create a BEAST2 configuration file. BEAUti has a user-friendly graphical user interface, with helpful default settings. As such, BEAUti is an attractive alternative to manual and error-prone editing of BEAST2 configuration files.

However, BEAUti cannot be called from a command-line script. This implies that when the user wants to explore the consequences of various settings, this must be done manually. This is the managable workflow when using a few alignments and doing a superficial analysis of sensitivity of the reconstructed tree to model settings. For exploring many trees (for instance from simulations) and for more thorough sensitivity analysis, one would like to loop through multiple (simulated) alignments, nucleotide substitution models, clock models and tree priors. One such tool to replace BEAUti is BEASTmasteR (Matzke 2015), which focuses on morphological traits and tip-dating, but also supports DNA data. BEASTmasteR, however, requires hundreds of lines of R code to setup the

BEAST2 model configuration and a Microsoft Excel file to specify alignment files.

BEAST2 is also associated with Tracer (Rambaut & Drummond 2007) and DensiTree (Bouckaert & Heled 2014). Both are desktop applications to analyze the output of BEAST2, each with a user-friendly graphical user interface. Tracer's purpose is to analyze the parameter estimates generated from a BEAST2 run. It shows, among others, the effective sample size (ESS) and time series ('the trace', hence the name) of each variable in the MCMC run. Both ESS and trace are needed to assess the strength of the inference. DensiTree visualizes the phylogenies of a BEAST2 posterior, with many options to improve the simultaneous display of many phylogenies.

However, for exploring the output of many BEAST2 runs, one would like a script to collect all parameters' ESSes, parameter traces and posterior phylogenies. There is no single package that offers a complete solution, but examples of R packages that offer a partial solution are rBEAST (Ratmann 2015) and RBeast (Faria & Suchard 2015). RBeast provides some plotting options and parsing of BEAST2 output files, but the plotting functions are too specific for general use. rBEAST was developed to test a particular biological hypothesis (Ratmann *et al.* 2016), and hence was not designed for general use.

Here, we present `babette`: BEAUti 2, BEAST2 and Tracer for R, which creates BEAST2 (v.2.4.7) configuration files, runs BEAST2, and analyzes its results, all from an R function call. This will save time, tedious mouse clicking and reduces the chances of errors in such repetitive actions. The interface of `babette` mimics the tools it is based on. This familiarity helps both beginner and experienced BEAST2 users to make the step from those tools to `babette`. `babette` enables the creation of a single-script pipeline from sequence alignments to posterior analysis in R.

2 Description

babette is written in the R programming language (R Core Team 2013) and enables the full BEAST2 workflow from a single R function call, in a similar way to what subsequent usage of BEAUti, DensiTree and Tracer would produce. babette's main function is bbt_run, which configures BEAST2, runs it and parses its output. bbt_run needs at least the name of a FASTA file containing a DNA alignment. The default settings for the other arguments of bbt_run are identical to BEAUti's and BEAST2's default settings. Per alignment, a site model, clock model and tree prior can be chosen. Multiple alignments can be used, each with its own (unlinked) site model, clock model and tree prior.

babette currently has 108 exported functions to set up a BEAST2 configuration file. babette can currently handle the majority of BEAUti use cases. Because of BEAUti's high number of plugins, babette uses a software architecture that is designed to be extended. Furthermore, babette has 13 exported functions to run and help run BEAST2. One function is used to run BEAST2, another one installs BEAST2 to a default location. Finally, babette has 21 exported function to parse the BEAST2 output files and analyze the created posterior. babette gives the same ESSes and summary statistics as Tracer. The data is formatted such that it can easily be visualized using ggplot2 (for a trace, similar to Tracer) or phangorn (Schliep 2011) (for the phylogenies in a posterior, similar to DensiTree).

Currently, babette does not contain all functionality in BEAUti, BEAST2 and their many plug-ins, because these tools themselves also change in time. babette currently works only on DNA data, because this is the most common use case. Nevertheless, babette provides the majority of default tree priors and supports the most important command-line arguments of BEAST2, provides the core Tracer analysis options, and has the most basic subset of plotting options of

DensiTree. Up till now, the `babette` features implemented are those requested

by users. Further extension of `babette` will be based on future user requests.

3   Usage

`babette` can be installed easily from CRAN:

```
install.packages("babette")
```

For the most up-to-date version, one can download and install the package from

`babette`'s GitHub repository:

```
devtools::install_github("richelbilderbeek/babette")
```

To start using `babette`, load its functions in the global namespace first:

```
library(babette)
```

Because babette calls BEAST2, BEAST2 must be installed. This can be done

from R, using:

```
install_beast2()
```

This will install BEAST2 to the default user data folder, but a different path

can be specified as well. BEAUti, and likewise `babette`, needs at least a FASTA

filename to produce a BEAST2 configuration file. In BEAUti, this is achieved

by loading a FASTA file, then saving an output file using a common save file

dialog. After this, BEAST2 needs to be applied to the created configuration

file. It creates multiple files storing the posterior. These output files must be

parsed by either Tracer or DensiTree. In `babette`, all this is achieved by:

```
out <- bbt_run(fasta_filenames = "anthus_aco.fas")
```

This code will create a (temporary) BEAST2 configuration file, from the FASTA

file with name `anthus_aco.fas` (which is supplied with the package, from

(Van Els & Norambuena 2018)), using the same default settings as BEAUti,

which are, among others, a Jukes-Cantor site model, a strict clock, and a Yule

birth tree prior. `babette` will then execute BEAST2 using that file, and parses

the output. The returned data structure, named `out`, is a list of parameter

estimates (called `estimates`), posterior phylogenies (called `anthus_aco_trees`,

named after the alignment's name) and MCMC operator performance (`operators`).

An example of using a different site model, clock model and tree prior is:

```
out <- bbt_run(
  fasta_filenames = "anthus_aco.fas",
  site_models = create_hky_site_model(),
  clock_models = create_rln_clock_model(),
  tree_priors = create_bd_tree_prior()
)
```

This code uses an HKY site model, a relaxed log-normal clock model and a birth-

death tree prior, each with their default settings in BEAUti. Table 1 shows an

overview of all functions to create site models, clock models and tree priors. Note

that the arguments' names `site_models`, `clock_models` and `tree_priors` are

plural, as each of these can be (a list of) one or more elements. Each of these

arguments must have the same number of elements, so that each alignment has

its own site model, clock model and tree prior. An example of two alignments,

each with its own site model, is:

```
out <- bbt_run(
  fasta_filenames = c(
    "anthus_aco.fas",
    "anthus_nd2.fas"
  ),
  site_models = list(
    create_tn93_site_model(),
    create_gtr_site_model()
```

```
156      )
157    )
```

babette also uses the same default prior distributions as BEAUti for each of
the site models, clock models and tree priors. For example, by default, a Yule
tree prior assumes that the birth rate follows a uniform distribution, from minus
infinity to plus infinity. One may prefer a different ddistribution instead. Here
is an example how to specify an exponential distribution for the birth rate in a
Yule tree prior in babette:

```
164    out <- bbt_run(
165      fasta_filenames = "anthus_aco.fas",
166      tree_priors = create_yule_tree_prior(
167        birth_rate_distr = create_exp_distr()
168      )
169    )
```

In this same example, one may specify the initial shape parameters of the expo-
nential distribution. In BEAST2's implementation, an exponential distribution
has one shape parameter: its mean, which can be set to any value with BEAUti.
To set the mean value of the exponential distribution to a fixed (non-estimated)
value, do:

```
175    out <- bbt_run(
176      fasta_filenames = "anthus_aco.fas",
177      tree_priors = create_yule_tree_prior(
178        birth_rate_distr = create_exp_distr(
179          mean = create_mean_param(
180            value = 1.0,
181            estimate = FALSE
182          )
183        )
```

```
184     )

185   )
```

babette also supports node dating. Like BEAUti, one can specify Most Recent Common Ancestor ('MRCA') priors. An MRCA prior allows to specify taxa having a common ancestor, including a distribution for the date of that ancestor. With babette, this is achieved as follows:

```
190  out <- bbt_run(
191    fasta_filenames = "anthus_aco.fas",
192    mrca_priors = create_mrca_prior(
193      taxa_names = sample(get_taxa_names("anthus_aco.fas"),
194          size = 2),
195      alignment_id = get_alignment_id("anthus_aco.fas"),
196      is_monophyletic = TRUE,
197      mrca_distr = create_normal_distr(
198        mean = create_mean_param(value = 15.0, estimate =
199            FALSE),
200        sigma = create_sigma_param(value = 0.025, estimate =
201            FALSE)
202      )
203    )
204  )
```

Instead of dating the ancestor of two random taxa, any subset of taxa can be selected, and multiple sets are allowed. babette allows for the same core functionality as Tracer to show the values of the parameter estimates sampled in the BEAST2 run. This is called the "trace" (hence the name). The start of the trace, called the "burn-in", is usually discarded, as an MCMC algorithm (such as used by BEAST2) first has to converge to its equilibrium and hence the parameter estimates are not representative. By default, Tracer discards the

first 10% of all the parameter estimates. To remove a 20% burn-in from all parameter estimates in `babette`, the following code can be used:

```
traces <- remove_burn_ins(
  traces = out$estimates,
  burn_in_fraction = 0.2
)
```

Tracer shows the ESSes of each posterior's variables. These ESSes are important to determine the strength of the inference. As a rule of thumb, an ESS of 200 is acceptable for any parameter estimate. To calculate the effective sample sizes (of all estimated variables) in `babette`:

```
esses <- calc_esses(
  traces = traces,
  sample_interval = 1000
)
```

Tracer displays multiple summary statistics for each estimated variable: the mean and its standard error, standard deviation, variance, median, mode, geo-metric mean, 95% highest posterior density interval, auto-correlation time and effective sample size. It displays these statistics per variable. In `babette`, these summary statistics are collected for all estimated parameters at once:

```
sum_stats <- calc_summary_stats(
  traces = traces,
  sample_interval = 1000
)
```

`babette` allows for the same functionality as DensiTree. DensiTree displays the phylogenies in a posterior at the same time scale, drawn one over one another, allowing to see the uncertainty in topology and branch lengths. The posterior phylogenies are stored as `anthus_aco_trees` in the object `out`, and can be

plotted as follows:

```
plot_densitree(phylos = out$anthus_aco_trees)
```

Instead of running the full pipeline, `babette` also allows to only create a BEAST2 configuration file. To create a BEAST2 configuration file, with all settings to default, use:

```
create_beast2_input_file(
    input_filenames = babette::get_babette_path("anthus_aco.
        fas"),
    output_filename = "beast2.xml"
)
```

This file can then be loaded and edited by BEAUti, run by BEAST2, or run by `babette`:

```
run_beast2(
    input_filename = "beast2.xml",
    output_log_filename = "run.log",
    output_trees_filenames = "posterior.trees",
    output_state_filename = "final.xml.state"
)
```

`run_beast2` is a function that only runs BEAST2, and does not parse the output files (unlike `bbt_run`). In the example above, we specify the names of the desired BEAST2 output files explicitly, and these will be created in the R working directory, after which they can be inspected with other tools, or used to continue a BEAST2 run. When the names of these files are not specified, both `bbt_run` and `run_beast2` put these files in the default temporary folder (as obtained from `temp.dir()`) to keep the working directory clean of intermediate files.

4 babette resources

babette is free, libre and open source software available at `http://github.com/richelbilderbeek/babette` and is licensed under the GNU General Public License v3.0. babette uses the Travis CI (`https://travis-ci.org`) continuous integration service, which is known to significantly increase the number of bugs exposed (Vasilescu *et al.* 2015) and increases the speed at which new features are added (Vasilescu *et al.* 2015). babette has a 100% code coverage, which correlates with code quality (Horgan *et al.* 1994; Del Frate *et al.* 1995). babette follows Hadley Wickham's style guide (Wickham 2015), which improves software quality (Fang 2001). babette depends on multiple packages, which are ape (Paradis *et al.* 2004), beautier (Bilderbeek 2018b), beastier (Bilderbeek 2018a), devtools (Wickham & Chang 2016), geiger (Harmon *et al.* 2008), ggplot2 (Wickham 2009), knitr (Xie 2017), phangorn (Schliep 2011), rmarkdown (Allaire *et al.* 2017), seqinr (Charif & Lobry 2007), stringr (Wickham 2017), testit (Xie 2014) and tracerer (Bilderbeek 2018c). We tested babette to give a clean error message for incorrect input, by calling babette one million times with random or random sensible inputs, using a high performance computer cluster. The test scripts are supplied with babette.

babette's development takes place on GitHub, `https://github.com/richelbilderbeek/babette`, which accommodates collaboration (Perez-Riverol *et al.* 2016) and improves transparency (Gorgolewski & Poldrack 2016). babette's GitHub facilitates feature requests and has guidelines how to do so.

babette's documentation is extensive. All functions are documented in the package's internal documentation. For quick use, each exported function shows a minimal example. For easy exploration, each exported function's documentation links to related functions. Additionally, babette has a vignette that demonstrates extensively how to use it. There is documentation on the GitHub

to get started, with a dozen examples of BEAUti screenshots with equivalent `babette` code. Finally, `babette` has tutorial videos that can be downloaded or viewed on YouTube, `https://goo.gl/weKaaU`.

5   Citation of babette

Scientists using `babette` in a published paper can cite this article, and/or cite the `babette` package directly. To obtain this citation from within an R script, use:

```
> citation("babette")
```

6   Acknowledgements

Thanks to Yacine Ben Chehida and Paul van Els for supplying their BEAST2 use cases. Thanks again to Paul van Els for sharing his FASTA files for use by this package. Thanks to Leonel Herrera-Alsina, Raphael Scherrer and Giovanni Laudanno for their comments on this package and article. Thanks to Huw Ogilvie and one anonymous reviewer for reviewing this article. Thanks to rOpenSci, and especially Noam Ross and Guangchuang Yu for reviewing the package's source code. We would like to thank the Center for Information Technology of the University of Groningen for their support and for providing access to the Peregrine high performance computing cluster. We thank the Netherlands Organization for Scientific Research (NWO) for financial support through a VICI grant awarded to RSE.

7   Authors' contributions

RJCB and RSE conceived the idea for the package. RJCB created and tested the package, and wrote the first draft of the manuscript. RSE contributed substantially to revisions.

References

Allaire, J., Xie, Y., McPherson, J., Luraschi, J., Ushey, K., Atkins, A., Wickham, H., Cheng, J. & Chang, W. (2017) *rmarkdown: Dynamic Documents for R*. R package version 1.8.

Bilderbeek, R.J. (2018a) beastier: BEAST2 from R. `https://github.com/richelbilderbeek/beastier` [Accessed: 2018-03-16].

Bilderbeek, R.J. (2018b) beautier: BEAUti 2 from R. `https://github.com/richelbilderbeek/beautier` [Accessed: 2018-03-16].

Bilderbeek, R.J. (2018c) tracerer: Tracer from R. `https://github.com/richelbilderbeek/tracerer` [Accessed: 2018-03-16].

Bouckaert, R. & Heled, J. (2014) Densitree 2: Seeing trees through the forest. *bioRxiv*, p. 012401.

Bouckaert, R., Heled, J., Kühnert, D., Vaughan, T., Wu, C.H., Xie, D., Suchard, M.A., Rambaut, A. & Drummond, A.J. (2014) Beast 2: a software platform for bayesian evolutionary analysis. *PLoS Comput Biol*, **10**, e1003537.

Charif, D. & Lobry, J. (2007) SeqinR 1.0-2: a contributed package to the R project for statistical computing devoted to biological sequences retrieval and analysis. U. Bastolla, M. Porto, H. Roman & M. Vendruscolo, eds., *Structural approaches to sequence evolution: Molecules, networks, populations*, Bi-

ological and Medical Physics, Biomedical Engineering, pp. 207–232. Springer Verlag, New York. ISBN : 978-3-540-35305-8.

Del Frate, F., Garg, P., Mathur, A.P. & Pasquini, A. (1995) On the correlation between code coverage and software reliability. *Software Reliability Engineering, 1995. Proceedings., Sixth International Symposium on*, pp. 124–132. IEEE.

Drummond, A.J., Suchard, M.A., Xie, D. & Rambaut, A. (2012) Bayesian phylogenetics with beauti and the beast 1.7. *Molecular biology and evolution*, **29**, 1969–1973.

Fang, X. (2001) Using a coding standard to improve program quality. *Quality Software, 2001. Proceedings. Second Asia-Pacific Conference on*, pp. 73–78. IEEE.

Faria, N. & Suchard, M.A. (2015) RBeast. `https://github.com/beast-dev/RBeast` [Accessed: 2018-03-02].

Gorgolewski, K.J. & Poldrack, R. (2016) A practical guide for improving transparency and reproducibility in neuroimaging research. *bioRxiv*, p. 039354.

Harmon, L., Weir, J., Brock, C., Glor, R. & Challenger, W. (2008) Geiger: investigating evolutionary radiations. *Bioinformatics*, **24**, 129–131.

Horgan, J.R., London, S. & Lyu, M.R. (1994) Achieving software quality with testing coverage measures. *Computer*, **27**, 60–69.

Matzke, N.J. (2015) BEASTmasteR: R tools for automated conversion of NEXUS data to BEAST2 XML format, for fossil tip-dating and other uses. `https://github.com/nmatzke/BEASTmasteR` [Accessed: 2018-02-28].

Paradis, E., Claude, J. & Strimmer, K. (2004) APE: analyses of phylogenetics and evolution in R language. *Bioinformatics*, **20**, 289–290.

Perez-Riverol, Y., Gatto, L., Wang, R., Sachsenberg, T., Uszkoreit, J., Lepre-
vost, F., Fufezan, C., Ternent, T., Eglen, S.J., Katz, D.S. *et al.* (2016) Ten
simple rules for taking advantage of git and github. *bioRxiv*, p. 048744.

R Core Team (2013) *R: A Language and Environment for Statistical Computing*.
R Foundation for Statistical Computing, Vienna, Austria.

Rambaut, A. & Drummond, A.J. (2007) *Tracer v1.4*. Available from
http://beast.bio.ed.ac.uk/Tracer.

Ratmann, O. (2015) rBEAST. `https://github.com/olli0601/rBEAST` [Ac-
cessed: 2018-03-02].

Ratmann, O., Van Sighem, A., Bezemer, D., Gavryushkina, A., Jurriaans, S.,
Wensing, A., De Wolf, F., Reiss, P., Fraser, C. *et al.* (2016) Sources of hiv
infection among men having sex with men and implications for prevention.
Science translational medicine, **8**, 320ra2–320ra2.

Schliep, K. (2011) phangorn: phylogenetic analysis in R. *Bioinformatics*, **27**,
592–593.

Van Els, P. & Norambuena, H.V. (2018) A revision of species limits in neotrop-
ical pipits anthus based on multilocus genetic and vocal data. *Ibis*.

Vasilescu, B., Yu, Y., Wang, H., Devanbu, P. & Filkov, V. (2015) Quality and
productivity outcomes relating to continuous integration in github. *Proceed-
ings of the 2015 10th Joint Meeting on Foundations of Software Engineering*,
pp. 805–816. ACM.

Wickham, H. (2009) *ggplot2: elegant graphics for data analysis*. Springer New
York.

Wickham, H. (2015) *R packages: organize, test, document, and share your code*.
O'Reilly Media, Inc.

Wickham, H. (2017) *stringr: Simple, Consistent Wrappers for Common String*

Operations. R package version 1.2.0.

Wickham, H. & Chang, W. (2016) *devtools: Tools to Make Developing R Pack-*

ages Easier. R package version 1.12.0.9000.

Xie, Y. (2014) *testit: A Simple Package for Testing R Packages.* R package

version 0.4, `http://CRAN.R-project.org/package=testit`.

Xie, Y. (2017) *knitr: A General-Purpose Package for Dynamic Report Genera-*

tion in R. R package version 1.17.

Name	Description
`bbt_run`	Run BEAST2
`create_gtr_site_model`	Create a GTR site model
`create_hky_site_model`	Create an HKY site model
`create_jc69_site_model`	Create a Jukes-Cantor site model
`create_tn93_site_model`	Create a TN93 site model
`create_rln_clock_model`	Create a relaxed log-normal clock model
`create_strict_clock_model`	Create a strict clock model
`create_bd_tree_prior`	Create a birth-death tree prior
`create_cbs_tree_prior`	Create a coalescent Bayesian skyline tree prior
`create_ccp_tree_prior`	Create a coalescent constant-population tree prior
`create_cep_tree_prior`	Create a coalescent exponential-population tree prior
`create_yule_tree_prior`	Create a Yule tree prior
`create_beta_distr`	Create a beta distribution
`create_exp_distr`	Create an exponential distribution
`create_gamma_distr`	Create a gamma distribution
`create_inv_gamma_distr`	Create an inverse gamma distribution
`create_laplace_distr`	Create a Laplace distribution
`create_log_normal_distr`	Create a log-normal distribution
`create_normal_distr`	Create a normal distribution
`create_one_div_x_distr`	Create a $1/X$ distribution
`create_poisson_distr`	Create a Poisson distribution
`create_uniform_distr`	Create a uniform distribution

Table 1: babette's main functions

Figure 1: Workflow using GUI tools. From an alignment (1) and BEAUti (2), a BEAST2 configuration file (3) is created. BEAST2 (4) uses that file to infer a posterior, storing it in multiple files (5). These results are visualized using DensiTree (6) and Tracer (7). babette allows for the same workflow, all from an R function call.