Title: Shared contextual knowledge strengthens inter-subject synchrony and pattern similarity in the semantic network

Authors: Petar P. Raykov, James L. Keidel, Jane Oakhill, Chris M. Bird

Affiliation: School of Psychology, University of Sussex, Falmer BN1 9QH, UK

Corresponding author: Petar P. Raykov, School of Psychology, University of Sussex, Falmer BN1 9QH, UK. Email: P.Raykov@sussex.ac.uk

Pages: 27; **Figures:** 4; **Words:** Introduction: 823, Discussion: 1339

Conflict of Interest: "The authors declare no competing financial interests."

Acknowledgements: This work was supported by the European Research Council (337822 to C.M.B.) and an Economic and Social Research Council studentship.

Abstract

Our knowledge of the world shapes how we comprehend and remember events. These stored representations facilitate the establishment of "event models": constructs which unite the multiple temporally and spatially varying components of experience into a united whole. Interestingly, aspects of these models appear to be shared across brains. We investigated how these shared representations are affected by the presence of narrative context. Participants watched videos for which they had complete knowledge of the narrative, or only knowledge of the general scene and characters involved. Presence of narrative knowledge strengthened inter-subject pattern similarity in the bilateral anterior temporal lobes and increased inter-subject correlations in ventromedial prefrontal cortex as well as left angular and inferior frontal gyri. We propose that shared narrative knowledge constrains participants' interpretation of the videos and thereby results in greater alignment of their event models, leading to increased BOLD-related measures of neural similarity.

Introduction

The world can be a confusing place. How we make sense of it is deeply influenced by our prior knowledge, which allows us to link our current perceptions with previously established semantic concepts and build predictions about what will happen in the future. Our prior experiences and schematic representations also shape our comprehension and memory of particular events (Anderson, 1994; Bartlett, 1932; Bransford & Johnson, 1972; Carmicheal, Hogan, & Walter, 1932; Dooling & Lachman, 1971; Posner & Keele, 1968) and support the formation of situation (Johnson-Laird, 1983; Zwaan & Radvansky, 1998) or more generally event models (Richmond & Zacks, 2017). These models are multimodal representations of the spatiotemporal and causal relationships between entities present in a particular context, or more colloquially, a description of *what is happening* in a given situation (Ranganath & Ritchey, 2012).

Event models are thought to comprise many dimensions including spatial location, time, the people present and their actions, goals and interests (Richmond & Zacks, 2017). Thus it is unsurprising that a widespread set of brain regions are implicated in their instantiation. In recent research from our group, participants watched and then later recalled short movies while in an MRI scanner. We found that the multivoxel representations evoked by the movies in numerous regions associated with the so-called default mode network (DMN) and semantic network were reinstated when participants later recalled these same movies (Bird et al., 2015; Oedekoven et al., 2017; see also St-Laurent, Abdi, & Buchsbaum, 2015). These results suggest the existence of a stable and reproducible representation of the overarching content of each movie across a network of regions.

While these studies have investigated processing of events within individual subjects, other research has shown that some aspects of event processing are shared across brains. In a seminal study, Hasson and colleagues (2004) found significant correlations in the timecourse of activity elicited by a movie across subjects (inter-subject correlations: ISC). In more recent work, Chen et al. (2017) demonstrated the existence of shared multivoxel representations of observed events in DMN areas similar to those found in Bird et al. (2015) and Oedekoven et al. (2017). In addition, similar patterns of activity are also evoked in the DMN when

people construct an event in their mind's eye while listening to it being described (Zadbood et al., 2017). The authors suggested that the "unit" of information being transferred between people in their study might be the event model.

However, the complexity of event models makes it difficult to confidently ascribe such pattern similarity effects to any particular aspect of the model. Thus, these effects could reflect very broad schematic representations of the content of the scenes (e.g. 'a conversation in a café', or 'a chase down the street'). While such schematic representations provide an essential scaffold for comprehending and remembering scenes, by themselves they provide no means of differentiating similar scenes (e.g. talking to different people on different days while having a coffee in the Bridge Café). Instead, much more specific information is required, such as the content or themes of the narrative of the scene.

A number of classic studies have investigated narrative comprehension by manipulating prior knowledge (e.g. Bransford & Johnson, 1972; Dooling & Lachman, 1971; Maguire, Frith, & Morris, 1999). In such experiments, ambiguous or confusing narratives can be understood with the provision of specific background contextual information before the narrative is read. Ames, Honey, Chow, Todorov, and Hasson (2015) used such a manipulation to investigate the effect of prior contextual knowledge on ISCs. The authors found that participants sharing the same background context showed increased synchronization in BOLD response in the ventromedial prefrontal cortex (vmPFC) and posterior cingulate cortex (PCC). In a conceptually similar study, van Kesteren, Fernandez, Norris, Hermans (2010) examined how prior knowledge affects the encoding of events depicted in a movie. Participants watched the first part of a movie either in temporally scrambled or intact order and then, on the following day, watched the last 15 minutes of the movie in the scanner. The authors observed higher vmPFC ISC in participants that had watched the first part of the movie in the correct temporal order. Both of these studies show that providing prior knowledge boosts the consistency of fluctuations in vmPFC activity across participants, presumably by leading participants to favour a particular interpretation of the events depicted and thereby reducing variability across the group.

In the current study we examine how the presence or absence of narrative context affects processing across participants. We presented participants with video excerpts taken from TV situational comedies that were divided into first and second halves. We manipulated availability of contextual knowledge by making the speech in the first half clips unintelligible for half of the clips each participant viewed (SRS see Fig. 1), while the second halves were all presented with unaltered speech. This design allows us to detect differences in moment-by moment synchronization and overall representational similarity across participants viewing an identical set of stimuli.

Methods

Participants

24 right-handed native English speakers with normal or corrected to normal vision were included in the study. 4 participants were not included in the final analysis due to artefacts in the MRI scans and 1 further participant did not complete the experiment. One participant had corrupted post-scanning behavioural data for the memory questions and was not included in the behavioural analysis. The project was approved by the Brighton and Sussex Medical School Research Governance and Ethics Committee (RGEC) and all participants gave informed consent and were paid £20.

Figure 1 Schematic of study design. Participants viewed videos from unfamiliar TV sitcoms that were divided into two halves. Ten of the first halves had comprehensible speech, whereas the other 10 had unintelligible speech, created by spectrally rotating the audio. Videos were counterbalanced across participants in a within-subjects design. SRS – spectrally rotated speech; NS – normal speech; HC – high context; LC – low context.

Stimuli

20 video clips from different US and UK television shows were used in the experiment. The TV shows originally aired between 1970 and 2003 and were selected to be unfamiliar to our sample. Each video was divided into first and second halves. The scene location and characters remained constant across the two halves. For our main experimental manipulation the speech in 10 of the first half videos was made unintelligible. This was done with Praat (version 6.0.15) (Boersma, 2001) by spectrally rotating the audio of the videos with a sinusoidal function with maximum frequency of 4 KHz. The audio for all videos was scaled to the have the same mean decibel intensity. The mean duration of all the excerpts was 32.47(±3.88) seconds. The first half videos (30.57±4.38) were on average shorter than the second half videos (34.37±2.02). Three different video clips, all with spectrally rotated audio, were used in the practice task with total video length of 4.36 minutes. Four lists were created to fully counterbalance the conditions and presentation order.

Procedure

Participants were informed they would see first- and second-half videos in four separate runs (five videos in each). They were told that the speech in some of the first-half videos would be unintelligible, and were asked to watch the clips as they would watch television at home. Participants were also informed that their memory for the clips would be tested after the scanning session. They completed an 8 minute practice session outside the scanner, to familiarise themselves with the task and the sound of spectrally rotated speech.

The scanning session started with a 4 minute resting state scan (data not reported here). Following this, the task was presented in four functional runs, each approximately 10 minutes long. Each run consisted of 5 first half and 5 second half clips and every clip was followed by a question and an active baseline task. In each run there were either two or three clips with rotated speech. Movie onsets were time-locked to the repetition time (TR). After each clip a white fixation cross was presented for 1 second. Each video was followed by a question about the general relationship between the characters in the scene (e.g. Did the characters appear to be enjoying themselves?). Behavioural piloting confirmed that participants could

answer the questions regardless of whether speech was rotated or not. The questions were presented for 8 seconds or until participants made a Yes/No response and were followed by a 500 milliseconds fixation. Participants made an odd/even number judgement during an active baseline task (Stark & Squire, 2001) presented in 16 seconds blocks in-between clips. Six randomly chosen numbers, between 1 and 98, were each presented for 2 seconds, followed by a fixation cross presented for 667 milliseconds. After the baseline task a red fixation cross was presented for a minimum of 400 milliseconds to signal that the next video was about to begin.

Outside of the scanner, participants completed a questionnaire about their familiarity with the shows. Only 6 participants reported any familiarity with 1-3 of the shows and none were familiar with the particular scenes used in the experiment. Afterwards, participants carried out a computer-based memory task, in which the first 4-6 seconds of the second half videos were presented as a memory cue. Participants were then asked to rate from 1 to 10: (1) the vividness of their memory of the video, (2) how coherent they found the story in the videos, (3) how engaging they found the video. Participants were also asked an open-ended memory question specific to each second half video (e.g. What was the address on his chest written in?). All memory questions concerned only material presented in the second half of the videos.

MRI acquisition

Data was acquired on a 1.5 T Siemens Avanto MRI scanner. Functional T2* weighted BOLD-sensitive images were acquired with EPI sequence with following parameters: FOV = 192mm, TR = 2.62 seconds, TE = 42 milliseconds, 90 degree flip angle, slice thickness = 3mm, 35 interleaved ascending slices with .6 mm gap, and 3.0x3.0x3.0 mm voxels. A high resolution T1-weighted image was acquired with the following parameters: FOV 256mm, TR = 2.73 seconds, TE = 3.57ms, 1.0x1.0x1.0mm voxel size.

Image pre-processing

All EPI images were pre-processed using SPM 12 (Wellcome Department of Imaging Neuroscience, London, UK). Field maps were used to correct for image distortions and susceptibility-by-movement effects using the Realign and Unwarp

option (Andersson, Hutton, Ashburner, Turner, & Friston, 2001; Hutton et al., 2002). All EPI images were aligned to the first image of the first session. The anatomical image of each subject was co-registered to their mean realigned EPI image. The anatomical images were then segmented into grey and white matter maps. Anatomical and EPI images were normalized to the MNI space using DARTEL (Ashburner, 2007) and smoothed with an 8 mm FWHM kernel. Images for the inter-subject pattern similarity were pre-processed as above with the exception that a 6 mm FWHM smoothing kernel was applied to the normalised images, as previously used by Chen et al. (2017).

Data Analysis

Data was analysed with SPM 12, the CoSMoMVPA toolbox (Oosterhof, Connolly, & Haxby, 2016) and custom scripts in MATLAB (Version 2016b, The MathWorks, Inc., Natick, MA, USA). All analyses were conducted on MNI normalised images within a grey matter mask. Segmentation of the high-resolution structural images provided us with grey matter tissue probability map for each subject. These probability maps were normalised to MNI, averaged across participants. The averaged mask was smoothed with a 6mm FWHM kernel. We selected all voxels within this average probability map higher than a threshold of 0.3. To describe and visualise our data we used the Bspmview toolbox (www.bobspunt.com/bspmview), which implements the MNI coordinates from the Anatomical Automatic Labelling 2 toolbox for SPM 12. Significance was tested with a one-sample random effects t test against zero. Unless otherwise stated, images were whole brain cluster corrected for FWE $p < 0.05$ at voxel height-defining threshold of $p < 0.001$.

GLM analysis

A single task regressor for each of the four conditions (SRS, NS, LC and HC: see Figure 1) was included in the first-level models. For all GLM first level models the questions after each video were modelled with a single regressor of no interest and the odd/even number judgment task was left unmodelled to represent the implicit baseline. A block design first level analysis was conducted to replicate previous findings. In this analysis all video stimuli were modelled with boxcar functions whose durations matched the stimulus duration. The models also included

the six motion parameters, a regressor for the mean session effects, and a high-pass filter with a cut-off of 1/128 Hz. We also ran an analysis identical to the above, but modelled only the onset of the videos with a gamma function, rather than including the whole duration of the video. This was done to replicate previous findings by Keidel et al. (2017). First-level models for the inter-subject pattern analysis included the same nuisance regressors as the previous analysis. However, each video was represented with its own block regressor that covered the whole duration of the video. This allowed us to examine video specific patterns.

Inter-Subject Analyses

     Inter-subject correlation (ISC)

     The ISC allowed us to examine how dynamic processing of the second half videos was modulated by previous knowledge. ISCs were computed voxelwise over second half videos (HC and LC videos, which contained coherent speech). To examine the similarity across participants under the same condition we constructed 2 condition lists. To construct 2 condition lists from 4 counterbalancing lists we combined the lists in which videos were seen under the same condition, but in different order. There were 9 and 10 people in the two condition lists. It has been shown that averaging over at least 4 people's time courses provides reliable ISC estimation (Hasson et al., 2004). The first 2 TRs (5.24 seconds) of each video were removed in order to remove transient onset effects that can lead to artificially high ISC (Ames et al., 2015).

     The raw time course for each video and each subject were extracted. These time-courses were used to compute the Fisher-transformed correlations across subjects for each video. For a given subject we computed the correlation between the subject's specific video time-course and the average time-course for the rest of the participants watching the same video under the same condition. This resulted in 20 time-course correlations for each subject, which represented the time-course similarity across participants watching the same videos (diagonal values in Fig. 3 A & C). The time-course correlations across participants for different videos were also computed for the general ISC analysis (see Fig. 3 A).

     First, a general ISC analysis allowed us to examine ISCs while watching the same videos irrespective of whether the context was familiar or not (see Fig. 3 A).

We compared the time-course correlations across participants watching the same video versus different videos.

Next, we examined how narrative themes affected ISCs. We contrasted a participants' time-course similarity with other participants for HC versus LC videos (see Fig. 3 B), in order to examine whether participants were more synchronised when they watched the HC clips versus when they watched the LC clips. This was performed for each subject by averaging over the 10 Fisher transformed correlations across HC videos and subtracting the average of the 10 LC coefficients.

Inter-Subject Pattern Similarity (ISPS)

This analysis was performed to examine spatial pattern similarity across participants experiencing the same events. The inter-subject pattern (ISPS) analysis was conducted on the normalised t-maps generated for each subject and each 2nd half video. For each subject a searchlight map was generated by centring a spherical searchlight with radius of 3 voxels (mean size 110 voxels) at each voxel. For a given participant the activity patterns for a specific video were correlated with the average activity pattern across participants watching the same video under the same condition. This resulted in 20 correlations for each subject representing the video specific pattern similarity across subjects (see diagonal Fig. 4 A). The across participants pattern similarity was also calculated for not matching videos resulting in 380 correlation coefficients for each searchlight (see off-diagonal Fig. 4 A). Contrast matrixes were used to weight the resulting Fisher-transformed correlations for each searchlight. The summed correlations were assigned to the central voxel of each searchlight. Two types of ISPS analyses were conducted by specifying different contrast matrixes

First, we conducted a "General Show" ISPS analysis to examined the similarity across participants watching the same clip versus when they were watching non-matching clips, irrespective of their prior knowledge (see Fig. 4).

Then we examined whether participants showed more highly correlated patterns for HC videos than for LC videos (see Fig. 4). Due to stimulus counterbalancing there were two groups (n = 9 and n = 10) of people who saw the same videos in the same condition. Therefore for the ISPS we compared the

similarity between a subject's patterns and the average patterns of the other subjects in their group.

Results

Behavioural results

Participants had an overall accuracy of 72.2% for the memory questions, which is high level of performance given the fact that the questions were open ended. Participants responded more accurately to the same questions when in the HC condition (80%) than in the LC condition (64.4%: t_{17} = 3.39, p = 0.003). The memory questions were specific to the 2nd half videos and did not require information from the 1st half videos. HC videos were also rated as being remembered more vividly (t_{17} = 7.15, p < 0.001), more coherent (t_{17} = 6.88, p < 0.001) and more engaging (t_{17} = 6.23, p < 0.001).

Figure 2. *Behavioural results.* A) Shows average memory performance for questions on HC versus LC videos. B) Shows that participants on average found HC videos more coherent. C) Higher vividness ratings were observed for HC videos. D) Participants reported HC videos as more engaging. ** p < .01; *** p < .001

fMRI Results

    GLM

The contrast of watching videos versus the active baseline task revealed higher activation in visual, auditory, medial and anterior temporal cortices (see Supplementary Fig. 1). This is consistent with previous studies using videos (e.g. Bartels & Zeki, 2004). Brain areas that showed higher activation for the onset of the videos versus baseline are shown in Supplementary Fig. 3. These results replicate Keidel et al.'s (2017) findings and showed that retrosplenial cortex (RSC) and parahippocampal cortex (PHG) extending into the ventral precuneus showed transient activation associated with the onset of the videos. In the current study the time-course analysis did not show that these PHG and RSC activations were modulated by our narrative themes manipulation, which addresses suggestions made in Keidel et al., (2017). The time-course analysis replicated previous findings in showing higher activation in the middle temporal gyrus (MTG), supramarginal gyrus (SMG) and angular gyrus (AG) for HC videos. However, in contrast to the previous study we did not observe higher activation in the inferior frontal gyrus (IFG) time-course analysis (See Supplementary Material for further discussion).

    Inter-Subject Correlation

The ISC analysis allowed us to examine synchronization of the BOLD response across participants. ISCs for watching videos irrespective of the context manipulation were found in extensive regions of the occipital and superior temporal lobes encompassing visual and auditory processing regions. Higher synchronization was also observed in bilateral IFG, medial prefrontal cortex, AG and precuneus (see Fig. 3).

The ISC comparison between HC and LC videos showed stronger coupling in the ventromedial portion of the prefrontal cortex as well as the left AG, IFG and superior parietal lobule (SPL) (see Fig. 3). We also observed a cluster in the left inferior parietal lobule (IPL), which showed greater synchronization for LC clips.

    Inter-Subject Pattern Similarity

The general ISPS allowed us to examine where spatial patterns of activity were more similar across participants watching the same videos versus watching

different videos irrespective of the context manipulation. The results are shown in Fig. 4. This analysis revealed significant video-specific similarity across participants in the primary sensory areas and areas associated with higher cognitive processes, such as the bilateral IFG, precuneus, the MTG, the inferior portion of the anterior temporal pole (ATL) and the medial prefrontal cortex. The video-specific pattern similarity results reported here strongly resemble the scene-specific cross-subject similarity reported by Chen et al. (2017).

However, our main interest was to examine whether narrative theme modulates this effect. We expected higher spatial pattern similarity for people watching HC videos as they had shared narrative knowledge and potentially interpretation of the videos. Indeed, for the HC > LC contrast we found that left and right anterior temporal lobe (ATL) to show higher pattern similarity across participants. Surprisingly, the reverse contrast showed that the precentral gyrus exhibited higher pattern similarity across subjects for LC clips.

Figure 3 *Inter-subject correlations*. A) The weight matrix (General ISC) tests for video specific time course similarity across participants. Each cell represents the correlation between subjects' time course for a particular video with the average time course of all remaining participants for a particular video. The diagonal represents correlations between time courses for the same videos. B) Brain map from video specific analysis, which shows extended synchronization across the brain for people watching the same videos. C) Weight matrix that tests for the time-course similarity across the same videos, depending on the prior knowledge provided for them. D) Brain map showing how time-course synchronicity was modulated by prior knowledge.

Figure 4 Inter-subject Pattern Similarity. A) The weight matrix (General ISPS) tests for video specific spatial pattern similarity across participants. The diagonal represents spatial similarity for the same videos. B) Brain map from video specific analysis, which shows extended pattern similarity across the brain for people watching the same videos. C) Weight matrix that tests for the spatial similarity across the same videos, depending on the prior knowledge provided for them. D) Brain map showing how spatial pattern similarity was modulated by prior knowledge.

Discussion

We rely on our prior knowledge to comprehend and form memories of the world around us. In this study we used naturalistic stimuli to investigate how prior knowledge of a narrative affects our event representations. Participants viewed videos for which they either were or were not provided with knowledge of the preceding narrative. The availability of contextual information increased participants' memory performance and subjective comprehension and vividness ratings. We found that bilateral vmPFC and left AG, IFG and SPL showed higher coupling in the moment-to-moment BOLD response across participants in the HC condition. In addition, we observed greater cross-participant multivoxel pattern similarity for HC videos in the bilateral anterior temporal lobes.

Our ISC results extend previous findings examining how prior knowledge affects event processing. Ames et al. (2015) and van Kesteren et al. (2010) found higher inter-subject correlation in vmPFC when participants were processing stimuli for which they had prior knowledge, and suggested that vmPFC activity supports the integration of incoming information with previously established representations (Gilboa & Marlatte, 2017; van Kesteren, Ruiter, Fernandez, & Henson, 2012). We have here both replicated this vmPFC finding and additionally showed increased synchronization in the left IFG and AG across participants sharing the knowledge of the narrative.

The AG and IFG play a central role in language and semantic processing (Binder, Desai, Graves, & Conant, 2009) and were highlighted in recent work from our lab investigating contextual effects (Keidel et al., 2017). They are likely involved in moment-by moment integration of knowledge gained by watching the intact first half of each video (for participants watching in the HC condition) with the incoming information provided by the second half of the video. For instance, in one of the second half videos (taken from the show "Just Shoot Me") two of the main characters (Jack and Maya) discuss the fact that penguins cannot fly. Jack claims that "penguins once filled the skies", but one day their confidence was shattered and they never flew again. A participant viewing this clip in the HC condition can relate this discussion back to the first half of the video, in which Jack explains how Maya hurt Elliot's confidence and the negative effect this has had on his work. However, because participants viewing this clip in the LC condition were familiar with the

general setting (Jack and Maya in an office), but not the specifics of the narrative, they would be more likely to have formed disparate interpretations of what the scene is really about. Thus, while participants in both conditions shared the general "scaffold" of the event model, only in the HC condition could participants bring the more specific information gained from the first half of the video to their understanding of the second half. Our results suggest that the integration of this contextual information relies in part on the activity of the left IFG and AG.

We also found greater video-specific pattern similarity in the bilateral ATL across participants viewing clips in the HC condition. We propose that participants viewing videos in the HC condition were able to more consistently bind individual semantic concepts into the context of the scene because the context provided by the intact first half of the video provides a common point of reference. This process is likely to occur throughout the whole duration of the video and is consistent with the proposed role of the anterior temporal lobes in semantic memory (L. Chen, Lambon Ralph, & Rogers, 2017; Patterson, Nestor, & Rogers, 2007; Rice, Hoffman, & Lambon Ralph, 2015). In addition, because our stimuli rely heavily on understanding the behaviour and intentions of the characters, our findings also mesh well with the proposed role of the ATL in social cognition (Olson, Plotzker, & Ezzyat, 2007; Ross & Olson, 2010; Zahn et al., 2007).

Taken together, the work of Bird et al. (2015), Keidel et al. (2017) and the current findings suggest a division of labour in the instantiation of event models in the brain, wherein the PCC represents the stable core of the model and lateral temporal and parietal regions more tightly track the rapidly changing aspects of the associated narrative, a view very similar to that proposed by Ranganath and Ritchey (2012). Bird et al. (2015) demonstrated strong representational similarity between watching and recalling the stimuli in the posterior medial cortex including the PCC and precuneus. In addition, they also identified a region of the PCC where the magnitude of these effects was modulated by the number of details recalled for each individual video. The nature of this design and analysis strongly suggests that these results reflect encoding and reactivation of the videos at a somewhat abstract or gist-like level. First, during videos and recall responses to each stimulus were effectively averaged across the entire active period. Second, participants were free to recall different aspects of the stimuli in any order they chose and at any speed, so it is

unlikely that they reproduced the videos in their mind's eye exactly as they were shown in the watching phase. The abstract and general nature of these posterior medial representations is also supported by Chen et al.'s (2017) and Zadbood et al.'s (2017) demonstration of shared cross-participant response patterns between watching, recalling and listening to spoken descriptions of scenes.

Beyond midline structures, Keidel et al. (2017) provided evidence for the role of left lateral temporal and parietal regions the processing of the narrative content of event models. Specifically, they modelled the time course of activation for videos that were or were not continuations of clips seen in an earlier phase of the experiment, and found that the left AG, SMG, MTG and IFG were all more active in the continuation condition. They interpreted these findings as reflecting reactivation of links between concepts that were established during viewing of the corresponding first half of each video. The current study has largely replicated these univariate effects (see Supplementary Methods, Supplementary Figures 3-4).

The results of Ames et al. (2015) provide a particularly interesting comparison to the current results. In their study, participants listened to short vignettes that were difficult to understand without the provision of a specially designed picture cue. They found significant ISC in the PMC whether or not participants were provided with the correct cue, along with significantly greater ISC in the valid vs. the invalid cue condition. This pattern differed from that observed in the vmPFC, where significant ISC were only observed in the valid cue condition. Assuming that participants in the invalid cue condition could not create a useful event model (as intended by study's design), these findings suggest that synchronization in the PCC is to some degree independent of the existence of a core event model, while engagement of medial prefrontal regions is dependent on such a model. This may appear at first to conflict with our findings, especially the lack of a context effect on ISC in PCC. However, both NS and SRS first-half videos contained sufficient information to establish a basic situation model. Thus, if PMC activity underpins the stable or slowly changing aspects of a situation model, then no differences in this region are expected. On the other hand, greater ISC in the vmPFC suggest that information from the intact first half videos did impact processing in this region. Given that the difference between the two first half conditions was the availability of what the characters were talking about, it seems likely that this increase in vmPFC relates to integration of semantic

and/or interpersonal information into the active situation model while watching the second half of the video.

In summary, we have shown how manipulation of available context impacts on the representation of situation models both within and across participants. The availability of information relating to the narrative of our stimuli led to increases in cross-participant synchronization and representational similarity in regions associated with semantic processing, reflecting both moment-by-moment and global updating of the situation model. These results provide important new insights into how the brain moulds temporally and spatially variable inputs into a cohesive whole.

References

Ames, D. L., Honey, C. J., Chow, M. A., Todorov, A., & Hasson, U. (2015). Contextual alignment of cognitive and neural dynamics. *Journal of Cognitive Neuroscience, 27*(4), 655-664. doi: 10.1162/jocn_a_00728

Anderson, R. C. (1994). *Role of the reader's schema in comprehension, learning, and memory*. Newark, DE, US: International Reading Association.

Andersson, J. L. R., Hutton, C., Ashburner, J., Turner, R., & Friston, K. (2001). Modeling Geometric Deformations in EPI Time Series. *NeuroImage, 13*(5), 903-919. doi: 10.1006/nimg.2001.0746

Ashburner, J. (2007). A fast diffeomorphic image registration algorithm. *NeuroImage, 38*(1), 95-113. doi: 10.1016/j.neuroimage.2007.07.007

Bartels, A., & Zeki, S. (2004). Functional brain mapping during free viewing of natural scenes. *Human Brain Mapping, 21*(2), 75-85.

Bartlett, F. C. (1932). *Remembering: A study in experimental and social psychology*. New York, NY, US: Cambridge University Press.

Binder, J. R., Desai, R. H., Graves, W. W., & Conant, L. L. (2009). Where Is the Semantic System? A Critical Review and Meta-Analysis of 120 Functional Neuroimaging Studies. *Cerebral Cortex, 19*(12), 2767-2796. doi: 10.1093/cercor/bhp055

Bird, C. M., Keidel, J. L., Ing, L. P., Horner, A. J., & Burgess, N. (2015). Consolidation of Complex Events via Reinstatement in Posterior Cingulate Cortex. *The Journal of Neuroscience, 35*(43), 14426-14434. doi: 10.1523/JNEUROSCI.1774-15.2015

Boersma, P. (2001). Praat, a system for doing phonetics by computer. *Glot International, 5*(9/10), 341-345. doi: citeulike-article-id:4016976

Bransford, J. D., & Johnson, M. K. (1972). Contextual Prerequisites for Understanding - Some Investigations of Comprehension and Recall. *Journal of Verbal Learning and Verbal Behavior, 11*(6), 717-726. doi: 10.1016/S0022-5371(72)80006-9

Carmicheal, L., Hogan, H. P., & Walter, A. A. (1932). An experimental study of the effect of language on the reproduction of visually perceived form. *Journal of Experimental Psychology, 15*, 73-86. doi: 10.1037/H0072671

Chen, J., Leong, Y. C., Honey, C. J., Yong, C. H., Norman, K. A., & Hasson, U. (2017). Shared memories reveal shared structure in neural activity across individuals. *Nature Neuroscience, 20*(1), 115-125. doi: 10.1038/nn.4450

Chen, L., Lambon Ralph, M. A., & Rogers, T. T. (2017). A unified model of human semantic knowledge and its disorders. *Nature Human Behaviour, 1*(3), 0039. doi: 10.1038/s41562-016-0039

Dooling, D. J., & Lachman, R. (1971). Effects of Comprehension on Retention of Prose. *Journal of Experimental Psychology, 88*(2), 216-222. doi: 10.1037/H0030904

Gilboa, A., & Marlatte, H. (2017). Neurobiology of Schemas and Schema-Mediated Memory. *Trends in Cognitive Sciences, 21*(8), 618-631. doi: 10.1016/j.tics.2017.04.013

Hasson, U., Nir, Y., Levy, I., Fuhrmann, G., & Malach, R. (2004). Intersubject synchronization of cortical activity during natural vision. *Science, 303*(5664), 1634-1640. doi: 10.1126/science.1089506

Hutton, C., Bork, A., Josephs, O., Deichmann, R., Ashburner, J., & Turner, R. (2002). Image distortion correction in fMRI: A quantitative evaluation. *NeuroImage, 16*(1), 217-240. doi: 10.1006/nimg.2001.1054

Johnson-Laird, P. N. (1983). *Mental models: towards a cognitive science of language, inference, and consciousness*: Harvard University Press.

Keidel, J. L., Oedekoven, C. S. H., Tut, A. C., & Bird, C. M. (2017). Multiscale Integration of Contextual Information During a Naturalistic Task. *Cerebral Cortex*, 1-9. doi: 10.1093/cercor/bhx218

Maguire, E. A., Frith, C. D., & Morris, R. G. (1999). The functional neuroanatomy of comprehension and memory: the importance of prior knowledge. *Brain, 122*(10), 1839-1850. doi: 10.1093/brain/122.10.1839

Oedekoven, C. S. H., Keidel, J. L., Berens, S. C., & Bird, C. M. (2017). Reinstatement of memory representations for lifelike events over the course of a week. *Scientific Reports, 7*(1), 14305. doi: 10.1038/s41598-017-13938-4

Olson, I. R., Plotzker, A., & Ezzyat, Y. (2007). The Enigmatic temporal pole: a review of findings on social and emotional processing. *Brain, 130*(7), 1718-1731. doi: 10.1093/brain/awm052

Oosterhof, N. N., Connolly, A. C., & Haxby, J. V. (2016). CoSMoMVPA: Multi-Modal Multivariate Pattern Analysis of Neuroimaging Data in Matlab/GNU Octave. *Frontiers in Neuroinformatics, 10*, 27. doi: 10.3389/fninf.2016.00027

Patterson, K., Nestor, P. J., & Rogers, T. T. (2007). Where do you know what you know? The representation of semantic knowledge in the human brain. *Nature Reviews Neuroscience, 8*(12), 976-987. doi: 10.1038/nrn2277

Posner, M. I., & Keele, S. W. (1968). On the genesis of abstract ideas. *Journal of Experimental Psychology, 77*(3), 353-363. doi: 10.1037/h0025953

Ranganath, C., & Ritchey, M. (2012). Two cortical systems for memory-guided behaviour. *Nature Reviews Neuroscience, 13*(10), 713-726. doi: 10.1038/nrn3338

Rice, G. E., Hoffman, P., & Lambon Ralph, M. A. (2015). Graded specialization within and between the anterior temporal lobes. *Ann NY Acad Sci*, 26. doi: 10.1111/nyas.12951

Richmond, L. L., & Zacks, J. M. (2017). Constructing Experience: Event Models from Perception to Action. *Trends in Cognitive Sciences, 21*(12), 962-980. doi: 10.1016/j.tics.2017.08.005

Ross, L. A., & Olson, I. R. (2010). Social cognition and the anterior temporal lobes. *NeuroImage, 49*(4), 3452-3462.

St-Laurent, M., Abdi, H., & Buchsbaum, B. R. (2015). Distributed Patterns of Reactivation Predict Vividness of Recollection. *Journal of Cognitive Neuroscience, 27*(10), 2000-2018. doi: 10.1162/jocn_a_00839

Stark, C. E. L., & Squire, L. R. (2001). When zero is not zero: The problem of ambiguous baseline conditions in fMRI. *Proceedings of the National Academy of Sciences, 98*(22), 12760. doi: 10.1073/pnas.221462998

van Kesteren, M. T., Fernandez, G., Norris, D. G., & Hermans, E. J. (2010). Persistent schema-dependent hippocampal-neocortical connectivity during memory encoding and postencoding rest in humans. *Proceedings of the National Academy of Sciences, 107*(16), 7550-7555. doi: 10.1073/pnas.0914892107

van Kesteren, M. T., Ruiter, D. J., Fernandez, G., & Henson, R. N. (2012). How schema and novelty augment memory formation. *Trends in Neurosciences, 35*(4), 211-219. doi: 10.1016/j.tins.2012.02.001

Zadbood, A., Chen, J., Leong, Y. C., Norman, K. A., & Hasson, U. (2017). How We Transmit Memories to Other Brains: Constructing Shared Neural Representations Via Communication. *Cerebral Cortex, 27*(10), 4988-5000. doi: 10.1093/cercor/bhx202.

Zahn, R., Moll, J., Krueger, F., Huey, E. D., Garrido, G., & Grafman, J. (2007). Social concepts are represented in the superior anterior temporal cortex. *Proceedings of the National Academy of Sciences, 104*(15), 6430.

Zwaan, R. A., & Radvansky, G. A. (1998). Situation models in language comprehension and memory. *Psychological Bulletin, 123*(2), 162-185. doi: 10.1037/0033-2909.123.2.162

Table 1. Inter-Subject Correlation. Significant clusters showing scene-specific cross-participant correlations.

Region	x	y	z	Size (voxels)	T
L Superior Occipital Gyrus	-15	-90	27	16039	15.70
L Lingual gyrus	-6	-81	-3	16039*	15.52
R Middle Occipital Gyrus	42	-69	3	16039*	15.19
R Calcarine Sulcus	18	-60	12	16039*	3.62
L Middle Occipital Gyrus	-42	-78	24	16039*	3.84
L Temporal Middle Gyrus	-42	-63	9	16039*	4.63
L Anterior Cingulate Gyrus	-9	33	18	34*	7.03
R Medial Orbitofrontal Cortex	12	60	-18	240*	6.96
R Caudate nucleus	12	0	15	114	6.68
L Superior Frontal Gyrus	-15	69	6	74	6.56
L Middle Frontal Gyrus	-30	51	9	74*	5.08
R Putamen	24	15	-12	29	4.89
L Caudate	-9	3	12	36	6.15
L Middle Frontal Gyrus	-27	6	54	39	5.59
L Cerebellum Crus II	-42	-57	-45	44	5.54
L Cerebellum Crus II	-33	-78	-51	44*	4.16
L Inferior Temporal Gyrus	-36	0	-42	37	5.43

Table 2. Significant clusters identified for the context-specific ISC contrasting HC >
LC. Clusters showing higher cross-participant coupling for HC vs. LC videos.

Region (ISC)	x	y	z	Size (voxels)	T
L Superior Frontal Gyrus	-24	27	42	36	8.31
L Superior Parietal Lobule	-18	-60	60	40	6.86
L Cerebellum IX	-9	-60	-51	72	6.64
L Cerebellum crus II	-12	-81	-45	24	5.13
L Inferior Frontal Gyrus	-57	18	15	65	5.86
L Angular Gyrus	-48	-69	27	72	5.46
L Medial Orbitofrontal Cortex	-3	27	-12	24	5.18
L Precentral gyrus	-39	-3	54	32	5.00
R Middle Frontal Gyrus	51	-6	51	126	6.49
R Middle Temporal Gyrus	51	-48	9	28	5.25
Negative					
L Angular Gyrus	-33	-57	36	24	-5.43

Table 3. Inter-Subject Pattern Similarity. Significant clusters showing scene-specific cross-participant pattern similarity for second half videos regardless of condition.

Region	x	y	z	Size (voxels)	T
L Middle Occipital Gyrus	-36	-90	0	10826	17.37
L Cuneus	-12	-60	24	10826*	12.49
R Calcarine sulcus	9	-93	9	10826*	12.31
R Middle Occipital Gyrus	30	-72	27	10826*	4.65
R Precuneus	6	-72	33	10826*	3.77
L Cerebellum IX	-6	-57	-51	114	10.22
L Inferior Frontal Gyrus	-39	39	-6	311	8.80
R Middle Temporal Gyrus	54	3	-21	285	7.31
R Inferior Temporal Gyrus	33	3	-42	285*	6.58
R Middle Frontal Gyrus	33	6	45	122	7.10
R Precentral Gyrus	54	-3	48	122*	4.24
R Inferior Frontal Gyrus	57	12	21	403	7.00
R Superior Middle Frontal Gyrus	6	21	42	85	6.91
R Supplementary Motor Area	15	12	66	88	6.65
L Medial Orbitofrontal Cortex	-9	66	-3	200	6.48
L Parahippocampal Gyrus	-30	-12	-27	70	5.72
L Supplementary Motor Area	-12	12	60	111	5.98
L Middle Frontal Gyrus	-36	30	45	111*	5.13
L Inferior Frontal Gyrus	-54	12	21	112	5.68

Table 4. Inter-Subject Pattern Similarity HC vs LC. Significant clusters showing higher pattern similarity across participants for HC vs. LC videos.

Region	x	y	z	Size (voxels)	T
R Medial Temporal Pole	39	15	-39	138	6.66
R Medial Temporal Pole	57	6	-21	138*	6.16
R Inferior Temporal Gyrus	51	-5	-36	138*	5.04
L Inferior Temporal Gyrus	-42	-3	-36	56	5.48
Negative					
R Cerebellum Crus I	48	-51	-39	156	-5.85
R Precentral Gyrus	33	-27	69	88	-5.11