Qoala-T: A supervised-learning tool for quality control of automatic segmented MRI data

Running head: Qoala-T: MRI quality control tool

Eduard T. Klapwijk[1,2,3], Ferdi van de Kamp[1,2], Mara van der Meulen[1,2,4], Sabine Peters[1,2], Lara M. Wierenga[1,2]

[1]Department of Developmental and Educational Psychology, Leiden University, the Netherlands [2]Leiden Institute for Brain and Cognition, the Netherlands [3]Department of Child and Adolescent Psychiatry, Curium-Leiden University Medical Center, the Netherlands [4]Leiden Consortium on Individual Development

Corresponding author:

Lara M. Wierenga

Institute of Psychology, Leiden University, The Netherlands

Wassenaarseweg 52 2333 AK Leiden, The Netherlands.

E: l.m.wierenga@fsw.leidenuniv.nl

Conflict of Interest: The authors declare that they have no biomedical financial interest or potential conflict of interest.

Keywords: structural magnetic resonance imaging; motion; artifacts; FreeSurfer; development; random forests

Abstract

Performing quality control to detect image artifacts and data-processing errors is crucial in structural magnetic resonance imaging, especially in developmental studies. Currently, many studies rely on visual inspection by trained raters for quality control. The subjectivity of these manual procedures lessens comparability between studies, and with growing study sizes quality control is increasingly time consuming. In addition, both inter-rater as well as intra-rater variability of manual quality control is high and may lead to inclusion of poor quality scans and exclusion of scans of usable quality. In the current study we present the Qoala-T tool, which is an easy and free to use supervised-learning model to reduce rater bias and misclassification in manual quality control procedures. First, we manually rated quality of N = 784 FreeSurfer-processed T1-weighted scans. Different supervised-learning models were then compared to predict manual quality ratings. Results show that the Qoala-T tool using random forests is able to predict scan quality with both high sensitivity and specificity (mean area under the curve (AUC) = 0.98). In addition, the Qoala-T tool was also able to adequately predict the quality of a novel unseen dataset (N = 112; mean AUC = 0.95). These outcomes indicate that using Qoala-T in other datasets could greatly reduce the time needed for quality control. More importantly, this procedure could further help to reduce variability related to manual quality control, thereby benefiting the comparability of data quality between studies.

Introduction

Quality control (QC) of structural magnetic resonance imaging (sMRI) data is an essential step in the image processing stream (Ducharme et al., 2016). These QC procedures enable detection of scanner-related artifacts, data-processing errors and participant-related artifacts such as head motion. Such artifacts are shown to result in underestimations of cortical volume and thickness measures (Reuter et al., 2015). This is of particular relevance to studies including children and adolescents or clinical groups (Brown et al., 2010; Van Dijk et al., 2012), as systematic group- and age-related differences in image quality (e.g., motion artifacts) may confound developmental or clinical inferences (Ducharme et al., 2016; Pardoe et al., 2016). Although QC procedures are widely applied, they are not extensively described in individual studies. Most studies use in-house developed protocols that include visual inspection of automatic brain segmentation procedures (such as FreeSurfer; Dale et al., 1999). Trained raters then decide which scans are of sufficient quality for further analysis (see Backhausen et al., 2016 for a detailed example). The reliability of these protocols is currently unknown as different protocols are rarely compared and examined between studies. In general, manual quality ratings suffer from a number of limitations: they are inherently subjective, time consuming and susceptible to both inter-rater as well as intra-rater variability (e.g., learning or fatigue). Furthermore, not all artifacts might be detectable by visual inspection (Gardner et al., 1995). This together makes manual ratings vulnerable to 1) misclassification, resulting in either data loss or inclusion of poor quality data, and 2) inconsistency in thresholds that are used to determine which scans should be included (both within and between studies). These issues are also problematic for the replicability of studies as it complicates

comparability of datasets (Poldrack et al., 2017). Hence there is a great need for automatized and unbiased QC assessments.

The present study introduces Qoala-T: A data-driven approach using a supervised-learning model to reduce rater bias and misclassification in manual QC procedures. Our aim was to test which supervised-learning model would best distinguish good quality FreeSurfer-processed scans from scans of insufficient quality by comparing three often used supervised-learning algorithms (see Methods for details). Although several studies have described automatic tools to assess the quality of T1-weighted MRI data (Alfaro-Almagro et al., 2016; Esteban et al., 2017; Pizarro et al., 2016; White et al., 2018; Woodard & Carley-Spencer, 2006) these procedures did not focus on automatic segmented data (e.g. as processed in FreeSurfer) but were performed early in the processing stream. This is in contrast to manual QC procedures that are commonly assessed on segmented scans. We propose that a data-driven supervised-learning model in combination with manual QC on a subset of the FreeSurfer-processed data could overcome many of the issues related to manual QC. The procedure introduced in the present paper moves beyond earlier studies on automated quality assessment for a number of reasons: 1) We are one of the first to apply automated QC procedures to a developmental dataset (see also Rosen et al., 2017; White et al., 2018). This is important, as these datasets are more susceptible to artifacts including motion, compared to adult samples (Power et al., 2012). 2) The input measures for the supervised-learning model consisted of automatic segmented data (i.e., using FreeSurfer) such that it matches data used in our manual QC procedure. These processed data measures were fed into the supervised-learning models. The rationale for using processed data measures is that these measures are our data of interest and hence it is their quality that is the most crucial for further

analysis. 3) Aside from within-sample cross-validation, we also applied the model on a novel independent dataset to test how well the model generalizes to other datasets. Hereby, we could demonstrate the potential of our current data-driven procedure, as our QC procedure could then be easily implemented elsewhere on a subset of data and extend to an unseen novel set of data. 4) To improve reproducibility we share a detailed description of our manual QC procedure that can be adapted to the specific needs of other datasets.

We propose that a full QC procedure using the Qoala-T tool would require manual QC only on a subset of data that is subsequently used as input for the supervised learning model. Such a combination of manual QC and automated QC may be a sufficient and accurate way of assessing the quality of sMRI scans in other datasets as well. In addition, we provide R code of all steps used in the development of the Qoala-T tool in order to advance the reproducibility of the current analysis. Taken together, the automated QC procedure proposed in this study could greatly reduce the time needed for QC and at the same time increase comparability of manual QC procedures. This is particularly relevant with the increasing size of datasets and heterogeneity of multi-site labs.

Materials and Methods

We used 784 structural MRI scans from the BrainTime dataset, which is a large accelerated longitudinal research project of normative development (Achterberg et al., 2016; Braams et al., 2015; Peters & Crone, 2017; Peters et al., 2016). We also used 112 structural MRI scans from an independent cross-sectional dataset that includes data from typically developing adolescents, adolescents with conduct disorder, and

with autism spectrum disorder (Aghajani et al., 2016; Aghajani et al., 2017; Klapwijk et al., 2016a; Klapwijk et al., 2017; Klapwijk et al., 2016b).

Participants

The BrainTime study included a total of 784 T1-weighted scans collected over three time points, with approximately 2 year intervals (see Table 1). At the first time point, 299 participants between ages 8-25 years participated in this MRI study. A high-resolution structural T1-weighted scan was available for 292 participants (142 males). Mean age at time point one was 14.05 (SD=3.67; range=8.01-25.95). IQ was estimated at time point one with two subtests (Similarities and Block Design) from the WISC-III (for participants < 16 years) and the WAIS-III (for participants ≥ 16 years) (Wechsler, 1991, 1997). Mean IQ was 109.39 (SD=10.97, range=80-143). At the second time point two years later, T1-weighted scans were available for 252 participants (121 males). Mean age at time point two was 16.15 (SD=3.54, range=9.92-26.61). At time point two, IQ was estimated using two different subtests (Vocabulary and Picture Completion) from the WISC-III and the WAIS-III. Mean IQ at time point two was 108.24 (SD=10.26, range=80-148). At the third time point, T1-weighted scans were available for 240 participants (115 males). Mean age at time point three was 18.16 (SD=3.68, range=11.94-28.72). The grand total of included data was 784 structural scans. Exclusion criteria prior to participation were current use of psychotropic medication or a psychiatric diagnosis. Participants and their parents (for participants younger than 18 years old) provided written informed consent. Participants (<18 years) received presents for their participation and their parents received payment for travel costs. Participants (≥18 years) received payment for participation.

The BESD (Brain, Empathy, Social Decision-making) dataset consisted of 112 participants (all males). This included T1-weighted scans of 52 participants with conduct disorder, 23 participants with autism spectrum disorder, and 37 typically developing controls, 15-19 years old (mean 17.06, SD=1.31, range=14.91-19.99). IQ was estimated using the WISC-III (for participants < 16 years) and the WAIS-III (for participants ≥ 16 years) with Vocabulary and Block Design subtests. Mean IQ was 98.65 (SD=9.36, range=75-128). Exclusion criteria for participation in this study were neurological abnormalities, a history of epilepsy or seizures, head trauma, left-handedness, and IQ lower than 75. For more details regarding recruitment and clinical characteristics see Aghajani et al. (2017) and Klapwijk et al. (2016a).

Both studies were approved by the Leiden University Medical Ethical Committee. A radiologist reviewed all anatomical scans and no clinically relevant abnormalities were detected.

Table 1. Demographic information for datasets

	BrainTime T1	BrainTime T2	BrainTime T3	BESD
N scans	292	252	240	112
Age in years (mean(SD))	14.05 (3.67)	16.15 (3.54)	18.16 (3.68)	17.06 (1.31)
Age range	8.01-25.95	9.92-26.61	11.94-28.72	14.91-19.99
Sex (males/females)	142/150	121/131	115/125	112/0
IQ (mean/SD)	109.39 (10.97)	108.24 (10.26)	*NA*	98.65 (9.36)
IQ range	80-143	80-148	*NA*	75-128

Note. SD = standard deviation; T1, T2, T3 = time point one, two, three

Imaging Data Acquisition and Processing

MRI scans of both samples were acquired on a Philips 3.0 T scanner, while using a standard whole-head coil. Data was collected on a Philips Achieva TX MR. A high-resolution 3D T1 anatomical scan was acquired a (TR = 9.76 ms, TE = 4.59 ms, 140 slices, voxel size = $0.875 \times 0.875 \times 1.2$ mm, FOV= $224 \times 177 \times 168$ mm).

Images were processed in FreeSurfer (v6.0.0). Tissue classification and anatomical labeling was performed on the basis of the T1-weighted MR image using the well-validated and well-documented FreeSurfer v6.0.0 software (http://surfer.nmr.mgh.harvard.edu/). In short, this software includes tools for non-brain tissue removal, cortical surface reconstruction, subcortical segmentation, cortical parcellation, and estimation of various measures of brain morphometry. Technical details of the automated reconstruction scheme are described elsewhere (Dale et al., 1999; Fischl et al., 1999). After pre-processing, measures of cortical thickness and surface area were computed based on the Desikan-Killiany-Tourville atlas (Desikan et al., 2006; Klein & Tourville, 2012). Anterior frontal and temporal poles were not included in the estimates of the outcome measures.

Manual Quality Control

In order to relate outcomes of the supervised-learning models to outcomes of the manual quality control, we first rated all FreeSurfer-processed scans manually. Five raters (E.K., F.K., M.M., S.P., L.W.) were trained to perform the manual QC procedures developed in our lab, see Supplemental Material X. The training set included 20 scans from an independent developmental dataset (not described). Next, the BrainTime dataset was randomized and split into five subsets. Each scan was rated as 1 = 'Excellent', 2 = 'Good', 3 = 'Poor', or 4 = 'Failed', based on a set of

specific criteria (e.g., affection by movement, missing brain areas in reconstruction, inclusion of dura or skull in reconstruction). A detailed, step-by-step explanation of the manual QC procedure can be found in the Supplementary Material X. To test reliability between the five raters, each subset of the current dataset included 10% overlap (i.e., 80 scans) such that these 80 scans were rated 5 times. In order to control for intra-rater drift, such as practice effects, each rater assessed half (N=40) of the overlapping scans at the start of the QC procedure, and the other half of the overlapping scans at the end of the QC procedure. Intra-class correlations were computed as an indication of inter-rater reliability.

Supervised-learning: the Qoala-T tool

This paper introduces a supervised-learning tool (Qoala-T) to assess manual quality ratings of FreeSurfer automatic segmented T1-weighted scans. Different supervised-learning models were compared. For these predictions, we used binary classification of included and excluded scans: manual rating scores 'Excellent', 'Good', and 'Poor' were considered as scans to be included and manual scores 'Failed' were considered exclusions. Our aims were to test 1) which supervised learning model best predicts scan quality, 2) whether manually rating of a subset of the data (e.g. 10%) would be able to predict the scan quality of the other 90% of the data, 3) which cutoff for exclusion should be used (i.e., whether scans that were manually rated as 'Poor' should be excluded in addition to 'Failed' scans) and 4) performance on a novel dataset (BESD sample). All statistical analyses were performed in R version 3.3.3 (R Core Team 2014). The development of the Qoala-T tool included a number of steps as described below.

Step 1: Model selection and hyper parameter tuning

First, we performed a preliminary evaluation to select the best performing supervised-learning model using 60% of the BrainTime data (see Figure 1A for model procedure).

Two of the most often used supervised-learning models in predicting MRI quality are support vector machine (SVM) (Esteban et al., 2017; Pizarro et al., 2016) and random forests modeling (RF) (Esteban et al., 2017). For the purpose of this paper we compared these models in addition to another tree-based supervised-learning model (gradient boosting machines; GBM) using the caret R library (Kuhn, 2008). SVM is a model in which input vectors are mapped into a high-dimensional space in which different categories are optimally separated by a hyperplane; new samples are then classified based on which side of the hyperplane they fall (Cortes & Vapnik, 1995). In RF models, a number of decision trees are generated for bootstrapped samples of the data, in which features are compared against a threshold. Classification of new data then occurs by popular vote over all trees (Breiman, 1996, 2001). GBM is also a tree-based statistical learning tool, but it differs from RF in that outcomes of previous trees influence subsequent trees by adjusting weights of misclassified instances (Freund & Schapire, 1995). These supervised-learning models each have a number of hyper-parameters that can be adjusted to optimize classification. To estimate the most optimal hyper-parameters, all models were tested using different combinations of hyper-parameter settings. Ultimately, we evaluated the best performing model using the most optimal hyper-parameter settings for that algorithm.

The analysis pipeline for this step is shown in Figure 1. First, the data was partitioned into a hold out and model selection dataset. Next, for each supervised-

learning model, the model selection data set was divided into five folds. As such, 5-fold nested cross-validation was repeated 1000 times (external cross validation, step 1A and 1B in Figure 1). Within each of these 5 folds, again 2-fold cross-validation was repeated 10 times for classifier selection and hyper-parameter tuning (internal cross validation). For each of the 1000 repetitions results were averaged other the 5 folds resulting in 1000 AUC estimates per supervised-learning model. The three models were compared using ANOVA and post-hoc t-tests. The hyper-parameters leading to the maximum average of the AUC scores in step 1C (internal cross validation) were selected for further analysis. To overcome issues related to imbalanced classes (a lower number of excluded scans than included scans) we used 'Random Over-Sampling Examples' (ROSE; Lunardon et al., 2014; Menardi & Torelli, 2014). ROSE is a bootstrap technique that generates synthetic balanced samples to improve estimations of binary classifiers that can be implemented within 'caret'.

Figure 1: Illustration of Step 1 (Model selection and hyper parameter tuning) and Step 2 (Validation on subset of data) for the development of the Qoala-T tool. Green indicates included scans based on manual ratings, red indicates scans manually rated to be excluded.

Step 2: Validation on subset of data

In the second step, we used the best supervised-learning model (SVM, RF or GBM) and the best hyper-parameter setting for that model selected in step 1, to evaluate the validity of the model. The aim of this step was to assess whether manual QC on only a subset of the scans (10%) would be sufficient to predict which scans should be excluded from the total sample. To do so we included 10% of the BrainTime data as the external cross validation training set and 90% of the dataset as the external test set, this step was repeated 10 times. Within these folds, 10 repeats of 2-fold internal

cross validation was performed for parameter tuning and classifier selection (see Figure 1B).

Class probability as an indicator of scan quality

Predicted outcome (inclusion or exclusion) and class probabilities were estimated for each scan. Class probabilities were used as an estimate of scan quality where an estimated scan quality above 50% indicated good quality while a probability lower than 50% indicated poor quality. The binary prediction model predicts 'exclude' when scans have poor quality below 50% and predicts 'include' for scans with good quality. As such, scan quality estimates closer to 50% may indicate higher uncertainty of the model to predict the binary outcome. To test the stability of the class probability estimates, validation was repeated 10 times, resulting in 10 folds (10-fold external cross-validation), such that all scans were part of the training set exactly once and part of the testing set 9 times. Within each fold output values (AUC, sensitivity, specificity and feature ranking) were assessed using 10 repetitions of 2-fold internal cross-validation (see Figure 1B). For each scan predicted classification and class probability estimates were used to test goodness of model fit.

Step 3: Where to draw the line - evaluation of QC threshold

In this step we evaluated the threshold for exclusion of scans. In previous steps scans manually rated as 'Failed' were excluded. However, perhaps a more stringent threshold where scans rated as 'Poor' are also labeled as 'exclude' would be a more sufficient cutoff. We repeated step 2 but this time labeled scans rated both as 'Poor' and 'Failed' as eligible for exclusion. The mean AUC values predicted by the 10-fold

cross validation were compared to the AUC values of the threshold model described above, using a one sided t-test.

Step 4: Evaluation on novel dataset

The model based on BrainTime data was tested on the BESD data (N = 112; see Participants section for details), of which all FreeSurfer-processed scans were manually rated. Secondly we assessed whether manual QC on only a subset of BESD data (10%) would be able to predict which scans should be excluded from the total sample. For this, we used 10-fold cross validation in which in each fold 10% of the scans were used as the training set (see step 2). As such, each scan was used in the training set once, and for each scan the outcome (include/exclude) was predicted 9 times.

Results

Correspondence of manual QC amongst raters

To test rater correspondence, 80 scans (10%) of the BrainTime dataset were rated by all five raters. Even though all raters followed the same protocol and were trained extensively, only 7.5% of the scans (i.e. 6 out of 80 scans) were rated in complete agreement. Of the 80 scans in this set, 86.3% of the scans (69 scans) were rated with an agreement of at least three raters (i.e. at least three raters gave the same score). For these scans, the most frequent rating was used as the final score. For the remaining scans with no majority rating, the rating of the coder with the highest reliability was used. Note that in these cases there was always one other rater who gave the same rating. The inter-coder reliability for the quality of the scans ranged from .38 to .72, with a mean inter-coder reliability of .53 (all $p < .001$), indicating moderate reliability

(Portney & Watkins, 2000). The results of the five ratings per scan can be observed in Figure 2. This figure illustrates the subjective aspect of manual QC assessment, even amongst well-trained raters, herewith highlighting the need for objective assessment.

Figure 2: A subset of 80 scans was subjected to manual QC by all five raters. Each pie represents one scan and each pie slice represents a rater where the color of that piece indicates the final rating given by a single rater (e.g. Excellent, Good, Poor, Failed).

Model selection and hyper parameter tuning

In step one the performance of the three supervised-learning models (SVM, RF, and GBM) was compared to test which of the three models was the most accurate in predicting manual quality ratings. The best supervised-learning model was selected based on the AUC values. The AUC results of the model comparison can be observed

in Figure 3. Analysis of variance showed that performance differed across the three algorithms (F(2, 2909) = 1270, p < .001), see results in Table 2 and Figure 3. A post hoc t-test showed that the AUC of the RF model was higher compared to both the GBM model (p < .001) as well as the SVM model (p < .001). Hence, the RF model was used in the next set of analyses, where the best performing hyper-parameter settings were 501 trees to grow (i.e., *ntree*) and 8 variables randomly sampled as candidates at each split (i.e., *mtry*).

Figure 3. Violin plot of area under the curve (AUC) values 1000 repetitions averaged over 5 folds for random forests (RF), gradient boosting machine (GBM) and support vector machine (SVM) models. The graphs show the spread of the AUC values for all folds and repetitions. Higher AUC values indicate better model fit. For instance, for GBM, there is a large spread in how well the model performed across all folds and repetitions, whereas for the RF model the mean AUC was higher and also showed less dispersion.

Table 2. Model comparison of supervised-learning models to predict manual quality ratings of FreeSurfer-processed T1-weighted BrainTime scans

	AUC		Sensitivity		Specificity	
	mean	SD	mean	SD	mean	SD
RF (random forests)	0.921	0.013	0.806	0.042	0.859	0.083
GBM (gradient boosting machine)	0.867	0.040	1.000	0.000	0.068	0.001
SVM (support vector machine)	0.880	0.005	0.573	0.014	0.944	0.002

Note. AUC = area under the curve; SD = standard deviation.

Validation using subset of data

The next set of analyses assessed how well the model was able to predict quality rating when only a subset of the sample (10%) would have had manual QC, to test the stability of the results this step was repeated 10 times. To do so we used 10-fold cross validation where in each fold 10% of the scans were used as the training set, in this way each scan was used in the training set once, and for each scan the outcome (include/exclude) was predicted 9 times. To estimate model accuracy these predictions were compared to the manual rating. The results of the 10 folds can be observed in Table 3. Mean AUC of the 10-folds was .977 (SD = .003). The results show that with 10 % of the data being manually assessed, whether a scan should be included or excluded in the remaining 90 % of the data quality can be predicted with both high sensitivity and specificity. The model provides not only a binary outcome (include/exclude), but also a probability score which indicates with how much certainty that scan was classified in the included or excluded group. This measure was used as an indication of scan quality (ranging from 0 to 100). Potentially these probability levels could be used to flag scans that would benefit from manual QC in a

novel dataset. Because each scan was predicted by the model nine times, there were nine of these inclusion/exclusion probabilities estimated for each scan, see Figure 4. These nine inclusion/exclusion probabilities were averaged to assess the predicted exclusion rate. As can be seen in Figure 4, scans with extremely high or extremely low scan quality estimates are more likely to be classified correctly than scans with average probability. In addition, scan quality ratings at the extreme ends showed more stable predictions across the 10 folds. The total number of falsely excluded scans was 18 out of 729 included scans (2.47 %), and the number of false negatives was 9 out of 55 excluded scans (16,4 %), see grey dots in Figure 4.

It could be the case that the AUC is simply high due to the imbalanced exclusion rate. That is, because of the low number of exclusions, it could be that the best model would simply predict to include all scans, which would result in relatively high levels of model prediction accuracy. In order to check the above chance model accuracy, we reassessed AUC by randomly shuffling exclusion labels (1000 permutations). AUC values of our model were considerably higher than the permuted AUC values (mean AUC = .502, SD = .0518, p < .001), meaning that the model performed much better than a model in which scans were randomly classified.

Table 3. 10-fold cross validation using subsets of BrainTime data to predict manual quality ratings of FreeSurfer-processed T1-weighted BrainTime scans

Fold	AUC	Sensitivity	Specificity
1	0.969	0.805	0.969
2	0.978	0.854	0.963
3	0.973	0.829	0.973
4	0.980	0.854	0.973
5	0.968	0.786	0.978
6	0.975	0.833	0.969
7	0.983	0.878	0.967
8	0.978	0.786	0.973
9	0.983	0.786	0.979
10	0.967	0.805	0.974
Mean	0.977	0.819	0.973
SD	0.003	0.039	0.006

Note. AUC = area under the curve; SD = standard deviation.

Classification

Figure 4. For each scan 9 values for predicted scan quality are displayed which we used to assessed scan quality (0-100) on the x-axis. Each value on the y-axis represents a scan ordered by mean scan quality. Lines between dots connect 9 values of predicted scan quality for a single scan. Scans with an average scan quality <50% are predicted to be excluded, and scan with an average scan quality >50% are predicted to be included. Colors indicate goodness of predicted classification (green

= 'correct include', red = 'correct exclude', grey = 'incorrect classification'). A total

of 27 scans out of a total of 784 scans (3.5%) were misclassified.

Class probabilities as indicator of scan quality

We compared mean class probabilities of the different manual rating categories for

scans that were predicted to be included and excluded by the model, since this

indicates with how much certainty the model was able to predict the binary outcome

(include/exclude). A total of 720 scans were rated as 'include' by both manual ratings

and the model (correct inclusions), and 37 scans were rated as 'exclude' by both the

manual ratings and the model (correct exclusions). There were 18 scans that were

excluded by the model but not by manual ratings (false excluded scans), and 9 scans

that were included by to the model but excluded according to manual ratings (false

included scans). These incorrectly classified scans could be related to errors in model

prediction, or errors in manual rating (e.g., due to fatigue). Hence, further

investigation of scan quality levels (i.e. with how much certainty the model places a

scan in the 'include' or 'exclude' category) could provide insights into the goodness

of model fit. The mean class probability levels for each scan estimated in step 2 are

displayed in Figure 5, in which the manual rating score is color-coded. Interestingly,

14 of the 18 'false' excluded scans were already manually rated as 'poor', and it could

therefore be that they are in fact scans that should be excluded (i.e., potentially an

error in manual ratings). In addition, the mean probability scores of scans for which

the manual and model rating differed was lower than when these were in

concordance, showing that the model was already less confident about these ratings.

That is, the mean scan quality score of false inclusions (red) was lower than the mean

scan quality of true inclusions (orange, yellow and green). Similarly, false excluded

scans (orange, yellow and green) have a higher mean scan quality compared to correct excluded scans (red). Note that these 4-category manual ratings were not included in model building, as only binary classification (include/exclude with cutoff between 3 'Poor' and 4 'Failed') were estimated.

Figure 5. Predicted mean scan quality are shown by manual rating category (y-axis), colors indicate manual ratings (green = 'Excellent', yellow = 'Good', orange = 'Poor', red = 'Failed'). Scans with a scan quality level < 50% are predicted to be excluded (right), and vice versa scans with scan quality levels > 50% are predicted to be included (left).

Variable importance for model prediction

Which variables are most important for the prediction of quality rating? The random forests model provides additional information about the importance of explanatory variables using marginal permutation. This method randomly permutes an explanatory variable (e.g. left caudate volume) and shows the mean decrease in prediction error that results from this permutation. If the explanatory variable is important for the accurate prediction of the model the predictive power of the model should systematically *decrease* model performance, while an unimportant variable would leave the predictive value unaffected (Breiman, 2001; Strobl et al., 2008). Variable importance values of the top 50 most important variables estimated by the random forests model for the BrainTime sample are summed in Figure 6. Mean importance variables across 10-fold cross validation on the full BrainTime sample showed highest importance values for left and right surface holes followed by left precentral, right entorhinal, and right precental thickness.

Figure 6. The permutation importance of explanatory variables for the prediction of scan quality. Only the 50 variables with the highest importance values are displayed. The importance measure on the x-axis represents the mean increase in classification error that results from randomly permuting that variable. Each boxplot shows the importance values of the 10 folds, ordered by their mean. Note that the importance value is a relative value that allows for a quick assessment of the relevance of a predictor for the outcome of interest.

Where to draw the line - evaluation of manual QC threshold

Finally, we investigated whether our original threshold of excluding scans which were rated as 'Failed' and including scans which were rated 'Excellent', 'Good' and 'Poor' was optimal, or whether additionally excluding scans rated as 'Poor' resulted in a better prediction (a more stringent threshold resulting in many more exclusions according to manual ratings, N=207). We reran the analyses in step 2 by assessing how well the model predicted manual inclusion of rating 'Excellent' & 'Good' and exclusion for both rating 'Poor' & 'Failed'. The 10-fold cross-validation on the full dataset showed that AUC values were significantly lower using this more stringent threshold compared to the original threshold (mean AUC = .85; t(16.919) = -40.242, p < .001). Now, a total of 149 scans were misclassified (see supplemental Figure 1), compared to 27 misclassifications with the original threshold. In addition, there were more scans classified with midrange (around 50) scan quality scores (see Supplementary Figure 1). This indicates that the original threshold was more optimal as it is more difficult to build a model that is able to distinguish scans that should be excluded using this more stringent threshold.

Evaluation on novel dataset

In the last set of analyses we tested the external validity of our approach by using the full BrainTime dataset as the training set and the BESD dataset as the testing set (N = 112). When comparing the model-based binary classification of scan quality with manual ratings, the model had an AUC value of 0.859, sensitivity of 0.571 and specificity of 0.967. Nine scans were falsely included and three scans falsely excluded (total 11%). In order to reduce this error to 5%, we would recommend to manually check scans rated with a scan quality between 30% and 70%. The majority of

misclassified scans will fall within these boundaries (see Figure 4 and Supplementary

Figure 2).

We also used 10-fold cross validation on the BESD dataset to check whether

rating of a subset of the data is sufficient to make reliable Qoala-T predictions. The

mean AUC of the ten folds was AUC= 0.953 (SD = 0.016); results of all ten folds can

be observed in Table 4. The mean number of falsely excluded scans was eight (SD =

5.51) (~7%) and mean number of falsely included was three (SD = 1.56) (~3%). The

high SD compared to the subset based model of the BrainTime data described earlier

indicates that the reliability of predictions probably increases with larger datasets.

Table 4. 10-fold cross validation using subsets of BESD data to predict manual
quality ratings of FreeSurfer-processed T1-weighted BrainTime scans

Fold	AUC	Sensitivity	Specificity
1	0.964	0.895	0.878
2	0.960	0.789	0.939
3	0.953	0.833	0.902
4	0.961	1.000	0.741
5	0.967	0.737	0.988
6	0.931	0.789	0.939
7	0.944	0.895	0.878
8	0.977	0.842	0.951
9	0.929	0.895	0.866
10	0.948	0.737	0.927
Mean	0.953	0.841	0.901
SD	0.016	0.082	0.068

Note. AUC = area under the curve; SD = standard deviation.

Discussion

In the current study we present Qoala-T as a tool to automatically evaluate quality of FreeSurfer-processed structural MRI data. The modest agreement between different manual raters confirmed the subjectivity of manual QC ratings. We then showed that the random forests (RF) model was the best performing supervised-learning model. Manually assessed MRI quality could be predicted with both high sensitivity and specificity, by using automatic segmented data of FreeSurfer. In addition, we demonstrate that when only a small amount of data is manually rated (e.g., 10%), the Qoala-T tool is able to effectively predict the quality of the remaining data. Furthermore, the Qoala-T tool can adequately predict the quality of unseen data. This automated procedure could therefore greatly help to reduce variability attached to manual QC (e.g., rater bias), thereby increasing the comparability of data quality between studies.

We looked for the best performing supervised-learning model that could distinguish FreeSurfer-processed scans that were manually rated with good quality from scans that were rated with insufficient quality. We therefore compared three often used supervised-learning algorithms (i.e., SVM: support vector machine, RF: random forests, GBM: gradient boosting machine). The model with the highest AUC values turned out to be the RF model. This is in line with findings from a recent study that compared SVM and RF models for predicting MRI quality using raw data (Esteban et al., 2017). Our results show that using the RF model, we can predict manually assessed MRI quality with both high sensitivity (0.82) and specificity (0.97). This model also performed reasonably well on a smaller unseen dataset with a sensitivity of 0.57 and specificity of 0.97. This implies that the Qoala-T tool might be useful in addition to or in substitution for manual QC in other MRI studies using

FreeSurfer. We therefore publicly share the Qoala-T source code through GitHub (https://github.com/Qoala-T/QC). The use of such a validated and systematic QC procedure is of great importance for structural MRI studies, as the inclusion of data containing artifacts has shown to lead to spurious results, especially in developmental and clinical populations (Ducharme et al., 2016; Reuter et al., 2015).

Results of the current study also reflect the subjectivity of manual QC. We could establish only moderate inter-rater agreement, similar to a recent study that compared two raters (Esteban et al., 2017). This was the case even though in the current study QC was performed by five well-trained raters that followed the same detailed procedure. Hence, the results of the manual QC underline the need for objective and reliable QC methods by means of automated procedures. The automated Qoala-T tool that we propose may help overcome limitations of manual QC, including the subjectivity of these procedures and the time needed to perform these.

In addition, this tool not considers raw image quality but the quality of subsequent segmentation, which is the data of interest in brain morphometric studies. A recent study found that image quality metrics (e.g., such as background voxels located outside the brain) derived from raw T1-weighted images indeed affect FreeSurfer derived cortical thickness and surface area (White et al., 2018). However, raw image quality metrics typically use information from noise outside the head (Esteban et al., 2017; Pizarro et al., 2016; White et al., 2018). By using FreeSurfer derived measures from inside the brain we increase the likelihood of detecting artifacts that might remain unnoticed when they do not alter characteristics of the air around the head (Pizarro et al., 2016).

Manual QC often includes a multipoint scale as outcome variable, the present study for instance used a 4-point scale. It can be challenging to establish the right

threshold for usable versus unusable scans. In the current study, we therefore compared two different cutoffs for exclusion: one in which only scans rated as 'Failed' were excluded and one in which both scans rated as 'Failed' and 'Poor' were excluded. The results show that the predictive power of the model using the second, more stringent, threshold was significantly lower and led to much more misclassifications than the original threshold. As such the method applied in this paper can help identify the most optimal cutoff for scan exclusion.

We also found that the most important measures that predicted data quality in the random forests model were the left and right surface holes. These surfaces holes are FreeSurfer outputs that reflect topological defects in the surface reconstruction. Although the number of holes is related to the quality of the topological reconstruction, small-scale defects may still result in a usable reconstruction (Dale et al., 1999). Interestingly, a recent study found that the Euler number, which is directly related to the number of surface holes (Dale et al., 1999), was very useful in predicting data quality (Rosen et al., 2017). In that study, the Euler number was highly correlated with manual QC ratings, could discriminate unusable from usable images with high accuracy, and could outperform other data quality measures such as those based on background voxels (Rosen et al., 2017). The predictions in the Qoala-T model are based on a combination of brain measures and not solely on surface hole measures, leading to increased model accuracy.

Practical Recommendations

The Qoala-T source code including instructions is publicly available through GitHub (https://github.com/Qoala-T/QC). Users can choose to either predict scan quality by using the BrainTime model (which does not necessarily requires manual QC) or to

predict scan quality by rating a subset (e.g., 10 %) of their own dataset. In both cases a Qoala-T score (ranging from 0 to 100) is computed for every individual scan. This score is based on class probability, where higher numbers indicate a higher chance of being a high quality scan, and thus that scan is more likely to be included. To reduce misclassification we would recommend to manually check scans rated with a scan quality between 30% and 70%, since many misclassified scans will fall within these boundaries (see Figure 4 and Supplementary Figure 2). The Qoala-T tool can also use a manually rated subset to predict the quality of the remaining data. In this case, we would recommend using sufficient manually rated scans (e.g., at least 50 scans) to be sure the model is fed with sufficient variability in scan quality (see for example the difference in variability in output variables between the folds in Tables 3 and 4). Finally, the Qoala-T tool could complement tools such as Mindcontrol (Keshavan et al., 2017) that could be used to edit images with fair quality scores but with errors in segmentation.

Limitations

Several limitations of the current study deserve consideration. First, in the current study we used data from one scanner site. Previous studies have shown that the accuracy of data quality predictions can vary across sites (Esteban et al., 2017; Rosen et al., 2017; White et al., 2018), but we currently do not know how large the variability of our tool will be across different scanners. Second, the Qoala-T tool requires FreeSurfer-processed scans, which limits use of this procedure to one software package that also requires extensive processing. However, FreeSurfer is a widely used platform; researchers that are already planning to use FreeSurfer can easily use the Qoala-T tool with only a few additional steps. Third, since the manual

QC rating is the outcome measure of our model, these manual scores will remain the principle QC rating. As such, we cannot distinguish the nature of misclassifications. These could be related to human error or classification error of the model.

Conclusions

In sum, we demonstrate that the Qoala-T tool is a useful tool to assess quality of MRI data that is automatically segmented using FreeSurfer. When a subset of data has been manually rated, the Qoala-T tool is able to predict the quality of the remaining data with high accuracy. Moreover, the quality of novel datasets can also be adequately predicted using the Qoala-T tool. We have made this tool publicly available, such that other researchers can use it as an add-on to manual QC in their studies. This could greatly increase comparability of data quality between studies.

Acknowledgements

The BrainTime study was funded by a starting grant of the European Research Council (ERC-2010-StG-263234 awarded to Eveline A. Crone). We are grateful to all participants and their parents for their willingness to participate. For the use of the BESD dataset, the authors are grateful to all participants and their parents, to the participating centers (De Jutters Palmhuis Forensic Psychiatric Unit, Forensic Center and Correctional Facility Teylingereind, Centrum Autisme Rivierduinen, Curium-LUMC), to Moji Aghajani, Romy Emmerig and Simone van Montfort for their help with data collection and to all involved in the design of this study (Moji Aghajani, Olivier Colins, Natasja van Lang, Arne Popma, Robert Vermeiren, Nic van der Wee). The BESD study was supported by the Netherlands Organization for Scientific Research (NWO) Grant No. 056-23-011.

References

Achterberg, M., Peper, J.S., van Duijvenvoorde, A.C., Mandl, R.C., & Crone, E.A.
(2016). Frontostriatal White Matter Integrity Predicts Development of Delay
of Gratification: A Longitudinal Study. *Journal of Neuroscience, 36*(6), 1954-
1961.

Aghajani, M., Colins, O.F., Klapwijk, E.T., Veer, I.M., Andershed, H., Popma, A.,
van der Wee, N.J., & Vermeiren, R.R. (2016). Dissociable relations between
amygdala subregional networks and psychopathy trait dimensions in conduct-
disordered juvenile offenders. *Human Brain Mapping, 37*(11), 4017-4033.

Aghajani, M., Klapwijk, E.T., van der Wee, N.J., Veer, I.M., Rombouts, S., Boon,
A.E., van Beelen, P., Popma, A., Vermeiren, R., & Colins, O.F. (2017).
Disorganized Amygdala Networks in Conduct-Disordered Juvenile Offenders
With Callous-Unemotional Traits. *Biological Psychiatry, 82*(4), 283-293.

Alfaro-Almagro, F., Jenkinson, M., Bangerter, N., Andersson, J., Griffanti, L., &
Douaud, G. (2016). UK Biobank Brain Imaging: Automated Processing
Pipeline and Quality Control for 100,000 subjects. *Organization for Human
Brain Mapping. Geneve, Switzerland*, 1877.

Backhausen, L.L., Herting, M.M., Buse, J., Roessner, V., Smolka, M.N., & Vetter,
N.C. (2016). Quality Control of Structural MRI Images Applied Using
FreeSurfer-A Hands-On Workflow to Rate Motion Artifacts. *Front Neurosci,
10*, 558.

Braams, B.R., van Duijvenvoorde, A.C., Peper, J.S., & Crone, E.A. (2015).
Longitudinal changes in adolescent risk-taking: a comprehensive study of
neural responses to rewards, pubertal development, and risk-taking behavior.
Journal of Neuroscience, 35(18), 7226-7238.

Breiman, L. (1996). Bagging predictors. *Machine learning, 24*(2), 123-140.

Breiman, L. (2001). Random forests. *Machine learning, 45*(1), 5-32.

Brown, T.T., Kuperman, J.M., Erhart, M., White, N.S., Roddey, J.C.,
Shankaranarayanan, A., Han, E.T., Rettmann, D., & Dale, A.M. (2010).
Prospective motion correction of high-resolution magnetic resonance imaging
data in children. *Neuroimage, 53*(1), 139-145.

Cortes, C., & Vapnik, V. (1995). Support-Vector Networks. *Machine learning, 20*(3),
273-297.

Dale, A.M., Fischl, B., & Sereno, M.I. (1999). Cortical surface-based analysis. I.
Segmentation and surface reconstruction. *Neuroimage, 9*(2), 179-194.

Desikan, R.S., Segonne, F., Fischl, B., Quinn, B.T., Dickerson, B.C., Blacker, D.,
Buckner, R.L., Dale, A.M., Maguire, R.P., Hyman, B.T., Albert, M.S., &
Killiany, R.J. (2006). An automated labeling system for subdividing the
human cerebral cortex on MRI scans into gyral based regions of interest.
Neuroimage, 31(3), 968-980.

Ducharme, S., Albaugh, M.D., Nguyen, T.V., Hudziak, J.J., Mateos-Perez, J.M.,
Labbe, A., Evans, A.C., Karama, S., & Brain Development Cooperative, G.
(2016). Trajectories of cortical thickness maturation in normal brain
development--The importance of quality control procedures. *Neuroimage,
125*, 267-279.

Esteban, O., Birman, D., Schaer, M., Koyejo, O.O., Poldrack, R.A., & Gorgolewski,
K.J. (2017). MRIQC: Advancing the automatic prediction of image quality in
MRI from unseen sites. *Plos One, 12*(9), e0184661.

Fischl, B., Sereno, M.I., & Dale, A.M. (1999). Cortical surface-based analysis. II: Inflation, flattening, and a surface-based coordinate system. *Neuroimage, 9*(2), 195-207.

Freund, Y., & Schapire, R.E. (1995). A desicion-theoretic generalization of on-line learning and an application to boosting. In P. Vitányi (Ed.), *Computational Learning Theory: Second European Conference, EuroCOLT '95 Barcelona, Spain, March 13–15, 1995 Proceedings* (pp. 23-37). Berlin, Heidelberg: Springer Berlin Heidelberg.

Gardner, E.A., Ellis, J.H., Hyde, R.J., Aisen, A.M., Quint, D.J., & Carson, P.L. (1995). Detection of degradation of magnetic resonance (MR) images: comparison of an automated MR image-quality analysis system with trained human observers. *Academic Radiology, 2*(4), 277-281.

Keshavan, A., Datta, E., I, M.M., Madan, C.R., Jordan, K., & Henry, R.G. (2017). Mindcontrol: A web application for brain segmentation quality control. *Neuroimage*.

Klapwijk, E.T., Aghajani, M., Colins, O.F., Marijnissen, G.M., Popma, A., van Lang, N.D., van der Wee, N.J., & Vermeiren, R.R. (2016a). Different brain responses during empathy in autism spectrum disorders versus conduct disorder and callous-unemotional traits. *Journal of Child Psychology and Psychiatry, 57*(6), 737-747.

Klapwijk, E.T., Aghajani, M., Lelieveld, G.J., van Lang, N.D.J., Popma, A., van der Wee, N.J.A., Colins, O.F., & Vermeiren, R. (2017). Differential Fairness Decisions and Brain Responses After Expressed Emotions of Others in Boys with Autism Spectrum Disorders. *Journal of Autism and Developmental Disorders, 47*(8), 2390-2400.

Klapwijk, E.T., Lelieveld, G.J., Aghajani, M., Boon, A.E., van der Wee, N.J., Popma, A., Vermeiren, R.R., & Colins, O.F. (2016b). Fairness decisions in response to emotions: a functional MRI study among criminal justice-involved boys with conduct disorder. *Social Cognitive and Affective Neuroscience, 11*(4), 674-682.

Klein, A., & Tourville, J. (2012). 101 labeled brain images and a consistent human cortical labeling protocol. *Front Neurosci, 6*, 171.

Kuhn, M. (2008). Building Predictive Models in R Using the caret Package. *Journal of statistical software, 28*(5), 1-26.

Lunardon, N., Menardi, G., & Torelli, N. (2014). ROSE: A Package for Binary Imbalanced Learning. *R Journal, 6*(1), 79-89.

Menardi, G., & Torelli, N. (2014). Training and assessing classification rules with imbalanced data. *Data Mining and Knowledge Discovery, 28*(1), 92-122.

Pardoe, H.R., Kucharsky Hiess, R., & Kuzniecky, R. (2016). Motion and morphometry in clinical and nonclinical populations. *Neuroimage, 135*, 177-185.

Peters, S., & Crone, E.A. (2017). Increased striatal activity in adolescence benefits learning. *Nat Commun, 8*(1), 1983.

Peters, S., Van Duijvenvoorde, A.C., Koolschijn, P.C., & Crone, E.A. (2016). Longitudinal development of frontoparietal activity during feedback learning: Contributions of age, performance, working memory and cortical thickness. *Dev Cogn Neurosci, 19*, 211-222.

Pizarro, R.A., Cheng, X., Barnett, A., Lemaitre, H., Verchinski, B.A., Goldman, A.L., Xiao, E., Luo, Q., Berman, K.F., Callicott, J.H., Weinberger, D.R., & Mattay, V.S. (2016). Automated Quality Assessment of Structural Magnetic

Resonance Brain Images Based on a Supervised Machine Learning Algorithm. *Front Neuroinform, 10*, 52.

Poldrack, R.A., Baker, C.I., Durnez, J., Gorgolewski, K.J., Matthews, P.M., Munafo, M.R., Nichols, T.E., Poline, J.B., Vul, E., & Yarkoni, T. (2017). Scanning the horizon: towards transparent and reproducible neuroimaging research. *Nat Rev Neurosci, 18*(2), 115-126.

Portney, L.G., & Watkins, M.P. (2000). *Foundations of clinical research: applications to practice*: Prentice Hall.

Power, J.D., Barnes, K.A., Snyder, A.Z., Schlaggar, B.L., & Petersen, S.E. (2012). Spurious but systematic correlations in functional connectivity MRI networks arise from subject motion. *Neuroimage, 59*(3), 2142-2154.

Reuter, M., Tisdall, M.D., Qureshi, A., Buckner, R.L., van der Kouwe, A.J., & Fischl, B. (2015). Head motion during MRI acquisition reduces gray matter volume and thickness estimates. *Neuroimage, 107*, 107-115.

Rosen, A.F.G., Roalf, D.R., Ruparel, K., Blake, J., Seelaus, K., Villa, L.P., Ciric, R., Cook, P.A., Davatzikos, C., Elliott, M.A., Garcia de La Garza, A., Gennatas, E.D., Quarmley, M., Schmitt, J.E., Shinohara, R.T., Tisdall, M.D., Craddock, R.C., Gur, R.E., Gur, R.C., & Satterthwaite, T.D. (2017). Quantitative assessment of structural image quality. *Neuroimage, 169*, 407-418.

Strobl, C., Boulesteix, A.L., Kneib, T., Augustin, T., & Zeileis, A. (2008). Conditional variable importance for random forests. *BMC bioinformatics, 9*(1), 307.

Van Dijk, K.R., Sabuncu, M.R., & Buckner, R.L. (2012). The influence of head motion on intrinsic functional connectivity MRI. *Neuroimage, 59*(1), 431-438.

Wechsler, D. (1991). *The Wechsler Intelligence Scale for Children-III*. San Antonio, TX: The Psychological Corporation.

Wechsler, D. (1997). *Wechsler Adult Intelligence Scale–III*. San Antonio, TX: The Psychological Corporation.

White, T., Jansen, P.R., Muetzel, R.L., Sudre, G., El Marroun, H., Tiemeier, H., Qiu, A., Shaw, P., Michael, A.M., & Verhulst, F.C. (2018). Automated quality assessment of structural magnetic resonance images in children: Comparison with visual inspection and surface-based reconstruction. *Human Brain Mapping, 39*(3), 1218-1231.

Woodard, J.P., & Carley-Spencer, M.P. (2006). No-reference image quality metrics for structural MRI. *Neuroinformatics, 4*(3), 243-262.