Beyond Core Object Recognition: Recurrent processes account for object recognition under occlusion

Karim Rajaei[1], Yalda Mohsenzadeh[2], Reza Ebrahimpour[3,1] *, Seyed-Mahdi Khaligh-Razavi[2,4] *

[1]School of Cognitive Sciences (SCS), Institute for Research in Fundamental Sciences (IPM), Niavaran, P.O. Box 19395-5746, Tehran, Iran

[2]Computer Science and AI Lab (CSAIL), MIT, Cambridge, MA, US

[3]Cognitive Science Research Lab., Department of Electrical and Computer Engineering, Shahid Rajaee Teacher Training University, P.O. Box 16785-163, Tehran, Iran

[4]Department of Brain and Cognitive Sciences, Cell Science Research Center, Royan Institute for Stem Cell Biology and Technology, ACECR, Tehran, Iran

*Correspondence to:

S-M., Khaligh-Razavi, skhaligh@mit.edu

R., Ebrahimpour, ebrahimpour@ipm.ir

Abstract

Core object recognition, the ability to rapidly recognize objects despite variations in their appearance, is largely solved through the feedforward processing of visual information. Deep neural networks are shown to achieve human-level performance in these tasks, and explain the primate brain representation. On the other hand, object recognition under more challenging conditions (i.e. beyond the core recognition problem) is less characterized. One such example is object recognition under occlusion. It is unclear to what extent feedforward and recurrent processes contribute in object recognition under occlusion. Furthermore, we do not know whether the **conventional** deep neural networks, such as AlexNet, which were shown to be successful in solving core object recognition, can perform similarly well in problems that go beyond the core recognition. Here, we characterize neural dynamics of object recognition under occlusion, using magnetoencephalography (MEG), while participants were presented with images of objects with various levels of occlusion. We provide evidence from multivariate analysis of MEG data, behavioral data, and computational modelling, demonstrating an essential role for recurrent processes in object recognition under occlusion. Furthermore, the computational model with local recurrent connections, used here, suggests a mechanistic explanation of how the human brain might be solving this problem.

Author Summary

In recent years, deep-learning-based computer vision algorithms have been able to achieve human-level performance in several object recognition tasks. This has also contributed in our understanding of how our brain may be solving these recognition tasks. However, object recognition under more challenging conditions, such as occlusion, is less characterized. Temporal dynamics of object recognition under occlusion is largely unknown in the human brain. Furthermore, we do not know if the previously successful deep-learning algorithms can similarly achieve human-level performance in these more challenging object recognition tasks. By linking brain data with behavior, and computational modeling, we characterized temporal dynamics of object recognition under occlusion, and proposed a computational mechanism that explains both behavioral and the neural data in humans. This provides a plausible mechanistic explanation for how our brain might be solving object recognition under more challenging conditions.

1. Introduction

There is abundance of feedforward, and recurrent connections in the primate visual cortex (Lamme et al., 1998, Sporns and Zwi, 2004). The feedforward connections form a hierarchy of cortical areas along the visual pathway, playing a significant role in various aspects of visual object processing (Felleman and Van Essen, 1991). However, the role of recurrent connections in visual processing have remained poorly understood (Lamme et al., 1998, Lamme and Roelfsema, 2000, Gilbert and Li, 2013, Kafaligonul et al., 2015, Klink et al., 2017).

Several complementary behavioral, neuronal, and computational modeling studies have confirmed

that a large class of object recognition tasks called "core recognition" are largely solved through a

single sweep of feedforward visual information processing (DiCarlo and Cox, 2007, DiCarlo et

al., 2012, Khaligh-Razavi and Kriegeskorte, 2014, Yamins et al., 2014, Cadieu et al., 2014, Wen

et al., 2018). Object recognition is defined as the ability to differentiate an object's identity or

category from many other objects having a range of identity-preserving changes (DiCarlo and Cox,

2007). Core recognition refers to the ability of visual system to rapidly recognize objects despite

variations in their appearance, e.g. position, scale, and rotation (DiCarlo and Cox, 2007).

Object recognition under challenging conditions, such as high variations (Ghodrati et al., 2014,

Karimi-Rouzbahani et al., 2017), object deletion and occlusion (Rensink and Enns, 1998, Nielsen

et al., 2006, Wyatte et al., 2012, O'Reilly et al., 2013, Wyatte et al., 2014, Kosai et al., 2014, Choi

et al., 2016, Spoerer et al., 2017, Tang et al., 2018), and crowding (Livne and Sagi, 2011, Manassi

and Herzog, 2013, Clarke et al., 2014) goes beyond the core recognition problem, which is thought

to require more than the feedforward processes. Object recognition under occlusion is one of the

key challenging conditions that occurs in many of the natural scenes we interact with every day.

How our brain solves object recognition under such challenging condition is still an open question.

Object deletion and object occlusion are shown to have different temporal dynamics (Johnson and

Olshausen, 2005). While object deletion has been studied before in humans (Nielsen et al., 2006,

Wyatte et al., 2012, O'Reilly et al., 2013, Wyatte et al., 2014, Tang et al., 2014, Tang et al., 2018),

we do not know much about the dynamics of object processing under the challenging condition of

occlusion; in particular there has not been any previous MEG study of occluded object processing,

with multivariate pattern analyses approach, linking models with both brain and behavior.

Furthermore, as opposed to the core object recognition problem, where the **conventional**

feedforward CNNs are shown to explain brain representations (Khaligh-Razavi and Kriegeskorte,

2014, Yamins et al., 2014, Cadieu et al., 2014, Wen et al., 2018), we do not yet have computational

models that successfully explain human brain representation and behavior under this challenging

condition [Regarding feedforward CNNs, also see (Eberhardt et al., 2016, Rajalingham et al.,

2018) where CNNs cannot fully explain patterns of human behavioral decisions].

Few fMRI studies have investigated how and where occluded objects are represented in the human

brain (Rauschenberger et al., 2006, Hulme and Zeki, 2007, Hegdé et al., 2008, Ban et al., 2013,

Erlikhman and Caplovitz, 2017). Hulme and Zeki (2007) found that faces and houses in fusiform

face area (FFA) and lateral occipital cortex (LOC) are represented similar with and without

occclusion. Ban et al. (2013) used topographic mapping with simple geometric shapes (e.g.

triangles), finding that the occluded portion of the shape is represented topographically in human

V1 and V2, suggesting the involvement of early visual areas in object completion. A more recent

study showed that the early visual areas may only code spatial information about occluded objects,

but not their identity, and higher-order visual areas instead represent object-specific information,

such as category or identity of occluded objects (Erlikhman and Caplovitz, 2017). While these

studies provide insights about object processing under occlusion, they do not provide any

information about the temporal dynamics of these processes, and whether object recognition under

occlusion requires recurrent processing.

Our focus in this study is understanding the temporal dynamics of object recognition under

occlusion; and whether recurrent connections are critical in processing occluded objects? If yes,

in what form are they engaged (e.g. long range feedback or local recurrent?), and how much is

their contribution compared to the contribution of the feedforward visual information? We

constructed a controlled image set of occluded objects, and used the combination of multivariate

pattern analyses (MVPA) of MEG signals, computational modeling, backward masking, and

behavioral experiments to characterize representational dynamics of object processing under

occlusion, and to determine unique contributions of feedforward and recurrent processes.

Here, we provide five complementary evidence for the contribution of recurrent processes in

recognizing occluded objects. *First*, MEG decoding time courses show that onset and peak for

occluded objects—without backward masking—are significantly delayed compared to when the

whole object is presented without occlusion. The timing of visual information plays an important

role in discriminating the processing stages (i.e. feedforward vs. recurrent) with early brain

responses reaching higher visual areas being dominantly feedforward and the delayed responses

being mainly driven by recurrent processes (Felleman and Van Essen, 1991, Lamme and

Roelfsema, 2000, Thorpe and Fabre-Thorpe, 2001, Liu et al., 2009, Khaligh-Razavi et al., 2015,

Grootswagers and Carlson, 2015, Kaneshiro et al., 2015, Mohsenzadeh et al., 2018). *Second*, time-

time decoding analysis (i.e. temporal generalization) suggests that occluded object processing goes

through a relatively long sequence of stages that involve recurrent interaction—likely local

recurrent. *Third*, the results of backward masking demonstrate that while the masking significantly

impairs both human categorization performances and MEG decoding performances under

occlusion, it has no significant effect on object recognition when objects are not occluded. *Fourth*,

results from two computational models showed that a **conventional** feedforward CNN (AlexNet)

that could achieve human-level performance in the no-occlusion condition, performed

significantly worse than humans when objects were occluded. Additionally, the feedforward CNN

could only explain the human MEG data when objects were presented without occlusion; but failed

to explain the MEG data under the occlusion condition. In contrast, a hierarchical CNN with local

recurrent connections (recurrent ResNet) achieved human-level performance and the

representational geometry of the model was significantly correlated with that of the MEG neural

data when objects were occluded. Finally, we quantified contributions of feedforward and

recurrent processes in explaining the neural data, showing a significant unique contribution only

for the recurrent processing under occlusion. These findings demonstrate significant involvement

of recurrent processes in occluded object recognition, and improve our understand of object

recognition beyond the core problem. To our knowledge this is the first MVPA study of MEG data

linking feedforward and recurrent deep neural network architectures with both brain and behavior

to investigate object recognition under occlusion in humans.

2. Results

We used multivariate pattern analysis (MVPA) of MEG data to characterize representational

dynamics of object recognition under occlusion (Carlson et al., 2013, Cichy et al., 2014, Isik et al.,

2014, Grootswagers et al., 2017). MEG along with MVPA allows for a fine-grained investigation

of the underlying object recognition processes across time (Grootswagers et al., 2017, Contini et

al., 2017). Subjects (N=15) were presented with images of objects with varying levels of occlusion

(i.e., 0% = no-occlusion, 60% and 80% occlusion; Figure 1b). We also took advantage of the

visual backward masking (Breitmeyer and Öğmen, 2006) as a tool to further control the

feedforward and feedback flow of visual information processing. In the MEG experiment, each

stimulus was presented for 34 ms [2 × screen frame rate (17ms) = 34ms], followed by a blank-

screen ISI, and then in half of the trials followed by a dynamic mask (Figure S1). We extracted

and pre-processed MEG signals from -200 ms to 700 ms with regard to the stimulus onset. To

calculate pairwise discriminability between objects, a support vector machine (SVM) classifier

was trained and tested at each time point (Figure 1a). MEG decoding time-courses show the

pairwise discriminability of object images averaged across individuals. We first present the MEG

results of the no-mask trials. After that in section 2.3 we discuss the effect of backward masking.

154 **2.1. Object recognition is significantly delayed under occlusion**

We used pairwise decoding analysis of MEG signals to measure how object information evolves

over time (Figure 1a). Significantly above-chance decoding accuracy means that objects can be

discriminated using the information available from the brain data at that time-point. The decoding

onset latency indicates the earliest time that the object-specific information becomes available and

the peak decoding latency is the time-point wherein we have the highest object-discrimination

performance.

We found that object information emerges significantly later under occlusion compared to the no-

occlusion condition. Object decoding under no-occlusion had an early onset latency at 79ms [±3

ms standard deviation (SD)] and was followed by a sharp increase reaching its maximum accuracy

(i.e. peak latency) at 139±1 ms (Figure 1c). This early and rapidly evolving dynamic is well

consistent with the known time-course of the feedforward visual object processing [see Figure S2

and (Liu et al., 2009, Carlson et al., 2013, Cichy et al., 2014)].

However, when objects were partially occluded (i.e. 60% occlusion), decoding time-courses were

significantly slower than the 0% occlusion condition: the onset for decoding accuracy was at

123±15 ms followed by a gradual increase in decoding accuracy until it reached its peak decoding

accuracy at 199±3 ms (Figure 1c). The difference between onset latencies and peak latencies were

both statistically significant with p<10^{-4} (two sided sign-rank test). Analysis of the behavioral

response times was also consistent with the MEG object decoding curves, showing a significant

delay in participants' response times when increasing the occlusion level (Figure S3). The slow

temporal dynamics of object recognition under occlusion and the observed significant temporal

delay in processing occluded objects compared to un-occluded (0% occlusion) objects do not

match with a fully feedforward account of visual information processing. Previous studies have

shown that first responses to visual stimuli that contain category-related information can reach

higher visual areas in as little as 100 ms. (Thorpe, 2009, Liu et al., 2009, Cichy et al., 2016b).

Therefore, the observed late onset and the significant delay in peak and onset of the decoding

accuracy for occluded objects, may be best explained by the engagement of recurrent processes.

182

183 **Figure 1. Temporal dynamics object recognition under various levels of occlusion**. **(a)** Multivariate pattern

184 classification of MEG data. We extracted MEG signals from -200 ms to 700 ms relative to the stimulus onset. At each

185 time point (ms resolution), we computed average pairwise classification accuracy between all exemplars. **(b)** Sample

186 images of occluded and un-occluded (0% occlusion) objects. There are four object categories: camel, deer, car, and

187 motor. Images are occluded at 0% (no-occlusion), 60%, and 80% occlusion. **(c)** Time courses of pairwise decoding

188 accuracies for the three different occlusion levels (without backward masking) averaged across 15 subjects. Thicker

189 lines indicate a decoding accuracy significantly above chance (right-sided signrank test, FDR corrected across time,

p < 0.05), showing that MEG signals can discriminate between object exemplars. Shaded error bars represent standard

error of the mean (SEM). The two vertical shaded areas show the time from onset to peak, for 60% occluded and 0%

occluded objects, which are largely non-overlapping. The onset latency is 79±3 ms (mean ± SD) in the no-occlusion

condition; and 123±15 ms in the 60% occlusion; the difference between onset latencies is significant (p<10⁻⁴, two-

sided signrank test). Arrows above the curves indicate peak latencies. The peak latencies are 139±1ms and 199±3ms

for the 0% occluded and partially occluded (60%) objects respectively. The difference between the peak latencies is

also statistically significant (p < 10⁻⁴).

Under 80% occlusion, the MEG decoding results did not reach significance [right-sided signrank

test, FDR corrected across time, p < 0.05] (Figure 1c). However, behaviorally, human subjects still

performed above-chance in object categorization even under 80% occlusion (Figure 5d). This

discrepancy might be due to MEG acquisition noise, whereas the behavioral categorization task is

by definition free from that type of noise.

While the MEG and behavioral data have different levels of noise, we showed that within the MEG

data itself, presented images with different levels of occlusion (0%, 60%, 80%) did not differ in

terms of their level of MEG noise (Figure S4). Thus, the difference in decoding performance

between different levels of occlusion cannot be simply explained by the difference in noise.

Furthermore, patterns of cross-decoding analyses (Figure 3) demonstrates that the observed delay

in peak latency under occlusion cannot be simply explained by a difference in signal strength.

2.2. Time-time decoding analysis for occluded objects suggests a

neural architecture with recurrent interactions

We performed time-time decoding analysis measuring how information about object

discrimination generalizes across time (Figure 2a). Time-time decoding matrices are constructed

by training a SVM classifier at a given time point and testing its generalization performance at all

other time-points (see Methods). The pattern of temporal generalization provides useful

information about the underlying processing architecture (King and Dehaene, 2014).

We were interested to see if there are differences between temporal generalization patterns of

occluded and un-occluded objects. Different processing dynamics may lead to distinct patterns of

generalization in the time-time decoding matrix [see (King and Dehaene, 2014) for a review]. For

example, a narrow diagonal pattern suggests a hierarchical sequence of processing stages wherein

information is sequentially transferred between neural stages. This hierarchical architecture is well

consistent with the feedforward account of neural information processing across the ventral visual

pathway. On the other hand, a time-time decoding pattern with off-diagonal generalization

suggests a neural architecture with recurrent interactions between processing stages [see Figure 5

in (King et al., 2016)].

The temporal generalization pattern under no-occlusion (Figure 2b) indicated a sequential

architecture, without an off-diagonal generalization until its early peak latency at 140 ms. This is

consistent with a dominantly feedforward account of visual information processing. There was

some off-diagonal generalization after 140 ms, however that was not of interest here, because the

ongoing recurrent activity after the peak latency (as shown in Figure 1c) did not carry any

information that further improves pairwise decoding performance of 0% occluded objects. On the

other hand, when objects were occluded, the temporal generalization matrix (Figure 2c) indicated

a significantly delayed peak latency at 199ms with extensive off-diagonal generalization before

reaching its peak. In other words, for occluded objects, we see a discernible pattern of temporal

generalization, which is characterized by 1) a relatively weak early diagonal pattern of the

decoding accuracy during [100 150]ms with limited temporal generalization, which is in contrast

with the high accuracy decoding of 0% occluded objects in the same time period. 2) A relatively

late peak decoding accuracy with a wide generalization pattern around 200ms. This pattern of

temporal generalization can be simulated by a hierarchical neural architecture with local recurrent

interactions within the network [Figure 5 of (King et al., 2016)]

We also performed sensorwise decoding analysis to explore spatio-temporal dynamics of object

information. To calculate sensorwise decoding, pairwise decoding analysis was conducted on 102

neighboring triplets of MEG sensors (2 gradiometers and 1 magnetometer in each location)

yielding a decoding map of brain activity at each time-point. The sensorwise decoding patterns

indicated the approximate locus of neural activity: in particular, we see that for both 0% occlusion

(supp. movie 1) and 60% occlusion (supp. movie2) conditions, during the onset of decoding as

well as the peak decoding time, the main source of object decoding is in the left posterior-temporal

sensors. From [110ms to 200ms], the peak of decoding accuracy remains locally around the same

sensors, suggesting a sustained local recurrent activity.

(a) Extract sensor activation

N-1 raw pattern vectors at time t_x

N^{th} raw pattern vector at time t_y

Time-Time decoding matrix

Train a SVM

Test

$\cdot$ (t_x, t_y)

-100 ms   700 ms

(b) 0% Occlusion

(c) 60% Occlusion

Decoding accuracy (%)

Plausible Architecture for Onset-to-Peak

(d) Difference

Plausible Architecture for Onset-to-Peak

Feedforward

Recurrent

Figure 2. Temporal generalization patterns of object recognition with and without occlusion. **(a)** Time-time decoding analysis. The procedure is similar to the calculations of pairwise decoding accuracies explained in Figure 1, except that here the classifier is trained at a given time-point, and then tested at all time-points. In other words, for each pair of time points (t_x, t_y), a SVM classifier is trained by N-1 MEG pattern vectors at time t_x and tested by the remaining one pattern vector at time t_y, resulting to an 801x801 time-time decoding matrix. **(b-c)** Time-time decoding accuracy and plausible processing architecture for no-occlusion and 60% occlusion. The results are for MEG trials without backward masking. Horizontal axis indicates testing times and vertical axis indicates training times. Color bars represent percent of decoding accuracies (chancel level = 50%); please note that in the time-time decoding matrices, the color bar ranges for 0% occlusion and 60% occlusion are different. Within the time-time decoding matrices, significantly above chance decoding accuracies, are surrounded by the white dashed contour lines (right-sided signrank test, FDR corrected across the whole 801x801 decoding matrix, $p < 0.05$). For each time-time decoding matrix, we also show the plausible processing architecture corresponding to it. These are derived from the observed patterns of temporal generalization from onset-to-peak decoding (shown by the gray dashed rectangles) [see Figure 5 of (King et al., 2016)]. Generalization patterns for the no-occlusion condition are consistent with a hierarchical feedforward architecture; whereas, for the occluded objects (60%) the temporal generalization patterns are consistent with a hierarchical architecture with recurrent connections. **(d)** Difference in time-time decoding accuracies between no-occlusion and occlusion conditions. Significantly above zero differences are surrounded by the white dashed contour lines (right-sided signrank test, FDR corrected across [80-240]ms matrix at $p < 0.05$).

276 **Generalization across time and occlusion levels:** Time-time decoding analyses can be further

277 expanded by training the classifiers in one condition (e.g. occluded) and testing their ability to

278 generalize to the other condition (e.g. un-occluded). The resulting pattern of generalization across

279 time and occlusion level provides diagnostic information about the organization of brain processes

280 (Figure 3). In particular, this can provide us with further evidence as to whether the observed

281 decoding results under occlusion is due to changes in activation intensity (e.g. weakening of the

282 signal), or a genuine difference in latency. As shown in ((King and Dehaene, 2014), Figure 4) each

283 of these two come with distinct cross-condition generalization matrices. A change of signal

284 intensity leads to asymmetric generalizations across conditions because it can be more efficient to

285 train a decoder with relatively high signal-to-noise ratio (SNR) data (e.g. 0% occlusion) and

286 generalize it to low SNR data (e.g. 60% occlusion) rather than vice versa. However, in Figure 3,

287 we do not see such asymmetry in decoding strengths, instead we observe different generalization

288 patterns that are more consistent with changes in the speed of information processing (i.e. latency).

289 More specifically, when the classifier is trained with 0% occlusion and tested on 60% occlusion

290 (upper-left matrix in Figure 3a) the generalization pattern is shifted to the above diagonal and vice

291 versa when trained with 60% occlusion and tested on 0% occlusion (the lower-right matrix).

Figure 3. Generalization across time and occlusion levels. (a) The classifier is trained on an occlusion level (e.g.

0% occlusion) and tested on the other occlusion level (e.g. 60% occlusion). Time-points with significant decoding

accuracy are shown inside the dashed contours (right-sided signrank test, FDR-corrected across time, p<0.05). The

contour of significant time-points has a shift towards the upper side of the diagonal when the classifier is trained with

0% occlusion and tested on 60% occlusion (i.e. 63% of significant time points are above the diagonal) whereas in the

lower right matrix we see the opposite pattern (66% of significant time points are located below the diagonal). **(b)**

The two color maps below the decoding matrices show the difference between the two decoding matrices located

above them.

2.3. Backward masking significantly impaired object recognition only under occlusion

Visual backward masking has been used as a tool to disrupt the flow of recurrent information processing, while feedforward processes are left relatively intact (Lamme and Roelfsema, 2000, Lamme et al., 2002, Bacon-Macé et al., 2005, Breitmeyer and Öğmen, 2006, Fahrenfort et al., 2007, Serre et al., 2007, Ghodrati et al., 2014). Our time-time decoding results (Figure 4d 0% occluded) additionally supports the recurrent explanation of backward masking: off-diagonal generalization in time-time decoding matrices are representative of recurrent interactions; these off-diagonal components disappear when backward masking is present.

Considering the recurrent explanation of the masking effect, we further examined how the recurrent processes contribute in object processing under occlusion. We found that backward masking significantly reduced both MEG decoding accuracy time-course (Figure 4b) and subjects' behavioral performances (Figure 5d), only when objects were occluded. When occluded objects are masked, the MEG decoding time-course from 185ms to 237ms is significantly lower than the decoding time-course when in no-mask condition (Figure 4b, black horizontal lines; two-sided signrank test, FDR-corrected across time $p < 0.05$). On the other hand, for un-occluded objects, we did not find any significant difference between decoding time-courses of the mask and no-mask conditions (Figure 4a).

Consistent with the MEG decoding results, while the masking significantly reduced behavioral categorization performances when objects were occluded, it had no significant effect on the categorization performance for the un-occluded objects (Figure 5d) [two-sided signrank test].

323 Particularly, the backward masking removed the late MEG decoding peak (around 200ms) under

324 occlusion (Figure 4f) likely due to disruption of later recurrent interactions.

325   Taken together, we demonstrated that visual backward masking, which is suggested to disrupt

326 recurrent processes (Lamme and Roelfsema, 2000, Lamme et al., 2002, Breitmeyer and Öğmen,

327 2006, Fahrenfort et al., 2007, Macknik and Martinez-Conde, 2007), significantly impairs object

328 recognition only under occlusion. On the other hand, masking did not affect object processing

329 under no occlusion, when information from the feedforward sweep is shown to be sufficient for

330 object recognition. Thus, providing further evidence for the essential role of recurrent processes in

331 object recognition under occlusion.

332

333

Figure 4. Backward masking significantly impairs object decoding under occlusion, but has no significant effect on object decoding under no occlusion. (a) Time-courses of the average pairwise decoding accuracies under no-occlusion. Thicker lines indicate significant time-points (right-sided signrank test, FDR corrected across time, p < 0.05). Shaded error bars indicate SEM (standard error of the mean). Downward pointing arrows indicate peak decoding accuracies. There is no significant difference between decoding time-courses for mask and no-mask trials, under no-occlusion **(b)** Time-courses of the average pairwise decoding under 60% occlusion (for 80% occlusion see Figure S5). Under occlusion, the decoding onset latency for the no-mask trials is 123±15ms, with its peak decoding accuracy at 199±3ms; whereas the time-course for the masked trials does not reach statistical significance, demonstrating that backward masking significantly impairs object recognition under occlusion. Black horizontal lines below the curves show the time-points at which the two decoding curves are significantly different. This is particularly evident around the peak latency of the no-mask trials [from 185ms to 237ms]. **(c, d)** Time-time decoding matrices of 60% occluded and (0%) un-occluded objects with and without backward masking. Horizontal axes indicate testing times and the vertical axes indicate training times. Color bars show percent of decoding accuracies. Please note that in the time-time decoding matrices, the color bar ranges for 0% occlusion and 60% occlusion are different. Significantly above chance decoding accuracies, are surrounded by the white dashed contour lines (right-sided signrank test, FDR corrected across the whole 801x801 decoding matrix, p < 0.05). **(f)** Difference between time-time decoding matrices with and without backward masking. Statistically significant differences are surrounded by the black dotted contours (right-sided signrank test, FDR corrected across time at p < 0.05). There are significant differences between mask and no-mask only under occlusion.

2.4. How well does a computational model with local recurrent interactions explain neural and behavioral data under occlusion?

Recent studies have shown that convolutional neural networks (CNNs) achieve human-level performance and explain neural data under non-challenging conditions—also referred to as the

core object recognition (DiCarlo and Cox, 2007, Khaligh-Razavi and Kriegeskorte, 2014, Yamins

et al., 2014). Here, we first examined whether such feedforward CNNs (i.e. AlexNet) can explain

the observed human neuronal and behavioral data in a challenging object recognition task when

objects are occluded. The model accuracy was evaluated by the same object recognition task used

to measure human behavioral performance (Figure S6). A multiclass linear SVM classifier was

trained on images from two occlusion levels and tested on the left-out occlusion level, using

features from the penultimate layer of the model (e.g. 'fc7' in AlexNet). The classification task

was to categorize images into car, motor, deer, or camel. This procedure was repeated for 15 times,

and the mean categorization performance is reported here.

We, additionally, used representational similarity analysis (RSA) to assess model's performance

in explaining the human MEG data. RSA correlates time-resolved human MEG representations

with that of the model, on the same set of stimuli. First, dissimilarity matrices (RDMs) were

separately calculated for the MEG signals and the model. The model RDM were then correlated

with MEG RDMs across time (Figure 5a; also see Methods).

We found that in the no-occlusion condition, the feedforward CNN achieved human-level

performance and CNN representations were significantly correlated with the MEG data.

Significant correlation between the model and MEG representational dissimilarity matrices

(RDMs) started at ~90ms after the stimulus onset and remained significant for several hundred

milliseconds with two peaks at 150ms and 220ms (Figure 5b). However, the feedforward CNNs

(i.e. AlexNet and the purely feedforward version of HRRN (HRRN with readout stage 0)) failed

to explain human MEG data when objects were occluded. And the model performance was

significantly lower than that of human in the occluded object recognition task.

We were wondering if a model with local recurrent connections could account for object

recognition under occlusion. Inspired by recent advancements in deep convolutional neural

networks (He et al., 2016a, He et al., 2016b, Liao and Poggio, 2016, Veit et al., 2016), we built a

hierarchical recurrent ResNet (HRRN) that follows the hierarchy of the ventral visual pathway

(Figure 6, also see Methods for more details about the model). The recurrent model (HRRN) could

rival the human performance in the occluded object recognition task (Figure 5d), performing

strikingly better than AlexNet in 60% and 80% occlusion. We also compared confusion matrices

(patterns of errors) between the models and human (Figure S7). Under the no-mask condition,

HRNN had a significantly higher correlation with humans under 0% and 80% occlusion (the

difference was not significant in 60% occlusion , Figure S7b).

Additionally, the HRRN model representation was significantly correlated with that of the human

MEG data under occlusion [Figure 5c] (onset = 138±2ms; peak = 182±19ms). It is worth noting

that the recurrent model here may be considered functionally equivalent to an arbitrarily deep

feedforward CNN. We think the key difference between AlexNet and HRRN, is indeed in the

number of non-linear transformations applied to the input image (please refer to section 3.3 for a

discussion about this).

The models here, the purely feedforward models (i.e. HRRN readout stage 0, and AlexNet) and

the model with local recurrent connections, were both trained on the same object image dataset

[ImageNet (Deng et al., 2009)] and had equal number of feedforward convolutional layers. Both

models performed similarly in object recognition under no-occlusion, and achieved human-level

performance. However, under occlusion, only the HRRN (i.e. the model with recurrent

connections) could partially explain the human MEG data and achieved human-level performance,

403   whereas the purely feedforward models failed to achieve human-level performance under

404   occlusion—in both MEG and behavior.

405

406

407   **Figure 5. Comparing human MEG and behavioral data with feedforward and recurrent computational models**

408   **of visual hierarchy. (a)** Time-varying representational similarity analysis between human MEG data and the

computational models. We, first, obtained representational dissimilarity matrices (RDM) for each computational

model —using feature values of the layer before the softmax operation—, and for the MEG data at each time-point.

For each subject, their MEG RDMs were correlated (Spearman' R) with the computational model RDMs (i.e. AlexNet

& HRRN) across time; the results were then averaged across subjects. **(b, c)** Time-courses of RDM correlations

between the models and the human MEG data**.** HRRN readout stage 0 represents the purely feedforward version of

HRRN. Thicker lines show significant time points (right-sided signrank test, FDR-corrected across time, p <= 0.05).

We indicate peak correlation latencies by numbers (mean ± SD) above the downward pointing arrows. Under no-

occlusion, AlexNet and HRRN demonstrate almost similar time-courses except that the peak latency for HRRN

(249±10ms) is significantly later than the peak latency for AlexNet (219±12ms). However, under occlusion, only

HRRN showed significant correlation with MEG data, with a peak latency of 182±19ms. **(d)** Object recognition

performance of humans (mask and no-mask trials) and models [AlexNet and HRRN-ReadoutStage-0 (feedforward)

and HRRN(recurrent)] across different levels of occlusion. We evaluated model accuracies on a multiclass recognition

task similar to the multiclass behavioral experiment done in humans (Figure S6). The models' performances were

calculated by holding out an occlusion level for testing, and training a SVM classifier on the remaining levels of

occlusion. Error bars are SEM.

425

426 **Figure 6. Hierarchical Recurrent ResNet (HRRN) in unfolded form is equivalent to an ultra-deep ResNet. (a)**

427 A hierarchy of convolutional layers with local recurrent connections. This hierarchical structure models the

428 feedforward and local recurrent connections along the hierarchy of ventral visual pathway (e.g. V1, V2, V4, IT). **(b)**

429 Each recurrent unit is equivalent to a deep ResNet with arbitrary number of layers depending on the unfolding depth.

430 h_t is the layer activity at a specific time (t) and K_t represents a sequence of nonlinear operations (e.g. convolution,

431 batch normalization, and ReLU). [see (Liang and Hu, 2015) for more info]

432

433

2.5 Contribution of feedforward and recurrent processes in solving object recognition under occlusion

To quantify the contribution of feedforward and recurrent processes in solving object recognition under occlusion, we first correlated the feedforward and recurrent model RDMs with the average MEG RDMs extracted from two time spans: 80 to 150 ms, which is dominantly feedforward (Liu et al., 2009, Cichy et al., 2016b, Mohsenzadeh et al., 2018), and 151 to 300 ms (significant involvement of recurrent processes). The results are shown in Figure 7a. HRRN and AlexNet both have a similar correlation with the MEG data at [80-150 ms]. However, the HRRN shows a significantly higher correlation with the MEG data at [151-300 ms] compared to the AlexNet.

We were further interested to determine the unique contribution of the models in explaining the neural data under occlusion. To this end, we calculated semipartial correlations between the model RDMs and the MEG RDMs (Figure 7b). We find that the HRRN and AlexNet perform similarly in explaining the mainly feedforward component (i.e. 80-150ms) of the MEG data and they do not have a significant unique contribution. On the other hand, for the later component (150-300 ms) of the MEG data, only the HRRN model has a unique contribution.

Figure 7. Contribution of the feedforward and recurrent models in explaining MEG data under 60% occlusion.

(a) Correlation between the models RDMs and the average MEG RDM over two different time bins. **(b)** Unique

contribution of each model (semipartial correlation) in explaining the MEG data. Error bars represent SEM (Standard

Error of the Mean). Significantly above zero correlations/semipartial-correlations and significant differences between

the two models are indicated by stars. * = p<0.05 ; ** = p<0.01; *** = p<0.001.

3. Discussion

We investigated how the human brain processes visual objects under occlusion. Using multivariate

MEG analysis, behavioral data, backward masking and computational modeling, we demonstrated

that recurrent processing plays a major role in object recognition under occlusion.

One of the unique advantages of the current work in comparison to a number of previous studies

that have investigated object recognition under partial visibility (Wyatte et al., 2014, Tang et al.,

2014) was bringing together neural data, behavioral data and computational models in a single

study. This enabled us to study the link between brain and behavior and propose a neural

architecture that is consistent with both. Whereas previous studies either related models with

behavior (e.g. (Wyatte et al., 2014)), missing the link with brain data; or otherwise highlighting

the role of recurrent processes using neural data (Tang et al., 2014) without suggesting a

computational mechanism that could explain the data and the potential underlying mechanisms

(however, please also see the recently published (Tang et al., 2018)).

Another unique advantage of the current study was the comparison of different deep neural

network architectures and comparing their ability in explaining neural and behavioral data under

occlusion. To our knowledge this was the first work that specifically compared deep convolutional

networks with neural data in occluded object processing.

3.1. Beyond core object recognition

Several recent findings have indicated that a large class of object recognition tasks referred to as

'core object recognition' are mainly solved in the human brain within the first ~100 ms after

stimulus onset (Thorpe, 2009, Liu et al., 2009, Carlson et al., 2013, Isik et al., 2014, Cichy et al.,

2016a), largely associated with the feedforward path of visual information processing (Lamme

and Roelfsema, 2000, Khaligh-Razavi and Kriegeskorte, 2014, Yamins et al., 2014, Cadieu et al.,

2014). More challenging tasks, such as object recognition under occlusion, go beyond the core

recognition problem. So far it has been unclear whether the visual information from the

feedforward sweep can fully account for this or otherwise recurrent information are essential to

solve object recognition under occlusion.

3.1.1. Temporal dynamics

We found that under the no-occlusion condition, the MEG object-decoding time-course peaked at

140ms with an early onset at 79ms, consistent with findings from previous studies (DiCarlo and

Cox, 2007, Carlson et al., 2013, Cichy et al., 2014, Isik et al., 2014). Intracranial recordings in

human visual cortex have shown that early responses to visual stimuli can reach higher visual areas

in as little as 100 ms, with a peak decoding performance after 150 ms (Liu et al., 2009, Cichy et

al., 2016b). These results suggest that category-related information around ~100 ms (±20 ms) after

stimulus onset are mainly driven by feedforward processes (see Figure S2 for time course of visual

processing in human). M/EEG studies in humans have additionally shown that approximately after

150 ms, a very complex and dynamic phase of visual processing may strengthen the category-

specific semantic representations (Clarke et al., 2011, Clarke, 2015), which are likely to be driven

by recurrent (Thorpe, 2009). In our study, when objects were occluded, object decoding accuracy

peaked at 200ms, with a late onset at 123ms—significantly later than the peak and onset under the

no-occlusion condition (i.e. 140ms and 79ms)—suggesting the involvement of recurrent

processes. Given the results from the temporal generalization analysis (Figure 2c), and the

computational modelling, we argue for the engagement of mostly *local* recurrent connections as

opposed to long-range top-down feedback in solving object recognition under occlusion for this

image set. Previous studies also suggest that long-range top-down recurrent (e.g. PFC to IT) is

prominently engaged after 200ms from stimulus onset (Tomita et al., 1999, Garrido et al., 2007,

Liu et al., 2009, Goddard et al., 2016). However, we do not rule out the possibility of involvement

of long-range feedback in processing occluded objects, specifically when stimuli become more

complicated (e.g. when objects are presented on natural backgrounds).

The additional time needed for processing occluded objects may facilitate object recognition by

providing integrated semantic information from visible parts of the target objects, for example, via

local recurrent in higher visual areas in the form of attractor networks (Devereux et al., 2018). In

other words, partial semantic information (e.g. having wheels, having legs, etc.) may activate prior

information associated with the category of the target object (Clarke and Tyler, 2014, Clarke,

2015). Overall these suggest the observed temporal delay under 60% occlusion can be best

explained by the engagement of recurrent processes—mostly local recurrent connections.

516   3.1.2. Computational modeling

Feedforward CNNs have been shown to be able to account for the core object recognition (Cadieu

et al., 2014, Khaligh-Razavi and Kriegeskorte, 2014, Yamins et al., 2014, Güçlü and van Gerven,

2015, Kubilius et al., 2016, Kheradpisheh et al., 2016a, Kheradpisheh et al., 2016b, Khaligh-

Razavi et al., 2017). The natural question to ask next is whether these models perform similarly

well under more challenging conditions, beyond the core object recognition. To address this, we

compared a conventional feedforward CNN with a recurrent convolutional network in terms of

their object recognition performance, and their representational similarity with that of the human

MEG data, under the challenging condition of occlusion. The feedforward CNN only achieved

human-level performance when objects were not occluded; and performed significantly lower than

the humans and the recurrent network when objects were occluded. The conventional feedforward

CNN also failed to explain human neural data when objects were occluded. On the other hand, the

convolutional network with local recurrent connections could achieve human-level performance

in occluded object recognition and explained a significant variance of the human neural data. Thus,

demonstrating that the conventional feedforward CNNs (such as AlexNet) do not account for

object recognition under such challenging conditions, where recurrent computations have a

prominent contribution.

533

3.2. Unique contribution of recurrent processes in solving object recognition under occlusion

536 AlexNet (i.e. feedforward model) and HRRN (i.e. recurrent model) both equally explained the
537 early component of the MEG data (<150 ms) with and without occlusion. Consistent with this, the
538 semipartial correlation analyses further revealed no unique variance for these models in explaining
539 the early component of the MEG data. These results suggest that the early component of the MEG
540 data under both conditions (with and without occlusion) are mainly feedforward and both AlexNet
541 and HRRN share a common feedforward component that is significantly correlated with
542 dominantly feedforward MEG representations before 150 ms (Figure S8 shows a plausible Venn
543 diagram describing the relationship between the two models and the MEG data.).

544 On the other hand, the later component of the MEG data (>150 ms) under occlusion was only
545 correlated with the recurrent model, which had a significant unique contribution in explaining the
546 MEG data under this condition. Under no occlusion, while the later component of the MEG data
547 is significantly correlated with both AlexNet and HRRN, only the HRRN model showed a
548 significant unique contribution in explaining the data (Figure S9). This shows that under no-
549 occlusion the later component of the MEG data can still be partially explained by the common
550 feedforward component of the two models, perhaps because object recognition under no-occlusion
551 is primarily a feedforward process, however the recurrent model has some unique advantages in
552 explaining later MEG components—even under no-occlusion.

553

3.3. Object occlusion vs. object deletion

555 Object recognition when part of an object is removed without an occluder is one of the challenging
556 conditions that has been previously studied (Nielsen et al., 2006, Wyatte et al., 2012, O'Reilly et
557 al., 2013, Wyatte et al., 2014, Tang et al., 2014, Tang et al., 2018) and may partly look similar to
558 occlusion. However, as shown by Johnson and Olshausen (2005) deleting part of an object is

different from occluding it with another object. See Figure S10 for sample images of occlusion

and deletion. Occlusion occurs when an object or shape appears in front of another one (Johnson

and Olshausen, 2005), in which case the occluding object might serve as an additional cue for

object completion. On the other hand, deletion occurs when part of an object is removed without

additional cues about the shape or the place of the missing part. Given the difference between these

two phenomena at the level of stimulus set, we expect the dynamics of object processing (and the

underlying computational mechanisms) to be also different when part of an object is occluded

compared to when it is deleted. Consistent with this, Johnson and Olshausen (2005) demonstrated

that ERP responses in occipital and parietal electrodes are signifcantly different between object

occlusion and deletion. Furthermore, there were significant behavioural differences between

object occlusion and deletion, including differneces in recogntion memory and response

confidence.

Object deletion has been previously studied in humans using a variety of techniques: Wyatte et.

al. (2012, 2014) used human behaviour (in a backward masking paradigm), and computational

modelling to show that object recogntion, when part of the object is deleted, requires recurrent

processing. Tang et. al. (2014, 2018) used intracranial field potential recording on epileptic patients

to study temporal dynamics of object deletion; and proposed an attractor-based recurrent model

that could explain the neural data. They found ~100 ms delay in processing objects when part of

the object was deleted, compared to when the whole object was present. In comparison, in our

study we found ~60 ms delay in object processing when objects were occluded. This suggests that

while object recognition under both occlusion and deletion requires recurrent processes, temporal

dynamics of object deletion is slower, potentially due to the absence of the occluder, which can

make the recognition task more difficult.

To summarize, while object deletion has been previously studied in humans, to our knowledge,

temporal dynamics of object occlusion had not been studied before. In particular this was the first

MVPA study in humans that characaterized representational dynamics of object recognition

under occlusion, and further provided a computational account of the underlying processes that

explained both behavioral and neural data.

3.4. Does a feedforward system with arbitrarily long depth work the same as a recurrent system with limited depth?

588
589

While conventional CNNs could not account for object recognition beyond the core recognition

problem, we do not rule out the possibility that much deeper CNNs could perform better under

such challenging conditions.

Computational studies have shown that very deep CNNs outperform shallow ones on a variety of

object recognition tasks (Simonyan and Zisserman, 2014, Szegedy et al., 2015, Taigman et al.,

2014). Specifically, residual learning allows for a much deeper neural network with hundreds (He

et al., 2016a) and even thousands (He et al., 2016b) of the layers providing better performance.

This is due to the fact that the complex functions that can be represented by deeper architectures

cannot be represented by shallow architectures (Bengio and LeCun, 2007). Recent computational

modeling studies have tried to clarify why increasing the depth of a network can improve its

performance (Liang and Hu, 2015, Liao and Poggio, 2016). These efforts have demonstrated that

unfolding a recurrent architecture across time leads to a feedforward network with arbitrary depth,

in which the weights are shared among the layers. Although such a recurrent network has far fewer

parameters, Liao and Poggio (2016) have empirically shown that it performs as well as a very deep

feedforward network *without* shared weights. We also showed that a very deep ResNet (e.g. with

150 layers) can be reformulated into the form of a recurrent CNN with much fewer layers (e.g.

five layers) (Figure 6). Thus, a compact architecture that resembles these very deep networks in

terms of performance is a recurrent hierarchical network with much fewer layers. This compact

architecture is probably what the human visual system has selected to be like (Lamme et al., 1998,

Sporns and Zwi, 2004), given the biological constraints of having a very deep neural network

inside the brain (Dunbar, 1992, Kaas, 2000, Weaver, 2005, Isler and van Schaik, 2009, Bosman

and Aboitiz, 2015).

From a computational viewpoint, recognition of complex images might require more processing

efforts; in other words, they might need to go through more layers of processing to be prepared for

the final readout. Similarly, in a recurrent architecture, more processing means more iterations.

Our modeling results supports this assumption, showing that under more challening recogntion

tasks, more iterations are required to reach human-level perfomrance. For example, under 60%

and 80% occlusion, the HRRN model reached human level performance, respectively after going

through 13 recurrent stages, and 43 recurrent stages (Figure S11). With more iterations, the HRRN

model tends to achieve a performance slightly better than the average categorization performance

in humans.

Our choice of a recurrent architecture, as opposed to an arbitrarily deep neural network, is mainly

driven by the plausibly of such architecture with the hierarchy of vision, where there is only a

limited number of processing layers. However, in terms of performance in real-world object

recognition tasks (e.g. object recognition under occlusion), the key in achieving a good

performance is the number of non-linear operations, which can come either in the form of deeper

networks in a feedforward architecture or otherwise more iterations in a recurrent architecture.

The neural basis of masking effect

Backward masking is a useful tool for studying temporal dynamics of visual object processing

(Lamme et al., 2002, Breitmeyer and Öğmen, 2006). It can impair recognition of the target object

and reduce or eliminate perceptual visibility through the presentation of a second stimulus (mask)

immediately or with an interval after the target stimulus, e.g. 50 ms after the target's onset. While

the origin of masking effect was not the focus of the current study, our MEG results could provide

some insights about the underlying mechanisms of backward masking.

There are several accounts of backward masking in the literature: Breitmeyer and Ganz (1976)

provided a purely feedforward explanation (two-channel model), arguing that the mask travels

rapidly through the fast channel disrupting recognition of the target object traveling through the

slow channel. A number of other studies, however, suggest that the masking mainly interferes with

the top-down feedback processes (Lamme and Roelfsema, 2000, Lamme et al., 2002, Breitmeyer

and Öğmen, 2006, Fahrenfort et al., 2007). And finally, Macknik and Martinez-Conde (2007)

explain the masking effect by the lateral inhibition mechanism of neural circuits within different

levels of the visual hierarchy; arguing that the mask interferes with the recognition of the target

object through lateral inhibition (i.e. inhibitory interactions between target and mask).

The last two accounts of masking, while being different, both argue for the disruption of recurrent

processes by the mask: either the top-down recurrent processes, or the local recurrent processes

(e.g. lateral interactions). With a short interval between the target and mask, the mask may interfere

with the fast recurrent processes (i.e. local recurrent) while with a relatively long interval it may

interfere with the slow recurrent processes (i.e. top-down feedback).

Our results of MEG decoding time-courses, time-time decoding and behavioral performances

under the no-occlusion condition does not support the purely feedforward account of visual

backward masking. We showed that the backward masking did not have a significant effect on

disrupting the fast feedforward processes of object recognition under no occlusion (MEG: Figure

4a; behaviorally: Figure 5d). On the other hand, when objects were occluded the backward

masking significantly impaired object recognition both behaviorally (Figure 5d) and neurally

(Figure 4b). Additionally, the time-time decoding results (Figure 4c,4d,4f) showed that backward

masking, under no occlusion, had no significant effect on disrupting the diagonal component of

the temporal generalization matrix that is mainly associated with the feedforward path of visual

processing. On the other hand, the masking removed the off-diagonal components and the late

peak (>200ms) observed in the temporal generalization matrix of the occluded objects.

Taken together, our MEG and behavioral results are in favor of a recurrent account for backward

masking. Particularly in our experiment with a short stimulus onset asynchrony (SOA = time from

stimulus onset to the mask onset), the mask seems to have affected mostly the local recurrent

connections.

4. Methods

4.1. Ethics Statement

668   The study was conducted according to the Declaration of Helsinki. The experiment protocol was

669   approved by the local committee on the use of humans as experimental subjects. Volunteers

670   completed a consent form before participating in the experiment and were financially compensated

671   after finishing the experiment.

673   4.2.   Occluded objects image set

Images of four different object categories (i.e. camel, deer, car, and motorcycle) were used as the

stimulus set (Figure 1b). Object images were transformed to be similar in terms of size and contrast

level. To generate an occluded image, in an iterative process we added several black circles (as

artificial occluders) of different sizes in random positions on the image. The configuration of black

circles (i.e. number, size, and their positions on the images) were randomly selected as such that a

V1-like model could not discriminate between images with 0%, 60% and 80% occlusion. To

simulate the type of occlusion that occurs in natural scenes, the black circles are positioned in both

front and back of the target object. The percent of object occlusion is defined as the percent of the

target object covered by the black occluders. We defined three levels of occlusion: 0% (no

occlusion), 60% occlusion and 80% occlusion. Black circles also existed in the 0% occlusion, but

not covering the target object; this was to make sure that the difference observed between occluded

and un-occluded objects cannot be solely explained by the presence of these circles. The generated

image set is comprised of 12 conditions: four objects × three occlusion levels. For each condition,

we generated M = 64 sample images varying by the occlusion pattern and the target object position.

To remove the potential effect of low-level visual features in object discrimination—objects

positions were slightly changed around the center of the images (by $\Delta x \leq 15$, $\Delta y \leq 15$ pixels).

Overall, we controlled for low-level image statistics, as such that images of different levels of

occlusion could not be discriminated simply by using low-level visual features (i.e. Gist and V1

model).

694 4.3. Participants and MEG experimental design

Fifteen young volunteers (22-38 year-old, all right-handed; 7 female) participated in the

experiment. During the experiment, participants completed eight runs; each run consisted of 192

trials and lasted for approximately eight minutes (total experiment time for each participant =

~70min). Each trial started with 1sec fixation followed by 34ms ($2 \times$ screen frame rate (17ms) =

34ms) presentation of an object image ($6°$ visual angle). In half the trials, we employed backward

masking in which a dynamic mask was presented for 102ms shortly after the stimulus offset—

inter-stimulus-interval (ISI) of 17ms—(Figure S1). In each run, each object image (i.e. camel,

deer, car, motor) was repeated 8 times under different levels of occlusions without backward

masking; and another 8 repetitions with backward masking. In other words, each condition (i.e.

combination of object-image, occlusion-level, mask or no-mask) was repeated 64 times over the

duration of the whole experiment.

Every 1-3 trials, a question mark appeared on the screen (lasted for 1.5 sec) prompting participants

to choose animate if the last stimulus was deer/camel and inanimate if the last stimulus was

car/motor (Figure S1; see Figure S12 for behavioral performance of animate/inanimate task).

Participants were instructed to only respond and blink during the question trials to prevent

contamination of MEG signals with motor activity and the eye-blink artifact. The question trials

were excluded from further MEG analyses.

The dynamic mask was a sequence of random images (n = 6 images; each presented for 17ms)

selected from a pool of the synthesized mask images. They were generated by using a texture

synthesis toolbox that is available at: http://www.cns.nyu.edu/~lcv/texture/ (Portilla and

Simoncelli, 2000). The synthesized images have low-level feature statistics similar to the original

stimuli.

4.4. MEG acquisition

To acquire brain signals with millisecond temporal resolution, we used 306-sensors MEG system

(Elekta Neuromag, Stockholm). The sampling rate was 1000Hz and band-pass filtered online

between 0.03 and 330 Hz. To reduce noise and correct for head movements, raw data were cleaned

by spatiotemporal filters [Maxfilter software, Elekta, Stockholm; (Taulu and Simola, 2006)].

Further pre-processing was conducted by Brainstorm toolbox (Tadel et al., 2011). Trials were

extracted -200ms to 700ms relative to the stimulus onset. The signals were then normalized by

their baseline (-200ms to 0ms), and were temporally smoothed by low-pass filtering at 20Hz.

4.5. Behavioral task of multiclass object recognition

We ran a psychophysical experiment, outside MEG, to evaluate human performance on a multi-

class occluded object recognition task. Sixteen subjects participated in a session lasting about 40

minutes. The experiment was a combination of mask and no-mask trials that were randomly

distributed across the experiment. Each trial, started by a fixation point presented for 0.5s followed

by a stimulus presentation of 34ms. In the masked trials, a dynamic mask of 102ms was presented

after a short ISI of 17ms (Figure S5). Subjects were instructed to respond accurately and as soon

as possible after detecting the target stimulus. They were asked to categorize the object images by

pressing one of the pre-assigned four keys on a keyboard corresponding to the four object

categories: camel, deer, car, and motorcycle.

Overall, 16 human subjects (25 to 40 years-old) participated in this experiment. Before the

experiment, participants performed a short training phase on a totally different image-set to learn

the task and reach a predefined performance level in the multi-class object recognition task. The

main experiment consisted of 768 trials that were randomly distributed into four blocks of 192

trials (32 repetitions of object images with small variations in position and the pattern of occlusion

$\times$ three occlusion levels $\times$ two masking conditions $\times$ four object categories = 768). Images of

256x256 pixels size were presented at a distance of 70 cm at the center of a CRT monitor with the

frame rate of 60 Hz and a resolution of 1024×768. We used the MATLAB based psychophysics

toolbox of (Pelli, 1997).

744　4.6. Multivariate pattern analyses (MVPA)

745　4.6.1. Pairwise decoding analysis

To measure temporal dynamics of object information processing, we used pairwise decoding

analysis on the MEG data (Isik et al., 2014, Cichy et al., 2014, Kietzmann et al., 2017). For each

subject, at each time-point, we created a data matrix of 64-trials $\times$ 306-sensors per condition. We

used a support vector machine (SVM) to pairwise decode any two conditions, with a leave-one-

out cross-validation approach. At each time-point, for each condition, *N-1* pattern vectors were

used to train the linear classifier [SVM; LIBSVM, (Chang and Lin, 2011), software available at

http://www.csie.ntu.edu.tw/~cjlin/libsvm/], and the remaining N^{th} vector was used for evaluation.

The above procedure was repeated 100 times with random reassignment of the data to training and

testing sets. This was then averaged over the six pairwise decoding accuracies. The SVM decoding

analysis is done independently for each subject and then we report the average decoding

performance over these individuals (Figure 1a).

757   4.6.2. Time-time decoding analysis

We also reported time-time decoding accuracies, obtained by cross-decoding across time. For each

pair of objects, a SVM classifier is trained at a given time and tested at all other time-points, thus

showing the generalization of the classifier across time. The results are then averaged across all

the pairwise classifications. This yields an 801x801 (t=-100 to 700 ms) matrix of average pairwise

decoding accuracies for each subject. Figure 2 shows the time-time decoding matrices averaged

across 15 participants. To test for statistical significance, we did one-sided signrank test against

the chance-level and then corrected for multiple comparison using FDR.

765   4.6.3. Sensorwise decoding analysis

We also examined a sensorwise visualization of pairwise object decoding across time (Supp

Movies 1 & 2). To this end, we trained and tested the SVM classifier at the level of sensors (i.e.

combination of three neighboring sensors) across the whole 306 sensors. First, 306 MEG sensors

were grouped into 102 triplets (Elekta Triux system; 2 gradiometers and 1 magnetometer in each

location). At each time-point, we applied the same pairwise decoding procedure as previously

explained in 4.5.1, this time at the level of groups of 3 adjacent sensors (instead of taking all the

306 MEG sensors together). Average pairwise decoding accuracies across subjects, at each time

point, are color-coded across the head surface. We used black dots to indicate channels with

significantly above chance accuracy (FDR-corrected across both time and sensors), and gray dots

to show accuracies with p<0.05, before correcting for multiple comparison. At each time-point,

we also specify the channel with peak decoding accuracy by a red dot.

778   4.6.4. Representational similarity analysis (RSA) over time

We used representational similarity analysis (RSA) (Kriegeskorte, 2009, Kriegeskorte and Kievit,

2013, Cichy et al., 2014, Carlson et al., 2013, Khaligh-Razavi et al., 2016), to compare

representations of computational models with time-resolved representations derived from MEG

data.

For the MEG data, representational dissimilarity matrices (RDM) were calculated at each time-

point by computing the dissimilarity (1 - Spearman's R) between all pairs of the MEG patterns

elicited by object images. Time-resolved MEG RDMs were then correlated (Spearman's R) with

the computational model RDMs, yielding a correlation vector over time (Figure 5a).

Semipartial correlation: We additionally calculated semipartial correlations between the MEG

RDMs and the computational model RDMs (Figure 7b). Semipartial correlation indicates the

unique relationship between a model representation (e.g. AlexNet RDM) and the MEG data, by

taking out the shared contribution of other models (e.g. HRRN RDM) in explaining the MEG data.

The semipartial correlation is computed as follows:

792
$$r_{1(2.3)} = \frac{r_{12} - r_{13}r_{23}}{\sqrt{1 - r_{23}^2}}$$

793    $'r_{1(2.3)}'$ is the correlation between *model X_1* and *model X_2* controlling for the effect of *model X_3*

794   (i.e. removing X_3 only from X_2)(Pedzahur, 1997).

795 To construct CNN model RDMs, we used the extracted features from the penultimate layer of the

796 networks (i.e. the layer before softmax operation). Significant correlations were determined by

797 one-sided signrank test ($p < 0.5$, FDR-corrected across time).

4.7. Significance Testing

We used the non-parametric Wilcoxon signrank test (Gibbons and Chakraborti, 2011) for random

effect analysis. To determine time-points with significantly above chance decoding accuracy (or

significant RDM correlations), we used a right-sided signrank test across n = 15 participants. To

adjust p-values for multiple comparisons (e.g. across time), we further applied the false discovery

rate (FDR) correction (Benjamini and Hochberg, 1995) [RSA-Toolbox: is available from

https://github.com/rsagroup/rsatoolbox (Nili et al., 2014)].

To determine whether two time-courses (e.g. correlation or decoding) are significantly different at

any time interval, we used a two-sided signrank test, FDR corrected across time.

Onset latency: We defined onset latency as the earliest time where performance became

significantly above chance for at least ten consecutive milliseconds. Mean and standard deviation

(SD) for onset latencies were calculated by leave-one-subject-out repeated for N=15 times.

Peak latency: The time for peak decoding accuracy was defined as the time where the decoding

accuracy was the maximum value. The mean and SD for peak latencies were calculated similar to

the onset latencies.

4.8. Computational modeling

4.8.1. Feedforward computational model (AlexNet)

We used a well-known CNN (AlexNet) (Krizhevsky et al., 2012) that is shown to account for the core object recognition (Khaligh-Razavi and Kriegeskorte, 2014, Cadieu et al., 2014, Kheradpisheh et al., 2016a, Kheradpisheh et al., 2016b). CNNs are cascades of hierarchically organized feature extraction layers. Each layer has several hundred convolutional filters and each convolutional filter scans various places on the input generating a feature map at its output. A convolutional layer may be followed by a local or global pooling layer merging outputs of a group of units. The pooling layers make the feature maps invariant to small variations (Bengio and LeCun, 2007). AlexNet has eight cascading layers: five convolutional layers, some of which followed by pooling layers, and three fully-connected layers (Krizhevsky et al., 2012). The last fully-connected layer is a 1000-way softmax that corresponds to the 1000 class labels. The network has 60 million free parameters. A pre-trained version of the model, which is trained on 1.2 million images from ImageNet dataset (Russakovsky et al., 2015) is used for the experiments here. We used the features extracted by the fc7 layer (before softmax operation) as the model output.

4.8.2. Hierarchical Recurrent ResNet (HRRN)

In convolutional neural networks, performance in visual recognition tasks can be substantially improved by adding to the depth of the network (Simonyan and Zisserman, 2014, Szegedy et al., 2015, He et al., 2015). However, this comes at a cost: deeper networks of simply stacking layers (plain nets) have higher training errors due to the vanishing gradients (degradation) (Glorot and Bengio, 2010) problem that prevents convergence in the training phase. To address this problem, He et al. (2016a) introduced a deep residual learning framework. Residual networks can overcome the vanishing gradient problem during learning by employing *identity shortcut connections* that

allow bypassing residual layers. This framework enables training ultra-deep networks, e.g. with

1202 layers, leading to much better performances compared to the shallower networks (He et al.,

2016a, He et al., 2016b).

Residual connections give ResNet an interesting characteristic of having several possible pathways

with different lengths from the network's input to the output instead of a single deep pathway (Veit

et al., 2016). For example, the ultra-deep 152-layers ResNet in its simplest form—by skipping all

the residual layers—is a hierarchy of five convolutional layers. By including additional residual

layers, more complex networks with various depths are constructed [see table 1 in (He et al.,

2016a)]. Each series of the residual modules can be reformulated into the form of a convolutional

layer with recurrent connections (Liang and Hu, 2015). Additionally, Liao and Poggio (2015) show

that a ResNet with shared weights can retain most of the performance of the corresponding network

with non-shared weights.

In this study, we proposed a generalization of this convolutional neural network by redefining

residual layers as local recurrent connections. As shown in Figure 5, we reformulated the 152-

layers ResNet of He et al. (2016a) into the form of a five-layer convolutional network with folded

residual layers as its local recurrent connections. The unfolded HRRN (=152 layers ResNet) is

deeper than the AlexNet and has different normalization (i.e. batch normalization) and filter sizes,

however, they still have a similar number of free parameters (60M). Comparing AlexNet with a

purely feedforward version of HRRN (readout stage 0, with five layers), AlexNet performs slightly

better than HRRN in readout stage 0, and gradually after 4 iterations HRRN reaches a

categorization performance similar to that of AlexNet (Figure S13). The model is pre-trained on

ImageNet 2012 dataset with a training set similar to that of Alexnet (1.2 million training images).

It is shown experimentally that an unfolded recurrent CNN (with shared weights) is similar to a

very deep feedforward network with non-shared weights (Liao and Poggio, 2016). In our analyses,

we used the extracted features of the penultimate layer (i.e. layer pool5, which is before the

softmax layer) as the model output.

Acknowledgement

869 The study was conducted at the Athinoula A. Martinos Imaging Center at the McGovern Institute

870 for Brain Research, Massachusetts Institute of Technology. We would like to thank Aude Oliva

871 and Dimitrios Pantazis for their help and support in conducting this study. We would also like to

872 thank Radoslaw Martin Cichy for helpful comments. SKR was funded by a return home fellowship

873 grant from Iranian national elite foundation.

References

BACON-MACÉ, N., MACÉ, M. J.-M., FABRE-THORPE, M. & THORPE, S. J. 2005. The time course of visual
processing: Backward masking and natural scene categorisation. *Vision research,* 45**,** 1459-1469.
BAN, H., YAMAMOTO, H., HANAKAWA, T., URAYAMA, S.-I., ASO, T., FUKUYAMA, H. & EJIMA, Y. 2013.
Topographic representation of an occluded object and the effects of spatiotemporal context in
human early visual areas. *Journal of Neuroscience,* 33**,** 16992-17007.
BENGIO, Y. & LECUN, Y. 2007. Scaling learning algorithms towards AI. *Large-scale kernel machines,* 34.
BENJAMINI, Y. & HOCHBERG, Y. 1995. Controlling the false discovery rate: a practical and powerful
approach to multiple testing. *Journal of the royal statistical society. Series B (Methodological)***,**
289-300.

BOSMAN, C. A. & ABOITIZ, F. 2015. Functional constraints in the evolution of brain circuits. *Frontiers in*
neuroscience, 9.
BREITMEYER, B. & ÖĞMEN, H. 2006. *Visual masking: Time slices through conscious and unconscious vision*,
Oxford University Press.
CADIEU, C. F., HONG, H., YAMINS, D. L., PINTO, N., ARDILA, D., SOLOMON, E. A., MAJAJ, N. J. & DICARLO,
J. J. 2014. Deep neural networks rival the representation of primate IT cortex for core visual object
recognition. *PLoS Comput Biol,* 10**,** e1003963.
CARLSON, T., TOVAR, D. A., ALINK, A. & KRIEGESKORTE, N. 2013. Representational dynamics of object
vision: the first 1000 ms. *Journal of vision,* 13**,** 1-1.
CHANG, C.-C. & LIN, C.-J. 2011. LIBSVM: a library for support vector machines. *ACM transactions on*
intelligent systems and technology (TIST), 2**,** 27.
CHOI, H., PASUPATHY, A. & SHEA-BROWN, E. 2016. Predictive coding in area V4: dynamic shape
discrimination under partial occlusion. *arXiv preprint arXiv:1612.05321*.
CICHY, R. M., KHOSLA, A., PANTAZIS, D., TORRALBA, A. & OLIVA, A. 2016a. Comparison of deep neural
networks to spatio-temporal cortical dynamics of human visual object recognition reveals
hierarchical correspondence. *Scientific reports,* 6**,** 27755.
CICHY, R. M., PANTAZIS, D. & OLIVA, A. 2014. Resolving human object recognition in space and time.
Nature neuroscience, 17**,** 455-462.
CICHY, R. M., PANTAZIS, D. & OLIVA, A. 2016b. Similarity-based fusion of MEG and fMRI reveals spatio-
temporal dynamics in human cortex during visual object recognition. *Cerebral Cortex,* 26**,** 3563-
3579.
CLARKE, A. 2015. Dynamic information processing states revealed through neurocognitive models of
object semantics. *Language, cognition and neuroscience,* 30**,** 409-419.
CLARKE, A., TAYLOR, K. I. & TYLER, L. K. 2011. The evolution of meaning: spatio-temporal dynamics of
visual object recognition. *Journal of cognitive neuroscience,* 23**,** 1887-1899.
CLARKE, A. & TYLER, L. K. 2014. Object-specific semantic coding in human perirhinal cortex. *Journal of*
Neuroscience, 34**,** 4766-4775.
CLARKE, A. M., HERZOG, M. H. & FRANCIS, G. 2014. Visual crowding illustrates the inadequacy of local vs.
global and feedforward vs. feedback distinctions in modeling visual perception. *Frontiers in*
psychology, 5.
CONTINI, E. W., WARDLE, S. G. & CARLSON, T. A. 2017. Decoding the time-course of object recognition in
the human brain: From visual features to categorical decisions. *Neuropsychologia*.
DENG, J., DONG, W., SOCHER, R., LI, L.-J., LI, K. & FEI-FEI, L. Imagenet: A large-scale hierarchical image
database. Computer Vision and Pattern Recognition, 2009. CVPR 2009. IEEE Conference on, 2009.
IEEE, 248-255.
DEVEREUX, B. J., CLARKE, A. D. & TYLER, L. K. 2018. Integrated deep visual and semantic attractor neural
networks predict fMRI pattern-information along the ventral object processing pathway. *Scientific*
Reports.
DICARLO, J. J. & COX, D. D. 2007. Untangling invariant object recognition. *Trends in cognitive sciences,* 11**,**
333-341.
DICARLO, J. J., ZOCCOLAN, D. & RUST, N. C. 2012. How does the brain solve visual object recognition?
Neuron, 73**,** 415-434.
DUNBAR, R. I. 1992. Neocortex size as a constraint on group size in primates. *Journal of human evolution,*
22**,** 469-493.
EBERHARDT, S., CADER, J. G. & SERRE, T. How deep is the feature analysis underlying rapid visual
categorization? Advances in neural information processing systems, 2016. 1100-1108.
ERLIKHMAN, G. & CAPLOVITZ, G. P. 2017. Decoding information about dynamically occluded objects in
visual cortex. *NeuroImage,* 146**,** 778-788.

FAHRENFORT, J. J., SCHOLTE, H. S. & LAMME, V. A. 2007. Masking disrupts reentrant processing in human
visual cortex. *Journal of cognitive neuroscience,* 19**,** 1488-1497.
FELLEMAN, D. J. & VAN ESSEN, D. C. 1991. Distributed hierarchical processing in the primate cerebral
cortex. *Cerebral cortex,* 1**,** 1-47.
GARRIDO, M. I., KILNER, J. M., KIEBEL, S. J. & FRISTON, K. J. 2007. Evoked brain responses are generated
by feedback loops. *Proceedings of the National Academy of Sciences,* 104**,** 20961-20966.
GHODRATI, M., FARZMAHDI, A., RAJAEI, K., EBRAHIMPOUR, R. & KHALIGH-RAZAVI, S.-M. 2014.
Feedforward object-vision models only tolerate small image variations compared to human.
Frontiers in computational neuroscience, 8**,** 74.
GIBBONS, J. D. & CHAKRABORTI, S. 2011. Nonparametric statistical inference. *International encyclopedia*
of statistical science. Springer.
GILBERT, C. D. & LI, W. 2013. Top-down influences on visual processing. *Nature Reviews Neuroscience,* 14**,**
350-363.
GLOROT, X. & BENGIO, Y. Understanding the difficulty of training deep feedforward neural networks.
Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics,
2010. 249-256.
GODDARD, E., CARLSON, T. A., DERMODY, N. & WOOLGAR, A. 2016. Representational dynamics of object
recognition: Feedforward and feedback information flows. *NeuroImage,* 128**,** 385-397.
GROOTSWAGERS, T. & CARLSON, T. 2015. Decoding the emerging representation of degraded visual
objects in the human brain. *Journal of vision,* 15**,** 1087-1087.
GROOTSWAGERS, T., WARDLE, S. G. & CARLSON, T. A. 2017. Decoding dynamic brain patterns from
evoked responses: A tutorial on multivariate pattern analysis applied to time series neuroimaging
data. *Journal of cognitive neuroscience*.
GÜÇLÜ, U. & VAN GERVEN, M. A. 2015. Deep neural networks reveal a gradient in the complexity of neural
representations across the ventral stream. *Journal of Neuroscience,* 35**,** 10005-10014.
HE, K., ZHANG, X., REN, S. & SUN, J. Delving deep into rectifiers: Surpassing human-level performance on
imagenet classification. Proceedings of the IEEE international conference on computer vision,
2015. 1026-1034.
HE, K., ZHANG, X., REN, S. & SUN, J. Deep residual learning for image recognition. Proceedings of the IEEE
conference on computer vision and pattern recognition, 2016a. 770-778.
HE, K., ZHANG, X., REN, S. & SUN, J. Identity mappings in deep residual networks. European Conference
on Computer Vision, 2016b. Springer, 630-645.
HEGDÉ, J., FANG, F., MURRAY, S. O. & KERSTEN, D. 2008. Preferential responses to occluded objects in the
human visual cortex. *Journal of vision,* 8**,** 16-16.
HULME, O. J. & ZEKI, S. 2007. The sightless view: neural correlates of occluded objects. *Cerebral Cortex,*
17**,** 1197-1205.
ISIK, L., MEYERS, E. M., LEIBO, J. Z. & POGGIO, T. 2014. The dynamics of invariant object recognition in the
human visual system. *Journal of neurophysiology,* 111**,** 91-102.
ISLER, K. & VAN SCHAIK, C. P. 2009. The expensive brain: a framework for explaining evolutionary changes
in brain size. *Journal of Human Evolution,* 57**,** 392-400.
JOHNSON, J. S. & OLSHAUSEN, B. A. 2005. The recognition of partially visible natural objects in the
presence and absence of their occluders. *Vision research,* 45**,** 3262-3276.
KAAS, J. H. 2000. Why is brain size so important: Design problems and solutions as neocortex gets biggeror
smaller. *Brain and Mind,* 1**,** 7-23.
KAFALIGONUL, H., BREITMEYER, B. G. & ÖĞMEN, H. 2015. Feedforward and feedback processes in vision.
Frontiers in psychology, 6.

KANESHIRO, B., GUIMARAES, M. P., KIM, H.-S., NORCIA, A. M. & SUPPES, P. 2015. A Representational
Similarity Analysis of the Dynamics of Object Processing Using Single-Trial EEG Classification. *PloS*
one, 10**,** e0135697.
KARIMI-ROUZBAHANI, H., BAGHERI, N. & EBRAHIMPOUR, R. 2017. Hard-wired feed-forward visual
mechanisms of the brain compensate for affine variations in object recognition. *Neuroscience,*
349**,** 48-63.
KHALIGH-RAZAVI, S.-M., BAINBRIDGE, W. A., PANTAZIS, D. & OLIVA, A. 2016. From what we perceive to
what we remember: Characterizing representational dynamics of visual memorability. *bioRxiv***,**
049700.
KHALIGH-RAZAVI, S.-M., CARLIN, J., MARTIN, C. R. & KRIEGESKORTE, N. 2015. The effects of recurrent
dynamics on ventral-stream representational geometry. *Journal of vision,* 15**,** 1089-1089.
KHALIGH-RAZAVI, S.-M., HENRIKSSON, L., KAY, K. & KRIEGESKORTE, N. 2017. Fixed versus mixed RSA:
Explaining visual representations by fixed and mixed feature sets from shallow and deep
computational models. *Journal of Mathematical Psychology,* 76**,** 184-197.
KHALIGH-RAZAVI, S.-M. & KRIEGESKORTE, N. 2014. Deep supervised, but not unsupervised, models may
explain IT cortical representation. *PLoS Comput Biol,* 10**,** e1003915.
KHERADPISHEH, S. R., GHODRATI, M., GANJTABESH, M. & MASQUELIER, T. 2016a. Deep networks can
resemble human feed-forward vision in invariant object recognition. *Scientific reports,* 6**,** 32672.
KHERADPISHEH, S. R., GHODRATI, M., GANJTABESH, M. & MASQUELIER, T. 2016b. Humans and deep
networks largely agree on which kinds of variation make object recognition harder. *Frontiers in*
computational neuroscience, 10.
KIETZMANN, T. C., GERT, A. L., TONG, F. & KÖNIG, P. 2017. Representational dynamics of facial viewpoint
encoding. *Journal of cognitive neuroscience,* 29**,** 637-651.
KING, J.-R., PESCETELLI, N. & DEHAENE, S. 2016. Brain mechanisms underlying the brief maintenance of
seen and unseen sensory information. *Neuron,* 92**,** 1122-1134.
KING, J. & DEHAENE, S. 2014. Characterizing the dynamics of mental representations: the temporal
generalization method. *Trends in cognitive sciences,* 18**,** 203-210.
KLINK, P. C., DAGNINO, B., GARIEL-MATHIS, M.-A. & ROELFSEMA, P. R. 2017. Distinct Feedforward and
Feedback Effects of Microstimulation in Visual Cortex Reveal Neural Mechanisms of Texture
Segregation. *Neuron*.
KOSAI, Y., EL-SHAMAYLEH, Y., FYALL, A. M. & PASUPATHY, A. 2014. The role of visual area V4 in the
discrimination of partially occluded shapes. *Journal of Neuroscience,* 34**,** 8570-8584.
KRIEGESKORTE, N. 2009. Relating population-code representations between man, monkey, and
computational models. *Frontiers in Neuroscience,* 3**,** 35.
KRIEGESKORTE, N. & KIEVIT, R. A. 2013. Representational geometry: integrating cognition, computation,
and the brain. *Trends in cognitive sciences,* 17**,** 401-412.
KRIZHEVSKY, A., SUTSKEVER, I. & HINTON, G. E. Imagenet classification with deep convolutional neural
networks. Advances in neural information processing systems, 2012. 1097-1105.
KUBILIUS, J., BRACCI, S. & DE BEECK, H. P. O. 2016. Deep neural networks as a computational model for
human shape sensitivity. *PLoS computational biology,* 12**,** e1004896.
LAMME, V. A. & ROELFSEMA, P. R. 2000. The distinct modes of vision offered by feedforward and
recurrent processing. *Trends in neurosciences,* 23**,** 571-579.
LAMME, V. A., SUPER, H. & SPEKREIJSE, H. 1998. Feedforward, horizontal, and feedback processing in the
visual cortex. *Current opinion in neurobiology,* 8**,** 529-535.
LAMME, V. A., ZIPSER, K. & SPEKREIJSE, H. 2002. Masking interrupts figure-ground signals in V1. *Journal*
of cognitive neuroscience, 14**,** 1044-1053.
LIANG, M. & HU, X. Recurrent convolutional neural network for object recognition. Proceedings of the
IEEE Conference on Computer Vision and Pattern Recognition, 2015. 3367-3375.

LIAO, Q. & POGGIO, T. 2016. Bridging the gaps between residual learning, recurrent neural networks and
visual cortex. *arXiv preprint arXiv:1604.03640*.
LIU, H., AGAM, Y., MADSEN, J. R. & KREIMAN, G. 2009. Timing, timing, timing: fast decoding of object
information from intracranial field potentials in human visual cortex. *Neuron,* 62**,** 281-290.
LIVNE, T. & SAGI, D. 2011. Multiple levels of orientation anisotropy in crowding with Gabor flankers.
Journal of vision, 11**,** 18-18.
MACKNIK, S. L. & MARTINEZ-CONDE, S. 2007. The role of feedback in visual masking and visual processing.
Advances in cognitive psychology, 3**,** 125-152.
MANASSI, M. & HERZOG, M. Crowding and grouping: how much time is needed to process good Gestalt?
Perception, 2013. 229.
MOHSENZADEH, Y., QIN, S., CICHY, R. M. & PANTAZIS, D. 2018. Ultra-Rapid serial visual presentation
reveals dynamics of feedforward and feedback processes in the ventral visual pathway. *Elife,* 7**,**
e36329.
NIELSEN, K. J., LOGOTHETIS, N. K. & RAINER, G. 2006. Dissociation between local field potentials and
spiking activity in macaque inferior temporal cortex reveals diagnosticity-based encoding of
complex objects. *Journal of Neuroscience,* 26**,** 9639-9645.
NILI, H., WINGFIELD, C., WALTHER, A., SU, L., MARSLEN-WILSON, W. & KRIEGESKORTE, N. 2014. A toolbox
for representational similarity analysis. *PLoS Comput Biol,* 10**,** e1003553.
O'REILLY, R. C., WYATTE, D., HERD, S., MINGUS, B. & JILK, D. J. 2013. Recurrent processing during object
recognition. *Frontiers in psychology,* 4**,** 124.
PEDZAHUR, E. 1997. Multiple regression in behavioral research: Explanation and prediction. *London, UK:*
Wadsworth, Thompson Learning.
PELLI, D. G. 1997. The VideoToolbox software for visual psychophysics: Transforming numbers into
movies. *Spatial vision,* 10**,** 437-442.
PORTILLA, J. & SIMONCELLI, E. P. 2000. A parametric texture model based on joint statistics of complex
wavelet coefficients. *International journal of computer vision,* 40**,** 49-70.
RAJALINGHAM, R., ISSA, E. B., BASHIVAN, P., KAR, K., SCHMIDT, K. & DICARLO, J. J. 2018. Large-scale, high-
resolution comparison of the core visual object recognition behavior of humans, monkeys, and
state-of-the-art deep artificial neural networks. *bioRxiv***,** 240614.
RAUSCHENBERGER, R., LIU, T., SLOTNICK, S. D. & YANTIS, S. 2006. Temporally unfolding neural
representation of pictorial occlusion. *Psychological Science,* 17**,** 358-364.
RENSINK, R. A. & ENNS, J. T. 1998. Early completion of occluded objects. *Vision research,* 38**,** 2489-2505.
RUSSAKOVSKY, O., DENG, J., SU, H., KRAUSE, J., SATHEESH, S., MA, S., HUANG, Z., KARPATHY, A., KHOSLA,
A. & BERNSTEIN, M. 2015. Imagenet large scale visual recognition challenge. *International Journal*
of Computer Vision, 115**,** 211-252.
SERRE, T., OLIVA, A. & POGGIO, T. 2007. A feedforward architecture accounts for rapid categorization.
Proceedings of the National Academy of Sciences, 104**,** 6424-6429.
SIMONYAN, K. & ZISSERMAN, A. 2014. Very deep convolutional networks for large-scale image
recognition. *arXiv preprint arXiv:1409.1556*.
SPOERER, C., MCCLURE, P. & KRIEGESKORTE, N. 2017. Recurrent Convolutional Neural Networks: A Better
Model Of Biological Object Recognition Under Occlusion. *bioRxiv***,** 133330.
SPORNS, O. & ZWI, J. D. 2004. The small world of the cerebral cortex. *Neuroinformatics,* 2**,** 145-162.
SZEGEDY, C., LIU, W., JIA, Y., SERMANET, P., REED, S., ANGUELOV, D., ERHAN, D., VANHOUCKE, V. &
RABINOVICH, A. Going deeper with convolutions. Proceedings of the IEEE Conference on
Computer Vision and Pattern Recognition, 2015. 1-9.
TADEL, F., BAILLET, S., MOSHER, J. C., PANTAZIS, D. & LEAHY, R. M. 2011. Brainstorm: a user-friendly
application for MEG/EEG analysis. *Computational intelligence and neuroscience,* 2011**,** 8.

TAIGMAN, Y., YANG, M., RANZATO, M. A. & WOLF, L. Deepface: Closing the gap to human-level
performance in face verification. Proceedings of the IEEE Conference on Computer Vision and
Pattern Recognition, 2014. 1701-1708.
TANG, H., BUIA, C., MADHAVAN, R., CRONE, N. E., MADSEN, J. R., ANDERSON, W. S. & KREIMAN, G. 2014.
Spatiotemporal dynamics underlying object completion in human ventral visual cortex. *Neuron,*
83**,** 736-748.
TANG, H., SCHRIMPF, M., LOTTER, W., MOERMAN, C., PAREDES, A., CARO, J. O., HARDESTY, W., COX, D. &
KREIMAN, G. 2018. Recurrent computations for visual pattern completion. *Proceedings of the*
*National Academy of Sciences***,** 201719397.
TAULU, S. & SIMOLA, J. 2006. Spatiotemporal signal space separation method for rejecting nearby
interference in MEG measurements. *Physics in Medicine & Biology,* 51**,** 1759.
THORPE, S. J. 2009. The speed of categorization in the human visual system. *Neuron,* 62**,** 168-170.
THORPE, S. J. & FABRE-THORPE, M. 2001. Seeking categories in the brain. *Science,* 291**,** 260-263.
TOMITA, H., OHBAYASHI, M., NAKAHARA, K., HASEGAWA, I. & MIYASHITA, Y. 1999. Top-down signal from
prefrontal cortex in executive control of memory retrieval. *Nature,* 401**,** 699.
VEIT, A., WILBER, M. J. & BELONGIE, S. Residual networks behave like ensembles of relatively shallow
networks. Advances in Neural Information Processing Systems, 2016. 550-558.
WEAVER, A. H. 2005. Reciprocal evolution of the cerebellum and neocortex in fossil humans. *Proceedings*
of the National Academy of Sciences of the United States of America, 102**,** 3576-3580.
WEN, H., SHI, J., CHEN, W. & LIU, Z. 2018. Deep Residual Network Predicts Cortical Representation and
Organization of Visual Features for Rapid Categorization. *Scientific Reports,* 8**,** 3752.
WYATTE, D., CURRAN, T. & O'REILLY, R. 2012. The limits of feedforward vision: Recurrent processing
promotes robust object recognition when objects are degraded. *Journal of Cognitive*
Neuroscience, 24**,** 2248-2261.
WYATTE, D., JILK, D. J. & O'REILLY, R. C. 2014. Early recurrent feedback facilitates visual object recognition
under challenging conditions.
YAMINS, D. L., HONG, H., CADIEU, C. F., SOLOMON, E. A., SEIBERT, D. & DICARLO, J. J. 2014. Performance-
optimized hierarchical models predict neural responses in higher visual cortex. *Proceedings of the*
National Academy of Sciences, 111**,** 8619-8624.

1103