HMMRATAC, The Hidden Markov ModeleR for ATAC-seq.

Evan D. Tarbell and Tao Liu

Abstract

ATAC-seq has been widely adopted to identify accessible chromatin regions across the

genome. However, current data analysis still utilizes approaches originally designed for

ChIP-seq or DNase-seq, without taking into account the transposase digested DNA

fragments that contain additional nucleosome positioning information. We present the

first dedicated ATAC-seq analysis tool, a semi-supervised machine learning approach

named HMMRATAC. HMMRATAC splits a single ATAC-seq dataset into nucleosome-

free and nucleosome-enriched signals, learns the unique chromatin structure around

accessible regions, and then predicts accessible regions across the entire genome. We

show that HMMRATAC outperforms the popular peak-calling algorithms on published

human and mouse ATAC-seq datasets.

Keywords

ATAC-seq; peak-calling; Hidden Markov Model; nucleosome-free regions; flanking

nucleosomes; decomposition and integration; machine learning; chromatin states

Introduction

The genomes of all known eukaryotes are packaged into a nucleoprotein complex called

chromatin. The nucleosome is the fundamental, repeating unit of chromatin, consisting

of approximately 147 base pairs of DNA wrapped around an octet of histone proteins [1].

The eviction of nucleosomes into nucleosome-free regions (NFRs) makes DNA more

accessible to various DNA binding factors. The binding of these factors to the accessible

DNA can exert spatiotemporal control of gene expression, which is critical in the

establishment of cellular identity during development, cellular responses to stimuli, DNA

replication and other cellular processes [2].

Several assays exist to identify open chromatin regions in a genome-wide manner. These

include DNase-seq, which utilizes the DNase I nuclease [3], FAIRE-seq, which utilizes

differences in polarity between nucleosome-bound and nucleosome-free DNA [4], and

ATAC-seq, which uses a transposase to selectively cut into accessible DNA [5].

Although each of these assays identifies some unique open chromatin regions, they are

generally highly correlated in their identifications [5]. Whereas DNase-seq and FAIRE-

seq are complicated protocols that require, on average, one million cells, ATAC-seq is a

simple three-step protocol, which is optimized for fifty thousand cells, and can be

performed on as few as 500 cells or at a single cell level [5, 6]. ATAC-seq has become

popular over the years, and the Cistrome Database [7], in an effort to collect all publicly

available functional genomics data, has listed nearly 1,500 datasets for human and

mouse.

Due to steric hindrance, the Tn5 transposase used in ATAC-seq preferentially inserts into

NFRs. However, it is also possible for the transposase to insert into the linker regions

between adjacent nucleosomes, resulting in larger (over 150bps) DNA fragments, which

correspond to the integer numbers of adjacent nucleosomes [5]. The DNA fragments are

constructed in a paired-end library for sequencing, and after mapping both sequenced

ends of each fragment to the genome sequence, we can infer their fragment lengths

according to the observed mapping locations, or the insertion length. As described in [5],

if we plot the observed fragment length versus frequency, we will see a multi-modal

distribution where transposase insertion into NFRs and linker regions creates different

modes. This allows ATAC-seq to elucidate multiple layers of information relative to the

other assays. Although computational tools exist for DNase-seq, FAIRE-seq and ChIP-

seq [8], that can be and are used for ATAC-seq analysis, these would fall short since they

only utilize a subset of information, usually the nucleosome-free signals. To date, there

are no dedicated peak-callers specifically to account for ATAC-seq.

In order to investigate the ATAC-seq profile around accessible genomic regions, we took

the ATAC-seq data in the human GM12878 cell line from Buenrostro et al. [5], and

separated the fragments into short nucleosome-free and mono-nucleosome fragments

based on cutoffs identified by Buenrostro et al. We plotted the two types of fragments

around the centers of DNaseI hypersensitive sites (DHSs) in the same cell line, identified

by ENCODE [9] (Supplementary Figure 1). We observed a clear, symmetrical pattern

around the centers of these sites characterized by an enrichment of the nucleosome-free

fragments and flanking enrichment of the mono-nucleosome fragments. We were able to

visually discern at least four distinct regions around an open site: 1) the *center*,

characterized by an enrichment of nucleosome-free fragments and flanked by nucleosome

fragments; 2) the *flanking regions*, characterized by an enrichment of nucleosome

fragments and directly next to the center; 3) the *non-flanking regions*, characterized by

lower levels of nucleosome fragments and directly next to the flanking regions; 4) and the

background, which although not visible on the figure, would be characterized by a

depletion in any type of fragments (Fig. 1a; Additional file 1: Fig. S1). This observation

coincides with current knowledge that accessible chromatin actively bound by

transcription factors is surrounded by highly positioned nucleosomes, then further by

unpositioned nucleosomes [10]. We hypothesized that this pattern would exist at all open

chromatin throughout the genome and that by learning and recognizing this pattern

computationally in a single ATAC-seq dataset, we would identify all open chromatin

regions with higher confidence than any other existing method.

We present here HMMRATAC, the Hidden Markov ModeleR for ATAC-seq, a semi-

supervised machine learning approach for identifying open chromatin regions from

ATAC-seq data. The principle concept of HMMRATAC is built upon "decomposition

and integration", whereby a single ATAC-seq dataset is decomposed into different layers

of signals corresponding to different chromatin features, and then the relationships

between the layers of signals at open chromatin regions are learned and utilized for

pattern reorganization (Fig. 1b). Our method takes advantage of the unique features of

ATAC-seq to more accurately identify the chromatin structure. We found that

HMMRATAC was able to identify chromatin architecture and the most likely

transcription factor binding sites. Additionally, compared with existing methods used for

ATAC-seq analysis, HMMRATAC outperformed them in most tests, including

recapitulating active and/or open chromatin regions identified with other assays and in

the reproducibility between replicates.

Results

Signal decomposition through the probabilistic approach

In the first ATAC-seq paper by Buenrostro et al., the authors separated the fragments

according to their insertion lengths into four populations representing those from the

NFRs and those spanning 1, 2 or 3 nucleosomes [5]. Non-overlapping and non-adjacent

cutoffs were used. For example, lengths below 100 bp represent nucleosome-free signals

and lengths between 180 and 250 bp represents mono-nucleosome signals. We consider

such cutoff-based strategy not a general practice for the following two reasons. First,

different species or different cell lines may have different nucleosome spacing and these

differences may not be properly understood [11, 12]. Secondly, since the fragments

whose size falls between the non-overlapping and non-adjacent cutoffs are discarded (e.g.

those between 100 and 180 bp long), the recall (or sensitivity) to identify accessible

regions will be reduced (Additional file 1: Fig. S2 and explained later). As a fact, about

15% of the entire data generated from original paper are ignored with their strategy. We

addressed the above two challenges in a probabilistic approach in HMMRATAC.

First, we let the data itself identify the optimal parameters for the four different

distributions of fragment lengths. Similar to Buenrostro et al., we create four distributions

to represent four different chromatin features: nucleosome-free regions (NFRs), mono-

nucleosomes (1Ns), di-nucleosomes (2Ns) and tri-nucleosomes (3Ns). HMMRATAC

uses a mixture model and Expectation-Maximization (EM) algorithm to identify optimum

parameters (See method section for more detail).   As an example, HMMRATAC

identified the optimum fragment lengths representing 1Ns, 2Ns, and 3Ns from ATAC-seq

data in the human GM12878 cell line, generated by merging three replicates from [5], as

being 195bp, 396bp and 693bp, respectfully. As a demonstration of different nucleosome

spacing in different species and datasets, HMMRATAC determined the optimum

fragment lengths for the 1Ns, 2Ns, and 3Ns from ATAC-seq data in mouse C2C12

myoblast cells, generated by merging two replicates from [13], as 174bp, 370bp and

623bp, respectfully. Additionally, the values for any of the individual replicates, in either

human or mouse (three human replicates [5] and two mouse replicates [13]), were never

more than 5bp off from the average values listed above for the merged datasets. Not all

ATAC-seq datasets show a clear multi-modal pattern, especially datasets from fewer

cells. As an example, the fragment distribution generated by Buenrostro and et al.

utilizing 500 cells (GM12878 cells) per-replicate, did not show as clear of a distribution

as 50,000 cells per replicate (Additional file 1: Fig. S3a and S3b) [5]. However, we found

our approach can robustly identify the parameters even if the multi-modal pattern is not

clear. As we can see from Fig. 1c and 1d, the mean and standard deviation values

converged after no more than 12 iterations and the parameters converged to very similar

values for either the 50,000-cell per-replicate or 500 cell per-replicate ATAC-seq datasets

in GM12878.

Secondly, we propose in HMMRATAC a probabilistic approach to make use of data

from the entire spectrum of fragment lengths. We generate four separated signal profiles

in 10bp resolution, for NFRs, 1Ns, 2Ns, and 3Ns, allowing each mapped fragment to

contribute to all profiles with different weights corresponding to its particular fragment

length. For each genomic location that is occupied by a particular fragment, all four

signal profiles are incremented by the probabilities that this fragment, assigned with an

observed fragment length through read mapping, belongs to each of the four

corresponding distributions. We tested the performance of a regular HMMRATAC

approach with this probabilistic method utilizing the entire data and an alternative

approach utilizing only the subset of data satisfying the cutoffs proposed in Buenrostro et

al. The two approaches were compared in terms of precision and recall against the

"active regions" true set (described in more detail below) (Additional file 1: Fig. S2). We

found that our probabilistic method had a considerably better recall and precision

compared to the cutoff based method.

Integration through Hidden Markov Model

After removing reads with low mapping quality, and masking blacklist regions from

downstream analysis [14], HMMRATAC identifies a set of training regions throughout

the genome to train a 4-states Hidden Markov Model (HMM) with multivariate Gaussian

emissions, representing the underlying four chromatin states of 1) the *center* of open

chromatin, 2) the *flanking regions*, 3) the *non-flanking regions* and 4) the *background*

(Fig. 1a). By default, training regions can be either specified by users or automatically

selected where the signal fold-change above background falls within a predetermined

range. After signal decomposition, a matrix of 10bp resolution signals for NFRs, 1Ns,

2Ns, and 3Ns in training regions is used to train the parameters in HMM through the

Baum-Welch algorithm [15]. The initial state transition probabilities are set equally as

0.25 and the emission parameters for each state are calculated after clustering all

locations in the training regions into 4 classes (See methods section for more detail).

Table 1 shows the final parameters for the HMM on ATAC-seq in the GM12878 cell

line, again generated by merging three replicates from [5]. Although the parameters will

change depending on the choice of training regions and the datasets provided, several key

characteristics are evident in the model and remain largely stable with different settings

and data. State 4 in the table, which HMMRATAC annotated as the *center* state, showed

the highest average signal across the four signal profiles. State 3, annotated as the

flanking region state, showed the second highest average values. Additionally, as we

hypothesized, the results show the *center* state mainly transit from or to the *flanking*

regions state.

After learning the model, HMMRATAC takes a matrix of genome-wide NFRs, 1Ns, 2Ns,

and 3Ns signals and labels each genomic locations with one of the states using the Viterbi

algorithm [16]. On the 50K cells ATAC-seq data in GM12878 cell line, there were about

4.5 million regions annotated as *background* with an average size of 254 bps (38% of

genome size), about 2.8 million regions annotated as *non-flanking regions* with an

average size of 235 bps (22%), about 3.7 million regions annotated as *flanking regions*

with an average size of 303 bps (37%), and about 166 thousand regions annotated as

center regions with an average size of 494 bps (3%). HMMRATAC finally connected

the *center regions* with their adjacent *flanking nucleosomes* and called a total of 93,276

accessible regions with an average size of 1,574 bps (5% of genome size), excluding

those with abnormally high coverage and those below a minimum length (see method

section for more details). It should be noted that many of the *flanking regions* do not

actually flank the *center* state. These may represent non-regulatory nucleosomes that

ATAC-seq is able to identify or may be artifacts due to increased transposition frequency.

Recapitulating chromatin architecture at functional elements

We hypothesized that HMMRATAC could identify chromatin architecture around

accessible regions, or ideally, nucleosomes near the regulatory elements. To prove this,

we explored the distribution of histone modification ChIP-seq signal around our

identified accessible regions. We downloaded and analyzed datasets released by

ENCODE in the GM12878 cell line [9], including ChIP-seq for CTCF, active histone

marks such as H3K4me1, H3K4me3, H3K9ac, and H3K27ac, repressive histone marks

such as H3K9me3 and H3K27me3, as well as sequencing of micrococcal nuclease

digestion (MNase-seq) and DNaseI digestion (DNase-seq). Fig. 2a shows a locus on

chromosome 1 identified as an accessible region by HMMRATAC. We observed that the

center state was located in regions characterized by depletion in both active histone

marks and MNase digestion, and by enrichment in DNase digestion and CTCF signal.

The surrounding *flanking nucleosome* states showed enrichment in active histone marks

and MNase digestion, together with depleted DNase digestion and CTCF signal. We

next plotted the same ChIP-seq, DNase-seq and MNase-seq data around all *center* states

and used k-means clustering to group the resulting profiles (Fig. 2b). We found that

HMMRATAC states can identify, what appear to be, different types of regulatory

elements. For example, the first cluster characterized by strong enrichment of H3K27ac

relative to H3K4me1 seems to indicate active enhancers while the third cluster marked by

high levels of H3K4me1 and more moderate levels of H3K27ac would suggest poised

enhancers (Fig. 2b). The second cluster, characterized by strong enrichment of CTCF

binding and lower levels of histone modifications, seems to suggest that this cluster

represents insulators or domain boundaries. Taken together, these results indicate that

HMMRATAC can recapitulate the histone architecture around accessible regions.

Functional regulatory elements that harbor transcription factor binding sites are generally

under higher evolutionary constraint [17]. Success in transcription factor ChIP-seq data

analysis is often benchmarked by high PhastCons score, a precompiled evolutionary

conservation score at every base pair [18], at the peak center or summit, relative to the

surrounding regions [19]. We found that the summits of accessible regions detected by

HMMRATAC in GM12878 cell line also showed PhastCons enrichment in vertebrates

(Additional file 1: Fig. S4), indicating that these summits were likely locations of

evolutionarily conserved regulatory elements and could represent functional regulatory

elements.

Method comparison with MACS2, F-seq, and Hotspot2

We next sought to compare the performance of HMMRATAC in identifying open chromatin regions to other popular software for ATAC-seq. We chose MACS2 [20], F-seq [21] and Hotspot2 [22], which had previously been shown to be the most accurate peak-callers in identifying open chromatin regions from DNase-seq [23]. MACS2, originally designed for ChIP-seq, utilizes a local Poison model wherein enrichment is calculated relative to a local Poisson model. F-seq invokes a Gaussian kernel-smoothing algorithm and then calculates enrichment based on the resulting Gaussian distribution. Hotspot2, originally designed for DNase-seq, calculates enrichment in a narrow window relative to a larger local window using the binomial distribution. Although none of them utilize the intrinsic and unique features in ATAC-seq data we described before, MACS2 has been used to analyze ATAC-seq data in many published works [6, 24-29], and MACS2 and F-seq is part of the ENCODE analysis pipeline for ATAC-seq data [30]. We tested the performance of the four algorithms using the two ATAC-seq datasets in GM12878 cell line [5] as the previous sections.

A major limitation in comparing the performance of identifying open chromatin regions is the absence of a valid "gold standard" [2]. To overcome this problem, we chose to compare the performance of HMMRATAC and the other algorithms to three distinct independent datasets as the proxies of true and false set: 1) the active regions and heterochromatins from chromatin states analysis combining multiple histone modification

features[31], 2) DNase-seq [3] and 3) FAIRE-seq [4] accessible regions of the same

GM12878 cell line. We also used replicate reproducibility and biological reproducibility

to assess each methods' robustness, following the guidelines developed for ChIP-seq by

the ENCODE and modENCODE consortiums [32].

Enrichment in chromatin states of active regions

The first proxy of the true set that we compared the algorithms to is referred to as "active

regions." These sites were defined through an integrative chromatin state segmentation

using chromHMM [31, 33] algorithm conducted by ENCODE project. 8 histone

modifications (H3K27me3, H3K36me3, H4K20me1, H3K4me1, H3K4me2, H3K4me3,

H3K27ac and H3K9ac), 1 transcription factor (CTCF) ChIP-seq and 1 whole genome

input datasets in the GM12878 cell line were integrated through an unsupervised machine

learning approach and each genomic location was annotated as one of 15 mutually-

exclusive states. Two resulting states, "active promoters" and "strong enhancers", were

merged together to create our list of "active regions". Additionally, the state annotated as

"heterochromatin" was used as a false set. We tested different cutoff values for each

algorithm (see Methods) and found that HMMRATAC outperformed the other

algorithms, in terms of precision, recall, and false positive rate in identifying these

"active regions" while avoiding "heterochromatin" (Fig. 3a top panel, Fig. 3b top panel).

We also found that HMMRATAC outperformed the other algorithms in terms of F1-

scores, the harmonic mean of precision and recall (Fig. 3c top panel). The area under the

curve (AUC) was then calculated for the recall vs. false positive rate curves (AU-ROC)

and for the precision vs. recall curves (AU-PRC) (Table 2). HMMRATAC was proved to

have better AUC than the three other methods. Taken together, these results indicate that

HMMRATAC is able to identify active chromatin regions with a higher recall and

precision and lower false positive rate, than MACS2, F-seq or Hotspot.

Consistency with results from DNase-Seq and FAIRE-Seq

We then used the accessible chromatin regions detected by two independent assays

DNase-seq and FAIRE-seq in GM12878 cell line as cross-validation of ATAC-seq

analysis. We downloaded DNaseI hypersensitive sites (DHSs) [3] and FAIRE-seq [4]

accessible regions called by ENCODE in the GM12878 cell line [9, 34], then merged

DHSs or FAIRE accessible regions that were within 2kb of each other to define our

alternative true sets. We continued to use the heterochromatin states outlined above as

our false set, although we eliminated any DHSs or FAIRE regions that overlapped a

heterochromatin state region and vice versa. We found that HMMRATAC outperformed

the other three methods in terms of precision, recall, false positive rate, and F1-score in

recapitulating DHSs (Fig. 3a, 3b, and 3c middle panels) as well as in AU-ROC and AU-

PRC (Table 2). As for FAIRE regions, we found that HMMRATAC outperformed the

other methods in recall vs. false positive rate, and the corresponding AU-ROC for FAIRE

accessible regions (Fig. 3a bottom panel, Table 2). F-seq was found to perform the best

in terms of F1-score and AU-PRC with the FAIRE-seq data (Fig. 3b, and 3c bottom

panel, Table 2).

Reproducibility in replicates

A common and robust method to gauge a method's performance in analyzing next-

generation sequencing data, in particular, ChIP-seq, is the robustness in technical and

biological replicates [32]. One such way to measure the reproducibility of peak callers is

the Irreproducible Discovery Rate (IDR) [35]. Therefore we sought to test the

reproducibility of HMMRATAC and the other algorithms in utilizing ATAC-seq

datasets. We calculated the number of reproducible accessible regions, defined as

overlapping accessible regions with an IDR score <= 0.05, between each pair of three

replicates for each algorithm. We show that when using the individual replicate data

(Fig. 4a), HMMRATAC produced a higher average number of reproducible accessible

regions than the other three algorithms. We found that Hotspot2 performed well in terms

of reproducibility while MACS2 and F-seq underperform both HMMRATAC and

Hotspot2 (Table 2)

Furthermore, we hypothesized that the biology (open chromatin) should be consistent

even with a smaller number of cells used in ATAC-seq. We tested how well each

algorithm performed at recapitulating the accessible regions called from the 50,000 cell

per-replicate data and the 500 cell per-replicate data. We found, similar to the results

from pair-wise replicate testing, that HMMRATAC was able to identify more

reproducible accessible regions, with IDR <= 0.05, using the different datasets than any

of the other algorithms (Fig. 4b). Once again, Hotspot performed well and identified

only slightly fewer reproducible accessible regions than HMMRATAC, while MACS2

and F-seq identified fewer (Table 2). These data indicate that HMMRATAC outperforms

Hotspot, MACS2, and F-seq in identifying statistically reproducible accessible regions.

The summary of method comparisons is shown in Table 2. We used a total of 8

independent measures to benchmark the performance of the four algorithms, including

AUC-ROC, AUC-PRC, and the numbers of reproducible regions as described before.

We found that HMMRATAC outperformed the other three methods in 7 of those 8

benchmarks. F-seq outperformed the other methods in 1 of the 8 benchmarks. F-seq also

came in second in 5 of the 6 AUC calculations, although it performed the worst in terms

of the reproducibility benchmarks. Hotspot2 performed very poorly at all of the AUC

calculations but came in second in both reproducibility benchmarks. MACS2 performed

very similar to F-seq in all benchmarks but never ranked higher than second in any of

them. Overall, these results indicate that HMMRATAC is the most accurate and reliable

peak-caller for ATAC-seq data analysis.

Application for mouse cells

Thus far, we have shown the performance of HMMRATAC and other algorithms with

data generated in the human GM12878 cell line. In order to determine our method's

performance with different data sets, different cell lines, and different species, we

analyzed ATAC-seq data generated in C2C12 myoblast mouse cells [13]. In addition to

ATAC-seq, Dell'Orso et al. performed ChIP-seq on the same cells for the active histone

mark histone H3K27ac and the repressive histone mark histone H3K27me3. Using the

active histone modification as the "true set" and the repressive histone modification as

the "false set", we compared the performance of the algorithms in the same way we

compared their performance in human data (Additional file 1: Fig. S5). We show that

HMMRATAC has superior precision, sensitivity, and specificity over both MACS2 and

F-seq. Hotspot2, for reasons unknown, was unable to process this data set. Overall, this

data indicates that HMMRATAC's superior performance over the other algorithms is

consistent across different data sets, different species, and different cell lines.

Discussion

HMMRATAC is designed to integrate the nucleosome-free and nucleosome-enriched

signals derived from a single ATAC-seq dataset in order to identify open chromatin

regions. For this reason, HMMRATAC should not be used on ATAC-seq datasets that

have undergone either physical or computational size selection. For that same reason,

single-end sequence libraries from ATAC-seq cannot be analyzed with HMMRATAC.

Therefore, a reasonable way to evaluate the quality of ATAC-seq data for HMMRATAC

analysis is to check the length distribution of the transposition fragments to ensure that

large fragments are present and relatively abundant.

The Tn5 transposase has an insertion preference for specific DNA sequences, as do

nucleases used in similar or complementary assays such as DNase-seq or MNase-seq.

We believe that such biases would have little effect on the performance and accuracy of

HMMRATAC for the following reasons. First, because HMMRATAC considers the

structure at regulatory chromatin, regions with an increase in transposition frequency

caused by a sequence preference and not by a depletion of nucleosomes, would be

unlikely to possess the characteristic pattern of nucleosome-free and nucleosome-

enriched signals and would not be identified as accessible by HMMRATAC. Second,

due to the smoothing strategy during peak calling, either by HMMRATAC or other

algorithms and the requirement for minimum peak size, such localized enrichment events

are unlikely to influence the peak call.

Identifying transcription factor footprints, wherein the DNA protected by a binding

protein shows resistance to nonspecific DNA digestion, is an area of active research.

However, we don't believe that the conventional strategies for footprint identification, i.e.

looking for a small window of depletion within a broader region of enrichment of cutting

events, are reasonable for ATAC-seq. First, the contamination from mitochondrial DNA

is a major concern in the common ATAC-seq protocol and it varies with different cell

types, so to identify fine features such as footprints requires higher sequencing depth

from ATAC-seq than that from other assays. Moreover, although the sequence bias of

the Tn5 transposase would have little effect on identifying open regions, it will have a big

impact on footprints. Although footprint identification may be possible with certain

datasets or for certain transcription factors, we believe that HMMRATAC identified

summits, or the position with the most insertion events within the open region, are more

robust to identify potential transcription factor binding sites.

It is possible to extend HMMRATAC to identify differentially accessible regions

between two or more conditions. Most of the approaches for identifying such differences

from ATAC-seq data would suffer from the same problems mentioned before, namely,

that these methods only consider the relative strength of the signal and the differences in

signal intensity between conditions. As we've shown here, the incorporation of the

structure of regulatory chromatin into a model could increase the accuracy and sensitivity

of a differential accessibility analysis pipeline.

Conclusions

ATAC-seq shows numerous advantages over other methods for identifying open

chromatin regions, such as DNase-seq and FAIRE-seq, owing to its low starting material

requirement and simple protocol. For these reasons, ATAC-seq has become one of the

standard assays for locating regions of open chromatin, particularly as biomedical

research continues to move toward translational research and precision medicine.

Although the number of published ATAC-seq datasets increases rapidly, researchers are

still using methods originally developed for ChIP-seq to analyze the data. We present

HMMRATAC as a dedicated algorithm for the analysis of ATAC-seq data. We take

advantage of the nature of the ATAC-seq experiment that due to the lack of size-selection

while preparing the DNA library in its protocol, DNA fragments associated with well-

positioned nucleosomes around open chromatin will be sequenced as well. Therefore, as

a side note, HMMRATAC shouldn't be applied to those ATAC-seq data generated with a

stringent size-selection on DNA fragments. Different with current methods where only

the read enrichment is considered, HMMRATAC separates and integrates ATAC-seq

data to create a statistical model that identifies the chromatin structure at accessible and

active genomic regions.   We have shown that HMMRATAC outperforms other

computational methods in recapitulating open and active chromatin identified with other

assays such as chromatin state analysis integrating multiple histone mark ChIP-seq,

DNase-seq and FAIRE-seq. We have also shown that HMMRATAC shows better

reproducibility among replicates, as well as in datasets generated from a different number

of cells. As HMMRATAC is a cross-platform and user-friendly algorithm, we envision it

becoming the standard for ATAC-seq data analysis, replacing current methods based on

ChIP-seq analysis.

Methods

Preprocessing of ATAC-seq data

The human GM12878 cell line ATAC-seq paired-end data used in this study was

publically available and downloaded under six SRA [36] accession numbers SRR891269-

SRR891274[5].   There are three biological replicates generated using 50,000 cells per

replicate and other three generated using 500 cells per replicate.   Each dataset was

aligned to the hg19 reference genome using bowtie2 [37].   After alignment, each group of

replicates (either 50,000 cells or 500 cells) were merged together, sorted and indexed.

Reads that had a mapping quality score below 30 or that were considered duplicates

(exact same start and stop position) were removed from the merged files.   It should be

noted that HMMRATAC will remove duplicate and low mapping quality reads by

default, although some other algorithms do not.

The merged, filtered and sorted BAM files, created as described above, were the input for

MACS2 and Hotspot. HMMRATAC took the sorted paired-end BAM file and its

corresponding BAM index file as the main inputs. In addition, HMMRATAC requires a

genome-wide read coverage file in BigWig format. To generate the coverage file,

MACS2 was run with the option set for reporting the read coverage in BedGraph format

(option –B) and this BedGraph was then converted to a BigWig file using UCSC's

bedGraphToBigWig program. F-seq requires a single-end BED file of read alignment

results as its input. To generate this BED file, we converted the paired-end BAM file into

a BED file, using an in-house script, and split each read pair into forward and reverse

strand reads.

The mouse data was publically available and downloaded under the accession numbers

SRR2999996 and SRR2999997 [13]. This data was generated from 50,000 C2C12

myoblast cells. Two replicates of ATAC-seq data were aligned to the mm10 reference

genome using bowtie2 [31]. All pre-processing steps were identical to the human

processing pipeline described above, including merging and filtering.

The HMMRATAC algorithm

Segregation of ATAC-Seq signals

After the preprocessing step that eliminates duplicate reads and low mapping quality

reads, the main HMMRATAC pipeline begins by separating the ATAC-seq signal into

four components, each representing a unique feature. These features are nucleosome-free

fragments (NFRs), which are most likely to occur within the open chromatin region itself,

and three nucleosomal features, representing mono-, di- and tri-nucleosomes (1Ns, 2Ns

and 3Ns), respectively. We utilize four distributions to represent the four signal tracks:

an exponential distribution for the nucleosome-free track and three Gaussian distributions

to represent the three nucleosomal signal tracks. The mean value of the exponential

distribution for NFRs is set as a fixed value at runtime, either as the default value or a

user-defined value. The parameters of three Gaussian distributions are initialized at

runtime with default or user-defined values and then updated using the expectation

maximization (EM) algorithm for Gaussian mixture models. Briefly, each nucleosomal

fragment, those larger than 100bp, is classified as belonging to one of the nucleosomal

distributions based on its weighted probability. Once each fragment has been classified,

new means, standard deviations, and weights are calculated for each distribution and

become the new values for the mixture model. This process continues iteratively until

the change in the mean values between iterations is less than a reasonable epsilon value.

At this point, the model is assumed to have reached convergence and the EM process is

halted (Fig. 1c and 1d). In order to decrease the time required for the EM algorithm,

HMMRATAC randomly sub-selects 10% of all the fragments to use as the training data.

Once the parameters of the four distributions have been determined, HMMRATAC

creates four genome-wide signal tracks. For every genomic position, all of the fragments

that occupy that position are determined.   Each track is then incremented by the

probability that a particular fragment belongs to the tracks' corresponding distribution

(Fig. 1b).

Training the Hidden Markov Model of accessible chromosomal regions, and refining

the model with the Baum-Welch algorithm

Once the four signal tracks have been created, the main HMMRATAC process begins.

HMMRATAC first identifies up to 1000 training regions throughout the genome, with

which it learns the model. These training regions are determined by scanning the genome

for regions whose read coverage fold changes over background falls within a certain

range. The default upper and lower limit of fold changes, as used in Result section, is set

between 10 and 20. These regions are then extended by 5KB in either direction. It is

also possible for users to provide a BED file containing predefined training regions. The

initial HMM has proportional initial probabilities, which are not updated during training,

as well as proportional transition probabilities, which are updated during training. The

emission probabilities are calculated with k-means clustering [38], by separating the

training regions into 4 clusters and calculating the means and covariance matrices for the

four signal tracks for each cluster, thereby modeling the emissions as a multivariate

Gaussian distribution.   These four clusters represent the four states of our model,

corresponding to the *center* of the open region, the *flanking nucleosomes*, the outer *non-*

flanking nucleosomes and a *background* state, respectively. It is also possible to create a

model using a different number of states instead of 4, although this option is not generally

recommended. Once this initial HMM is created, the transition and emission parameters

are updated with the Baum-Welch algorithm [15] until convergence.

Annotating with the Viterbi algorithm

Once the HMM has been created and refined, the Viterbi algorithm [16] is used to

classify every genomic position into one of the four states of our model. In our

experience, Viterbi has trouble when encountering a very high coverage region.

Therefore, regions whose z-scored coverage is above a certain cutoff, either a default or

user-defined value, are masked from the Viterbi algorithm. Additionally, it is possible to

include a list of genomic regions to mask along with the extremely high coverage

regions, such as annotated blacklisted sites. A genome-wide BedGraph of all state

annotations can be reported by HMMRATAC, although this is not the default behavior.

By default, HMMRATAC will take all regions classified as belonging to the open state

and whose length is above a default or user-defined threshold and merge them with the

nucleosome states located both upstream and downstream of the open state. We

generally consider the nearby nucleosomes to be part of the regulatory region, and

therefore the region is then reported as a peak in gappedPeak format.

It should be noted that at all stages of the algorithm, HMMRATAC does not store the

read or coverage information in memory. Any information needed by the program is

read from the desired file and used at the specific time. This was incorporated to reduce

the memory usage of HMMRATAC. However, because of this feature, it is not

recommended to run HMMRATAC simultaneously with the same data files.

Post-processing and output

When the report peak option is set for HMMRATAC (option -p True), the peak region is

reported in gappedPeak format. The total peak region reported is a region that was

classified as being in the *center* state of the model (and is longer than a default or user-

supplied length cutoff) along with the nucleosome states, both upstream and downstream.

Each peak is given a score, which represents the maximum read coverage of the open

state. It is also possible to report the average read coverage, the median coverage, and

the fold change above the genomic background, the zscore of the average coverage or all

values. Additionally, those high coverage regions that are masked from Viterbi decoding

(see above), are added back to the final peak file. They are annotated by HMMRATAC

as "High Coverage Accessible regions". The user may then keep or discard these regions

and explore them as they see fit.

Additionally, when the report peak option is set, HMMRATAC also supplies an

additional file containing the summits of each peak. To calculate a summit,

HMMRATAC first smoothes the read coverage signal through the *center* state using a

Gaussian smoothing function with a window size of 120bp. It then calculates the

position that has the maximum read coverage and reports that position as the summit.

Evaluation

Calculating Precision, Recall, False Positive Rate and F1-scores

Let Predicted Positive (PP) represent the number of base pairs identified as accessible regions from any method. Let Real Positives (RP) represent the number of base pairs in the "gold standard" sets (described below). Let Real Negatives (RN) represent the number of base pairs in the "real negative" set described below. Let True Positive (TP) represent the number of overlapping base pairs between a called peak and a real positive. Let False Positive (FP) represent the number of overlapping base pairs between a called peak and a real negative.

Then *precision* or positive predictive value (PPV) is calculated as:

$PPV = TP/TP+FP$

Recall, or true positive rate (TPR), is calculated as:

$TPR = TP/RP$

False positive rate (FPR) is calculated as:

$FPR = FP/RN$

The F1-score is the harmonic mean of precision and recall and is calculated according to the equation:

F1 = 2 * ((precision * recall)/(precision + recall)).

The number of overlapping base pairs was calculated with the BEDTools intersect tool

[39] and custom python scripts.

Compiling the "Gold Standard" lists and "True Negative" set

We tested the performance of HMMRATAC and other methods against three "gold

standard" datasets. The first one, which we call "Active Regions", is made by combining

two chromatin state annotations generated in GM12878 cells using chromHMM [31, 33]

(wgEncodeBroadHmmGm12878HMM). These two annotations are "Active Promoters"

and "Strong Enhancers".

The other two "gold standard" test sets that were used in this study were DNaseI

hypersensitive sites (wgEncodeAwgDnaseUwdukeGm12878UniPk) and FAIRE

accessible regions (wgEncodeOpenChromFaireGm12878Pk) [9, 34]. We found that there

were numerous cases throughout the genome where clusters of DNase or FAIRE

accessible regions were in close proximity to one another. These clusters tended to have

broad enrichment in either DNase-seq or FAIRE-seq signal across the regions.

Therefore, we merged all accessible regions that were within 2KB of each other into a

single peak and used these merged sets as the "gold standard" sets.

The "real negative" set was made with the "Heterochromatin" annotation from

chromHMM. When using the "active region" set, no modifications were necessary

because the three states are mutually exclusive. When using either the DNase or FAIRE

sets, any "heterochromatin" states that overlapped (by any amount) a DNase or FAIRE

peak were excluded from the final "real negative" set. Additionally, any DNase or

FAIRE peak that overlapped any "heterochromatin" state (by any amount) was, likewise,

excluded from its respective "gold standard" set.

The "gold standard" set used for the mouse data were H3K27ac ChIP-seq accessible

regions from the C2C12 myoblast cell line [13]. The raw sequencing data was

downloaded under the SRA accession numbers SRR2999984-5, aligned to the mm10

reference genome using bowtie2 (using default parameters as with all alignments

performed in this study). The resulting aligned reads were merged and broad peaks were

called with MACS2 using the parameters –g mm, --broad, --nomodel, --extsize 150 and –

p 0.12.

The "real negative" set for the mouse data were H3K27me3 peaks from the same cell

type [13]. The raw sequencing reads were downloaded under the SRA accession number

SRR2999992, aligned to the mm10 reference genome with bowtie2 and processed into

broad peaks with MACS2 using the parameters –g mm, --broad, --nomodel, --extsize 150

and –p 0.03.

The p-value parameter for MACS2 broad peak calling, for both histone marks, were

determined by setting multiple values and then calculating the number of peaks called

versus the parameter value. The point where the number of peaks called began to rapidly

increase or decrease relative to the parameter value was considered the best value for

broad peak calling (data not shown).

When calling broad peaks from MACS2, for either histone mark, an input file was used.

This data was downloaded under the accession number SRR3139303 and aligned to the

mm10 genome using bowtie2. The aligned read file was then used as an input control (-c

option).

Calls from MACS2, F-Seq, Hotspot, and HMMRATAC

Version 2.1 of MACS was used to call peaks using the sorted paired-end BAM files

created as described above. With each run the input file format (option –f) was set to

"BAMPE" and the option for keeping duplicate reads (option –keep-dup) was set to "all",

as duplicate reads had already been discarded in pre-processing. MACS2 was run with

the local lambda option turned off (option --nolambda) and was run with q-value cutoffs

(option –q) set to 0.5, 0.1, 0.05 (default), 0.005, 0.0005 and 0.00005. It was also run with

a p-value cutoff (option –p) set to 0.6.

Version 1.84 of F-Seq was used to call peaks using the single-end BED files created as

described previously. With each run, the output was reported as a BED file (option –of).

The standard deviation cutoff (option –t) was set to 0.1, 1, 4 (default), 6, 7, 8, 10, 15 and

20.

Version 4.1 of Hotspot was used to call peaks from the BAM files created as described

previously. Hotspot was run using the shell script provided in the release (runhotspot)

with parameters laid out in the token file (runall.token.txt). This script automatically

calls several programs in the Hotspot pipeline and outputs a peak BED file. The tag

length was set to 50bp (_K_ = 50) and duplicate tags were allowed (_DUPOK_ = T)

(considering that they had been removed previously, this setting has little effect). The

FDR settings (_FDR_) used were 0.1, 0.05, 0.01 (default) and 0.005. It should be noted

that the Hotspot pipeline would not finish or report completed peak BED files at higher

or lower cutoffs. Mappable files were downloaded from hotspot website [40] for both

mm10 and hg19 and used by the hotspot pipeline (_MAPPABLE_FILE_). Blacklisted

regions for hg19 were also used to mask these regions from peak calling [9, 14].

Additionally, Hotspot was unable to process the mouse data with any setting.

HMMRATAC was run using the sorted BAM files, BAM index files and genome-wide

coverage files created as described previously. The upper limit fold-change for choosing

training regions (option –u) was set to 20 with corresponding lower limits (option –l) set

to 10. These settings are the HMMRATAC defaults. HMMRATAC was also run using

blacklisted sites for hg19 [9, 14], which were masked from the program and all

subsequent steps. For the precision, recall and false positive rate calculations, the

HMMRATAC peaks were filtered by minimum score cutoffs of 0, 5, 10, 15, 20, 25, 30,

35 and 40. Additionally, HMMRATAC was run using non-default settings where the

upper limit (option –u) was set to 10 and the lower limit (option –l) was set to 2. The

minimum scores of 0 and 5 filtered these peaks.

Calculating reproducibility

Reproducibility was determined using the Irreproducible Discovery Rate (IDR) originally

described by Li et al. [35]. Peaks were called using the following parameters: the q-value

for MACS2 was set to 0.87 for 50,000 cell per-replicate data and 0.89 for 500 cell per-

replicate data, the standard deviation for F-seq was set to 6 for both datasets, Hotspot

FDR values were set to 0.05 for both datasets and the fold-change range for

HMMRATAC was set to 2-10 for both datasets. The parameters for MACS2 and F-seq

were determined by setting multiple values and then calculating the number of peaks

called versus the parameter value. The point where the number of peaks called began to

rapidly increase or decrease relative to the parameter value was considered the best value

for IDR analysis (data not shown).

For calculating the 500 to 50,000 cell per-replicate reproducibility, each method was run

using the merged file(s) described previously, with the respective parameters as described

previously. For each method, each pair of resulting peak files, from the 500 cell per-

replicate and 50,000 cell per-replicate datasets, were run through the IDR algorithm using

default parameters and each methods' respective score column as the rank. The output

files were sorted by their local IDR value and plotted as ranked peaks versus IDR score.

For replicate testing, each method was run with the same parameters as described

previously, using the individual replicate file(s) as their input. Each possible pair of

replicates was then run through the IDR algorithm with default parameters. For each

replicate pair, the number of peaks whose local IDR score was equal to or below 0.05

was calculated and plotted.

Abbreviations

ATAC-seq: assay for transposase-accessible chromatin with sequencing; ChIP-seq:

chromatin immunoprecipitation with sequencing; MNase-seq: Micrococcial nuclease

digestion with sequencing; FAIRE-seq: formaldehyde assisted isolation of regulatory

elements; DNase-seq: DNaseI digestion with sequencing; DNA: deoxyribonucleic

acid; HMM: hidden markov model; HMMRATAC: hidden markov modeler for ATAC-

seq; NFR: nucleosome free region; DHS: DNaseI hypersensitive sites; ENCODE:

encyclopedia of DNA elements; EM: Expectation-Maximization algorithm; 1N: mono-

nucleosome; 2N: di-nucleosome; 3N: tri-nucleosome; BP: base-pairs; KB: kilo base-

pairs; MB: mega base-pairs; CTCF: CCCTC binding factor; AUC: area under the curve;

ROC: receiver operator characteristic; AUPRC: area under the precision recall curve;

AUROC: area under the receiver operator characteristic curve; IDR: irreproducible

discovery rate; PP: predicted positive; RP: real positive; RN: real negative; TP: true

positive; FP: false positive; PPV: positive predictive value; TPR: true positive rate;

FPR: false positive rate

Declarations

Funding

This work was supported by the startup fund for TL from Jacobs School of Medicine and

Biomedical Sciences, University at Buffalo.

Availability of data and materials

The HMMRATAC source code, executable file, quick start guide and javadocs can be

downloaded from https://github.com/LiuLabUB/HMMRATAC. All peaks/regions called

by HMMRATAC, FSeq, Hotspot2, and MACS2, as well as the various "gold standard"

files, can be downloaded from the following URL:

http://biomisc.org/download/HumanData.tar.gz and

http://biomisc.org/download/MouseData.tar.gz.

Authors' contributions

EDT and TL conceived and designed the computational method. EDT developed the

software package, implemented the method and analyzed the data. EDT and TL wrote the

paper. All authors read and approved the final manuscript.

Competing interests

The authors declare that they have no competing interests.

Ethics approval and consent to participate

Ethics approval is not applicable for this study.

752 **Tables**

754 **Table 1. Hidden Markov Model trained from GM12878 ATAC-Seq data.**

756 Numbers show transition probabilities from each state to other states, and emission

757 probabilities of NFR, 1Ns, 2Ns, and 3Ns signals for each state.

State index	1	2	3	4
Annotation	Background	Non-flanking	Flanking	Open
Transition to State 1	0.942	0.027	0.019	0
Transition to State 2	0.025	0.958	0.008	0
Transition to State 3	0.033	0.015	0.967	0.01
Transition to State 4	0	0	0.005	0.99
Mean value of NFR	0.001	0.032	0.037	0.117
Mean Value of 1Ns	0	0.069	0.079	0.21
Mean Value of 2Ns	0.021	0.033	0.07	0.183
Mean Value of 3Ns	0.022	0.006	0.049	0.125

Table 2. Summary of method comparisons of HMMRATAC, MACS2, FSeq, and

HotSpot2.

Area under the curves calculated for the three ROC curves (Fig. 3a) and for the three

precision vs. recall curves (Fig. 3b), the median number of reproducible peaks from

pairwise replicate testing (Fig. 4a) and the number of reproducible peaks between 500

cells per replicate and 50,000 cells per replicate data with a local IDR value below 0.05

(Fig. 4b). The numbers of the best performance are shown in bold.

Method	Active regions		DNase-seq		FAIRE-seq		Reproducible Peaks within Replicates	Reproducible Peaks 500 to 50K cells
	AUC-ROC	AUC-PRC	AUC-ROC	AUC-PRC	AUC-ROC	AUC-PRC		
HMMRATAC	**0.895**	**0.618**	**0.865**	**0.592**	**0.844**	0.550	**43,942**	**20,842**
MACS2	0.815	0.521	0.805	0.554	0.801	0.575	24,317	12,696
F-seq	0.826	0.526	0.817	0.565	0.818	**0.592**	15,008	10,123
Hotspot2	0.581	0.260	0.607	0.362	0.611	0.362	39,787	17,296

Figure Legends

Fig. 1 The HMMRATAC Algorithm.

a. A schematic to represent the structure of an accessible region. **b.** The algorithmic

workflow. Estimation of fragment length parameters through Expectation Maximization

algorithm: **c.** Mean and **d.** standard deviation parameters per EM iteration for three

nucleosomal distributions are consistent among datasets using 50,000 and 500 cells per

replicate.

Fig. 2 Chromatin Architecture at HMMRATAC Peaks.

a. IGV browser snapshot of various signals around FAM212B locus on chromosome 1.

Top three tracks show ATAC-seq signals, after being separated by size, the fourth track

shows CTCF ChIP-seq signal, fifth through eighth tracks show various histone

modification ChIP-seq signal and ninth track shows MNase-seq signal. The bottom panel

shows RefSeq genes, HMMRATAC center and flanking nucleosome annotations (called

with default settings), MACS2 peaks (called with default parameters), "Active

Promoters" and "Strong Enhancers" state annotations from chromHMM (see methods

section). **b.** Various ChIP-seq, DNase-seq and MNase-seq signals plotted across all *open*

states. Data were clustered using k-means algorithm into 5 clusters.

Fig. 3 HMMRATAC outperforms other methods in precision, recall and false

positive rate.

a. Receiver Operator Characteristic (ROC) plots for the real positive and real negative

pairs of 1. Active regions vs. heterochromatin (top panel), 2. DNase peaks vs.

heterochromatin (middle panel) and 3. FAIRE peaks vs. heterochromatin (bottom panel).

Note: the endpoints, (0,0) and (1,1), are added to the plots for completeness. **b.** Precision

vs. Recall plots for the real positive – real negative pairs of 1. Active regions vs.

heterochromatin (top panel), 2. DNase peaks vs. heterochromatin (middle panel) and 3.

FAIRE peaks vs. heterochromatin (bottom panel). Note: the endpoints, (0,1) and (1,0),

are added to the plots for completeness**. c.** Boxplots showing the F1-scores of the four

methods for the data shown in B.

Fig. 4 HMMRATAC shows better reproducibility in peak calls, over other methods.

a. The numbers of reproducible peaks, identified with an IDR value below 0.05, from

three pairwise replicate tests for each method. **b.** The numbers of overlapping peaks,

identified with 500 cells per replicate and 50,000 cells per replicate, versus local IDR

value. The horizontal line represents IDR value of 0.05.

References

1.   Li G, Reinberg D: **Chromatin higher-order structures and gene regulation.**

Curr Opin Genet Dev 2011, **21:**175-186.

2.   Tsompana M, Buck MJ: **Chromatin accessibility: a window into the genome.**

Epigenetics Chromatin 2014, **7:**33.

3.   Boyle AP, Davis S, Shulha HP, Meltzer P, Margulies EH, Weng Z, Furey TS,

Crawford GE: **High-resolution mapping and characterization of open**

chromatin across the genome. *Cell* 2008, **132:**311-322.

4.   Giresi PG, Kim J, McDaniell RM, Iyer VR, Lieb JD: **FAIRE (Formaldehyde-**

Assisted Isolation of Regulatory Elements) isolates active regulatory elements

from human chromatin. *Genome Res* 2007, **17:**877-885.

5.   Buenrostro JD, Giresi PG, Zaba LC, Chang HY, Greenleaf WJ: **Transposition of**

native chromatin for fast and sensitive epigenomic profiling of open

chromatin, DNA-binding proteins and nucleosome position. *Nat Methods*

2013, **10:**1213-1218.

6.   Buenrostro JD, Wu B, Litzenburger UM, Ruff D, Gonzales ML, Snyder MP,

Chang HY, Greenleaf WJ: **Single-cell chromatin accessibility reveals**

principles of regulatory variation. *Nature* 2015, **523:**486-490.

7.   Mei S, Qin Q, Wu Q, Sun H, Zheng R, Zang C, Zhu M, Wu J, Shi X, Taing L, et

al: **Cistrome Data Browser: a data portal for ChIP-Seq and chromatin**

accessibility data in human and mouse. *Nucleic Acids Res* 2017, **45:**D658-

D662.

8.   Barski A, Cuddapah S, Cui K, Roh TY, Schones DE, Wang Z, Wei G, Chepelev

848   I, Zhao K: **High-resolution profiling of histone methylations in the human**

849   **genome.** *Cell* 2007, **129:**823-837.

850   9.   Consortium EP: **An integrated encyclopedia of DNA elements in the human**

851   **genome.** *Nature* 2012, **489:**57-74.

852   10.   Bell O, Tiwari VK, Thoma NH, Schubeler D: **Determinants and dynamics of**

853   **genome accessibility.** *Nat Rev Genet* 2011, **12:**554-564.

854   11.   Lantermann AB, Straub T, Stralfors A, Yuan GC, Ekwall K, Korber P:

855   **Schizosaccharomyces pombe genome-wide nucleosome mapping reveals**

856   **positioning mechanisms distinct from those of Saccharomyces cerevisiae.** *Nat*

857   *Struct Mol Biol* 2010, **17:**251-257.

858   12.   Valouev A, Johnson SM, Boyd SD, Smith CL, Fire AZ, Sidow A: **Determinants**

859   **of nucleosome organization in primary human cells.** *Nature* 2011, **474:**516-

860   520.

861   13.   Dell'Orso S, Wang AH, Shih HY, Saso K, Berghella L, Gutierrez-Cruz G,

862   Ladurner AG, O'Shea JJ, Sartorelli V, Zare H: **The Histone Variant**

863   **MacroH2A1.2 Is Necessary for the Activation of Muscle Enhancers and**

864   **Recruitment of the Transcription Factor Pbx1.** *Cell Rep* 2016, **14:**1156-1168.

865   14.   **Human ENCODE Data Analysis Consortium Blacklisted Regions**

866   [http://hgdownload.cse.ucsc.edu/goldenPath/hg19/encodeDCC/wgEncodeMapabil

867   ity/wgEncodeDacMapabilityConsensusExcludable.bed.gz]

15.   Baum LE, Petrie T, Soules G, Weiss N: **A Maximization Technique Occurring**

in the Statistical Analysis of Probabilistic Functions of Markov Chains. *The*

Annals of Mathematical Statistics 1970, **41:**164-171.

16.   Viterbi A: **Error bounds for convolutional codes and an asymptotically**

optimum decoding algorithm. *IEEE Trans Inf Theor* 1967, **13:**260-269.

17.   Liu Y, Liu XS, Wei L, Altman RB, Batzoglou S: **Eukaryotic regulatory element**

conservation analysis and identification using comparative genomics. *Genome*

Res 2004, **14:**451-458.

18.   Siepel A, Bejerano G, Pedersen JS, Hinrichs AS, Hou M, Rosenbloom K,

Clawson H, Spieth J, Hillier LW, Richards S, et al: **Evolutionarily conserved**

elements in vertebrate, insect, worm, and yeast genomes. *Genome Res* 2005,

15:1034-1050.

19.   Shin H, Liu T, Duan X, Zhang Y, Liu XS: **Computational methodology for**

ChIP-seq analysis. *Quant Biol* 2013, **1:**54-70.

20.   Zhang Y, Liu T, Meyer CA, Eeckhoute J, Johnson DS, Bernstein BE, Nusbaum

C, Myers RM, Brown M, Li W, Liu XS: **Model-based analysis of ChIP-Seq**

(MACS). *Genome Biol* 2008, **9:**R137.

21.   Boyle AP, Guinney J, Crawford GE, Furey TS: **F-Seq: a feature density**

estimator for high-throughput sequence tags. *Bioinformatics* 2008, **24:**2537-

2538.

22.   John S, Sabo PJ, Thurman RE, Sung MH, Biddie SC, Johnson TA, Hager GL,

Stamatoyannopoulos JA: **Chromatin accessibility pre-determines**

glucocorticoid receptor binding patterns. *Nat Genet* 2011, **43:**264-268.

23.   Koohy H, Down TA, Spivakov M, Hubbard T: **A Comparison of Peak Callers**

892   **Used for DNase-Seq Data.** *PLoS One* 2014, **9:**e96303.

893   24.   Hansel-Hertsch R, Beraldi D, Lensing SV, Marsico G, Zyner K, Parry A, Di

894   Antonio M, Pike J, Kimura H, Narita M, et al: **G-quadruplex structures mark**

895   **human regulatory chromatin.** *Nat Genet* 2016, **48:**1267-1272.

896   25.   Philip M, Fairchild L, Sun L, Horste EL, Camara S, Shakiba M, Scott AC, Viale

897   A, Lauer P, Merghoub T, et al: **Chromatin states define tumour-specific T cell**

898   **dysfunction and reprogramming.** *Nature* 2017, **545:**452-456.

899   26.   Denny SK, Yang D, Chuang CH, Brady JJ, Lim JS, Gruner BM, Chiou SH, Schep

900   AN, Baral J, Hamard C, et al: **Nfib Promotes Metastasis through a Widespread**

901   **Increase in Chromatin Accessibility.** *Cell* 2016, **166:**328-342.

902   27.   Chen X, Shen Y, Draper W, Buenrostro JD, Litzenburger U, Cho SW, Satpathy

903   AT, Carter AC, Ghosh RP, East-Seletsky A, et al: **ATAC-see reveals the**

904   **accessible genome by transposase-mediated imaging and sequencing.** *Nat*

905   *Methods* 2016, **13:**1013-1020.

906   28.   Novakovic B, Habibi E, Wang SY, Arts RJW, Davar R, Megchelenbrink W, Kim

907   B, Kuznetsova T, Kox M, Zwaag J, et al: **beta-Glucan Reverses the Epigenetic**

908   **State of LPS-Induced Immunological Tolerance.** *Cell* 2016, **167:**1354-1368

909   e1314.

910   29.   Risca VI, Denny SK, Straight AF, Greenleaf WJ: **Variable chromatin**

911   **structure revealed by in situ spatially correlated DNA cleavage**

912   **mapping.** *Nature* 2017, **541:**237-241.

913   30.   **ENCODE ATAC-Seq analysis pipeline** [https://www.encodeproject.org/atac-

914   seq/]

915   31.   Ernst J, Kellis M: **ChromHMM: automating chromatin-state discovery and**

916   **characterization.** *Nat Methods* 2012, **9:**215-216.

917   32.   Landt SG, Marinov GK, Kundaje A, Kheradpour P, Pauli F, Batzoglou S,

918   Bernstein BE, Bickel P, Brown JB, Cayting P, et al: **ChIP-seq guidelines and**

919   **practices of the ENCODE and modENCODE consortia.** *Genome Res* 2012,

920   **22:**1813-1831.

921   33.   Ernst J, Kheradpour P, Mikkelsen TS, Shoresh N, Ward LD, Epstein CB, Zhang

922   X, Wang L, Issner R, Coyne M, et al: **Mapping and analysis of chromatin state**

923   **dynamics in nine human cell types.** *Nature* 2011, **473:**43-49.

924   34.   Thurman RE, Rynes E, Humbert R, Vierstra J, Maurano MT, Haugen E, Sheffield

925   NC, Stergachis AB, Wang H, Vernot B, et al: **The accessible chromatin**

926   **landscape of the human genome.** *Nature* 2012, **489:**75-82.

927   35.   Li QH, Brown JB, Huang HY, Bickel PJ: **Measuring Reproducibility of High-**

928   **Throughput Experiments.** *Annals of Applied Statistics* 2011, **5:**1752-1779.

929   36.   Kodama Y, Shumway M, Leinonen R, International Nucleotide Sequence

930   Database C: **The Sequence Read Archive: explosive growth of sequencing**

931   **data.** *Nucleic Acids Res* 2012, **40:**D54-56.

932   37.   Langmead B, Salzberg SL: **Fast gapped-read alignment with Bowtie 2.** *Nat*

933   *Methods* 2012, **9:**357-359.

934   38.   MacQueen J: **Some methods for classification and analysis of multivariate**

935   **observations.** In *Proceedings of the Fifth Berkeley Symposium on Mathematical*

936   *Statistics and Probability, Volume 1: Statistics*; *1967; Berkeley, Calif.* University

937   of California Press; 1967: 281-297.

938   39.   Quinlan AR, Hall IM: **BEDTools: a flexible suite of utilities for comparing**

939   **genomic features.** *Bioinformatics* 2010, **26:**841-842.

940   40.   **HotSpot Mappability for Human Genome** [www.uwencode.org/proj/hotspot/]

Fig. 1

Fig. 2

Fig. 3

Fig. 4