1   Title
2
3   Probing the chemical-biological relationship space with the Drug Target Explorer
4
5   Authors
6

7   Robert Allaway[1], Salvatore La Rosa[2], Justin Guinney[1], Sara Gosline[1*]
8
9   [1]Sage Bionetworks, 1100 Fairview Avenue N, Seattle, WA, 98109
10 [2]Children's Tumor Foundation, New York, NY, 10005
11 *corresponding author: sara.gosline@sagebionetworks.org

12
13 Abstract
14

Modern phenotypic high-throughput screens (HTS) present several challenges including
identifying the target(s) that mediate the effect seen in the screen, characterizing 'hits' with a
polypharmacologic target profile, and contextualizing screen data within the large potential
space of drugs and biological screening model combinations. To address these challenges, we
developed an interactive web application that enables exploration of the chemical-biological
interaction space. Compound-target interaction data from public resources were quantified for
over 280,000 molecules. Each molecule was annotated with a name and chemical structure,
and every target was annotated with gene identifiers. The Drug-Target Explorer allows users to
query molecules within this database of experimentally-derived and curated compound-target
interactions and identify structurally similar molecules. It also enables network-based
visualizations of the compound-target interaction space, and incorporates comparisons to
publicly-available *in vitro* HTS datasets. Users can also identify compounds given one or more
targets of interest. The Drug Target Explorer is a multifunctional platform for exploring chemical
space as it relates to biological targets, and may be useful at several steps along the drug
development pipeline including target discovery, structure-activity relationship, and lead
compound identification studies.

31
32
33 Keywords
34   Drug targets, polypharmacology, webapp, phenotypic drug screen, compound-target
35 network

45   Introduction
46

In the modern drug discovery and development process, high-throughput screens (HTS)
of drugs have become a common and important step in the identification of novel treatments for
disease. In the past decade, studies describing or citing high throughput drug screening are
increasingly prevalent, topping 1000 per year for the past 5 years (Figure 1) and span many
disease domains such as cancer, neurodegenerative disease, and cardiopulmonary diseases.
These screens are often phenotypic in nature whereby a large panel of compounds of known,
presumed known, and/or unknown mechanisms of action are tested in a biological model of
interest and generate phenotypic readouts such as apoptosis or proliferation. While these types
of screens facilitate the rapid identification of biologically active drugs or chemical probes, they
also present several challenges.

Figure 1 -   High throughput drug screening is an increasingly common experimental
approach. Yearly count of Pubmed-indexed publications that appear with the search term "high
throughput drug screening." Search performed on January 30, 2018.

One prevailing challenge is the identification of the specific biological mechanisms within
a cell that determine the response in a screen. The search for novel drugs constantly pushes
the pharmaceutical researchers to include novel chemical sets in phenotypic screens, with the
caveat that the underlying mechanism of action (MoA) of a particular compound cannot usually
be gleaned from the phenotypic screens. (1) Most of the time, identifying the MoA requires
additional experimentation, particularly if the molecule represents a novel or understudied
chemical entity. Another challenge is that the polypharmacologic nature of many small
molecules can make it difficult to interpret HTS results as a given drug may affect multiple
targets with a range of efficacy. This, in turn, presents the difficulty of consolidating multiple
targets into a unified biological mechanism or set of mechanisms leading to poorly annotated
targets, misunderstood MoAs (2), and unknown or ambiguous off-targets with potential deadly

side effects (3,4). A final challenge is that identification of related molecules and their targets is
not always straightforward; in the context of HTS analysis, structurally and functionally related
molecules that are not contained in a screening library might be useful to explore.
Multiple tools and databases have attempted to address various aspects of the
challenges outlined above (see Table 1). These tools allow the user to explore known
polypharmacology of small molecules. Many also allow users to explore compound-target
relationships by querying either by molecule or by target: DGIdb, DT-Web, BindingDB,
Polypharmacology Browser, STITCH, and SuperTarget allow users to identify MoAs/targets of a
given compound by evaluating a query drug (5–10), while DT-Web, BindingDB,
Polypharmacology Browser, and STITCH allow users to search by chemical similarity using any
query molecule (Table 1). Probe Miner, alternatively, is designed primarily to handle target-
based queries (11). All tools listed in Table 1 allow users to identify molecules with known
polypharmacology, but only two, STITCH and SuperTarget, provide the ability to summarize
these targets into biological pathways/mechanisms using a gene list enrichment approach
(9,10). The final challenge - identifying structurally or functionally related molecules - is
addressed by DT-Web, BindingDB, Polypharmacology Browser, and STITCH (6–9).
While several of the tools listed address one or more of these challenges, there are
some gaps (Table 1). For example, ChEMBLSpace does not have a web interface and therefore
requires installation on a compatible system before use (12). In addition, not all of these tools
are open-source (STITCH, SuperTarget, and BindingDB). An easy to modify open-source
application could enable users to create features that are helpful for their specific analyses.
While most tools allow both drug-based and target-based queries, none appear to facilitate
queries for molecules that affect several targets, which may be useful for users who want to
leverage polypharmacology by employing drugs that inhibit multiple biological mechanisms.
While multiple targets can be queried at one time in STITCH, it is not straightforward to identify
single molecules that affect all query targets. In addition, DGIdb and ChEMBLSpace cannot be
used to explore similar chemical space to the query molecule. These two, plus SuperTarget,
also cannot be queried using molecules that are not in the database; a feature that might help
users with novel preclinical candidate drugs. With the exception of DT-Web and STITCH, these
tools do not allow visualization of drug-target networks, which may help users address the
challenge of identifying structurally or functionally related drugs. No tools other than STITCH
perform gene list enrichment, which may help users interpret the biological MoAs of
polypharmacologic molecules.
To address these gaps, we developed the Drug-Target Explorer. Specifically, the Drug-
Target Explorer enables the user to (1) look up targets for individual molecules and groups of
molecules, (2) explore networks of targets and drugs, (3) perform gene list enrichment of targets
to assess target pathways of compounds, (4) compare query molecules to cancer cell line
screening datasets, and (5) discover bioactive molecules using a query target and exploration of
these networks. We anticipate that the users will include biologists and chemists involved in
drug discovery who are interested in performing hypothesis generation of human targets for
novel molecules, identifying off-targets for bioactive small molecules of interest, and exploring of
the polypharmacologic nature of small molecules.

	Drug-Target Explorer	Probe Miner	DGIdb v3.0	DT-Web	BindingDB	Polypharmacology Browser	STITCH	ChEMBLSpace	SuperTarget
Web app?	X	X	X	X	X	X	X		X
Open-source software?	X		X	X - underlying R package only	unknown	X		X	
Search by targets to find drugs?	X	X	X	X	X	X - only by PDB-listed ligands	X	X	X
Search by drugs to find targets?	X		X	X	X	X	X		X
Identification of molecules that are associated with multiple query targets?	X			unknown					
Drug structure input?	X			X	X	X	X		
Drug name/ID input?	X		X	X	X	X	X		X
Visualize drug-target networks?	X			X, with user provided drug-target networks	not currently functioning		X		
Identify chemically similar drugs?	X			X, with user provided drug-target networks	X	X	X		X
Allows queries using molecules not in database?	X			X, with user provided drug-target networks	X	X	X		
Target organism?	human	human	human	human	human and others	human and others	human and others	unknown	human and others
Target space?	3.6k	2.2k	6.1k	3.8k	>7k	4.6k	9.6mil	unknown	>6k
Chemical space?	280k	400k	10k	4.4k	>642k	870k	500k	unknown	>196k
Quantitative interactions?	X	X		unknown	X	X	X	X	X
Qualitative interaction?	X	X	X	X			unknown		X
Explore polypharmacology?	X	X	X	X	X	X	X	X	X
Polypharmacologic target enrichment?	X						X		X
Comparison of query molecule to HTS drug response datasets?	X								
Target prediction?				X	X	X			
Database access?	Open	Open	Open	Open	Open	Open	Full database requires license	unknown	unknown
Last known update	2018	2018	2018	2018	2018	2016	2016	2015	2012

Table 1 - Summary of selected features/uses of databases and applications for exploring molecule-target relationships and their overlapping features with the Drug-Target Database. Related tools include Probe Miner (11), DGIdb (5), DT-Web (6), BindingDB (7), Polypharmacology Browser (8), STITCH (9), ChEMBLSpace (12), and SuperTarget (10).

Results

The Drug Target Explorer was designed to facilitate the following use-cases: hypothesis generation of targets for newly-discovered molecules, identification of off-targets for bioactive research molecules, and exploration of the polypharmacologic nature of many drugs. Below, we include vignettes highlighting how the Drug-Target Explorer can facilitate analysis in these areas.

Identifying potential off-target effects of novel molecules

To highlight the use of this app to find potential off-targets of a novel molecule, we queried the Drug-Target Explorer for C21, a recently-published Polo like kinase (PLK) inhibitor that is not captured in our database (29). This molecule inhibits Plk2 and Plk1 in the low nM range, and Plk3 in the low uM range (29). Using a Tanimoto similarity of 0.65 or greater, we identified 14 molecules (Figure 2A, Supplemental Table 1). PLK1, PLK2, and PLK3 are known targets of several of these molecules, such as BI 2536 and volasertib. Curiously, CAMKK, BRD4, PDXK, and PTK2 are also targeted by molecules in this chemical set, with pChEMBL values >6-8. A plausible hypothesis could be that these targets are affected by this family of molecules, including the query molecule, in the 10-1000 nM range, which would indicate that further research is needed to determine the selectivity of C21 or other structurally related molecules.

145
146
Figure 2 - Molecule-target networks highlight targets within chemical families. (A)
Using the novel Plk inhibitor C21 as a query with a Tanimoto cutoff of 0.65 (SMILES:
CCNC(=O)C1=CC2=C(C=C1)N(C=C2)C1=NC=C2N(C)C(=O)[C@@H](CC)N(C3CCCC3)C2=N1), we identify 14 related
molecules (blue vertices), and observe several targets (green vertices) common to multiple
members of this family, including PLK1, PLK2, BRD4, CAMKK2, PTK2, and PDXK. (B) A gene-
based query for two targets (green vertices), LIMK1 and LIMK2, identifies 10 molecules (blue
vertices), as well as other targets affected by these molecules. (C) A query for multiple targets
relevant to tumors caused by neurofibromatosis type 2 identifies three promiscuous molecules
that have associations with these targets.

156
157   *Identifying off targets of existing molecules*

158
This app may also be useful in identifying off-targets of existing molecules in a
preclinical or exploratory research setting. In order to confidently interrogate the role of cellular
targets, one must use compounds with specificity for those targets. A well-known example of a
non-specific inhibitor is imatinib. This molecule, developed for use in the treatment of chronic

myelogenous leukemia, was initially considered a selective inhibitor of Abl (30). More recently,
several other targets have been identified for imatinib such as KIT, PDGFRA, and PDGFRB
(31). Querying the Drug Target Explorer indicates that there is evidence for 61 targets of
imatinib, several of which have pChEMBL values within a reasonable range of Abl, PDGFRA,
and PDFGRB (Supplemental Table 2). These targets must all be considered when evaluating
imatinib in human model systems.

A more recent example is the tool compound G-5555, a selective PAK1 inhibitor (32).
This compound has been used to demonstrate the role of PAK1 in cellular processes such as
invasion (33). A search of the Drug-Target Explorer database showed that this molecule not
only binds PAK1 (mean pChEMBL = 8.01), but there is qualitative evidence for effects on
PAK2/3, and quantitative evidence suggesting an effect on SIK2, MAP4K5, and PAK2 at similar
concentrations of G-5555 (mean pChEMBLs 8.05, 8, and 7.96 respectively, Table 2). G-5555
also may have an effect on STK family proteins (STK3, STK24, STK25, STK26) and LCK.
Therefore, any findings with G-5555 with regards to PAK1 inhibition must be validated with other
selective inhibitors or genetic approaches, as Jeannott and colleagues did (using other PAK
inhibitors such as FRAX597 and FRAX1036, as well as PAK1 silencing RNA), to confirm that
the effects observed are PAK1 specific (33).
180

Molecule Name	HGNC Symbol	Mean pChEMBL	n Quantitative	n Qualitative	KSI	Confidence
CHEMBL3770443	PAK1	8.01	3	1	0.1	11
CHEMBL3770443	PAK2	7.96	2	1	0.1	9.96
CHEMBL3770443	SIK2	8.05	1		0.1	9.05
CHEMBL3770443	MAP4K5	8	1		0.1	9
CHEMBL3770443	STK26	7.7	1		0.1	8.7
CHEMBL3770443	STK25	7.47	1		0.1	8.47
CHEMBL3770443	STK24	7.37	1		0.1	8.37
CHEMBL3770443	STK3	7.37	1		0.1	8.37
CHEMBL3770443	LCK	7.28	1		0.1	8.28
CHEMBL3770443	PAK3			1	0.1	1

181
182 **Table 2 – Targets of G-5555 found in the Drug-Target Explorer Database.**
183
184   *Identifying polypharmacologically-targeted pathways and drugs with similar biological*
185 *effects*
186

In order to provide biological context, this app allows the user to aggregate multiple
targets from compounds into functional categories. Using the previous example of G-5555, we
performed enrichment analysis on the list of targets to identify potential biological pathways and
MoAs that this molecule may disrupt. In doing so, we observed that G-5555 targets are enriched
in several Gene Ontology terms and KEGG Pathways like T-cell receptor signaling, Ras/MAPK
signaling, and Golgi-localized proteins (Supplemental Table 3). The app also allows the user to
compare the query molecule to drugs in the Cancer Cell Line/CTRP and GDSC/Sanger cell line
screening datasets. Specifically, the app identifies the most similar molecule available in these

datasets and uses that molecule as a reference to plot chemical similarity vs drug response
correlation.
197
198   *Finding a drug for known targets*
199
Finally, the tool allows users to perform a reverse search, i.e. identify molecules that
have an association with a query target or targets and assess the known selectivity of these
molecules. For example, Petrilli et. al. identified LIM domain kinases as targets of interest in
tumors caused by the genetic disease neurofibromatosis type 2 (NF2) (34). They found that
pharmacologic (LIMK1/2 inhibitor BMS-5) and genetic modulation of LIMK1 and LIMK2 caused
cell-cycle inhibition and reduced viability in merlin (*Nf2*) deficient Schwann cells (34). In the
context of follow-up and validation studies, it may be beneficial to use alternate molecules that
target LIMK1/2 at the same or greater potency than BMS-5. We used the Drug-Target Explorer
to find molecules that target LIMK1 and LIMK2 (Supplemental Table 4, Figure 2B). For example,
BMS-5 (CHEMBL2141887 in the Drug-Target Explorer) has mean pChEMBLs of 7.33 and 7.07
for LIMK1 and LIMK2 respectively. A good alternative to validate the effects of this molecule
might be CHEMBL3623442, a relatively structurally distinct small molecule (extended fingerprint
Tanimoto similarity of 0.433 to BMS-5 in this database), with pChEMBLs of 9 and 8.52 for
LIMK1 and LIMK2 respectively. Another interesting possibility is the identification of multiple
molecules with overlapping desired targets and non-overlapping off-targets to reduce off-target
effects, or to identify synergistic/additive single-target, multi-drug combinations as outlined by
Fitzgerald et al 2006 (35). Using the above scenario with LIMK1/2, it may be possible to use
structurally distinct molecules in combination or in sequence, like CHEMBL3356433 and
Compound 31 highlighted in Figure 2B, to reduce off-target effects or inhibit LIMK1/2 in an
additive or synergistic manner. The opposite approach could also be taken by finding a single
molecule that binds multiple desired targets. In the case of merlin-deficient cells, focal adhesion
kinases (FAKs) such as PTK2 (FAK2) and PTK2B, as well as Aurora kinase A (AURKA) have
been highlighted as potential targets of interest (34,36,37). Using the Drug-Target Explorer, we
can identify molecules that target LIMK1/2, PTK2/2B, and AURKA (Supplemental Table 5,
Figure 2C). Using this information, a rational hypothesis might be that CYC116 or danusertib
could be effective and selective for *NF2*-deficient tumor cells; to our knowledge, the use of these
molecules in this setting has yet not been explored.
227
228
229 **Discussion**
230
In the present study, we demonstrate that the Drug-Target Explorer enables the user to
look up targets for novel and known molecules such as C21, G-5555, and imatinib, as well as
explore networks of these drugs and their targets. Users can perform target enrichment to
consolidate multiple targets to into pathways, compare query molecules to screening datasets,
and identify bioactive molecules given a query target.
Several future directions are envisioned for this application. The code and database has
been designed in such a way that any database with structural information and drug-gene target
information (qualitative associations, or quantitative associations that can be coerced to

pChEMBL values) can be harmonized and integrated into the database. Therefore, as new
datasets become available, such as the recently-published Drug-Target Commons (38), they
can be integrated and released. We also envision occasional errors being identified as the
database is explored and vetted by users and have included a feedback form for users to
suggest new data to integrate, as well as to highlight necessary corrections to the dataset.
Currently, the query molecule to full database similarity calculation is computationally intensive.
One solution to speed up calculation times may be to implement a locality sensitive hashing
method in future versions of the database and web app, such as the method devised by Cao et
al 2010 (39). An additional planned feature for this app is the implementation of a bulk
annotation feature to allow users to annotate HTS data with targets and/or putative targets of
identical or structurally related molecules. Finally, the integration of a predictive framework for
identifying targets of query drugs based on drug and target feature data would enable users to
quantitatively predict targets of novel molecular entities rather than manually exploring
structurally similar molecules.

The Drug-Target Explorer enables users to explore known molecule-human target
relationships as they relate to chemical similarity rapidly and with minimal effort. We anticipate
that users such as biologists and chemists using chemical probes or studying preclinical
therapeutics will find this tool useful in several areas. Specifically, this tool may aid drug
discovery efforts by accelerating hypothesis generation, simplifying the transition from
phenotypic HTS results to mechanistic studies, and streamlining the identification of candidate
molecules that target a protein or mechanism of interest.

260
261 **Methods**
262

To build the database of known compound-target interactions, we aggregated five data
sources containing qualitative and quantitative interactions (Figure 3). We considered qualitative
interactions to be curated compound-target associations with no associated numeric value.
Quantitative interactions were defined as compound-target information with a numeric value
indicating potency of compound-target binding or functional changes. Qualitative compound-
target associations were retrieved from the DrugBank 5.0.11 XML database, the DGIdb v3.0.1
interactions.tsv file, and ChemicalProbes.org (acc. Jan 17 2018) (5,13,14). pChEMBL, IC50,
C50, EC50, AC50, Ki, Kd, and potency values for *Homo sapiens* targets were retrieved from the
ChEMBL v23 MySQL database (15). Kd values were also obtained from Klaeger et al 2017, in
which the authors determined the Kd of 244 kinase inhibitors against 343 kinases (16). For all
quantitative and qualitative data sources, compound structural information (SMILES) was
retrieved when available. When not available, it was batch annotated using the Pubchem
Identifier Exchange Service, or, in some cases, manually annotated via PubChem and
ChemSpider search (17,18).

Figure 3 - Process for developing the Drug-Target Explorer. Molecule-target and chemical structure data were collected from public sources. In the case of DGIdb, chemical structures were assigned using the PubChem Chemical Identifier Exchange or manually assigned using ChemSpider and PubChem. Chemical structures were converted to circular fingerprints and the databases were mapped to internal Drug-Target Explorer identifiers. Qualitative and quantitative data were summarized by calculating several summary statistics, and these data were stored together with the internal identifiers to form the Drug-Target Explorer database.

To consolidate data for "identical" molecules within and across multiple databases, the functional connectivity fingerprint (FCFP6)-like 'circular' fingerprint for each SMILES was calculated using the R interface (rcdk) to the Java Chemical Development Kit (CDK) (19–21). The package was modified to use the latest version of the CDK (2.1.1), which enables perception of chiral centers, enabling differentiation between isomeric molecules. Each unique circular fingerprint and all external IDs and SMILES associated with that fingerprint were then assigned an internal identifier, so that groups of molecules with identical fingerprints were assigned to the same internal ID. The internal molecular IDs were then mapped to each database to permit their aggregation. All datasets were combined and summaries were generated for each compound-target comparison using functions from the R 'tidyverse' (22).

The summary metrics described in Table 3 were calculated. One of these metrics, pChEMBL, is used to convey the efficacy of a given molecule. It is calculated from one of

several semi-comparable values in the ChEMBL database, and is defined as the negative log
10 molar of the IC50, XC50, EC50, AC50, Ki, Kd, or potency (15). For example, a pChEMBL
value of 7 would indicate that there is a measurable effect on a given target in the presence of
100 nM of molecule. To harmonize the data from Klaeger et al with ChEMBL data, the Kd
values were converted to pChEMBLs. The mean pChEMBL was calculated for every molecule-
target
combination, as well as the number of quantitative and qualitative associations found in
the source databases.

Metric	Unit	Meaning
mean IC50/AC50/EC50/C50/Potency/Ki/Kd	nM	mean of values obtained from quantitative datasets; available in database but not app
mean pChEMBL	-log10(nM)	mean -log10(nM) of all semi-comparable quantitative values
n_qualitative	count	number of qualitative associations identified
n_quantitative	count	number of quantitative associations identified
known selectivity score	N/A	1 divided by the number of known targets, lower is less selective
confidence score	N/A	mean pChEMBL, multiplied by n_quantitative, plus n_qualitative

308
309   **Table 3 - Drug-target association metrics summarized in the Drug-Target Explorer**
310   **database.**
311

We calculated a known selectivity score for each molecule, which we defined as 1
divided by the total number of targets for that molecule (lower values correspond to lower
molecule selectivity), and a confidence score for each molecule-target relationship, which we
defined as the mean pChEMBL multiplied by the number of quantitative measurements, in
addition to the number of qualitative annotations. A larger confidence score indicates greater
confidence in this relationship; this confidence is weighted by the potency to give increased
preference to high-potency compound-target interactions.
This resulted in a database containing 3645 human targets (represented by HUGO gene
symbols), ~280,000 small molecules, and ~623,500 molecule-target relationships summarized
from ~598,000 quantitative associations and ~25,000 qualitative associations. Finally, this
database as well as fingerprints and chemical aliases for each molecule were saved as R binary
files and stored on Synapse (23). All of the data, as well as snapshots of the source databases
used to build the Drug Target Explorer database (with the exception of DrugBank, which
requires a license to access) are accessible at www.synapse.org/dtexplorer. The Drug-Target
Database is licensed under CC BY-SA 4.0.

333
334
335   Figure 4 - **Layout of the Drug-Target Explorer.** The "About" tab describes the apps
336   functions and uses, the "Molecules" tab permits molecule-based searching, the "Genes" tab
337   permits target queries, and the "Settings" tab allows the user to pick the fingerprinting method
338   used.
339
We developed a Shiny application to permit exploration of the database (24,25). For
chemical queries, users can search for molecules in the database by one of three methods:
from a list of aliases obtained from the source databases, retrieving the chemical structure using
the 'webchem' interface to the Chemical Identifier Resolver, or by directly inputting the SMILES
string (26). A Tanimoto similarity threshold allows the user to narrow or widen the chemical
space of the results. After querying, the input molecule is converted to a fingerprint and it's
similarity calculated relative to all molecules in the database, using 'extended' fingerprints. The
user then can view the resulting set of molecules as well as the molecule-target relationships in
interactive tables and graphs (Figure 4). In addition, the user can remove or include molecules
on an a-la-carte basis, view the 2D structural representation of the input molecule, and perform
target list enrichment analysis (27,28). Furthermore, the query molecule can be compared
against molecules in the CTRP and Sanger cancer cell line drug-screening datasets to identify
identical or similar structures in these datasets, and compare the relationship between chemical
structure and correlations in drug response.
For target queries, users can input one or more query HUGO gene(s) and identify
molecules that are reported to bind those targets, and view these data in an interactive table.
Users can also view these drugs in an interactive graph format to view their association with the
query   target   and   their   other   targets.   The   Drug-Target   Explorer   is   available   at

www.synapse.org/dtexplorer, and requires a free Synapse account to access. The source code
for the Drug-Target Explorer app is available at https://github.com/Sage-
Bionetworks/polypharmacology-db. The source code is licensed under Apache 2.0.
361
362
363 Supplemental table legends:
364
365 **Supplemental Table 1 – Targets of C21-like compounds in the Drug-Target Explorer**
366 **Database.**
367
368 **Supplemental Table 2 – Targets of imatinib in the Drug-Target Explorer Database.**
369
370 **Supplemental Table 3 – Target enrichment analysis of G-5555 highlights putative**
371 **mechanistic effects.** G-5555 targets were enriched in multiple Gene Ontology terms and
372 KEGG pathways.
373
374 **Supplemental Table 4 – Molecules targeting LIMK1/2.** The database was queried for
375 molecules that may modulate LIMK1 and LIMK2; this analysis revealed a large set of putative
376 tool compounds.
377
378 **Supplemental Table 5 – Identification of multi-kinase-targeting molecules for NF2.** A query
379 of the database for molecules that target several kinases of interest in NF2 (AURKA, LIMK1/2,
380 PTK2/2B) identified 3 polypharmacologic compounds.
381
382 References
383

1.   Wagner BK. The resurgence of phenotypic screening in drug discovery and development.
Expert Opin Drug Discov [Internet]. 2016 Feb 10 [cited 2018 Mar 13];11(2):121–5.
Available from: http://www.tandfonline.com/doi/full/10.1517/17460441.2016.1122589
2.   Santos R, Ursu O, Gaulton A, Bento AP, Donadi RS, Bologa CG, et al. A comprehensive
map of molecular drug targets. Nat Rev Drug Discov [Internet]. 2017 Jan 2 [cited 2018
Mar 26];16(1):19–34. Available from: http://www.nature.com/articles/nrd.2016.230
3.   van Esbroeck ACM, Janssen APA, Cognetta AB, Ogasawara D, Shpak G, van der Kroeg
M, et al. Activity-based protein profiling reveals off-target proteins of the FAAH inhibitor
BIA 10-2474. Science [Internet]. 2017 Jun 9 [cited 2018 Mar 26];356(6342):1084–7.
Available from: http://www.ncbi.nlm.nih.gov/pubmed/28596366
4.   Roy M, Dumaine R, Brown AM. HERG, a primary human ventricular target of the
nonsedating antihistamine terfenadine. Circulation [Internet]. 1996 Aug 15 [cited 2018
Mar 26];94(4):817–23. Available from: http://www.ncbi.nlm.nih.gov/pubmed/8772706
5.   Cotto KC, Wagner AH, Feng Y-Y, Kiwala S, Coffman AC, Spies G, et al. DGIdb 3.0: a
redesign and expansion of the drug–gene interaction database. Nucleic Acids Res
[Internet]. 2017 Nov 16 [cited 2018 Mar 20]; Available from:
http://academic.oup.com/nar/article/doi/10.1093/nar/gkx1143/4634012
6.   Alaimo S, Bonnici V, Cancemi D, Ferro A, Giugno R, Pulvirenti A. DT-Web: a web-based
application for drug-target interaction and drug combination prediction through domain-
tuned network-based inference. BMC Syst Biol [Internet]. 2015 [cited 2018 Mar
20];9(Suppl 3):S4. Available from: http://www.ncbi.nlm.nih.gov/pubmed/26050742

7. Gilson MK, Liu T, Baitaluk M, Nicola G, Hwang L, Chong J. BindingDB in 2015: A public
database for medicinal chemistry, computational chemistry and systems pharmacology.
Nucleic Acids Res [Internet]. 2016 Jan 4 [cited 2018 Mar 20];44(D1):D1045–53. Available
from: https://academic.oup.com/nar/article-lookup/doi/10.1093/nar/gkv1072
8. Awale M, Reymond J-L. The polypharmacology browser: a web-based multi-fingerprint
target prediction tool using ChEMBL bioactivity data. J Cheminform [Internet]. 2017 Dec
21 [cited 2018 Mar 20];9(1):11. Available from:
http://jcheminf.springeropen.com/articles/10.1186/s13321-017-0199-x
9. Szklarczyk D, Santos A, von Mering C, Jensen LJ, Bork P, Kuhn M. STITCH 5:
augmenting protein-chemical interaction networks with tissue and affinity data. Nucleic
Acids Res [Internet]. 2016 Jan 4 [cited 2018 Mar 20];44(D1):D380-4. Available from:
http://www.ncbi.nlm.nih.gov/pubmed/26590256
10. Günther S, Kuhn M, Dunkel M, Campillos M, Senger C, Petsalaki E, et al. SuperTarget
and Matador: resources for exploring drug-target relationships. Nucleic Acids Res
[Internet]. 2008 Jan [cited 2018 Mar 20];36(Database issue):D919-22. Available from:
http://www.ncbi.nlm.nih.gov/pubmed/17942422
11. Antolin AA, Tym JE, Komianou A, Collins I, Workman P, Al-Lazikani B. Objective,
Quantitative, Data-Driven Assessment of Chemical Probes. Cell Chem Biol [Internet].
2018 Feb 15 [cited 2018 Apr 25];25(2):194–205.e5. Available from:
http://www.ncbi.nlm.nih.gov/pubmed/29249694
12. Fechner N, Papadatos G, Evans D, Morphy JR, Brewerton SC, Thorner D, et al.
ChEMBLSpace—a graphical explorer of the chemogenomic space covered by the
ChEMBL database. Bioinformatics [Internet]. 2013 Feb 15 [cited 2018 Mar 20];29(4):523–
4. Available from: http://www.ncbi.nlm.nih.gov/pubmed/23257198
13. Wishart DS, Feunang YD, Guo AC, Lo EJ, Marcu A, Grant JR, et al. DrugBank 5.0: a
major update to the DrugBank database for 2018. Nucleic Acids Res [Internet]. 2018 Jan
4 [cited 2018 Mar 20];46(D1):D1074–82. Available from:
http://www.ncbi.nlm.nih.gov/pubmed/29126136
14. ChemicalProbes.org [Internet]. 2018 [cited 2018 Jan 17]. Available from:
www.chemicalprobes.org
15. Gaulton A, Hersey A, Nowotka M, Bento AP, Chambers J, Mendez D, et al. The ChEMBL
database in 2017. Nucleic Acids Res [Internet]. 2017 Jan 4 [cited 2018 Mar
20];45(D1):D945–54. Available from: http://www.ncbi.nlm.nih.gov/pubmed/27899562
16. Klaeger S, Heinzlmeir S, Wilhelm M, Polzer H, Vick B, Koenig P-A, et al. The target
landscape of clinical kinase drugs. Science [Internet]. 2017 Dec 1 [cited 2018 Mar
20];358(6367):eaan4368. Available from: http://www.ncbi.nlm.nih.gov/pubmed/29191878
17. Kim S, Thiessen PA, Bolton EE, Chen J, Fu G, Gindulyte A, et al. PubChem Substance
and Compound databases. Nucleic Acids Res [Internet]. 2016 Jan 4 [cited 2018 Mar
20];44(D1):D1202-13. Available from: http://www.ncbi.nlm.nih.gov/pubmed/26400175
18. Pence HE, Williams A. ChemSpider: An Online Chemical Information Resource. J Chem
Educ [Internet]. 2010 Nov [cited 2018 Mar 20];87(11):1123–4. Available from:
http://pubs.acs.org/doi/abs/10.1021/ed100697w
19. Guha R. Chemical Informatics Functionality in R. J Stat Softw. 2007;18(6).
20. Willighagen EL, Mayfield JW, Alvarsson J, Berg A, Carlsson L, Jeliazkova N, et al. The
Chemistry Development Kit (CDK) v2.0: atom typing, depiction, molecular formulas, and
substructure searching. J Cheminform [Internet]. 2017 Dec 6 [cited 2018 Mar 22];9(1):33.
Available from: http://jcheminf.springeropen.com/articles/10.1186/s13321-017-0220-4
21. Guha R. fingerprint: Functions to Operate on Binary Fingerprint Data [Internet]. 2017.
Available from: https://cran.r-project.org/package=fingerprint
22. Wickham H. tidyverse: Easily Install and Load the "Tidyverse" [Internet]. 2017. Available
from: https://cran.r-project.org/package=tidyverse

23. Hoff B, Truong K. synapser: R language bindings for Synapse API [Internet]. 2018.
Available from: https://www.sagebase.org
24. Chang W, Cheng J, Allaire JJ, Xie Y, McPherson J. shiny: Web Application Framework
for R [Internet]. 2017. Available from: https://cran.r-project.org/package=shiny
25. R Core Team. R: A Language and Environment for Statistical Computing [Internet].
Vienna, Austria; 2018. Available from: https://www.r-project.org/
26. Szöcs E. {webchem}: retrieve chemical information from the web [Internet]. Zenodo.
2015. Available from: http://dx.doi.org/10.5281/zenodo.33823
27. Kuleshov M V, Jones MR, Rouillard AD, Fernandez NF, Duan Q, Wang Z, et al. Enrichr:
a comprehensive gene set enrichment analysis web server 2016 update. Nucleic Acids
Res [Internet]. 2016 [cited 2018 Mar 20];44(W1):W90-7. Available from:
http://www.ncbi.nlm.nih.gov/pubmed/27141961
28. Jawaid W. enrichR: Provides an R Interface to "Enrichr" [Internet]. 2017. Available from:
https://cran.r-project.org/package=enrichR
29. Zhan M-M, Yang Y, Luo J, Zhang X-X, Xiao X, Li S, et al. Design, synthesis, and
biological evaluation of novel highly selective polo-like kinase 2 inhibitors based on the
tetrahydropteridin chemical scaffold. Eur J Med Chem [Internet]. 2018 Jan 1 [cited 2018
Feb 1];143:724–31. Available from:
https://www.sciencedirect.com/science/article/pii/S0223523417309613
30. Druker BJ, Tamura S, Buchdunger E, Ohno S, Segal GM, Fanning S, et al. Effects of a
selective inhibitor of the Abl tyrosine kinase on the growth of Bcr-Abl positive cells. Nat
Med [Internet]. 1996 May [cited 2018 Feb 8];2(5):561–6. Available from:
http://www.ncbi.nlm.nih.gov/pubmed/8616716
31. Pardanani A, Tefferi A. Imatinib targets other than bcr/abl and their clinical relevance in
myeloid disorders. Blood [Internet]. 2004 Oct 1 [cited 2018 Feb 8];104(7):1931–9.
Available from: http://www.ncbi.nlm.nih.gov/pubmed/15166033
32. Ndubaku CO, Crawford JJ, Drobnick J, Aliagas I, Campbell D, Dong P, et al. Design of
Selective PAK1 Inhibitor G-5555: Improving Properties by Employing an Unorthodox
Low-pK_a Polar Moiety. ACS Med Chem Lett [Internet]. 2015 Dec 10 [cited 2018 Feb
8];6(12):1241–6. Available from:
http://pubs.acs.org/doi/10.1021/acsmedchemlett.5b00398
33. Jeannot P, Nowosad A, Perchey RT, Callot C, Bennana E, Katsube T, et al. p27Kip1
promotes invadopodia turnover and invasion through the regulation of the PAK1/Cortactin
pathway. Elife [Internet]. 2017 Mar 13 [cited 2018 Feb 8];6. Available from:
http://www.ncbi.nlm.nih.gov/pubmed/28287395
34. Petrilli A, Copik A, Posadas M, Chang L-S, Welling DB, Giovannini M, et al. LIM domain
kinases as potential therapeutic targets for neurofibromatosis type 2. Oncogene
[Internet]. 2014 Jul 12 [cited 2018 Feb 20];33(27):3571–82. Available from:
http://www.ncbi.nlm.nih.gov/pubmed/23934191
35. Fitzgerald JB, Schoeberl B, Nielsen UB, Sorger PK. Systems biology and combination
therapy in the quest for clinical efficacy. Nat Chem Biol [Internet]. 2006 Sep 18 [cited
2018 Feb 21];2(9):458–66. Available from:
http://www.nature.com/doifinder/10.1038/nchembio817
36. Poulikakos PI, Xiao G-H, Gallagher R, Jablonski S, Jhanwar SC, Testa JR. Re-
expression of the tumor suppressor NF2/merlin inhibits invasiveness in mesothelioma
cells and negatively regulates FAK. Oncogene [Internet]. 2006 Sep 1 [cited 2018 Apr
11];25(44):5960–8. Available from: http://www.nature.com/articles/1209587
37. Shapiro IM, Kolev VN, Vidal CM, Kadariya Y, Ring JE, Wright Q, et al. Merlin deficiency
predicts FAK inhibitor sensitivity: a synthetic lethal relationship. Sci Transl Med [Internet].
2014 May 21 [cited 2018 Feb 21];6(237):237ra68. Available from:
http://www.ncbi.nlm.nih.gov/pubmed/24848258

38.   Tang J, Tanoli Z-U-R, Ravikumar B, Alam Z, Rebane A, Vähä-Koskela M, et al. Drug
Target Commons: A Community Effort to Build a Consensus Knowledge Base for Drug-
Target Interactions. Cell Chem Biol [Internet]. 2018 Feb 15 [cited 2018 Mar
21];25(2):224–229.e2. Available from: http://www.ncbi.nlm.nih.gov/pubmed/29276046
39.   Cao Y, Jiang T, Girke T. Accelerated similarity searching and clustering of large
compound sets by geometric embedding and locality sensitive hashing. Bioinformatics
[Internet]. 2010 Apr 1 [cited 2018 Feb 14];26(7):953–9. Available from:
http://www.ncbi.nlm.nih.gov/pubmed/20179075
515