1 **Title:** An automated, machine learning-based detection algorithm for spike-wave
2 discharges (SWDs) in a mouse model of absence epilepsy.
3

4 **Authors and Affiliations:** Jesse A. Pfammatter[1], Rama K. Maganti[2], and Mathew V.
5 Jones[1]
6
7 [1]Department of Neuroscience, University of Wisconsin, 1111 Highland Avenue,
8 Madison, WI, 53705
9
10 [2]Department of Neurology, University of Wisconsin, 1685 Highland Avenue, Madison,
11 WI 53705
12
Corresponding Author:
Jesse Pfammatter
5505 WIMR II
1111 Highland Ave.
Madison WI, 53705
email: pfammatter@wisc.edu

19
20 **Keywords:** nonconvulsive, animal model, electroencephalogram, machine learning,
21 sleep
22
23
Number of Text Pages: 21
Number of Words: 5236
Number of References: 31
Number of Figures: 7 (1 supplemental)
Number of Tables: 0

Summary and Keywords

Manual detection of spike-wave discharges (SWDs) from EEG records is time

intensive, costly and subject to inconsistencies and biases. Additionally, manual scoring

often omits information on SWD confidence/intensity which may be important for the

investigation of mechanistic-based research questions. While there are some

automated and semi-automated methods for the detection of SWDs in humans and rats,

there has been minimal development of these methods for SWDs in mice. Here we

develop a support vector machine (SVM)-based algorithm for the automated detection

of SWDs in the γ2R43Q mouse model of absence epilepsy. The algorithm first identifies

putative SWD events using frequency- and amplitude-based peak detection. Four

humans experienced at identifying SWDs scored a set of 2500 putative events identified

by the algorithm. Then, using predictors calculated from the Morlet wavelet transform of

each event and the labels from the human scored events, we trained a SVM to classify

(SWD/nonSWD) and assign confidence scores to each event identified from 60 24-hour

EEG records (11 animals). We provide a detailed assessment of intra- and inter-rater

scoring that demonstrate the advantages in reliability of automated scoring over human

scoring. The result of this algorithm is a scoring of SWDs along a 'confidence'

continuum that is highly correlated with human confidence and that allows us to more

effectively characterize ambiguous events in order to gain a better understanding of

'ground truth' in SWD detection (i.e., the most reliable features agreed upon by human

scorers that also correlate with objective physiological measures). Finally, we

demonstrate that events along our scoring continuum are temporally and

proportionately correlated, on the scale of seconds, with abrupt changes in spectral

power bands relevant to normal behavioral states including sleep. Our results

demonstrate the value of viewing detection of SWDs as a continuous, rather than

discrete, classification problem.

Keywords: nonconvulsive, animal model, electroencephalogram, machine

learning, sleep

Key Point Box

• Clinicians and researchers may benefit from an automated method of SWD

detection that provides a framework for the quantitative description of SWDs and

how they relate to other electrographic events.

• We present an algorithm for the automated, consistent, and rapid scoring of

SWDs that assigns a confidence to detected events that is highly correlated with

human scoring confidence.

• We characterize the human inter- and intra-rater consistency in the scoring of

potential SWD events and compare them with the algorithm.

• Events along the scoring continuum generated by the algorithm are temporally

and proportionately correlated with changes in spectral power bands relevant to

behavioral states including sleep.

Introduction

Spike-wave discharges (SWDs) are the signature electrographic (i.e. electroencephalogram, EEG) feature associated with absence epilepsy (1,2). These oscillations are thought to be associated with reverberations in thalamocortical networks and in rodents have a characteristic ~6Hz oscillation (3-5). Identification of SWDs from EEG records is extremely important both in the clinic as a tool for the diagnosis of absence epilepsy (6) and in research. In the clinic, identifying the presence of seizure related events in a patient's EEG may be sufficient to identify appropriate treatments. However detailed scoring of epilepsy-related events may be required for better patient care in the clinic (7) and to identify potential mechanisms of disease or to investigate the efficacy of drug treatments in research labs.

Manual scoring of SWDs is time-consuming and thus costly (8). In our experience, a skilled human may require 2-3 hours to score a 24-hour record. In both clinical and research settings where there are many subjects undergoing long-term monitoring, there may be many hundreds of hours of EEG from humans or experimental animals that must be scored. As a result of the significant burden of scoring numerous long EEG records, one technique for research labs is to use snippets or small segments of EEG that are presumed to be representative of the full dataset. Selective cherry-picking of data could introduce unanticipated bias.

In addition to the time and cost associated with manual scoring of SWDs, inconsistencies between multiple scorers may be abundant (3). Such inconsistencies are not well characterized for SWD detection in rodents (we present a detailed example here), however inconsistencies have been described in the scoring of other nonconvulsive epileptiform events such as interictal spikes (9). Indeed, nonconvulsive

epileptiform events are difficult to identify and classify for numerous reasons. First, the

definition of 'epileptiform' is often vague (10-12) and is subject to disagreement.

Clinicians and researchers typically use subjective criteria, such as that an event

'stands out of the background' (13), to force events into binary categories. Additionally,

many electrographic features appear hidden in the time domain (14) and thus may be

difficult to detect via visual inspection of EEG records. As we show below, events can

appear ambiguous to the same expert scorer such that, on repeated presentations, a

scorer changes their mind about an event's categorization. Such ambiguity is

reminiscent of human perception of optical illusions such as the Necker Cube (15) and

suggests that 'ground truth' (What do humans define as SWDs and how do those

events relate to, or arise from, ongoing non-epileptic brain activity?) in identifying

electrographic events may need to be considered in terms of confidence measures

rather than certainty.

Thus, there is a need for the development of robust, automated methods for the

detection of SWDs that allow for confidence-based scoring of events along a continuum

(as opposed to discrete) that mirrors physiologically relevant EEG features and that

matches human scoring characteristics. While algorithms have been developed for the

automated detection of SWDs (16-19), there has been little development of algorithms

for the detection or quantification of SWDs in mice (16). This is an important gap

because rodent models are currently the main research tools for understanding basic

mechanisms of epilepsy. They allow for prospective and well-controlled research

designs that are not ethically or practically feasible in humans.

We present a support vector machine (SVM)-based algorithm for the detection of

SWDs in mice expressing a GABA$_A$ receptor mutation (γ2R43Q) that causes absence

epilepsy (5,20). This algorithm is much faster than a human, scoring a 24-hour record in

~3 minutes. Importantly, this algorithm agrees well with human scoring and captures the

statistical characteristics of human uncertainty. Additionally, and unlike human experts,

it is 100% self-consistent. Finally, we show that events along the scoring continuum

generated by the algorithm are temporally and proportionately correlated with changes

in spectral power bands relevant to behavioral states including sleep.

Methods

All use of animals in this manuscript conformed to the *Guide for the Care and*

Use of Laboratory Animals (21) and was approved by the University of Wisconsin-

Madison Institutional Animal Care and Use Committee.

Animal colonies. Animals were bred from a colony maintained at the University of

Wisconsin-Madison. In a paired breeding scheme, female wild-type (RR) mice of a

C57BL/6J-OlaHsD background (Harlan, Madison, WI) were bred with male

heterozygous mice expressing the γ2R43Q knock-in mutation in the same background.

Heterozygous knock-in mice (RQ) experience SWDs concurrent with behavioral arrests

(5) whereas homozygous mutants were almost never born. The γ2R43Q strain was

provided by Dr. Steven Petrou (The University of Melbourne, Parkville, Australia).

Computer Programing and Code Accessibility. All analyses, data processing, and

event classification was done in Matlab (Mathworks, Natick, MA) using a combination of

home-written and publicly available scripts. The final version of this algorithm was

executed with Matlab 2017b and all code is available at the GitHub repository:

https://github.com/jessePfammatter/detectSWDs.

EEG implantations, recording, and data. EEG electrodes were implanted as

described in (22). Briefly, male heterozygous knock-in (RQ) and wild-type (RR) mice

were implanted at p24 under isoflurane anesthesia (1-2% in 100% O2). Each animal

was implanted with gold plated miniature screw electrodes over the right and left frontal

and parietal cortices, and one over the cerebellum as reference. Two vinyl-coated

braided stainless-steel wire electrodes were placed in the nuchal muscle for

electromyogram (EMG) recording. The EEG and EMG leads were wired to a head cap,

which was affixed to the skull with dental acrylic.

After recovery from surgery (2-3 days), animals were connected to a

multichannel neurophysiology recording system (Tucker-Davis Technologies, TDT,

Alachua, FL, USA) to continually sample EEG and EMG signals at 256 Hz (digitally

bandpass filtered between 0.1 and 100 Hz) for up to fourteen days. Offline, data were

notch filtered at 60 Hz using a Chebyshev Type II digital filter and high-pass (>2 Hz)

filtered with a Chebyshev Type I digital filter. EEG signals were then normalized using

the following variation of a z-score normalization: First, we fit a Gaussian distribution to

the all-points histogram of each 24-hour record using least-squares minimization via

Nelder-Mead Simplex optimization (23) as implemented by the fminsearch() function in

Matlab. We then normalized the 24-hour record by subtracting the mean from each data

point and dividing by the standard deviation of the model fit. The resultant normalization

is different from the standard z-score normalization in that the mean and standard

deviation are calculated from estimating the best-fit Gaussian model of the EEG rather

than empirically calculating the mean and standard deviation from the entire record. We

employed this normalization because it is less influenced by high amplitude EEG signal

(e.g. convulsive seizures or high amplitude spikes) and artifacts. All analyses here used

a frontal EEG channel (usually front-left).

Automated Event Detection. We used a two-stage algorithm for the detection and

classification of SWDs. In Stage 1, we automatically detected putative SWD events

using a frequency and amplitude threshold-based approach. The parameters we

selected for this first stage were intended to be 'all inclusive' of potential SWD events at

the cost of also finding false positives, which were filtered out in Stage 2. First, we

detected all peaks that were a) above 3 standard deviations from the mean of the

normalized EEG signal and b) that had a peak greater than 3 standard deviations from

the mean of the derivative signal (the negative of the first derivative of the normalized

signal) that preceded (within 60 ms) the peaks identified in the normalized EEG. Then,

sets of peaks were grouped into 'possible SWD events' if their frequency was between

3-11 Hz. This procedure selected events with both a fast-rising phase (i.e. peaks from

the negative first derivative signal correspond to fast rising phases) and a prominent

amplitude. These event features fall within previously published guidelines for the

characteristics of SWDs in mice (24),(5) and rats (4),(3).

Manual Event Classification. We presented 2500 putative SWD events identified

by the Stage 1 detection method to each of four human scorers for manual

classification. Of these, 2050 were randomly selected unique events from 10 24-hour

EEG records from 5 animals (3 RQ and 2 RR). We also randomly selected 50 events to

be repeated 10 times each. Each of the 2500 events was shown to the human scorers

in random order via a graphical user interface (GUI). Each event was presented as an

8-second length of normalized single-channel EEG with the putative event highlighted in

yellow. Scorers were asked to classify each event as either a SWD or nonSWD and

were given as much time as they needed to view/review/reclassify events. All four

human scorers were already skilled in the identification of SWDs but were blind to the

genotypes, and two were blind to the presence of repeated events. None of the scorers

were aware of which events were repeated because the order of events was random.

This manual scoring of a small subset of data (much less than 1%) required about 1-2

hours per scorer.

193   Additionally, and prior to the scored described in the previous paragraph, scorer

194   S1 manually scored five unaided (without computer assistance) 24-hour EEG records

195   for the presence of SWDs. This scorer marked epochs containing SWDs using Svarog

196   v1.0.10 (Braintech, Ltd., United Kingdom).

197   EEG/EMG signals were also manually scored for sleep stages (wake, NREM, or

198   REM) (see Fig. 3) in 4 second epochs with Serenia Sleep Pro software (Pinnacle

199   Technology, Lawrence, KS, USA).

200   *Event Predictor Variables:* From the putative events detected by Stage 1, we

extracted 12 predictor variables for use in Stage 2 of the automated algorithm: event

classification with a Support Vector Machine (SVM). These variables were calculated

from four sets of scale ranges from the wavelet transform using the cwt function in

Matlab (Morlet wavelet) of each event. These ranges were picked to target the

characteristic ~6Hz frequency of SWDs in mice and several of its harmonic

components. For each of the 4 sets of scales (49-40 $\approx$ 4.4-8.2 Hz, 39-30 $\approx$ 8.8-16.4 Hz,

29-20 ≈ 17.6-32.8 Hz, and 19-10 ≈ 35.1-65.5 Hz,) we summed the absolute value of the

wavelet transform scalogram amplitude across the scale set and across the duration of

the event and then calculated the mean, standard deviation and maximum (4 scale

ranges * 3 statistics = 12 predictors).

Automated Event Classification. For Stage 2 of the algorithm we developed an

SVM-based automated method to classify SWD events identified in Stage 1 using the

12 event predictors. In brief, a SVM is a machine learning-based classification method

that aims to separate groups of events after being trained with set of 'known' labels. The

boundaries of the classification space are defined by events assigned as support

vectors. The location of each event relative to the nearest support vectors in predictor

space can be used for binary classification of events as SWD or nonSWD. The distance

from each event to its nearest support vector can be used as a proxy for confidence in

the assigned classification of each events. Readers unfamiliar with SVM may find a

suitable introduction in (25) or (24). We trained the SVM (fitcsvm() function) using the

labels provided by the human scorers (10000 labels, 2500 per scorer for 2050 unique

events) where the algorithm created a weighted response for each unique event based

on the average human label across all four scorers. In our preliminary testing of the

algorithm and upon visual inspection of the predictor variables for these events, we

choose a Gaussian kernel for the SVM (24). In order to choose the proper

hyperparameters for the SVM (kernel scale, box constraint, and cost matrix used in

fitcsvm()), we employed a grid-search based optimization process. We trained the SVM

under each unique combination of the following parameters; kernel scale = [1, 5, 10, 15,

20], box constraint = [5, 10, 15, 20, 25], and a cost matrix of [0, 1; x, 0] where x = [1,

1.5, 2, 2.5, 3]. We then chose hyperparameters with the following guidelines: A) Each

scorer's bias should be as balanced as possible in the final model. This was achieved

by minimizing the standard deviation of the agreement between human scorers and the

SVM. B) To avoid overfitting, we assessed our model fit using k-fold cross-validation

which partitions the data into multiple subsets in order to test model fit on each subset

individually (24). We quantified this by calculating the mean 5-fold cross-validation

accuracy between the SVM and the training labels for each of 10 iterations of model

construction (there is variability as this is a stochastic process) and taking the standard

deviation of this value (26). Minimizing this quantity allowed us to select a model that

performs similarly on numerous randomly chosen subsets of data. C) The model should

match human uncertainty in order to generate accurate confidence-based model scores

(distance from each event to the nearest support vector). We calculated this agreement

by calculating the R^2 between the model scores and the weighted human responses for

each of the 50 repeated events within the data set (i.e. intra-rater reliability). Maximizing

this quantity produces a model with high fit to the human uncertainty. Although A, B,

and C were the primary parameters for optimization, we considered several other

quantities including: i) agreement between the SVM and the events that all humans

agreed upon (human consensus data or HC), ii) average agreement between the

human scorers and the SVM and iii) average of the 5-fold cross-validation process.

While these parameters are important, their optimal set point is unclear given that

variability between human scorers suggests that ground truth labels may not exist for

these data. Here, we used the following hyperparameters: kernel scale = 10, box

constraint = 10, cost matrix x = **1.5**.

In order to highlight the relative predictive importance of the variables used in the

SVM we performed a LASSO regression (27) with the SVM classification score as a

response variable and the 12 variables calculated from the wavelet transform of each

event as predictor variables. We allowed the LASSO regression 100 iterations with

cross validated (10 fold) fits and selected the final coefficients from the model with a

lambda value (indicating lowest cross-validation error) that was one standard deviation

larger than the model with the lowest lambda value.

In order to highlight the differences between the human and SVM scoring of the

2500 events identified by Stage 1, we calculated receiver operating characteristic

curves between each scorer and the algorithm, and a table showing pairwise agreement

between each of the four human scorers, the SVM trained with K-means labels, the final

SVM, and the human consensus labels. In order to demonstrate the performance of the

algorithm in comparison to the human scoring of an unannotated (no information from

Stage 1) and out-of-training data set, we calculated confusion matrices from the epoch-

by-epoch scoring of SWDs identified by S1 and the Stage 1 events, and SWDs

identified by S1 and the Stage 2 (final SVM) scores.

Application of the algorithm and preliminary testing of the SWD output scores.

We then applied the algorithm to classify SWDs in several 24-hour EEG records that

were not used for algorithm development (i.e., out-of-sample data). Using the output of

the algorithm we calculated the event-triggered average: (i.e., the average of all

segments of one signal aligned to the time of events in another signal) of 50 random

examples of strong SWDs (distance to support vector of >1 to 2), moderate SWDs (>0.5

to 1), weak SWDs (>0 to 0.5), weak nonSWDs (<0 to -0.5), moderate nonSWDs (<-0.5

to -1), and strong nonSWDs (<-1 to -2), and 50 random locations not identified by our

algorithm to delta (0.5-4 Hz) , theta (6-9 Hz), sigma (10-14 Hz), and gamma (25-100 Hz)

power surrounding each event during lights-on and lights-off periods.

Results

We found that SWDs in γ2R43Q animals have a characteristically strong and

continuous power in the ~6 Hz frequency range during the entire discharge event, (Fig.

1) which is consistent with previous descriptions of SWDs in these animals (5).

Additionally, SWDs have a very reliable 'fingerprint' in the wavelet transform time-

frequency decomposition (Fig. 1).

Manual Scoring and Inter- and Intra-Rater Reliability. Overall, human scorers

were quite variable in their scoring. Out of the 2050 unique events, the four human

scorers were in complete agreement (i.e., consensus labels) for 57% of the events

(1159 events, 940 nonSWD and 219 SWD). Figure 2 shows a characterization of

human scoring of the 2500 events presented as 2D cross-sections in predictor space for

6 of the predictor variables used in the SVM. Humans tended to agree about nonSWD

events (blue) whereas disagreement (green) and agreement about SWDs (red) tended

to occupy similar regions of feature space. Further characterization of the inter- and

intra-rater reliability are shown in Figure 3, which demonstrates the difference in rating

trends of 3 of the human scorers. Figure 3B shows 8 example events pulled from the 50

events presented to each human scorer 10 times. These 8 events are ranked in order of

agreement where events in dark red were fully agreed upon SWDs (0:40,

nonSWD:SWD), blue were fully agreed upon nonSWDs (40:0) and intermediate colors

represent ambiguous responses. For each of the 2500 events presented to human

scorers, agreed-upon SWD events have high values for both the maximum values in

4.4-8.2 Hz and 17.6-32.8 Hz ranges whereas agreed-upon nonSWD events have a low

maximum value for these bands (Fig. 3B). Intra- and inter-rater reliability data are

shown in Figure 3C-E. Inter-rater reliability on the 50 repeated events (RE) data (Figure

3D) agreed with the trend in distribution of human agreement for all of the 2500 events

presented (low-resolution data). Average intra-rater reliability across all scorers was

100% for 13 of 50 repeated events (Figure 3E). Thirteen of the 50 RE had an average

intra-rater agreement of 90% or less across all scorers. For individual scorers, intra-

rater agreement was as low as 50% for the most ambiguous events. Average Intra-rater

reliability was 94% across all scorers and all 50 repeated events.

Performance of Automated Detection Compared to Manual Scoring. Traditional

clustering methods such as K-means failed to partition the data similar to the human

scorers (notice the 'fuzziness' in SWD/nonSWD scoring in Figure 3A) but rather drew a

hard line between SWD/nonSWD events (Fig. 4A). Figure 4B shows the output of the

SVM that was trained using the human scoring labels and demonstrates a similar

'fuzziness' in SWD/nonSWD scoring as human scorers. In fact, the SVM classification

scoring associated with each event (e.g. distance to the nearest support vector) is

strongly correlated with human inter-rater reliability (Fig. 4C). In comparing labels from

our final SVM algorithm and the human consensus labels, the sensitivity (or the true

positive rate, equal to the number of agreed upon SWD events between SVM and the

human consensus labels divided by the total number of SWD events from the human

consensus labels) was 0.98 and the specificity (or the true negative rate, equal to the

number of agreed upon nonSWD events between SVM and the human consensus

labels divided by the total number of nonSWD events from the human consensus

labels) was 0.95. Figure 4D shows the coefficients for the LASSO regression. The

absolute value of these coefficients indicates the relative importance of each variable

whereas the sign indicates whether a large versus small value of that variable, relative

to the others, was most predictive of the SVM classification scores. Importantly,

negative coefficients do not indicate that the magnitude for those variables were lower

for SWDs than nonSWDs on average. Figure 4E-G show additional information for

assessing agreement between various stages of the algorithm and human scoring.

Figure 4E shows the receiver operating characteristics curves between the 2500 events

scored by each of the human scorers and the SVM scores. The average agreement

between humans was similar to that between humans and K-means but lower than the

average agreement between the SVM and the humans. The standard deviation of the

agreement between the SVM and the human scorers is much lower than between the

human scorers indicating that the SVM agrees with the humans with less variability than

the humans agree with themselves (Fig. 4F). Figure 4G shows a comparison between

performance of the scoring of five unannotated (without computer assistance) 24-hour

EEG records by S1 and the SVM. Importantly, the first stage of our algorithm captured

the majority of epochs marked as containing and SWD by S1.

We present graphical results for the optimization of our tunable SVM parameters

in the Supplemental Figure S1.

Application of the Algorithm. We applied the algorithm to analyze SWDs in a set

of 60 24-hour EEG recordings from RR and RQ animals, 50 of which were not used for

SVM development. The algorithm analyzed these records in ~40 minutes, or ~1.5

minutes per 24-hour record (compare with 1-3 hours required for a human to score

SWDs in a 24-hour record). We found an average of 737.51 ± 482.28 events per 24-

hour RQ record (n = 8 animals, 45 24-hour records) where 194.09 ± 169.37 of these

events are considered SWD events (> 0 SVM score). Per 24-hour record in RR animals

(n = 3 animals, 14 24-hour records), we find 409.64 ± 207.28 possible events where

26.79 ± 21.18 of these events are considered SWD events. Figure 5 shows the

application of our algorithm on a representative 24-hour record from a RQ animal. Using

the output of the algorithm (a list of event times and distance to nearest support vector)

on an RQ animal, we demonstrated the relatedness of SWD and nonSWD events (as

labeled by the SVM) to sleep staging. We found strong and abrupt relationships

between SWDs and each power band that sometimes preceded the SWD by several

minutes (Fig. 5D-K).

As previously mentioned, the detection algorithm found 26.79 ± 21.18 events

considered to be SWD in RR animals. This value might be considered by some as the

'false positive' rate for our detection algorithm in wild-type animals. However, some

proportion of these events have very strong SWD features and show a temporal

relationship to the delta, theta, sigma, and gamma power bands as events in RQ

animals (data not shown). Figure 6 shows six events pulled from normal animals that

have strong visual SWD characteristics.

Discussion

We have developed an automated, SVM-based algorithm for the detection of

SWDs that leverages human agreement to develop a continuous, confidence-based

score in addition to a binary classification (SWD/nonSWD). The algorithm was trained

using a dataset with 2500 putative events and labels (SWD or nonSWD) from four

expert human scorers, using 5-fold internal cross-validation, and tested against the

performance of a human scorer (S1) on an unannotated (no computer information) and

out out-of-training data set. The resultant SVM agreed with humans as well as they

agreed with each other (~70%) but, unlike the other classification technique that we

investigated (K-means, Fig. 4A), the SVM did not draw sharp boundaries in predictor

space between regions containing SWDs vs nonSWDs. Instead, it drew fuzzy, tightly

interleaved boundaries similar to those of human scorers. The algorithm also correlated

well with the uncertainty of individual humans when presented with repetitions of the

same waveforms, thus capturing ~77% of the ambiguity in human perception of SWD

waveforms (Fig. 4C).

We optimized the algorithm to minimize the variance between human scorers

and the SVM, thus reducing biases introduced by any individual human scorer.

Importantly, as evident from the LASSO regression and similar to human scorers, the

algorithm selected an ensemble of predictor variables that allows for a maximization of

the signal to noise ratio in SWD events. After training, fully-automated scoring of 24-

hour EEG records was conducted, requiring ~1.5 minutes per 25-hour record. Thus, the

algorithm reproduced statistical features of the human decision-making process while

adding important aspects that humans lack, including consistent, unbiased and rapid

scoring of events.

There are, of course, some caveats. Although the method works quite well on the

γ2R43Q model of absence epilepsy, we have yet to fully test it in other models of

absence epilepsy. Continued development will include testing and expansion to other

animal models as well as to human EEG. We anticipate that Stage 1 (event detection)

should work quite well for most types of absence seizures exhibiting a ~6 Hz character

(as occurs in rodents). The frequency range of interest can be easily adjusted for

different data sets. However, for Stage 2 (the SVM classification), some retraining of the

algorithm may be necessary, using human scoring on a very small subset of data that

are representative of the different types of subjects/treatments being analyzed. The

time/cost of such retraining may be as low as a few hours per human scorer. It is

possible that the current SVM could be tuned to perform broadly across additional

models of absence epilepsy without re-training via a tuning of the SVM

hyperparameters. In this current version, we selected a set of optimization parameters

and SVM kernel that best fit the characteristics of human scoring. In general,

modification of the hyperparameters or kernel can make a SVM more generalizable

(25). Continued development of this algorithm may also include components shown to

be important for other SWD detection algorithms such as using phase information from

the wavelet transform such as was done in (16).

Despite its limitations, we have used this algorithm to highlight a few important

aspects of SWDs that would have been difficult or impossible to identify solely with

human classification. Our data show that events along the spectrum of the SVM score

(and thus SWD confidence) show temporal and proportional correlations with abrupt

changes in EEG power bands. While these correlations are most prominent in SWDs

with the highest SVM scores, events with lower scores (and even those below

threshold) continue to show correlations, albeit with smaller effects. Qualitatively similar

temporal patterns were observed in all of the R43Q animals analyzed in this study (data

not shown). Thus, the SVM reveals physiologically-relevant changes in brain activity

that are commonly used in the scoring of sleep and shows that these changes are

temporally linked to, and could potentially be used to predict, the occurrence of SWDs.

Importantly, our findings align with previous work showing shifts in phase-amplitude

coupling up to a minute prior to SWDs (28), and that SWDs are related to sleep timing

(29).

Additionally, our algorithm provides the opportunity to investigate SWDs and

SWD-like activity of short duration. Most research associated with SWD detection

discards events shorter than one second or half a second (16). Although brief

electrographic events with SWD-like characteristics are not likely to be associated with

behavioral absence seizures, examining their relation to other physiological events

(e.g., Fig. 5) may be important for understanding the ongoing brain mechanisms that

evolve into such seizures.

We also identified SWD-like events in wild-type mice, consistent with the

hypothesis that SWD events represent a corruption of otherwise normal brain processes

(30). If so, finding examples of SWDs in wild-type mice with low intensity (i.e. smaller

distance to nearest SV) is to be expected. Additionally, (31) found that 8 of 27 strains of

wild type mice had SWDs including several from the C57-related backgrounds. It is

important to have a rigorous method that is capable of detecting these lower intensity

events because, similar to higher intensity SWD events, many show a temporal

relationship with several bands of EEG power (Fig. 5). These low intensity events would

mostly likely be missed by human scorers because they either have lower amplitude or

a less consistent pattern in the time domain (14) (i.e. not easily identifiable by human

scorers). Nonetheless, these low intensity events show temporal relationships with

several EEG power bands that coincide with confident SWD events (data not shown).

Although other groups have developed algorithms for the detection of SWDs (16-

19), to the best of our knowledge, no other group has designed an algorithm to mirror

human confidence in scoring. We used the confidence-based scores generated from

our algorithm and based on human scoring characteristics as a starting point to help

establish ground truth for SWD events. We present some data, namely that the

relationship between event-triggered averages and EEG power spectra change in a

continuous trend with decreasing likelihood of SWD (i.e. SVM score), that indicates that

variability in inter- and intra-rater reliability are important characteristics to consider in

helping us learn more SWDs. However, it is important to note that this is only a step

towards a clearer understanding of SWDs.

Acknowledgements

We would like to thank Kile P. Mangan for scoring SWDs, Eli Wallace for scoring

sleep, and Rebecca Willet for helpful conversations regarding SVMs. The data analyzed

were collected by KPM and Aaron Nelson in the lab of Chiara Cirelli. Antoine Madar and

Eli Wallace provided invaluable feedback during the development of this work. Rachel

Bergstrom and two anonymous reviewers provided valuable reviews which improved

this manuscript. This work was funded in part by grants from the National Institute for

Health (RO1 NS075366, MVJ) and the Department of Defense (PR161864, RKM).

Conflicts of Interest

The authors report no conflicts of interest.

Ethical Publication Statement

We confirm that we have read the Journal's position on issues involved in ethical

publication and affirm that this report is consistent with those guidelines.

References

1.   McCormick DA, Contreras D. On the cellular and network bases of epileptic
seizures. Annu Rev Physiol. 2001 63(1):815–46.

2.   Huguenard JR, McCormick DA. Thalamic synchrony and dynamic regulation of
global forebrain oscillations. Trends Neurosci. 2007 30(7):350–6.

3.   Pinault D, Vergnes M, Marescaux C. Medium-voltage 5-9-Hz oscillations give
rise to spike-and-wave discharges in a genetic model of absence epilepsy: In
vivo dual extracellular recording of thalamic relay and reticular neurons.
Neuroscience. 2001 105(1):181–201.

4.   Sitnikova E, van Luijtelaar G. Electroencephalographic characterization of
spike-wave discharges in cortex and thalamus in WAG/Rij rats. Epilepsia. 2007
48(12):2296–311.

5.   Tan HO, Reid CA, Single FN, Davies PJ, Chiu C, Murphy S, et al. Reduced
cortical inhibition in a mouse model of familial childhood absence epilepsy.
Proc Natl Acad Sci USA. 2007 104(44):17536–41.

6.   Lowenstein DH. Seizures and Epilepsy. In Kasper DL (Ed) Harrison's
Principles of Internal Medicine. 19th Ed. New York, N.Y.: McGraw-Hill
Education; 2015.

7.   Boly M, Maganti R. Monitoring epilepsy in the intensive care unit: Current state
of facts and potential interest of high density EEG. Brain Injury. 2014
28(9):1151–5.

8.   Tzallas AT, Tsipouras MG, Tsalikakis DG, Karvounis EC, Astrakas L,
Konitsiotis S, Tzaphlidou M. Automated epileptic seizure detection methods: a
review study. In Epilepsy-histological, electroencephalographic and
phychological aspects 2012. InTech.

9.   Webber WR, Litt B, Lesser RP, Fisher RS, Bankman I. Automatic EEG spike
detection: what should the computer imitate? Electroencephalogr Clin
Neurophysiol. 1993 87(6):364–73.

10.   Fisher RS, Scharfman HE, deCurtis M. How can we identify ictal and interictal
abnormal activity? In Issues in Clinical Epilpetology: A View from the Bench
2014 (pp. 3-23). Springer, Dordrecht.

11.   Koutroumanidis M, Arzimanoglou A, Caraballo R, Goyal S, Kaminska A,
Laoprasert P, et al. The role of EEG in the diagnosis and classification of the
epilepsy syndromes: a tool for clinical practice by the ILAE Neurophysiology
Task Force (Part 1). Epileptic Disord. 2017 19(3):233–98.

12. Koutroumanidis M, Arzimanoglou A, Caraballo R, Goyal S, Kaminska A,
Laoprasert P, et al. The role of EEG in the diagnosis and classification of the
epilepsy syndromes: a tool for clinical practice by the ILAE Neurophysiology
Task Force (Part 2). Epileptic Disord. 2017 19(4):385–437.

13. Webber WRS, Lesser RP. Automated spike detection in EEG. Clin
Neurophysiol. 2017 128(1):241–2.

14. Lüttjohann A. Disclosing hidden information in the electroencephalogram using
advanced signal analytical techniques. J Physiol (Lond). 2017 595(23):7021–2.

15. Kornmeier J, Bach M. The Necker cube - an ambiguous figure disambiguated
in early visual processing. Vision Res. 2005 45(8):955–60.

16. Richard CD, Tanenbaum A, Audit B, Arneodo A, Khalil A, Frankel WN.
SWDreader: A wavelet-based algorithm using spectral phase to characterize
spike-wave morphological variation in genetic models of absence epilepsy. J
Neurosci Meth. 2015 242:127–40.

17. Ovchinnikov A, Lüttjohann A, Hramov A, van Luijtelaar G. An algorithm for
real-time detection of spike-wave discharges in rodents. J Neurosci Meth. 2010
194(1):172–8.

18. Xanthopoulos P, Rebennack S, Liu C-C, Zhang J, Holmes GL, Uthman BM, et
al. A Novel Wavelet Based Algorithm for Spike and Wave Detection in
Absence Epilepsy. IEEE; 2010. pp. 14–9.

19. Bauquier SH, Lai A, Jiang JL, Sui Y, Cook MJ. Evaluation of an automated
spike-and-wave complex detection algorithm in the EEG from a rat model of
absence epilepsy. Neuroscience Bulletin. 2015 31(5):601–10.

20. Petrou S, Reid CA. The GABAAγ2(R43Q) mouse model of human genetic
epilepsy. In Jespers Basic Mechanisms of the Epilepsies. 4th ED. Bethesda
(MD): National Center for Biotechnology Information (US); 2012.

21. National Research Council. Guide for the Care and Use of Laboratory Animals.
National Academics Press. 2010.

22. Nelson AB, Faraguna U, Zoltan JT, Tononi G, Cirelli C. Sleep patterns and
homeostatic mechanisms in adolescent mice. Brain Sci. Multidisciplinary
Digital Publishing Institute; 2013 Mar 19;3(1):318–43.

23. Nelder JA, Mead R. A Simplex Method for Function Minimization. The
Computer Journal. 1965 7(4):308–13.

24. Christianini N, Shawe-Taylor J. An Introduction to Support Vector Machines
and Other Kernel-based Learning Methods. 2000.

25. Ben-Hur A, Weston J. A User's Guide to Support Vector Machines. In: Data
Mining Techniques for the Life Sciences. Totowa, NJ: Humana Press; 2009.
pp. 223–39. (Methods in Molecular Biology; vol. 609).

26. Cawley GC, Talbot NLC. On Over-fitting in Model Selection and Subsequent
Selection Bias in Performance Evaluation. Journal of Machine Learning
Research. 2010 11:2079–107.

27. Muthukrishnan R, Rohini R. LASSO: A feature selection technique in predictive
modeling for machine learning. IEEE; 2016. pp. 18–20.

28. Maheshwari A, Akbar A, Wang M, Marks RL, Yu K, Park S, et al. Persistent
aberrant cortical phase-amplitude coupling following seizure treatment in
absence epilepsy models. J Physiol (Lond). 2017 10(23):387–7260.

29. Halasz P, Terzano MG, Parrino L. Spike-wave discharge and the
microstructure of sleep-wake continuum in idiopathic generalised epilepsy. Clin
Neurophysiol. 2002 32(1):38–53.

30. Kelly KM. Spike–wave Discharges: Absence or Not, a Common Finding in
Common Laboratory Rats. Epilepsy Currents. American Epilepsy Society;
2004 4(5):176–7.

31. Letts VA, Beyer BJ, Frankel WN. Hidden in plain sight: spike-wave discharges
in mouse inbred strains. Genes, Brain and Behavior. Blackwell Publishing Ltd;
2014 13(6):519–26.

 Legends

Figure 1: **(A)** An EEG trace from the frontal left channel of a mutant

γ2R43Q mouse showing three putative SWD events detected by Phase 1. **(B)** The

wavelet transform scalogram of the trace in A. We use the maximum, average and

standard deviation of the scalogram amplitude from four bands (~4.4-8.2 Hz, ~8.8-16.4

Hz, ~17.6-32.8 Hz, and, ~35.1-65.5 Hz shown as bands with white frequency labels) to

generate 12 predictors to train the SVM-based classification algorithm.

Figure 2: Each of the 2500 human-scored events labeled by agreed SWD (red),

consensus agreed nonSWD (blue), and consensus disagreed (green) shown as a 2D

cross-sections in predictor space for 6 of the 12 predictor variables used to characterize

a SWD event. The diagonal shows the histograms for each category of label for each of

the 6 predictor variables. Notice how disagreed-upon events tend to align with SWD

rather than nonSWD events.

Figure 3: A characterization of the variability of human classification of SWD events.

(A) Each of the 2500 events as labeled by human scorers 1-3. Note the dramatic

variability in labeling between each of the scorers. **(B)** examples of eight events

identified as 'putative' SWD events by the first stage of the algorithm. The colored bar

below each trace represents the start and end of each event, where color shows the

degree of agreement between human scorers. This color scale matches that above

Panel C. **(C)** Each of the 2500 putative SWD events presented to each human scorer,

plotted by the maximum value of the wavelet transform from ~ 4.4-8.2 Hz versus the

maximum value of the wavelet transform from ~ 17.6-32.8 Hz. The numbers mark

locations the 8 example events from panel B. **(D)** The average *inter-rater* agreement

for each of the 50 repeated events (RE, large circles) plotted over the same data. Note

that the agreement between raters approaches a coin flip (green) near the intersection

of the strong SWD and nonSWD events. **(E)** The average ***intra-rater*** reliability for the

same 50 repeated events as shown in panel D. Note the shifting scale associated with

the color bars above panels C, D, and E.

Figure 4: SVM-based approach to SWD classification. **(A-B)** each of the 2500 potential

SWD events displayed by the maximum value of the wavelet transform from ~ 4.4-8.2

Hz versus the maximum value of the wavelet transform from ~ 17.6-32.8 Hz. **(A)** shows

events as clustered by K-means clustering using the 12 wavelet transform predictor

variables. **(B)** Events labeled by a SVM trained with the human scoring labels and fit

with a Gaussian kernel. The numbers 1-8 are overlaid to show the SVM's classification

of the 8 example events from Figure 2. **(C)** The relationship between the distance to

nearest support vector (x axis, 2 is more likely SWD) and the average intra-rater

reliability (from Fig. 2C) for the 50 repeated events. **(D)** The coefficients from a LASSO

regression which highlights the relative importance (absolute value of coefficients) and

relative magnitude (sign of coefficients) of the variables used to predict the SVM score.

(E) Receiver operating characteristic curves showing the performance of each human

scorer as compared to the SVM scores. **(F)** The agreement matrix for classification of

2500 potential SWD events as classified by four human scorers (S1-S4), an SVM

trained with the KM labels, and the human consensus data (HC, the events on which all

human scorers agreed). Note that the agreement between all of the humans (bold,

green) was comparable to that between the SVM classification and the humans (italic,

blue) although the agreement between the SVM and the humans shows much lower

variability than the agreement between the humans alone. **(G)** Confusion matrices

comparing the epoch-by-epoch scoring of events identified by Stage 1 of the algorithm

(top matrix) and events classified as SWD by the Stage 2 SVM (bottom matrix) and S1

scoring of five 24-hour EEG records representing two RQ and two WT animals. S1

scored these files without the any information from the algorithm regarding putative

SWD events. Red values show the false negatives and green values show the false

positives (relative to the human scoring).

Figure 5: Implementation of the SWD detection algorithm on a 24-hour EEG recording

from a mutant γ2R43Q mouse with absence epilepsy and a demonstration of the high-

resolution data provided the 'distance to SV' measure associated with each identified

event. **(A)** A hypnogram showing WAKE (blue), nREM (green) and REM (magenta)

epochs (4 s) manually scored by RM. **(B)** A visual representation of the events identified

by the SVM-based algorithm. The vertical height of each bar represents the distance to

nearest support vector where values > 0 are likely to be SWDs whereas events < 0 are

likely nonSWD events. The color at the end of each vertical bar shows the sleep stage

associated with the identified event. The histogram on the right of panel C shows the

distribution of event scores and colors are representative of the categories of events

used in panels D-K. **(C)** shows the average number of SWDs (score > 0) per hour for all

sleep stages (red, larger circles), WAKE, nREM, and REM sleep stages. Notice the

pattern of increased SWD events during lights on periods (07:00 - 18:00, normal sleep

time for mice) as compared to lights off. The event-triggered average of delta **(D, H)**,

theta **(E, I)**, sigma **(F, J)**, and γ **(G, K)** power (calculated in 4 s epochs) for events at

several sets of distances from the nearest support vector where redder colors are more

likely to be SWDs (red: >1 to 2, yellow: >0.5 to 1, lime: 0 to 0.5, green: 0 to -0.5, cyan:

<-0.5 to -1, blue: <-1 to -2). Note that the color scale in this figure matches the color

scale in panel B of Figure 3. The black trace in each of these panels shows the null-

hypothesis: the event-triggered average of each power value for 100 randomly selected

epochs in the EEG record. Events with the largest positive distance to SV (red) show a

strong relationship to all power bands during lights on (white panels) and lights off (grey

panels) and this relationship deteriorates as event distances decrease. Note that all

events identified by the algorithm show some sort of temporal relationship with theta

and sigma power as compared to randomly selected EEG locations. Further

investigation is needed to identify the relationship of each group of these events to

absence epilepsy.

Figure 6: Six SWD-like events from a 24-hour record of a wild type, nonepileptic animal

as identified by the SWD detection algorithm.

Supplemental Figure S1: Parameter optimization for the SVM. We used a grid search

method to vary box constraint, kernel scale, and the cost function parameters of the

SVM. **(A-F)** Unique pair-wise combinations of our output parameters: 1) the standard

deviation of the 5-fold cross fold validation, 2), the agreement between the humans and

the SVM 3) the standard deviation of the agreement between the humans and the SVM,

and 4) the R^2 between the SVM classification score and the repeated event data set.

A F.L. EEG signal w/ absence seizures

5 Norm. EEG Amp.
1 s

B continuous wavelet transform,'Mortlet'

35.1-65.5 Hz

17.6-32.8 Hz

8.8-16.4 Hz

4.4-8.2 Hz

A intra-rater Agreement

S1 S2 S3 S4

SWD
notSWD

Max CWT Value at ~ 17.6-32.8 Hz

Max CWT Value at ~ 4.4-8.2 Hz

B Examples of Repeated Events (RE)

5 Norm. EEG Amp.
1 s

1 2 3 4

5 6 7 8

notSWD (0:4)   2:2   SWD (4:0)

notSWD   20:20   SWD

.75   1

C inter-rater Reliability ALL

D inter-rater Reliability RE

E intra-rater Reliability

Max CWT Value at ~ 17.6-32.8 Hz

Max CWT Value at ~ 4.4-8.2 Hz