Using set theory to reduce redundancy in pathway sets

Ruth Stoney[1*], Jean-Marc Schwartz[2], David L Robertson[3,], Goran Nenadic[1]

[1]School of Computer Science, University of Manchester, M13 9PT, UK
[2]Faculty of Biology, Medicine and Health, University of Manchester, M13 9PT, UK
[3]MRC-University of Glasgow Centre for Virus Research, Garscube Campus, Glasgow, G61 1QH, UK.

Ruth Stoney: ruth.stoney@manchester.ac.uk
David L Robertson: David.L.Robertson@glasgow.ac.uk
Goran Nenadic: g.nenadic@machester.ac.uk
Jean-Marc-Schwartz: jean-marc.schwartz@manchester.ac.uk

This work has been supported by the Biotechnology and Biological Sciences Research Council DTP [BB/J014478/1].

* corresponding author

1. Abstract

1.01 **Background**

The consolidation of pathway databases, such as KEGG[1], Reactome[2]and ConsensusPathDB[3], has generated widespread biological interest, however the issue of pathway redundancy impedes the use of these consolidated datasets. Attempts to reduce this redundancy have focused on visualizing pathway overlap or merging pathways, but the resulting pathways may be of heterogeneous sizes and cover multiple biological functions. Efforts have also been made to deal with redundancy in pathway data by consolidating enriched pathways into a number of clusters or concepts. We present an alternative approach, which generates pathway subsets capable of covering all of genes presented within either pathway databases or enrichment results, generating substantial reductions in redundancy.

1.02 **Results**

We propose a method that uses set cover to reduce pathway redundancy, without merging pathways. The proposed approach considers three objectives: removal of pathway redundancy, controlling pathway size and coverage of the gene set. By applying set cover to the ConsensusPathDB dataset we were able to produce a reduced set of pathways, representing 100% of the genes in the original data set with 74% less redundancy, or 95% of the genes with 88% less redundancy. We also developed an algorithm to simplify enrichment data and applied it to a set of enriched osteoarthritis pathways, revealing that within the top ten pathways, five were redundant subsets of more enriched pathways. Applying set cover to the enrichment results removed these redundant pathways allowing more informative pathways to take their place.

1.03 **Conclusion**

Our method provides an alternative approach for handling pathway redundancy, while ensuring that the pathways are of homogeneous size and gene coverage is maximised. Pathways are not altered from their original form, allowing biological knowledge regarding the data set to be directly applicable. We demonstrate the ability of the algorithms to prioritise redundancy reduction, pathway size control or gene set coverage. The application of set cover to pathway enrichment results produces an optimised summary of the pathways that best represent the differentially regulated gene set.

Keywords

Set cover, data redundancy, pathways, gene enrichment analysis

2.   Background

Pathways are sets of genes corresponding to functionally related interacting proteins. Pathway data is available from many databases dependent on biological focus. The fragmented nature of pathways across multiple databases makes it difficult to perform inclusive analysis of all known data. To address this issue, many attempts have been made to consolidate pathway databases such as ConsensusPathDB (CPDB) [4], PathwayCommons [5], The Human Pathway Database (HPD) [6], Pathway Interaction Database (PID) [7], and NCBI Biosystems [8]. Amalgamating multiple databases into a consistent searchable format facilitates the use of these resources, however the arbitrary nature of pathway boundaries results in overlap and redundancy. This redundancy greatly increases the quantity and complexity of pathway data, which has lead to the development of a range of tools to assist in data simplification and interpretation [6, 7, 9–11]. Previous solutions presented to deal with redundancy include visualizing redundancy between pathways to the user [6], merging pathways based on similarity [10, 11] and even integrating full pathway sets into a non-redundant, single unified pathway [12]. Reducing redundancy simplifies the pathway-related descriptive space, allowing multiple resources to be combined while limiting the number of pathway attributes assigned to each gene. The advantages are apparent, with resources such as PathCards being integrated into the widely used GeneCards[11].

Redundancy Control in Pathway Databases (ReCiPa) [10] uses a pathway merging algorithm to combine pathways with high levels of overlap. Users select a maximum overlap threshold and pathway pairs displaying greater levels of overlap are merged. Within that study redundancy was observed within five large databases (KEGG, Biocarta, CGP, NCI-PID, and Reactome). They proceeded to merge pathways from the Molecular Signatures Database (MSigDB), whose overlap exceeded 75%, reducing pathway redundancy.

Pathcards described a multistep procedure to reduce pathway redundancy, also through pathway merging [11]. Two thresholds were calculated and sequential merging steps were used to minimize overlap, while preventing the generated super-pathways from becoming too large to be informative. By merging pathways into super-pathways, Pathcards suggested many new molecular interactions. They demonstrated that many of these newly generated interactions are supported by high numbers of literature co-mentions and high experimental interactions scores according to STRING. However, while the generation of potential interactions can be highly beneficial, if the aim is to utilize previously validated data, merging pathways introduces a source of uncertainly into the dataset.

 A major application of pathway data sets is pathway enrichment analysis. Both Pathcards and ReCiPa explored the capability of their reduced pathway dataset to

improve enrichment results. Enrichment analysis of 830 differential expression
sets was performed using the super-pathways generated within Pathcards. The
enrichment results from super-pathways tended to be more significant than the
enrichment scores of their constituent pathways. Similarly within the ReCiPa study
enrichment analysis was performed using genes differentially expressed in
obesity. After merging, the top 20 most significantly enriched pathways showed
less overlap and greater significance towards the disease, compared to the original
dataset.
92
Pathway Distiller implemented an alternative approach by removing redundancy
from enriched pathway sets following enrichment analysis [9]. Pathways may be
consolidated into pathway concepts based on gene expression profiles, gene
membership, protein-protein interaction data or shared Gene Ontology (GO)
terms. Each method provides varying, complementary views of the data, with
different pathway concepts generated. Consolidating enrichment output into a
reduced number of pathway concepts increases data manageability and
readability, by organizing redundant pathways into their major groups.
101
All of the approaches discussed to this point have used merging and consolidation
to address redundancy. Alexa et al. (2006) demonstrated that redundancy in GO
enrichment results could be reduced by selecting a subset of representative terms
[13]. Pathway enrichment analysis and GO enrichment analysis are similar
techniques in which sets of differentially expressed genes are compared to gene
sets associated with pathways or GO terms. Alexa et al. (2006) introduced two
algorithms, *elim* and *weight*, which use the Gene Ontology topology to select a
representative subset of highly enriched GO terms [13]. The enrichment set cover
algorithm presented in this paper shares some conceptual similarity with this
approach however, the implementation is different since there is no organized
topological hierarchy for combined pathway datasets and the rules governing the
Gene Ontology, such as the true path rule [14], do not apply.
114
Within this paper we show that set cover can be used to reducing redundancy by
selecting subsets of representative pathways. We describe a set of algorithms for
reducing redundancy in pathway datasets, as well as a separate algorithm for
reducing redundancy from pathway enrichment results. The proportional set
cover algorithm and hitting set cover algorithm aim to identify a minimum subset
of pathways required to cover the genes in highly redundant, consolidated
pathway databases. The generated set covers are not designed to depict the full
range of possible pathway boundaries and their accompanying cellular functions,
but rather they provide a simplified set of pathways to represent the actions of
genes within the dataset. Since the pathways are not merged database and
biological information remains directly applicable and functional specificity is not
lost through pathway size expansion. The proposed method also removes the risk
of biologically distinct pathways being merged. The algorithm's ability to remove
overlap is not limited by thresholds, conferring an advantage compared to
approaches such as Pathcards and ReCiPa in which redundancy between pathway

pairs can only be removed if the overlap exceeds the threshold. Set cover
algorithms also consider redundancy between multiple pathways, rather than just
comparing pathway pairs.
133

We also developed the enrichment set cover algorithm for handling pathway
enrichment data and applied it to a set of enriched osteoarthritis pathways [15]. In
contrast to the approaches used by ReCiPa and Pathcards, the enrichment set
cover algorithm is designed to be used following enrichment analysis, which
should be performed using the full pathway dataset. Redundancy is then removed
from the enriched pathway set by selecting the pathway with the lowest p-value to
cover each differentially regulated gene. Enriched pathways are not merged or
altered and the number of enriched pathways required to cover the dataset is
reduced. The resulting pathways set can therefore be used as an optimized
summary output, conveniently showing the most important pathways for
describing the differentially regulated gene set. By increasing the number of
differentially regulated genes covered by the most highly enriched pathways,
researchers examining the top 10 or 20 pathways are provided with a more
inclusive portrayal of the gene set.
148

149   3.   Approach

We downloaded pathway data from ConsensusPathDB (CPDB), an opensource
online collection of pathways, that incorporates 32 sources including KEGG,
Wikipathways, PDB, Reactome. CPDB makes these resources available as a single
download, which we acquired on 24/09/2015 containing 4,011 pathways. We
applied the set cover algorithm to the CPDB data set, analyzing it's effectiveness at:
reducing pathway overlap; reducing pathway size variability; and preserving the
maximum number of genes in the data set. We found that standard set cover
caused unacceptable increases in pathway size, therefore we modified the
algorithm and assessed the modified algorithms capability to meet the previous
three objectives.
160

Set cover is a well-defined algorithm in computer science for handling overlapping
sets of sets. For example, set cover is used by CLASS, a bioinformatics program that
maps RNA sequence data to transcripts [16]. Set cover has also been used to
predict protein-protein interactions based on binding domains [17], to reduce the
complexity of SNP sets [18] and to minimize the number of probes needed to
analyze DNA [19].
167

Set cover algorithms deal with elements and sets, which relate to genes and
pathways respectively. All the unique genes in the data set are collectively referred
to as the universe. The aim is to produce a reduced selection of sets (pathways),
which collectively cover all the elements (genes) in the universe (dataset). This

subset of the original data is called the cover set [20]. Each time a pathway is
added to the cover set the genes in the pathway become covered (Figure 1). Direct
application of set cover lead to extremely large, functionally non-specific pathways
dominating the cover set, therefore we implemented the proportional set cover
and hitting set cover algorithms to better control pathway size, while reducing
redundancy and covering the dataset.
178
When dealing with enrichment analysis data the aim is to reduce redundancy
between pathways, while preserving the order of enrichment significance denoted
by the p-values. We designed an algorithm that would select the set of pathways
with the lowest p-values capable of covering all the genes in the dataset. This
ensures that the filtered results return the most enriched pathways available for
each gene.
185

4.   Methods

4.01   **Overlap score**
To measure overlap across different algorithms we measured the mean number of
pathways that each gene appears in. Within the raw data genes appeared in a
mean of 12.4 pathways. We refer to this metric as the overlap score.

4.02   **Set cover**
We applied the set cover algorithm to the data set, which generates a subset of
pathways called a cover set, in which all the genes in the data set are represented
or "covered". Set cover begins by first assigning values to each pathway (v_i). The
set cover values correspond to the number of uncovered genes each pathway
contains (Equation 1).
197

$$v_i = \mid \boldsymbol{s_i} \cap \boldsymbol{R} \mid$$

198
199 where ($\boldsymbol{s_i}$) is the pathway's gene set and $\boldsymbol{R}$ is the set of all uncovered genes.
200
At the beginning of the algorithm all the genes in the dataset are uncovered so the
algorithm selects the largest pathway. The genes from the selected pathway are
then covered, so it is unnecessary to cover them again using additional pathways.
The algorithm then recalculates how many uncovered genes each pathway
contains and continues to add the pathway with the maximum value to the set
cover until all genes in the data set are covered.
207
208
209   *Algorithm 1 Set cover (in separate file)*

210   where R is the set of uncovered genes, U is all the genes in the dataset, C is the
211   covered genes, SC is the set cover result, GC is the gene coverage (see Section 4.03)
212   and s_i is a pathway.
213
214   Application of the set cover algorithm was effective in reducing overlap between
215   the pathways; however, it selected very large pathways with reduced
216   informativeness (maximum size 2320, standard deviation 160, almost double the
217   standard deviation on the original dataset 86.9). We therefore explored methods
218   that avoid preferential selection of large pathways.
219

4.03   Gene Set Coverage
As the set cover algorithm approaches completion and the final sets are added to
the cover set, increases in data coverage are gained at the expense of redundancy
reduction. This is because the final sets required to cover the few remaining genes
tend to have the most overlap with other pathways already in the set cover. In
addition, fewer pathways are available to cover the final few genes, restricting
options to control pathway size. To allow a user-defined compromise between the
gene coverage, pathway redundancy and pathway size we introduce the Gene
Coverage (GC) parameter. Setting GC below 100% allows the algorithm to finish
before the final elements have been covered. We experimented setting GC to 90,
95, 99 and 100% of the number of genes in the data set.
231

232   ### 4.04   Proportional set cover
233   When reducing pathway redundancy there are three competing aims: reducing
234   redundancy; controlling pathway size; and covering the entire gene set. The
235   proportional set cover algorithm was generated to focus on controlling pathway
236   size.
237
To control the size of the pathways we altered the scoring mechanism to rank
pathways based on the proportion of uncovered genes they contained, rather than
the absolute number (Equation 2). This works because larger pathways are more
likely to have a proportion of their genes covered when other pathways are
selected. Additionally this mechanism directly penalizes overlap, which the
standard algorithm does not. At the beginning of the proportional set cover
algorithm none of the genes are covered so the proportion of uncovered genes in
every pathway is 1. This would result in the starting pathway being selected at
random. To ensure that pathway size variability is controlled as strictly as
possible, we implemented the second part of Equation 2, which ensures that
pathways of mean pathway size are preferentially selected when multiple
pathways with the same proportion of uncovered genes are available.
250

$$v_i = \frac{|\, s_i \cap R \,|}{|s_i|} + \frac{1}{abs\left(|s_i| - \overline{|s_i|}\right) * k}$$

where s_i is the pathway's gene set, $\overline{|s_i|}$ is the mean pathway length, R is the

uncovered genes set and k is a large constant to limit the influence of the second

term (taken equal to 10,000).

4.05 Hitting set cover

The set-covering problem can be reformulated into the equivalent set-hitting

problem. In this formulation genes and pathways are visualized as bi-partite graph

in which the pathways are connected to the genes that they contain. In this

depiction it is clear that some genes are only linked to a single pathway, which

must be selected if the gene is to be covered. The importance of pathways can

therefore be considered as a factor of how infrequent their genes are. The hitting

set cover is therefore designed to reduce redundancy as much as possible without

directly selecting for pathway size.

We calculated the frequency of each gene in the data set (F), then assigned the

gene's value $gv(j)$ as $1/F$. We then assigned a value v_i to each pathway defined as

the sum of each uncovered gene's scores divided by the number of genes in the

pathway (Equation 3).

$$gv(j) = 1\,/F(j)$$
$$v_i = \frac{\sum_{j \epsilon s_i \cap R} gv(j)}{|\, s_i \,|}$$

where $gv(j)$ is the value of a gene, $F(j)$ is the number of pathways a gene is in,

$\ \ j\epsilon s_i \cap R$ means for each uncovered gene in the pathway and $|s_i|$ is the length of

$\ \ $ the pathway.

4.06 Set cover for pathway enrichment analysis

Pathway analysis is a frequently used method; therefore a modified set cover

algorithm to address this situation could be highly useful. The universe represents

differentially expressed genes and the sets are enriched pathways generated

through enrichment analysis. Enrichment analysis results represent entirely

different input data compared to the pathway datasets used in the previous

algorithms, as the enriched pathways already have scores (p-values). We wish to

reduce redundancy (gene overlap) between enriched pathways and it is essential

that the pathways with the lowest possible p-values are selected. Equation 4

allows the pathways with the lowest p-values to be selected, unless all of their

genes are covered by other enriched pathways with even lower p-values.

$$s_i \cap \boldsymbol{R} \ = \ \theta \rightarrow b = \ 0, \qquad s_i \cap \boldsymbol{R} \ \neq \ \theta \rightarrow b = \ 1$$
$$v_i = (1 - pvalue_i) * b$$

289 where s_i is the enriched pathway's gene set, $\boldsymbol{R}$ is the uncovered gene set, b is a
290 binomial operator, $pvalue_i$ is the pathway's p-value and v_i is the pathway's set
291 cover value.

292 We generated the enriched data set by applying GOseq [21] to expression data
293 from the damaged cartilage in osteoarthritis patients and controls [15].

5. Results

296 We started with the large, extensively redundant CPDB data set and used set cover
297 to reduce pathway overlap, while controlling pathway size and seeking to cover as
298 much of the data set as possible. We describe the ability of the standard set cover
299 algorithm and two modified algorithms, in conjunction with the GC parameter, to
300 meet these objectives.
301

5.01 Pathway redundancy varies between different algorithms
The original pathway data set contained 11,196 genes and 3,305 pathways; the
starting overlap score (see methods) was 12.4. The standard set cover algorithm
reduced overall redundancy from 12.4 to 4.1, a 73% reduction (since a completely
discrete pathway set would have a score of 1). The overlap score for proportional
set cover was 4.36, slightly higher than the standard set cover algorithm, but still
representing a 70% reduction in overlap from the original data. The hitting set
cover algorithm was designed to select pathways that contained rare genes within
the data set, resulting in the greatest reduction in overlap (overlap score of 3.95
equivalent to a 74% reduction).
312

After application of the set cover algorithms the distribution of the remaining
overlap between pathways varied greatly. Figure 2 shows the Jaccard similarity
between pairs of pathways, in the outputs produced by each of the three
algorithms. The standard set cover algorithm produced the lowest maximum
overlap (Jaccard similarity = 0.68) between the pathway pairs. However, compared
to the original data, a higher proportion of pathway pairs in the set cover output
showed Jaccard similarities between 10-30%. Proportional set cover had the
greatest maximum Jaccard similarity at 0.93, out of the set cover algorithms. The
hitting set cover algorithm produced a maximum Jaccard similarity between two
pathways of 0.82, despite having the lowest overlap score.
323

    Gene Coverage can be lowered to reduce redundancy
For each of the algorithms it is possible to use the GC parameter to prioritize
reductions in redundancy over gene coverage by stopping any algorithm before all
of the genes in the dataset have been covered. Figure 3 shows improved ability of
the set cover algorithms to reduce pathway overlap for different values of GC. If
99% of the genes are required then the hitting set algorithm achieves the lowest
overlap score of 3.24, equivalent to an 80% reduction in overlap. Redundancy can
be further reduced if only 95% of the genes are covered, with the proportional and
hitting set algorithms producing an overlap score of 2.41, equivalent to a 88%
reduction in redundancy. Both the proportional set cover and the hitting set cover
are more effective at reducing redundancy than the standard set cover if GC is set
to less than 100%.
336

Pathway size is affected by the set cover algorithm and Gene Coverage
setting
When GC was set to 100% the standard set cover algorithm represented all of the
genes in the dataset using only 524 pathways (16% of the original pathway set).
However, many of these were very large increasing the mean size to 87.2
(standard deviation 160.1). These pathways have reduced informativeness since
functional specificity is lost. Figure 4A illustrates the tendency of this algorithm to
select extremely large pathways.
345

The proportional set cover algorithm was designed to preferentially select
moderately sized pathways. This returned a cover set of 1,336 pathways with
controlled size variation (mean of 36.5, standard deviation 55.1) shown in Figure
4A. The hitting set cover algorithm was less able to control pathway size than the
proportional set cover algorithm, returning 957 pathways with a mean size of 46.2
(standard deviation 61.7).
352

Figures 4B – D show that as GC is reduced the tendency of the standard set cover to
select very large pathways becomes more exaggerated. Decreasing GC also
improves the ability of the proportional set cover algorithm to select moderately
sized pathways. The hitting set algorithm also tends to select smaller pathways
when GC is reduced, since larger pathways often contain more frequent genes.
Reducing GC affects pathway size since in the later stages of the algorithm, fewer
pathways are available to cover the remaining genes, reducing the available
options. Therefore, lowering GC has the ability to help control pathway size when
the proportional set cover and hitting set cover algorithms are used.
362

Since the databases that contribute to CPDB contain pathways of different sizes, the set cover generated may
preferentially select pathways from some databases more than others.

Table 1 shows the proportion of pathways that come from each database in the
cover set generated by each algorithm. All algorithms generate set covers with
reduced INOH and SMPDB pathways, showing that SMPBD's focus on small
molecules and INOH's ontology-based approach tend to be ill-suited to the
generation of discrete pathway protein sets. The standard set cover algorithm
generates sets containing large pathways, preferentially selecting pathways from
KEGG (median size 65, see Table 1) and Netpath (median size 51); while
proportional set cover tends to select smaller pathways from Reactome (median
size 17), HumanCyc (median size 5) and Signalink (median size 32), whilst
avoiding NetPath.
375

Table 1. Proportion of pathways from CPDB databases. Median size represents the
median sizes of the pathways in the CPDB dataset. CPDB % represents the proportion
of the pathways in the unaltered dataset that came from each database. The
following columns represent the proportion of pathways in the set cover generated
by the standard set cover algorithm, the hitting set cover algorithm and the
proportional set cover algorithm. Different results are obtained by altering the
proportion of the gene set covered, shown in subcolumns below the algorithm header.

	Median size	CPDB %	Standard set cover				Hitting set cover		
			100%	99%	95%	90%	100%	99%	95%
BioCarta	15.0	6.3	6.3	4.6	0.5	0.0	4.7	4.8	5.4
EHMN	32.5	1.6	3.2	3.4	2.6	1.0	2.1	2.3	1.8
HumanCyc	5.0	8.2	6.5	7.7	2.6	0.0	10.1	10.9	12.9
INOH	34.5	2.3	1.7	1.9	1.0	1.0	0.8	0.6	0.3
KEGG	65.0	7.2	29.0	30.5	37.6	40.4	15.8	15.0	13.5
NetPath	51.0	0.9	2.1	2.4	3.6	5.1	1.1	1.2	1.1
PharmGKB	13.0	2.8	3.1	2.9	0.5	0.0	2.0	2.1	2.4
PID	35.0	5.2	15.6	13.9	10.3	6.1	9.5	9.8	9.4
Reactome	17.0	39.6	4.2	5.3	10.8	21.2	36.1	35.1	34.7
Signalink	32.0	0.4	1.0	1.2	1.0	0.0	0.6	0.7	0.7
SMPDB	11.0	16.7	1.7	1.4	0.5	0.0	1.6	1.5	1.4
Wikipathways	26.0	8.8	25.6	24.9	28.9	25.3	15.6	16.0	16.2

Reducing redundancy in pathway enrichment analysis
To demonstrate the ability of the set cover algorithm to handle enrichment data,
we applied the enrichment set cover algorithm to an osteoarthritis data set,
retrieved from Dunn et al. (2016) [15]. From the osteoarthritis data set, 58.3% of
the differentially expressed genes could be mapped to a CPDB pathway, which was

a 17% improvement on the GOseq [21] implemented data set. We retrieved 42
enriched pathways with a p-value lower than 0.05, following the Benjamini-
Hochberg correction for multiple testing. Set cover for enrichment analysis
reduced the number of pathways required to cover the differentially expressed
genes to 23 (supplementary table 1).
395
The heat map in Figure 5A shows the asymmetric overlap between the top ten
pathways before application of the algorithm. The p-values from pathway
enrichment determine the order in which pathways were considered for inclusion
in the cover set. Pathways were omitted if all of the differentially expressed genes
that they covered were also covered by more enriched pathways. Note that overlap
tends to be higher in the bottom left triangle as pathways added later were often
smaller subcomponents of larger pathways. We can see that 'extracellular matrix
organization', the most enriched pathway, was placed in the cover set first. Next
was 'collagen biosynthesis and modifying enzymes'; however, all of the
differentially expressed genes in this pathway are also covered by the larger
pathway 'extracellular matrix organization', as indicated by the red cell in the
'collagen biosynthesis and modifying enzymes' row, 'extracellular matrix
organization' column. The corresponding cell in the 'extracellular matrix
organization' row reveals that 24% of the differentially expressed genes in
'extracellular matrix organization' are also in 'collagen biosynthesis and modifying
enzymes'.
412
Figure 5B shows overlap between the top ten pathways after application of the
enrichment set cover algorithm. Because the differentially expressed genes
covered by the 'collagen biosynthesis and modifying enzymes' pathway are a
subset of those covered by the 'extracellular matrix organization' pathway, the
'collagen biosynthesis and modifying enzymes' pathway is removed from the cover
set (Figure 5B). The second pathway in this list therefore becomes 'GPCR signaling
g alpha q'. The 'collagen formation' and 'class b 2 secretin family receptors'
pathways are also removed because the differentially expressed genes they cover
are additionally covered by the more enriched pathways 'extracellular matrix
organization' and 'signal transduction' pathways (respectively). Additionally,
'GPCR signaling pertussis toxin' and 'GPCR signaling cholera toxin' are absent from
the returned list, as all of their differentially expressed genes are found in 'GPCR
signaling g alpha q' or 'signal transduction'.
426
Some pathways in the enrichment set cover do still show high levels of overlap, for
example 'wnt signalling network' is included despite 89% of its differentially
expressed genes being covered by 'signal transduction'. This is acceptable because
'signal transduction' is more highly enriched than 'wnt signalling network', yet the
'wnt signalling network' is worth including as it contains three differentially
expressed genes that are not in 'signal transduction'. If 'wnt signalling network'

had been excluded then these genes would not have been described by the most
significant pathway available to represent them. The unmodified top ten enriched
pathways only cover 78.0% of the enriched genes. Using the set cover enrichment
algorithm increases this figure to 85.2% without disrupting the pathway order
given by the enrichment p-values.
438

6. Discussion and conclusion

We described algorithms suitable for reducing overlap in large pathway data sets
allowing multiple databases to be amalgamated without excessive redundancy
impeding the usefulness of the resource. Standard set cover is the best algorithm
to reduce the number of pathways required to cover the data set, but significantly
increases pathway size, which can be controlled by proportional set cover or
hitting set cover. The proportional set cover is the best algorithm for controlling
pathway size and the hitting set cover is the preferred choice for covering all of the
genes in the dataset with minimal pathway redundancy. We showed that reducing
the GC parameter allows further reductions in pathway redundancy; for example, if
only 95% of the genes in the CPDB dataset were covered redundancy can be
reduced by up to 88%. In addition reducing GC increases pathway size control
when the proportional set cover and hitting set cover algorithms are used.
452

For pathway enrichment analysis we aimed to reduce redundancy while selecting
the most significantly enriched pathways based on p-values. As an application we
used the modified set cover algorithm to reduce the results of enrichment analysis
from a large osteoarthritis data set. We found that 5 out of the 10 top ranking
pathways could be omitted as they were subsets of more highly enriched
pathways. Overlap between pathways returned from enrichment data is not
always immediately obvious and requires further consideration. By reducing this
redundancy, data interpretation is made more intuitive. Reducing redundancy also
allows the user to explore substantially more of the data set using the same
number of pathways.
463

The enrichment set cover algorithm presented within this study differs from
existing methods implemented by ReCiPa and Pathcards, since enrichment
analysis is performed prior to reduction of redundancy. This is because the
different sets of pathway boundaries available in the full dataset may optimally fit
the differentially expressed genes. For example, comparison of the 'apoptosis'
taken from KEGG, Reactome and Wikipathways, reveals that many of the proteins
are specific to a single database [22]. This is due to the vague definition of pathway
boundaries, as well as differing experimental focus on cellular contexts, such as
tissues or disease states. Following enrichment analysis the pathways that are
most significantly enriched are selected to represent the differentially expressed

genes and superfluous pathways are removed. This prevents the top results from
being dominated by large numbers of highly similar pathways.
476
Set cover uses greedy heuristic methods, which provide good approximations of
the optimal solution in a time effective manner. These methods are extremely
efficient and can be run in a matter of minutes, however it should be noted that
they do not guarantee an optimal solution. This is particularly true for the
proportional set cover algorithm where the randomness of early selections
influences the result. However, all possible outcomes result in reduced
redundancy. The enrichment set cover algorithm is exempt from these
considerations unless multiple pathways have identical p-values.
485
486 We have provided a method to dramatically reduce redundancy in pathways
487 facilitating a more concise portrayal of cellular processes, while avoiding the issues
488 introduced by pathway merging. Our algorithms are publicly available and have
489 wide applicability to analysis of pathway datasets from any organism.
490

491 7.   List of abbreviations
492 CPDB   Consensus PathwayDB
493 GC   Gene cover
494 SNP   Single nucleotide polymorphism
495

496 8.   Declarations

Ethics approval and consent to participate NA
Consent for publication NA
Availability of data and materials: https://github.com/RuthStoney/set-cover-and-
set-packing-to-reduce-redundancy-in-pathway-data
Competing interests: The authors declare that they have no competing interests
Funding: This work has been supported by the Biotechnology and Biological
Sciences Research Council DTP [BB/J014478/1].
Author contributions: All authors contributed to the design of the study. R.S.
performed the analysis and wrote the manuscript. All authors edited the
manuscript and approved its final version.
507
508 Acknowledgements: We would like to thank Jamie Soul and Sara Dunn from the
509 University of Manchester, for providing the osteoarthritis data.
510

511 9.   References

1. Kanehisa M, Goto S. KEGG: kyoto encyclopedia of genes and genomes. Nucleic
Acids Res. 2000;28:27–30.

http://www.pubmedcentral.nih.gov/articlerender.fcgi?artid=102409&tool=pmce
ntrez&rendertype=abstract.
2. Fabregat A, Sidiropoulos K, Garapati P, Gillespie M, Hausmann K, Haw R, et al.
The reactome pathway knowledgebase. Nucleic Acids Res. 2016;44:D481–7.
3. Kamburov A, Pentchev K, Galicka H, Wierling C, Lehrach H, Herwig R.
ConsensusPathDB : toward a more complete picture of cell biology. 2011;39
November 2010:712–7.
4. Kamburov A, Wierling C, Lehrach H, Herwig R. ConsensusPathDB--a database for
integrating human functional interaction networks. Nucleic Acids Res. 2009;37
Database issue:D623-8. doi:10.1093/nar/gkn698.
5. Cerami EG, Gross BE, Demir E, Rodchenkov I. Pathway Commons , a web
resource for biological pathway data. 2011;39 November 2010:685–90.
6. Chowbina SR, Wu X, Zhang F, Li PM, Pandey R, Kasamsetty HN, et al. HPD: an
online integrated human pathway database enabling systems biology studies. BMC
Bioinformatics. 2009;14 Suppl 11:S5. doi:10.1186/1471-2105-10-S11-S5.
7. Schaefer CF, Anthony K, Krupa S, Buchoff J, Day M, Hannay T, et al. PID: The
pathway interaction database. Nucleic Acids Res. 2009;37 SUPPL. 1:674–9.
8. Geer LY, Marchler-Bauer A, Geer RC, Han L, He J, He S, et al. The NCBI BioSystems
database. Nucleic Acids Res. 2009;38 SUPPL.1:492–6.
9. Doderer MS, Anguiano Z, Suresh U, Dashnamoorthy R, Bishop AJR, Chen Y.
Pathway Distiller - multisource biological pathway consolidation. BMC Genomics.
2012;13 Suppl 6 Suppl 6:S18. doi:10.1186/1471-2164-13-S6-S18.
10. Vivar JC, Pemu P, McPherson R, Ghosh S. Redundancy control in pathway
databases (ReCiPa): an application for improving gene-set enrichment analysis in
Omics studies and "Big data" biology. Omics. 2013;17:414–22.
doi:10.1089/omi.2012.0083.
11. Belinky F, Nativ N, Stelzer G, Zimmerman S, Iny Stein T, Safran M, et al.
PathCards: multi-source consolidation of human biological pathways. Database.
2015;2015:bav006-bav006. doi:10.1093/database/bav006.
12. Yu N, Seo J, Rho K, Jang Y, Park J, Kim WK, et al. hiPathDB: A human-integrated
pathway database with facile visualization. Nucleic Acids Res. 2012;40:797–802.
13. Alexa A, Rahnenführer J, Lengauer T. Improved scoring of functional groups
from gene expression data by decorrelating GO graph structure. Bioinformatics.
2006;22:1600–7.
14. Camon E, Magrane M, Barrell D, Lee V, Dimmer E, Maslen J, et al. The Gene
Ontology Annotation (GOA) Database: sharing knowledge in Uniprot with Gene
Ontology. Nucleic Acids Res. 2004;32:D262–6.
15. Dunn SL, Soul J, Anand S, Schwartz JM, Boot-Handford RP, Hardingham TE.
Gene expression changes in damaged osteoarthritic cartilage identify a signature
of non-chondrogenic and mechanical responses. Osteoarthr Cartil. 2016;24:1431–
40. doi:10.1016/j.joca.2016.03.007.
16. Song L, Florea L. CLASS: constrained transcript assembly of RNA-seq reads.
BMC Bioinformatics. 2013;14 Suppl 5 Suppl 5:S14. doi:10.1186/1471-2105-14-S5-
S14.
17. Huang C, Morcos F, Kanaan SP, Wuchty S, Chen DZ. Predicting Protein-Protein
Interactions from Protein Domains Using a Set Cover Approach. Quality.
2007;4:78–87.
18. Ao SI, Yip K, Ng M, Cheung D, Fong PY, Melhado I, et al. CLUSTAG: Hierarchical
clustering and graph methods for selecting tag SNPs. Bioinformatics.

2005;21:1735–6.
19. Borneman J, Chrobak M, Della Vedova G, Figueroa a, Jiang T. Probe selection
algorithms with applications in the analysis of microbial communities.
Bioinformatics. 2001;17 Suppl 1:S39-48.
http://www.ncbi.nlm.nih.gov/pubmed/11472991.
20. Kordalewski D. New Greedy Heuristics For Set Cover and Set Packing. 2013;
April:49. http://arxiv.org/abs/1305.3584.
21. Young MD, Wakefield MJ, Smyth GK, Oshlack A. Gene ontology analysis for
RNA-seq: accounting for selection bias. Genome Biol. 2010;11:R14.
doi:10.1186/gb-2010-11-2-r14.
22. Herwig R, Hardt C, Lienhard M, Herwig R, Hardt C, Lienhard M, et al. Analyzing
and interpreting genome data at the network level with ConsensusPathDB
Analyzing and interpreting genome data at the network level with
ConsensusPathDB. 2016; October.
577
578

10.   Figure legends

Figure 1. Set cover A) A simple set of overlapping sets. B) The red set with 8
uncovered elements is selected first. C) The blue set with 3 elements is selected
second. D) The orange set then covers all the elements in the universe.

Figure 2. Jaccard coefficient between pathway pairs in the cover set results produced
by each algorithm.

586
587 *Figure 3. Redundancy in set cover outputs given different GC values.*

588
589 *Figure 4. Pathway sizes in cover set when GC is set to A) 100%, B) 99%, C) 95% and*
590 *D) 90%. The boxes indicate the 25th and 75th percentiles and the whiskers indicate*
591 *the 5th and 95th percentiles.*

592
Figure 5. Pathway redundancy heat maps. (A) Pathway overlap for top ten enriched
pathways. (B) Pathway overlap for top ten enriched pathways after application of set
cover. The values represent asymmetric overlap, i.e. for each pathway shown on the
left axis, values represent the proportion of genes that are also included in the
pathway shown on the bottom axis.

11.   Additional material

Supplementary table 1: Enriched pathways from the osteoarthritis dataset (p-
value<0.05). The set cover column indicated the 23 pathways that were included
in the set cover. Found in additional file 1.docx.

603
604

Set cover

A

B

Set Cover

Start with $\mathbf{R} = \mathbf{U}$, $\mathbf{C} = \emptyset$ and $\mathbf{SC} = \emptyset$

while $|\boldsymbol{C}|/|\boldsymbol{U}| * 100 < GC$ **do**

    Select set $\boldsymbol{s_i}$ that maximizes $\boldsymbol{v_i}$

    Add $\boldsymbol{s_i}$ to $\boldsymbol{SC}$

    Add the elements in $\boldsymbol{s_i}$ to $\boldsymbol{C}$

    Delete the elements in $\boldsymbol{s_i}$ from $\boldsymbol{R}$

end

Return $\boldsymbol{SC}$