OUTRIDER: A statistical method for detecting aberrantly expressed genes in RNA sequencing data

Felix Brechtmann,[1,5] Agnė Matusevičiūtė,[1,5] Christian Mertes,[1,5] Vicente A Yépez,[1,2,3] Žiga Avsec,[1,2] Maximilian Herzog,[1] Daniel M Bader,[1,6] Holger Prokisch,[3,4] Julien Gagneur[1,2,*]

[1]Department of Informatics, Technical University Munich, Boltzmannstr. 3, 85748 Garching, Germany

[2]Quantitative Biosciences Munich, Gene Center, Department of Biochemistry, Ludwig-Maximilians Universität München, Feodor-Lynen-Strasse 25, 81377 München, Germany

[3]Institute of Human Genetics, Helmholtz Zentrum München, Ingolstädter Landstr. 1, 85764 Neuherberg, Germany

[4]Institute of Human Genetics, Klinikum rechts der Isar, Technical University Munich, 13 Ismaninger Str. 22, 81675 München, Germany

[5]These authors contributed equally to this work

[6]Present address: Evotec (München) GmbH, Am Klopferspitz 19a, 82152 Martinsried, Germany

*Correspondence: gagneur@in.tum.de

Abstract

RNA sequencing (RNA-seq) is gaining popularity as a complementary assay to genome sequencing for precisely identifying the molecular causes of rare disorders. An obvious and powerful approach is to identify aberrant gene expression levels as potential pathogenic events. However, existing methods for detecting aberrant read counts in RNA-seq data either lack

assessments of statistical significance, so that establishing cutoffs is arbitrary, or they rely on subjective manual corrections for confounders. Here, we describe OUTRIDER (OUTlier in RNA-seq fInDER), an algorithm developed to address these issues. The algorithm uses an autoencoder to model read count expectations according to the co-variation among genes resulting from technical, environmental, or common genetic variations. Given these expectations, the RNA-seq read counts are assumed to follow a negative binomial distribution with a gene-specific dispersion. Outliers are then identified as read counts that significantly deviate from this distribution. The model is automatically fitted to achieve the best correction of artificially corrupted data. Precision–recall analyses using simulated outlier read counts demonstrated the importance of correction for co-variation and of significance-based thresholds. OUTRIDER is open source and includes functions for filtering out genes not expressed in a data set, for identifying outlier samples with too many aberrantly expressed genes, and for the *P*-value-based detection of aberrant gene expression, with false discovery rate adjustment. Overall, OUTRIDER provides a computationally fast and scalable end-to-end solution for identifying aberrantly expressed genes, suitable for use by rare disease diagnostics platforms.

Introduction

Many patients suspected to suffer a Mendelian disorder undergo whole exome or whole genome sequencing. Nonetheless, in most cases no clear pathogenic variant can be pinpointed[1,2]. A possible reason is that the pathogenic variant is regulatory. However, precisely identifying pathogenic regulatory variants is difficult for at least two reasons. First, an individual harbors a very large number of rare non-coding variants, with about 60,000 non-coding single nucleotide variants compared with 475 protein-affecting rare variants per genome (with MAF < 0.005)[3]; and second, our understanding of regulatory sequences is much poorer than our

understanding of coding sequences, so the prioritization of regulatory sequences can be
difficult.

Two recent studies have shown that using RNA sequencing (RNA-seq) to directly investigate
gene expression defects in patients' cells provides a promising complementary method for
pinpointing pathogenic regulatory defects[4,5]. RNA-seq can help to reveal splicing defects, the
mono-allelic expression of heterozygous loss-of-function variants, and expression outliers (i.e.
genes aberrantly expressed outside their physiological range)[4,5]. The two studies used different
approaches to identify expression outliers. Cummings *et al.*[4] computed Z-scores on the
logarithm of gene-length normalized read counts by subtracting the mean count and dividing by
the standard deviation. Expression outliers were identified as read counts with an absolute Z-
score greater than 3. No test of statistical significance was performed. This expression outlier
analysis did not yield any convincing candidates. In contrast, the study by Kremer *et al.*[5]
identified 4 out of 6 newly diagnosed individuals as expression outliers. Read count outliers
were identified as those with an absolute Z-score greater than 3 and further being statistical
significant according to DESeq2, a statistical test originally developed for differential expression
analyses[6], which was applied by testing each sample in turn against the rest of the cohort.
DESeq2 is based on the negative binomial distribution, which can be used to model
overdispersed count data[7]. The application of a statistical test, appropriate for count data, may
be one reason for the difference in success rates between the studies. However, the reason for
the difference remains unclear because of the relatively small number of diagnosed cases, the
absence of ground truth, and the lack of a direct comparison between the two approaches
based on the same data.

The two studies did not only differ in whether or not a statistical test was applied but also
differed in the way the data was corrected for confounders. Cummings *et al.*[4] used RPKM

(reads per kilobase per million mapped reads) expression values. These control for variations in

sequencing depth but not for other sources of co-variation among the read counts. Controlling

for further sources of co-variation is important because the identification of a gene as aberrantly

expressed depends on the context, for example the sex of the donor. Genes encoded on the Y

chromosome are not present, and thus not expressed, in women. However, in men, loss of the

expression of a Y chromosome-encoded gene can be an aberrant expression event. Hence, not

taking the sex of the donor into account would not allow for the detection of aberrantly silenced

Y chromosome-encoded genes in males. While the sex of the donor is usually available and can

be controlled for, other contexts for gene expression, such as the exact tissue of origin of the

sample, the sample's cell type composition, the genetic background, and technical biases, may

not be known *a priori*, yet causing similar but less intuitive variations. Kremer *et al*.[5] corrected

expression levels for sex, biopsy site as inferred from the *HOX* gene set, and common technical

sources of variation, which were identified by visual inspection of a hierarchical clustering of the

samples. In a study that identified expression outliers, although not for the diagnosis of rare

diseases, Li *et al*.[8] corrected for sex and the top three genotype principal components, as well

as for hidden confounding effects estimated using the probabilistic estimation of expression

residuals (PEER) method[9]. However, the algorithms controlling for co-variations in RNA-seq

read count data used in the studies of Li *et al*.[8] and Kremer *et al*.[5] were not assessed or tuned to

detect aberrantly expressed genes.

Here, we introduce OUTRIDER (OUTlier in RNA-seq fInDER), an algorithm that provides a

statistical test for outlier detection in RNA-seq samples while controlling for co-variations among

the gene read counts. Its parameters are optimized automatically for correcting read counts

corrupted *in silico*. The modeling of co-variation is performed by an autoencoder that controls for

read count variations caused by factors not known *a priori*. Autoencoders were introduced to

find low-dimensional representations of high-dimensional data through a hidden layer[10–12]. They

have been shown to be useful for extracting meaningful biological features from RNA-seq

data[13]. A subclass of autoencoders, the so-called denoising autoencoders, are used to

reconstruct corrupted high-dimensional data through exploiting correlations in the data[14]. In

OUTRIDER, the autoencoder approach is used to correct for the common co-variation patterns

among genes. In this article we describe the OUTRIDER algorithm, its implementation, as well

as its performance and results on two data sets.

Material and Methods

Data sets

The read counts for the rare disease cohort were downloaded from Supplementary Data 1

published as part of the study by Kremer *et al*.[5]

(https://www.nature.com/articles/ncomms15824). GTEx read counts were obtained from the

GTEx Portal (V6p counted with RNA-SeQCv1.1.8, https://www.gtexportal.org/home/datasets)[15].

We considered all the expressed genes in each data set. Read counts for the Kremer *et al*. data

set were computed according to the UCSC annotation build hg19[16], considering the full gene

body. In contrast, GTEx is based on the Gencode v19 annotation[17], and the read count of a

gene is defined as the number of paired-end read pairs overlapping exons of that gene only.

FPKM (fragments per kilobase per millions of reads) values were obtained using DESeq2[6],

where the gene length was defined as the aggregated length of all the exons. We then filtered

for genes for which at least 5% of the samples had a FPKM value greater than 1 (Figure S1A

and B). We further filtered out samples with a sequencing depth less than the mean sequencing

depth minus three standard deviations (Figure S1C and D).

Statistical model

We assume that the read count k_{ij} of gene $j = 1, ..., p$ in sample $i = 1, ..., n$ follows a negative binomial (NB) distribution[18,19], with gene-specific dispersion parameter θ_j, and mean μ_{ij} equal to the product of a control factor c_{ij} and a gene-wise adjustment factor a_j:

$$P(k_{ij}) = \text{NB}(k_{ij} | \mu_{ij} = a_j \cdot c_{ij}, \theta_j). \tag{1}$$

Both c_{ij} and a_j are required to be >0.01 during fitting because the NB distribution is not defined for $\mu \leq 0$. The correction factor c_{ij} is the product of the sample-specific size factor s_i, and the exponential of the sum of the co-variation factor y_{ij} and the mean log read count per gene $\bar{x}_j = \text{mean}_i \left(\log \left(\frac{k_{ij}+1}{s_i} \right) \right)$:

$$c_{ij} = s_i \cdot \exp(y_{ij} + \bar{x}_j) \tag{2}$$

The size factors s_i capture variations within the sequencing depth; they are robustly estimated as the median of the ratios of the gene read counts to their geometric means[18]. The co-variation factors y_{ij} capture co-variations across genes; they are modeled using an autoencoder of encoding dimension $q < p$. Specifically,

128
$$\mathbf{y}_i = \mathbf{h}_i \cdot \mathbf{W}^T + \mathbf{b} \qquad (3)$$

129
$$\mathbf{h}_i = \mathbf{x}_i \cdot \mathbf{W}, \qquad (4)$$

130 where the $p \times q$ matrix $\mathbf{W}$ is the encoding matrix and its transpose the decoding matrix, the q-

131 vector $\mathbf{h}_i$ is the encoded representation and the p-vector $\mathbf{b}$ a bias term. The input to the

132 autoencoder, $\mathbf{x}_i$, is a vector of the log counts divided by the size factors centered on the gene

133 mean:

134
$$x_{ij} = \log\left(\frac{k_{ij}+1}{s_i}\right) - \bar{x}_j, \qquad (5)$$

135 where we add one to prevent computing the logarithm of zero. In the following, we call the

136 combination of Equations (2 - 5) the autoencoder, or short: $c_{ij} = \mathrm{AE}(k_{ij})$.

Fitting the autoencoder parameters

To fit the autoencoder, we set the adjustment factors a_j to 1 because the goal of the

autoencoder is to model as much as possible of the read count co-variation. We found that joint

estimations of the dispersion parameter and the autoencoder led to poor results, possibly

because one compensated for the other one. We therefore set the initial dispersion parameters

for all the genes to a common value ($\theta = 25$) that is arbitrary yet realistic. This value

corresponds to a coefficient of variation for large read count expectations of 20%. The

coefficient is also known as the biological coefficient of variation[19]. A biological coefficient of

variation of 20% is typically seen for RNA-seq data sets of human cell lines with identical

genetic background[20].

For a given encoding dimension q, adjustment factors a_j, and dispersion parameters θ_j, the

parameters of the autoencoder **W** and **b** are fitted by maximizing the likelihood (Equation 1)

using the L-BFGS algorithm[21] as provided by the R optimization function *optim()*. A detailed

derivation of the gradient is given in the supplemental methods.

Fitting the encoding dimension

The optimal encoding dimension is obtained by assessing the autoencoder's performance in

correcting corrupted data. We artificially introduce corrupted read counts randomly with a

probability of 10^{-2} by shifting the true read counts 2 standard deviations on a log scale

randomly up or down. The introduced values are rounded to the nearest integer.

With C denoting the set of index pairs of corrupted read counts, and $\tilde{\mathbf{k}}_i$ the vector of read counts

for sample *i* after the injection of the corrupted read counts, an evaluation function was defined

as:

159
$$\text{evaluation} = -\frac{1}{|C|}\sum_{(i,j)\in C}\log\left(\text{NB}\left(k_{ij}\middle|\mu_{ij} = a_j \cdot \text{AE}(\tilde{\mathbf{k}}_i), \theta\right)\right) \tag{6}$$

The optimal encoding dimension for this evaluation function can be selected from the integer

range [1;100] by computing the loss for each value for a given $\theta = 25$.

Estimation of the dispersion and adjustment parameters

Once the autoencoder and thus the control factors c_{ij} is fitted, the adjustment a_j and dispersion

θ_j are obtained by maximizing the log-likelihood of Equation (1). To estimate the parameters,

the negative log-likelihood is minimized for each gene independently using BFGS optimization,

as implemented in the *optim()* function of R[22–25]. Initial values are estimated as $\hat{a}_j = \frac{1}{p}\sum\frac{k_{ij}}{c_{ij}}$ for

the adjustment and $\hat{\theta}_j = \frac{\hat{\mu}_j^2}{\hat{\sigma}_j^2 - \hat{\mu}_j}$ for the dispersion if $\hat{\sigma}_j^2 > \hat{\mu}_j$, or 1 otherwise.

P-value computation

After determining the fit parameters, the algorithm computes two-sided *P*-values using the

following equation:

171
$$P_{ij} = 2 \cdot \min\left\{\frac{1}{2}, \sum_{k=0}^{k_{ij}} NB\left(k_{ij}\middle|\mu_{ij},\theta_j\right), 1 - \sum_{k=0}^{k_{ij}-1} NB\left(k_{ij}\middle|\mu_{ij},\theta_j\right)\right\}. \qquad (7)$$

The term ½ is included to handle cases when both other terms exceed ½, which is possible

because of the discrete nature of the NB distribution.

Expression levels of different genes for the same sample are correlated because of biological

confounding effects such as co-regulation, which cannot be entirely excluded even after

correction by the autoencoder. The computed *P*-values can therefore be correlated. Multiple

testing correction was performed using the Benjamini–Yekutieli false discovery rate (FDR)

method, which holds under positive dependence[26].

Z-score computation

Z-scores Z_{ij} are computed on a logarithmic scale, as follows:

$$181 \qquad\qquad\qquad\qquad Z_{ij} = \frac{l_{ij} - \mu_j^l}{\sigma_j^l} \qquad\qquad\qquad\qquad (8)$$

182   where l_{ij} is the log$_2$ corrected count calculated as $l_{ij} = \log_2\left(\frac{k_{ij}+1}{c_{ij}}\right)$, σ_j^l is the standard deviation

183   of l_{ij} for gene j, and μ_j^l is the mean of l_{ij} for gene j.

Controlled counts

185   To obtain comparable counts across samples after controlling for various effects, we compute

186   the following controlled counts: $k_{ij}^c = \frac{k_{ij}+1}{c_{ij}}\overline{c_i}$. These are all of the same magnitude, independent

187   of the control method applied. When c_{ij} are size factors, the mean of all c_{ij} is approximately 1

188   and the count k_{ij}^c is of the same magnitude as the raw count k_{ij}. When c_{ij} is the estimated

189   mean, this equation provides a similar controlled count.

Benchmark by injection of outliers

To assess the sensitivity and specificity of alternative outlier detection methods, artificial read

count outliers were injected with pre-specified amplitudes (Z-scores). This process was

separate from the injection of corrupted data described earlier in "Fitting the autoencoder

hyperparameters." The outlier injection scheme described in this section was used to

independently assess OUTRIDER's performance in comparison with the Z-score approach.

To obtain a data set with samples that contained only a few outliers, all GTEx samples from the

skin tissue not exposed to the sun were fitted and tested and only the non-outlier samples as

described above in which fewer than 0.1% of all the genes were aberrantly expressed were

used for the benchmark set. The read counts were then replaced with a probability of 10^{-4} by an

outlier read count k_{ij}^{o}, defined as:

$$k_{ij}^{o} = \text{round}\left(s_i \cdot 2^{l_{ij}}\right),$$

202   where

$$l_{ij} = z^{o} \cdot \text{sd}\left(l_j\right) + \overline{l_j}.$$

Implementation

OUTRIDER is implemented as an R package that is available through GitHub

(https://github.com/gagneurlab).

Results

We considered two RNA-seq data sets, which we refer to as the Kremer and GTEx data sets.

The Kremer data set contains 119 RNA-seq samples from skin fibroblasts of patients with a

suspected rare mitochondrial disorder[5]. This data set was analyzed in a previous study with the

systematic effects corrected by manual inspection of sample correlation matrices[5]. In this study

4 genes were identified as aberrantly expressed out of 6 pathogenic genes validated by

functional assays[5]. This data set therefore served as our benchmark data set for rare disease

applications. The GTEx data set contains 271 RNA-seq samples obtained from the not sun

exposed skin tissue in the Genotype-Tissue Expression project (GTEx V6p[15]). We focused on

these skin samples because the tissue was similar to the tissue of origin of the Kremer data set.

The donors of the GTEx samples did not suffer from any condition and were not under

treatment. Nevertheless, aberrant gene expression in these samples has been reported[8].

For both data sets, we filtered out genes not expressed across the whole data set, resulting in

10,559 genes in the Kremer set and 18,250 genes in the GTEx set (Figure S1A and B). In the

GTEx set, we additionally filtered out two samples because of a low sequencing depth, resulting

in 269 samples (Figure S1C and D). Both data sets exhibited a strong correlation structure with

very distinct sample clusters (Figure 2A and Figure S2A). These correlations may have arisen

from biological variations such as the sex of the donor, the origin of the tissue, population

structure, or from hidden confounders such as poorly understood systematic technical

variations[5,8]. Applying the autoencoder on the read counts allowed co-variations to be estimated

and corrected for. The dimension of the autoencoder was fitted using a scheme in which

artificially corrupted read counts were injected and presented as the input to the autoencoder,

maximizing the likelihood of the original, uncorrupted data. Based on the GTEx data set, we

obtained 20 as optimal encoding dimension while 13 was optimal for the Kremer data set. We

note that encoding dimensions close to the optimum yielded similar results. After the correction

was applied, the co-variation clusters disappeared from both data sets (Figure 2B and Figure

S2B).

Testing for aberrant expression revealed aberrant samples in both data sets

The OUTRIDER algorithm models RNA-seq read counts as a NB distribution with a mean that is

the expected value provided by the autoencoder. Expression outliers are detected as significant

deviations of the observed read counts from these expected values, assuming negative

binomial distributions with gene-specific dispersions. Quantile–quantile plots for individual genes

indicated that OUTRIDER reasonably modeled the count distribution (Figures 3B and D and S3)

and that the resulting *P*-values can be used to detect outliers (Figure 3).

Globally, at an FDR threshold of 0.05 (Benjamini–Yekutelli method[26]), we detected aberrantly

expressed genes in 168 and 63 samples for the GTEx and Kremer data sets, respectively

(Figure 4A and B), with 90th percentiles of 10 and 4 aberrant genes per sample. The number of

significant outliers exhibited a skewed distribution across samples in both data sets, consistent

with the results of Kremer *et al.*[5]. This suggested that some samples differed from others to a

considerable extent. This may have been due to strong technical artifacts in the samples or

because the samples were from donors that were genetically distant from the others or who had

diseases with a severe regulatory impact. Regardless of the cause, it was difficult to narrow

down the candidate pathogenic aberrantly expressed genes in these samples to a short,

practical list (Figure 4C and D). We therefore introduced a cutoff (number of outliers > 0.1% of

expressed genes) to filter out these samples. This resulted in 19 outlier samples (7.1%) in the

GTEx data set and 4 outlier samples (3.4%) in the Kremer data set, as well as much improved

global quantile–quantile plots (Figure 4E and F).

Recall benchmark

To benchmark OUTRIDER, we injected outlier read counts and tested the fraction that could be

recalled. We used the 269 skin tissue samples not exposed to the sun from the GTEx data set,

from which we removed 19 outlier samples. Aberrant counts were then injected into this count

matrix of 250 samples and 18,250 genes. Using a frequency of 10^{-4}, we injected 434 aberrant

counts to create three scenarios: i) all underexpressed, ii) all overexpressed, and iii) 50%

overexpressed and 50% underexpressed. Each scenario was repeated for three different

simulated amplitudes (with Z-score values of 3, 4, and 6).

We then ran OUTRIDER, controlling either for sequencing depth alone or for co-variations using

the autoencoder. Thereby, we monitored the recall of injected read count outliers and the

precision, i.e. the number of injected outliers among the reported outliers using the different

detection methods (Figure 5). Off note, the precision and recall in this setup were

underestimates because the original data also contained genuine outliers. We observed that the

proposed correction strategy outperformed controlling only for sequencing depth in almost all

simulations. The size factor approach performed better only for very extreme overexpressed

outliers ($|Z| = 6$). However, the recall of OUTRIDER with the autoencoder decreased by less

than 5% compared to control using sequencing depth alone in this case.

The two most commonly used Z-score cutoffs ($|2|$ and $|3|$[4,8]) recalled almost all the outliers

(median=99%) in each simulation, yet at the cost of a high false discovery rate (precision <

0.02). In contrast, applying a significance cutoff corrected for multiple testing reduced the rate of

false discoveries and hence increased the precision, which confirms the importance of a *P*-

value based strategy.

In the scenario of overexpressed genes, the precision–recall curves with and without

significance overlapped. (Figure 5, middle column). This indicated that Z-scores and *P*-values

for high counts gave essentially the same rankings. The advantage of *P*-values is that they

provide a principled way to establish a cutoff that takes statistical significance and multiple

testing into account. With low gene expression levels, the overlap of the precision–recall curves

was less strong (Figure 5, right column). Only genes with a sufficiently high mean expression

level (mean count >80 with recall >55% and precision >60%; Figure S4B) yielded significant *P*-

values to recall the injected aberrantly low outliers. This is due to the non-negative nature of

counts, where even large Z-scores do not result in significant deviations from the mean

expression level (Figure S4). This limited the recall because a significant fraction of genes had a

mean expression level that was too low. Overall, these results demonstrated that it is important

to control for co-expression and to assess significance.

Applying OUTRIDER to the Kremer data set and filtering out the outlier samples resulted in a

recall of 47 events (66%) identified by Kremer *et al*. (Figure S5) based on the 48 previously

undiagnosed samples. Additionally, OUTRIDER detected 33 new expression outliers of which

19 were down-regulated. OUTRIDER was able to recall 5 out of the 6 pathogenic events (3

expression outliers, 1 mono-allelic expression, 2 splicing defects) validated by Kremer *et al.*.

While Kremer at al. additionally detected the mono-allelically expressed gene *ALDH18A1* as an

expression outlier it was not significant using OUTRIDER. In this case, a compound

heterozygous defect was detected in *ALDH18A1*, where only the missense mutation was

expressed. Hence, there was a reduction of about 40% of the overall gene expression.

Nevertheless, *ALDH18A1* was the gene with the second most extreme *P*-value among the

down-regulated genes in this sample. Furthermore, *ALDH18A1* can also be detected with a test

for mono-allelic expression[5], arguably the most appropriate aberrant expression category in this

case. Two further genes, *CLPP* and *MCOLN1*, diagnosed by Kremer *et al.*[5] by testing for

splicing defects, were detected by OUTRIDER as expression outliers. Those cases exhibited

reduced gene expression due to severe splicing defects.

Discussion

We have introduced OUTRIDER, a new end-to-end solution for identifying aberrantly expressed

genes within RNA-seq data, controlling for hidden confounders in an automated fashion, and

providing statistical significance estimates. OUTRIDER combines an autoencoder, which allows

for automatic correction of technical and biological variations among genes, and a statistical test

based on a NB distribution. OUTRIDER has three advantages over preceding methods. First, it

computes *P*-values, which can be adjusted to control the false discovery rate. Z-score-based

approaches lack *P*-values, so the setting of cutoffs is arbitrary. Second, the parameters of the

model are automatically fitted evaluating the ability of the model to correct for simulated

corrupted read counts. A precision–recall analysis demonstrated the advantage of correcting for

co-variations and employing significance-based thresholds. Third, OUTRIDER is implemented

and   made   available   as   an   open   source   R   package   (from

https://github.com/gagneurlab/OUTRIDER). The package provides plotting functionality and

allows full analyses to be made with only a few lines of code. Furthermore, the package comes

along with a comprehensive vignette guiding the user through a typical analysis.

We implemented OUTRIDER so that it is not restricted to the autoencoder, allowing the outlier

test to be used with any other normalization method. In particular, autoencoders with additional

layers could be employed to capture nonlinear relationships. However, the analysis of

correlations post-control did not suggest the need for a more complex autoencoder. This is

consistent with the study of Way and Greene, who modeled co-variations in RNA-seq samples

using a single layer autoencoder[13]. Independently of the way the correction is modeled,

OUTRIDER offers functionality for finding the optimal parameter set using a modeling scheme

based on corrupted count data. An advantage of this hyperparameter optimization is that no

manual intervention is needed to find the optimal parameters.

Despite controlling for co-variations, some samples exhibited a much larger number of aberrant

genes than others in both of the data sets investigated. This is consistent with the findings of

Kremer *et al.*[5]. In outlier samples where hundreds of genes are identified as aberrant, it is

difficult to draw any conclusion about the cause of such aberrant expression profiles. We

therefore label those samples as outlier samples and recommend to investigate them and their

global expression profile changes in a separate analysis. Some of these global changes may

have a technical basis, such as the two discarded samples from the GTEx data set with

aberrantly low coverage, whereas others may reflect the phenotype of the disease. Alternative

methods have been developed to detect such samples; these exploit global measures such as

the Mahalanobis distance to measure the dissimilarity of a sample from the population and to

identify aberrantly expressed gene sets[27,28]. Analysis of these genome-wide regulatory defects

could be interesting.

We have not addressed the handling of replicate samples because we do not expect them to

occur in diagnostic settings. The reason for this is that outliers are events that show strong

effects, so replicates are not essential for detecting these types of events. If a putative disease-

causing event is detected, such as an aberrantly expressed gene, follow-up experiments

involving assays complementary to RNA-seq are necessary instead of replicates to establish

the functional link of the event to the disease[1,29]. In contrast, if an RNA-seq sample is suspected

to have a technical problem, a new library can be prepared, and the new data is substituted for

the former. Neither of these situations results in replicate samples. When replicates are

available, users can combine the *P*-values of replicate samples using Fisher's method for

combining *P*-values[30] by assuming independence of the read counts conditioned on the

expected means predicted by the autoencoder.

In general, the autoencoder controlling scheme and the read count modeling approach benefit

from additional sequencing data; the more data that can be combined, the better the estimation

of the typical patterns within a population will be. This holds true when the overall data is equally

distributed across population structures or sequencing protocols, because each sample is

assumed to be an independent representative of the whole population. This assumption was

partially violated in this study because RNA-seq data sets such as GTEx comprise >85%

Caucasian individuals[15]. Such overrepresentation of a given population in the data set is

disadvantageous to our method, and additional samples from underrepresented groups would

be especially beneficial. More testing is needed to assess whether our strategy for controlling

raw read counts can control for different data sources including data from multiple sequencing

platforms or control data sets. The ability to control for different protocols enables count data to

be combined from multiple sources. This would allow studies with a few samples to merge their

results with sources such as the publicly available GTEx data set[15]. Currently, the best practice

is to use the same cell handling and library preparation protocol which reduces the analyzable

data set and therefore limits the statistical power.

The initial aim of developing OUTRIDER was to create an expression outlier detection

framework for RNA-seq data in a diagnostic setting. Our primary focus was to identify aberrantly

expressed genes in RNA-seq samples from patients with rare diseases. OUTRIDER will be

useful for the identification of potentially disease-causing genes in patients for whom current

methods, such as WES and WGS, provide variants of unknown significance rather than a

limited set of candidate genes. However, our approach is not restricted to such data or

experiments. In principle, OUTRIDER could model any count data derived from next-generation

sequencing. Previous studies that established links between rare variants and aberrant gene

expression, such as the study of Li *et al.*[8], could benefit from OUTRIDER's refined outlier

detection approach. Our approach could also be applied to data such as DNA accessibility from

ATAC-seq reads. In this case, promotor regions or enhancers would be used as features

instead of gene bodies. Finally, the methodology of OUTRIDER could be adopted to data from

proteomics or splicing experiments.

Supplemental Data

The Supplemental Data accompanying this article includes five figures and a detailed derivation of the loss function's gradient.

Declaration of Interests

The authors declare no competing interests.

Acknowledgments

This study was supported by the German Bundesministerium für Bildung und Forschung (BMBF) through the German Network for mitochondrial disorders (mitoNET, 01GM1113C to H.P.), the E-Rare project GENOMIT (01GM1207 to H.P.), and the Juniorverbund in der Systemmedizin 'mitOmics' (FKZ 01ZX1405A J.G. and V.A.Y.). A Fellowship through the Graduate School of Quantitative Biosciences Munich (QBM) supports V.A.Y. and Z.A. A.M was supported by a Fellowship through the Katholischer Akademischer Ausländer-Dienst (KAAD). C.M., F.B., V.A.Y., H.P. and J.G. are supported by EU Horizon2020 Collaborative Research Project SOUND (633974). The Genotype-Tissue Expression (GTEx) Project was supported by the Common Fund of the Office of the Director of the National Institutes of Health, and by NCI, NHGRI, NHLBI, NIDA, NIMH, and NINDS. The data used for the analyses described in this manuscript were obtained from the GTEx Portal on 06/12/17 with dbGaP accession number phs000424.v6.p1.

Author Contributions

J.G. conceived the project and overviewed the research with the help of Z.A, H.P., and V.A.Y. F.B., A.M., C.M. analyzed the data. F.B., C.M. and A.M. developed the software. D.M.B. and M.H contributed to the software development and early stage data analysis. J.G. and Z.A. devised the statistical analysis. F.B., V.A.Y., C.M., and J.G. made the figures. F.B., C.M., A.M., V.A.Y. and J.G. wrote the manuscript. All authors performed critical revision of the manuscript.

Web Resources

OUTRIDER: https://github.com/gagneurlab/OUTRIDER

GTEx: https://www.gtexportal.org/home

Supplementary data and additional results: https://i12g-gagneurweb.in.tum.de/public/paper/OUTRIDER

References

1. Taylor, J.C., Martin, H.C., Lise, S., Broxholme, J., Cazier, J.-B., Rimmer, A., Kanapin, A., Lunter, G., Fiddy, S., Allan, C., et al. (2015). Factors influencing success of clinical genome sequencing across a broad spectrum of disorders. Nat. Genet. *47*, 717–726.

2. Wortmann, S.B., Koolen, D.A., Smeitink, J.A., van den Heuvel, L., and Rodenburg, R.J. (2015). Whole exome sequencing of suspected mitochondrial patients in clinical practice. J. Inherit. Metab. Dis. *38*, 437–443.

3. 1000 Genomes Project Consortium, Auton, A., Brooks, L.D., Durbin, R.M., Garrison, E.P., Kang, H.M., Korbel, J.O., Marchini, J.L., McCarthy, S., McVean, G.A., et al. (2015). A global

reference for human genetic variation. Nature *526*, 68–74.

4. Cummings, B.B., Marshall, J.L., Tukiainen, T., Lek, M., Foley, A.R., Bolduc, V., Waddell, L.B.,

Sarah, A., Grady, G.L.O., Estrella, E., et al. (2017). Improving genetic diagnosis in Mendelian

disease with transcriptome sequencing. Sci. Transl. Med. *9*, 1–25.

5. Kremer, L.S., Bader, D.M., Mertes, C., Kopajtich, R., Pichler, G., Iuso, A., Haack, T.B., Graf,

E., Schwarzmayr, T., Terrile, C., et al. (2017). Genetic diagnosis of Mendelian disorders via

RNA sequencing. Nat. Commun. *8*, 15824.

6. Love, M.I., Huber, W., and Anders, S. (2014). Moderated estimation of fold change and

dispersion for RNA-seq data with DESeq2. Genome Biol. *15*, 550.

7. Whitaker, L. (1914). On the Poisson law of small numbers. Biometrika *10*, 36–71.

8. Li, X., Kim, Y., Tsang, E.K., Davis, J.R., Damani, F.N., Chiang, C., Hess, G.T., Zappala, Z.,

Strober, B.J., Scott, A.J., et al. (2017). The impact of rare variation on gene expression across

tissues. Nature.

9. Stegle, O., Parts, L., Piipari, M., Winn, J., and Durbin, R. (2012). Using probabilistic

estimation of expression residuals (PEER) to obtain increased power and interpretability of gene

expression analyses. Nat. Protoc. *7*, 500–507.

10. Lecun, Y. (1987). PhD thesis: Modeles connexionnistes de l'apprentissage (connectionist

learning models) (Paris: Universite P. et M. Curie (Paris 6)).

11. Bourlard, H., and Kamp, Y. (1988). Auto-association by multilayer perceptrons and singular

value decomposition. Biol. Cybern. *59*, 291–294.

12. Hinton, G.E., and Zemel, R.S. (1994). Autoencoders, Minimum Description Length and

Helmholtz Free Energy. In Advances in Neural Information Processing Systems 6, J.D. Cowan,

G. Tesauro, and Alspector J., eds. (Morgan-Kaufmann), pp. 3--10.

13. Way, G.P., and Greene, C.S. (2018). Extracting a biologically relevant latent space from

cancer transcriptomes with variational autoencoders. Pac. Symp. Biocomput. *23*, 80–91.

14. Vincent, P., Larochelle, H., Bengio, Y., and Manzagol, P.-A. (2008). Extracting and

composing robust features with denoising autoencoders. Proc. 25th Int. Conf. Mach. Learn. -

ICML '08 1096–1103.

15. The GTEx Consortium, Welter, D., MacArthur, J., Morales, J., Burdett, T., Hall, P., Junkins,

H., Klemm, A., Flicek, P., Manolio, T., et al. (2015). The Genotype-Tissue Expression (GTEx)

pilot analysis: multitissue gene regulation in humans. Science (80-.). *348*, 648–660.

16. Casper, J., Zweig, A.S., Villarreal, C., Tyner, C., Speir, M.L., Rosenbloom, K.R., Raney,

B.J., Lee, C.M., Lee, B.T., Karolchik, D., et al. (2018). The UCSC Genome Browser database:

2018 update. Nucleic Acids Res. *46*, D762–D769.

17. Harrow, J., Frankish, A., Gonzalez, J.M., Tapanari, E., Diekhans, M., and Kokocinski, F.

(2012). GENCODE: The Reference Human Genome Annotation for The ENCODE Project.

Genome Res *22*, 1760–1774.

18. Anders, S., and Huber, W. (2010). Differential expression analysis for sequence count data.

Genome Biol. *11*, R106.

19. McCarthy, D.J., Chen, Y., and Smyth, G.K. (2012). Differential expression analysis of

multifactor RNA-Seq experiments with respect to biological variation. Nucleic Acids Res. *40*,

4288–4297.

20. Yoon, S., and Nam, D. (2017). Gene dispersion is the key determinant of the read count

bias in differential expression analysis of RNA-seq data. BMC Genomics *18*, 408.

21. Byrd, R.H., Lu, P., Nocedal, J., and Zhu, C. (1995). A Limited Memory Algorithm for Bound

Constrained Optimization. SIAM J. Sci. Comput. *16*, 1190–1208.

22. Broyden, C.G. (1970). The Convergence of a Class of Double-rank Minimization Algorithms

1. General Considerations. IMA J. Appl. Math. *6*, 76–90.

23. Shanno, D.F. (1970). Conditioning of quasi-Newton methods for function minimization.

Math. Comput. *24*, 647–647.

24. Fletcher, R. (1970). A new approach to variable metric algorithms. Comput. J. *13*, 317–322.

25. Goldfarb, D. (1970). A family of variable-metric methods derived by variational means. Math.

Comput. *24*, 23–23.

26. Benjamini, Y., and Yekutieli, D. (2001). The control of the false discovery rate in multiple

testing under dependency. Ann. Stat. *29*, 1165–1188.

27. Zeng, Y., Wang, G., Yang, E., Ji, G., Brinkmeyer-Langford, C.L., and Cai, J.J. (2015).

Aberrant Gene Expression in Humans. PLoS Genet. *11*, 1–20.

28. Guan, J., Yang, E., Yang, J., Zeng, Y., Ji, G., and Cai, J.J. (2016). Exploiting aberrant

mRNA expression in autism for gene discovery and diagnosis. Hum. Genet. *135*, 797–811.

29. MacArthur, D.G., Manolio, T.A., Dimmock, D.P., Rehm, H.L., Shendure, J., Abecasis, G.R.,

Adams, D.R., Altman, R.B., Antonarakis, S.E., Ashley, E.A., et al. (2014). Guidelines for

investigating causality of sequence variants in human disease. Nature *508*, 469–476.

30. Fisher, R.A. (1970). Statistical Methods for Research Workers, 14[th] edition (Oliver & Boyd).

 Figures

Figure 1: Context-dependent outlier detection. The algorithm identifies gene expression

outliers whose read counts are significantly aberrant given the co-variations typically observed

across genes in an RNA sequencing data set. This is illustrated by a read count (left panel, fifth

column, second row from the bottom) that is exceptionally high in the context of correlated

samples (left six samples) but not in absolute terms for this given gene. To capture commonly

seen biological and technical contexts, a denoising autoencoder models co-variations in an

unsupervised fashion and predicts read count expectations. By comparing the earlier mentioned

context dependent read count with these expectations it is revealed as exceptionally high (right

panel). The lower panels illustrate the distribution of read counts before and after applying the

correction for the relevant gene. The red dotted lines depict the significance cutoff.

Figure 2: Controlling count data with autoencoders. (A) Correlation matrix of row-centered

log-transformed read counts for the skin samples not exposed to the sun from the GTEx data

set (of 269 samples and 18,250 genes). Red indicates a positive correlation and blue a negative

correlation. The color code on the left indicates a normal sample as green and an outlier sample

as orange. The dendrogram represents the sample-wise hierarchical clustering. **(B)** Same as for

A, but with the autoencoder controlled read counts.

Figure 3: Using the negative binomial distribution for significance assessment. (A, **C)** Normalized RNA sequencing read counts plotted against their rank. **(B**, **D)** Quantile–quantile plots of observed *P*-values against expected *P*-values with confidence area. Outliers are shown in red (FDR < 0.05). Panels A and B show data for the gene *AL627309.8* with no detected expression outlier, and panels C and D show data for the gene *SLC39A4* with two expression outliers.

Figure 4: RNA sequencing expression outlier detection. (A, **B)** Number of aberrant genes

(FDR < 0.05) per sample for the GTEx (A) and Kremer data sets (B). The orange bars represent

abnormal samples (with >0.1% aberrantly expressed genes). **(C**, **D)** *P*-values versus Z-scores

for a representative normal sample (C) and a representative abnormal sample (D). Genes with

significantly aberrant read counts are marked in red. **(E**, **F)** Quantile–quantile plots for the data

shown in panel A (E), and in panel B (F). Observed *P*-values are plotted against the expected

P-values with confidence area.

Figure 5: Outlier detection benchmark. The proportion of simulated outliers among reported outliers (precision) plotted against the proportion of reported simulated outliers among all simulated outliers (recall) for decreasing Z-score and for different methods. Plots are provided for three simulated amplitudes (by row, with simulated absolute Z-scores of 3, 4, and 6, top to bottom, respectively) and for all combined results (left column), for the subset of aberrantly high counts (middle column), and for the subset of aberrantly low counts (right column). The read counts were either controlled for sequencing depth only (black) or were also controlled for gene co-variation with the autoencoder (orange). The solid lines show the results restricted to significant counts only (FDR < 0.05) and the dashed lines show the results for all counts. Two commonly used Z-score cutoffs for outlier detection[4,8] are marked with a diamond (|Z| > 2) and a cross (|Z| > 3).

Supplemental Data

Supplemental Figures

Figure S1: Filtering of genes and samples. (A) Histogram of the RPKM values for the GTEx data set grouped according to the filter status. Green indicates the genes that passed the filter and gray those that were filtered out. **(B)** The same as A, but for the Kremer data set. **(C)** The total sequencing depth sorted from low to high for all the GTEx samples. The red horizontal line represents the Z-score cutoff of -3. **(D)** The same as C, but for the Kremer data set.

Figure S2: Controlling count data with autoencoders. (A) Correlation matrix of row-centered

log-transformed read counts for the Kremer data set (with 119 samples and 10559 genes). Red

indicates a positive correlation and blue a negative correlation. The color code on the left

indicates a normal sample as green and an outlier sample as orange. The dendrogram

represents the sample-wise hierarchical clustering. **(B)** Same as in A, but with the autoencoder

controlled read counts.

Figure S3: Using the negative binomial distribution for read counts. (A) Quantile–

quantile plots for 24 randomly selected genes from the GTEx data set. **(B)** Same as in A, but

for the Kremer data set.

Figure S4: Expression level-dependent recall. Precision versus recall for artificially injected low expression outliers with a Z-score of 6. **(A)** For all the injected outliers. **(B)** Split into 12 equal bins according to the mean expression level of the genes. Only a small fraction of the injected outliers was significant for the two lowest bins, with a mean expression level smaller than 81 counts.

Filtered Kremer data set

552 **Figure S5: Benchmark of OUTRIDER using the Kremer data set.** Venn diagram of the

553 expression outliers detected by OUTRIDER (orange), expression outliers detected by Kremer *et*

554 *al*. (violet), and pathogenic events validated by Kremer *et al*. (green) within 48 previous to

555 Kremer *et al*. undiagnosed samples[5].

We use L-BFGS to fit the autoencoder model as described in the Methods. To speed up the fitting we implemented the gradient as derived below.

The expectations μ are modeled by:

$$\mu_{ij} = s_i e^{y_{ij} + \bar{x}_j}$$

$$\mathbf{Y} = \mathbf{XWW}^T + \mathbf{b}$$

where the matrix $\mathbf{X}$ is given by the matrix: $\log \frac{k_{ij}+1}{s_i} - \bar{x}_j$.

The negative binomial log likelihood is given by:

$$ll = \sum_{ij} k_{ij} \log(\mu_{ij}) + \sum_{ij} \theta \log(\theta) - \sum_{ij} (k_{ij} + \theta) \log(\mu_{ij} + \theta)$$

$$+ \sum_{ij} \log(\Gamma(\theta + k_{ij})) - \sum_{ij} \log(\Gamma(\theta) k_{ij}!)$$

For the derivation of the gradient only the first and third term need to be considered, as all other terms are independent of μ.

Computing the derivative of the first term with respect to the matrix $\mathbf{W}$ by subsituting the autoencoder model for μ. Here the operations $\log[a]$ and $\exp[a]$ are understood to be element-wise.

$$\frac{d}{dw_{ab}} \sum_{ij} k_{ij} \log(\mu_{ij})$$

$$= \frac{d}{dw_{ab}} \sum_{ij} k_{ij} \log\left[\exp\left[\mathbf{XWW}^T + \mathbf{b}\right]\right]$$

$$= \frac{d}{dw_{ab}} \sum_{ij} k_{ij} (\mathbf{XWW}^T + \mathbf{b})$$

$$= \frac{d}{dw_{ab}} \sum_{ij} k_{ij} \left(\sum_{lm} x_{il} w_{lm} w_{jm} + b_j\right)$$

$$= \sum_{ij} k_{ij} \left(x_{ia} w_{jb} + \delta_{aj} \sum_{l} x_{il} w_{lb}\right)$$

$$= \sum_{ij} x_{ia} k_{ij} w_{jb} + \sum_{il} k_{ia} x_{il} w_{lb}$$

Which can be written as:

$$\mathbf{K}^T \mathbf{X} \mathbf{W} - \mathbf{X}^T \mathbf{K} \mathbf{W}$$

Equivalently the derivative of the third term is:

$$-\mathbf{L}^T \mathbf{X} \mathbf{W} - \mathbf{X}^T \mathbf{L} \mathbf{W}$$

where the components of the matrix $\mathbf{L}$ are computed by:

$$l_{ij} = \frac{(k_{ij} + \theta)\mu_{ij}}{\theta + \mu_{ij}}$$

The combined result is then:

$$\frac{dll}{d\mathbf{W}} = \mathbf{K}^T \mathbf{X} \mathbf{W} + \mathbf{X}^T \mathbf{K} \mathbf{W} - \mathbf{L}^T \mathbf{X} \mathbf{W} - \mathbf{X}^T \mathbf{L} \mathbf{W}$$

The derivative of the first term with respect to the bias $\mathbf{b}$ is computed as:

$$\frac{d}{db_a} \sum_{ij} k_{ij} \log\left(\mu_{ij}\right)$$
$$= \frac{d}{db_a} \sum_{ij} k_{ij} (\sum_{lm} x_{il} w_{lm} w_{jm} + b_j)$$
$$= \sum_i k_{ia}$$

Equivalently for the third therm the derivative is $-\sum_i l_{ia}$ and so the derivative of the loglikelihood with respect to the bias is:

$$\frac{dll}{db_a} = \sum_i k_{ia} - l_{ia}$$