SOFTWARE

TreeSwift: a massively scalable Python package for trees

Niema Moshiri

Correspondence:
niemamoshiri@gmail.com
Bioinformatics and Systems
Biology Graduate Program, UC
San Diego, Gilman Drive, 92093
La Jolla, California, USA
Full list of author information is
available at the end of the article

Abstract

Background: Phylogenetic trees are essential to evolutionary biology, and numerous methods exist that attempt to extract information applicable to a wide range of disciplines, such as epidemiology and metagenomics. Currently, the two main Python packages for trees are Bio.Phylo and DendroPy, but as dataset sizes grow, parsing and manipulating ultra-large trees becomes impractical.

Results: This article describes TreeSwift, a Python package for traversing and manipulating trees that does not require any external dependencies, and it then compares its performance against that of Bio.Phylo and DendroPy.

Conclusions: TreeSwift is a freely available, open source, and scalable Python package for traversing and manipulating trees. Source code and documentation are publicly available on GitHub (www.github.com/niemasd/TreeSwift), and it can easily be installed from PyPI (www.pypi.org/project/treeswift) using `pip`.

Keywords: phylogenetics; tree; traversal; Python; scalable

Background

Phylogenetic trees are essential to evolutionary biology, and phylogenetic methods are applicable to a wide range of disciplines, such as epidemiology [1, 2, 3] and metagenomics [4, 5, 6]. However, the datasets used by these methods are growing rapidly as sequencing costs continue to fall, emphasizing the need for scalable methods of tree traversal and manipulation.

Currently, the two main Python packages for trees are the Bio.Phylo module of Biopython [7] and DendroPy [8]. The two tools are simple to integrate into new methods, include a plethora of functions that cater to most phylogenetics needs, and are fast for reasonably-sized trees. However, as dataset sizes grow, parsing and manipulating ultra-large trees becomes impractical. I introduce TreeSwift, a scalable cross-platform Python package for traversing and manipulating trees that does not require any external dependencies, and I compare its performance against that of Bio.Phylo and DendroPy.

Implementation

TreeSwift is a pure-Python package that has no external dependencies. It has been tested on Python versions 2.6–2.7 and 3.3–3.7, but it should theoretically work on all versions. It is also compiled and hosted on PyPI, meaning it can easily be installed with a single `pip` command without any need for administrative privileges or any advanced knowledge. The primary TreeSwift documentation can be found as an Application Programming Interface (API) on the GitHub repository. Further,

the classes and functions of TreeSwift are thoroughly documented with Python "docstrings," so the user can access usage information via Python's `help` command.

A key feature of TreeSwift is its simplicity in class design in order to reduce time and memory overhead of loading, traversing, and manipulating trees. The entire package consists of just two classes: a `Node` class, which contains the data and local relationships, and a `Tree` class, which handles manipulation and traversal on the `Node` objects. A key distinction between TreeSwift and DendroPy is that DendroPy stores bipartition information to enable efficient comparisons between multiple trees that share the same set of taxa, but because TreeSwift is designed for the fast traversal and manipulation of a single tree (and not the comparison of multiple trees), TreeSwift forgoes this feature to avoid the accompanied overhead, resulting in a much lower memory footprint and faster execution of equivalent functions.

TreeSwift provides generators that iterate over the nodes of a given tree in a variety of traversals, including pre-order, in-order, post-order, level-order, ordered by distance from the root, and more. These built-in generators intend to provide developers a simple yet efficient manner in which to implement their own algorithms such that they only need to consider higher-level details of the traversal process. TreeSwift also provides the ability to compute various statistics of a given tree, such as tree height, average branch length, patristic distances between nodes in the tree, treeness [9], the Gamma statistic [10], etc.

Results and Discussion

As can be seen in Figure 1, TreeSwift is significantly faster than DendroPy for all tested functions and almost twice as fast as Bio.Phylo for almost all tested functions. The exceptions are when computing a distance matrix, in which case Bio.Phylo is significantly faster, when performing a level-order traversal, in which case TreeSwift is only negligibly faster than Bio.Phylo, and when finding the most recent common ancestor (MRCA) of a set of leaves, in which case TreeSwift is significantly faster than Bio.Phylo.

It must be emphasized that these comparisons do not reflect deficits in the existing packages against which TreeSwift was compared. These other libraries allow the integration of richer datasets, such as the integration of sequence data onto the taxa, as well as other relevant features TreeSwift has no intention of replicating, as they would likely come at a performance loss. Instead, these comparisons intend to highlight differences in use-cases between the various tools, and TreeSwift is designed to complement these other packages by providing a simple yet fast tree package meant specifically for traversal-intensive tasks on ultra-large phylogenetic trees.

Conclusions

TreeSwift is an open source Python 2 and 3 tree package suitable for phylogenetic algorithms on ultra-large trees. TreeSwift can be installed easily from PyPI using the `pip` command, and the cross-platform nature of Python as well as the simplicity of the classes within TreeSwift poise the package for community contribution.

Competing interests
The author declares that he has no competing interests.

Author's contributions

NM completed all portions of the project.

Acknowledgements

I would like to acknowledge Siavash Mirarab for his mentorship. I would also like to acknowledge Jeet Sukumaran and Mark Holder, as DendroPy provided much motivation for TreeSwift's development.

References

1. Ragonnet-Cronin, M., Hodcroft, E., Hué, S., Fearnhill, E., Delpech, V., Brown, A.J., Lycett, S.: Automated analysis of phylogenetic clusters. BMC Bioinformatics **14**(1), 317 (2013). doi:10.1186/1471-2105-14-317
2. Rose, R., Lamers, S.L., Dollar, J.J., Grabowski, M.K., Hodcroft, E.B., Ragonnet-Cronin, M., Wertheim, J.O., Redd, A.D., German, D., Laeyendecker, O.: Identifying Transmission Clusters with Cluster Picker and HIV-TRACE. AIDS Research and Human Retroviruses **33**(3), 211–218 (2017). doi:10.1089/aid.2016.0205
3. Moshiri, N.: TreeCluster: Massively scalable transmission clustering using phylogenetic trees. bioRxiv (2018). doi:10.1101/261354
4. Kembel, S.W., Eisen, J.A., Pollard, K.S., Green, J.L.: The phylogenetic diversity of metagenomes. PLoS ONE **6**(8), 23214 (2011). doi:10.1371/journal.pone.0023214. arXiv:1208.5792v1
5. Darling, A.E., Jospin, G., Lowe, E., Matsen, F.A., Bik, H.M., Eisen, J.A.: PhyloSift: phylogenetic analysis of genomes and metagenomes. PeerJ **2**, 243 (2014). doi:10.7717/peerj.243
6. Filipski, A., Tamura, K., Billing-Ross, P., Murillo, O., Kumar, S.: Phylogenetic placement of metagenomic reads using the minimum evolution principle. BMC Genomics **16**(Supplement 1), 13 (2015). doi:10.1186/1471-2164-16-S1-S13
7. Cock, P.J.A., Antao, T., Chang, J.T., Chapman, B.A., Cox, C.J., Dalke, A., Friedberg, I., Hamelryck, T., Kauff, F., Wilczynski, B., De Hoon, M.J.L.: Biopython: Freely available Python tools for computational molecular biology and bioinformatics. Bioinformatics **25**(11), 1422–1423 (2009). doi:10.1093/bioinformatics/btp163. arXiv:1011.1669v3
8. Sukumaran, J., Holder, M.T.: DendroPy: A Python library for phylogenetic computing. Bioinformatics **26**(12), 1569–1571 (2010). doi:10.1093/bioinformatics/btq228
9. Phillips, M.J., Penny, D.: The root of the mammalian tree inferred from whole mitochondrial genomes. Molecular Phylogenetics and Evolution **28**(2), 171–185 (2003). doi:10.1016/S1055-7903(03)00057-5
10. Pybus, O.G., Harvey, P.H.: Testing macro-evolutionary models using incomplete molecular phylogenies. Proceedings of the Royal Society B: Biological Sciences **267**(1459), 2267–2272 (2000). doi:10.1098/rspb.2000.1278

Figures

Figure 1 Tree Package Comparison. Runtimes of DendroPy, Bio.Phylo, and TreeSwift for a wide range of typical tree operations using trees of various sizes, as well as memory consumption after loading a tree.