gwasurvivr: an R package for genome wide survival analysis

Abbas A Rizvi[1*], Ezgi Karaesmen[1*], Martin Morgan[2], Leah Preus[1], Junke Wang[1], Theresa Hahn[3], Michael Sovic[1], Lara E Sucheston-Campbell[1,4]

[1]College of Pharmacy, The Ohio State University, Columbus, OH, [2]Department of Biostatistics and Bioinformatics, Roswell Park Comprehensive Cancer Institute, [3]Department of Medicine, Roswell Park Comprehensive Cancer Center, Buffalo, NY, [4]College of Veterinary Medicine, The Ohio State University, Columbus, OH

*These authors contributed equally

ABSTRACT

Summary: To address the limited software options for performing survival analyses with millions of SNPs, we developed gwasurvivr, an R/Bioconductor package with a simple interface for conducting fast genome wide survival analyses using VCF (outputted from Michigan or Sanger imputation servers) and IMPUTE2 files. We benchmarked gwasurvivr with other GWAS software capable of conducting genome wide survival analysis (genipe, SurvivalGWAS_SV, and GWASTools) and demonstrate improved scalability including shorter runtimes for large sample sizes and larger number of SNPs.

Availability and implementation: gwasurvivr, including source code, documentation, and vignette are available at: https://github.com/suchestoncampblllab/gwasurvivr

Contact: Abbas Rizvi, Rizvi.33@osu.edu; Lara Sucheston-Campbell, sucheston-campbell.1@osu.edu

1 INTRODUCTION

Genome-wide association studies (GWAS) are population-level experiments that investigate genetic variation in individuals to observe single nucleotide polymorphism (SNP) associations with a phenotype. Genetic variants tested for association are genotyped on an array and imputed from a reference panel of sequenced genomes using 1000 Genomes Project or Haplotype Reference Consortium (HRC) (Das, et al., 2016; Genomes Project, et al., 2015). Imputation increases genome coverage from hundreds of thousands or a few million to upwards of 30 million SNPs, improves power to detect genetic associations, and/or homogenizes variant sets for meta-analyses (Das, et al., 2016). Imputed SNPs can be tested for association with binary outcomes (case/control) and quantitative outcomes (i.e. height) using a range of available software packages including SNPTEST (Marchini, et al., 2007) or PLINK (Purcell, et al., 2007). However, existing software options for performing survival analyses [genipe (Lemieux Perreault, et al., 2016), SurvivalGWAS_SV (Syed, et al., 2017), and GWASTools (Gogarten, et al., 2012)] across millions of imputed SNPs either require user interaction with raw output, were not initially designed for survival and/or have other limitations that could deter more introductory users developed an R/Bioconductor package, gwasurvivr, for genome wide survival analyses of imputed data in multiple formats with flexible analysis and output options.

2 DATA STRUCTURES

Gwasurvivr can be used to analyze IMPUTE2 data or VCF derived from Michigan or Sanger imputation servers. Data from each are prepared in gwasurvivr by leveraging existing Bioconductor packages GWASTools or VariantAnnotation (Obenchain, et al., 2014) depending on the imputation output.

IMPUTE2 IMPUTATION

IMPUTE2 format is a standard genotype (.gen) file that is (typically) partitioned into 5 Mb chunks which store genotype probabilities (GP). We utilized GWASTools in R to compress files into genomic data structure (GDS) format. This allows for efficient, iterative accession to subsets of the data while simultaneously converting GP into dosages (DS) (Gogarten, et al., 2012) for use in survival analyses.

MICHIGAN or SANGER SERVER IMPUTATION

VCF files generated from these servers include a DS field and server specific meta-fields (INFO score, reference panel allele frequencies) which are iteratively read in by VariantAnnotation.

3 FUNCTIONALITY

Gwasurvivr implements a Cox proportional hazards regression model (Cox, 1992). to test each SNP with an outcome, with or without covariates and/or SNP-covariate interaction. To potentially decrease the number of iterations needed for convergence when optimizing the parameter estimatesx in the Cox model, we modified the R package survival (Therneau and Grambsch, 2000) such that the covariates in the model are first fit without the SNP and those parameter estimates are used as initial points. If no additional covariates are added to the model, the parameter estimation optimization begins with null initial value.

Survival analyses are run using genetic data in either VCF or IMPUTE2 formats. For both formats, survival time, survival status and additional covariates are stored in a phenotype file indexed by sample ID. The VCF files contain both genomic data and sample IDs, while IMPUTE2 requires .gen and sample files. Gwasurvivr functions for IMPUTE2 (impute2CoxSurv) or VCF (michiganCoxSurv or sangerCoxSurv) include arguments for the survival model (event of interest, time to event, and covariates), and arguments for quality control which filter on minor allele frequency (MAF) and INFO score. Users can also provide a list of sample IDs for gwasurvivr to internally subset the data, an option not available for SurvivalGWAS_SV. Gwasurvivr outputs two files: (1) .snps_removed, listing all SNPs that failed QC parameters, including their MAF and INFO score (2) a .coxph file with the results from the analyses, including parameter estimates, p-values, MAF, INFO score for sample set analyzed, the number of events and total sample N for each SNP. Gwasurvivr is well suited for multi-core processors and users can specify the number of cores used during computation on Windows and Unix. Lastly, gwasurvivr overcomes potential memory limitations that are often attributed to R by iteratively reading in data on subsets of the entire data making it possible to conduct genome-wide analyses on a typical laptop computer.

4 BENCHMARKING PERFORMANCE

We benchmarked gwasurvivr with genipe, SurvivalGWAS_SV v.1.3.2, and GWASTools using IMPUTE2 data (the comparison packages do not take VCF) for varying sample sizes (n=100, n=1000, n=5000) and number of SNPs (p=1,000, p=10,000, p=100,000), and including three non-genetic covariates. Survival time and event (alive/dead) were simulated using a normal and binomial distribution, respectively; covariates were simulated using normal distributions. Genetic data were simulated using HAPGENv2 (Su, et al., 2011) with SNP sets selected from chromosome 18 (1000 Genomes NCBI build 36). Benchmarking was performed using identical CPU constraints, 1 node (2.27 GHz Clock Rate) and 8 cores with 24 GB of RAM, on the University at Buffalo Center for Computational Research supercomputer. Genipe, SurvivalGWAS_SV, and GWASTools analyses were performed as specified by the authors in the online manual or vignette. All 4 software packages showed excellent agreement between MAF estimates, coefficient estimates, and p-values. For the smallest dataset, the 95% CIs overlap, as such the mean runtimes do not differ between the 4 programs (Figure 1, left panel). However, with increasing n and p the mean runtime differs substantially. For the largest dataset, gwasurvivr was faster than SurvivalGWAS_SV, genipe, GWASTools by 136.3, 9.4, 2.5-fold, respectively (Figure 1, right panel), further demonstrating the improved scalability implemented in gwasurvivr.

FUNDING

This work was supported by the National Institute of Health R01HL102278-01A1 [to LSC and TH]

ACKNOWLEDGEMENTS

The authors would like to thank Amy Webb and Guy Brock at The Ohio State University Department of Biomedical Informatics for listening to presentations on and offering suggestions about gwasurvivr. This work was performed in part at the University at Buffalo's Center for Computational Research.

REFERENCES

Cox, D.R. Regression Models and Life-Tables. Springer; 1992.

Das, S.*, et al.* Next-generation genotype imputation service and methods. *Nat Genet* 2016;48(10):1284-1287.

Genomes Project, C.*, et al.* A global reference for human genetic variation. *Nature* 2015;526(7571):68-74.

Gogarten, S.M.*, et al.* GWASTools: an R/Bioconductor package for quality control and analysis of genome-wide association studies. *Bioinformatics* 2012;28(24):3329-3331.

Lemieux Perreault, L.P.*, et al.* genipe: an automated genome-wide imputation pipeline with automatic reporting and statistical tools. *Bioinformatics* 2016;32(23):3661-3663.

Marchini, J.*, et al.* A new multipoint method for genome-wide association studies by imputation of genotypes. *Nat Genet* 2007;39(7):906-913.

Obenchain, V.*, et al.* VariantAnnotation: a Bioconductor package for exploration and annotation of genetic variants. *Bioinformatics* 2014;30(14):2076-2078.

Purcell, S.*, et al.* PLINK: a tool set for whole-genome association and population-based linkage analyses. *Am J Hum Genet* 2007;81(3):559-575.

Su, Z., Marchini, J. and Donnelly, P. HAPGEN2: simulation of multiple disease SNPs. *Bioinformatics* 2011;27(16):2304-2305.

Syed, H., Jorgensen, A.L. and Morris, A.P. SurvivalGWAS_SV: software for the analysis of genome-wide association studies of imputed genotypes with "time-to-event" outcomes. *BMC Bioinformatics* 2017;18(1):265.

Therneau, T.M. and Grambsch, P.M. Modeling Survival Data: Extending the Cox Model. Springer; 2000.

Figure 1. Runtime for survival analyses. The x-axis shows the three sample sizes (n=100, 1000, 5000) with SNP set sizes across the top (p=1000, 10000 and 100000). The y-axis is the total runtime in log₁₀seconds. The mean runtime and 95% confidence intervals (CI) for each n and p combination are show for genipe (red), GWASTools (green), SurvivalGWAS_SV (purple) and gwasurvivr (cyan). Each of the nine simulations were run in triplicate with identical CPU constraints (1 node, 8 cores).