Rapid alignment-free phylogenetic identification of metagenomic sequences

Benjamin Linard [1,2,3*], Krister Swenson [1,4], Fabio Pardi [1,4]

1. LIRMM, Univ Montpellier, CNRS, Montpellier, France
2. ISEM, Univ Montpellier, CNRS, IRD, EPHE, CIRAD, INRAP, Montpellier, France
3. Montpellier SupAgro, Univ Montpellier, Montpellier, France
4. Institut de Biologie Computationnelle, Montpellier, France

*To whom correspondence should be addressed.

Abstract

Motivation: Taxonomic classification is at the core of environmental DNA analysis. When a phylogenetic tree can be built as a prior hypothesis to such classification, *phylogenetic placement* (PP) provides the most informative type of classification because each query sequence is assigned to its putative origin in the tree. This is useful whenever precision is sought (*e.g.* in diagnostics). However, likelihood-based PP algorithms struggle to scale with the ever increasing throughput of DNA sequencing.

Results: We have developed RAPPAS (Rapid Alignment-free Phylogenetic Placement via Ancestral Sequences) which uses an alignment-free approach, removing the hurdle of query sequence alignment as a preliminary step to PP. Our approach relies on the precomputation of a database of k-mers that may be present with non-negligible probability in relatives of the reference sequences. The placement is performed by inspecting the stored phylogenetic origins of the k-mers in the query, and their probabilities. The database can be reused for the analysis of several different metagenomes. Experiments show that the first implementation of RAPPAS is already faster than competing likelihood-based PP algorithms, while keeping similar accuracy for short reads. RAPPAS scales PP for the era of routine metagenomic diagnostics.

Availability: Program and sources freely available for download at gite.lirmm.fr/linard/RAPPAS.

Contact: benjamin.linard@lirmm.fr

Supplementary information: Supplementary data are available at Bioinformatics online.

Keywords

phylogenetic placement ; metagenomics ; alignment-free ; species identification ; ancestral

sequence reconstruction

1. Introduction

Inexpensive high-throughput DNA sequencing has become a standard first step to inspect and estimate biodiversity from environmental samples. Metagenomics is the study of this vast variety of environmental DNA. Contrary to genomic approaches studying a single genome, metagenomes are generally built from bulk DNA extractions representing complex biological communities including known and yet unknown species (*e.g.* protists, bacteria, viruses). Applications range from health care to agro-environmental projects, with important implications on large-scale DNA-based biomonitoring (Baird and Hajibabaei, 2012). Furthermore, with DNA sequencing miniaturization, DNA-based diagnostics will soon be pushed to many layers of society (Gilbert, 2017; Zaaijer *et al.*, 2016). The bioinformatic analysis of metagenomes is, however, challenging because many sampled organisms are still unknown. Identifying the species at the origin of metagenomic sequences remains a bottleneck for analyses based on environmental DNA.

Several classes of approaches are possible for taxonomic classification of metagenomic sequences, the choice of which will generally depend on the availability of prior knowledge (*e.g.* a reference database of known sequences and their relationships) and a trade-off between speed and precision. For instance, without prior knowledge the exploration of relatively unknown clades can rely on unsupervised clustering (Sedlar *et al.*, 2017; Ondov *et al.*, 2016). The precision of this approach is limited and clusters are generally assigned to taxonomic levels via posterior analyses involving pairwise alignments to reference databases. An alternative is to contextualise pairwise alignments with taxonomic metadata. For instance, MEGAN (Huson *et al.*, 2007, 2016) assigns a query metagenomic sequence (noted QS) to the "Last-Common-Ancestor" (LCA) of all sequences to which it could be aligned with a statistically-significant similarity score (*e.g.* using BLAST or other similarity search tools). A faster alternative is to build a database of taxonomically-informed k-mers which are pre-computed from a set of reference sequences and stored in a database. Classification algorithms then assign a QS to the LCA sharing the highest number of those k-mers (Liu *et al.*, 2018; Müller *et al.*, 2017; Wood and Salzberg, 2014). All of these approaches use simple sequence similarity metrics and no probabilistic modeling of the evolutionary phenomena linking QSs to reference sequences. The advantage is that, particularly in the case of k-mer-based approaches, these methods allow the analysis of millions of QSs in a timescale compatible with large-scale monitoring and everyday

diagnostics.

Nevertheless, in many cases highly precise species identification is desired. This is particularly true for medical diagnostics where adapted treatments will be administered only after robust identification of the pathogen(s) (Butel, 2014) . Especially in the case of viruses (poorly known and characterized by rapid evolution), only advanced evolutionary modelling is sufficient to elucidate a detailed classification. A possible answer in this direction may be the use of phylogenetic inference methods. However, the standard tools for phylogenetic inference are not applicable to metagenomic datasets, simply because the sheer number of sequences cannot be handled by current implementations (Izquierdo-Carrasco *et al.*, 2011).

A solution to this bottleneck is phylogenetic placement (PP) (Matsen *et al.*, 2010; Berger *et al.*, 2011). The central idea is to ignore the evolutionary relationships between the metagenomic sequences and to focus only on elucidating the relationships between a metagenomic sequence and the known reference genomes. A number of reference genomes (or genomic markers) of well-known species are aligned together and a "reference" phylogenetic tree is inferred from the resulting alignment. This reference is the backbone onto which the reads matching the reference genomes will be "placed", *i.e.* assigned to specific edges. When a QS is placed on an edge, this is interpreted as the evolutionary point where it diverged from the phylogeny. Note that when the placement edge of a QS is not close to a leaf of the tree, the interpretation is that it does not belong to any reference genome but to a yet unknown/unsampled genome for which the divergence point has been clearly identified. This is different from LCA-based approaches where a QS assigned to an internal node usually means that it cannot be confidently assigned to any species of the corresponding subtree. Currently, only two PP methods are available: PPlacer (Matsen *et al.*, 2010; McCoy and Matsen, 2013) and EPA (until recently a component of RAxML) (Berger *et al.*, 2011). They are both likelihood-based, *i.e.* they try to place each QS in the position that maximises the likelihood of the tree that results from the addition of the QS at that position. Alternative algorithms were also described, but not yet publicly released (Filipski *et al.*, 2015; Brown and Truszkowski, 2013). Despite their robustness in identifying communities (Matsen *et al.*, 2010), these methods show some limitations: (i) likelihood-based methods require that each query QS is aligned to the reference genomes prior to the placement itself, a complex step that may dominate the computation time for long references and (ii) despite being much faster than a full phylogenetic reconstruction, they struggle to scale with increasing sequencing throughputs. Recently, the development of EPA-ng (Barbera *et al.*, 2018) provided an answer to the second point via the choice of advanced optimization and efficient parallel computing. But no fundamental algorithmic changes were introduced and the method still relies on a preliminary alignment.

To avoid these bottlenecks, we have developed the phylogenetic placement program RAPPAS (Rapid Alignment-free Phylogenetic Placement via Ancestral Sequences). The novelty of our approach rests on two key ideas: i) a database of "phylogenetically-informed" k-mers is built from the reference tree and reference alignment ii) later, QSs are placed on the tree by matching their k-mer compositions against the ancestral k-mer database. For a specific group of organisms, the maintenance of the RAPPAS database can be seen as a periodic "build-and-update" cycle, while the phylogenetic placement of new metagenomes becomes a scalable, alignment-free, process compatible with day-to-day routine diagnostics. This algorithmic evolution bypasses the alignment of QSs to the reference required by existing algorithms. Moreover, for short length reads RAPPAS produces placements that are as accurate as previous ML-based methods. Despite the preliminary state of its implementation, our experiments show that RAPPAS is already at least an order of magnitude faster than the most optimized versions of competing tools.

2.   Materials and Methods

2.1 Analyzing metagenomes with RAPPAS

In order to perform phylogenetic placement, one must define a reference dataset (alignment and tree) on which future QS will be placed. Typically, in a context of metagenomic analysis and large-scale taxonomic classification, such datasets will be based on well-established genome markers (*e.g. 16S rRNA, cox1, etc.*) or short genomes (*e.g.* organelles, viruses, *etc.*).

One of the main differences between our approach and the existing PP methods is in the workflows that they entail. Existing PP algorithms require the alignment of every QS to the reference alignment prior to the placement itself, a complex step that relies on techniques such as profile Hidden Markov Models, and that may dominate computation time. For each sample analyzed, the alignment phase is then followed by the placement phase, which relies on phylogenetic inference (Figure 1-A). RAPPAS uses a more efficient approach where all computationally-heavy phylogenetic analyses are performed as a preprocessing phase, which is only executed once before the analysis of any metagenomic sample. This phase builds a data structure (named pkDB; see next section) which will be the only information needed to place QSs. Then many samples can be routinely placed on the tree without the need   for   any   alignment   (Figure   1-B). An advantage of this approach is that many different pkDBs can be computed for different reference datasets and copied to less powerful devices for routine analyses. To follow the standards defined by previous PP methods, the placements are reported in a JSON file

following the "jplace" specification (Matsen *et al.*, 2012). In these files, the "likelihood weight ratio", "pendant branch length" and "distal branch length" reported by RAPPAS are equivalent to those reported by EPA and PPlacer algorithms. Elseways, the "likelihood" field contains the sum of the votes received by each placement (see Suppl. File S1 for more details). Jplace files allow the exploitation of RAPPAS results in all compatible software, such as iTol (visualization) Guppy (diversity analyses) or BoSSA (visualisation and diversity analysis) (Letunic and Bork, 2016; Matsen and Evans, 2013; Lefeuvre, 2018).

2.2 Ghost nodes and phylo-kmers

Before performing placements, one must build a database of k-mers called *phylo-kmers* that may be present with non-negligible probability in a QS related to the reference sequences. The input for this phase is a reference tree (denoted *refT*) and a reference alignment (denoted *refA*) on which refT was built. RefT is assumed to be rooted. This process is divided in three steps (see Figure 2): A) the injection of "ghost nodes" on every edge of refT, B) a process of ancestral state reconstruction based on this extended tree, and C) the generation of the phylo-kmers and their storage in a data structure.

The first step attempts to simulate evolution that might have occurred and resulted in sequences not present in the reference alignment. For each edge of refT, a new edge branching off at its midpoint *M* is created (Figure 2, step A). The length b_{new} of the new edge will be the average length over all paths from *M* to its descendant leaves. The new leaves of these new edges, which we refer to as "ghost nodes" (e.g. *G* in Figure 2) represent unsampled sequences that may have split from the reference tree at some point in the past. Newly sampled QSs which are only distantly related to the reference sequences should match the sequences that will be inferred at the ghost nodes.

The second step computes the state probabilities associated to all ghost nodes via standard phylogenetic methods for ancestral sequence reconstruction (Figure 2, step B). Briefly, given refA, an alignment consisting of *m* sites over *S* possible states (4 for DNA, 20 for amino acids), for each individual ghost node *G* we compute a $S \times m$ table $\left(p_{¿¿} s, j \right)_{¿}$ of probabilities , where $p_{s,j}$ represents the *marginal* probability of state *s* at site *j* (Yang *et al.*, 1995). From this table, we compute the probabilities of any given k-mer at any ghost node *G*. Let *k* be an empirically chosen k-mer size and let $n \in \{1,2,...,m-(k-1)\}$ be a particular site of refA. Assuming independence among sites (see, e.g., (Penny, 2004)), the probability *P* of *k*-mer $s_1 s_2 ... s_k$ at sites $\{n, n+1, ..., n+k-1\}_\square$ is given by:

$$(1) \qquad P = \prod_{i=1}^{k} p_{s_i, n+i-1}.$$

Each k-mer with a probability P larger than a (parameterized) threshold (by default $1/S^k$) is then stored together with a) the edge corresponding to the ghost node of origin and b) the probability P associated to this k-mer at the ghost node of origin (Figure 2, step C). In the end, all the k-mers reconstructed above are stored in a data structure linking each k-mer with the list of edges for which it was reconstructed, and the probabilities associated to each of these edges. This structure will be referred to as the *phylo-kmers database* (*pkDB*). When the same k-mer is generated at different positions n of refA for a single edge, only the highest probability is retained in the pkDB.

For a specific reference (refT, refA), the user needs to generate the corresponding pkDB as a preliminary step to all subsequent phylogenetic placements (Figure 1-B). The same pkDB can be reused for different datasets of QSs.

2.3 Placement algorithm

RAPPAS places each query sequence on the sole basis of the matches that can be found between k-mers extracted from a QS and phylo-kmers stored in the pkDB. An algorithm akin to a weighted vote is employed: each k-mer casts multiple votes – one for each edge associated to the k-mer in the pkDB – and each vote is weighted proportionally to the (logarithm of the) k-mer probability at the voted edge. The edge receiving the largest total weighted vote is the one considered as the best placement. A detailed description and complexity analysis for this algorithm can be found in Suppl. File S1. Unlike for alignment-dependent algorithms, the running time of RAPPAS does not depend on the length of the reference sequences, and rather than scaling linearly in the size of the reference tree, it only depends on the number of edges that are actually associated to some k-mer in the QS.

2.4 Accuracy experiments

The accuracy of the placements produced by RAPPAS were evaluated following established simulation protocols (Matsen *et al.*, 2010; Berger *et al.*, 2011). Briefly, these protocols rely on independent pruning experiments, in which sequences are removed from the tree and then placed back to the pruned tree. The pruned sequences are expected to be placed on the branch from which they were pruned. If the observed placement disagrees with the expected one, a topological metric quantifies the distance between them by counting the number of nodes separating the two edges. To make the placement procedure more challenging, we not only prune randomly chosen tree leaves, but whole subtrees identified

by their parent node. We consider this approach more realistic in the light of current metagenomic challenges because it is indeed common that large sections of the Tree Of Life are absent from the reference datasets. We also decided to simulate not only one query per pruned leaf but as many non-overlapping reads as permitted by the length of refA (*e.g.* a pruned sequence of 500bp results in 3 non-overlapping simulated QSs of 150 bps each). A detailed procedure can be found in Suppl. File S1.

2.5 Runtime and memory experiments

CPU times were measured for each software with the Unix command 'time', using a single CPU core and on the same desktop PC (64Gb of RAM, Intel i7 3.6GHz, SSD storage). The whole process time was measured: for EPA, EPA-ng and PPlacer this includes the compulsory alignment of query reads to the reference alignment. In the case of RAPPAS this includes the overhead induced by the initial loading of the pkDB into memory. The program fast aligner 'hmmalign' from the HMMER package (Eddy, 2011) was used to build the profile alignments, as in previous placement studies (Matsen *et al.*, 2010). Placement runtimes were measured for two datasets: D652 corresponds to a short reference alignment of 2,2kb, and D155 corresponds to a 4-fold longer 8,8kb alignment. Each software was launched independently 3 times and only the shortest CPU time was retained. For EPA, EPA-ng and PPlacer, model parameters were manually defined to avoid any optimization phase prior to the placement. For EPA-RAxML and EPA-ng, a single thread was explicitly assigned (option -T 1). The PPlacer implementation only uses a single thread and required no intervention. RAPPAS is based on Java 8+, which uses a minimum of 2 threads. We ensured fair comparison by using the unix controller 'cpulimit', which aligns CPU consumption to the equivalent of a single thread (options --pid process_id --limit 100). Defaults values were used for all other parameters.

2.6 Methods tested and datasets

The performance of RAPPAS (v1.00), both in terms of accuracy and computational efficiency, was compared against that of EPA (from RAxML v8.2.11) (Berger and Stamatakis, 2011), PPlacer (v1.1alpha19) (Matsen *et al.*, 2010) and EPA-ng (v0.2.0-beta, with the agreement of its authors) (Barbera *et al.*, 2018). Datasets submitted to the procedure evaluating accuracy were aggregated from (Matsen *et al.*, 2010; Berger *et al.*, 2011) with the exception of D155, which was built for this study. Each reference dataset is composed of a pair (refA, refT) built from refA. RefT is assumed to be correct (*i.e.* the tree is well supported). Each dataset is identified by the the number of taxa present in the tree (D150 representing a tree 150 taxa). Basic descriptive metadata

describing the nature of the locus, the length of the alignment and the gap content are present in Figure 3 (left headers) and Suppl. File S2. Globally, the datasets represent a panel of loci commonly used in metabarcoding and metagenomic studies.

The QSs submitted to the running time experiments are based on two sources. Runtimes measures on the D652 dataset uses real world 16S rRNA bacterial amplicons retrieved from the Earth Microbiome Project (Thompson *et al.*, 2017) via the European Nucleotide Archive (Silvester *et al.*, 2018) and the help of custom scripts from github.com/biocore/emp/ . Only reads with length superior to 100bp were retained (max length 150bp). For the runtime experiments based on the D155 dataset, 10^7 Illumina short reads of 150bp were simulated from the 155 viral genomes composing this dataset using the Mason read simulator (Holtgrewe, 2010) . A SNP rate of 0.1% and very low indel rate of 0.0001% was chosen to avoid generating longer profile alignments which would have impacted negatively the runtime of EPA, EPA-ng and PPlacer.

3. Results

3.1 Accuracy

The simulation procedure (see methods) was repeated for 10 different datasets representing genes commonly used for species identification. Accuracy is measured on the basis of the node distance (ND) separating observed placement and expected placement (see Suppl. File S1). The closer to zero the node distances are, the more accurate the method is. Figure 3 summarizes the results of each of these simulations. Horizontal lines link the per software ND means in order to facilitate their comparison. Detailed mean values are reported in Suppl. File S3.

For all datasets EPA, EPA-ng, and PPlacer show very similar performance with an average node distance (ND) below 5 in most cases. All methods perform similarly, with high accuracy. A second trend comes from the tested read lengths. The longer the placed reads are, the more accurate the placement is (Figure 3, left to right boxes). The worst performances were observed for the D628 and D855 datasets, which agrees with previous studies (Matsen *et al.*, 2010; Berger *et al.*, 2011).

RAPPAS was subjected to the same tests using fours k-mer sizes. Globally, similar results are observed: the longer the placed reads are the more accurate the placement is. The corresponding results can nevertheless be classified into two groups.

The first group contains the datasets for which using different values of *k* has a limited impact (Figure 3, D140, D150, D500, D714, D855, D1604). For these, RAPPAS shows globally an accuracy which is comparable to existing software, and shows mean ND values

below 5 in most cases. Note that the corresponding accuracy results are less balanced in RAPPAS than with other software (in both a positive and negative way). In simulations based on the shortest read lengths (Figure 3, leftmost boxes) similar or even slightly better accuracies (leftmost boxes of D150, D152, D714) measured. At the opposite, some of the longest read lengths resulted to slightly lower accuracy than in other methods (rightmost boxes of D150, D500).

The second group contains datasets where different values of k resulted in variable accuracy (Figure 3, D218, D628, D652, D155). Three out of these four datasets are also characterized by a high proportion of gaps in their reference alignments (Figure 3, left headers). They all show a multimodal distribution of the measured ND, which is particularly visible in the rightmost boxes of D218 and D628. Finally, D155 which corresponds the longest reference alignment (8,8kb) is the only dataset where only the longer k-mer sizes improved RAPPAS accuracy and where RAPPAS shows clearly a lower accuracy than EPA and PPlacer when considering the longer read lengths (D155, rightmost boxes).

3.2 Speed

Figure 4 summerises runtimes measured for the placement of 10^3 to 10^7 QSs on two datasets corresponding to short and long reference sequences (a marker gene and a complete virus genome). To consider the actual time needed for placing a set of metagenomic sequences, EPA, EPA-ng, and PPlacer runtime includes both read alignment and placement itself while the RAPPAS runtime includes the overhead related to the pkDB loading. EPA, PPlacer, and EPA-ng show a runtime linear with respect to the amount of placed bases for both datasets. With the D155 dataset, EPA and PPlacer failed to place a set of 10^7 reads due to high memory requirements. On this dataset, PPlacer showed placement runtimes up to 10x faster than EPA while EPA-ng was up to 64x faster than PPlacer and 252x faster than EPA. It is important to note their runtimes cannot be shorter that the time needed for sequence alignment, which is reported by the blue line of Figure 4.

RAPPAS runtimes appear to be non-linear with respect to the amount of bases when less than 10^4 reads are placed due to the overhead imposed by loading the pkDB into memory. On the other hand, for larger read sets ($>10^4$) this overhead becomes negligible and RAPPAS shows placement runtimes that scale linearly with the number of reads. RAPPAS is much faster than the other methods. With D652, which is a short RefA (Figure 4, rightmost box), RAPPAS was up to 5x faster than EPA-ng (5x for k=12 and 3x for k=8) and up to 35x faster than PPlacer (35x for k=12 and 20x for k=8). With D155, which is a longer reference alignment (Figure 4, leftmost box), greater speed increases are observed: RAPPAS was 43x faster than EPA-ng (39x for k=8 or 43x for k=12) and 135x times faster than PPlacer. More

concretely, using a single CPU and a common desktop computer RAPPAS is capable to place one million 100-150bp DNA fragments in 30 minutes on D652 and in 11 minutes on D155.

3.3 Implementation

RAPPAS is distributed as a standalone command-line application. It is compatible with any system supporting Java 1.8+. Ancestral sequence reconstruction is performed via an external program. Currently Phyml 3.3+ and PAML 4.9+ binaries are supported by RAPPAS. The most limiting factor for RAPPAS is the amount of memory required to build the pkDB (and subsequently, to load the pkDB when placing). Figure 5 reports the memory peaks experienced for three datasets and different values of k. D150 (few leaves, short alignment), D155 (few leaves, long alignment) and D1604 (many leaves, short alignment) show memory peaks below 12Gb, which indicated that RAPPAS can be launched on most standard laptop computer. Still, for larger values of k (>=10) we strongly recommend allocating more memory to avoid unnecessary reallocations and accelerate the process of building the pkDB. GIT repository, instructions to compile RAPPAS and tutorials are available at https://gite.lirmm.fr/linard/RAPPAS.

4.   Discussion

Advantages of Alignment-free placement

The innovative algorithm introduced in RAPPAS removes two of the major limitations imposed by previous PP algorithms: i) their reliance on a pre-computed multiple alignment merging both reference alignment and query sequences and ii) the fact that this pre-process has to be repeated for each new set of query sequences (Figure 2-A). The idea of attaching k-mers to pre-computed metadata to accelerate sequence classification was already explored by tools combining taxonomically-informed k-mers and LCA-based classification (Liu *et al.*, 2018; Müller *et al.*, 2017; Wood and Salzberg, 2014; Ounit *et al.*, 2015). But none of these methods were targeting highly accurate classifications based on probabilistic models. RAPPAS adapts this idea to PP by generating sets of phylogenetically-informed k-mers, called *phylo-kmers.* The resulting classifications are based on kmers that are probable under standard models of sequence evolution. As compared to previous PP methods, RAPPAS provides two critical algorithmic properties. First, placement complexity does not depend on the length of refA because any alignment can be summarized by its phylo-kmer composition, having an upper bound of $(¿\,states)^k$ possible phylo-kmers. Second, placement runtime only depends on the number of branches associated to the queried phylo-kmers,

independent of tree size. This second property has limited impact for small refT with very similar taxa or for small values of k (*i.e.* k-mers will be assigned to many tree branches), but is highly favorable for large refT and large values of k (*i.e.* k-mers will be assigned to a low proportion of the branches). As a consequence of these properties, the initial implementation of RAPPAS already shows placements that are faster than existing PP algorithms. This includes the beta release of EPA-ng that, despite being based on low level optimizations (*e.g.* SSE/AVX instructions, optimized C++ libraries, *etc.*) (Barbera *et al.*, 2018), is faster only when few sequences are analysed (when the pkDB loading is slower than the combination of alignment and placement). The speed gain provided by our alignment-free approach appears to be even more preponderant when longer reference alignments are considered (Figure 4). Finally, while the present implementation is based on a single thread, most steps of RAPPAS algorithm are atomic and should be fully parallelizable, offering even faster placements in the future.

Gaps and phylo-kmer generation

The presence of dense gappy regions in the refA have an impact on accuracy, a phenomenon accentuated by longer read lengths. D218, D628, and to a lower extant D652, are the most gappy of the tested datasets and show increasingly worse accuracy (compared to EPA/PPlacer) when k increases from 8 to 12 (Figure 3). This limitation may be related to several sources. First, the standard evolutionary models used during ancestral state reconstruction do not account for gaps (standard models in PhyML or PAML don't). Second, when generating phylo-kmers from a highly gappy refA column a decision between the two following choices needs to be made: i) this position is still taken into account, because posterior probabilities can be computed even if they are based on a limited amount of leaves ii) this column is ignored to build a phylo-kmer which "jumps" this likely less informative column. The first choice may generate k-mers that are unrelated to most regions of refT but may be necessary to discriminate placements in clades where sequence signal is actually present and informative. The second choice may produce k-mers which are more representative of the reference dataset but may lead to accuracy loss in the said clades. Currently, RAPPAS makes the arbitrary choice to ignore columns composed of more than 99.9% gaps, and to generate phylo-kmers which "jump" over gappy columns when the input refA is composed of more than 30% gaps (these values can be parameterized by the user). In the future, we could consider inexact matches between the query and the pkDB. This solution has been already explored in several k-mer based sequence classification tools (Müller *et al.*, 2017; Wood and Salzberg, 2014) via the use of the "spaced seeds" techniques, which allow probabilistic matches between k-mers following a particular match

template. Alternatively, inexact k-mer matches could be statistically evaluated via substitution matrices (at least in gappy regions) (Horwege *et al.*, 2014). Solutions to adapt these techniques to RAPPAS will be explored in the future to reduce its sensitivity to gaps.

Future work

RAPPAS placements are accurate for read lengths that are commonly produced by Illumina sequencing (150-300bp are common in Illumina kits). However, RAPPAS tends to produce slightly less accurate placements for longer read lengths (Figure 3). During pkDB construction, each phylo-kmer is associated to only one posterior probability per branch (Figure 2), which corresponds to the refA position with highest probability (see methods). While this choice was made to reduce the memory footprint, it is not ideal. For example, a longer refA is more likely to hold the same k-mer in different positions, a phenomenon which is accentuated for lower values of *k*. Also, different regions of refA could be subject to different evolutionary constraints (*e.g.* more and less conserved regions), yet only the more conserved regions (those generating the highest probabilities) will account for the placement score of this query sequence. This design choice may be the reason for the poor accuracy observed in the D155 dataset, which corresponds to a complete viral genome rather than a single genomic marker (Figure 3, rightmost box).

Long read sequencing is developing rapidly. Future versions of RAPPAS, therefore, will have to consider refA positions from which the phylo-kmers originated. Further improvements to the data structure for the pkDB will be required in order to store this information in an efficient way. Advanced solutions for the indexing of taxonomically-informed k-mers have been explored by some LCA-based approaches such as MetaCache (Müller *et al.*, 2017) or MetaOthello (Liu *et al.*, 2018). In particular, the use of k-mer minimizers exploits the redundancy imposed by overlapping k-mers, facilitating both efficient k-mer storage and very fast database access. Another approach would limit the database to the most discriminant phylo-kmers, as those of high frequency in the genomes or marker loci may become a source of noise rather than a source of discriminative phylogenetic signal. Such approaches have been explored by the read classifier CLARK (Ounit *et al.*, 2015), but so far appears to be less accurate than previous solutions (at least for bacterial genomes, see (Müller *et al.*, 2017)).

Despite the many potential optimizations to RAPPAS, it is already faster than other PP implementations. This speed enables the routine analysis of large numbers of metagenomic reads while resulting in placements which are as accurate as previous methods when short reads are used (*e.g.* current Illumina standards). The principle behind RAPPAS is

particularly adapted to metagenomic analyses run on portable devices with less computing capacity. As a preparatory step, one could easily build a set of pkDBs from reference datasets maintained in standard molecular markers databases such as EukRef (/eukref.org), SILVA (Quast *et al.*, 2013), RDP (Cole *et al.*, 2014), PhytoRef (Decelle *et al.*, 2015), or more specialized reference datasets maintained locally. These databases can then be shared on many sequencing devices, allowing RAPPAS to place millions of base pairs on different trees, efficiently identifying a sample's composition. RAPPAS has great potential in the context of field-based DNA sequencing, which is rapidly developing thanks to the portability of long read sequencing technologies (Lu *et al.*, 2016). As the RAPPAS algorithm evolves to handle longer query sequences with lower quality, it will open the door to phylogenetic placement as a means to robust real-time on-site species identification.

Acknowledgments

We would like to thank Olivier Gascuel for helpful advice, as well as Anne-Mieke Vandamme, Krystof Theys, Pieter Libin and Frédéric Mahé for sharing data and fruitful discussions. BL is also grateful to Vincent Lefort for his everyday advice. BL, KS and FP conceived of the study; BL and FP designed the algorithm; BL coded the software; BL, KS and FP wrote the manuscript.

Funding

This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 634650 (Virogenesis.eu), and from the Univ. of Montpellier under the InterLabex NUMEV Cemeb SupAgro (post-doctoral fellowship to BL).

References

Baird,D.J. and Hajibabaei,M. (2012) Biomonitoring 2.0: a new paradigm in ecosystem assessment made possible by next-generation DNA sequencing. *Mol. Ecol.*, **21**, 2039–2044.

Barbera,P. *et al.* (2018) EPA-ng: Massively Parallel Evolutionary Placement of Genetic Sequences.

Berger,S.A. *et al.* (2011) Performance, accuracy, and Web server for evolutionary placement of short sequence reads under maximum likelihood. *Syst. Biol.*, **60**, 291–302.

Berger,S.A. and Stamatakis,A. (2011) Aligning short reads to reference alignments and trees. *Bioinformatics*, **27**, 2068–2075.

Brown,D.G. and Truszkowski,J. (2013) LSHPlace: fast phylogenetic placement using

locality-sensitive hashing. *Pac. Symp. Biocomput.*, 310–319.

Butel,M.-J. (2014) Probiotics, gut microbiota and health. *Médecine et Maladies Infectieuses*, **44**, 1–8.

Cole,J.R. *et al.* (2014) Ribosomal Database Project: data and tools for high throughput rRNA analysis. *Nucleic Acids Res.*, **42**, D633–42.

Decelle,J. *et al.* (2015) PhytoREF: a reference database of the plastidial 16S rRNA gene of photosynthetic eukaryotes with curated taxonomy. *Mol. Ecol. Resour.*, **15**, 1435–1445.

Eddy,S.R. (2011) Accelerated Profile HMM Searches. *PLoS Comput. Biol.*, **7**, e1002195.

Filipski,A. *et al.* (2015) Phylogenetic placement of metagenomic reads using the minimum evolution principle. *BMC Genomics*, **16 Suppl 1**, S13.

Gilbert,M.T.P. (2017) Documenting DNA in the dust. *Mol. Ecol.*, **26**, 969–971.

Holtgrewe,M. (2010) Mason – A Read Simulator for Second Generation Sequencing Data.

Horwege,S. *et al.* (2014) Spaced words and kmacs: fast alignment-free sequence comparison based on inexact word matches. *Nucleic Acids Res.*, **42**, W7–11.

Huson,D.H. *et al.* (2007) MEGAN analysis of metagenomic data. *Genome Res.*, **17**, 377–386.

Huson,D.H. *et al.* (2016) MEGAN Community Edition - Interactive Exploration and Analysis of Large-Scale Microbiome Sequencing Data. *PLoS Comput. Biol.*, **12**, e1004957.

Izquierdo-Carrasco,F. *et al.* (2011) Algorithms, data structures, and numerics for likelihood-based phylogenetic inference of huge trees. *BMC Bioinformatics*, **12**, 470.

Lefeuvre,P. (2018) BoSSA: A Bunch of Structure and Sequence Analysis.

Letunic,I. and Bork,P. (2016) Interactive tree of life (iTOL) v3: an online tool for the display and annotation of phylogenetic and other trees. *Nucleic Acids Res.*, **44**, W242–5.

Liu,X. *et al.* (2018) A novel data structure to support ultra-fast taxonomic classification of metagenomic sequences with k-mer signatures. *Bioinformatics*, **34**, 171–178.

Lu,H. *et al.* (2016) Oxford Nanopore MinION Sequencing and Genome Assembly. *Genomics Proteomics Bioinformatics*, **14**, 265–279.

Matsen,F.A. *et al.* (2012) A format for phylogenetic placements. *PLoS One*, **7**, e31009.

Matsen,F.A. *et al.* (2010) pplacer: linear time maximum-likelihood and Bayesian phylogenetic placement of sequences onto a fixed reference tree. *BMC Bioinformatics*, **11**, 538.

Matsen,F.A.,4th and Evans,S.N. (2013) Edge principal components and squash clustering: using the special structure of phylogenetic placement data for sample comparison. *PLoS One*, **8**, e56859.

McCoy,C.O. and Matsen,F.A.,4th (2013) Abundance-weighted phylogenetic diversity measures distinguish microbial community states and are robust to sampling depth. *PeerJ*, **1**, e157.

Müller,A. *et al.* (2017) MetaCache: context-aware classification of metagenomic reads using minhashing. *Bioinformatics*, **33**, 3740–3748.

Ondov,B.D. *et al.* (2016) Mash: fast genome and metagenome distance estimation using MinHash. *Genome Biol.*, **17**, 132.

Ounit,R. *et al.* (2015) CLARK: fast and accurate classification of metagenomic and genomic sequences using discriminative k-mers. *BMC Genomics*, **16**, 236.

Penny,D. (2004) Inferring Phylogenies.—Joseph Felsenstein. 2003. Sinauer Associates, Sunderland, Massachusetts. *Syst. Biol.*, **53**, 669–670.

Quast,C. *et al.* (2013) The SILVA ribosomal RNA gene database project: improved data processing and web-based tools. *Nucleic Acids Res.*, **41**, D590–6.

Sedlar,K. *et al.* (2017) Bioinformatics strategies for taxonomy independent binning and visualization of sequences in shotgun metagenomics. *Comput. Struct. Biotechnol. J.*, **15**, 48–55.

Silvester,N. *et al.* (2018) The European Nucleotide Archive in 2017. *Nucleic Acids Res.*, **46**, D36–D40.

Thompson,L.R. *et al.* (2017) A communal catalogue reveals Earth's multiscale microbial diversity. *Nature*, **551**, 457–463.

Wood,D.E. and Salzberg,S.L. (2014) Kraken: ultrafast metagenomic sequence classification

using exact alignments. *Genome Biol.*, **15**, R46.

Yang,Z. *et al.* (1995) A new method of inference of ancestral nucleotide and amino acid sequences. *Genetics*, **141**, 1641–1650.

Zaaijer,S. *et al.* (2016) Using mobile sequencers in an academic classroom. *Elife*, **5**.

Figure legends

Figure 1: Generation of ancestral k-mers

The same procedure is repeated on each branch of the the reference tree. A. One ghost branch ended by a terminal ghost node G is attached to the middle of the original branch b. B. A technique of ancestral state reconstruction will generate a probability table for the sequences states expected at node G. C. Ancestral k-mers are generated from this table and assigned to the branch b.

Figure 2: Comparison between existing PP software and RAPPAS

The pipeline from query sequence datasets to placement results (jplace files) is described. Panel A. shows how other software requires the step of aligning a query to the reference alignment via an external tool (red box), which must be repeated for each new query. This extended alignment is the input for the phylogenetic placement itself (blue box). Panel B. show how RAPPAS builds a database of ancestral k-mers once. Many datasets can then be placed without alignment, matching their k-mer content to this database. Each operation is run with a seperate call to RAPPAS (blue boxes).

Figure 3: Placement accuracy

Datasets corresponding to different marker genes or small genomes (left headers) were submitted to a procedure testing placement accuracy for different read sizes (top header). Each grey box corresponds to a couple of dataset and read length. In each box, the X axis represents the tested software (RAPPAS was tested for several k-mer sizes), while the Y axis corresponds to the measured "node distance" (ND) (a metric of placement accuracy, the closer to 0, the more accurate the placement). White violins and included horizontal grey lines show the distribution of the ND measured for each software. Distribution means are linked by a red (RAPPAS at different ks) or a blue (other software) continuous line.

Figure 4: Placement runtime

Figure 5: Memory requirement related to pkDB construction

A.

1   2   3   [...] *n*

Query datasets

Query k-mers   *Query k-mers*

References

Alignment

Tree

1 time
ML inference: ancestral k-mer stored in DB

RAPPAS DB

***n* times**
k-mer matches analysis
(query vs DB)

n placements
(jplace files)

B.

1   2   3   [...] *n*

Query datasets

Reference
Alignment

***n* times**
Query to ref. alignment (external tool)

Reference
Tree

***n* times**
ML inference: placement algorithm

n placements
(jplace files)

Reference tree

Ghost branch

Most plausible k-mers of **G** are associated to *b*

A.

B. **Ancestral states reconstruction:** ML inference of ancestral k-mers at node **G**

C.

b

k-mer	probability
AATGC	0.99
ATTGC	0.90
AGTGG	0.78
[...]	[...]