Accounting for taste: A multi-attribute neurocomputational model explains the neural

dynamics of choices for self and others

Alison Harris*[†1], John A. Clithero[2], Cendri A. Hutcherson[3,4]

[1]Department of Psychology, Claremont McKenna College, Claremont, CA USA

[2]Lundquist College of Business, University of Oregon, Eugene, OR USA

[3]Department of Psychology, University of Toronto Scarborough, Toronto, ON Canada

[4]Department of Marketing, Rotman School of Management, Toronto, ON Canada

ABBREVIATED TITLE: A neurocomputational model of choices for others

Address correspondence to:

Alison Harris, PhD

Department of Psychology

Claremont McKenna College

850 Columbia Avenue

Claremont, CA 91711

aharris@cmc.edu

[†]All authors contributed equally to the work.

Number of pages: 61

Number of figures/tables: 7/3

Number of words for Abstract/Introduction/Discussion: 250/646/1496

Conflict of interest: The authors declare no competing financial interests.

28   **Abstract**

29   How do we make choices for others with different preferences from our own? Although

30   neuroimaging studies implicate similar circuits in representing preferences for oneself and

31   others, some models propose that additional corrective mechanisms come online when choices

32   for others diverge from one's own preferences. Here we used event-related potentials (ERP) in

33   humans, in combination with computational modeling, to examine how social information is

34   integrated in the time leading up to choices for oneself and others. Hungry male and female

35   participants with unrestricted diets selected foods for themselves, a similar unrestricted eater, and

36   a dissimilar, self-identified healthy eater. Across choices for both oneself and others, ERP value

37   signals emerged within the same time window but differentially reflected taste and health

38   attributes based on the recipient's preferences. Choices for the dissimilar recipient were

39   associated with earlier activity localized to brain regions implicated in social cognition including

40   temporoparietal junction (TPJ). Finally, response-locked analysis revealed a late ERP component

41   specific to choices for the similar recipient, localized to the parietal lobe, that appeared to reflect

42   differences in the response threshold based on uncertainty. A multi-attribute computational

43   model supported the link between specific ERP components and distinct model parameters, and

44   was not significantly improved by adding time-dependent dual processes. Model simulations

45   suggested that longer response times (RTs) previously associated with effortful correction may

46   alternatively arise from higher choice uncertainty. Together these results provide a parsimonious

47   neurocomputational mechanism for social decision-making, additionally explaining divergent

48   patterns of choice and RT data in decisions for oneself and others.

Significance Statement

How do we choose for others, particularly when they have different preferences? Whereas some studies suggest that similar neural circuits underlie decision-making for oneself and others, others argue for additional, slower perspective-taking mechanisms. Combining event-related potentials with computational modeling, we found that integration of others' preferences occurs over the same timescale as for oneself, while differentially tracking recipient-relevant attributes. Although choosing for others took longer and produced differences in late-emerging neural responses, computational modeling attributed these patterns to greater response caution rather than egocentric bias correction. Computational simulations also correctly predicted when and why choosing differently for others takes longer, suggesting that a model incorporating value integration and evidence accumulation can parsimoniously account for complex patterns in social decision-making.

61   Whether in parenting or politics, we are often required to make decisions for other

62   individuals whose preferences may differ substantially from our own. A critical question

63   concerns whether and when such choices require perspective-taking mechanisms that are slower,

64   more effortful, or computationally costly (Epley et al., 2004). For example, studies of response

65   time (RT) find that people take longer to choose for similar others when those choices diverge

66   from what they choose for themselves (Tamir and Mitchell, 2013; Apps et al., 2016; Volz et al.,

67   2017), perhaps because slower, more controlled processing is required to adjust an otherwise

68   automatic egocentric bias. Overcoming egocentric choice biases has also been associated with

69   increased activation in brain regions associated with social cognition, such as the ventromedial

70   prefrontal cortex (VMPFC) and temporoparietal junction (TPJ) (Tamir and Mitchell, 2010; Silani

71   et al., 2013).

72   Yet recent work using computational modeling suggests that slower RTs and activation in

73   VMPFC and TPJ during some social decision-making tasks can result from a noisy value-

74   integration mechanism, without requiring additional slow or effortful cognitive processes

75   (Hutcherson et al., 2015; Krajbich et al., 2015; Berkman et al., 2017). Moreover, several

76   functional magnetic resonance imaging (fMRI) studies have found that constructing values and

77   choices for oneself and others recruit the same regions of VMPFC, even when preferences differ

78   substantially (Nicolle et al., 2012; Janowski et al., 2013). Unfortunately, the low temporal

79   resolution of fMRI obscures the dynamics of this process, and recent computational models of

80   choice for others (Devaine and Daunizeau, 2017; Tarantola et al., 2017) have not explicitly

81   examined when and why constructing values for others might require longer, more extensive

82   processing compared to the self.

83   This paper aims to answer three related questions. First, are additional neural

84   computations involved when choosing for others with similar or dissimilar preferences? Second,

85   what are the temporal dynamics of those computations? Third, how might these computations

86   explain when and why people show egocentric biases, or instead make different choices for

87   themselves and others? To address these questions, we use a dietary choice task (Figure 1) in

88   which participants with unrestricted diets made food choices for themselves and two partners: a

89   *Similar* partner with unrestricted dietary preferences, and a *Dissimilar* partner who self-identified

90   as a healthy eater. We employed a novel combination of event-related potentials (ERP),

91   computational modeling, and simulation to identify the processes necessary to account for the

92   full pattern of choices, RTs, and neural responses observed when choosing for oneself, similar,

93   and dissimilar others.

94   The best-fitting model, a multi-attribute version of the drift-diffusion model (DDM)

95   (Smith and Ratcliff, 2004; Ratcliff and McKoon, 2008), suggests that individuals may indeed use

96   their own preferences as a source of information, particularly when deciding for similar others.

97   Yet a slow, serial adjustment mechanism is not required to explain when and why people choose

98   differently for others and take longer to do so. Instead, an early-acting perspective-taking

99   mechanism, localized to the temporoparietal junction (TPJ), may play a role in adjusting the

100   importance of different stimulus attributes (e.g., tastiness and healthiness) based on inferences

101   about the recipient's preferences. These attributes are integrated into a noisy overall value signal,

102   localized to a region of VMPFC previously implicated in value construction (Bartra et al., 2013;

103   Clithero and Rangel, 2014) with a similar time course regardless of recipient. We find further

104   evidence that these VMPFC value signals serve as input to an evidence accumulation process

105   (Rangel and Clithero, 2013) that produces a choice when the accumulated evidence crosses a

threshold whose height can be adjusted based on uncertainty about others' preferences. Thus,

although choices for other involve multiple distinct systems, these computations follow different

temporal dynamics and play different functional roles than previously hypothesized. These

results show that a parsimonious neurocomputational framework can account not only for when

people choose differently for themselves than for others, but also when and why these choices

are associated with additional processing time.

Methods

Participants

Thirty-eight right-handed participants (ages 18-40, 20 female) from the Claremont Colleges

participated in exchange for course credit. Participants were screened to ensure that they enjoyed

common appetitive snacks and did not self-identify as healthy eaters. Although all 38

participants were included in the behavioral model, two individuals were excluded from the

combined behavioral-neurophysiological model due to excessively noisy EEG data in which

cognitive signals could not be reliably separated from artefactual noise using artifact removal

protocols (see "EEG data acquisition and preprocessing"). All participants provided written

informed consent before participation. Procedures were reviewed and approved by the Claremont

McKenna College Institutional Review Board.

Stimuli

Stimuli consisted of color pictures of 250 common appetitive foods on a black background

(Figure 1C; 576 x 432 pixels). Foods were chosen to span a full range of perceived tastiness and

healthiness based on pilot ratings from a separate group of participants (N = 25). The stimulus

set included fruits and vegetables, chips, and candy bars.

Procedure

132   The experiment consisted of three parts (Figure 1A). In Part 1, participants received

information about the two partners for whom they would be making food choices, after which

they rated foods in terms of taste and health attributes. In Part 2, participants made choices about

whether to eat these foods, separately for themselves and their two partners (*Own* self, *Similar*

other, *Dissimilar* other conditions), while their brain activity was recorded with

electroencephalography (EEG). Finally, in Part 3, a single trial was randomly selected for each

recipient and the outcome of that trial was implemented.

139   Participants were instructed to fast for four hours prior to arrival to ensure they were

hungry and motivated to perform the decision task. Compliance was assessed verbally before

starting the experiment. Next, the experimenter took a photo of the participant against a white

wall, which was employed as a visual cue for the trials in which the participant chose food for

him/herself in Part 2. Participants then completed a short computer-based survey in which they

indicated the extent to which they generally use health information in deciding what to eat, and

made a series of twelve binary choices between a healthier and less healthy but tastier option

(e.g., green salad vs. French fries).

147   Participants received instructions familiarizing them with the overall structure of the

decision task and introducing the two partners (Figure 1B), matched to the participant's own

gender. Participants were informed that the partners were real people expressing their true

dietary preferences, and that they had in fact agreed to eat at least three bites of whichever food

the participant selected for them. This was true; no deception was used in the experiment. Each

participant received information that one partner had unrestricted dietary preferences similar to

their own (*Similar* partner; Figure 1B, top), while the other had quite different preferences

(*Dissimilar* partner; Figure 1B, bottom). First, participants viewed two short video interviews in

which each partner responded to prompts about their eating habits. Each partner was introduced

by name via an intertitle at the beginning of the interview. During the interview, partners

described their food preferences in general, and answered questions about specific choices (e.g.,

"Pizza or a salad"). Representative quotes for the partner without dietary restrictions included:

"I would say for me, taste is my number one consideration when I'm eating…If it tastes good but

it's not healthy, I'll just eat less of it, but for me eating food is all about it tasting good."

Representative quotes for the self-identified healthy eater included the following: "I don't eat

anything with added sugars…I try to eat a lot of fruits and vegetables, and I eat a lot of peanut

butter and almond butter." The video interviews were lightly edited for conciseness, but

otherwise were not manipulated. To give participants a fuller picture of the partners' preferences,

they were also shown the partners' responses to the same 12-item food questionnaire they had

completed earlier.

Following introduction to the partners, participants completed two blocks of trials in

which they rated each of 250 appetitive foods in terms of tastiness and healthiness. Each food

was displayed until the participant entered a keypress response using a 4-point scale (1 = Strong

No, 2 = Weak No, 3 = Weak Yes, 4 = Strong Yes). The order of the rating blocks and the left-to-

right order of the response keys was counterbalanced across participants.

Next, EEG data were recorded while participants performed a simple decision-making

task (Figure 1C) in which they chose whether or not a particular recipient (*Own* self, *Similar*

174 other, or *Dissimilar* other) would have the opportunity to consume each food at the end of the

175 experiment. Due to time constraints, this decision task used a subset of 200 foods (out of the

176 original 250), chosen to span the full range of the participant's taste and health ratings.

177 Participants made decisions regarding each food both for themselves and the two partners,

178 resulting in a total of 600 trials, in blocks of 10 trials per recipient. At the beginning of each

179 block, the participant saw a prompt ("For the next set of trials, please choose for this person")

180 above a picture of the intended recipient. For *Own* self trials, this picture was the head shot taken

181 upon the participant's arrival at the lab; the other partners' images were captured from

182 screenshots of the video interviews. The duration of the recipient prompt was randomly jittered

183 between 4 and 5 seconds. In addition, a smaller picture of the intended recipient was displayed at

184 the top of the screen throughout the block. On each trial, participants saw a food image centered

185 on the screen, which remained visible until a response was entered (maximum duration 4 s),

186 using a 4-point scale (1 = Strong No, 2 = Weak No, 3 = Weak Yes, 4 = Strong Yes). This

187 response method captures both the strength and direction of participants' preferences (Hare et al.,

188 2009; Hutcherson et al., 2015). The order of the recipient blocks and of the food images was

189 randomized across participants. The task was subdivided into 6 runs, and within each run the

190 blocks of trials were further subdivided by intervening self-paced breaks. During the decision

191 trials, participants were instructed to maintain central fixation and minimize eye movements and

192 blinks; adherence was monitored by checking the EEG signal for stereotypical patterns of eye-

193 movement-related artifact in frontal electrodes during the recording. Following each trial, a

194 screen consisting of a fixation dot was shown for a randomly jittered inter-trial interval of 4-6

195 seconds. Participants were instructed to respond as quickly and accurately as possible, and

196 completed a short practice block before the actual experiment.

197 Participants cared about their choices because they knew that a single randomly selected

198 trial would be implemented for each recipient at the end of the experiment. If the participant had

199 said yes on the selected trial, the recipient would have to eat at least three bites of the depicted

200 food. If the participant said no, the recipient would not receive the food.

202 *EEG data acquisition and preprocessing*

203 EEG data were collected using a 128-channel BioSemi ActiveTwo system (Biosemi

204 B.V., Amsterdam, Netherlands) with active electrodes with sintered Ag-AgCl tips in fitted

205 headcaps. Evoked brain potentials were digitized continuously at 512 Hz with default low-pass at

206 1/5 of the sampling rate. Two additional electrodes with a 4-mm sintered Ag-AgCl pallet were

207 placed bilaterally on the mastoids for use as references in data import. Prior to the start of data

208 collection, electrical offsets were verified to be between –20 and 20 µV across all channels.

209 Data preprocessing was performed offline using the EEGLAB toolbox (Delorme and

210 Makeig, 2004) for Matlab (Mathworks, Natick, MA). Upon import into EEGLAB, data were re-

211 sampled to 500 Hz and re-referenced to an average reference. To address DC offsets, linear

212 detrending was performed on the continuous data. High-pass filtering at 1 Hz and notch filtering

213 at 60 Hz was applied to remove slow voltage drifts and electrical noise, respectively, via a two-

214 way least-squares FIR filter. Epochs were then extracted for a 2400 ms window around the onset

215 of the food stimulus (–200 ms pre- to 2200 ms post-stimulus onset) for initial artifact rejection.

216 Although participants made an equal number of decisions for themselves and the two

217 partners, subsequent division of the data into conditions by stimulus value or stimulus attribute

218 (e.g., taste or health rating) produced unequal numbers of trials per condition due to individual

219 variations in choice. Because traditional artifact rejection methods remove whole epochs,

reducing the number of trials available to be averaged (Picton et al., 2000), use of these

techniques could lead to even greater asymmetries in the distribution of trials by condition,

potentially skewing the resulting average waveforms. Therefore, in lieu of traditional trial-based

artifact rejection, we employed independent components analysis (ICA), a method that has been

demonstrated to provide superior detection and removal for a variety of artefactual signals in

EEG (Delorme et al., 2007; Uriguen and Garcia-Zapirain, 2015) without affecting the overall

number of trials. Specifically, second-order blind identification (Belouchrani et al., 1997; Tang et

al., 2005) (SOBI) was applied to "unmix" the EEG data into a sum of temporally correlated and

spatially fixed components, which were then classified as task-related or artefactual (Harris et al.,

2011). Whereas artifacts such as eye blink, muscle activity, and electrode noise tend to have

highly localized scalp distributions and spectral peaks outside of typical EEG frequencies (e.g.,

60-Hz line noise) without consistent time-locking to stimuli or responses, task-related cognitive

components usually show meaningful dipolar scalp topographies, spectral peaks at typical EEG

frequencies (e.g., 10-Hz "alpha") and clear stimulus- or response-locking across the majority of

trials. Only task-related components were projected back onto the scalp, allowing us to obtain

artifact-corrected brain signals (Jung et al., 2000) from which 1600-ms stimulus-locked epochs

(−100 ms pre-, 1500 ms post-stimulus onset) and 700-ms response-locked epochs (−600 pre-,100

ms post-response onset) were extracted.

EEG: Regression analysis

In our first analysis, we sought to characterize the time course of value signal

computations, as identified by sensors and time windows in which neural activity correlated with

the stimulus value of the foods. For each channel, evoked data for each trial were integrated over

50-ms windows from 100 to 1250 ms after stimulus onset, producing a matrix of EEG responses

over 128 x 23 time windows in each participant. The response-locked data was likewise binned

over 30-ms windows from –600 to 90 ms before response onset, resulting in 128 x 23 sensor-

time window combinations in the response-locked data. For each analysis, the EEG responses for

each participant across all 128 x 23 time windows were then entered into a linear regression

model as in Equation 1:

$y_{sensor,time} = \beta_0 + \beta_1 Similar + \beta_2 Dissimilar + \beta_3 Stimulus\ Value + \beta_4 Similar * SV +$

$\beta_5 Dissimilar * SV + \beta_6 Arousal + \beta_7 Similar * Arousal + \beta_8 Dissimilar * Arousal + \varepsilon\ (1),$

where $y_{sensor,\ time}$ consists of trial-by-trial data (in μV) for a particular sensor and time window,

and β_0 is the average activity in the sensor. The Similar and Dissimilar covariates have a value of

1 when the decision is for the specified recipient (*Similar* or *Dissimilar*, respectively) and 0 in all

other cases. The Stimulus Value covariate encodes the value of the subject's decision from 1 for

Strong No to 4 for Strong Yes. The Arousal covariate, measuring the strength of preference

regardless of valence (0 for Weak No or Weak Yes, 1 for Strong No or Strong Yes), was

included to increase the statistical power of the linear model to identify activity associated with

value (Litt et al., 2010). Finally, we computed separate covariates for the interaction of *Similar*

and *Dissimilar* recipients with stimulus value and arousal, as indicated by Similar*SV,

Dissimilar*SV, Similar*Arousal, and Dissimilar*Arousal. This linear regression analysis

generated a set of estimated regression coefficients (i.e., beta map) for every sensor, time

window, and subject. These maps were then aggregated into mixed-effect group estimates by

computing one-sample t tests versus zero for each sensor and time window across all

participants. The resulting *t*-statistic map allowed us to identify sensor and time window

combinations in which neural activity was significantly correlated with stimulus value across

participants. Results were corrected for multiple comparisons using an approximate permutation

test in which the labels for all 600 trials were randomly shuffled 1000 times, and the resulting

beta maps entered into one-sample t tests from which an empirical distribution of *t* values for

each sensor and time window combination was then computed.

Next, we looked at how the weighting of taste and health attributes varied by recipient.

We defined a time window of interest from 500 to 650 ms post-stimulus onset based on the time

course of significant activity associated with the Stimulus Value covariate, which was also

generally consistent with the timing of stimulus value effects in previous studies (Harris et al.,

2011; Harris et al., 2013; Harris and Lim, 2016). Data in this time window was then inspected

for the fully independent effects of recipient and attribute using a linear regression following

Equation 2:

$y_{sensor,time} = \beta_0 + \beta_1 Health + \beta_2 Taste + \beta_3 Similar + \beta_4 Dissimilar + \beta_5 Similar *$

$Health + \beta_6 Dissimilar * Health + \beta_7 Similar * Taste + \beta_8 Dissimilar * Taste +$

$\beta_9 Health * Taste + \varepsilon$ (2),

where the Health and Taste covariates correspond to the taste and health attribute ratings for each

food item given by the individual participant, Health*Taste measures the interaction of the

attribute ratings, and Similar*Health, Dissimilar*Health, Similar*Taste and Dissimilar*Taste

reflect the interaction of a specific attribute with the identity of the recipient. Beta maps resulting

from the linear regression in Equation 2 above were then compared using paired *t* tests of

Similar*Taste – Similar*Health and Dissimilar*Taste – Dissimilar*Health to identify significant

interactions of attribute by recipient. Specifically, sensors of interest (SOIs) were defined from

the conjunction of significant sensors for the Similar*Taste – Similar*Health and

Dissimilar*Taste – Dissimilar*Health comparisons within the predefined time window of

interest (500-650 ms post-stimulus onset), and scalp topography and grand average waveforms

were obtained for these SOIs.

EEG: Bayesian source reconstruction

293   To localize activity associated with the Stimulus Value covariate to specific brain

regions, we applied distributed source reconstruction using SPM8 (Wellcome Department of

Imaging Neuroscience, Institute of Neurology, London, UK). In this approach, an empirical

Bayesian algorithm (Friston et al., 2008) is used to model the cortical sheet as a series of

hundreds of small dipolar patches, with the constraint that a common set of underlying sources

account for the evoked responses across all participants (Litvak and Friston, 2008). In contrast to

traditional dipole fitting, this method does not require *a priori* assumptions about the number or

spatial locations of sources. Instead, source reconstructions were first computed across the entire

trial to obtain models of activity in all potential sources and time points, followed by a more

specific reconstruction of the time window of interest (WOI; 500 to 650 ms post-stimulus onset)

defined on the basis of previous findings and the output of our mixed-effects ERP regression

analysis.

305   Data from all participants were entered into the same source space using a "canonical

mesh" based on the SPM template head model derived from the MNI brain. Sensors were

coregistered with the MRI coordinate system using a generic template of the BioSemi 128-

channel layout provided with the SPM software. Sensor locations were matched to the cortical

mesh via an iterative alignment algorithm, and the source space was modeled using a boundary

element model.

Our analysis employed a "localization of differences" approach (Henson et al., 2007), in

which we searched for a set of neural sources representing different levels of the psychological

variable of Stimulus Value. Difference waveforms were computed for each sensor and

participant by multiplying the average waveforms for each condition by weights used to test for a

linear (monotonically increasing) trend, and then summing across all weighted averages. To

localize activity related to stimulus value computations, we used weights of $(-3, -1, +1, +3)$

corresponding to the four levels of the Stimulus Value regressor, from Strong No to Strong Yes.

To localize activity related to main effects of participant identity, contrast weights for Recipient

corresponding to *Own*, *Similar*, and *Dissimilar* recipient choices were $(-1, 0, 1)$ for the early 350

to 400 ms post-stimulus window and $(-1, 1, 0)$ for the -300 to -180 ms pre-response window.

Following reconstruction of the difference waveform for each participant, reconstructions for the

WOI across participants were entered into a statistical analysis to identify statistically significant

source estimates across individuals. In part due to the relatively high consistency of sensor

locations across participants with the fixed cap layout used by this system, our initial analysis

found large clusters of significant dipoles covering much of the brain, even at relatively rigorous

family-wise-error (FWE) corrected statistical thresholds. Therefore, we chose a highly stringent

threshold of $F \geq 100$ to maximize separation of source estimates into distinct clusters while

retaining significant dipoles. Results were visualized in terms of maximal intensity projection,

focusing on cortical generators most likely to contribute to potentials recorded at the scalp

(Cohen et al., 2011).

Drift Diffusion Model Fitting: Time Varying Models

Our first modeling goal was to parameterize popular dual-process models of choice for others (i.e. anchoring and adjustment models) in a computational framework, in order to identify the most parsimonious set of parameters that accounted for patterns of choice and RT. Consistent with a growing body of work on value-based choices (Hutcherson et al., 2015; Tusche and Hutcherson, 2018) we assumed that choices can be captured using a multi-attribute variant of a drift diffusion model (DDM) (Smith and Ratcliff, 2004; Ratcliff and McKoon, 2008), in which noisy value signals accumulate over time and a choice is made when the accumulated signal crosses a pre-defined threshold for choice. In the simplest of these models, we assumed that this value signal (also known as the drift rate v) at each instantaneous time point t could be described as the linearly weighted sum of perceived tastiness and healthiness of the food on that trial, corrupted by Gaussian noise:

$$v_t = \beta_{Taste} \times Taste_i + \beta_{Health} \times Health_i + \varepsilon_t \quad (3)$$

where β_{Taste} and β_{Health} represent the relative weights on Taste and Health, $Taste_i$ and $Health_i$ represent the values of Taste and Health attributes for the food shown on trial i, and ε_t is distributed $\sim N(0, .1)$. We assumed that the weights on Taste and Health could vary as a function of recipient (i.e., when deciding for the *Dissimilar* healthy partner, the weight on health might be higher than when deciding for oneself or for a *Similar*, unrestrained partner: $\beta_{Health|Dissimilar} > \beta_{Health|Similar}$).

The canonical version of the DDM assumes that β_{Taste} and β_{Health} remain constant throughout the course of a single decision. However, most dual-process models assume that participants make choices for similar others by anchoring first on their own preferences, and then serially adjusting away from this anchor using effortful perspective taking mechanisms. This

suggests that β_{Taste} and β_{Health} might vary systematically over time, with early values resembling

weights for one's own self, and later values shifting to better reflect knowledge or assumptions

about one's partner. Although most descriptions of anchoring-and-adjustment models fail to

specify precisely the temporal dynamics of this process, we attempted to capture their basic spirit

using the following modifications to the standard DDM. First, we assume that the value signal at

instantaneous time t can be described by the following equation

363                    $$v_t = \beta_{Taste,t} \times Taste_i + \beta_{Health,t} \times Health_i + \varepsilon_t \quad (4)$$

which is identical to Eq. 3, with the exception that β_{Taste} and β_{Health} are allowed to vary at each

instantaneous time point t. Second, we assume that, when choosing for one's *Own* self, β_{Taste} and

β_{Health} are constant throughout the trial (i.e. $\beta_{Taste|Own,0} = \beta_{Taste|Own,t}$ and $\beta_{Health|Own,0} = \beta_{Health|Own,t}$).

Third, we assume that when choosing for others, participants begin with their own preferences

(i.e. $\beta_{Taste|Other,0} = \beta_{Taste|Own,0}$ and $\beta_{Health|Other,0} = \beta_{Health|Own,0}$). However, these initial weights can

begin to shift after a delay T to a new set of weights, at a rate r that determines how long the shift

takes once it begins. We used these two parameters to capture the common notion in dual

process models that perspective-taking might take time to implement, and that it should take

longer the greater the difference in value between the old and new values. Thus, the full model

when choosing for one's *Own* self consisted of one fixed parameter (within-trial decision noise ε,

which by convention is set to .1), and 4 parameters fitted to the data: weights on health and taste

($\beta_{Taste|Own}$ and $\beta_{Health|Own}$), the choice-determining threshold ($\pm a$) and the non-decision time (ndt).

Choices for others consisted of three fixed parameters (within-trial noise $\varepsilon = .1$, $\beta_{Taste,0} = \beta_{Taste|Own}$

and $\beta_{Health,0} = \beta_{Health|Own}$) and six fitted parameters (new weights $\beta_{Taste, t>T}$ and $\beta_{Health, t>T}$, $\pm a$, ndt,

the transition delay T and the transition rate r).

Unfortunately, no known analytical solution to the DDM exists with time-varying drift

rate parameters, rendering standard approaches to model-fitting and parameter estimation

intractable. Thus, we employed a maximum-likelihood numerical simulation method similar to

that employed in previous work on social decision-making (Hutcherson et al., 2015), with some

important differences to speed up computation time (for details, see Tusche and Hutcherson,

2018). For each participant in each condition (*Own, Similar*, *Dissimilar*), we began by first

simulating probability distributions of choices and response times for different combinations of

parameters. We then used these probability distributions to identify the likelihood of the

observed data for each parameter combination, and selected the parameter combination with the

highest likelihood. Because this numerical simulation method takes a considerable amount of

time that scales exponentially with the number of parameters and parameter values, we limited

computational time by exploring a discrete set of values for each parameter. For the *Own*

condition, we explored the following parameter values: threshold a = [.08, .1, .12, .14], non-

decision time ndt = [.2, .3, …, .7], and β_{Taste} = β_{Health} = [-.02, -.01, -.005, 0, .005, .01, .02, ….14].

Parameter values for the Similar and Dissimilar partner conditions were identical except that the

fitted values of β_{Taste} and β_{Health} represented the post-adjustment weights on Taste and Health

after shifting away from the egocentric *Own* weights (estimated from the *Own* condition), and

we included two additional time parameters to describe this shift: a delay parameter T = [0, .1,

…, .5] sec, and a rate parameter r = [1.2, 2.4, 4.8, 9.6, 1000] describing how quickly old values

shifted to new values following the delay. For example, a rate r = 1.2 suggests that it takes 1

second to shift 1.2 value units, or, equivalently, 250ms to shift .4 units. A rate r = 1000 indicates

an instantaneous shift.

Using these values, we performed model fitting and model selection in the following

manner. We first estimated the best-fitting parameter values for each participant's choices in the

Similar and *Dissimilar* partner conditions separately, estimating the full model with six free

parameters. We then estimated a reduced, four-parameter model with only base parameters

allowed to vary, T fixed at 0 (i.e. no early egocentric bias) and r fixed at 1000 (no gradual shift).

Then, for each subject, we calculated the Bayesian Information Criterion (BIC) for each model

based on the estimated likelihood of the data using the best-fitting parameter values. The

winning model was determined based on which model had the lowest BIC value for the largest

number of subjects, as well as the lowest BIC value when summing over all subjects. As we

describe in greater detail in the results section below, this procedure identified the four-parameter

model as the most parsimonious model to account for the data.

Drift Diffusion Model Fitting: Constant Value Models

Because the analyses described above found no evidence for a time-varying adjustment

process, all subsequent DDM estimation used canonical versions of the DDM, and was

performed using a recently developed software package freely available in Python (Wiecki et al.,

2013). Models were estimated using a Bayesian hierarchical framework, with Markov chain

Monte Carlo (MCMC) sampling methods employed to estimate a joint posterior distribution of

the model parameters. Hierarchical Bayesian estimation allows individual participant estimates

to be constrained by a group distribution, but also to vary to the extent that their data demonstrate

separation from the data of others. Estimation used non-informative priors: all priors were

uniform distributions over large intervals of possible parameter values.

Several different DDM specifications were fit to the data. All of the DDM specifications

assume the drift rate is a linear sum of weighted Taste and Health ratings, where the weights are

allowed to vary by condition (*Own*, *Similar*, *Dissimilar*):

$v = \beta_{1Own}I(Own)Taste + \beta_{2Own}I(Own)Health +$

$\beta_{1Similar}I(Similar)Taste + \beta_{2Similar}I(Similar)Health + \beta_{1Dissimilar}I(Dissimilar)Taste +$

$\beta_{2Dissimilar}I(Dissimilar)Health$, (5)

where I(Recipient) is an indicator function for each of the three conditions. The first model (M1)

only allowed drift rate, as specified in Equation 3, to vary by task condition. All other parameters

(*ndt,a,z*) were allowed to vary by subject, but did not vary within subject. The second model

(M2) included drift rate as in M1, but also allowed the barrier parameter to vary with task

condition, according to

$$a = \beta_0 + \beta_1 I(Similar) + \beta_2 I(Dissimilar). \text{ (6)}$$

This model allowed for the possibility that, in addition to weighting attributes differently by

recipient, individuals may also employ different thresholds depending upon the recipient. A third

model (M3) considered the same drift rate as in M1, but also allowed the starting point, or bias,

parameter *z* to vary with task condition, similar to Equation 4. This model did not allow barrier

to vary with task condition. A fourth model (M4) allowed drift rate, barrier, and starting point to

vary within participants. In all DDM specifications, the non-decision time parameter *ndt* was

modeled to vary across participants, but not within participants.

We used two methods to compare fits of the various DDM specifications. First, we used

the Deviance Information Criterion (DIC), a flexible measure for goodness-of-fit in hierarchical

Bayesian models (Spiegelhalter et al., 2002). The DIC combines a measure of deviance (i.e., lack

of fit) with a penalty for model complexity. A lower DIC represents a better model fit, and

differences in DIC greater than 10 are typically thought to reflect significant differences

(Spiegelhalter et al., 2002). Second, we compared observed data to data generated using random

samples from the sampled posteriors (Wiecki et al., 2013). For each of the four models, 100

samples for each experimental subject were created. The squared error between each simulation

and observed data was computed for both choices and RT, with the mean squared error (MSE)

computed across the 100 runs. These statistics are reported for each model in Table 1.

Model convergence was assessed using the Gelman-Rubin (G-R) $\hat{R}$ statistic (Gelman and

Rubin, 1992). The $\hat{R}$ statistic compares within-chain and between-chain variance of different

runs of the same model. Perfect convergence would be demonstrated with an $\hat{R}$ equal to 1. The $\hat{R}$

statistic was computed for all of the model parameters based on five runs of the model.

Another advantage of Bayesian estimation is that it is straightforward to compare

differences in parameter estimates. Significance inference is possible using the posterior

distributions generated from sampling. To compare coefficients to the null hypothesis ($\beta = 0$)

the percentage of the N=10000 samples greater than zero can be assessed. Similarly, to

determine whether or not a regression coefficient is greater than another, the percentage of the

difference between the N=10000 samples that is greater than zero can computed.

Drift Diffusion Model Fitting: Models Using ERP Data

In addition to the models M1 through M4, we also estimated a DDM using individual

trial ERP components, which was identical to M2 in all ways except for additional regressors on

the drift rate based on the ERP data (Equation 5). Specifically, as described above under "EEG:

Regression Analysis", we defined SOIs from the conjunction of significant sensors for

Similar*Taste – Similar*Health and Dissimilar*Taste – Dissimilar*Health in the predefined time

window from 500 to 650 ms post-stimulus onset. Within this SOI set and time window, we

extracted average ERP amplitudes (in µV) separately for each participant and trial. Trial-by-trial

ERP amplitudes were entered into a model with seven additional regressors beyond M2: one to

measure the basic effect of the average trial-by-trial stimulus-locked ERP data on drift rate, and

six to determine how trial-by-trial ERP data fluctuated with each of the decision targets and

attributes (*Own*, *Similar*, *Dissimilar* for Health and Taste).

A similar procedure was followed to estimate the effect of response-locked ERP on the

decision threshold. Trial-by-trial ERP amplitudes (in µV) were averaged across sensors showing

a significant effect of *Similar* recipient identity between –300 and –180 ms pre-response. Along

with behavioral choice and RT data, ERP amplitudes were entered into a model identical to M2

except for an additional regressor on the decision threshold to measure the effect of the trial-to-

trial fluctuations in the ERP data (Equation 6). All estimation and statistical inference followed

the same procedures outlined in the previous section.

Post-Hoc Analysis: Individual Differences in Attribute Re-weighting by Neural Encoding of

Identity

As we describe in greater detail below, we found neural responses that distinguished

choices for the *Dissimilar* recipient relative to one's *Own* self from approximately 350-400ms,

localized to regions implicated in social cognition including the superior temporal sulcus (STS).

At the same time, we observed that weights given to the Health and Taste attributes during

choice varied as a function of recipient identity, with the largest differences in weights observed

when comparing the *Dissimilar* other to the *Own* self. Taken together, these results suggest that

neural responses from 350-400 ms may reflect a perspective-taking process that influences

attribute re-weighting when deciding for others. If so, we speculated that the strength of this

early ERP response should predict how much an individual shifts their weights on taste and/or

health when choosing for others (particularly the *Dissimilar* other) compared to their *Own*

choices. To test this idea, we correlated each individual's neural response to recipient identity

with the magnitude of their shifts in attribute weighting for each recipient.

To compute individual differences in the ERP response, we extracted average amplitudes

between 350-400 m post-stimulus onset within the set of sensors showing a significant effect of

Dissimilar recipient identity for this time window. Then, for each individual participant we

calculated the difference in average ERP amplitudes separately for *Similar* vs. *Own* and

Dissimilar vs. *Own* conditions. To compute individual differences in attribute weighting, we

used the drift rate weights on Health and Taste attributes estimated from Model 2, Equation 5, to

compute the following contrasts: 1) TASTE$_{Similar\ vs.\ Own}$: change in Taste weight, *Similar* vs. *Own*

trials (i.e., $\beta_{1Similar} - \beta_{1Own}$); 2) TASTE$_{Dissimilar\ vs.\ Own}$: change in Taste weight, *Dissimilar* vs. *Own*

trials (i.e., $\beta_{1Dissimilar} - \beta_{1Own}$); 3) HEALTH$_{Similar\ vs.\ Own}$: change in Health weight, *Similar* vs. *Own*

trials (i.e., $\beta_{2Similar} - \beta_{2Own}$); 4) HEALTH$_{Dissimilar\ vs.\ Own}$: change in Health weight, *Dissimilar* vs.

Own trials (i.e., $\beta_{2Dissimilar} - \beta_{Own}$). We then computed Spearman's rank-order correlations

between ERP$_{Similar\ vs.\ Own}$ and TASTE$_{Similar\ vs.\ Own}$; ERP$_{Similar\ vs.\ Own}$ and HEALTH$_{Similar\ vs.\ Own}$;

ERP$_{Dissimilar\ vs.\ Own}$ and TASTE$_{Dissimilar\ vs.\ Own}$; and ERP$_{Dissimilar\ vs.\ Own}$ and HEALTH$_{Dissimilar\ vs.\ Own}$.

Results

In this experiment, we investigated the neural and computational bases of decisions for

self and others by measuring behavioral and ERP responses as participants with unrestricted

diets made food choices for themselves and two partners: a similar partner with unrestricted

preferences, and a dissimilar self-identified healthy eater (*Own* self, *Similar* other, and

Dissimilar other conditions, Figure 1). First, participants rated 250 different appetitive snack

foods on their perceived tastiness and healthiness. Second, for a subset of 200 foods selected to

vary in taste and health, they were asked to decide whether they would select the pictured food

for consumption after the experiment, making these choices once for each of the three recipients.

To ensure that choices were incentive compatible, at the end of the study, one random trial was

selected for each recipient and the participant's choice on these trials was realized.

To characterize the neural and behavioral correlates of this social decision scenario, we

performed a series of analyses as detailed in the following sections. First, we analyzed the

behavioral choice and RT data to verify that participants were taking recipients' preferences into

consideration when making their decisions, and to replicate patterns previously associated with

egocentric correction mechanisms. Next, we examined the stimulus-locked ERP data to find

neural signals associated with stimulus value computations, further assessing how taste and

health attributes were incorporated for each recipient during value integration. To determine how

neural activity differed as a function of recipient, we compared ERP responses in each condition,

time-locked to either the stimulus or the keypress response.

Although these analyses gave us a set of ERP components that correlated with different

aspects of the decision process, they were blind to the specific cognitive operations indexed by

these neural markers. Thus, to shed further light on the nature of these signals, we developed a

set of novel multi-attribute computational models of choices for self and others based on

extensions of the drift diffusion model (Ratcliff et al., 2016) and applied it to our event-related

data. The primary assumption of these models is that weights on attributes like taste and health

shape the evidence accumulated in favor of accept or reject responses. These weights can vary,

not only as a function of choice recipient, but also as a function of time (i.e., biased toward

automatic, egocentric defaults early on and then shifting over time with the application of

controlled perspective taking). To test this latter assumption, we first implemented computational

models in which the construction of value was allowed to vary systematically over time within a

decision, and used formal model comparison and selection procedures to test whether and when

this shift might occur. Second, having identified the simplest behavioral computational model to

account for patterns of choice and RT, we then attempted to link trial-by-trial fluctuations in

neural response to trial-by-trial variation in specific cognitive parameters such as the rate of

evidence accumulation and threshold for response. Finally, applying our neurocomputational

model to the behavioral data, we ran a series of simulation exercises demonstrating that

distributions of choice and RT which appear consistent with default egocentric biases and slow

effortful correction models of decision making can in some cases be explained without a

correction mechanism, and assuming only relatively egocentric attribute weighting and value

integration.

Behavior: Observed choice and RT

To verify that participants made inferences consistent with their partner's preferences, we

first examined whether recipient identity influenced the likelihood of making a healthy choice

(i.e., accepting/rejecting items rated high/low on health, Figure 2A). As expected, participants

made healthier choices when choosing for the *Dissimilar* "healthy eater" compared to choosing

either for *Own* self (paired-t_{37} = 9.19, P = 5x10^{-9}) or the *Similar* other (paired-t_{37} = 10.49, P =

1x10^{-12}). Participants made marginally *fewer* healthy choices for the *Similar* other (paired-t_{37} =

1.87, P = .069).

We also asked how often participants made the same choice for themselves and their

partner, one way of testing for egocentric responses. Participants made the same accept or reject

choice for the *Similar* other as for themselves on 72±11% of trials, but chose the same

significantly less often (60±17% of the time) when choosing for the *Dissimilar* other (paired-t_{37}

= 3.69, *P* = .0007). These results suggested that participants tend to choose similarly for both

recipients, with a more pronounced bias for the *Similar* other.

Next, we examined RTs for evidence that decisions for others might require additional

computational resources. We analyzed behavior in two ways: average RT across all choices, and

RT as a function of choice similarity between self and other. In line with the idea that choosing

for others is more computationally costly, we observed significant differences in mean RTs

depending on the recipient's similarity (Figure 2B). Participants were fastest when choosing for

themselves (mean = 1.11 s, SD = 0.18) and slowest when choosing for the similar other (paired-

t_{37} = 7.59, *P* = 5x10^{-9}), with choices for the dissimilar partner lying in between and significantly

different from the other two conditions (both paired-t_{37} > 2.17, both *P* < .036).

A critical finding from previous research is that individuals take longer to choose for

similar others when making choices that differ from their own preferences, but that this effect is

reduced when choosing for dissimilar others (Epley et al., 2004; Tamir and Mitchell, 2013). As

seen in Figure 2C-E, we replicated this pattern, observing longer RTs when choices diverge from

Own preferences, for both *Similar* (different choice: mean = 1.37 s, SD = 0.25; same choice:

mean = 1.22 s, SD = 0.28; paired-t_{37} = 7.90, *P* = 2x10^{-9}) and *Dissimilar* (different choice: mean

= 1.23 s, SD = 0.26; same choice: mean = 1.14 s, SD = 0.23; paired-t_{37} = 3.35, *P* = .002)

conditions. This effect was marginally more pronounced in choices for the *Similar* partner

compared to the Dissimilar partner (paired-t_{37} = 1.75, P = .089), in keeping with prior work

(Tamir and Mitchell, 2013).

Intriguingly, however, we also found a slowing effect when making choices for one's self

that diverged from the choices made for partners (*Own* vs. *Similar*: mean $RT_{Different}$ = 1.22±0.20

s, mean RT_{Same} = 1.09±0.17 s, paired-t_{37} = 6.27, P = 2x10^{-5}; *Own* vs. *Dissimilar*: mean $RT_{Different}$

= 1.23±0.26 s, mean RT_{Same} = 1.14±0.23 s, paired-t_{37} = 3.35, P = .002). This analysis has not

been reported previously, to our knowledge, and raises important questions about the most

parsimonious explanation of RT differences for divergent choices, as we discuss in greater detail

with respect to our computational simulation results below.

ERP: stimulus value integration

Given that participants adjusted their choices to reflect the recipient's preferences, a

further question is when and how relevant value signals emerge in the brain. Although fMRI

studies have identified overlapping regions of VMPFC representing value for both oneself and

others (Nicolle et al., 2012; Janowski et al., 2013), some dual-process models suggest that these

signals should take longer to construct for others. Therefore, the high temporal resolution of ERP

is of crucial importance in determining the time course of stimulus value integration when

choosing for oneself versus others. We began by identifying neural correlates of stimulus value

computation, which previous neurophysiological studies of choice for oneself have identified

between 400 and 650 ms after stimulus onset, localized to regions including the VMPFC (Harris

et al., 2011; Harris et al., 2013; Harris and Lim, 2016).

We applied a linear regression analysis to the ERP data in order to identify neural activity

correlated with the decision made in each trial (1 = Strong No to 4 = Strong Yes) across

participants. As shown in Figure 3A, ERP data was binned over 50-ms windows from 100 ms to

1200 ms after stimulus onset, for all 128 sensors grouped by scalp location. Data were

permutation-corrected to account for multiple statistical comparisons. This analysis revealed

significant main effects of stimulus value, regardless of recipient, at two major time windows

leading up to the time of choice. Generally consistent with the time range of stimulus value

effects reported in previous studies, the earliest major cluster of value-related activity occurred

from approximately 500 to 650 ms after stimulus onset (Figure 3A, green box), with additional

activity in roughly the same set of sensors re-emerging from 700 to 850 ms post-stimulus onset

(Figure 3A, blue box). Distributed source reconstruction of scalp topography for these two time

windows localized the stimulus value signal to regions including VMPFC, with a particularly

pronounced localization to VMPFC in the 500-650 ms time window (Figure 3B, circled).

Although the coarse spatial resolution of ERP precludes detailed specification of sources, the

sources found here closely resemble those from previous fMRI studies (Figure 3B, top inset), as

well as prior ERP localizations (Figure 3B, bottom inset) within the same latency range (Harris

et al., 2013; Harris and Lim, 2016).

Given the overlapping sensor distributions and source localizations for the earlier and

later time periods, what differentiates neural value integration during these two windows? To

address this question, we examined stimulus value computations as a function of recipient

identity using the conjunction of significant sensors 500-650 ms and 700-850 ms after stimulus

onset (Figure 3C). Grand average waveforms from central sensors (Figure 3C, left) revealed a

clear linear ordering from Strong No to Strong Yes for all recipients between 500 and 650 ms

post-stimulus (Figure 3C, shaded green region). In contrast, activity in the later 700-850 ms

window demonstrated a strong "self-relevance" effect (Grueschow et al., 2015): the strongest

629 Stimulus Value responses were observed for one's *Own* self, perhaps reflecting sustained

630 attention to one's own choices, with diminished responses for *Similar* and *Dissimilar* partners

631 (Figure 3C, shaded blue region).

632 　　　To confirm these effects statistically, we examined covariates representing the interaction

633 of stimulus value with each recipient that were computed as part of the larger regression analysis

634 (Eq. 1). Visualizing these effects at the scalp separately for time windows 550 and 800 ms post-

635 stimulus onset (Figure 3D) revealed that, despite highly significant activity at central sensors for

636 stimulus value in the earlier window (Figure 3D, top left), the interactions of stimulus value with

637 *Similar* (Figure 3D, middle left) and *Dissimilar* (Figure 3D, bottom left) were largely non-

638 significant, with *t*-values surviving a threshold of $p \leq 0.05$ in 0 and 1 sensors, respectively. In

639 contrast, during the later window (Figure 3D, right), interactions of recipient and stimulus value

640 were significantly negative for both partners (*Similar:* 18 sensors, average $p = 0.01$; *Dissimilar*:

641 12 sensors, average $p = 0.03$), suggesting that stimulus value computations for others are

642 diminished rather than enhanced during this late time window. Thus, we did not find stronger

643 delayed value representations during decisions for others, as would be expected if participants

644 required additional time to construct others' preferences. Instead, later value responses more

645 likely reflect sustained attention and/or arousal to choices with a direct impact on one's own

646 outcomes.

647

648 *ERP: attribute weighting by recipient*

649 　　　In line with the hypothesized role of VMPFC in context-dependent value integration

650 (Hare et al., 2009), ERP value signals from roughly 500 to 650 ms post-stimulus have previously

651 been shown to reflect increased weighting of health attributes when participants are incentivized

to exercise dietary self-control (Harris et al., 2013), overlapping with the time window of

significant stimulus value effects in our current data. Thus, we predicted that neural activity in

the time window of 500-650 ms post-stimulus onset would show differential weighting on taste

and health depending on the recipient of the choice.

To test this, we computed a second regression identifying sensors in which neural activity

significantly correlated with the interactions of *Similar* and *Dissimilar* recipient by Taste and

Similar and *Dissimilar* recipient by Health (Equation 2). The beta maps resulting from this

regression were then compared using paired t-tests to find sensors where the relative weighting

of taste (Figure 4A, left) and health (Figure 4A, middle) varied by recipient during our time

window of interest from 500 to 650 ms after stimulus onset. Difference plots of scalp topography

in this time window identified a set of central sensors (Figure 4A, right) for the interaction of

taste and health in both *Similar* and *Dissimilar*, overlapping those associated with stimulus value

in our initial analysis. Sensors of interest (SOIs) were formally defined via the conjunction of

sensors associated with significant weighting on Taste – Health in both *Similar* and *Dissimilar*

recipient conditions.

To clarify the direction of the interaction defined by our conjunction analysis, we next

examined grand average waveforms and linear contrasts extracted from the SOIs (Figure 4B-D)

separately for taste and health attributes by recipient. In line with our predictions, the clearest

parametric effect of taste was visible when deciding for one's *Own* self versus the two partners

(Figure 4B, left; Figure 4C), whereas the linear ordering of health showed the greatest effect for

the *Dissimilar* healthy eater and negligible distinction by health for one's *Own* self (Figure 4B,

right; Figure 4D). We confirmed these observations statistically using a repeated-measures

ANOVA on the linear contrast weights with Attribute (Taste/Health) and Recipient

(Own/Similar/Dissimilar) as covariates, focusing on the interaction of Attribute x Recipient. We

found a significant interaction of Attribute x Recipient ($F(2,70) = 5.05$, $p = 0.009$), reflecting a

significant linear contrast ($F(1,35) = 8.39$, $p = 0.006$) driven by the opposing linear trends in

neural weighting of taste and health attributes across recipients. These results support the idea

that value integration from approximately 500 to 650 ms post-stimulus reflects differential

attribute weighting for oneself and others.

ERP: neural signals related to recipient identity

The findings described above bolster the idea that decisions for others recruit similar

value computation mechanisms as decisions for oneself, on the same time scale, regardless of

how dissimilar the recipient's preferences may be. However, these results raise an additional

question: how and when does the brain modify value computations to distinguish the intended

recipient of the choice? To address this issue, we next looked for neural activity that

differentiated recipient identity, using ERP data time-locked to both stimulus and response.

Some versions of a dual-process account suggest that inhibition of egocentric biases

should emerge relatively late in the process and, because similar individuals more strongly

activate egocentric biases that need correcting, such inhibition should be more pronounced for

the *Similar* other (Tamir and Mitchell, 2013). In contrast, other research suggests attention and

perspective taking mechanisms should be most pronounced for the *Dissimilar* other, whose

preferences differ most markedly from one's *Own* self (Silani et al., 2013). Given that we found

a similar time course of value integration by recipient, we hypothesized that this perspective-

taking and adjustment process might actually occur *early,* prior to or during the window of

stimulus value computation (i.e., prior to 500 to 650 ms post-stimulus). Previous neuroimaging

698   research has suggested that regions associated with social cognition, such as TPJ and superior

699   temporal sulcus (STS), play a key role in directing value integration in VMPFC during social

700   decisions (Hare et al., 2010; Hutcherson et al., 2015; Strombach et al., 2015). Therefore, we

701   further predicted that any differences would localize to regions including TPJ.

702   To test these predictions, we computed a linear regression with separate dummy-coded

703   indicator variables for *Similar* and *Dissimilar* recipient; the results of this analysis from 100 to

704   600 ms after stimulus onset, our *a priori* time window of recipient computation, are shown in

705   Figure 5A. Although the covariate for *Similar* recipient (Figure 5A, left) was largely non-

706   significant during this time window, we found significant ERP activity for the *Dissimilar*

707   recipient from approximately 350 to 400 ms post-stimulus onset (Figure 5A, right). Average

708   waveforms for these sensors and time window (Figure 5B) revealed a positive response for the

709   *Dissimilar* condition relative to one's *Own* self, localized to sources including posterior superior

710   temporal sulcus (STS) and TPJ (Figure 5B, right). Consistent with previous studies (Saxe, 2006;

711   Andrews-Hanna et al., 2010; Hare et al., 2010; Hutcherson et al., 2015), these results suggest a

712   mechanism by which brain networks involved in mentalizing about others may communicate

713   with valuation regions in order to adjust attribute weights during value integration.

714   Although pre-value signals differentiated the *Dissimilar* other from both *Own* self and

715   *Similar* other trials, we also sought to test predictions of several dual-process models that there

716   may also be a late adjustment process, unique to choices for *Similar* others, that delays choices

717   and corrects egocentric values to account for differing preferences. Although we did not find

718   evidence for late value integration signals when deciding for *Similar* others (see "Stimulus value

719   integration" results above), we nevertheless asked whether there was a main effect of recipient

720   identity in late-emerging response-locked ERP signals, as might be predicted by some dual-

process models. Intriguingly, a linear regression on ERP data time-locked to the keypress

response revealed a significant main effect of *Similar* recipient from approximately –300 ms to –

180 ms pre-response (Figure 5C), reflecting a more positive deflection for *Similar* relative to

Own and *Dissimilar* (Figure 5D). To shed light on the nature of this process, we performed

source localization from –300 to –180 ms pre-response. In this time window, the main effect of

Similar recipient was predominantly localized to the intraparietal sulcus (IPS), close to an area

previously identified as being more activated when choosing for others (Janowski et al.,

2013). In contrast, significant main effects of *Dissimilar* recipient in this time window were

largely confined to the period immediately prior to response (–120 to 0 ms pre-response), and

thus are more likely to reflect the initiation of movement potentials associated with the motor

response.

Computational Modeling

As described above, our analysis of the time course of value integration suggests that a

single valuation mechanism, localized to the VMPFC, computes stimulus values using weighted

attribute integration for both self and others, with similar temporal dynamics. Yet the presence of

both early- and late-emerging components in TPJ and IPS that were specific to choosing for

others is fully consistent with dual-process models of choice in which perspective-taking

mechanisms alter value computations to reduce egocentric biases. This raises an important

question: what is the most parsimonious computational framework to account for both the

behavioral and neural data?

To address this issue, we used the power of formal model comparison and selection

procedures to identify the most parsimonious computational model of decision making for

744   oneself versus others, and then explored how changes in parameter values across choices for self

745   and others shed light on neural and behavioral responses. We began by specifying a multi-

746   attribute variant of the DDM that allowed us to capture basic assumptions of dual-process

747   accounts, which suggest that the construction of value should vary in systematic ways over the

748   course of a decision. More specifically, we assumed that weights on taste and health attributes

749   influence the overall drift rate (v), and that these weights should be egocentrically biased early on

750   during a decision but shift gradually after a delay to a new set of weights that reflect a

751   participant's assumptions about the preferences of their partner after deliberation. We compared

752   this model to a nested model in which, when choosing for others, participants simply begin at the

753   outset with a set of weights that reflect their assumptions about the other person's preferences,

754   with no delay or gradual adjustment process (see Methods for details). Remarkably, for the

755   *Similar* condition, the nested model with no time-varying parameters had a lower BIC value

756   combining over all subjects (1.2159×10^5) compared to the time-varying model (1.2189×10^5),

757   as well as a lower BIC value for 36 out of 38 individual subjects. Conclusions were largely

758   similar using the more liberal Akaike Information Criterion (AIC) instead of BIC. We arrived at

759   identical conclusions when examining choices for the *Dissimilar* other (total BIC of the simple

760   model = 1.1487×10^5, total BIC of the time-varying model = 1.1518×10^5).

761   Having shown that a simple DDM provided a more parsimonious fit to the data, we then

762   sought to determine how the values of different model parameters might change as a function of

763   choices for *Own Self, Similar,* and *Dissimilar* others. Specifically, we implemented a multi-

764   attribute version of the DDM with five parameters: weights on the taste and health attribute in

765   the drift rate (v), threshold for choice (a), starting point bias (z), and non-decision time. We fit

766   four different versions of the DDM to the data, in which drift rate, threshold, and starting point

bias were allowed to vary depending on the choice recipient (Table 1). The best-fitting model, as

assessed by both lower DIC values and lower MSE (M2; Table 1) suggested that, as expected,

weights on health and taste varied significantly by recipient. On average, participants weighted

both the health and taste attributes more similarly to themselves for the Similar individual than

for the Dissimilar individual (Table 2). However, in all cases there were significant pairwise

differences between attribute weights for different recipients. Taste ratings were weighted

highest for *Own* self, somewhat less for the *Similar* other, and not at all for the *Dissimilar* other

(all comparisons: 100% of the difference in posteriors > 0, i.e., all *P*-values = .000). Health

ratings were weighted highest for *Dissimilar*, significantly less for the *Similar* other, and least for

Own self (all comparisons significantly different, all *P* = .000).

Although weights on taste and health attributes differed significantly on average during

choices for both *Similar* and *Dissimilar* others compared to *Own* self, most models of choice

assume that participants also show egocentric biases, using their own preferences when making

choices for others (e.g., Devaine and Daunizeau, 2017; Tarantola et al., 2017). To test this

possibility, we theorized that if people do use their own preferences to some degree when

choosing for others, then individual differences in the weights estimated for Taste and Health

attributes in *Own* choices should predict the weights estimated for these attributes when choosing

for others, particularly when those preferences are relevant to the choice at hand. This prediction

was robustly confirmed. Individual weights on taste for one's *Own* self correlated strongly with

weights on taste for the *Similar* other (r_{36} = .58, *P* = .0002) but not for the *Dissimilar* other (r_{36} =

.07, *P* = .66). Individual weights on health for one's *Own* self correlated with weights for both

the *Similar* other (r_{36} = .57, *P* = .0002) and *Dissimilar* other (r_{36} = .48, *P* = .003). Thus, our best-

fitting model strongly supports the existence of an egocentric bias when making choices for

others.

Intriguingly, the best-fitting model also suggested significant variation in the threshold

parameter *a* as a function of choice recipient. Participants adopted greater caution when choosing

for others compared to themselves, with the highest threshold associated with choosing in the

Similar other condition. We speculate that these thresholds are adjusted to accommodate greater

uncertainty about the appropriate choice, and that this uncertainty may have been highest for the

Similar other, a point we return to in the Discussion. In contrast to attribute weights and

threshold, starting point (i.e. response bias) did not significantly differ from an unbiased value of

0.5 (11.9% of posterior > 0.50, i.e., *P* = .119) and was similar for all recipients.

To confirm the ability of the DDM to successfully capture both observed choice and RT

data, posterior predictive simulations (Wiecki et al., 2013) were generated using 100 randomly

selected samples from the posterior, effectively generating 100 synthetic datasets. Posterior

predictive checks using this simulated data confirmed the ability of the model to recreate

acceptance rates and RTs at both the group and individual level. Pearson correlations between

the true data and synthetic data for participant-level average data were for high for both

acceptance rates (*Own*: 0.863, *Similar*: 0.750, *Dissimilar*: 0.755) and RT (*Own*: 0.934, *Similar*:

0.921, *Dissimilar*: 0.942). Importantly, convergence statistics suggested stable parameter

estimates across all parameters in the hierarchical model (Table 2).

Combined ERP-model results

We next sought to validate our model not only through behavior, but by linking specific

ERP components to specific model parameters. We predicted that if value signals in the VMPFC

measured on-line during decision making between 500-650ms represent the most proximal input

into the evidence accumulation process, fluctuations in this signal should be directly related to

variation in the model-estimated influence of taste and health on the drift rate, *even after*

accounting for behavioral ratings collected after the fact. To test this prediction, we entered trial-

by-trial stimulus-locked ERP data from our SOIs and 500-650 ms time window of interest

(Figure 6A) into the M2 specification for the DDM, interacted with both Health and Taste

ratings. Note that stimulus-locked signals in the VMPFC were identified based on their

association with health and taste ratings collected independently of the choice, and are here

assumed to be an *input* into the accumulation process, and not an output of it.

As predicted, during choices for both *Own* self and *Similar* other, the amplitude of the

ERP value response predicted a significantly higher influence of Taste on the drift rate when

choosing for *Own* self and *Similar* other (Figure 6B, 100% of the posteriors for the interaction >

0, i.e., *P* = .000), but not when choosing for the *Dissimilar* other (*P* = .380). *Own* and *Similar*

Taste*ERP effects were not significantly different from each other (*Own* > *Similar*, P=.118), but

were both significantly greater than *Dissimilar* (*P* = .000). By contrast, the amplitude of the ERP

response significantly enhanced the influence of the Health attribute when choosing for the

Dissimilar other (*P* = .000), and this effect was significantly greater than for *Own* (P=.001) or

Similar (*P* = .000) choices (Figure 6C). Notably, the addition of parameters reflecting ERP

activity to the drift rate did not substantially alter the parameter estimates derived from

behavioral data (Table 3), suggesting that the neural data provide an additional, unique source of

information to our computational model. These results strongly support the idea that VMPFC

value signals from 500-650ms contribute to choice by influencing the accumulation of attribute

evidence toward a choice.

If attribute representations in the VMPFC contribute to evidence accumulation, shifting

to represent preferences of the choice recipient, what drives changes in those attribute

representations, particularly during choices for the *Dissimilar* other? Based on previous research

implicating TPJ and STS in directing VMPFC value integration during social decision (e.g., Hare

et al., 2010), we speculated that the ERP response for *Dissimilar* choices from 350-400 ms post-

stimulus may play a role in perspective taking and attribute weighting. If so, the strength of this

response across individuals should predict individual differences in alteration of the weights on

taste and/or health. To test this hypothesis, we computed the mean differences in the amplitude

of this response for *Dissimilar – Own* and *Similar – Own*, and correlated this difference with

differences in taste and health weights for the same contrast. Consistent with the idea that this

response may serve to inhibit the use of egocentric preferences, larger ERP amplitude from 350-

400 ms across participants significantly predicted reduced weighting on taste for the *Dissimilar*

recipient (Spearman's rho = -.41, P = .01). No other correlations were significant, suggesting a

specific role for this signal in reducing egocentric use of taste preferences.

We next sought to use our computational model to understand the nature of the response-

locked signals localized to the IPS, which showed the largest difference in signal for *Similar*

others (Figure 6D). Notably, applying our computational model to the behavioral data suggested

that, rather than resulting from serial correction mechanisms, longer RTs on average when

choosing for others could result in part from the adoption of different response thresholds

relative to the self, particularly in the case of the *Similar* other (Figure 6E). If so, we would

predict that response-locked ERPs localized to the IPS may contribute to adjusting the *response*

threshold, rather than correcting egocentric value signals.

Therefore, we directly tested whether this neural response-locked component influenced

the threshold parameter by entering the trial-by-trial ERP data from the response-locked

posterior SOIs and –300 to –180 ms time window of interest into the M2 specification for the

DDM, interacted with the response threshold. Results confirmed a significant relationship

between neural response in the IPS and the height of the response threshold (Figure 6F).

Moreover, adding this regressor improved model fit (DIC = 41421.1, compared to DIC= 41625.6

for an equivalent to M2 with the same set of trials used in the response-locked ERP version of

M2). Importantly, the estimate of the ERP regressor was strongly positive (P = .000), with no

significant interaction as a function of recipient. Although the polarity of the observed ERP

signal depends on a variety of factors including reference electrode, sensor location, and cortical

anatomy, the positive influence of this ERP component on the barrier coefficient is in line with

the more positive amplitude observed in the response-locked data when choosing for the *Similar*

other compared to the other two conditions.

Simulation exercise: RTs for same and different choices

Above, we demonstrate that the best-fitting parameters of a simple weighted-integration,

constant-value DDM can account for overall choice and RT patterns, and can be linked to

specific ERP components. Notably, this model supports the idea of egocentric biases, but does

not include a late-acting mechanism for adjusting preferences when choice for self and similar or

dissimilar others diverge. This contrasts with dual-process models such as anchoring-and-

adjustment, which are primarily supported by behavioral and RT data. We thus asked whether

our model could generate the RT patterns typically associated with an anchoring-and-adjustment

mechanism: namely, longer RTs when choices for Similar others diverge from choices for

oneself. To do this, we generated 160,000 simulated food choices for each recipient (*Own*,

Similar, *Dissimilar*) based on the 16 possible combinations of health and taste ratings. Then, for

each pairing of recipients (i.e., *Own* vs. *Similar*, *Own* vs. *Dissimilar*, *Similar* vs. *Dissimilar*), we

determined how often foods with each combination of taste and health rating led to similar or

different simulated choices (Figure 7), as well associated RTs. All statistical comparisons of the

simulated RTs were performed using Bayesian analysis incorporating MCMC estimation to

generate distributions of likely means and standard deviations (Kruschke, 2013). A *P*-value of

zero thus represents completely non-overlapping simulated distributions.

As expected, model simulations with the fitted parameters suggested that choices for

Own self and *Similar* other agree more frequently (68% of simulated choices) than for *Dissimilar*

other (52% agreement). More importantly, the simulated data also clearly replicate the RT

patterns observed both in previous work and in the present study (Figure 7A, top). When

comparing decisions for the *Similar* recipient to one's *Own* choices, RTs were considerably

faster for same versus different choices (*P* = .000). When comparing decision for *Dissimilar*

other to one's *Own* choices, RTs were also on average faster for same versus different choices,

although the differences were notably smaller (*P* = .073). Finally, when comparing choices for

one's *Own* self to decisions for others, we replicated the novel observation that decisions for the

self that result in the same response as that made for similar others *also* tend to be made faster

than choices for the self that differ (P = .000).

To provide additional insight into *when* choices converge or diverge, and why these are

consistently associated with different RTs, we compared the projected value of a food for two

given recipients to the likelihood that the model simulations make different choices about that

food (Figure 7B). We divided foods by the sixteen possible combinations of health and taste

903   ratings (e.g., health = 3 and taste = 2). Using health and taste weights derived from model M2,

904   we mapped the projected value of the food versus the percentage of different choices. As

905   expected, this analysis shows that the values of different foods fall closer to the diagonal when

906   comparing choices for one's *Own* self to a *Similar* other, suggesting that these values are more

907   tightly related (Figure 7B, left). In this case, choices diverge more frequently for options with

908   intermediate overall values (i.e., ratings of Weak No or Weak Yes on both taste and health

909   attributes vs. Strong No or Strong Yes), largely due to noisier choices in the face of indifference.

910   In contrast, when comparing choices made for *Own* self and a *Dissimilar* other (Figure 7B,

911   middle), the values of the food are less correlated, and a greater percentage of divergent choices

912   are observed at the extremes (e.g., very unhealthy but very tasty, or vice versa), due to the

913   differences in attribute weights. Divergent choices in this case are also less likely to be errors.

914   Next we examined the extent to which observed patterns of choice divergence correspond

915   to our model predictions (Figure 7C). We first used multiple regression to estimate the

916   coefficients on health and taste for choices made in the *Own*, *Similar*, and *Dissimilar* conditions,

917   separately for each subject. From these coefficients, we estimated the overall decision value for

918   each subject of each food in each condition. Then, for each of the 16 combinations of health and

919   taste ratings, we calculated the average decision value across all subjects for that combination,

920   separately for each condition. Finally, we also calculated the percentage of the time that choices

921   diverged for two recipients, separately for each of the 16 combinations. As can be seen from

922   Figure 7C, the data hew closely to the simulated predictions. Specifically, there is a strong

923   correlation between the value for one's *Own* self and the value for *Similar* other, and the largest

924   difference between choices for *Own* and *Similar* occur for values close to 0 (Figure 7C, left). In

925   contrast, when comparing values and choices for one's *Own* self and the *Dissimilar* other, the

most divergent choices occur at the extremes of conflict between health and taste (Figure 7C,

middle). Comparison of choices for *Similar* and *Dissimilar* lie in between (Figure 7C, right).

Thus, our model explains the longer RTs we observed when making different choices for

similar others, compared to dissimilar others. Put simply, in this paradigm people choose

differently for similar others in the same cases where they would be less certain what to choose

for *themselves*. Our simulations suggest that the extra deliberation time and divergent choice in

these trials emerges organically from increased uncertainty within a single decision process,

despite giving the appearance of resulting from a serial, slow-to-activate corrective process.

Discussion

To what extent do decisions for oneself and others rely on shared neurocomputational

mechanisms versus recruiting additional slow or deliberative mechanisms (Epley et al., 2004;

Tamir and Mitchell, 2013)? Do increases in response time for others reflect effortful correction

or uncertainty within a process of stochastic evidence accumulation? Here we exploited the high

temporal precision of ERP and the power of computational model fitting (Ruff and Fehr, 2014;

Crockett, 2016) to generate novel insights into these important questions.

Consistent with previous work (Nicolle et al., 2012; Janowski et al., 2013), our results

strongly support the existence of a shared value integration process for self and others, and

further suggest that this process follows similar temporal dynamics. Neural value signals for

other recipients emerged within the same temporal window as those for oneself, approximately

500-650 ms after stimulus onset and localized to regions including VMPFC. Importantly,

however, these value signals represented taste and health attributes differently depending on the

decision context, in line with previous data on dietary self-control (Harris et al., 2013).

Moreover, we demonstrated a link between trial-level fluctuations in the ERP value signal and

trial-by-trial differences in the process of evidence accumulation associated with each recipient.

Whereas VMPFC signals promoted taste considerations when deciding for oneself or the similar

other, these same signals promoted health attributes when deciding for the dissimilar, healthy

eater. Notably, these signals emerged in the stimulus-locked data more than 400 ms prior to the

average response time, suggesting that they represent an input into brain systems associated with

choice selection (Hare et al., 2011) rather than directly implementing accumulation-to-bound and

choice at the motor level. However, in light of previous work linking VMPFC response to choice

selection processes (Hunt et al., 2012; Strait et al., 2014), as well as other data demonstrating

rapid interactions between VMPFC and sensorimotor systems (Harris and Lim, 2016), further

research will be necessary to fully disentangle the relationship between ERP value signals and

evidence accumulation.

This shared VMPFC mechanism might also explain, in part, the robust and consistent

evidence for egocentric biases when choosing for others (Ross et al., 1977; Devaine and

Daunizeau, 2017; Tarantola et al., 2017). In our study, we found some evidence that people use

their own preferences to guide choices for others, particularly when those preferences may be

relevant. One's own weights on *both* taste and health predicted weights used when choosing for a

similar other, whereas when choosing for a dissimilar, healthy eater, only one's own health

preferences predicted choice. Thus, we find not only that people use their own preferences, but

also that they do so selectively based on inferences about the intended recipient.

Our results also support the use of additional perspective-taking mechanisms, particularly

when deciding for people with different preferences from one's own. We observed an ERP

component specific to choosing for the *Dissimilar* recipient from 350 to 400 ms after stimulus

onset, just before the time window associated with stimulus valuation. This signal was localized

to posterior temporal areas near the temporoparietal junction (TPJ), a region previously

implicated in various aspects of social cognition, including suppression of egocentric biases

(Silani et al., 2013), perspective taking (Saxe, 2006; Tusche et al., 2016), and pro-social behavior

(Morishima et al., 2012; Hutcherson et al., 2015). However, the timing of this response, as well

as the failure of time-varying egocentrically-biased computational models to better account for

choice and RT patterns, are both inconsistent with the idea that such perspective-taking

mechanisms activated slowly, *after* the emergence of a default self-centered bias (Epley et al.,

2004; Tamir and Mitchell, 2013).

Nonetheless, we do find evidence for late-acting, response-related control mechanisms.

We observed a comparatively late ERP signal differentiating choices by recipient from –300 ms

before response. Whereas the stimulus-locked component showed an increased response

specifically for the *Dissimilar* recipient, this neural activity predominantly distinguished the

Similar condition. Yet, in contrast to the idea that this signal might be needed to correct or inhibit

egocentric values, our computational analyses linked it only to variation in the response

threshold for choice. What could be driving increases in response threshold for the similar

recipient? One possible factor could be choice uncertainty. In line with this idea, participants

took longer on average and had higher decision thresholds when choosing for the similar other,

suggesting the need for additional evidence accumulation relative to the other conditions.

Additionally, weights on taste were modestly but consistently lower for the similar other

compared to choices for one's self, while weights on health were slightly higher, suggesting that

participants may have "hedged" their choices where the similar other was concerned. These

results provide a different perspective on the role of controlled processing in self-other decision-

making. They suggest that some forms of controlled processing may influence choices for others

not by modifying value signals, but by raising the criterion for choice.

Given evidence of strong egocentric biases, rapid perspective-taking, and no

computational evidence for delayed adjustment, what then explains patterns of longer response

time when choosing differently from the self? Simulations performed using our combined

neurocomputational model suggested that choices for self and other can diverge either due to

differences in attribute weighting (as observed when making choices for the dissimilar other), or

simply due to noise in the process of evidence accumulation (as observed when making choices

for partners with similar preferences). In other words, trials where choices for self and similar

others diverge may sometimes be trials on which choices for the self alone might be inconsistent

from one instantiation to the next, due to ambivalent and noisy values. These will also tend to be

the choices with the longest RTs, for both self and others. Although our model underestimated

the observed RT differences somewhat, we suspect that the extra time may stem from conflict-

triggered increases in threshold at the single-trial level (Cavanagh et al., 2011). This effect would

tend to magnify the difference in RT beyond that predicted by a canonical DDM, in precisely

those trials where divergent choices are most likely to be observed. Taken together, these results

suggest that, at least in some decision scenarios, patterns of behavior previously associated with

the action of both anchoring and adjustment may be better explained simply by anchoring,

implemented in a stochastic decision system.

Note that these results do not argue against the basic idea of dual- or even multi-system

models of choice. If anything, our results highlight the importance of *both* perspective-taking

and response inhibition, and tie them to value integration and threshold computations,

respectively. Moreover, there may be important decision scenarios in which choices for others do

engage dissociable correction or perspective-taking mechanisms, operating at different

timescales (Epley et al., 2004; Evans, 2008). For example, our paradigm included no feedback.

In cases where a decision maker must integrate both general information (e.g., knowledge about

a person's culture, background, or similarity to oneself) and direct experience with another's

choices, we might expect an initial egocentric preference that is corrected based on learning and

memory (Devaine and Daunizeau, 2017; Tarantola et al., 2017). There may also be important

individual differences in the speed or strength of social cognitive mechanisms, which might

depend on the integrity of areas like the STS and TPJ. Our work highlights the utility of

computational modeling for determining when patterns of choice, RT, and neural data that

appear on their face to support dual-process models are instead more consistent with a single

value integration mechanism (as observed in our study) and when additional computational

mechanisms might be necessary to fully account for behavior.

Careful consideration of the timing of these processes also generates a novel prediction

regarding the effects of time pressure versus cognitive load in social decision scenarios. Our data

suggest that making accurate choices for people with divergent preferences relies more on early

perspective-taking mechanisms, occurring from 300 to 500 ms post-stimulus onset in TPJ, while

making accurate choices for partners with uncertain preferences relies more on later response

threshold mechanisms localized to posterior cingulate cortex. If this is indeed the case,

manipulations using time pressure or cognitive load may sometimes have quite different effects

on social decision-making. Time pressure, which in perceptual choice has been tied to reductions

in response threshold (Forstmann et al., 2010), might be expected to result in reduced accuracy

only when others' preferences are uncertain. In contrast, cognitive load may disrupt effortful

perspective-taking mechanisms, resulting in stronger reductions in accuracy when preferences

differ from the self.

Our work provides the first computational account of decision making capable of

explaining the full pattern of choice, response times and neural dynamics when choosing for

others, in a context where preferences are well-specified but can differ among individuals. Future

studies will need to examine choices for others in different contexts and with different

information. We believe that the unique combination of neural and computational modeling

presented here provides a powerful and essential tool for this research, and will foster exciting

new avenues for exploring how we choose for ourselves and others.

1049

Author Contributions

1051 A.H. and C.A.H. designed the experiment. A.H. collected the data. A.H., J.A.C., and C.A.H.

1052 analyzed the data. A.H., J.A.C., and C.A.H. interpreted the results and wrote the paper.

References

1053

1054

Andrews-Hanna JR, Reidler JS, Sepulcre J, Poulin R, Buckner RL (2010) Functional-anatomic

fractionation of the brain's default network. Neuron 65:550-562.

Apps MA, Rushworth MF, Chang SW (2016) The Anterior Cingulate Gyrus and Social

Cognition: Tracking the Motivation of Others. Neuron 90:692-707.

Bartra O, McGuire JT, Kable JW (2013) The valuation system: a coordinate-based meta-analysis

of BOLD fMRI experiments examining neural correlates of subjective value.

Neuroimage 76:412-427.

Belouchrani A, Abed-Meraim K, Cardoso J-F, Moulines E (1997) A blind source separation

technique using second-order statistics. IEEE Transactions on Signal Processing 45:434-

444.

Berkman ET, Hutcherson CA, Livingston JL, Kahn LE, Inzlicht M (2017) Self-Control as

Value-Based Choice. Current directions in psychological science 26:422-428.

Cavanagh JF, Wiecki TV, Cohen MX, Figueroa CM, Samanta J, Sherman SJ, Frank MJ (2011)

Subthalamic nucleus stimulation reverses mediofrontal influence over decision threshold.

Nat Neurosci 14:1462-1467.

Clithero JA, Rangel A (2014) Informatic parcellation of the network involved in the computation

of subjective value. Social cognitive and affective neuroscience 9:1289-1302.

Cohen MX, Cavanagh JF, Slagter HA (2011) Event-related potential activity in the basal ganglia

differentiates rewards from nonrewards: temporospatial principal components analysis

and source localization of the feedback negativity: commentary. Hum Brain Mapp

32:2270-2271.

Crockett MJ (2016) How Formal Models Can Illuminate Mechanisms of Moral Judgment and

Decision Making. Current directions in psychological science 25:85-90.

Delorme A, Makeig S (2004) EEGLAB: an open source toolbox for analysis of single-trial EEG

dynamics including independent component analysis. J Neurosci Methods 134:9-21.

Delorme A, Sejnowski T, Makeig S (2007) Enhanced detection of artifacts in EEG data using

higher-order statistics and independent component analysis. Neuroimage 34:1443-1449.

Devaine M, Daunizeau J (2017) Learning about and from others' prudence, impatience or

laziness: The computational bases of attitude alignment. PLoS Comput Biol

13:e1005422.

Epley N, Keysar B, Van Boven L, Gilovich T (2004) Perspective taking as egocentric anchoring

and adjustment. J Pers Soc Psychol 87:327-339.

Evans JSB (2008) Dual-processing accounts of reasoning, judgment, and social cognition. Annu

Rev Psychol 59:255-278.

Forstmann BU, Anwander A, Schafer A, Neumann J, Brown S, Wagenmakers EJ, Bogacz R,

Turner R (2010) Cortico-striatal connections predict control over speed and accuracy in

perceptual decision making. Proc Natl Acad Sci U S A 107:15916-15920.

Friston K, Harrison L, Daunizeau J, Kiebel S, Phillips C, Trujillo-Barreto N, Henson R, Flandin

G, Mattout J (2008) Multiple sparse priors for the M/EEG inverse problem. Neuroimage

39:1104-1120.

Gelman A, Rubin DB (1992) Inference from iterative simulation using multiple sequences.

Statistical science:457-472.

Grueschow M, Polania R, Hare TA, Ruff CC (2015) Automatic versus choice-dependent value

representations in the human brain. Neuron 85:874-885.

1099   Hare TA, Camerer CF, Rangel A (2009) Self-control in decision-making involves modulation of

1100   the vmPFC valuation system. Science 324:646-648.

1101   Hare TA, Camerer CF, Knoepfle DT, Rangel A (2010) Value computations in ventral medial

1102   prefrontal cortex during charitable decision making incorporate input from regions

1103   involved in social cognition. J Neurosci 30:583-590.

1104   Hare TA, Schultz W, Camerer CF, O'Doherty JP, Rangel A (2011) Transformation of stimulus

1105   value signals into motor commands during simple choice. Proc Natl Acad Sci U S A

1106   108:18120-18125.

1107   Harris A, Lim SL (2016) Temporal Dynamics of Sensorimotor Networks in Effort-Based Cost-

1108   Benefit Valuation: Early Emergence and Late Net Value Integration. J Neurosci 36:7167-

1109   7183.

1110   Harris A, Hare T, Rangel A (2013) Temporally dissociable mechanisms of self-control: early

1111   attentional filtering versus late value modulation. J Neurosci 33:18917-18931.

1112   Harris A, Adolphs R, Camerer C, Rangel A (2011) Dynamic construction of stimulus values in

1113   the ventromedial prefrontal cortex. PLoS One 6:e21074.

1114   Henson RN, Mattout J, Singh KD, Barnes GR, Hillebrand A, Friston K (2007) Population-level

1115   inferences for distributed MEG source localization under multiple constraints: application

1116   to face-evoked fields. Neuroimage 38:422-438.

1117   Hunt LT, Kolling N, Soltani A, Woolrich MW, Rushworth MF, Behrens TE (2012) Mechanisms

1118   underlying cortical activity during value-guided choice. Nature neuroscience 15:470-476,

1119   S471-473.

1120   Hutcherson CA, Bushong B, Rangel A (2015) A Neurocomputational Model of Altruistic Choice

1121   and Its Implications. Neuron 87:451-462.

Janowski V, Camerer C, Rangel A (2013) Empathic choice involves vmPFC value signals that

are modulated by social processing implemented in IPL. Social cognitive and affective

neuroscience 8:201-208.

Jung TP, Makeig S, Humphries C, Lee TW, McKeown MJ, Iragui V, Sejnowski TJ (2000)

Removing electroencephalographic artifacts by blind source separation.

Psychophysiology 37:163-178.

Krajbich I, Bartling B, Hare T, Fehr E (2015) Rethinking fast and slow based on a critique of

reaction-time reverse inference. Nat Commun 6:7455.

Kruschke JK (2013) Bayesian estimation supersedes the t test. J Exp Psychol Gen 142:573-603.

Litt A, Plassmann H, Shiv B, Rangel A (2010) Dissociating Valuation and Saliency Signals

during Decision-Making. Cereb Cortex.

Litvak V, Friston K (2008) Electromagnetic source reconstruction for group studies. Neuroimage

42:1490-1498.

Morishima Y, Schunk D, Bruhin A, Ruff CC, Fehr E (2012) Linking brain structure and

activation in temporoparietal junction to explain the neurobiology of human altruism.

Neuron 75:73-79.

Nicolle A, Klein-Flugge MC, Hunt LT, Vlaev I, Dolan RJ, Behrens TE (2012) An agent

independent axis for executed and modeled choice in medial prefrontal cortex. Neuron

75:1114-1121.

Picton TW, Bentin S, Berg P, Donchin E, Hillyard SA, Johnson R, Jr., Miller GA, Ritter W,

Ruchkin DS, Rugg MD, Taylor MJ (2000) Guidelines for using human event-related

potentials to study cognition: recording standards and publication criteria.

Psychophysiology 37:127-152.

Plassmann H, O'Doherty J, Rangel A (2007) Orbitofrontal cortex encodes willingness to pay in

everyday economic transactions. J Neurosci 27:9984-9988.

Rangel A, Clithero J (2013) The computation of stimulus values in simple choice. In:

Neuroeconomics: Decision Making and the Brain (Glimcher PW, Ferh E, eds): Academic

Press.

Ratcliff R, McKoon G (2008) The diffusion decision model: theory and data for two-choice

decision tasks. Neural Comput 20:873-922.

Ratcliff R, Smith PL, Brown SD, McKoon G (2016) Diffusion decision model: current issues

and history. Trends in cognitive sciences 20:260-281.

Ross L, Greene D, House P (1977) The "false consensus effect": An egocentric bias in social

perception and attribution processes. Journal of experimental social psychology 13:279-

301.

Ruff CC, Fehr E (2014) The neurobiology of rewards and values in social decision making. Nat

Rev Neurosci 15:549-562.

Saxe R (2006) Uniquely human social cognition. Curr Opin Neurobiol 16:235-239.

Silani G, Lamm C, Ruff CC, Singer T (2013) Right supramarginal gyrus is crucial to overcome

emotional egocentricity bias in social judgments. J Neurosci 33:15466-15476.

Smith PL, Ratcliff R (2004) Psychology and neurobiology of simple decisions. Trends Neurosci

27:161-168.

Spiegelhalter DJ, Best NG, Carlin BP, Van Der Linde A (2002) Bayesian measures of model

complexity and fit. Journal of the Royal Statistical Society: Series B (Statistical

Methodology) 64:583-639.

Strait CE, Blanchard TC, Hayden BY (2014) Reward value comparison via mutual inhibition in

ventromedial prefrontal cortex. Neuron 82:1357-1366.

Strombach T, Weber B, Hangebrauk Z, Kenning P, Karipidis II, Tobler PN, Kalenscher T (2015)

Social discounting involves modulation of neural value signals by temporoparietal

junction. Proceedings of the National Academy of Sciences 112:1619-1624.

Tamir DI, Mitchell JP (2010) Neural correlates of anchoring-and-adjustment during mentalizing.

Proc Natl Acad Sci U S A 107:10827-10832.

Tamir DI, Mitchell JP (2013) Anchoring and adjustment during social inferences. J Exp Psychol

Gen 142:151-162.

Tang AC, Sutherland MT, McKinney CJ (2005) Validation of SOBI components from high-

density EEG. Neuroimage 25:539-553.

Tarantola T, Kumaran D, Dayan P, De Martino B (2017) Prior preferences beneficially influence

social and non-social learning. Nature Communications 8:817.

Tusche A, Hutcherson CA (2018) Cognitive regulation alters social and dietary choice by

changing attribute representations in domain-general and domain-specific brain circuits.

eLife 7:e31185.

Tusche A, Böckler A, Kanske P, Trautwein F-M, Singer T (2016) Decoding the charitable brain:

empathy, perspective taking, and attention shifts differentially predict altruistic giving.

Journal of Neuroscience 36:4719-4732.

Uriguen JA, Garcia-Zapirain B (2015) EEG artifact removal-state-of-the-art and guidelines. J

Neural Eng 12:031001.

1188   Volz LJ, Welborn BL, Gobel MS, Gazzaniga MS, Grafton ST (2017) Harm to self outweighs

1189   benefit to others in moral decision making. Proceedings of the National Academy of

1190   Sciences:201706693.

1191   Wiecki TV, Sofer I, Frank MJ (2013) HDDM: Hierarchical Bayesian estimation of the Drift-

1192   Diffusion Model in Python. Front Neuroinform 7:14.

1193

 Figure Legends

 Figure 1. Social food choice task. (A) Experimental session. In Part 1, hungry participants with

 unrestricted diets were introduced to two partners, and provided taste and health ratings for the

 foods used in the experiment. Then, in Part 2, participants made food choices for themselves and

 the partners while their brain activity was measured with EEG. Participants knew that their

 choices mattered because a single trial was randomly selected and implemented for each

 recipient in Part 3. (B) Sample statements from the *Similar* (top) and *Dissimilar* (bottom)

 partners in the experiment. (C) Sample stimuli and screens from the decision task.

 Figure 2. Behavioral results. (A) Percentage of healthy choices for each recipient. (B) Average

 observed RT by recipient. (C-E) Observed RT for trials separated on the basis of whether, given

 the same food option, the decision maker chose the same for (C) *Own* vs. *Similar*, (D) *Own* vs.

 Dissimilar, and (E) *Dissimilar* vs. *Similar*. Thus, *Own-Similar*:Same Response reflects RT for

 trials in which the choice was for *Own* self, and the response was the same as for the *Similar*

 other, whereas *Own-Similar*:Different Response reflects RTs on those trials where the response

 was different from the comparable choice for the *Similar* other; and likewise for the other

 comparisons.

 Figure 3. ERP analysis of stimulus value integration by recipient. (A) Heat map of significant *P*

 values associated with stimulus value, showing significant effects from 500 to 650 ms (green

 box) and 700 to 850 ms (blue box) after stimulus onset. (B) Source reconstructions from 500 to

 650 ms (green) and 700 to 850 ms (blue) overlaid on a representative brain image. Particularly

during the earlier 500-650 ms window, stimulus value activity was localized to regions including

VMPFC (circled). Inset, top: Spherical masks based on peak coordinates from three

neuroimaging studies [blue (Plassmann et al., 2007), magenta (Hare et al., 2009), cyan (Litt et

al., 2010)]. Inset, bottom: Source localization of stimulus value from approximately 450 to 600

ms post-stimulus onset in two ERP studies [red: (Harris et al., 2013), yellow: (Harris and Lim,

2016)]. (C) Stimulus value integration by recipient. Topographic scalp distribution (left) and

average waveforms for the linear ordering of stimulus value (red: Strong No; orange: Weak No;

cyan: Weak Yes; green: Strong Yes) in the 500-650 ms window (shaded green box) and 700-850

ms window (shaded blue box), plotted separately for each recipient (*Own*: solid, *Similar*: dashed;

Dissimilar: dotted). (D) Comparison of scalp topography at 550 ms (left) and 800 ms (right)

post-stimulus for the main effect of stimulus value (top), the interaction of stimulus value with

Similar recipient (middle) and the interaction of stimulus value with *Dissimilar* recipient

(bottom) revealed significant reductions in stimulus value signals for the two other recipients

during the late window, in line with average waveform data in (C).

Figure 4. ERP analysis of attribute weighting by recipient. (A) Scalp topography during time

window of interest from 500 to 650 ms post-stimulus revealed differences in neural weighting of

taste ratings (left) and health ratings (middle) by recipient. Sensors of interest (SOI) were

identified by taking the conjunction of sensors showing significant ERP activity for *Similar* and

Dissimilar in the Taste – Health comparison (black box, right). (B) Average waveforms

associated with the linear ordering of taste (left) and health (right) plotted separately for each

recipient (*Own*: solid; *Similar*: dashed; *Dissimilar*: dotted). Orange: taste; Green: health. (C-D)

Linear contrast weights for taste (C) and health (D) as a function of recipient.

1241   **Figure 5.** Differences in average ERP waveforms by recipient identity. (A) Heat map of

1242   significant *P* values showing stimulus-locked regression results for the main effects of *Similar*

1243   (left) and *Dissimilar* (right). Significant effects were visible for the *Dissimilar* recipient, but not

1244   the *Similar* recipient, at time windows including 350 to 400 ms after stimulus onset (green box).

1245   (B) Scalp topography (left) and average waveforms (right) associated with choice recipient

1246   identity (*Own* self: cyan, *Similar* other: blue, *Dissimilar* other: orange) 350-400 ms post-stimulus

1247   onset. Inset: Source reconstruction from 350-400 ms post-stimulus overlaid on a representative

1248   brain image localized this response to regions including the temporoparietal junction (TPJ) and

1249   superior temporal sulcus (STS). (C). Heat map of significant *P* values showing response-locked

1250   regression results for the main effects of *Similar* (left) and *Dissimilar* (right). Significant effects

1251   were visible for the *Similar* recipient, but not *Dissimilar* recipient, approximately 300ms to 180

1252   ms prior to the response (green box). Later effects in the Dissimilar condition coincide with

1253   motor activity related to initiation of the key press response. (D) Scalp topography (left) and

1254   average waveforms (right) associated with choice recipient identity (*Own* self: cyan, *Similar*

1255   other: blue, *Dissimilar* other: orange). Inset: Source reconstruction from 300 to 180 ms prior to

1256   the response localized this differential response to regions including the intraparietal sulcus

1257   (IPS).

1258

1259   **Figure 6.** Hierarchical Bayesian parameter estimates of the influence of neural response on

1260   model parameters. (A-C) Trial-by-trial fluctuations in the ERP in sensors-of-interest (SOIs) for

1261   the value-related ERP from 500-650ms (A) were linked with significantly greater influence on

1262   the drift rate *v* of the taste attribute when choosing for *Own* self and *Similar* other (B) and the

1263   health attribute when choosing for the *Dissimilar* other (C), suggesting that this response relates

1264   to evidence accumulation in the computational model. (D-F) Trial-by-trial fluctuations in the

1265   response-locked ERP component (D) differentiated choices for the *Similar* other to a greater

1266   extent than *Dissimilar* or *Own* choices, consistent with computational model-fitting of the

1267   behavioral barrier parameter (E), and likewise demonstrated a significant influence on the barrier

1268   for response (F).

1269

1270   **Figure 7.** DDM simulations. (A) Simulations (N=10000) of RT data for same versus different

1271   choice using best-fitting specification M2. Trials are separated based on the same criteria

1272   described for observed data in Figure 2, with observed data (left) plotted next to predicted model

1273   RTs (right) for each combination of recipient. (B-C) Predicted (B) and observed (C) relationship

1274   between drift rates and percentage of different choices when comparing choices for two

1275   recipients, simulated separately for each of the 16 possible combinations of health and taste

1276   rating. Proximity of the dots to the diagonal reflects similarity of food values for two recipients,

1277   and size and color of dots are coded according to the percentage of different choices. Additional

1278   details are provided in the main text.

1279   **Table 1: DDM Specifications Summary**

Parameter w/ Trialtype	Model#	DIC	MSE Choice	MSE RT Yes	MSE RT No
v	M1	46384.2	0.0137	0.0537	0.0694
v,a	M2	46318.6	0.0135	0.0532	0.0689
v,z	M3	46522.1	0.0137	0.0559	0.0655
v,a,z	M4	46415.6	0.0137	0.0538	0.0682

1280   **Note:** v = drift rate, a = threshold, z = starting point.

 Table 2: DDM posterior estimates and convergence for Model M2

Parameter	Mean	Stdev
Drift (v), Intercept	-1.982	0.055
Drift (v), HealthOwn	0.062	0.011
Drift (v), HealthSimilar	0.183	0.010
Drift (v), HealthDissimilar	0.660	0.011
Drift (v), TasteOwn	0.722	0.011
Drift (v), TasteSimilar	0.665	0.010
Drift (v), TasteDissimilar	0.007	0.011
Barrier (a), Intercept	2.006	0.047
Barrier (a), Similar	0.125	0.015
Barrier (a), Dissimilar	0.049	0.015
Starting point (z)	0.493	0.006
NonDecisionTime	0.357	0.026
Convergence	**Mean**	**Stdev**
$\hat{R}$	1.0002	0.0002

1282 **Note:** Statistics for parameter estimates reflect the mean and standard deviation of the N=10000
1283 posterior samples of group-level parameters.

 Table 3: DDM posterior estimates and convergence for Model M2 with stimulus-locked
 ERP data.

Parameter	Mean	Stdev
Drift (v), Intercept	-2.004	0.057
Drift (v), ERP	-0.049	0.010
Drift (v), ERP HealthOwn	0.000	0.005
Drift (v), ERP HealthSimilar	-0.003	0.004
Drift (v), ERP HealthDissimilar	0.017	0.004
Drift (v), ERP TasteOwn	0.028	0.004
Drift (v), ERP TasteSimilar	0.023	0.004
Drift (v), ERP TasteDissimilar	-0.001	0.004
Drift (v), HealthOwn	0.054	0.011
Drift (v), HealthSimilar	0.179	0.011
Drift (v), HealthDissimilar	0.672	0.011
Drift (v), TasteOwn	0.734	0.011
Drift (v), TasteSimilar	0.675	0.010
Drift (v), TasteDissimilar	-0.006	0.010
Barrier (a), Intercept	2.000	0.043
Barrier (a), Similar	0.118	0.016
Barrier (a), Dissimilar	0.043	0.016
Starting point (z)	0.494	0.006
NonDecisionTime	0.360	0.025
Convergence	**Mean**	**Stdev**
$\hat{R}$	1.0006	0.0010

 Note: Statistics for parameter estimates reflect the mean and standard deviation of the N=10000
 posterior samples of group-level parameters.

A

I. Set-Up	II. EEG	III. Outcome
• *Photo taken* • *Partner introductions* • *Taste/Health ratings*	*Decision (6 runs) for:* • *Own Self* • *Similar Partner* • *Dissimilar Partner*	*Receive random food based on decision*

B

Similar: No dietary restrictions

...Taste is my number one consideration...For me eating food is all about it tasting good.

Dissimilar: Self-identified healthy eater

...I don't eat anything with added sugars...I try to eat a lot of fruits and vegetables.

C

Sample Trial, Decision Task

Please choose for this person

Until response (max 4 s)

A Healthy Choices by Recipient

N = 38
± sem

% Healthy Choice

Own   Sim   Dissim

ns   **   **

B Mean Observed RT by Recipient

RT (s)

Own   Sim   Dissim

**   *   *

C Observed RT,
Own vs. Similar

RT (s)

Own   Similar

**   **

D Observed RT,
Own vs. Dissimilar

Own   Dissimilar

**   **

E Observed RT,
Dissimilar vs. Similar

Dissimilar   Similar

ns   **

△ Same Response   △ Different Response

A Stimulus Value, Permutation-Corrected

Sensor Location: Frontal, aTemporal, Central, Parietal, pTemporal, Occipital

Time Window (ms): 300, 600, 900, 1200

0.05 – 0

B

+8

VMPFC

$F \geq 100$

fMRI

ERP

C Stimulus Value x Recipient, Grand Average Waveform

550 ms

T Values: 5 to −5

Strong YES

Strong NO

Own

Sim

Dissim

0.5 µV

100 ms

D Scalp Topography

Stimulus Value
550 ms   800 ms

SV x Similar
550 ms   800 ms

SV x Dissimilar
550 ms   800 ms

A Scalp Topography, 500 to 650 ms post-stimulus

B Taste and Health by Recipient, 500 to 650 ms post-stimulus

A Recipient, Stimulus-Locked, Permutation-Corrected

Similar   Dissimilar

Sensor Location: Frontal, aTemporal, Central, Parietal, pTemporal, Occipital

Time Window (ms): 200, 400, 600

0.05 — 0

B Dissimilar Recipient, 350 to 400 ms post-stimulus

350 ms

Own
Similar
Dissimilar

+58

TPJ/STS

$F \geq 100$

0.5 µV

100 ms

C Recipient, Response-Locked, Permutation-Corrected

Similar   Dissimilar

Sensor Location: Frontal, aTemporal, Central, Parietal, pTemporal, Occipital

Time Window (ms): −360, −180, −30

0.05 — 0

D Similar Recipient, −300 to −180 ms pre-response

−240 ms

+33

IPS

$F \geq 100$

0.4 µV

100 ms

A ERP, 500 to 650 ms
post-stimulus

0.5 µV

100 ms

No ▮▮▮ ▮▮▮ Yes

B ERP Drift Coefficient, Taste

1800

Posterior Distribution

Own
Similar
Dissimilar

−0.02   0   0.02   0.04
Drift Coefficient

C ERP Drift Coefficient, Health

−0.02   0   0.02   0.04
Drift Coefficient

D ERP, −300 to −180 ms
pre-response

0.4 µV

100 ms

E Behavioral Barrier Coefficient

1800

Posterior Distribution

−0.05   0   0.05   0.1   0.15
Barrier Coefficient

F ERP Barrier Coefficient

0   0.01   0.02
Barrier Coefficient