The Unreasonable Effectiveness of Convolutional Neural Networks in Population

Genetic Inference

Lex Flagel[1,2], Yaniv Brandvain[2], and Daniel R. Schrider[3,*]

[1]Monsanto Company, Chesterfield, MO.

[2]Department of Plant and Microbial Biology, University of Minnesota, St. Paul, MN.

[3]Department of Genetics, University of North Carolina, Chapel Hill, NC.

*Corresponding author. Email: drs@unc.edu

ABSTRACT

Population-scale genomic datasets have given researchers incredible amounts of information

from which to infer evolutionary histories. Concomitant with this flood of data, theoretical and

methodological advances have sought to extract information from genomic sequences to infer

demographic events such as population size changes and gene flow among closely related

populations/species, construct recombination maps, and uncover loci underlying recent

adaptation. To date most methods make use of only one or a few summaries of the input

sequences and therefore ignore potentially useful information encoded in the data. The most

sophisticated of these approaches involve likelihood calculations, which require theoretical

advances for each new problem, and often focus on a single aspect of the data (e.g. only allele

frequency information) in the interest of mathematical and computational tractability. Directly

interrogating the entirety of the input sequence data in a likelihood-free manner would thus offer

a fruitful alternative. Here we accomplish this by representing DNA sequence alignments as

images and using a class of deep learning methods called convolutional neural networks (CNNs)

to make population genetic inferences from these images. We apply CNNs to a number of

evolutionary questions and find that they frequently match or exceed the accuracy of current

methods. Importantly, we show that CNNs perform accurate evolutionary model selection and

parameter estimation, even on problems that have not received detailed theoretical treatments.

Thus, when applied to population genetic alignments, CNN are capable of outperforming

expert-derived statistical methods, and offer a new path forward in cases where no likelihood

approach exists.

INTRODUCTION

Using genetic data to make inferences about the natural histories of populations represents a major goal of evolutionary research. As the ever-increasing throughput of DNA sequencing technologies makes the generation of large population genomic data sets more routine, researchers can leverage patterns of genetic variation across the genome to characterize the evolutionary forces at play (Hahn 2018). For example, advances have been made in identifying historical demographic events such as population size changes (Marth *et al.* 2004; Tennessen *et al.* 2012; Gazave *et al.* 2014) and genetic exchange between populations and species (Martin *et al.* 2013; Hellenthal *et al.* 2014; Sankararaman *et al.* 2014; Corbett-Detig and Nielsen 2017; Schrider *et al.* 2018). Population genomic analyses have also revealed the pervasive impact of selection on linked neutral polymorphism (Begun and Aquadro 1992; Begun *et al.* 2007; Langley *et al.* 2012; Elyashiv *et al.* 2016), both through positive selection (Maynard Smith and Haigh 1974; Kaplan *et al.* 1989) and purifying selection (Charlesworth *et al.* 1993). As the volume of population genomic data sets has increased, so too has the demand for powerful computational methods capable of using these data to learn about the fundamental evolutionary processes shaping genomic variation.

To meet this need, myriad statistical and computational tools have been devised to answer evolutionary questions using population genetic data. One particularly common paradigm, which predates the high-throughput sequencing revolution, is that of the population genetic summary statistic: a value (or sometimes a vector of values) designed to capture the information present in a sequence alignment of individuals from one or more populations. When a particular evolutionary phenomenon acts on a population it alters the shapes of genealogies, and this effect is manifest in the observed sequence alignment. For example, a population expansion will result in genealogies with longer branches near the leaves of the tree, which will manifest as an excess of rare alleles. Many summary statistics seek to uncover the signature of these genealogical skews through their effect on the alignment; e.g. Tajima's *D* will be negative following a recent expansion or recovery from a bottleneck (Tajima 1989; Simonsen *et al.* 1995). Ideally a summary statistic will only detect the signal of the evolutionary process it is being used to investigate, but in practice summary statistics are frequently confounded by other forces that may have similar effects on the shapes and/or sizes of genealogies. For example, Tajima's *D* is sensitive to positive selection as well as population size changes (Simonsen *et al.* 1995). Moreover,

such summary statistics do not capture all of the information present in the alignment. Thus a

major challenge of population genetic inference is to create methods that utilize as much

information from the input data as possible in order to maximize our ability to distinguish among

the numerous evolutionary processes that can give rise to an observed signal.

One approach researchers have adopted to address this challenge is to incorporate a

larger number of observations from the data into likelihood-based inference methods. However,

calculating likelihoods of population genomic data sets is often mathematically and

computationally intractable, and therefore such approaches often use composite likelihoods

which ignore the non-independence of observations (e.g. Hudson 2001; Nielsen *et al.* 2005). For

example, Nielsen et al.'s SweepFinder (2005), which examines allele frequencies at

polymorphisms flanking a focal region to determine whether that region has experienced a recent

selective sweep (Maynard Smith and Haigh 1974), treats each allele frequency as an independent

observation despite the partially shared evolutionary histories linked alleles experience. Another

drawback of most likelihood-based methods is that they generally compute the likelihood of only

a few features of the data (often only one), and therefore additional information that could

improve accuracy is ignored. For example, SweepFinder examines allele frequencies but ignores

linkage disequilibrium (LD), which is elevated in areas flanking the selected site (Kim and Nielsen

2004). Hidden Markov models (Hobolth *et al.* 2007; Boitard *et al.* 2009; Dutheil *et al.* 2009; Kern

and Haussler 2010), including those based on the sequential Markov coalescent (Li and Durbin

2011; Schiffels and Durbin 2014), have also proved effective at using population genetic

observations along a recombining chromosome to make evolutionary inferences.

More recently, population geneticists have begun to explore an alternative strategy of

using a large set of complementary summary statistics for model selection and parameter

estimation, an approach that often results in more powerful and robust inference (e.g. Lin *et al.*

2011; Pybus *et al.* 2015; Gao *et al.* 2016; Schrider and Kern 2016; Sheehan and Song 2016). Each

summary statistic seeks to measure a particular attribute of the genealogy, and one can thus

design a customized set of summary statistics to more fully represent the genealogical information

present in the sequence alignment. This view deploys summary statistics less for their individual

links to underlying theory, and more for their collective ability to perform pattern recognition.

The challenge then becomes extracting information about the underlying evolutionary processes

from the set of summary statistics. Two exciting approaches for dealing with this challenge that

have garnered increasing attention in recent years are approximate Bayesian computation (ABC;
reviewed in Beaumont 2010) and supervised machine learning (reviewed in Schrider and Kern
2018). Both of these approaches make use of suites of user-defined summary statistics and
training data generated under known parameters to identify reasonable evolutionary models and
parameterizations that could have generated the observed data. Here we focus on the supervised
machine learning approach, as it sets the scene for the convolutional neural networks described
below.

In the terminology of supervised machine learning, each summary statistic is called a
feature, and the full set of statistics used is called a feature vector. To use supervised machine
learning, a researcher must first obtain training data (often referred to as "labeled" data)—a set of
data points each summarized by a feature vector (the explanatory variables) accompanied by a
known outcome (the response variable). Next, a supervised machine learning algorithm is trained
to predict the outcome given the feature vector using the labeled training data. Thus, the
supervised machine learning technique automates the process of extracting information and
constructing rules from a set of summary statistics. Across many areas of research, supervised
machine learning techniques are fast replacing rules developed by human experts because they
are often more accurate (LeCun *et al.* 2015).

Supervised machine learning methods are increasingly being applied to numerous
problems in population genetics (Schrider and Kern 2018). In this context, labeled training data
are usually generated via population genetic simulation, an endeavor that has grown
considerably more feasible given recent improvements in simulation flexibility and efficiency (e.g.
Thornton 2014; Kelleher *et al.* 2016; Haller and Messer 2017; Kelleher *et al.* 2018). To date,
population genetic applications of machine learning include demographic inference (Pudlo *et al.*
2016; Sheehan and Song 2016), local ancestry inference (Schrider *et al.* 2018), inferring
recombination rates (Lin *et al.* 2013; Gao *et al.* 2016), and detecting genomic regions experiencing
recent selective sweeps (Pavlidis *et al.* 2010; Lin *et al.* 2011; Ronen *et al.* 2013; Pybus *et al.* 2015;
Schrider and Kern 2016). While such methods have great promise, they still rely on a user-
defined set of summary statistics (ranging in number from dozens to hundreds). Moreover, it is
not known whether it is possible to construct a set of statistics that sufficiently captures all
relevant information in the input data.

Unlike other machine learning approaches, convolutional neural networks (CNN; LeCun

et al. 1998) are pattern recognition algorithms that do not require a predefined feature vector.

When fed labeled training data (e.g. a set of haplotypes simulated under a known biological

scenario), a CNN discovers meaningful features, in essence making a feature vector, and then

extracts information from these features in order to make inferences. CNNs have proved effective

in a number of fields (reviewed in LeCun *et al.* 2015), and particularly in the field of image

recognition, where they have achieved dramatic improvements over previous efforts (e.g.

Lawrence *et al.* 1997; Krizhevsky *et al.* 2012; Simonyan and Zisserman 2014). The application of

CNNs to population genomic inference is just beginning, and shows great promise (Chan *et al.*

2018). Population genetic questions may be particularly well suited for CNN-based learning

because they take matrices as inputs, and alignments of sequenced chromosomes are quite

naturally represented in this manner.

The goal of this paper is to assess the effectiveness of CNNs as a general strategy for

population genomic inference. We demonstrate that CNNs can be successfully applied to a

number of population genomic problems, in some cases achieving surprising accuracy. In

particular, we use simulation to show that CNNs can leverage images of aligned sequences to

accurately uncover regions experiencing gene flow between related populations/species, estimate

recombination rates, detect selective sweeps, and make demographic inferences. Indeed, in most

cases we observe performance that matches or exceeds that of current methods. We also use a

CNN to accurately infer recombination rates from read coverage data in a simulated

autotetraploid, demonstrating this approach's flexibility in handling noisy data while solving a

complex problem for which no theoretical solution exists. In light of these encouraging findings,

we argue that population genetics researchers should consider CNNs as a potential solution to a

variety of problems involving evolutionary inferences from sequence data. Because some readers

may have little background with this tool, we also provide an overview of the inner workings of

CNNs and explore several technical considerations that may impact performance.

RESULTS

Our goal is to use a CNN to make population genetic inferences from an alignment image, which

can be thought of as matrices where each entry represents the allele present in a given

chromosome at a given site. In particular, we focus on four distinct problems: identifying local

introgression, estimating the recombination rate, detecting selective sweeps, and inferring

population size changes. We chose these four tasks because each represents a different challenge

in population genetic inference, each with its own attendant branch of theory. To show the

ability of CNNs to solve problems for which no statistical approaches have been proposed, we

extended our recombination inference to infer recombination rates in autotetraploids with

tetrasomic inheritance.

Below, we address each of these problems in turn, providing a brief overview of the

phenomenon in question and existing methodology before describing our results using CNNs.

But prior to tackling these problems, we first give an overview of CNNs and discuss strategies for

reorganizing our input data that we found helpful in making CNNs work more efficiently with

population genetic alignments.

Overview of convolutional neural networks

Internally, a CNN is a type of artificial neural network − a collection of connected layers of

combinatorially linked mathematical functions (termed *artificial neurons*) that take an input and

transform it into an output value (Mitchell 1997). In a typical fully connected artificial neural

network, the input values are fed through a series of layers of artificial neurons (fig. 1A), termed

hidden layers, before reaching the output layer which transforms its inputs into a final prediction.

The output for the jth neuron within one of the hidden layers is given by the following:

$$f\left(\sum_i^n w_{ij}x_i + b_j\right)$$

In the expression above, x_i is the neuron's ith input value (either an input value from the data or

from a neuron in the previous layer's output), and w_{ij} is the *weight* attached to the connection

between that node (i) and the current node (j) and b_j is the current node's *bias* term. That is, to

obtain the value of neuron j, we compute the linear combination of the vector containing all

values from the previous layer and the jth neuron's vector of weights; the results of this summation

are in turn added to neuron j's bias term and then fed as input to some function f, termed the

activation function and which may be nonlinear. Thus, an artificial neural network is a

mathematical function.

Importantly, by changing the values of the weights and biases, an artificial neural network

can be tuned to detect informative patterns in the input data in order to produce the desired

Fig. 1: Schematics of a standard feedforward neural network and two convolutional neural network designs used in this study. A) Diagram of a fully connected feedforward neural network. Gray circles represent input (left side), output (right side), or hidden (center) neurons. Blue circles represent collections of bias terms. With the exception of the input layer, the value of any given neuron is a linear combination of values from the previous layer plus a bias term; this sum is then passed to an activation function (not shown). Each edge represents a distinct weighted input or bias term. Outputs may represent class membership posterior probabilities or estimates of continuous variables. B) A diagram of a 2D CNN similar to that used in this study to infer demographic parameters. The input is an alignment represented as an image which is passed through a first convolutional layer in order to create a set of feature maps. These feature maps are then downsized via a pooling step which replaces the values of a 1 or 2D matrix within a feature map with a single value summarizing it (e.g. the mean or maximum value of that matrix). For example, a 2D pooling operation of size 2 will reduce the size of a feature map by a factor of 4, as each adjacent 2×2 matrix within the input feature map is replaced by a single value (e.g. the maximum of those four values). These downsized feature maps are then passed through a second convolutional filter and pooling step, and the resulting output is flattened into a one dimensional vector and passed as input into a fully connected feedfoward layer (bias terms not shown). Also passed into this layer is output from a second branch of this network: the vector of positions of segregating sites in the alignment which have been passed through their own fully connected layer. Finally, the last fully connected neural network layer yields the predicted output values. C) Similar to panel B, but showing a 1D CNN with three convolutional layers (each followed by a pooling step), as used for our recombination rate estimator.

184
output. In the case of image recognition, an image is first represented numerically, typically as a
matrix of pixel intensities, and then transformed by the artificial neural network to produce an
output, for example a prediction of the type of object in the image. CNNs (Fig. 1B–C) differ from

standard artificial neural networks in that they begin with one or more convolutional layers, in
which a series of smaller weight matrices referred to as "filters" slide across the input image—
mimicking the manner in which animal cortical neurons each focus on input only from a small
receptive field—and perform a matrix convolution at each step until a series of filtered image
matrices are produced (LeCun *et al.* 1998). These filters are constructed during training (see
below). Each convolutional layer is often followed by a pooling layer (see Fig 1B and caption)
which reduces the size of these filtered image matrices while maintaining potentially important
discriminatory information obtained by the convolutional filters. Finally, these matrices are
flattened into one-dimensional vectors and then fed into a fully connected (or "dense") artificial
neural network (for an accessible overview see LeCun *et al.* 2015). Thus, salient features derived
from the image matrix by the convolutional and pooling layers are passed into one or more
layers of a fully connected neural network whose output layer then yields our predicted response
value.
CNNs allow for two types of convolutional layers: 1-dimensional and 2-dimensional,
which differ only with respect to the possible shapes that the convolutional filter can take (Fig.
1B–C). 1-dimensional (1D) convolutions are often used in the application to time-series data (e.g.
Dieleman and Schrauwen 2014; Kim 2014), and are thus applicable to sequence alignment
matrices. Despite its name, a 1D filter is not a vector but rather a rectangular matrix that spans a
user-defined number of entries (called the "kernel size") in one dimension in the input data (in
our case this dimension is that of the polymorphic sites in the alignment), and stretches entirely
across the other dimension (in our case across all chromosomes in the sample). A 2-dimensional
(2D) convolutional filter, which is more often used with image data, allows the user to specify
both dimensions of the filter matrix (often using a square matrix). Whether 1- or 2-dimensional,
the benefit of incorporating convolutions is that it allows the CNN to take advantage of structural
information in the input data. For example, from an image of a face, a CNN can learn to detect
the repeated pattern of the eye shape and the location of both eyes relative to one another and to
other features. When there is meaningful structural information such as this, CNNs tend to
outperform non-convolutional neural networks.
Here our input data is an alignment of linked segregating sites with partially shared
evolutionary histories. Our hope is that a CNN can discover structural information in these data
in order to make evolutionary inferences—for example, locating the valley in diversity at the

center of a sweep (Maynard Smith and Haigh 1974), the "shoulders" on the flanks of a sweep
where linkage disequilibrium and allele frequencies are both elevated (Schrider *et al.* 2015), or
even the spatial relationship between these patterns. We also note that neural networks such as
CNNs can have multiple "branches" each with separate architectures and input types—in some
of the cases discussed in this paper we incorporate an additional network branch whose input is
the vector of the positions of the segregating sites (Fig. 1B–C).

Like all supervised machine learning methods, a CNN must be trained on labeled
training data before it can make predictions on unlabeled data (i.e. data whose response variables
are unknown). Training is accomplished by tuning the weights and biases that control the
behavior of its artificial neurons so that together they maximize the accuracy of the outputs on
the training data. Note that the weights determined during the training process include the values
of the convolutional filter matrices, and thus different filters will be algorithmically created for
each task we address in this paper. This tuning occurs over a number of iterations using the
backpropagation algorithm (Rumelhart *et al.* 1986), which in modern implementations feeds a
small number of training examples (a "mini-batch") through the network and then estimates the
error gradient on the output vectors produced for these examples. The error gradient is then
propagated in reverse through the network—a given hidden neuron's contribution to the error is
proportional to the linear combination of its weight vector and the errors associated with each
neuron in the next layer. The weights are then updated using one of the many flavors of
stochastic gradient descent (e.g. Kingma and Ba 2014). This process repeats until each training
example has been fed through the network, marking the completion of a single training iteration.
Training continues for a number of these iterations (often called epochs) until a specified stopping
criterion is reached (e.g. a predefined number of iterations has been performed, accuracy on the
validation set has not improved relative to the previous iteration, etc.).

In the context of population genetics, the CNN's input could be a matrix of allelic states
at each polymorphic site (Fig. 2). For example, an alignment of haploid individuals M, where
$M_{ij}=0$ if the ith individual has the ancestral allele at the jth segregating site in the alignment, and 1
if this individual has the derived allele (an input format that can easily be altered to allow for
multiallelic polymorphisms); we adopt this approach and variants of it below. The output can be
a categorical indicator (e.g. whether or not the genomic window experienced a recent selective
sweep) in which the problem is referred to as a classification task in machine learning

terminology, a quantitative value (e.g. the population recombination rate) in which case the task

is referred to as regression, or a vector containing both categorical and quantitative values. Once

the CNN has been trained to produce the desired output, it can be applied to unlabeled data (e.g.

sequence from natural populations).

Fig. 2: Example population genetic alignments visualized as black-and-white images. An unsorted alignment matrix (left) and this same matrix sorted by genetic similarity among chromosomes (right) are shown. Each row represents one of twenty chromosomes in the sample and each column represents one of forty segregating sites. Derived and ancestral states are encoded as black and white, respectively.

Because supervised machine learning relies on predictive functions tuned algorithmically

from training data, CNNs can be applied to any problem for which a training set can be

obtained, and therefore our inference is not limited to problems for which appropriate likelihood

models or statistics have been derived and implemented. In a population genetics context,

coalescent simulations provide a versatile and computationally efficient (Hudson 2002; Teshima

and Innan 2009; Ewing and Hermisson 2010; Kelleher *et al.* 2016; Kern and Schrider 2016)

means to generate training data. In this paper we relied exclusively on coalescent simulations to

produce training data for the CNN. However, compute-intensive forward population simulations

may offer greater flexibility than coalescent simulations in some situations, and recent advances

are making them more computationally feasible (Kelleher *et al.* 2018).

Using a CNN to make inferences from an alignment: a simple test case

We evaluated the performance impact of transposing the alignment matrix (so that columns

rather than rows correspond to chromosomes) and sorting the chromosomes in the alignment

matrix by genetic similarity. We did this using a 1D CNN trained to estimate the population-

scaled mutation rate, θ, in an equilibrium population. We found that both of these techniques
accelerate the decline in root-mean-square error (RMSE; Fig. 3), showing that they help the
network achieve better performance. Transposing the alignment matrix so that chromosomes are
represented by rows and polymorphisms by columns has a particularly notable effect (compare
blue and black lines in Fig. 3). Additionally, sorting the chromosomes by genetic similarity further
increases the accuracy of the CNN when combined with the matrix transposition above
(magenta line); alternatively, using a permutation-invariant network architecture would obviate
any need for this step (Chan *et al.* 2018). The effect of transposition should disappear when using
2D convolutions because in those cases we always used a square convolutional filter matrix
(Methods), but we found that 1D CNNs often performed as well as 2D CNNs (data not shown).
Thus, unless otherwise specified we use 1D convolutions for the tasks discussed below.
282

Fig. 3: The impact of input data reorganization on accuracy. We show the root mean squared error (RMSE) of a 1D CNN's predictions of θ as assessed on 1,000 test alignments after a given number of training iterations. Each line is the average of 10 runs. The blue line shows accuracy after training using alignment matrices with each row representing one chromosome. The black line shows accuracy after transposing all matrices so that chromosomes correspond to columns; this makes 1D convolutional filters examine each individual at a group of adjacent segregating sites. The magenta line shows the impact of transposing matrices, and sorting the chromosomes in the alignment matrix by genetic similarity.

283
284 **CNN's can accurately detect introgressed loci**

Recent studies indicate that closely related species often exchange genes (Kulathinal *et al.* 2009; Martin *et al.* 2013; Brandvain *et al.* 2014; Fontaine *et al.* 2015). There are several motivations for locating genomic segments introgressed from one species into another. For one, the occurrence of cross-species gene flow raises the possibility of adaptive introgression, wherein a beneficial allele enters a population via migration from a related species (reviewed in Hedrick 2013). Discovering introgressed loci can therefore identify alleles underlying rapid ecological adaptation as well as the source of these alleles. In addition, uncovering genomic regions that are and are not porous to cross species gene flow may help to illuminate the genomic basis of reproductive isolation (Turner *et al.* 2005).

Fig. 4: Performance of classifiers for detecting introgression. We use confusion matrices to show the performance of a CNN trained to detect genomic regions of introgression between two closely related species (panel A), and a competing method that uses a vector of summary statistics to the same end (FILET; panel B). These classifiers were both trained and tested on the same data sets which were simulated under a joint demographic history inferred from a sample of *Drosophila simulans* and *D. sechellia* individuals (as described in the Methods) with and without introgression. The classifiers seek to discriminate among three classes: no introgression in the genomic window being examined, introgression from *D. sechellia* to *D. simulans*, and introgression from *D. simulans* into *D. sechellia*. Each entry in the matrix shows the fraction of test examples belonging to the class specified on the *y*-axis that were inferred by the method to belong to the class specified on the *x*-axis. Correct classifications are those found along the diagonals, while all off-diagonal entries represent incorrect classifications.

Researchers have thus sought to devise methods capable of detecting introgressed regions from multispecies population genomic data sets. These include methods that attempt to infer the ancestry for each individual at each site (e.g. Price *et al.* 2009; Lawson *et al.* 2012; Sohn *et al.* 2012) and those that explicitly seek to discriminate between introgressed and non-introgressed loci

(Sankararaman *et al.* 2014; Geneva *et al.* 2015; Rosenzweig *et al.* 2016; Schrider *et al.* 2018). We

trained a CNN to identify introgression in a scenario modeled after the demographic history of

the *Drosophila simulans*-*D. sechellia* species pair (Methods), for which there is evidence for recent

gene flow (Garrigan *et al.* 2012).

Fig. 4A displays the results of these tests in the form of confusion matrices, which show

the fraction of test examples correctly predicted for each class (diagonal values) as well as the

fractions incorrectly assigned (off-diagonal values). To compare the performance of our CNN to

competing approaches, Fig. 4B displays the confusion matrix for FILET, a method previously

shown to outperform several methods, including two statistics for detecting introgression (Joly *et*

al. 2009; Geneva *et al.* 2015), and a tool that infers local ancestry tracks for each individual

(Lawson *et al.* 2012). Overall, this CNN classified 88.5% of test simulations correctly (95%

confidence interval: 87.7–89.2%). The most difficult scenario for the CNN was introgression

from *D. simulans* into *D. sechellia*, which it misclassified as "no introgression" 23% of the time. For

the other two classes the CNN accuracy was >95%. Importantly, for every class this CNN

achieved greater accuracy than FILET (overall accuracy of 82.5%; 95% confidence interval:

81.7%–83.4%), a machine learning approach that leverages a vector of 31 summary statistics

(Schrider *et al.* 2018). Thus, it is a useful measuring stick for assessing the CNN's accuracy, and

the CNN's success in this comparison is encouraging.

Estimating historical recombination rates

Recombination creates new combinations of alleles, and the degree of linkage between selected

sites affects the efficiency with which natural selection can act on each individual site (Hill and

Robertson 1966). The interplay of selection and recombination also influences the landscape of

diversity across the genome (Begun and Aquadro 1992). Knowledge of recombination rates is

thus key to population genetics research. As a more practical alternative to estimating rates

directly (e.g. from pedigrees; Kong *et al.* 2010), one can infer recombination rates from

population genetic data by examining associations among alleles at different sites. A number of

methods have been proposed to solve this problem, including summary statistic estimation

approaches (e.g. Hudson and Kaplan 1985; Hudson 1987; Hey and Wakeley 1997), composite

likelihood-based methods (e.g. Hudson 2001; McVean *et al.* 2004; Chan *et al.* 2012), and machine

learning tools using a vector of statistics (Lin *et al.* 2013; Gao *et al.* 2016). We sought to determine

Fig. 5: Accuracy of recombination rate estimates from LDhat and our CNN. Panels A and B show the real *ρ* values per base pair on the *x*-axes and LDhat's (A) and the CNN's (B) predictions on the *y*-axes. Panel C again shows the real *ρ* values on the *x*-axis, and the probability that the CNN was more accurate than LDhat (black line) on the *y*-axis. This probability was calculated by scoring estimates where the CNN outperformed LDhat as one and the reciprocal as zero, and then smoothing these values with a lowess curve with a span of 15%. The red line represents the expectation if both methods had identical accuracy. Panel D shows the results from the simulated autotraploid model, with the real *ρ* values on the *x*-axes and the CNN prediction on the *y*-axes.

330
whether a CNN taking an alignment image as input could be trained to tackle this task. To

address this problem, we first trained a CNN to estimate the historical population recombination

rate $\rho=4Nr$ (where *r* is the crossover rate per base pair per meiosis) from phased chromosomes.

This is the simplest scenario, as the arrangement of alleles on chromosomes is completely

resolved. Following training, we compared the CNN's performance to that of `LDhat` (McVean

et al. 2004), a widely used composite likelihood method, on the same testing data (Fig. 5). We

generated a test set of alignments whose values of *ρ* spanned three orders of magnitude, from

0.0002 to 0.2 (expressed per bp). Overall, both approaches performed well at predicting the true

value of ρ. LDhat had an $R^2 = 0.77$ and an RMSE = 0.016, whereas the CNN had a $R^2 = 0.86$

and an RMSE = 0.011 (Fig. 5A,B). LDhat appears to estimate ρ slightly better than the CNN

for lower recombination rates, whereas the CNN performs better at the higher values of ρ (Fig.

5C). Additionally, the CNN appears to provide a roughly unbiased estimator of ρ, while LDhat's

estimates appear downwardly biased.

Because the CNN was capable of estimating ρ independent of θ, we were interested to see

how well it could interpolate between the θ values it was trained with. The CNN was trained with

a large gap between $N = 20{,}000$ and $N = 50{,}000$ (and thus a large gap in θ; see Methods), so we

used coalescent simulations to generate an additional test set with N values drawn uniformly

among 30,000, 35,000, 40,000, and 45,000. When tested on these data the CNN's predictions

had an $R^2 = 0.82$ and an RMSE = 0.017. This represents a slight decrease in accuracy from the

values obtained when tested on the same N values used in training, but nonetheless shows that

the CNN can interpolate between training parameters without a dramatic loss in accuracy. This

could be a useful property, for example in cases where N (or θ) is unknown, but where one can

generate coalescent simulations across a range of plausible values.

Further complications arise when estimating ρ from unphased data. Under this scenario

the arrangement of alleles on chromosomes is not known. One work-around is to first phase the

alleles and then infer ρ as above, but not all data sources are easily phased, and phasing errors

will, of course, reduce accuracy. Another approach is to analyze the unphased data directly. The

relevant theory required to tackle this problem in a probabilistic manner has been worked out for

unphased diploids (Auton and McVean 2007), but expanding this theory to higher ploidies would

require a substantial effort. Take for example an autotetraploid with tetrasomic inheritance,

where there are five possible genotypes (*AAAA*, *AAAa*, *AAaa*, *Aaaa*, and *aaaa*). To further

complicate things, after sequencing an autotetraploid genome to a moderate depth of coverage

and identifying polymorphisms, the true underlying genotype may be uncertain. For example,

given a site with 10 reads supporting *A* and 10 supporting *a*, the true genotype could be *AAAa*,

AAaa, or *Aaaa*. To show the utility of CNNs in addressing novel population genomic inference

problems, we designed a CNN capable of inferring ρ from a simulated set of sequence reads from

an unphased autotetraploid population sample.

We used a simple simulation scheme to produce read counts for each allele at each site for each individual in a sample of 12 autotetraploids, each with approximately 25X expected genome-wide coverage (see Methods). Rather than allelic assignments, the input matrix for this CNN contains for every site in each individual the fraction of reads bearing the a allele. Deriving a likelihood function for ρ under this formulation may be challenging, and such a solution has not yet been attempted. However, appropriately designed artificial neural networks are universal approximators, meaning that they have the potential to approximate any continuous function over a compact input space (Hornik 1991). Thus it is possible for a CNN to approximate the desired likelihood function, even in its absence. To this end we trained a CNN with a similar architecture to the one used above on phased haploid chromosomes (see Methods). We evaluated the performance of this CNN on a set of simulations where ρ again ranged from 0.0002 to 0.2 (still scaling by $4N$, rather than $8N$ which would be appropriate for tetraploids, so the result can be compared to those above). The CNN's predictions had an $R^2 = 0.83$ and an RMSE $= 0.012$ (Fig. 5D). As before, the estimate of ρ was made independent of θ, which varied over an order of magnitude. The fact that this autotetraploid network performed only slightly worse than the haploid version demonstrates that a CNN can solve problems for which no model-based likelihood (or even composite likelihood) approach has been obtained, empowering empiricists untrained in methods development to address questions specific to their biological system.

CNNs can accurately detect and categorize signatures of recent positive selection

When a new mutation is immediately favored by positive selection, it rapidly increases in frequency until it fixes (i.e. completely replaces all other alleles at that site). This phenomenon, referred to as a hard selective sweep, drastically reduces the amount of linked neutral variation (Maynard Smith and Haigh 1974), and produces characteristic skews in the allele frequency spectrum (Fay and Wu 2000) and linkage disequilibrium at linked sites (Kim and Nielsen 2004). Alternatively, in a process known as a "soft sweep" populations may adapt via selection on a polymorphism that has been segregating for some time, such that the adaptive allele exists on numerous haplotypes (Hermisson and Pennings 2005). To uncover the mode of recent adaptation and the genomic regions underlying recent adaptation, a large number of methods have been devised to detect and characterize selective sweeps. These include summary statistics (Kelly 1997; Fay and Wu 2000; Kim and Nielsen 2004; Voight *et al.* 2006; Garud *et al.* 2015),

composite likelihood-based approaches (Kim and Stephan 2002; Kim and Nielsen 2004; Nielsen
et al. 2005; Vy and Kim 2015), and supervised machine learning approaches using a vector of
statistics to obtain greater power than individual tests/statistics (Lin *et al.* 2011; Pybus *et al.* 2015;
Schrider and Kern 2016; Sheehan and Song 2016; Sugden *et al.* 2018). Although these efforts
have led to considerable progress, detecting and distinguishing between hard and soft sweeps
remains a major challenge.

We built a CNN to detect selective sweeps and to discriminate between hard sweeps and
soft sweeps. This CNN follows the S/HIC method of Schrider and Kern (2016) by casting the
problem as a classification task where the genomic region being examined is assigned to one of
five disjoint classes: a recent classic "hard" sweep, a recent "soft" sweep, a region linked to a
nearby hard sweep, a region linked to a nearby soft sweep, or a neutrally evolving region.

Fig. 6: Confusion matrices showing accuracies of two methods that seek to detect recent positive selection by discriminating among hard sweeps, soft sweeps, unselected regions closely linked to hard and soft sweeps, and neutrally evolving regions. (A) Confusion matrix summarizing the performance of our CNN, which uses an alignment image as input. (B) Performance of S/HIC, which uses a vector of summary statistics each measured in windows surrounding the region to be classified. These two classifiers were both trained and tested on the same data sets described in the Methods.

Like FILET for the problem of detecting introgression, comparing the CNN's accuracy to
that of S/HIC is informative because S/HIC was previously shown under a variety of simulated
scenarios to have greater power than a number of competing methods (Schrider and Kern 2016).
Rather than adopting S/HIC's approach of using a large vector of statistics, the CNN takes an
alignment image as input. We tested both methods against data simulated under a challenging
demographic history estimated from human population data (Methods). As evidenced by the

confusion matrices in Fig. 6, the CNN has slightly higher overall accuracy than S/HIC (60.6% with 95% confidence interval: 58.8–62.3% for the CNN; versus 58.5% with 95% confidence interval: 56.7%–60.2% for S/HIC). While S/HIC appears to be somewhat more sensitive to sweeps, the CNN is achieves a more than 3-fold reduction in false positive rate: 2% of neutral simulations are classified as sweeps by the CNN, versus 6.35% for S/HIC; all of these false positives are classified as soft sweeps. This quality may be particularly desirable when scanning genomes where sweeps are relatively rare and thus a high degree of specificity is required to maintain a low false discovery rate, although the proclivity of either classifier to produce false positives versus false negatives can be adjusted by imposing a posterior probability cutoff. Note that these classifiers were both trained under the same demographic history from which the test data were generated. We would not expect this CNN to match S/HIC's robustness to demographic misspecification given that S/HIC's feature vector was designed with this in mind, though we did not test this. Nonetheless, the fact that the CNN has similar accuracy to S/HIC under this difficult test scenario is highly encouraging.

CNNs can extract demographic information from alignments

A major focus of population genetics research is to use genomic data to elucidate species' demographic histories—the extent and timing of population size changes, and the history of population splits and migration events. For example, a host of population genetic approaches have been devised to infer the times and intensities of population contractions and expansions over the course of a species' recent history (e.g. Marth *et al.* 2004; Schiffels and Durbin 2014; Liu and Fu 2015), and to elucidate the history of population splits and subsequent gene flow (Nielsen and Wakeley 2001; Hey 2009), and population merging events (e.g. Lipson *et al.* 2013; Loh *et al.* 2013). We asked whether CNNs can effectively extract demographic information from alignment images, focusing on the task of inferring population size histories. In particular, we attempted to train a CNN to estimate the parameters of a three-epoch model of instantaneous effective population size changes. There are five such parameters: the ancestral population size (N_2), the time of the more ancient population size change (T_2), the population size after this change (N_1), the time of the more recent change (T_1), and the present-day population size (N_0); our response variable is the vector of these 5 real-valued parameters. Thus this analysis also allows us to assess the ability of CNNs to predict multiple population parameters simultaneously.

Fig. 7: Accuracy of demographic inference CNN. The scatterplots show the correlation between true and predicted demographic parameter values using our best-performing CNN for this task when applied to an independent test set. Note that there may be some monotonicity in the relationship between the true and predicted values of some of these parameters, which may affect calculations of the Spearman correlation coefficients shown above each scatterplot. These estimates should thus be viewed as a rough summary of this relationship, while the RMSE values reported in the text better summarize our accuracy. The inset on the bottom right shows the demographic model and its five parameters.

We simulated 50 haploid chromosomes under a variety of randomly selected population size histories, and trained a CNN to estimate the demographic model parameters. The simulated region was roughly equivalent in length to 1.5 Mbp of the human genome (Methods). Because we found this problem to be comparatively difficult, we experimented with a variety of hyperparameters governing the neural network structure and input/output format. In supplementary table S1 we show the optimal RMSE (i.e. the minimum RMSE across training iterations) for each hyperparameter combination examined. This experiment revealed several general trends. First, 1D convolutional networks tended to fare slightly better than their 2D counterparts (median RMSE of 0.52 across all hyperparameter combinations with 1D convolutional filters, and median RMSE 0.54 for 2D convolutions; $p=1.1\times10^{-4}$; Mann-Whitney

U test); however several 2D networks performed nearly as well as the best 1D network, achieving

an RMSE of <0.5 while the best score obtained overall was 0.43. Second, smaller convolutional

filters tended to perform slightly better than larger ones—we observed a positive correlation of

kernel size with RMSE across hyperparameter combinations (ρ=0.26; p=6.9×10^{-4}; Mann-

Whitney *U* test). For example, the median validation RMSE was 0.51 for a kernel size of 2 versus

0.56 for a kernel size of 10. Third, log-scaling the demographic parameters to be estimated

increased accuracy (RMSE decreased from 0.55 to 0.52; p=0.020; Mann-Whitney *U* test). For

this problem sorting chromosomes by relatedness resulted in a small improvement (RMSE

decreased from 0.54 to 0.53; p=0.034). Encoding ancestral and derived alleles as '0' and '255'

(i.e. black and white in a grayscale image), respectively, versus '-1' and '1' had a significant

influence on accuracy, with the former yielding better performance than the latter (RMSE of

0.51 vs. 0.60; p=1.5×10^{-15}). Finally, using dropout resulted in a slight decrease in accuracy

(median RMSE increased from 0.52 to 0.55) though this was not statistically significant

(p=0.092). We note that these trends may change if the amount of training data is increased or

decreased, and may not necessarily hold for other tasks.

In Fig. 7, we show the correlation between the true and inferred values for each of these 5

parameters for the best performing network. For N_0 and T_0, these correlations are quite high,

implying that our CNN can recover the true values reasonably well. However, for the remaining

parameters, the correlation is lower (though still highly significant), and our CNN produces

downwardly biased estimates when the values of these parameters are larger. Although our

accuracy is far from perfect, we consider these results fairly encouraging because we are only

examining a single moderately sized genomic region, while other modern demographic inference

methods use data from across the genome. For example, $\partial a \partial i$ (Gutenkunst *et al.* 2009) uses allele

frequencies measured at a large number of polymorphisms (e.g. those found in all distal

intergenic regions across the genome; Gazave *et al.* 2014). PSMC and MSMC (Li and Durbin

2011; Schiffels and Durbin 2014) take data from a single very large recombining region such as

an entire chromosome. In essence, we are currently only able to utilize information about the

coalescent histories of the region in question—and this collection of histories may not match that

of the entire population, which would be more accurately reflected in genome-wide data. In the

Discussion, we address prospects for incorporating genome-scale data in demographic inference.

DISCUSSION

Convolutional neural networks are well suited for population genetic problems

Population geneticists have devised a wide array of computational methods to make evolutionary

inferences from genomic data. Typically the goal of these efforts is to aggregate information

across genomic sites in order to make an accurate inference. These methods include likelihood-

based approaches (e.g. Kim and Stephan 2002; Nielsen *et al.* 2005; Gutenkunst *et al.* 2009; Liu

and Fu 2015), probabilistic graphical models such as hidden Markov models (e.g. Turner *et al.*

2005; Boitard *et al.* 2009; Lawson *et al.* 2012), and those that rely on the use one or more

summary statistics designed to characterize patterns of variation within a genomic region (e.g.

Tajima 1989; Fu and Li 1993; Kelly 1997; Fay and Wu 2000; Kim and Nielsen 2004; Voight *et*

al. 2006; Ferrer-Admetlla *et al.* 2014). While these approaches differ substantially from one

another, they all have one thing in common: they make use of population genomic theory to

connect the features of a data set to the underlying evolutionary process. Here we have

demonstrated the potential of an alternative approach: treating population genetic inference as

an image recognition problem where the "image" is the population genetic alignment, which is

directly fed as input to a CNN. In contrast to most mainstream approaches, this CNN approach

makes use of the entirety of the data, rather than using theoretically derived estimators or closed-

form likelihood functions to connect a small number of features of the data to an evolutionary

process.

Here we have shown that CNNs perform remarkably well on a number of problems in

population genetics. We developed CNNs with comparable if not greater power to detect

selective sweeps, identify introgressed loci, and infer local recombination rates when compared to

current methods on simulated data sets. The CNNs for detecting sweeps and introgression

demonstrate the ability to use an alignment image to distinguish among multiple evolutionary

models, while the recombination rate estimator demonstrates that continuous parameters can

also be inferred. Finally, although our demographic parameter estimates were fairly imprecise,

they were only based on a short stretch of the genome, and nonetheless demonstrate that CNNs

have the potential to infer multiple parameters from a sequence alignment. While we were in the

process of preparing this manuscript, Chan et al. completed an important study demonstrating

that a CNN can accurately detect recombination hotspots (Chan *et al.* 2018). Taken together

these results suggest that CNNs have enormous potential as a general paradigm for population
genetic inference.

The effectiveness and generality of CNNs in population genetic inference should not be
surprising. CNNs offer a number of intrinsic advantages that make them particularly amenable
to population genetic data. First, there have been a number of efforts to move in the direction of
making inferences on the basis of the full complement of data present in an alignment rather
than one or more summary statistics (Li and Stephens 2003; Lawson *et al.* 2012; Smith *et al.*
2018). CNNs represent a natural way of examining the entirety of an alignment in order to
increase inferential power. The development of novel CNN architectures to better handle spatial
associations in the data across multiple scales (Yu and Koltun 2015) has the potential to improve
CNN-driven population genetic inference even further. For example, improved ability to detect
both the localized reduction in diversity at a sweep (Maynard Smith and Haigh 1974) as well as
the potentially confounding skews in patterns of diversity produced in its flanking regions
(Schrider *et al.* 2015) would be beneficial in sweep detection.

Another desirable property of CNNs is that they effectively perform automated feature
detection (LeCun *et al.* 2015). Because they discover discriminatory information directly from the
image, there is no need to manually construct an optimal set of features. CNNs may thus
outperform methods based on a set of manually curated features as observed here, although this
may not be the case for all tasks (e.g. Bellot *et al.* 2018). This brings up perhaps the strongest
quality of CNNs in the context of evolutionary inference: because CNNs can make inference in
the absence of statistics or a likelihood function, they can make predictions for phenomena for
which there exists no analytical expectation.

Indeed, CNNs can tackle problems for which no relevant summary statistics have been
devised—vectors of such statistics are required for other likelihood-free methods such as ABC
(Beaumont 2010) or traditional supervised machine learning techniques (Schrider and Kern
2018). On a related note, neural networks are particularly amenable to the incorporation of
disparate data types with no prior knowledge of their relationships. For example, here we have
included both genotype information and positional information for segregating sites as branches
to our networks, allowing both to be used together in prediction despite the fact that our network
isn't instructed how these two pieces of information relate to one another. All that is required is
appropriate training data. Thus, we may not have to wait for theoretical advances in order to

draw inferences from data, provided we are concerned with evolutionary models for which
training data can be obtained from simulation—including the wide range of scenarios that could
potentially be investigated via increasingly flexible and efficient forward simulators (Thornton
2014; Haller and Messer 2017; Kelleher *et al.* 2018).

This point is driven home by the success of our CNN for estimating recombination rates
in autotetraploids from read pileup information alone—despite the input's lack of genotype calls,
let alone phased haplotypes, these inferences are nearly as accurate as those that we obtained
from haplotype alignments. This result also suggests that CNNs may be well suited for other
inferences where genotype calls are unreliable (e.g. low coverage sequencing data; Korneliussen *et*
al. 2014) or unobtainable (e.g. pooled population sequencing; Schlötterer *et al.* 2014). Given
CNNs' flexibility, future studies should evaluate their potential to tackle not only those problems
examined in this paper, but the myriad additional important challenges in evolutionary genetics
to which they could be readily applied, including but not limited to uncovering adaptive
introgression (Racimo *et al.* 2016), joint inference of selective and demographic histories (Sheehan
and Song 2016), and even inferring structured outputs such as ancestral recombination graphs
(Rasmussen *et al.* 2014).

To what extent are CNNs robust to model misspecification?
Another particularly encouraging result of our recombination rate estimation analysis is that we
were able to infer rates for data generated from a range of parameter values to which the CNN
had not been exposed during training with very little decrease in accuracy. This ability to
interpolate between training values is a particularly desirable property. First, it implies that
CNNs can be used to create flexible inference tools using a modest training data set, and second
that researchers can focus training between reasonable parameter bounds, without knowing the
true (and often unknowable) underlying parameters; future efforts must explore the possibility of
training networks to be robust to more extreme cases of model misspecification.

One illustrative example of the potential pitfalls of model misspecification is the problem
of detecting selective sweeps without accounting for confounding demographic events. For
example, population bottlenecks will skew genealogies in a manner similar to sweeps (Simonsen *et*
al. 1995), and thus may result in a large fraction of false positives (Jensen *et al.* 2005; Nielsen *et al.*
2005). Schrider and Kern (2016) were able to mitigate this problem by designing a feature vector

that is sensitive to the spatial skews in patterns of variation created by a sweep but insensitive to

genome-wide skews produced by demographic events. Although this strategy is not possible with

CNNs because they perform automated feature extraction, it may be that incorporating training

examples generated under potentially confounding scenarios could alleviate this issue.

Therefore, future work must thoroughly 1) assess how CNNs trained on data simulated

under one range of evolutionary parameters fare when applied to different parameterizations,

and 2) determine whether robustness to such misspecification might be achieved by training a

CNN under a wide range of parameter values that are likely to encapsulate the correct values—

the recombination rate estimator's successful interpolation suggests that this may be a possibility.

Model misspecification is not a concern for tasks where training data may be obtained without

simulation (e.g. detecting selective constraint; Schrider and Kern 2015), though in such cases one

must take care to prevent dependencies between training and test examples because of shared

evolutionary histories due to physical linkage or paralogy/orthology relationships (Washburn *et*

al. 2018).

Outstanding practical challenges associated with the application of CNNs to

sequence data

Although the CNN approach outlined above has great potential, there are several outstanding

challenges with applying CNNs to a wider spectrum of problems. One important obstacle is the

large amount of training data required by CNNs, which makes applications requiring alignments

of large regions (e.g. entire chromosomes) more difficult. This challenge includes both the

generation of large labeled training examples, and time- and memory-efficient training with these

large examples given limited computational resources. Fortunately, continued improvements in

simulation speed (Kelleher *et al.* 2016; Kelleher *et al.* 2018) and the efficiency of CNN training

(Chilimbi *et al.* 2014; Yu and Koltun 2015; Jouppi *et al.* 2017; Köster *et al.* 2017) is mitigating this

problem. Such advances would be a boon for efforts to infer demographic parameters, which

require simultaneously examining data sampled from across the genome or along an entire

chromosome,   unlike   scans   to   infer   locus-by-locus   histories   of

selection/recombination/introgression. Advances in handling large or high-resolution images

may also prove fruitful. For example, CNN-based strategies that simultaneously examine a

number of smaller "patches", each covering a portion of the image rather than the entirety of the

image (e.g. Lu *et al.* 2015), may aid efforts to extract demographic information from genome-
scale data.

Another challenge with the application of CNNs is that their performance can be
sensitive to network architecture (Szegedy *et al.* 2015). There is no underlying theory for selecting
optimal network architecture, though improved architectures are sure to continue to arise, and
automated methods exist for optimizing the many hyperparameters of a given architecture (e.g.
Snoek *et al.* 2012). Though we uncover some promising CNN architectures for population
genetic inference, we suspect that substantial improvements can still be made.

We have also demonstrated that CNNs are sensitive to the input format of the population
genetic alignment, and our work has yielded several insights along this front. First, we found that
the ordering of haplotypes within the alignment can impact accuracy, and our results suggest that
it is often beneficial to reorder haplotypes so that more similar chromosomes appear next to one
another. This may be a suboptimal solution, and more creative approaches may be required to
provide a more general strategy. To this end, research into permutation-invariant neural
networks (Zaheer *et al.* 2017) may prove promising when dealing with sequence alignments. This
is evidenced by Chan et al.'s recent findings that a permutation-invariant architecture improves
both training speed and final accuracy of their CNN for detecting recombination rate hotspots
(Chan *et al.* 2018). Chan et al.'s network avoids any convolution or pooling operations that
combine information across individuals until an operation that collapses each column of the
(filtered) alignment matrix down to a single value in an order-invariant manner (e.g. site-wise
maximum). This design choice means that permuting the order of individuals within the
alignment will have no impact on their network's output. We also observed that 1D convolutions
in the proper orientation perform as well as the more widely used 2D convolutions in many
cases. Also, scaling response variables for regression problems (both log-scaling and
standardization) may also affect accuracy. We therefore recommend that users experiment with
these different ways of representing their data, as well as different CNN architectures, in order to
find the design that works best for the task at hand.

Another important consideration of CNNs is that once trained, they are specialized to a
particular problem as defined by the training set. That is, a CNN trained to infer recombination
rates under a European demographic history may have reduced accuracy when applied to an
African sample. Training under a variety of demographic scenarios may make a CNN more

robust to this problem, but a question for further study is whether this can be accomplished
without a loss in power relative to a more specialized CNN. Even a change as subtle as adding
another chromosome to a dataset will make one of our previously trained CNNs inapplicable, as
the input matrix would no longer be the proper size and either a new CNN must be trained or
the data subsampled. Importantly, Chan et al. (2018) describe an architecture that can allow for
variation in the number individuals in the input matrix. It is also important to note that in spite
of their limitations, recent advances have greatly simplified training CNNs, and it will often be
practical—or even preferable—for a researcher to create a CNN tailored to their specific data
set.
654

Are CNNs a black box?
Artificial neural networks are algorithms that seek to maximize their predictive accuracy by
optimizing their internal mathematical operations on training data and CNNs are an extremely
flexible subclass of these methods because they can act directly on the input data matrix (in our
case a sequence alignment). However, one consequence of this is that CNNs are in some ways a
"black box". For example, a CNN cannot "explain" why it made a particular prediction given its
input. Supervised machine learning algorithms in general have perhaps been unfairly maligned
with this "black box" label. These methods can in principle reveal much about underlying
processes by determining which features are most informative under certain scenarios (i.e. feature
ranking; see Breiman 2001). For example, the observation that certain features are highly
informative for recent but not ancient introgression (Schrider *et al.* 2018) suggests some key
differences between the genealogies produced under these two scenarios. Due to their complex
inner workings, less progress has been made in breaking through the CNN "black box" as
compared to more traditional supervised machine learning techniques. However, some successful
explanatory tools are available for CNNs (Ribeiro *et al.* 2016), and there is ongoing research in
this area. Moreover, because the CNN framework we adopt here works on images, it may be
possible to translate future breakthroughs in CNN interpretation from other fields (e.g. image
recognition) into population genetic inference. Thus a more optimistic view is that as CNNs and
related methods become more interpretable, these likelihood-free image recognition approaches
may help to reveal theoretical insights into evolutionary processes.

In the near-term, CNNs may remain useful only as a predictive tool, and we will continue
to rely on theoretical advances to improve our understanding of population genetic processes. In
spite of the shortcomings noted above, the highly encouraging results that we have laid out here
suggest that CNNs are able to discover information about the underlying genealogies from
alignment images and to use this information to more accurately elucidate the evolutionary
phenomena that have shaped these genealogies. CNNs have enormous potential for population
genomic inference. We believe that progress on a host of problems could accelerate appreciably
were this technology to be embraced by the field. Indeed, when it comes to the business-end of
population genetics—drawing accurate evolutionary inferences from data—we predict that
increasingly, likelihood-free approaches such as the ones we have describe here will prove most
effective at solving existing problems, and expand the universe of problems that researchers can
investigate.

MATERIALS AND METHODS

Computational environment for training CNNs
All CNNs used in this study were developed using two open source Python packages: Keras
(version 2.0.6; https://keras.io/) to define neural network architecture and orchestrate training
and testing, and TensorFlow (version 1.1.0; https://www.tensorflow.org/) as the backend (i.e.
TensorFlow performs the computation during training/testing). CNN training is computationally
intensive, but cloud-based GPU resources have made it affordable. As an example, our network
for detecting selective sweeps was trained on a cloud-based system with one Nvidia K80 GPU. It
took 6.6 hrs to train, and at $0.90 US dollars per hour the total cost was under $7. All code used
for training is available online (https://github.com/flag0010/pop_gen_cnn).

CNN validation strategy
For each task, we divided our simulated inputs into three sets: a training set, a validation set, and
a test set. The training set was used to optimize the weights and biases of the CNN. The
validation set was used during training to determine how well the CNN generalizes to unseen
data, and adjustments were made to the CNN to improve its performance on the validation data.
We also used the validation set to terminate training once accuracy on this set appeared to

plateau—this process took different numbers of iterations for different tasks. Finally, the test set

was used to obtain a performance assessment of the final trained network. Importantly, this test

set was previously unseen by the CNN and therefore yields an unbiased evaluation of its

accuracy. We used binom.test in R to estimate 95% confidence intervals for classification

accuracies.

Evaluating techniques for rescaling and reordering inputs to improve CNN

accuracy

To evaluate the impact of alternative data preparation techniques, we developed a simple CNN

that estimates the locus-wide population mutation rate $\theta=4N\mu L$ where μ is the mutation rate per

base pair per generation and L is the physical length of the locus being examined. This CNN is

trained using alignment images with forty chromosomes and θ drawn uniformly between 10 and

50 as simulated for a panmictic, constant sized population by **ms** (Hudson 2002). We trained this

CNN to minimize the root mean squared error (RMSE) between its prediction and the true value

of θ using 4,000 training matrices. Then its accuracy was scored on 1,000 test matrices that the

CNN was never trained on. These values were compared under different data preparation

approaches described below.

First, the matrices output by most coalescent simulation software, including **ms**, encode

ancestral and derived alleles for bialleleic sites as 0 and 1, respectively, and present the matrix

with phased haploid chromosomes as rows and sites as columns. When doing 1D convolutions,

we sought to use row-wise convolutional filters (Fig. 1C), i.e. those that examine each

chromosome in our sample across a small number of contiguous segregating sites (specified by

the "kernel_size" parameter in Keras) before sliding the filter forward one site (our stride length,

"strides" in Keras, was always set to 1). At present Keras does not allow for row-wise 1D

convolutions, so we accomplished this by transposing the alignment matrix and performing

column-wise convolutions.

We also assessed the impact on accuracy of sorting the chromosomes in the alignment by

genetic similarity. For example, the matrices in Fig. 2 contain identical information, but

chromosomes in the matrix on the left are randomized, while on the right they are sorted by

genetic similarity. We offer a fast algorithm for sorting matrices by genetic similarity

(https://github.com/flag0010/pop_gen_cnn/blob/master/sort.min.diff.py).

Introgression detection

To detect introgression, we simulated phased haploid training and test examples with msmove

(https://github.com/geneva/msmove) from the same demographic model that Schrider et al.

(2018) used to train the FILET classifier for detecting introgression between *Drosophila simulans*

and *D. sechellia*. In total we produced 237,500 coalescent simulations from 3 classes: 112,500

without no migration between species (No Introgression), 112,500 with gene flow from *D.*

simulans into *D. sechellia* (*sim→sech*), and 12,500 with gene flow from *D. sechellia* into *D. simulans*

(*sech→sim*). We used fewer *sech→sim* examples because test runs on smaller training sets suggested

that the network could detect this class fairly accurately, which allowed us to increase the

sampling of the other two more challenging classes by simulating more examples from them. To

our knowledge this approach of intentionally inflating the number and proportion of training

examples from the more challenging classes is unusual, as typically a balanced training set is

preferred. However we found that including additional examples from classes into our data set

substantially improved our ability to correctly them. The simulations were randomly assigned to

training and validation sets so that the training set included 107,500 examples each from the No

Introgression and *sim→sech* classes, and 7,500 examples from the *sech→sim* class. Both the

validation set and the test set contained 2,500 of each class (i.e. 7,500 total). Importantly, because

our test and validation sets were evenly balanced, they provided unbiased estimates of our

accuracy.

As in the *Drosophila* data set to which Schrider et al. applied FILET, each of our

coalescent simulations generated 34 chromosomes (14 *D. sechellia* and 20 *D. simulans*). Each

column in the alignment corresponded to a biallelic polymorphism, which was encoded as "0"

(ancestral allele) or "1" (derived allele) for each chromosome. In practice, the ancestral and

derived states may not be known with 100% certainty, and one may instead use major/minor

alleles, or randomly mispolarize a fraction of sites in the training data if one has an estimate of

the fraction of mispolarized sites in the true data. The effects of these design choices on

performance may then be evaluated on test data. Each matrix was organized so that individual

chromosomes were grouped by species. Each coalescent simulation produced a different number

of segregating sites (with the largest containing 1201 polymorphisms). Because the CNN's input

matrices must all have the same dimensions, we padded the right side of all matrices with fewer

than 1201 polymorphisms with columns containing only "0" until the total number of columns
reached 1201. Finally we transposed this matrix resulting in a 1201×34 matrix for each
coalescent simulation. In practice, one will have to set the image width to the largest number of
SNPs encountered across all training, test/validation, or real data examples included in the
analysis. Alternatively, one may select a fixed number of segregating sites to include in the
analysis, in which case each example may correspond to a different physical size (creating
additional variance in total recombination rates). Thus, when using this alternative approach,
one should adjust the lengths of simulated examples accordingly.

We trained a CNN architecture with three 1D-convolutional layers (kernel size = 2), each
followed by average-pooling, and finally two densely connected layers (i.e. the same network
architecture as the main network branch illustrated in Fig. 1C, but with one additional dense
layer). These layers contained 256, 128, 128, 128, and 128 neurons, respectively. To avoid
overfitting during training, each layer used dropout regularization (randomly removing 25% of
neurons between convolutional layers during each training iteration, and 50% between densely
connected layers) and rectified linear unit activation functions (i.e. ReLUs; Hahnloser *et al.* 2000;
Nair and Hinton 2010). Dropout regularization encourages the CNN to learn redundant
representations of the data, thereby reducing the network's dependence on individual weights
(Srivastava *et al.* 2014). The last layer was a sigmoid output layer with 3 neurons, each
corresponding to the 3 classes given above. The CNN was trained using the Adam optimization
procedure (Kingma and Ba 2014), a categorical cross-entropy loss function, and a mini-batch size
of 256. The CNN was run for 19 training iterations through the training data.

Recombination rate: phased haplotype version
For the recombination rate estimator we used `ms` (Hudson 2002) to simulate 50 phased
chromosomes, each with a target length of 20kb. To do so, we drew a population size (N) from
the following values: 5,000, 10,000, 15,000, 20,000, and 50,000, and set the population-scaled
mutation rate parameter $\theta = 4N\mu L$ (letting $\mu=1.5\text{x}10^{-8}$ and L=20kb). We also set a population-
scaled recombination rate, $\rho = 4NrL$, where r is the per bp crossover rate per meiosis, by drawing
r from a bounded exponential distribution raging from10^{-8} to 10^{-6}. This yields a range of ρ per
base pair of 2×10^{-4} to 2×10^{-1}. These values roughly encompass the range of recombination rates
experienced in humans and *Drosophila*. Following this procedure, we generated 156,275

coalescent simulations. ~92% were used to train the CNN, and ~4% each were set aside for
validation and testing. To assess our CNNs ability to interpolate to unseen population sizes, we
also created 5,000 additional test matrices using the procedures above, but with N drawn
uniformly from the following: 30,000, 35,000, 40,000, and 45,000.

803   Each simulation was represented by a matrix of 50 rows, one for each chromosome, and
418 columns (the largest number of segregating sites). As before, we encoded the ancestral allele
with "0" and the derived allele with "1". Because not all simulations resulted in the same number
of polymorphisms, we padded both the genotype matrix and the position vector in the same
manner as for the introgression CNN, bringing the total size of each matrix to 50×418. Next, we
sorted each matrix by genetic similarity among chromosomes as described above and then
transposed the matrix to 418×50. We also extracted the segregating site positions vector from the
`ms` output which represents each position as a real number between zero (the leftmost position
on the simulated chromosome) and one (the rightmost position). For simulations with fewer than
418 segregating sites, we padded the positions vector with "-1"s.

813   We transformed the ρ values for the training, validation, and test sets by taking the natural
814 log of each value and centering them on the mean of the training set. By using the mean from the
815 training set for all transformations, we ensure that there is no leakage of information between
816 training and validation/testing.

817   We trained a CNN with two input branches. The first branch took the haplotype
matrices as input and included three 1D-convolutional layers (kernel size = 2), each followed by
average-pooling. These layers contained 1250, 256, and 256 neurons, respectively. Each of these
layers uses dropout normalization (25%), L2-regularization of the weights ($\lambda = 0.0001$), and
ReLU activation functions. The second branch took the position vector as input and contains
one densely connected layer with 64 neurons, again using dropout normalization (10%) and a
ReLU activation function. The two branches are then merged into another densely connected
layer of 256 neurons with ReLU activation functions. Finally, the output layer is a single neuron
with a simple linear activation function that predicts the continuous ρ value. The CNN was
trained using the Adam optimization algorithm, using mean-squared error as our loss function,
and a mini-batch size of 32. The CNN was trained for 16 iterations.

828   We compared our CNN's results to those of `LDhat` version 2.2a
(https://github.com/auton1/LDhat). We chose `LDhat` because it is widely used to estimate

historical recombination rates, and because it can be efficiently run on large data sets. LDhat will

estimate ρ only for a specified population mutation rate ($\theta = 4N\mu$), and we supplied it with the

exact θ value used for each coalescent simulation. This was done by creating five likelihood

lookup tables using the `complete` program, all set for 50 haploid chromosomes, for the

following θ values: 6, 12, 18, 24, and 60. Respectively, these correspond to N = 5,000, 10,000,

15,000, 20,000, and 50,000 (the same values we used for training our CNNs). `LDhat` only

predicts values within the bounds of the lookup table. Therefore, to facilitate a fair comparison to

results from our CNN, which is unbounded, we selected the maximum ρ value in the likelihood

lookup table to be 133.3% of the true maximum for each θ. We then set the grid size of ρ equal 1,

and estimated ρ on the test set using `LDhat`'s `pairwise` program.

In contrast, the CNN was not provided information about θ, and instead had to infer ρ

independent of θ. This ability would be a desirable property for an estimator, as θ is likely to vary

considerably across the genome and outside of simulated data sets one may never know θ

precisely. On the other hand, the CNN was provided with the physical distance between

segregating sites, information `LDhat` does not utilize but which will generally be available when

making inferences on real data. Both of these factors make our direct comparison of the CNN

with `LDhat` imperfect because each had access to information the other lacked when producing

its estimate. Nonetheless we consider this example a useful illustration of the CNN's

performance.

Recombination rate: autotetraploid version

We sought to train a CNN to estimate a locus-wide recombination rate in autotetraploid

genomes. To add a level of methodological realism to this problem, we did so from a matrix

storing a simple summary of read pileup information at each site for each individual.

To this end, we generated new coalescent simulations with 48 chromosomes each

following the procedure outlined above for the haploid CNN. This approach is reasonable

because it has been shown that the standard coalescent approximates the appropriate coalescent

for autotetraploids as long as N is larger than a few hundred (Arnold *et al.* 2012). We generated

217,500 coalescent simulations, and randomly assigned 200,000 to the training set, 10,000 to the

validation set, and 7,500 to the test set. Next, within each coalescent simulation, we randomly

partitioned our 48 chromosomes into twelve sets of four. Each set represents one synthetic

autotetraploid genome and every site has five possible genotypes (*AAAA*, *AAAa*, *AAaa*, *Aaaa*, and

aaaa). For each autotetraploid genome i and each site j we simulated the number of reads

covering the site (C_{ij}) by drawing a random sample from a Poisson distribution with $\lambda = 25$. Then

we selected the number of reads representing the *a* allele $R_{ij} \sim Binom(n=C_{ij}, p=x_{ij})$, where x_{ij}

represents the frequency of the *a* allele in the tetraploid genotype (i.e. 0, 0.25, 0.5, 0.75, and 1 for

the five genotypes listed above). For each individual i at site j, the corresponding entry in the

input matrix was the fraction R_{ij}/C_{ij}, i.e. the fraction of reads supporting the derived allele. The

AAAA and *aaaa* genotypes were always 0 and 1, respectively. For the three heterozygous

genotypes (*AAAa*, *AAaa*, and *Aaaa*), R_{ij}/C_{ij} varied based on sampling error but had expected values

of 0.25, 0.5, and 0.75, respectively. Thus at each site the original 48 chromosomes were reduced

to a set of 12 values corresponding to the fractions of reads supporting the *a* allele in a pool of

sequence reads from an autotetraploid sequenced at ~25X coverage. Note that this scheme

includes neither sequencing error, nor the site-specific depth which would be necessary to

calculate a likelihood, but is nonetheless adequate for our proof of concept.

As above, we sorted the rows of this matrix by genetic similarity and padded each matrix

with zeros to a length of 460 (the most segregating sites of any of the simulated matrices) before

transposing, yielding a 460×12 matrix. Again, we recorded the padded vector of positions from

the simulation output. Our CNN architecture was identical to the one given above for the phased

haplotype version, except for the dimensionality of the input changed to 460×12, and we

reduced the first convolutional layer from 1250 to 256 because of the smaller second dimension

of the input. The CNN was trained for 9 iterations.

Detecting selective sweeps and discriminating between modes of selection

For detecting selective sweeps, we used the same coalescent simulations that Schrider and Kern

(2017) used to train a classifier to detect sweeps in the JPT population (Japanese individuals from

Tokyo) from Phase 3 of the 1000 Genomes dataset (Auton *et al.* 2015). The JPT demographic

scenario is one where detecting selective sweeps is fairly difficult (see Figure S1 from Schrider and

Kern 2017), as expected for bottlenecked populations (Jensen *et al.* 2005). For this CNN, we

began with a set of 269,000 simulated genomic windows with the 5 following classes: a recent

hard sweep (i.e. fixation of a *de novo* beneficial mutation), a recent soft sweep (i.e. fixation of a

beneficial but previously neutral segregating polymorphism), a region linked to a nearby hard

sweep, a region linked to a nearby soft sweep, and a neutrally evolving region. Each simulated
alignment contained 208 chromosomes and we kept only coalescent simulations that contained ≤
5,000 segregating sites, and again padded with zeros so that all matrices were 208×5000. This
left 238,655 simulations, and from those we constructed a training set of 233,655 simulations. In
trial runs, we found that regions flanking hard and soft sweeps were the most difficult classes to
predict, so we again simulated additional examples from these more challenging classes. This
shifted the balance of our training set so that is was comprised of approximately 13% neutral
regions, 17% each for hard and soft sweeps, and 26.5% each for regions linked to nearby hard
and soft sweeps windows. We then set aside an evenly balanced set of 2,000 simulations for
validation and 3,000 for testing.

As before, we sorted each matrix by genetic similarity among chromosomes and then
transposed the matrix to 5000×208. We also extracted the segregating site positions vector from
these simulations which were generated by `discoal` (Kern and Schrider 2016), which like `ms`
represents each position as a real number between zero and one.

As above, we trained a CNN with two input branches. The first branch took the
haplotype matrices as input and included five 1D-convolutional layers (kernel size = 2), each
followed by average-pooling. These layers each contained 256 neurons and used dropout
normalization (20%). The second branch took the position vector as input and contained one
densely connected layer with 64 neurons, again using dropout normalization (10%). The two
branches were then merged into another densely connected layer of 256 neurons with 25%
dropout. Each hidden layer of the network used L2-regularization of the weights ($\lambda = 0.0001$)
and ReLU as the activation function. Finally, the output of this layer was fed to a five neuron
layer with softmax activation functions that predicts the five classes given above. The CNN was
trained using the Adam optimization algorithm, the categorical cross-entropy loss function, and a
mini-batch size of 32. The CNN was trained for 3 iterations.

Inferring population size histories
To show how CNNs can be used to infer species' demographic histories, and how CNN
architecture can impact this inference, we experimented with a variety of CNN approaches to
infer the 5 parameters of a 3-epoch model of instantaneous population size changes (i.e. 3
population sizes and 2 times of size change). We also use this challenging problem as an

opportunity to evaluate how alternative approaches to building a CNN can influence its

performance. In effect, we conducted a full grid search of the following attributes of both our

CNN architecture and input/output format: the dimensionality of our convolutions (1D or 2D),

the kernel size (i.e. the width of our 1D convolutional filters and both the height and width of our

square 2D filters; we tried each multiple of 2 raging from 2 to 10), whether to include dropout

(yes or no) following max pooling steps or dense layers, whether to sort our rows based on

similarity (yes or no), whether to log-scale our response variables (yes or no), and whether to

represent ancestral and derived alleles as -1/1 or as 0/255. When included, our dropout layers

immediately followed both max pooling steps, the dense layer following the distance input layer,

and the final dense layer. Each of these dropout steps randomly removed 25% of neurons. Each

response variable was transformed to a z-score according to the sample mean and variance for

that variable across all simulated examples.

The network we used for this task had two branches: a standard CNN like that depicted

in Fig. 1B–C but with more convolutional layers (four CNN layers each producing 128 filters and

each followed by a max pooling layer with a kernel size of 2), and a dense neural network layer

(consisting of 32 nodes) taking positional information as its input, and concatenating its output

with that of the final max pooling layer of the CNN prior to being fed into the final dense layer

(256 nodes). The positional information was a vector, **d**, whose length was the maximum of the

number of segregating sites observed across all simulated examples minus one. Each value in the

vector d_i was simply the distance (scaled between zero and one where one is the total length of the

simulated region) between segregating site i and site i-1.

In total, we simulated 100,000 alignments of phased chromosomes using `ms`. 10,000 each

were set aside for testing and validation, while the remaining 80,000 were used for training. The

simulated population size histories were generated randomly—each demographic model

parameter was drawn uniformly from a range listed in supplementary table S2. Each simulated

region was roughly equivalent 1.5 Mbp in the human genome, assuming per base pair mutation

and recombination rates of 1.2×10^{-8} and 1×10^{-8}, respectively. However, in order to make the size

of the simulation output more tractable for processing in a CNN we divided the mutation rate by

10 (equivalent to randomly downsampling the number of polymorphisms included in the input

by a factor of 10). During training we used a batch size of 200, trained our networks for up to 10

iterations, and retained the best performing CNN as assessed on the validation set. Often the best

CNN was obtained prior to completing all 10 training iterations. We then evaluated the

performance of the best CNN for each network architecture and input format on the test set by

calculating total RMSE (our loss function for this task); we also calculated Spearman correlation

coefficients between the true and predicted values for each of the five demographic model

parameters.

ACKNOWLEDGMENTS

We thank Matt Hahn for comments on the manuscript. DRS was funded by the National

Institutes of Health under award number R00HG008696. YB would like to acknowledge the

Minnesota Supercomputing Institute for computational resources.

REFERENCES

Arnold, B., K. Bomblies and J. Wakeley, 2012 Extending coalescent theory to autotetraploids.
Genetics **192:** 195-204.
Auton, A., L. D. Brooks, R. M. Durbin, E. P. Garrison, H. M. Kang *et al.*, 2015 A global
reference for human genetic variation. *Nature* **526:** 68-74.
Auton, A., and G. McVean, 2007 Recombination rate estimation in the presence of hotspots.
Genome Res. **17:** 1219-1227.
Beaumont, M. A., 2010 Approximate Bayesian computation in evolution and ecology. *Annual*
review of ecology, evolution, and systematics **41:** 379-406.
Begun, D. J., and C. F. Aquadro, 1992 Levels of naturally occurring DNA polymorphism
correlate with recombination rates in *D. melanogaster*. *Nature* **356:** 519-520.
Begun, D. J., A. K. Holloway, K. Stevens, L. W. Hillier, Y.-P. Poh *et al.*, 2007 Population
genomics: whole-genome analysis of polymorphism and divergence in Drosophila
simulans. *PLoS Biol.* **5:** e310.
Bellot, P., G. de los Campos and M. Pérez-Enciso, 2018 Can Deep Learning Improve Genomic
Prediction of Complex Human Traits? *Genetics***:** genetics. 301298.302018.
Boitard, S., C. Schlötterer and A. Futschik, 2009 Detecting selective sweeps: a new approach
based on hidden Markov models. *Genetics* **181:** 1567-1578.
Brandvain, Y., A. M. Kenney, L. Flagel, G. Coop and A. L. Sweigart, 2014 Speciation and
introgression between Mimulus nasutus and Mimulus guttatus. *PLoS Genet.* **10:** e1004410.
Breiman, L., 2001 Statistical modeling: The two cultures (with comments and a rejoinder by the
author). *Statistical science* **16:** 199-231.
Chan, A. H., P. A. Jenkins and Y. S. Song, 2012 Genome-wide fine-scale recombination rate
variation in Drosophila melanogaster. *PLoS Genet.* **8:** e1003090.
Chan, J., V. Perrone, J. P. Spence, P. A. Jenkins, S. Mathieson *et al.*, 2018 A Likelihood-Free
Inference Framework for Population Genetic Data using Exchangeable Neural Networks.
bioRxiv.
Charlesworth, B., M. Morgan and D. Charlesworth, 1993 The effect of deleterious mutations on
neutral molecular variation. *Genetics* **134:** 1289-1303.

Chilimbi, T. M., Y. Suzue, J. Apacible and K. Kalyanaraman, 2014 Project Adam: Building an
Efficient and Scalable Deep Learning Training System, pp. 571-582 in *OSDI*.
Corbett-Detig, R., and R. Nielsen, 2017 A hidden Markov model approach for simultaneously
estimating local ancestry and admixture time using next generation sequence data in
samples of arbitrary ploidy. *PLoS Genet.* **13:** e1006529.
Dieleman, S., and B. Schrauwen, 2014 End-to-end learning for music audio, pp. 6964-6968 in
Acoustics, Speech and Signal Processing (ICASSP), 2014 IEEE International Conference on. IEEE.
Dutheil, J. Y., G. Ganapathy, A. Hobolth, T. Mailund, M. K. Uyenoyama *et al.*, 2009 Ancestral
population genomics: the coalescent hidden Markov model approach. *Genetics* **183:** 259-
274.
Elyashiv, E., S. Sattath, T. T. Hu, A. Strutsovsky, G. McVicker *et al.*, 2016 A genomic map of
the effects of linked selection in Drosophila. *PLoS Genet.* **12:** e1006130.
Ewing, G., and J. Hermisson, 2010 MSMS: a coalescent simulation program including
recombination, demographic structure and selection at a single locus. *Bioinformatics* **26:**
2064-2065.
Fay, J. C., and C.-I. Wu, 2000 Hitchhiking under positive Darwinian selection. *Genetics* **155:**
1405-1413.
Ferrer-Admetlla, A., M. Liang, T. Korneliussen and R. Nielsen, 2014 On detecting incomplete
soft or hard selective sweeps using haplotype structure. *Mol. Biol. Evol.* **31:** 1275-1291.
Fontaine, M. C., J. B. Pease, A. Steele, R. M. Waterhouse, D. E. Neafsey *et al.*, 2015 Extensive
introgression in a malaria vector species complex revealed by phylogenomics. *Science* **347:**
1258524.
Fu, Y.-X., and W.-H. Li, 1993 Statistical tests of neutrality of mutations. *Genetics* **133:** 693-709.
Gao, F., C. Ming, W. Hu and H. Li, 2016 New software for the fast estimation of population
recombination rates (FastEPRR) in the genomic era. *G3: Genes, Genomes, Genetics* **6:** 1563-
1571.
Garrigan, D., S. B. Kingan, A. J. Geneva, P. Andolfatto, A. G. Clark *et al.*, 2012 Genome
sequencing reveals complex speciation in the Drosophila simulans clade. *Genome Res.* **22:**
1499-1511.
Garud, N. R., P. W. Messer, E. O. Buzbas and D. A. Petrov, 2015 Recent selective sweeps in
North American Drosophila melanogaster show signatures of soft sweeps. *PLoS Genet.* **11:**
e1005004.
Gazave, E., L. Ma, D. Chang, A. Coventry, F. Gao *et al.*, 2014 Neutral genomic regions refine
models of recent rapid human population growth. *Proceedings of the National Academy of*
Sciences **111:** 757-762.
Geneva, A. J., C. A. Muirhead, S. B. Kingan and D. Garrigan, 2015 A new method to scan
genomes for introgression in a secondary contact model. *PLoS ONE* **10:** e0118621.
Gutenkunst, R. N., R. D. Hernandez, S. H. Williamson and C. D. Bustamante, 2009 Inferring
the joint demographic history of multiple populations from multidimensional SNP
frequency data. *PLoS Genet.* **5:** e1000695.
Hahn, M. W., 2018 *Molecular Population Genetics*. Oxford University Press.
Hahnloser, R. H., R. Sarpeshkar, M. A. Mahowald, R. J. Douglas and H. S. Seung, 2000 Digital
selection and analogue amplification coexist in a cortex-inspired silicon circuit. *Nature*
405: 947.
Haller, B., and P. Messer, 2017 SLiM 2: Flexible, Interactive Forward Genetic Simulations. *Mol.*
Biol. Evol. **34:** 230.

Hedrick, P. W., 2013 Adaptive introgression in animals: examples and comparison to new
mutation and standing variation as sources of adaptive variation. *Mol. Ecol.* **22:** 4606-
4618.
Hellenthal, G., G. B. Busby, G. Band, J. F. Wilson, C. Capelli *et al.*, 2014 A genetic atlas of
human admixture history. *Science* **343:** 747-751.
Hermisson, J., and P. S. Pennings, 2005 Soft sweeps molecular population genetics of adaptation
from standing genetic variation. *Genetics* **169:** 2335-2352.
Hey, J., 2009 Isolation with migration models for more than two populations. *Mol. Biol. Evol.* **27:**
905-920.
Hey, J., and J. Wakeley, 1997 A coalescent estimator of the population recombination rate.
Genetics **145:** 833-846.
Hill, W. G., and A. Robertson, 1966 The effect of linkage on limits to artificial selection. *Genetics*
Research **8:** 269-294.
Hobolth, A., O. F. Christensen, T. Mailund and M. H. Schierup, 2007 Genomic relationships
and speciation times of human, chimpanzee, and gorilla inferred from a coalescent
hidden Markov model. *PLoS Genet.* **3:** e7.
Hornik, K., 1991 Approximation capabilities of multilayer feedforward networks. *Neural networks*
4: 251-257.
Hudson, R. R., 1987 Estimating the recombination parameter of a finite population model
without selection. *Genetics Research* **50:** 245-250.
Hudson, R. R., 2001 Two-locus sampling distributions and their application. *Genetics* **159:** 1805-
1817.
Hudson, R. R., 2002 Generating samples under a Wright–Fisher neutral model of genetic
variation. *Bioinformatics* **18:** 337-338.
Hudson, R. R., and N. L. Kaplan, 1985 Statistical properties of the number of recombination
events in the history of a sample of DNA sequences. *Genetics* **111:** 147-164.
Jensen, J. D., Y. Kim, V. B. DuMont, C. F. Aquadro and C. D. Bustamante, 2005
Distinguishing between selective sweeps and demography using DNA polymorphism
data. *Genetics* **170:** 1401-1410.
Joly, S., P. A. McLenachan and P. J. Lockhart, 2009 A statistical approach for distinguishing
hybridization and incomplete lineage sorting. *The American Naturalist* **174:** E54-E70.
Jouppi, N. P., C. Young, N. Patil, D. Patterson, G. Agrawal *et al.*, 2017 In-datacenter
performance analysis of a tensor processing unit, pp. 1-12 in *Proceedings of the 44th Annual*
International Symposium on Computer Architecture. ACM.
Kaplan, N. L., R. Hudson and C. Langley, 1989 The" hitchhiking effect" revisited. *Genetics* **123:**
887-899.
Kelleher, J., A. M. Etheridge and G. McVean, 2016 Efficient coalescent simulation and
genealogical analysis for large sample sizes. *PLoS Comput. Biol.* **12:** e1004842.
Kelleher, J., K. Thornton, J. Ashander and P. Ralph, 2018 Efficient pedigree recording for fast
population genetics simulation. *bioRxiv*: 248500.
Kelly, J. K., 1997 A test of neutrality based on interlocus associations. *Genetics* **146:** 1197-1206.
Kern, A. D., and D. Haussler, 2010 A population genetic hidden Markov model for detecting
genomic regions under selection. *Mol. Biol. Evol.* **27:** 1673-1685.
Kern, A. D., and D. R. Schrider, 2016 discoal: flexible coalescent simulations with selection.
Bioinformatics **32:** btw556.
Kim, Y., 2014 Convolutional neural networks for sentence classification. *arXiv preprint*
arXiv:1408.5882.

Kim, Y., and R. Nielsen, 2004 Linkage disequilibrium as a signature of selective sweeps. *Genetics* **167:** 1513-1524.

Kim, Y., and W. Stephan, 2002 Detecting a local signature of genetic hitchhiking along a recombining chromosome. *Genetics* **160:** 765-777.

Kingma, D. P., and J. Ba, 2014 Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*.

Kong, A., G. Thorleifsson, D. F. Gudbjartsson, G. Masson, A. Sigurdsson *et al.*, 2010 Fine-scale recombination rate differences between sexes, populations and individuals. *Nature* **467:** 1099-1103.

Korneliussen, T. S., A. Albrechtsen and R. Nielsen, 2014 ANGSD: analysis of next generation sequencing data. *BMC Bioinformatics* **15:** 356.

Köster, U., T. Webb, X. Wang, M. Nassar, A. K. Bansal *et al.*, 2017 Flexpoint: An adaptive numerical format for efficient training of deep neural networks, pp. 1742-1752 in *Advances in Neural Information Processing Systems*.

Krizhevsky, A., I. Sutskever and G. E. Hinton, 2012 Imagenet classification with deep convolutional neural networks, pp. 1097-1105 in *Advances in neural information processing systems*.

Kulathinal, R. J., L. S. Stevison and M. A. Noor, 2009 The genomics of speciation in Drosophila: diversity, divergence, and introgression estimated using low-coverage genome sequencing. *PLoS Genet.* **5:** e1000550.

Langley, C. H., K. Stevens, C. Cardeno, Y. C. G. Lee, D. R. Schrider *et al.*, 2012 Genomic variation in natural populations of *Drosophila melanogaster*. *Genetics* **192:** 533-598.

Lawrence, S., C. L. Giles, A. C. Tsoi and A. D. Back, 1997 Face recognition: A convolutional neural-network approach. *IEEE transactions on neural networks* **8:** 98-113.

Lawson, D. J., G. Hellenthal, S. Myers and D. Falush, 2012 Inference of population structure using dense haplotype data. *PLoS Genet.* **8:** e1002453.

LeCun, Y., Y. Bengio and G. Hinton, 2015 Deep learning. *Nature* **521:** 436-444.

LeCun, Y., L. Bottou, Y. Bengio and P. Haffner, 1998 Gradient-based learning applied to document recognition. *Proceedings of the IEEE* **86:** 2278-2324.

Li, H., and R. Durbin, 2011 Inference of human population history from individual whole-genome sequences. *Nature* **475:** 493-496.

Li, N., and M. Stephens, 2003 Modeling linkage disequilibrium and identifying recombination hotspots using single-nucleotide polymorphism data. *Genetics* **165:** 2213-2233.

Lin, K., A. Futschik and H. Li, 2013 A fast estimate for the population recombination rate based on regression. *Genetics* **194:** 473-484.

Lin, K., H. Li, C. Schlötterer and A. Futschik, 2011 Distinguishing positive selection from neutral evolution: boosting the performance of summary statistics. *Genetics* **187:** 229-244.

Lipson, M., P.-R. Loh, A. Levin, D. Reich, N. Patterson *et al.*, 2013 Efficient moment-based inference of admixture parameters and sources of gene flow. *Mol. Biol. Evol.* **30:** 1788-1802.

Liu, X., and Y.-X. Fu, 2015 Exploring population size changes using SNP frequency spectra. *Nat. Genet.* **47:** 555-559.

Loh, P.-R., M. Lipson, N. Patterson, P. Moorjani, J. K. Pickrell *et al.*, 2013 Inferring admixture histories of human populations using linkage disequilibrium. *Genetics* **193:** 1233-1254.

Lu, X., Z. Lin, X. Shen, R. Mech and J. Z. Wang, 2015 Deep multi-patch aggregation network for image style, aesthetics, and quality estimation, pp. 990-998 in *Proceedings of the IEEE International Conference on Computer Vision*.

Marth, G. T., E. Czabarka, J. Murvai and S. T. Sherry, 2004 The allele frequency spectrum in genome-wide human variation data reveals signals of differential demographic history in three large world populations. *Genetics* **166:** 351-372.

Martin, S. H., K. K. Dasmahapatra, N. J. Nadeau, C. Salazar, J. R. Walters *et al.*, 2013 Genome-wide evidence for speciation with gene flow in Heliconius butterflies. *Genome Res.* **23:** 1817-1828.

Maynard Smith, J., and J. Haigh, 1974 The hitch-hiking effect of a favourable gene. *Genet. Res.* **23:** 23-35.

McVean, G. A., S. R. Myers, S. Hunt, P. Deloukas, D. R. Bentley *et al.*, 2004 The fine-scale structure of recombination rate variation in the human genome. *Science* **304:** 581-584.

Mitchell, T. M., 1997 Artificial neural networks. *Machine Learning* **45:** 81-127.

Nair, V., and G. E. Hinton, 2010 Rectified linear units improve restricted boltzmann machines, pp. 807-814 in *Proceedings of the 27th international conference on machine learning (ICML-10)*.

Nielsen, R., and J. Wakeley, 2001 Distinguishing migration from isolation: a Markov chain Monte Carlo approach. *Genetics* **158:** 885-896.

Nielsen, R., S. Williamson, Y. Kim, M. J. Hubisz, A. G. Clark *et al.*, 2005 Genomic scans for selective sweeps using SNP data. *Genome Res.* **15:** 1566-1575.

Pavlidis, P., J. D. Jensen and W. Stephan, 2010 Searching for footprints of positive selection in whole-genome SNP data from nonequilibrium populations. *Genetics* **185:** 907-922.

Price, A. L., A. Tandon, N. Patterson, K. C. Barnes, N. Rafaels *et al.*, 2009 Sensitive detection of chromosomal segments of distinct ancestry in admixed populations. *PLoS Genet.* **5:** e1000519.

Pudlo, P., J.-M. Marin, A. Estoup, J.-M. Cornuet, M. Gautier *et al.*, 2016 Reliable ABC model choice via random forests. *Bioinformatics* **32:** 859-866.

Pybus, M., P. Luisi, G. M. Dall'Olio, M. Uzkudun, H. Laayouni *et al.*, 2015 Hierarchical boosting: a machine-learning framework to detect and classify hard selective sweeps in human populations. *Bioinformatics* **31:** 3946-3952.

Racimo, F., D. Marnetto and E. Huerta-Sanchez, 2016 Signatures of archaic adaptive introgression in present-day human populations. *Mol. Biol. Evol.* **34:** 296-317.

Rasmussen, M. D., M. J. Hubisz, I. Gronau and A. Siepel, 2014 Genome-wide inference of ancestral recombination graphs.

Ribeiro, M. T., S. Singh and C. Guestrin, 2016 Why should i trust you?: Explaining the predictions of any classifier, pp. 1135-1144 in *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*. ACM.

Ronen, R., N. Udpa, E. Halperin and V. Bafna, 2013 Learning natural selection from the site frequency spectrum. *Genetics* **195:** 181-193.

Rosenzweig, B. K., J. B. Pease, N. J. Besansky and M. W. Hahn, 2016 Powerful methods for detecting introgressed regions from population genomic data. *Mol. Ecol.* **25:** 2387-2397.

Rumelhart, D. E., G. E. Hinton and R. J. Williams, 1986 Learning representations by back-propagating errors. *Nature* **323:** 533.

Sankararaman, S., S. Mallick, M. Dannemann, K. Prüfer, J. Kelso *et al.*, 2014 The genomic landscape of Neanderthal ancestry in present-day humans. *Nature* **507:** 354-357.

Schiffels, S., and R. Durbin, 2014 Inferring human population size and separation history from multiple genome sequences. *Nat. Genet.* **46:** 919-925.

Schlötterer, C., R. Tobler, R. Kofler and V. Nolte, 2014 Sequencing pools of individuals— mining genome-wide polymorphism data without big funding. *Nature Reviews Genetics* **15:** 749.

Schrider, D., J. Ayroles, D. R. Matute and A. D. Kern, 2018 Supervised machine learning
reveals introgressed loci in the genomes of *Drosophila simulans* and *D. sechellia*. *PLoS Genet.*
14: e1007341.
Schrider, D. R., and A. D. Kern, 2015 Inferring selective constraint from population genomic
data suggests recent regulatory turnover in the human brain. *Genome Biol. Evol.* **7:** 3511-
3528.
Schrider, D. R., and A. D. Kern, 2016 S/HIC: Robust Identification of Soft and Hard Sweeps
Using Machine Learning. *PLoS Genet.* **12:** e1005928.
Schrider, D. R., and A. D. Kern, 2017 Soft sweeps are the dominant mode of adaptation in the
human genome. *Mol. Biol. Evol.* **34:** 1863–1877.
Schrider, D. R., and A. D. Kern, 2018 Supervised Machine Learning for Population Genetics: A
New Paradigm. *Trends Genet.* **34:** 301-312.
Schrider, D. R., F. K. Mendes, M. W. Hahn and A. D. Kern, 2015 Soft shoulders ahead:
spurious signatures of soft and partial selective sweeps result from linked hard sweeps.
Genetics **200:** 267-284.
Sheehan, S., and Y. S. Song, 2016 Deep learning for population genetic inference. *PLoS Comput.*
Biol. **12:** e1004845.
Simonsen, K. L., G. A. Churchill and C. F. Aquadro, 1995 Properties of statistical tests of
neutrality for DNA polymorphism data. *Genetics* **141:** 413-429.
Simonyan, K., and A. Zisserman, 2014 Very deep convolutional networks for large-scale image
recognition. *arXiv preprint arXiv:1409.1556*.
Smith, J., G. Coop, M. Stephens and J. Novembre, 2018 Estimating time to the common
ancestor for a beneficial allele. *Mol. Biol. Evol.*
Snoek, J., H. Larochelle and R. P. Adams, 2012 Practical bayesian optimization of machine
learning algorithms, pp. 2951-2959 in *Advances in neural information processing systems*.
Sohn, K.-A., Z. Ghahramani and E. P. Xing, 2012 Robust estimation of local genetic ancestry in
admixed populations using a nonparametric Bayesian approach. *Genetics* **191:** 1295-1308.
Srivastava, N., G. Hinton, A. Krizhevsky, I. Sutskever and R. Salakhutdinov, 2014 Dropout: A
simple way to prevent neural networks from overfitting. *The Journal of Machine Learning*
Research **15:** 1929-1958.
Sugden, L. A., E. G. Atkinson, A. P. Fischer, S. Rong, B. M. Henn *et al.*, 2018 Localization of
adaptive variants in human genomes using averaged one-dependence estimation. *Nature*
Communications **9:** 703.
Szegedy, C., W. Liu, Y. Jia, P. Sermanet, S. Reed *et al.*, 2015 Going deeper with convolutions,
pp. in *CVPR*.
Tajima, F., 1989 Statistical method for testing the neutral mutation hypothesis by DNA
polymorphism. *Genetics* **123:** 585-595.
Tennessen, J. A., A. W. Bigham, T. D. O'Connor, W. Fu, E. E. Kenny *et al.*, 2012 Evolution and
functional impact of rare coding variation from deep sequencing of human exomes.
Science **337:** 64-69.
Teshima, K. M., and H. Innan, 2009 mbs: modifying Hudson's ms software to generate samples
of DNA sequences with a biallelic site under selection. *BMC Bioinformatics* **10:** 166.
Thornton, K. R., 2014 A C++ template library for efficient forward-time population genetic
simulation of large populations. *Genetics* **198:** 157-166.
Turner, T. L., M. W. Hahn and S. V. Nuzhdin, 2005 Genomic islands of speciation in
Anopheles gambiae. *PLoS Biol.* **3:** e285.

Voight, B. F., S. Kudaravalli, X. Wen and J. K. Pritchard, 2006 A map of recent positive
selection in the human genome. *PLoS Biol.* **4:** e72.
Vy, H. M. T., and Y. Kim, 2015 A Composite-Likelihood Method for Detecting Incomplete
Selective Sweep from Population Genomic Data. *Genetics* **200:** 633-649.
Washburn, J. D., M. K. M. Guerra, G. Ramstein, K. A. Kremling, R. Valluru *et al.*, 2018
Evolutionarily informed deep learning methods: Predicting transcript abundance from
DNA sequence. *bioRxiv*: 372367.
Yu, F., and V. Koltun, 2015 Multi-scale context aggregation by dilated convolutions. *arXiv*
preprint arXiv:1511.07122.
Zaheer, M., S. Kottur, S. Ravanbakhsh, B. Poczos, R. R. Salakhutdinov *et al.*, 2017 Deep sets,
pp. 3394-3404 in *Advances in Neural Information Processing Systems*.

1238

1239

1240 **SUPPLEMENTARY TABLE LEGENDS**

1241

1242 **Supplementary table S1: The effect of different neural network**

1243 **input/output/architecture hyperparameters on demographic inference error.**

1244

1245 **Supplementary table S2: Demographic parameter ranges used to simulate 3-epoch**

1246 **population size histories.**