1

Robust mouse tracking in complex environments

using neural networks

Brian Q. Geuther, Sean P. Deats, Kai J. Fox, Steve A. Murray, Robert E. Braun,

Jacqueline K. White, Elissa J. Chesler, Cathleen M. Lutz, Vivek Kumar*

The Jackson Laboratory, Bar Harbor, ME, United States of America

* Corresponding author

Email: vivek.kumar@jax.org (VK)

Abstract

The ability to track animals accurately is critical for behavioral experiments. For video-based assays, this is often accomplished by manipulating environmental conditions to increase contrast between the animal and the background, in order to achieve proper foreground/background detection (segmentation). However, as behavioral paradigms become more sophisticated with ethologically relevant environments, the approach of modifying environmental conditions offers diminishing returns, particularly for scalable experiments. Currently, there is a need for methods to monitor behaviors over long periods of time, under dynamic environmental conditions, and in animals that are genetically and behaviorally heterogeneous. To address this need, we developed a state-of-the-art neural network-based tracker for mice, using modern machine vision techniques. We test three different neural network architectures to determine their performance on genetically diverse mice under varying environmental conditions. We find that an encoder-decoder segmentation neural network achieves high accuracy and speed with minimal training data. Furthermore, we provide a labeling interface, labeled training data, tuned hyperparameters, and a pre-trained network for the mouse behavior and neuroscience communities. This general-purpose neural network tracker can be easily extended to other experimental paradigms and even to other animals, through transfer learning, thus providing a robust, generalizable solution for biobehavioral research.

Author summary

Accurate tracking of animals is critical for behavioral experiments, however tracking in complex environments has been a long-standing issue in neurogenetics. If the environment changes during the test or if occlusion occurs, then tracking using existing methods often fails. These technological constraints limit the complexity of behavioral paradigms that can be carried out. Here we use modern convolutional neural networks to overcome these limitations and design a trainable mouse tracker for complex and dynamic environments. We test several neural network architectures and show that a single trained network can track all strains of mice we have tested consisting of various coat colors, body shapes, and behaviors. We provide a labeling interface, labeled training data, tuned hyperparameters, and a pre-trained network for the mouse behavior and neuroscience communities.

Introduction

Behavior is primarily an output of the nervous system in response to internal or external stimuli. It is hierarchical, dynamic, and high dimensional, and is generally simplified for analysis [1, 2]. For instance, the rich locomotor movement performed by a mouse that is captured in video is routinely abstracted to either a simple point, a center of mass, or an ellipse for analysis. In order to do this well with current methods, the experimental environment is simplified to obtain optimal contrast between the mouse and background for proper segmentation. Segmentation, a form of background subtraction, classifies pixels belonging to mice from background in video and enables these high level abstractions to be mathematically calculated. During mouse experimental assays, the arena background color is often changed depending on the animal's coat color, potentially altering the behavior itself [3-5]. Making such changes comes at a cost, as current video tracking technologies cannot be applied in complex and dynamic environments or with genetically heterogeneous animals without a high level of user involvement, making both long term experiements and large experiments unfeasible. As neuroscience and behavior moves into an era of big behavioral data [2] and computational ethology [6], current tracking methods are inadequate and improved methods are necessary that enable tracking animals in semi-natural and dynamic environments over long periods of time. To address this shortfall, we developed a robust scalable method of mouse tracking in an open field using modern convolutional neural network architecture. Our trained neural network is capable of tracking all commonly used strains of mice—including mice with different coat colors, body shapes, and behaviors—under multiple experimental conditions without any user-involved adjustment of tracking parameters. Thus we present a scalable and robust solution that allows tracking in diverse experimental conditions.

Results

We first used existing tracking methods to track 59 different mouse strains in multiple

environments, and found them inadequate for our large-scale strain survey experiment (1,845

videos, 1,691 hours). Specifically, we tracked all the videos in this experiment using Ctrax [7], a

modern open-source tracking software package that uses background subtraction and blob

detection heuristics, and LimeLight (Actimetrics, Wilmette, IL), a commercially available tracking

software package that uses a proprietary tracking algorithm. Ctrax abstracts a mouse on a per

frame basis to five metrics: major and minor axis, x and y location of center of the mouse, and

the direction of the animal [7]. It utilizes the MOG2 background subtraction model, whereby the

software estimates both the mean and variation of the background of the video for use in

background subtraction. Ctrax uses the shape of the predicted foreground to fit ellipses.

LimeLight uses a single key-frame background model for segmentation and detection. Once a

mouse is detected using LimeLight, this software package abstracts the mouse to a center of

mass using a proprietary algorithm.

Our strain survey experiment includes videos of mice with different genetic backgrounds

causing expression of different coat colors including black, agouti, albino, grey, brown, nude,

and piebald (Fig. 1A, columns 1, 2, 3 and 4). We tracked all animals in the same open field

apparatus, which had a white background; this yielded good results for darker mice (black and

agouti mice), but poor results for lighter-colored (albino and grey mice) or piebald mice (Fig. 1A,

columns 1, 2, 3 and 4, S1 Video). Examples of ideal and actual tracking frames are shown for

the various coat colors (Fig. 1A, row 3 and 4 respectively).

Fig. 1. Proposed solutions for our tracking problem. (A) A representation of the environments
analyzed by existing approaches. A black mouse in a white open field achieves high foreground-
background contrast, and therefore actual tracking closely matches the ideal (column 1). Grey mice are
visually similar to the grey-colored arena walls and therefore often have their noses, which are grey,
removed while rearing on walls (column 2). Albino mice are visually very similar to the white arena floor
and are frequently not found during tracking (column 3). Piebald mice are broken in half by the tracking
software due to their patterned coat color (column 4). Placing a food cup, that is visually similar to the
mouse, into the arena causes tracking issues when the mouse climbs on top of the food cup (column 5).
Arenas with reflective surfaces also produce errors with tracking algorithms (column 6). (B) We identified

the cause of bad tracking as poor segmentation. However, testing a variety of difficult frames with multiple background subtraction algorithms from the background subtraction library, we did not resolve this segmentation issue. From top to bottom the background subtraction algorithms shown are: SuBSENSE, Adaptive Median, Adaptive Background Learning, MultiCue BGS, and LOBSTER. (C) Our objective tracking takes the form of an ellipse description of a mouse. For clarity, we show a cropped frame as input into the networks, whereas the actual input is an unmarked full frame. (D) The structure of the segmentation network architecture functions similarly to classical tracking approaches in which the network predicts the segmentation mask for the mouse and then fits an ellipse to the predicted mask. (E) The structure of the binned classification network architecture predicts a probability distribution of the value for each ellipse-fit parameter, represented by the table where a max value is selected. Only three parameters of the six ellipse-fit parameters are visually shown (X = center x-location, Major = major axis length, Angle = direction of the mouse's nose). (F) The structure of the regression network architecture directly predicts the 6 parameters used to describe an ellipse for tracking.

We also carried out video analysis of behavior in challenging environments including both 24-hour experimental videos that added bedding and a food cup to our open field arena, and videos from the open field experiment carried out as part of The Jackson Laboratory KOMP2 (Knockout Mouse Phenotyping Project) [8] Phenotyping Center (Fig. 1A, column 5, 6, respectively). In the 24-hour experiment, we collected data over multiple days in which mice were housed in the open field with white paper bedding and food cup. The mice were kept in the open field in this multiday data collection paradigm, and continuous recording was carried out in light and dark conditions using an infrared light source. The bedding and food cups were moved by the mouse and the imaging light source alternated between infrared and visible light over the course of each day. The KOMP2 experiment uses a beam-break system in which mice are placed in a clear acrylic arena with infrared beams on all sides. Since the floor of the arena is clear acrylic, the surface of the table on which the arenas were placed shows through as dark grey. In addition, one arena was placed on the junction between two tables, leaving the joint visible. Further, the LED lights overhead caused a very high glare unique to each arena (S2 Video). This KOMP2 program has collected over five years of data using this system, and we wanted to carry out video-based recording as an added analysis modality to detect gait affects that cannot be identified by beam-break systems. Since environmental alterations could affect the behavioral output and legacy data interpretation, we could not optimize or otherwise alter the environment for video data collection. Instead, we simply added a camera on top of each arena.

Traditionally, contrast and reflection hurdles could be overcome by changing the environment

such that video data collection is optimized for analysis. For instance, to track albino mice, one

can increase contrast by changing the background color of the open field to black. However, the

color of the environment can effect the behavior of both mice and humans, and such

manipulations can potentially confound the experimental results [3, 4]. Regardless, such

solutions will not work for piebald mice in a standard open field, or any mice in either the 24-hour

data collection experiment or the KOMP2 arena.

We found that the combination of mouse coat colors and environments were difficult to

handle with Ctrax (S1 Video) and LimeLight. We optimized and fine-tuned Ctrax for each video

(Methods) in each of the three experiments and still found a significant number frames with poor

tracking performance (Fig. 1A, row 4). Such optimization or tuning of background model was not

feasible with LimeLight. The frequency of poor tracking instances in an individual video

increased as the environment became less ideal for tracking. We discovered these errors in

ellipse fitting lead to larger errors in classifying behaviors using the Ctrax tracking output in

supervised classification using Janelia Automatic Animal Behavior Annotator (JAABA)[9]. Thus,

even the seemingly minor errors seen in grey and black mice (S1 Video) decreased

performance when the tracking data were used for behavior classification. Furthermore, the

distribution of the errors was not random; for example, tracking was highly inaccurate when mice

were in the corners, near walls, or on food cups (Fig. 1A, row 4), and less inaccurate when

animals were in the center (S1 Video). While it is feasible to discard poorly tracked frames, this

can lead to biased sampling and skewed biological interpretation.

We explored the cause of bad tracking across our three experiments and discovered

that, in most cases, improper tracking was due to poor segmentation of the mouse from the

background. This included both types of errors: Type I, instances when portions of the

background are included as the foreground (e.g. shadows), and Type II, instances when

portions of the mouse are removed from the foreground (e.g. albino mouse matching the

background color). Since Ctrax uses a single background model algorithm, we tested whether

other background model algorithms could improve tracking results. We tested 26 different

segmentation algorithms [10] and discovered that each of these traditional algorithms performs

well under certain circumstances and fail in others (Fig. 1B). Other available tracking software

packages including CADABRA [11], EthoVision [12], idTracker [13], MiceProfiler [14], MOTR

[15], Cleversys TopScan (http://cleversysinc.com/CleverSysInc/), Autotyping [16], and

Automated Rodent Tracker [17], all of which rely on background subtraction approaches for

tracking. Since all 26 background subtraction methods failed in some circumstances, we

postulate that our results for Ctrax and LimeLight will hold true for these other technologies. In

sum, although many video tracking solutions exist, none address the fundamental problem of

mouse segmentation appropriately and generally rely on environmental optimization to achieve

proper segmentation, therefore creating potential confounds with respect to robust data

sampling and analysis. Thus, we could not overcome the fundamental issue of proper mouse

segmentation in order to achieve high-fidelity mouse tracking with existing solutions.

A drawback in addition to the problem of inadequate mouse segmentation was the time

cost for fine-tuning Ctrax's settings or another background subtraction algorithm's parameters.

Fine-tuning the tracking settings for each video added significant time to our workflow when

analyzing thousands of videos. For example, in tracking data from the 24-hour experiment, when

mice were sleeping in one posture for an extended period of time, the mouse became part of the

background model and could not be tracked. Typical supervision, such as using the Ctrax

settings supervision protocol we outline in our methods, would take an experienced user 5

minutes of interaction for each hour of video to ensure high-quality tracking results. While this

level of user interaction is tractable for smaller and more restricted experiments, large-scale and

long-term experiments require a large time commitment to supervise the tracking performance.

We sought to overcome these difficulties by building a robust-next generation mouse

tracker that uses neural networks and achieves high performance under complex and dynamic

environmental conditions, is indifferent to coat color, and does not require persistent fine tuning

by the user. Convolutional neural networks are computational models that are composed of

multiple spatial processing layers that learn representations of data with multiple levels of

abstraction. These methods have dramatically improved the state-of-the-art in speech

recognition, visual object recognition, object detection, and many other domains such as drug

discovery and genomics [18]. One of the key advantages of neural networks is that once an

efficient network with suitable hyperparameters has been developed, it can easily be extended

to other tasks by simply adding appropriate training data [19]. Thus, we sought to build a highly

generalizable solution for mouse tracking.

We tested three primary neural network architectures for solving this visual tracking

problem (Fig. 1D-E). Each approach attempted to describe the location of the animal through six

variables: x and y location of the mouse in the matrix, major and minor axes of the mouse, and

the angle the head is facing (Fig. 1C). To avoid the discontinuity of equivalent repeating angles,

the networks predict the sine and cosine of the angle.

The first architecture is an encoder-decoder segmentation network that predicts a

foreground-background segmented image from a given input frame (Fig. 1D). This network

predicts on a pixel-wise basis whether there is a mouse or no mouse, with the output being a

segmentation mask. The segmentation mask identifies all the pixels in the image that belong to

the mouse. The primary structure of this architecture starts with a feature encoder, which

abstracts the input image down into a small-spatial-resolution set of features. The encdoded

features are then passed to a feature decoder that converts this set of features back into the

same shape as the original input image. Additionally, the encoded features are also passed to

three fully connected layers to predict which cardinal direction the ellipse is facing. We trained

this feature decoder to produce a foreground-background segmented image. After the network

produces this segmented image, we applied an ellipse-fitting algorithm for tracking (Note A in S1

Information).

The second network architecture is a binned classification network, whereby a probability

distribution across a pre-defined range of possible values is predicted for each of the 6 ellipse-fit

parameters (Fig. 1E). This network architecture begins with a feature encoder that abstracts the

input image down into a small-spatial-resolution set of features. The encoded features are

flattened and connected to additional fully connected layers whose output shape is determined

by the desired resolution of the output. For instance, at a desired resolution of 1 pixel for the x-

coordinate location of the mouse, there are 480 possible x-values to select from for a 480 x 480

px image. As such, the network contains 480 values (bins) to select from, one bin for each x-

column in the 480 x 480 px image. When the network is run, the largest value in each heatmap

is selected as the most probable value of the corresponding parameter. Each desired output

parameter is realized as an independent set of trainable fully connected layers connected to the

encoded features.

The third architecture is a regression network that predicts the numerical ellipse values

directly from the input image (Fig. 1F). The network architecture begins with a feature encoder

that abstracts the input down into a small spatial resolution. These encoded features are then

flattened and connected to fully connected layers to produce an output shape of 6, the number

of values that we ask the network to predict to fit an ellipse. We tested a variety of currently

available general purpose feature encoders, and present data from the feature encoder Resnet

V2 [20] with 200 convolutional layers, which achieved the best performing results for this

architecture.

To test the neural network architectures, we built a training dataset of 16,234 training

images and 568 separate validation images across multiple mouse strains and experimental

setups (Note B in S1 Information). Annotated training images were augmented eightfold during

training by applying reflections. Additionally, training images were further augmented by adding

small random changes in contrast, brightness, and rotations to make the network robust to minor

fluctuations in input data. We created an OpenCV-based labeling interface for creating our

training data (Methods) that allows us to quickly label foreground and background, and fit an

ellipse (S1 Fig.). This labeling interface can be used to quickly generate annotated training data

in order to adapt any network to new experimental conditions through transfer learning.

Our network architectures were built, trained, and tested in Tensorflow v1.0, an open-

source software library for designing applications that use neural networks [21]. Training

benchmarks presented were conducted on the Nvidia P100 GPU architecture. We tuned the

hyperparameters through several training iterations. After the first training of networks, it was

observed that the networks performed poorly under particular circumstances that had not been

included in the annotated data, including mid-jump, odd postures, and urination in the arena.We

identified and incorporated these difficult frames into our training dataset to further improve

performance. A full description of the network architecture definitions and training

hyperparameters are available (Methods, Table A in S1 Information). Overall, training and

validation loss curves indicated that each of the three network architectures trains to a

performance with an average error between 1 and 2 pixels (Fig. 2A). The encoder-decoder

segmentation architecture converged to a validation error of 0.9px (Fig. 2 A, B, C). Surprisingly,

upon inspection of the validation curve for the binned classification network we found that it

displayed unstable loss curves, indicating overfitting and poor generalization (Fig. 2B, E). The

regression architecture converged to a validation error of 1.2 px, showing a better training than

validation performance (Fig. 2A, B, D).

Fig. 2. Neural network performance metrics. (A-E) Performance of our tested network architectures
during trainings. (A) Training curves show comparable performances of the three architectures during
training, independent of the network architecture. (B) Validation curves show different performances
across the three network architectures. The encoder-decoder segmentation network performs the best.
(C, D, E) Comparison of training and validation performance curves, by network architecture type. (C)
Performance increases for validation in our encoder-decoder segmentation network architecture. (D)
Performance decreases for validation in our regression network architecture, but a good generalization
performance is maintained by asymptotically converging to a value. (E) The binned classification network
architecture becomes unstable at 55 epochs of training, even though the training curve shows continued
improved performance at this timepoint. (F) Comparing our encoder-decoder segmentation network
architecture with a beam break system, we observe a high correlation. Each point represents an individual
video tracked using both our neural network and a beam break system. Our network performs
consistently, even though the arenas are visually different from one another. We identify two videos of
individual mice that deviate the from this trend (red arrows). (G) Predictions from two approaches yield
high agreement on environments with high contrast between the mouse and background (black, grey, and
piebald mice in the white background open-field assay). As the segmentation problem becomes more
computationally difficult, the relative error increases (albino mice in the white background open-field assay
black mice in the 24-hr assay, KOMP2 experiment). Due to low activity in the 24-hr setup, minor errors in
tracking have a large influence on measurements of thetotal distance traveled. Points indicate individuals
in a group, bars indicate mean +/- standard deviation. (H) Relative standard deviation of the minor axis
maintains a high correlation when the mouse and environment have a high contrast (black mice in the
white background open-field assay). When segmentation includes shadows, includes reflections, or
removes portions of the mouse, the minor axis length is not properly predicted and increases the relative
standard deviation (grey, piebald, and albino mice in the white background open-field assay, black mice in
the 24-hour assay, KOMP2 experiment). Points indicate individuals in a group, bars indicate mean +/-
standard deviation.

Not only does the encoder-decoder segmentation architecture perform well, but it also is

computationally efficient for GPU compute, requiring an average processing time of 5-6ms per

frame. With the encoder-decoder segmentation architecture, our video data could be processed

at a rate of up to 200 frames per second (fps) (6.7X realtime) on a Nvidia P100, which is a

server-grade GPU.; and a rate of up to 125 fps (4.2X realtime) on a Nvidia TitanXP, a consumer-

grade GPU. This high processing speed is likely due to the structure of the encoder-decoder

segmentation architecture, as it is only 18 layers deep and contains only 10.6 million trainable

parameters. In comparison, Resnet V2 200, the feature extractor that gave the best results for

the regression architecture, is a large and deep network with over 200 layers and 62.7 million

trainable parameters and leads to a substantially longer processing time per frame (33.6ms on a

Nvidia P100). Other pre-built general-purpose networks [22] achieve similar or worse

performances at a tradeoff of faster compute time. Thus, regression networks are an accurate

but computationally expensive solution.

We also tested the minimum training dataset size required to train the encoder-decoder

segmentation network, by randomly subsetting our training dataset to smaller numbers of

annotated images (10,000 to 500) and training the network from the beginning. Surprisingly, we

obtained good results from a network trained with only 2,500 annotated images, a task that

takes approximately three hours to generate with our labeling interface (S2 Fig.). Given the

computational efficiency, accuracy, and training stability of the encoder-decoder segmentation

architecture, and the small training dataset size that it requires, we concluded that this

architecture is optimal for our needs. We used this trained neural network to predict the location

of mice for entire videos and compare tracking performance with other non-neural network

approaches including a beam-break system (KOMP2) and a video tracking system (Ctrax).

We evaluated the quality of the encoder-decoder segmentation neural network tracking

architecture by inferring entire videos from mice with disparate coat colors and data collection

environments (Fig. 1A) and visually evaluating the quality of the tracking. We also compared this

neural network-based tracking architecture with an independent modality of tracking, the

KOMP2 beam-break system (Fig. 1A, column 6). We tracked 2,002 videos of individual mice

comprising 700 hours of video from the KOMP2 experiment using the encoder-decoder

segmentation neural network architecture and compared the results with the tracking data

obtained using the KOMP2 beam-break system (Fig. 2F). These data comprised mice of 232

knockout lines on the C57BL/6NJ background that were tested in 20-minute open field assay in

2016 and 2017. Since each KOMP2 arena has slightly different background due to the

transparent and reflective walls, we compared tracking performances of the two approaches for

each of the eight testing arenas used in the 2016 and 2017 KOMP2 open-field assays (Fig. 2F,

colors shows arena), and compared tracking performances for all the arenas combined (Fig. 2F,

black line). We observed a very high correlation between the total distance traveled in the open

field as measured by the two approaches across all eight KOMP2 testing arenas (R = 96.9%,

Fig. 2F). We observed two animals with high discordance from this trend (Fig. 2F, red arrows).

Observation of the video showed odd behaviors for both animals, with a waddle gait in one and

a hunched posture in the other (S2 Video). We postulate that these behaviors led to abnormal

beams breaks causing erroneously high total distances traveled measured via the beam break

system. This example highlights an important advantage of the neural network, as it is

unaffected by the behavior of the animal.

We then compared the performance of our trained segmentation neural network with the

performance of Ctrax across a broad selection of videos from the various testing environments

and coat colors previously tracked using Ctrax and LimeLight (Fig. 1A). We wish to emphasize

that we compared the performance of our network with that of Ctrax because Ctrax is one of the

best conventional tracking software packages that allows fine tuning of the many tracking

settings, is open source, and provides user support. Given the results with the 26 background

subtraction approaches (Fig. 1B), we expected similar or worse performances from other

tracking systems. We tracked 72 videos, broken into 6 groups (Fig. 1A) with 12 animals per

group, with both our trained encoder-decoder segmentation neural network and Ctrax. The

settings for Ctrax were fine-tuned for each of the 72 videos, as described in 'Ctrax Settings

Supervision Protocol' in Methods. Videos from the 24-hr experiment showing that animals that

were sleeping continually for the full video duration (one hour) were manually omitted from

comparison, as Ctrax will incorporate the mouse as part of the background model. We

calculated a cumulative relative error of total distance traveled between Ctrax and our neural

network (Fig. 2G). Specifically, for every minute in the video, we compared the distance-traveled

prediction of the neural network with that of Ctrax. This metric measures the accuracy of center

of mass tracking of each mouse. Tracking for black, gray, and piebald mice in the white-

background open-field apparatus showed errors less than 4%; however, significantly higher

levels of error were seen in albino mice in the open-field arena with a white floor (14%), black

mice in the 24-hour arena (27%), and black mice in the KOMP2 testing arena (10%) (Fig. 2G

and S1 Video). Thus, we could not adequately track albino mice in the open-field arena with a

white floor, black mice in the 24-hour arena, or black mice in the KOMP2 testing arena without

the neural network tracker.

We also observed, using Ctrax, that when foreground segmentation prediction is

incorrect, such as when shadows are included in the prediction, the ellipse fit does not correctly

represent the posture of the mouse (S1 Video). In these cases, even though the center of mass

tracking was acceptable, the ellipse fit itself was highly variable. Modern machine learning

software for behavior recognition, such as the Janelia Automatic Animal Behavior Annotator

(JAABA)[9], utilize the time series of ellipse fit tracking for classification of behaviors. We

quantitated the stability of ellipse tracking through measuring the relative standard deviation of

the minor axis and comparing approaches. This metric shows the least variance across all sizes

of laboratory mice, as the width of an individual mouse remains similar through a wide range of

postures expressed in behavioral assays when tracking is accurate. We observed a high level of

tracking variation with grey and piebald mice in the white open field arena (Fig. 2H) even though

there is low cumulative relative error of total distance traveled (Fig. 2G). As expected, we

observed a high relative standard deviation of the minor axis for albino mice (white open field

arena) and KOMP2 tracking. Thus, for both center of mass tracking and variance of ellipse fit we

find that the neural network tracker outperforms traditional background subtraction-based

trackers.

Having established the encoder-decoder segmentation neural network as a highly

accurate tracker, we tested its performance using two large behavioral experiments. For the first

experiment, we generated white-surfaced open-field video data with 1,845 mice, including 58

strains of mice including mice with diverse coat colors, piebald mice, nude mice, and obese

mice; and covering a total of 1,691 hours (Fig. 3A). This dataset consists of 47 inbred strains

and 11 isogenic F1 strains and is the largest open-field dataset generated, based on the data in

the Mouse Phenome Database[23]. Using a single trained network without any user tuning, we

were able to track all mice with high accuracy. We visually checked mice from a majority of the

strains for fidelity of tracking and observed excellent performance. The activity phenotypes that

we observed agree with previously published datasets of mouse open-field behavior[23]. For the

second dataset, we tracked 24-hour video data collected for four C57BL/6J and two BTBR T^{+}

ltpr3^{tf}/J mice (Fig. 1A, column 5). These mice were housed with beddingand a food cup over

multiple days during which the food changed location and under 12:12 light-dark conditions.

Video data were recoded using visible and infrared light sources. We tracked activity across all

animals under these conditions using the same encoder-decoder segmentation neural network

architecture used for the first experiment, and observed very good performance under light and

dark conditions (Fig. 3B, light and dark blue points, respectively). As expected, we observed

daily activity rhythm with high levels of locomotor activity during the dark phase (Fig. 3B, red

curve).

Fig. 3. Highly scalable tracking with a single neural network. (A) A large strain survey showing
genetically diverse animals traced with our encoder-decoder segmentation network. 1,845 animals
including 58 inbred and F1 isogenic strains, totaling 1,691 hours of video, were processed by a single
trained neural network without any user-involved fine-tuning. Total distance traveled in a 55-minute open
field assay is shown. Points indicate individuals in a strain, bars indicate mean +/- standard deviation. Two
reference mouse strains are shown in bold, C57BL/6J and C57BL/6NJ (B) Daily activity rhythms were
observed in six animals continuously tracked over 4 days in a dynamic environment with our encoder-

decoder segmentation neural network. Points indicate distance traveled in an epoch. Red line indicates polynomial fit showing daily activity rhythms.

Discussion

Video-based tracking of animals in complex environments has been a long-standing challenge in the field of animal behavior [24]. Current state-of-the-art animal-tracking systems do not address the fundamental issue of animal segmentation and rely heavily on visual contrast between the foreground and background for accurate tracking. As a result, the user must restrict the environment to achieve optimal results. Here we describe a modern neural network-based tracker that is able to function in complex and dynamic environments. Our network addresses a fundamental issue in tracking—foreground and background segmentation—by using a trainable neural network. We test three different architectures and find that an encoder-decoder segmentation network architecture achieves the highest level of accuracy and functions at a high speed (over 6X real time). Furthermore, we provide a labeling interface that allows the user to train a new network for their specific environment by labeling as few as 2,500 images, which takes approximately 3 hours. We compare our network to two existing solutions and find that it vastly outperforms them in complex environments. We expect similar results with any off-the-shelf system that utilizes traditional background subtraction approaches. In fact, when we tested 26 different background subtraction methods we discovered that each failed under certain circumstances. However, a single neural network architecture functions for all coat colors of mice under multiple environments without the need for fine tuning or user input. Our machine learning approach enables long-term tracking under dynamic environmental conditions with minimal user input, thus establishing the basis of the next generation of tracking architecture for behavioral research.

Materials and methods

Experimental arenas

Open Field Arena

Our open field arena measures 52cm by 52cm by 23cm. The floor is white PVC plastic and the walls are grey PVC plastic. To aid in cleaning maintenance, a white 2.54cm chamfer was added to all the inner edges. Illumination is provided by an LED ring light (Model: F&V R300). The ring light was calibrated to produce 600 lux of light in each of our 24 arenas.

24-Hour monitoring open field arena

We augmented 6 of our open field arenas for multiple day testing. We set our overhead LED lighting to a standard 12:12 light-dark cycle. ALPHA-dri was placed into the arena for bedding. To provide food and water, a single Diet Gel 76A food cup was placed in the arena. This nutritional source was monitored and replaced when depleted. Each arena was illuminated at 250 lux during the day and <5 lux during the night. For recording videos during the night, additional IR LED (940nm) lighting was added.

KOMP2 open field arena

In addition to our custom arenas, we also benchmarked our approach on a commercially available system. The Accuscan Versamax Activity Monitoring Cages is constructed using clear plastic walls. As such, visual tracking becomes very difficult due to the consequent reflections. The cage measures 42cm by 42cm by 31cm. Lighting for this arena was via LED illumination at 100-200 lux.

Video acquisition

Imaging hardware

All data was acquired using the same imaging equipment. Data was acquired at

640x480px resolution, 8-bit monochrome depth, and 30fps using Sentech cameras (Model:

STC-MB33USB) and Computar lenses (Model: T3Z2910CS-IR). Exposure time and gain were

controlled digitally using a target brightness of 190/255. Aperture was adjusted to its widest so

that lower analog gains were used to achieve the target brightness. This in turn reduced

amplification of baseline noise. Files were saved temporarily on a local hard drive using the "raw

video" codec and "pal8" pixel format. Our typical assays run for two hours, yielding a raw video

file of approximately 50GB. Overnight, we use FFmpeg software (https://www.ffmpeg.org/) to

apply a 480x480px crop, de-noise filter, and compress using the mpeg4 codec (quality set to

max), which yields a compressed video size of approximately 600MB.

One camera and lens was mounted approximately 100cm above each arena to alleviate

perspective distortion. Zoom and focus were set manually to achieve a zoom of 8px/cm. This

resolution both minimizes the unused pixels on our arena border and yields approximately 800

pixels area per mouse. Although the KOMP2 arena is slightly smaller, the same zoom of 8px/cm

target was utilized.

Ctrax settings supervision protocol

Ctrax contains a variety of settings to enable optimization of tracking [7]. The authors of

this software strongly recommend, first and formost, ensuring that he arena is set up under

specific criteria to ensure good tracking. In most of our tests, we intentionally use an

environment in which Ctrax is not designed to perform well (e.g., albino mice on a white

background). That being said, with well-tuned parameters, a good performance is still

achievable. However, with a large number of settings to manipulate, Ctrax can easily require

substantial time to achieve a good tracking performance. Here, we describe our protocol for

setting up Ctrax for tracking mice in our environments.

First, we create a background model. The core of Ctrax is based on background

subtraction, and thus a robust background model is essential for functionality. Models function

optimally when the mouse is moving. To create the background model, we seek to a segment of

the video in which the mouse is clearly moving, and we sample frames from that section. This

ensures that the mouse is not included in the background model. This approach significantly

improves Ctrax's tracking performance on our 24-hour data, as the mouse moves infrequently

due to sleeping and would typically be incorporated into the background model.

The second step is to set the settings for background subtraction. Here, we use the

Background Brightness normalization method with a Std Range of 254.9 to 255.0. The

thresholds applied to segment out the mouse are tuned on a per-video basis, as slight changes

in exposure and coat color will influence the performance. To fine-tune these thresholds, we

apply starting values based on previous videos analyzed and adjust values by checking multiple

portions of the video. Every video is inspected for proper segmentation on difficult frames, such

as the mouse rearing on the wall. Additionally, we apply morphological filtering to both remove

minor noise in the environment as well as remove the tails of mice for fitting an ellipse. We use

an opening radius of 4 and a closing radius of 5.

Lastly, we manually set a variety of tracking parameters that Ctrax enables to ensure that

the observations are in fact mice. For optimal time efficiency, these parameters were tuned well

once and then used for all other mice tracked. If a video was performing noticeably poorly, the

general settings were tweaked to improve performance. For the shape parameters, we

computed bounds based on two standard deviations from an individual black mouse video. We

lowered the minimum values further because we expected that certain mice would perform

poorly on the segmentation step. This allows Ctrax to still find a good location of the mouse

despite not being able to segment the entire mouse. This approach functions well, as all of our

setups have the same zoom of 8, and the mice tested are generally the same shape. Motion

settings are very lenient, because our experimental setup tracks only one mouse in the arena at

a time. Under the observation parameters, we primarily utilize the "Min Area Ignore" setting to

filter out detections larger than 2,500 pixels. Under the hindsight tab, we use the "Fix Spurious

Detections" setting to remove detections with a length shorter than 500 frames.

Training sets

Labeling software

We annotated our own training data using custom software that was written to

accommodate obtaining the necessary labels. We used the OpenCV library (https://opencv.org/)

to create an interactive watershed-based segmentation and contour-based ellipse-fit. Using the

software GUI we developed, the user left-clicks to mark points as the foreground (a mouse) and

right-clicks to label other points as the background (S1 Fig.). Upon a keystroke, the watershed

algorithm is executed to predict a segmentation and ellipse. If users need to make edits to the

predicted segmentation and ellipse, they can simply mark additional areas and run the

watershed again. When the predictions are of sufficiently high quality, users then select the

direction of the ellipse. They do this by selecting one of four cardinal directions: up, down, left,

right. Since the exact angle is selected by the ellipse-fitting algorithm, users need only to identify

the direction ±90 degrees. Once a direction is selected, all the relevant data is saved to disk and

users are presented with a new frame to label. Full details on the software controls can be found

in the software documentation.

The objective of our annotated dataset is to identify good ellipse-fit tracking data for

mice. While labeling data, we optimized the ellipse-fit such that the ellipse was centered on the

mouse's torso with the major axis edge approximately touching the nose of the mouse.

Frequently, the tail was removed from the segmentation mask to provide a better ellipse-fit. For

training networks for inference, we created three annotated training sets. Each training dataset

includes a reference frame (input), segmentation mask, and ellipse-fit. Each training set was

generated to track mice in a different environmental setup.

Neural network models

The neural networks we trained fall into three categories: segmentation, regression, and

binning. Our tested models can be viewed visually in Fig. 1D-F.

The first network architecture is modeled after a typical encoder-decoder structure for

segmentation (Fig. 1D). The first half of the network (encoder) utilizes 2D convolutional layers

followed by batch normalization, a ReLu activation, and 2D max pooling layers. We use a

starting filter size of 8 that doubles after every pooling layer. The kernels used are of shape 5x5

for 2D convolution layers and 2x2 for max pooling layers. Our input is of shape 480x480x1 and

after six of these repeated layers, the resulting shape is 15x15x128. We apply another 2D

convolutional layer (kernel 5x5, 2x filters) followed by a 2D max pool with a different kernel of

3x3 and stride of 3. One final 2D convolutional layer is applied to yield our feature bottleneck

with a shape of 5x5x512. This feature bottleneck is then passed to both the segmentation

decoder and angle predictor. The segmentation decoder reverses the encoder using strided

transpose 2D convolutional layers and carries over pre-downsampled activations through

summation junctions. It should be noted that this decoder does not utilize ReLu activations. After

the layers return to the 480x480x8 shape, we apply one additional convolution, with a kernel

size of 1x1, to merge the depth into two images: background prediction and foreground

prediction. We apply a softmax function across this depth. From the feature bottleneck, we also

create a prediction for angle prediction. We achieve this by applying two 2D convolution layers

with batch normalization and ReLu activations (kernel size 5x5, feature depths 128 and 64).

From here, we flatten and use one fully connected layer to yield a shape of four neurons, which

function to predict the quadrant in which the mouse's head is facing. Since the angle is predicted

by the mask, we need only to select the correct direction (± 180 deg). The four possible

directions that the network can select are 45-135, 135-225, 225-315 and 315-45 degrees on a

polar coordinate grid. These boundaries were selected to avoid discontinuities in angle

prediction.

The second network architecture is a binned regression approach (Fig. 1E). Instead of

predicting the parameters directly, the network instead selects the most probable value from a

selection of binned possible values. The major difference between this structure and a

regression structure is that the binned regression network training relies on a cross entropy loss

function whereas a regression network relies on a mean squared error loss function. Due to

memory limitations, we tested only custom VGG-like networks with reduced feature dimensions.

Our best-performing network is structured with two 2D convolutional layers followed by a 2D

max pooling layer. The kernels used are of shape 3x3 for 2D convolutional layers and 2x2 for 2D

max pooling layers. We start with a filter depth of 16 and double after every 2D max pool layer.

This two convolutional plus max pool sequence is repeated five times to yield a shape of

15x15x256. This layer is flattened and connected to a fully connected layer for each output

ellipse-fit parameter. The shape of each output is dictated by the desired resolution and range of

the prediction. For testing purposes, we observed only the center location and trained with a

range of the entire image (0-480). Additional outputs, such as angle prediction, could simply be

added as additional output vectors.

The third network architecture is modeled after a typical regression predictor structure

(Fig. 1F). While the majority of regression predictors realize the solution through a bounding box,

an ellipse simply adds one additional parameter: the angle of the mouse's head direction. Since

the angle is a repeating series with equivalence at 360deg and 0deg, we transform the angle

parameter into its sine and cosine components. This yields a total of six parameters regressed

from the network. The first half of this network encodes a set of features relevant to correctly

predicting the six parameters. From the encoded feature set, we flatten the network and applied

a fully convolutional layer to regress the parameters for the ellipse-fit. We tested a wide variety

of pre-built feature detectors including Resnet V2 50, Resnet V2 101, Resnet V2 200, Inception

V3, Inception V4, VGG, and Alexnet. In addition to these pre-built feature detectors, we also

surveyed a wide array of custom networks. Of these general purpose feature encoders and

custom networks, Resnet V2 200 performed the best.

Neural network training

This section describes all of the procedures pertaining to training our neural network

models. The three procedures described here are training set augmentation, training

hyperparameters, and a benchmark for training set size.

Training set augmentation has been an important aspect of training neural networks

since Alexnet [25]. We utilize a handful of training set augmentation approaches to achieve good

regularization performance. Since our data is from a birds-eye view, it is straightforward to apply

horizontal, vertical, and diagonal reflections for an immediate 8x increase in our equivalent

training set size. Additionally, at runtime, we apply small rotations and translations for the entire

frame. Rotation augmentation values are sampled from a uniform distribution. Finally, we apply

noise, brightness, and contrast augmentations to the frame. The random values used for these

augmentations are selected from a normal distribution.

Hyperparameters, such as training learn rate and batch size, were selected

independently for each network architecture trained. While larger networks, such as Resnet V2

200, can run into memory limitations for batch sizes at an input size of 480x480, good learn rate

and batch size were experimentally identified using a grid search approach [26]. Table A in S1

Information summarizes all the hyperparameters selected for training these network

architectures.

We also benchmarked the influence of training set size on network generalization in

order to determine the approximate amount of annotated training data required for good network

performance of the encoder-decoder segmentation network architecture (S2 Fig.). We tested

this benchmark by shuffling and randomly sampling a subset of the training set. Each

subsampled training set was trained and compared to an identical validation set. While the

training curves appear indistinguishable, the validation curves tained with fewer than 2,500

training annotations diverge from the group. This suggests that the training set is no longer large

enough to allow the network to generalize well. While the exact number of training samples will

ultimately rely on the difficulty of the visual problem, a recommended starting point would be

around 2,500 training annotations.

Animals used

All animals were obtained from The Jackson Laboratory production colonies. Adult mice

aged 8 to 14 weeks were behaviorally tested in accordance with approved protocols from The

Jackson Laboratory Institutional Animal Care and Use Committee guidelines. Open field

behavioral assays were carried out as previously described [27]. Briefly, group-housed mice

were weighed and allowed to acclimate in the testing room for 30-45 minutes before the start of

video recording. Data from the first 55 minutes of activity are presented here. Where available, 8

males and 8 females were tested from each inbred strain and F1 isogenic strain.

Code and training set availability

604   Neural network training and inference code as well as annotated datasets will become

605   available upon publication.

Acknowledgments

We thank the members of the Kumar laboratory for suggestions and editing of the

manuscript. We thank JAX Information Technology team members Edwardo Zaborowski, Shane

Sanders, Rich Brey, David McKenzie, and Jason Macklin for infrastructure support; and we

thank KOMP2 behavioral testers James Clark, Pamelia Fraungruber, Rose Presby, Zachery

Seavey, and Catherine Witmeyer. This work used the National Science Foundation (NSF)

Extreme Science and Engineering Discovery Environment (XSEDE) XStream service at

Stanford University through allocation TG-DBS170004. Funding also included the NIH grant

DA041668 from NIDA, a Brain and Behavioral Foundation Young Investigator Award, and a JAX

Director's Innovation Fund to V. K. We thank Nvidia GPU grant program for providing a TitanXP

for our work.

References

1.   Egnor SE, Branson K. Computational Analysis of Behavior. Annu Rev Neurosci. 2016;39:217-36.
doi: 10.1146/annurev-neuro-070815-013845. PubMed PMID: 27090952.

2.   Gomez-Marin A, Paton JJ, Kampff AR, Costa RM, Mainen ZF. Big behavioral data: psychology,
ethology and the foundations of neuroscience. Nat Neurosci. 2014;17(11):1455-62. doi: 10.1038/nn.3812.
PubMed PMID: 25349912.

3.   Valdez P, Mehrabian A. Effects of color on emotions. Journal of experimental psychology:
General. 1994;123(4):394.

4.   Kulesskaya N, Voikar V. Assessment of mouse anxiety-like behavior in the light-dark box and
open-field arena: role of equipment and procedure. Physiol Behav. 2014;133:30-8. doi:
10.1016/j.physbeh.2014.05.006. PubMed PMID: 24832050.

5.   Dell AI, Bender JA, Branson K, Couzin ID, de Polavieja GG, Noldus LP, et al. Automated image-
based tracking and its application in ecology. Trends in ecology & evolution. 2014;29(7):417-28.

6.   Anderson DJ, Perona P. Toward a science of computational ethology. Neuron. 2014;84(1):18-31.

7.   Branson K, Robie AA, Bender J, Perona P, Dickinson MH. High-throughput ethomics in large
groups of Drosophila. Nature methods. 2009;6(6):451.

8.   Austin CP, Battey JF, Bradley A, Bucan M, Capecchi M, Collins FS, et al. The knockout mouse
project. Nat Genet. 2004;36(9):921-4. doi: 10.1038/ng0904-921. PubMed PMID: 15340423; PubMed
Central PMCID: PMCPMC2716027.

9.   Kabra M, Robie AA, Rivera-Alba M, Branson S, Branson K. JAABA: interactive machine learning
for automatic annotation of animal behavior. Nat Methods. 2013;10(1):64-7. doi: 10.1038/nmeth.2281.
PubMed PMID: 23202433.

10.   Sobral A, editor BGSLibrary: An opencv c++ background subtraction library. IX Workshop de
Visao Computacional; 2013.

11.   Dankert H, Wang L, Hoopfer ED, Anderson DJ, Perona P. Automated monitoring and analysis of
social behavior in Drosophila. Nature methods. 2009;6(4):297.

12.   Noldus LP, Spink AJ, Tegelenbosch RA. EthoVision: a versatile video tracking system for
automation of behavioral experiments. Behavior Research Methods, Instruments, & Computers.
2001;33(3):398-414.

13.   Pérez-Escudero A, Vicente-Page J, Hinz RC, Arganda S, De Polavieja GG. idTracker: tracking
individuals in a group by automatic identification of unmarked animals. Nature methods. 2014;11(7):743.

14.   De Chaumont F, Coura RD-S, Serreau P, Cressant A, Chabout J, Granon S, et al. Computerized
video analysis of social interactions in mice. Nature methods. 2012;9(4):410.

15.   Ohayon S, Avni O, Taylor AL, Perona P, Egnor SR. Automated multi-day tracking of marked mice
for the analysis of social behaviour. Journal of neuroscience methods. 2013;219(1):10-9.

16.   Patel TP, Gullotti DM, Hernandez P, O'Brien WT, Capehart BP, Morrison III B, et al. An open-
source toolbox for automated phenotyping of mice in behavioral tasks. Frontiers in behavioral
neuroscience. 2014;8:349.

17.   Hewitt BM, Yap MH, Hodson-Tole EF, Kennerley AJ, Sharp PS, Grant RA. A novel automated
rodent tracker (ART), demonstrated in a mouse model of amyotrophic lateral sclerosis. Journal of
neuroscience methods. 2017.

18.   LeCun Y, Bengio Y, Hinton G. Deep learning. Nature. 2015;521(7553):436-44. doi:
10.1038/nature14539. PubMed PMID: 26017442.

19.   Yosinski J, Clune J, Bengio Y, Lipson H, editors. How transferable are features in deep neural
networks? Advances in neural information processing systems; 2014.

20.   He K, Zhang X, Ren S, Sun J, editors. Identity mappings in deep residual networks. European
Conference on Computer Vision; 2016: Springer.

21.   Abadi M, Barham P, Chen J, Chen Z, Davis A, Dean J, et al., editors. TensorFlow: A System for
Large-Scale Machine Learning. OSDI; 2016.

22.   Zoph B, Vasudevan V, Shlens J, Le QV. Learning transferable architectures for scalable image
recognition. arXiv preprint arXiv:170707012. 2017.

23.   Bogue MA, Grubb SC, Walton DO, Philip VM, Kolishovski G, Stearns T, et al. Mouse Phenome
Database: an integrative database and analysis suite for curated empirical phenotype data from laboratory
mice. Nucleic Acids Res. 2018;46(D1):D843-D50. doi: 10.1093/nar/gkx1082. PubMed PMID: 29136208;
PubMed Central PMCID: PMCPMC5753241.

24.   Egnor SR, Branson K. Computational analysis of behavior. Annual review of neuroscience.
2016;39:217-36.

25.   Krizhevsky A, Sutskever I, Hinton GE, editors. Imagenet classification with deep convolutional
neural networks. Advances in neural information processing systems; 2012.

26.   Larochelle H, Erhan D, Courville A, Bergstra J, Bengio Y, editors. An empirical evaluation of deep
architectures on problems with many factors of variation. Proceedings of the 24th international conference
on Machine learning; 2007: ACM.

27.   Kumar V, Kim K, Joseph C, Thomas LC, Hong H, Takahashi JS. Second-generation high-
throughput forward genetic screen in mice to isolate subtle behavioral mutants. Proceedings of the
National Academy of Sciences. 2011;108(Supplement 3):15557-64.

Supporting information

S1 Information. (Note A) Description of the ellipse-fit function. (Note B) Annotated

dataset descriptions. (Table A) Training hyperparameters.

S1 Fig. Example of our labeling GUI software. (A) Our software allows the user to

zoom into the the region of interest for annotation (mouse) and placed two marks: one

for foreground (green) and one for background (red). (B) Upon a keystroke, the software

provides the resulting segmentation (magenta), ellipse-fit (cyan), and the old

background annotations (yellow).

S2 Fig. Training set size scaling benchmark. We benchmarked how the training-set

size influences the performance of a trained encorder-decoder segmentation network.

Full training set includes 16,234 annotated frames. (A) Training-set size does not impact

training set error rate. (B) Validation performance converges to the same value above

2,500 training samples, but the error rate increases when 1,000 or fewer training

samples are used. (C-F) Validation accuracy outperforms training accuracy when 2,500

or more training samples are used. (G) Validation accuracy begins to show signs of

weak generalization by only matching, and not exceeding, training accuracy at 1,000

training samples. (H) A network trained using only 500 training samples is clearly

overtraining, shown by the diverging and increasing validation error rate.

S1 Video. Comparison of mouse tracking. A comparison of mouse tracking across a

variety of coat colors and environments using both our proposed encoder-decoder

segmentation neural network (red) and Ctrax (blue). (0-22s) Black mice and (22-45s)

grey mice in a white environment have strong agreement across approaches. When

rearing on the wall, Ctrax starts to not properly fit the ellipse. (45-66s) Piebald mice in a

white environment have strong tracking concordance, but depending upon the unique

coat pattern may have incorrect shape predicted by Ctrax. (66-90s) Albino mice on a

white background are a difficult problem for background subtraction approaches (Ctrax),

while a neural network approach tracks appropriately. (90-112s) Black mice in the 24-hr

setup, which contains bedding and a food cup, are difficult for background subtraction

approaches (Ctrax) to create adequate background models for tracking. A neural

network approach learns to handle this difficulty. (112-134s) Black mice in the KOMP2

arena, which has reflective floors and walls, poses a difficult situation for background

subtraction approaches (Ctrax). A neural network approach learns to not include

reflections without any tuning of parameters. Playback for all clips in this video are at

half-speed to better observe and compare tracking performance.

S2 Video. KOMP2 observed odd behavior. A 1-minute sample from the two off-

718   diagonal KOMP2 videos. In the first clip (0-62s), we observe a high degree of waddle in

719   the animal's gait as well as odd stride frequency. In the second clip (62-125s), we

720   observe a hunched posture during locomotion as well as a frequent sideways motion.

721   Red ellipse denotes our neural network tracker prediction.

A

	Black	Grey	Albino	Piebald	24-hour	KOMP
Full Frame						
Cropped						
Ideal Tracking						
Actual Tracking						

B

C

x-coord, y-coord, major axis, minor axis, angle

D

Input Frame → Encoder → Decoder → Segmentation Mask → Fit Ellipse

Angle → Max

E

Input Frame

X — Max — 480

Major — Max

Angle — 0° — Max — 360°

F

Input Frame → 6 Ellipse Fit Parameters

● 2D Conv + BN + Relu ● Strided 2D Transpose Conv ● 2D Conv ● Fully Connected
● 2D Max Pool ○ Sum ● Resnet V2 200