Faces and voices in the brain: a modality-general person-identity representation in

superior temporal sulcus

Abbreviated title: Modality-general identity representation in STS

Maria Tsantani[1], Nikolaus Kriegeskorte[2], Carolyn McGettigan[3], Lúcia Garrido[1]

[1] Division of Psychology, Department of Life Sciences, Brunel University London

[2] Zuckerman Mind Brain Behavior Institute, Columbia University

[3] Department of Psychology, Royal Holloway, University of London

Corresponding authors:

Maria Tsantani, Division of Psychology, Department of Life Sciences, Brunel University

London, Uxbridge UB8 3PH, United Kingdom, Telephone: (+44) 01895268155, E-mail:

maria.tsantani@gmail.com

Lúcia Garrido, Division of Psychology, Department of Life Sciences, Brunel University

London, Uxbridge UB8 3PH, United Kingdom, Telephone: (+44) 01895265555, E-mail:

garridolucia@gmail.com

Number of pages: 46

Number of figures: 5; Number of tables: 3

Number of words: Abstract: 244; Introduction: 650; Discussion: 1467

Acknowledgements: This work was supported by a research grant by the Leverhulme Trust

(RPG-2014-392). We thank Matthew Longo for comments on a previous version of the

manuscript, and Tiana Rakotonombana, Roxanne Zamyadi, and Rasanat Nawaz for help with

preparing and piloting the stimuli. The authors declare no competing financial interests.

Abstract

Face-selective and voice-selective brain regions have been shown to represent face-identity and voice-identity, respectively. Here we investigated whether there are modality-general person-identity representations in the brain that can be driven by either a face or a voice, and that invariantly represent naturalistically varying face and voice tokens of the same identity. According to two distinct models, such representations could exist either in multimodal brain regions (Campanella and Belin, 2007) or in face-selective brain regions via direct coupling between face- and voice-selective regions (von Kriegstein et al., 2005). To test the predictions of these two models, we used fMRI to measure brain activity patterns elicited by the faces and voices of familiar people in multimodal, face-selective and voice-selective brain regions. We used representational similarity analysis (RSA) to compare the representational geometries of face- and voice-elicited person-identities, and to investigate the degree to which pattern discriminants for pairs of identities generalise from one modality to the other. We found no matching geometries for faces and voices in any brain regions. However, we showed crossmodal generalisation of the pattern discriminants in the multimodal right posterior superior temporal sulcus (rpSTS), suggesting a modality-general person-identity representation in this region. Importantly, the rpSTS showed invariant representations of face- and voice-identities, in that discriminants were trained and tested on independent face videos (different viewpoint, lighting, background) and voice recordings (different vocalizations). Our findings support the Multimodal Processing Model, which proposes that face and voice information is integrated in multimodal brain regions.

Significance statement

It is possible to identify a familiar person either by looking at their face or by listening to their voice. Using fMRI and representational similarity analysis (RSA) we show that the right posterior superior sulcus (rpSTS), a multimodal brain region that responds to both faces and voices, contains representations that can distinguish between familiar people independently of whether we are looking at their face or listening to their voice. Crucially, these representations generalised across different particular face videos and voice recordings. Our findings suggest that identity information from visual and auditory processing systems is combined and integrated in the multimodal rpSTS region.

Introduction

Looking at a familiar person's face or listening to their voice automatically grants us access to a wealth of information regarding the person's identity, such as their name, our relationship to them, and memories of previous encounters. Knowledge about how the brain processes faces and voices separately has advanced significantly over the past twenty years: functional magnetic resonance imaging (fMRI) revealed cortical regions that are face-selective (Kanwisher et al., 1997) and regions that are voice-selective (Belin et al., 2000). Recent advances using multivariate classification methods have further shown that some of these regions are important for identification. In particular, face-selective regions in the posterior occipitotemporal lobe, anterior temporal lobe, and posterior superior temporal sulcus (pSTS) can discriminate different facial identities (Kriegeskorte et al., 2007; Nestor et al., 2011; Goesaert and Op de Beeck, 2013; Verosky et al., 2013; Axelrod and Yovel, 2015; Collins et al., 2016; Visconti Di Oleggio Castello et al., 2017). Crucially, a number of studies also found representations in these regions that generalised across different images of the same person (Anzelotti et al., 2014; Anzelotti and Caramazza, 2016; Guntupalli et al., 2017), i.e., were able to "tell people together" (Jenkins et al., 2011; Burton, 2013). Similarly for voices, Formisano et al. (2008) found voice-identity representations in the right STS and Heschl's gyrus that could both discriminate between speakers and generalise across different vowel sounds spoken by the same voice.

Despite these advances, we still have a limited understanding of how the brain combines and integrates face and voice information. Two major models have been put forward. The *Multimodal Processing Model* proposes that there are multimodal systems that process information about people and receive input from both face- and voice-responsive regions (Ellis et al., 1997; Campanella and Belin, 2007). Patient (Ellis et al., 1989; Gainotti, 2011) and fMRI

studies (Shah et al., 2001; Joassin et al., 2011; Watson et al., 2014a) suggest the anterior

temporal lobe, the posterior cingulate cortex, the STS, and the hippocampus as candidate

multimodal regions. In contrast, the *Coupling of Face and Voice Processing Model* proposes

that the direct coupling between face- and voice-responsive brain regions is crucial for the

integration of person-identity information (von Kriegstein et al., 2005). In particular, fMRI

studies have shown that voice recognition of familiar (or recently learned) people is associated

with increased activation in face-responsive regions of the fusiform gyrus (von Kriegstein et

al., 2005, 2006, 2008; von Kriegstein and Giraud, 2006).

In this study, we tested the predictions from these two models by investigating whether there

are modality-general person-identity representations in multimodal regions (Multimodal

Model) and/or in face- and voice-selective regions (Coupling Model). We used representational

similarity analysis — RSA (Kriegeskorte et al., 2008a, 2008b) to compare the representational

geometries of face- and voice-elicited person-identities, and to investigate the degree to which

pattern discriminants for pairs of identities generalise from one modality to the other. We

predict that, if a region shows a modality-general person-identity representation, the

representational geometry of face and voice identities will match, and/or pattern discriminants

will generalise across faces and voices. Two recent studies found some support for the

Multimodal Model by showing that multimodal regions in the STS and inferior frontal gyrus

(Hasan et al., 2016; Anzelotti and Caramazza, 2017) could discriminate between the activation

patterns of two face-identities based on voice information (and vice-versa). However, these

studies did not show that the regions that could decode identities across modalities could also

decode identities within each modality, which is a crucial feature of modality-general person-

identity representations. Furthermore, these studies used very few identities and tokens per

identity. In our study, we included multiple, naturalistically varying face videos and voice

recordings of 12 different identities. Thus, we were able to sample the variability of visual and

auditory appearance that we are exposed to in everyday life, and to better capture processes of

person identification, which are distinct from image or sound recognition (Burton, 2013).

Materials and Methods

Overview of study

In this study, we measured fMRI activation patterns in response to the faces and voices of 12

famous individuals. It was important to use highly familiar individuals because we needed to

guarantee that participants were well acquainted with the faces and voices of those individuals.

We thus only recruited participants for the full study if they demonstrated that they were

familiar with the majority of the famous individuals in an online Recognition Task. The full

study consisted of two MRI scanning sessions and one behavioural session, with each session

taking approximately 90 minutes. All three sessions took place on separate days. Before

entering the scanner at the start of the first MRI session, participants repeated the Recognition

Task in the presence of the experimenter and also completed a Familiarity Task in which they

rated all face and voice stimuli on perceived familiarity.

In each MRI session participants completed three functional runs (main experimental runs) in

which they viewed the faces and listened to the voices of the famous people in an event-related

design. In addition, participants underwent two structural scans (one in each session) and

functional localisers for face-selective, voice-selective, and multimodal regions of interest

(ROIs). Across both sessions participants completed at least one run (in most cases two) of (1)

the temporal voice area (TVA) localiser (Belin et al., 2000), (2) a face localiser, (3) a

multimodal (face-voice) localiser, and (4) a voice localiser. Finally, participants completed a

behavioural testing session. In this behavioural session they rated the famous faces and voices

on various social and perceptual dimensions; however, these results are not included here.

To investigate the existence of modality-general person-identity representations in each of our

ROIs we used RSA (Kriegeskorte et al., 2008a, 2008b; Kriegeskorte and Kievit, 2013) to

compare the representational geometry of face-identities with the representational geometry of

voice-identities (Analysis A), and to investigate the degree to which pattern discriminants for

each pair of identities generalise from one modality to the other (Analysis B). Analysis A

focused on the representational geometry of all of identities, i.e. the entire structure of pairwise

distances between the activity patterns elicited by these identities in each modality, and

compared geometries across modalities. Analysis B focused on the discriminability of pairs of

identities, and used a linear discriminant computed in one modality to test discriminability of

the same pair of identities in the other modality (in a similar way to traditional pattern

classification methods). These two analyses complement each other and allowed us to test

different predictions regarding the nature of modality-general person-identity representations.

For Analysis A (RSA comparing representational geometries), we predicted that brain regions

with modality-general person-identity representations would show matching representational

geometries for face-identities and voice-identities. This analysis is constrained by two

assumptions. The first assumption is that there is sufficient variability in the representational

distances between different identities within-modality, i.e. different degrees of similarity

between identities. If all identities are equally distinct from each other, we do not expect to find

correlations between geometries across the two modalities. The second assumption is that

modality-general information dominates over any modality-specific information that may be

present in the same voxels. Specifically, it is possible that the voxels comprising the pattern

estimates contain both unimodal and multimodal neurons (Quiroga et al., 2009). In this case,

the influence of modality-specific information on the representational distances between all

identities could override the influence of modality-general information on the representational

geometry, and could result in non-matching representational geometries across modalities.

We thus also conducted Analysis B (RSA investigating identity discriminability), and we

predicted that brain regions with modality-general person-identity representations would be

able to discriminate between pairs of identities in one modality based on their representational

distance in the other modality. This analysis focuses on one pair of identities at a time, and thus

is not affected by the degree of variability in the representational distances between all

identities. In addition, this analysis is focused on pattern discriminants that generalise across

modalities, and therefore we believe that it is more sensitive to detect modality-general person-

identity representations even in the presence of modality-specific information.

Participants

Participants were recruited at Royal Holloway, University of London and Brunel University

London to take part in a behavioural and fMRI experiment. All participants were required to be

native English speakers aged between 18 and 30, and to have been resident in the UK for a

minimum of 10 years. These requirements were set to increase the likelihood of participants

being familiar with the famous people whose faces and voices were presented in the

experiment. In addition, participants completed an online Recognition Task (see below) as part

of the screening procedure for the study and were only invited if they were able to recognise at

least 75% of our set of famous people from both their face and their voice.

Thirty-one healthy adult participants were recruited who matched all the above criteria. One

participant was excluded from the study after the first MRI session due to excessive head

movement in the scanner (more than 3 mm in any direction within one run). The final sample

consisted of 30 participants (eight males) with mean age of 21.2 years (SD=2.37, range=19-

27). All reported normal or corrected-to-normal vision and normal hearing, provided written

informed consent and were reimbursed for their participation. The study was approved by the

Ethics Committee of Brunel University London.

Recognition Task

Participants completed a face and voice Recognition Task to determine whether they could

recognise at least 75% of the famous people (i.e. at least 9 out of 12) from both the face and the

voice. Face stimuli consisted of single photographs of each of the 12 famous people that were

obtained from the Internet through Google Image searches. Photographs included the top part

of the body and were front-facing. Voice stimuli consisted of single sound-clips for each of the

12 famous people and were obtained from YouTube videos. Sound-clips were approximately

8-seconds long and were root-mean-square (RMS) normalized using Praat (version 5.3.80;

Boersma and Weenink, 2014; www.praat.org). None of these face or voice stimuli were

presented in the main experiment.

Stimuli were presented using Qualtrics (Qualtrics, Provo, UT). For each stimulus participants

had to identify the person shown in the picture or the person speaking (by providing their name

or other uniquely identifying biographical information). In the online task participants typed

their responses below each stimulus, and in the lab task responses were made verbally.

Stimuli for Familiarity Task and Main Experimental Runs

Six silent, non-speaking video clips of moving faces, and six sound clips of voices for each of

the 12 famous people (six female, six male) were obtained from videos on YouTube (in total,

72 stimuli per modality). These people had been identified in our pilot studies as having highly

recognisable faces and voices within samples of native English speakers between the ages of

18-30 who have been resident in the UK for a minimum of 10 years. This list of famous people

included actors, pop stars, politicians, comedians, and TV personalities: Alan Carr, Beyonce

Knowles, Daniel Radcliffe, Emma Watson, Arnold Schwarzenegger, Barack Obama, Sharon

Osbourne, Kylie Minogue, Graham Norton, Cheryl Cole, Barbara Windsor, and Jonathan Ross.

The face stimuli were selected so that the background did not provide any cues to the identity

of the person. Other than the absence of speech, there were no constraints on the type of face

movement. Examples of face movements included nodding, smiling, and rotating the head.

However, all stimuli were selected to be primarily front-facing. Face stimuli were edited using

Final Cut Pro X (Apple, Inc.) so that they were three seconds long and centred on the bridge of

the nose. Six video-clips of the face of the same person were obtained from different original

videos set in a different background.

Voice stimuli were edited using Audacity® 2.0.5 recording and editing software

(RRID:SCR_007198) so that they contained three seconds of speech after removing long

periods of silence. Voice stimuli were converted to mono with a sampling rate of 44100, low-

pass filtered at 10KHz, and RMS normalised using Praat. Six sound clips of the voice of the

same person were obtained from different original videos. All of the voice stimuli had a

different verbal content and were non-overlapping. The stimuli were selected so that the

speakers' identity could not be determined based on the verbal content, conforming to the

standards set by Van Lancker et al. (1985) and Schweinberger et al. (1997).

Familiarity Task

Before entering the scanner, participants rated all stimuli that would be presented in the main

experimental runs on perceived familiarity. Participants were presented with the face stimuli

first, followed by the voice stimuli, in separate blocks. Stimuli were presented using the

Psychophysics Toolbox (version 3; RRID:SCR_002881; Brainard, 1997; Pelli, 1997) running

in Matlab (version R2013b; MathWorks; RRID:SCR_001622). Face stimuli were presented in

the centre of the screen. Participants listened to the voice stimuli through headphones

(Sennheiser HD 202). Participants rated each stimulus on scale from 1 (very unfamiliar) to 7

(very familiar). Each block took approximately 5 minutes to complete.

MRI data acquisition

Participants were scanned using a 3.0 Tesla Tim Trio MRI scanner (Siemens, Erlangen) with a

32-channel head coil at the Combined Universities Brain Imaging Centre (CUBIC) at Royal

Holloway, University of London. In each of the two scanning sessions, a whole-brain T1-

weighted anatomical scan was acquired using magnetization-prepared rapid acquisition

gradient echo (MPRAGE) [1.0 x 1.0 in-plane resolution; slice thickness, 1.0mm; 176 axial

interleaved slices; PAT, Factor 2; PAT mode, GRAPPA (GeneRalized Autocalibrating

Partially Parallel Acquisitions); repetition time (TR), 1900ms; echo time (TE), 3.03ms; flip

angle, 11°; matrix, 256x256; field of view (FOV), 256mm].

For all functional runs T2*-weighted whole-brain functional scans were acquired using echo-

planar imaging (EPI) [3.0 x 3.0 in-plane resolution; slice thickness, 3.0mm; PAT, Factor 2;

PAT mode, GRAPPA (GeneRalized Autocalibrating Partially Parallel Acquisitions); 34

sequential (descending) slices; repetition time (TR), 2000ms; echo time (TE), 30ms; flip angle,

78°; matrix, 64x64; field of view (FOV), 192mm]. For the majority of participants, slices

covered all parts of the brain except for the most dorsal part of parietal cortex. In each

experimental run we obtained 293 brain volumes, in the TVA localiser we obtained 251 brain

volumes, and in each run of the face, voice, and multimodal localiser runs we obtained 227

brain volumes.

fMRI data pre-processing

Data were pre-processed using Statistical Parametric Mapping (SPM12; Wellcome Department

of Imaging Science, London, UK; RRID:SCR_007037; http://www.fil.ion.ucl.ac.uk/spm)

operating in Matlab. Pre-processing was performed separately for each scanning session. All

runs within each session (main experiment or localizer runs) were pre-processed together. The

first three EPI images in each run (dummy scans) were discarded to allow for T1-equilibration

effects. Images were slice-time corrected based on the middle slice in each volume and then

realigned to correct for head movement based on the first image. The structural image in native

space was then coregistered with the realigned mean functional image and segmented into grey

matter, white matter, and cerebrospinal fluid. No smoothing was performed on the images from

the experimental runs. Functional images from the localiser runs were smoothed with a 4-mm

Gaussian kernel (full width at half maximum).

After separate pre-processing of the images in each session, images from the second scanning

session were realigned to the structural image from the first session. Specifically, the structural

image from session two was coregistered to the structural image from session one, and the

transformation was then applied to all functional images from session two. As a result, all

functional images were in the same space.

Functional localiser runs

TVA localiser. We used the TVA localiser developed by Belin et al. (2000) which contains

vocal and non-vocal auditory stimuli. Stimuli were presented in 40 blocks of 8 seconds each.

Vocal stimuli were presented in 20 blocks and included speech and non-speech vocalisations

obtained from 47 speakers (Pernet et al., 2015). Non-vocal stimuli were presented in 20 blocks

and consisted of industrial sounds, environmental sounds, and animal vocalisations. Within

each block stimuli were presented in a random order that was fixed across participants.

Participants were instructed to close their eyes and focus on the sounds. The TVA localiser was

presented directly after the main experimental runs. The duration of a single run was

approximately 10 minutes.

Face, Voice, and Multimodal localisers. We created new face, multimodal, and voice

localiser runs that shared the same experimental design and presented stimuli from comparable

categories (people and objects/scenes). Importantly, we used videos and not static images of

faces. Dynamic face stimuli have been shown to be more effective that static face stimuli for

localising face-selective regions (Fox et al., 2009; Pitcher et al., 2011). Stimuli used for the

face localiser were silent, non-speaking video clips of famous and non-famous (French

celebrities unknown to our participants) moving faces, and silent video clips of moving large

objects and natural or manmade visual scenes (such as videos of airplanes, trains, traffic,

rainforests, waves on a beach) obtained from videos on YouTube. For the multimodal localiser

the stimuli were audio-visual and included videos clips of the faces of famous and non-famous

people speaking, and video clips of moving large objects and natural or manmade scenes (same

categories as above). For the voice localiser we presented voice clips of famous and non-

famous people, and sound clips of manmade or natural environmental sounds (same categories

as used in the other two types of localisers), with no video.

Videos (640 x 360 pixels) were presented at the centre of the screen. The screen resolution was

1024 x 768 pixels, and from a distance of 85 cm, the videos subtended 20.83 x 12.27 degrees

of visual angle. Audio stimuli were presented via MR-compatible earbuds (S14; Sensimetrics

Corp.), which participants used for each entire scanning session. Each stimulus lasted 8

seconds and each run presented 48 stimuli. Stimuli were presented in pairs (24 pairs) showing

the same person (such as two videos of Brad Pitt) or the same category of objects or scenes

(such as two videos of trains). Eight pairs showed stimuli from famous people, eight pairs

showed stimuli from non-famous people, and eight pairs showed object/scene stimuli.

Participants were encouraged to always fixate at the centre of the screen. Participants

performed a one-back task in which they had to detect the exact same stimulus repetition

within each pair, which occurred in approximately 15% of the trials. A 16-second period of

fixation was presented at the end of each run and twice in the middle of each run (every 16

trials).

The order of the face, voice, and multimodal localisers was counterbalanced across

participants. For participants who completed two runs of each localiser, different identities

were presented on each run. The duration of each localiser run was approximately 8 minutes.

General linear models. To identify face-selective (face localiser), voice-selective (voice

localiser and TVA localiser), and people-selective (multimodal localiser) brain regions, we

computed mass univariate time-series models for each participant. Regressors modelled the

blood-oxygenation-level-dependent (BOLD) response following the onset of the stimuli and

were convolved with a canonical hemodynamic response function (HRF). We also used a high-

pass filter cutoff of 128 seconds, and autoregressive AR(1) model to account for serial

correlations. For the face, voice, and multimodal localisers there were three experimental

regressors: (1) famous faces/voices/people, (2) non-famous faces/voices/people, and (3) objects

and scenes. For the TVA localiser there were two experimental regressors: (1) voices and (2)

non-voices. For all localisers six head motion parameters computed during realignment were

included as covariates. Selectivity was defined with a *t*-test contrasting the responses to

faces/voices/people (famous and non-famous) *versus* responses to the control stimuli.

ROI definition. We used probabilistic maps from previous studies to define regional masks in

which we predicted that our regions of interest (ROIs) would be located. We then defined

ROIs by extracting all selective voxels within those regional masks for each participant. This

approach is similar to the one implemented by Julian et al. (2012) and avoids experimenter

biases in ROI definition.

Probabilistic maps were thresholded to only show voxels that were present in 20% of the

participants and binarised to create regional masks. We used a probabilistic map of the TVAs

created by Pernet et al. (2015) and obtained from neurovault

(http://neurovault.org/images/106/) to create separate masks for the right and left TVA (rTVA,

lTVA). For all other regional masks, we used probabilistic maps that were obtained from a

previous study conducted in the lab (unpublished data). In this previous study we tested 22

participants using the same face and voice localisers as the current study (we did not use the

multimodal localiser in this previous study). We defined face-selective and voice-selective *t*-

test images for each participant, thresholded each image at *p*<.05 (uncorrected), binarised the

resulting image, and summed all images across participants to create face-selective and voice-

selective probabilistic maps. In cases where there was some overlap between the masks for

different regions we manually defined the borders of these masks using anatomical landmarks.

Regional masks of face-selective regions were created for the right fusiform face area (rFFA),

377 the right occipital face area (rOFA), and the right posterior superior temporal sulcus (rpSTS).

378 Regional masks of voice-selective regions were created for the right and the left superior

379 temporal sulcus and gyrus (rSTS/STG, lSTS/STG). Regional masks of multimodal regions

380 were created based on joint face-selective and voice-selective probabilistic maps. These masks

381 were created for a number of regions that showed *both* face-selective and voice-selective

382 responses in most participants: precuneus/posterior cingulate, orbitofrontal cortex (OFC),

383 frontal pole (FP), and right and left temporal pole with anterior inferior temporal cortex (rTP-

384 aIT, lTP-aIT) — we considered the TP and aIT together as the peaks were difficult to separate

385 in most participants. We did not create a mask of the multimodal STS using this method due to

386 the voice-selective STS region being much larger than the face-selective STS region. However,

387 there was large overlap between our mask of the face-selective rpSTS and our masks of the

388 rSTS/STG and rTVA, suggesting that this face-selective rpSTS region also responds to voices.

390 All of the regional masks (in MNI space) were registered and resliced to each participant's

391 native space using FSL (version 5.0.9; RRID:SCR_002823; Jenkinson et al., 2012). These

392 masks were then used to extract ROIs from the *t*-test maps obtained from the contrasts of

393 interest from the face, voice, TVA, and multimodal localisers from the current study. All

394 voxels that fell within the boundaries of the mask and that were significantly activated at

395 $p<.001$ (uncorrected) were included in the subject-specific ROI. If there were fewer than 30

396 voxels at $p<.001$ the threshold was lowered to $p<.01$ or $p<.05$. If we could not define 30

397 selective voxels even at $p<.05$, the ROI for that participant was not included in the analyses.

398 We required that all ROIs be present in at least 20 participants (out of 30).

400 **Main experimental runs: Experimental design and statistical analysis**

401 **Design and procedure.** Face and voice stimuli were presented using the Psychophysics

Toolbox via a computer interface inside the scanner. Face and voice clips of all 12 identities

were intermixed within each run. A fixation point was always present and participants were

asked to fixate. The videos were 640 x 360 pixels and, from a viewing distance of 85cm,

videos subtended 20.83 x 12.27 degrees of visual angle. The six face videos and the six voice

recordings for each of the 12 identities were evenly distributed among the three runs so that

each run contained two different videos of the face and two different recordings of the voice of

each identity. Each individual stimulus was presented twice within each run. Therefore, in each

run there were 96 experimental trails (48 face trials, 48 voice trials) in total.

Participants performed an anomaly detection task that involved pressing a button when they

saw or heard a novel famous person that was not part of the set of the 12 famous people that

they had been familiarised with prior to entering the scanner. Therefore, each run also

contained 12 task trials presenting six famous faces and six famous voices that were not part of

the set of famous people that the participants had been familiarised with.

Stimuli were presented in a pseudorandom order that ensured that within each modality each

identity could not be preceded or succeeded by one of the other identities more than once, and

that each stimulus could not be succeeded by a repetition of the exact same stimulus. Face and

voice clips were presented for three seconds with a SOA of four seconds. Thirty-six null

fixation trials were added to each run (~25% of the total number of trials). Thus, each run

contained 144 trials in total and lasted approximately 10 minutes.

The presentation order of the three runs was counterbalanced across participants. The same

three runs with the same face videos and voice recordings that were presented in scanning

session one were also presented in session two. However, the three runs were presented in

different orders in both sessions (counterbalanced across participants) and stimuli within each

run were presented in a new pseudorandom sequence. As an exception, the stimuli for the task

trials were different in the two sessions in order to maintain their novelty.

General linear models. We computed mass univariate time-series models for each participant.

Models were defined separately for each scanning session and each experimental run (six runs

in total). Regressors modelled the BOLD response following the onset of the stimuli and were

convolved with a canonical hemodynamic response function (HRF). We also used a high-pass

filter cutoff of 128 seconds and autoregressive AR(1) model to account for serial correlations.

The 12 different identities in each modality were entered as separate regressors in the model

(i.e. 24 regressors). Each of these regressors included the two different face videos and voice

recordings of each identity that were presented in the run, as well as the two repetitions of each

stimulus. Task trials and six head motion parameters computed during realignment were

included as regressors of no interest.

As part of the crossvalidation procedure used in the RSA analyses described below, separate

models were estimated for each partition of each crossvalidation fold, thus resulting in

parameter estimates and residual time courses for every possible independent partition. For

partitions with two runs, data was concatenated before estimating the model. In the analyses

described below we used the beta estimates computed at each voxel of each ROI for each of

the 24 experimental conditions (12 face-identities and 12 voice-identities).

Mean response to faces and voices in ROIs. We conducted an analysis to characterise the

responses to faces and voices in each ROI, and to confirm that each ROI showed the expected

responsivity to faces and voices. For this analysis, we calculated the mean (across all voxels in

each ROI, and across all runs) of the parameter estimates for the 12 face-identities and the

mean of the parameter estimates for the 12 voice-identities. For each ROI we tested whether

the mean for faces and mean for voices were significantly different from zero (across

participants) using one-sample *t*-tests. P values were corrected for 24 comparisons (2 tests x 12

ROIs) controlling the false discovery rate (FDR), with *q*<.05. We also compared the mean for

faces with the mean for voices in each ROI using paired *t*-tests. P values were corrected for

multiple comparisons (12 comparisons) using FDR with *q*<.05.

Analysis A: RSA comparing representational geometries. For this analysis we computed

representational dissimilarity matrices (RDMs) for faces and voices (12x12 matrices)

separately for each participant, each scanning session and each ROI. We then computed the

correlations between pairs of these RDMs (for an example, see Figure 4). These analyses were

performed using in-house Matlab code and the RSA toolbox (Nili et al., 2014). To compute the

RDMs we used the linear discriminant contrast (LDC), a crossvalidated distance measure (Nili

et al., 2014; Walther et al., 2016). For each ROI, each modality (i.e. faces and voices

separately), and each scanning session, we calculated the LDC between the pattern estimates

(beta estimates across all voxels within an ROI) elicited by the different identities. The

resulting 12x12 matrices were symmetric around a diagonal of zeros (Figure 4). Each cell in

the RDMs showed the discriminability of the pattern estimates corresponding to a pair of

identities in the chosen modality and ROI.

RDMs were computed using leave-one-run-out crossvalidation across the three runs in each

session (each run presented the same identities with different stimuli). In each of three

crossvalidation folds, the pattern estimates for each identity were computed with data from two

runs (partition one) and separately from the pattern estimates from the remaining run (partition

two). The pattern estimates from each pair of identities from partition one were used to obtain a

linear discriminant, which was then applied to differentiate the activity patterns of the same

identity pairs in partition two (Nili et al., 2014; Walther et al., 2016). We applied multivariate

noise normalisation by computing a noise variance-covariance matrix based on the residual

time courses obtained from the model that was estimated with data from partition one. More

specifically, to compute the LDC for each pair of identities we first multiplied the contrast

between the patterns of a pair of identities in partition one (the discriminant weights) by the

inverse of the noise variance-covariance matrix (after regularisation using the optimal

shrinkage method: Ledoit and Wolf, 2004), and transformed the resulting weights to unit

length. We then computed the dot product between the resulting vector and the vector with the

contrast between the patterns of the same pair of identities from partition two (Carlin and

Kriegeskorte, 2017), which resulted in a single value showing the discriminability of those

identities. Finally, the resulting RDMs with LDC values from each crossvalidation fold were

averaged to create one RDM per scanning session. This procedure resulted in four RDMs per

participant per ROI: faces session 1, voices session 1, faces session 2, and voices session 2

(Figure 4). Crossvalidating across runs with different videos of the face and recordings of the

voice of each identity ensured that the resulting RDMs represented face- and voice-*identity*,

rather than specific face videos and voice recordings.

In order to compare the representational geometries of the face- and voice-identities, the RDMs

for each participant were compared across the two scanning sessions using Pearson's

correlation coefficient (Figure 4). We also compared the representational geometries of face

and voice-identities within modality across two scanning sessions in order to investigate the

stability of the representational geometries across the two scanning sessions. For the

crossmodal comparisons we compared the face and voice RDMs from session one with the

RDMs of the *other* modality in session two (i.e. faces session 1 vs. voices session 2, and voices

session 1 vs. faces session 2). For the *unimodal comparisons* we compared the face and voice

RDMs from session one with RDMs of the *same* modality in session two (i.e. faces session 1

vs. faces session 2 and voices session 1 vs. voices session 2). At the group level for each ROI

we compared the single-subject correlations for each of the four comparisons (two crossmodal,

two unimodal) against zero using one-sample one-tailed Wilcoxon signed-rank tests (because

correlations are not normally distributed). P values were corrected for multiple comparisons

(48 comparisons: 4 tests x 12 ROIs) controlling for FDR with $q < .05$.

Analysis B: RSA investigating identity discriminability. For this analysis we computed

crossmodal RDMs separately for each participant, each scanning session and each ROI. We

used the activity patterns of identity pairs in one modality to create a linear discriminant and

then applied the discriminant to the activity patterns of the same identity pairs in the other

modality. With this exception, the crossvalidation procedure was identical to the procedure for

creating face and voice RDMs for the previous analysis. Two crossmodal RDMs for each ROI

were computed using this method: one by applying a linear discriminant based on face data to

voice data, and one by applying a linear discriminant based on voice data to face data. The

LDC provides a continuous measure of discriminability for each pair of stimuli (Nili et al.,

2014; Walther et al., 2016; Carlin and Kriegeskorte, 2017). Importantly, under the null

hypothesis the LDC is symmetrically distributed around zero, and thus unbiased. By

calculating the mean LDC value across all cells in an RDM for a certain ROI we can determine

the overall ability of that ROI to discriminate between identities. Mean LDC values for all

participants can then be subjected to random-effects inference comparing against zero.

Therefore, we predicted that crossmodal RDMs for regions with modality-general person-

identity representations would show mean LDC values that are significantly greater than zero.

In addition to investigating identity discrimination *across modalities* using crossmodal RDMs,

we also investigated the ability of each ROI to discriminate between identities *within modality,*

using the face and voice RDMs that were created in the previous analysis. We predicted that

face or voice RDMs for regions that represent face or voice identity, respectively, would show

mean LDC values that are significantly greater than zero.

For this analysis the corresponding RDMs (e.g. faces session 1 and faces session 2) for each

scanning session were averaged across the two sessions, and then the mean LDC across the

vectorised matrix was calculated. Thus, for each participant and each ROI we obtained four

mean LDC values representing (1) face discriminability, (2) voice discriminability, (3a)

crossmodal discriminability - face discriminant generalised to voices, and (3b) crossmodal

discriminability - voice discriminant generalised to faces. For each ROI and each type of

discriminability we entered participants' LDC values into a one-sample one-tailed *t*-test

comparing them against zero. P values were corrected for all comparisons (48 comparisons: 4

tests x 12 ROIs) controlling for FDR with *q*<.05.

Code and data accessibility. All the code and data for the above analyses will be made

available after publication.

Exploratory whole-brain searchlight analyses. Despite including a broad range of

functionally defined ROIs, it is possible that modality-general person-identity representations

may exist in brain regions not included in our ROIs. Specifically, these representations may

exist in brain regions that are not face-selective or voice-selective. Therefore, we used an

exploratory whole-brain searchlight analysis to identify potential brain regions with person-

identity representations using the same methods as in our main ROI analyses. We note that we

focused solely on modality-general person-identity representations in this exploratory analysis,

as that was the main aim of this study.

For each participant we created 6mm radius spheres centred on each voxel within a grey-matter

mask of their brain (obtained from the segmentation procedure) using the RSA toolbox (Nili et

al., 2014) in Matlab. A 6 mm radius resulted in a searchlight sphere of 33 voxels, which

matched our requirement for minimum ROI size of 30 voxels in the main analyses. For the

analysis comparing representational geometries we computed a face and a voice RDM in each

searchlight sphere, averaging the RDMs from both scanning sessions, and then calculated the

Pearson correlation between them. Correlations were Fisher z-transformed. The output of this

analysis was a whole-brain map of Fisher-transformed correlation coefficients for each

participant. For the second analysis investigating identity discriminability we computed a

single crossmodal RDM in each searchlight sphere by averaging the crossmodal face-voice

RDM with the crossmodal voice-face RDM, and then calculating the mean LDC across the

resulting matrix in vector form. The output for each participant was a whole-brain map of mean

LDC values.

The whole-brain searchlight maps from each analysis were normalised to MNI space using the

normalisation parameters generated during the segmentation procedure and spatially smoothed

with 9-mm Gaussian kernel (full width at half maximum) to correct for errors in intersubject

alignment. For group-level analysis, all searchlight maps were entered into a one-sample t-test

to determine whether the correlation coefficient/mean LDC value was significantly greater than

zero at each voxel. We used the randomise tool (Winkler et al., 2014) in FSL for inference on

the resulting statistical maps (5,000 sign-flips). Clusters were identified with threshold-

free cluster enhancement (TFCE), and p-values were corrected for multiple comparisons (FWE

< 0.05).

Results

Familiarity ratings

Familiarity ratings of both faces and voices were high (Faces: $M = 6.28$, $SD = 0.5$; Voices: $M =$

6.2, $SD = 0.49$). Average familiarity of each identity's face and voice are shown in Table 1.

Table 1. Familiarity ratings of the face and voice of each identity averaged across participants showing the mean
(M) rating of the face and voice of each identity across all face videos and all voice recordings of that identity, the
standard deviation (SD) of participants' ratings of each identity, and the range of mean ratings for the six face
tokens and six voice tokens for each identity. The rating scale ranged from 1 (very unfamiliar) to 7 (very familiar).

		AC	AS	BO	DR	GN	JR	BK	BW	CC	EW	KM	SO
Faces	M	6.48	5.72	6.94	6.76	6.27	6.42	6.36	5.65	6.49	6.73	5.25	6.32
	SD	0.75	1.19	0.2	0.59	0.85	0.59	0.94	1.45	0.79	0.45	1.48	0.92
	Token range	6.37- 6.60	4.83- 6.13	6.90- 7	6.67- 6.87	5.87- 6.5	6.17- 6.57	6.07- 6.57	5.33- 5.9	6.37- 6.60	6.47- 6.9	4.6- 5.57	6.17- 6.47
Voices	M	6.59	5.66	6.73	6.69	6.37	6.54	6.23	5.54	6.63	6.07	5.3	6.02
	SD	0.54	1.48	0.63	0.57	0.77	0.71	1.04	1.74	0.74	0.94	1.45	1.03
	Token range	6.37- 6.83	5.43- 5.87	6.7- 6.8	6.57- 6.8	6.07- 6.67	6.3 6.7	6.07- 6.37	5.47- 5.67	6.4- 6.77	4.6- 6.53	5- 5.53	5.5- 6.43

ROI definition

Using functional localisers we defined face-selective ROIs (rFFA, rOFA, rpSTS), voice-

selective ROIs (rSTS/STG, rTVA, lSTS/STG, lTVA), and multimodal ROIs (OFC, FP, rTP-

aIT, lTP-aIT, Prec./P.Cing. [including the retrosplenial cortex]) in each participant. We were

able to localise these ROIs with at least 30 voxels in all 30 participants, except for the face-

selective rFFA (28 participants) and rOFA (29 participants), the Prec./P.Cing. (26

participants), and the OFC (21 participants). We note that the voice-selective ROIs in the right

hemisphere (rTVA, rSTS/STG) overlap with each other and with the face-selective rpSTS and

the multimodal rTP-aIT ROIs. In addition, the voice-selective ROIs in the left hemisphere

(lTVA, lSTS/STG) overlap with each other and with the multimodal lTP_aIT ROI. For

visualisation purposes only, probabilistic maps of all ROIs were created by normalising the

single subject ROIs to MNI space and summing them. Figure 1 shows those maps thresholded

to display all voxels that were present in at least 20% of the participants.

605
606   **Figure 1: Face-selective, voice-selective, and multimodal ROIs**. Location of ROIs that resulted from the face,
607   voice, and multimodal localisers in MNI space.
608
609   r = right, l = left, FFA = fusiform face area, OFA = occipital face area, pSTS = posterior superior temporal sulcus,
610   STS/STG = superior temporal sulcus/superior temporal gyrus, TVA = temporal voice area, OFC = orbitofrontal
611   cortex, FP = frontal pole, TP = temporal pole, aIT = anterior inferior temporal cortex, Prec = precuneus, P.Cing. =
612   posterior cingulate.
613

Mean response to faces and voices in ROIs

In order to confirm that each ROI showed the expected responsiveness to faces and voices, we

computed the regional mean of the parameter estimates for faces and for voices across

participants for each ROI and modality (Figure 2). As expected, mean beta values for faces

were high and significantly greater than zero in all three face-selective ROIs (all one-sample *t*-

tests with *p<.0001*). Mean beta values for voices were also significantly greater than zero in

the rFFA (*p<.0001*) and rpSTS (*p<.0001*), but not in the rOFA. The rFFA and the rOFA

showed significantly greater responses to faces compared with voices (both paired-samples *t*-

tests with *p<.0001*). In contrast, the rpSTS showed significantly greater responses to voices

compared with faces (*p=.0002*) despite being defined using our face localiser. This is most

likely due to the large overlap between this ROI and the voice-selective rSTS/STG and rTVA

ROIs. This finding demonstrates that the rpSTS also showed substantial responses to voices.

627
628
Figure 2: Regional mean responses to faces and voices in ROIs. Regional mean responses for all face-identities
and for all voice-identities in face-selective, voice-selective, and multimodal ROIs (mean beta estimates across all
voxels of each ROI, and across all runs). Bars show mean responses across participants, error bars show standard
error, and grey circles show individual participants. We tested whether mean responses were significantly greater
than zero using one-sample *t*-tests across all 30 participants, and stars show significant results at *p≤.0209* (FDR
corrected for all 24 comparisons). We also tested whether mean beta values for faces were significantly different
from mean beta values for voices in each ROI using paired *t*-tests across all participants. In all ROIs mean beta
values for faces and voices were significantly different at *p≤.0011* (FDR corrected for all 12 ROIs).
637

It could be that the responses to voices in rpSTS were due to the voices being familiar, and not

because of being voices *per se*. To determine whether this region responded to voices more

generally or just to familiar voices, we investigated the responses in rpSTS to familiar voices,

unfamiliar voices, and non-voices during the functional voice localisers. For each participant,

we calculated the mean parameter estimates across all voxels of the face-selective rpSTS for

each condition of the voice localiser (familiar voices, unfamiliar voices, and auditory scenes)

and of the TVA localiser (vocal and non-vocal sounds). For the voice localiser, both the

familiar and the unfamiliar voices had significantly higher parameter estimates than the

auditory scenes (both $p<.0001$). For the TVA localiser, the rpSTS also showed significantly

higher responses to voices than non-voices ($p<.0001$). These results show that the face-

selective rpSTS also responds to voices in general and not only familiar voices (for similar

results, see Deen et al., 2015), and therefore in the rest of this article we will refer to this rpSTS

region as displaying multimodal responses.

Returning to the analysis of the parameter estimates for faces and voices during the main

experimental runs, the mean beta values for voices were significantly greater than zero for all

four voice selective ROIs (all $p<.0001$). Mean beta values for faces were also significantly

greater than zero for all voice-selective ROIs (all $p≤.0209$), but the parameter estimates were

significantly lower than for voices (all $p<.0001$).

For the multimodal ROIs mean beta values for faces and for voices were significantly greater

than zero in all ROIs (all $p≤.0009$) except the frontal pole for faces. This result demonstrates

that, although we still included the frontal pole ROI in the main analyses, we cannot be

confident about the multimodal responses of this ROI. Also, we note that in all multimodal

ROIs (OFC, FP, rTP-aIT, lTP-aIT, Prec./P.Cing.) mean beta values for voices were

significantly higher than mean beta values for faces (all $p≤.0011$). We observed this

consistently across all participants.

Analysis A: RSA comparing representational geometries

Our first main analysis compared the representational geometry of the 12 famous identities across and within modalities in each ROI. We computed face and voice RDMs separately for each session using the LDC and compared the RDMs using Pearson correlation (Figures 3 & 4). We then tested whether these correlations were significantly above zero.

Figure 3: Results of RSA comparing representational geometries. Comparisons between the representational distance matrices (RDMs) from two scanning sessions using Pearson's correlation coefficient. Bars show mean correlations across participants, error bars show standard error, and grey circles show the correlations of individual participants. Correlations were calculated across scanning sessions and compared face RDMs, voice RDMs, face and voice RDMs, and voice and face RDMs in face-selective, voice-selective, and multimodal ROIs. We tested whether correlations were significantly greater than zero using Wilcoxon signed-rank tests across all 30 participants. No correlations were significant after correction for multiple comparisons at $p \leq .0001$ (FDR corrected for all 48 comparisons). Note that in this figure the rpSTS is classed as a face-selective ROI for consistency purposes only, but in fact it demonstrated multimodal properties.

Figure 4: Representational distance matrix (RDM) comparisons across scanning sessions 1 and 2 in the rpSTS. Face and voice RDMs for the rpSTS were averaged across all 30 participants for illustration purposes. Each cell shows the discriminability of the brain activity patterns corresponding to a pair of identities (12 identities in total) computed using the linear discriminant contrast (LDC) and crossvalidating across data from three runs. Each matrix is symmetric around a diagonal of zeros. A value of zero or lower indicates no discriminability. For each participant we compared the representational geometry of the face and voice RDMs with the representational geometry in the RDM of the *other* modality (crossmodal comparisons) and in the RDM of the *same* modality (unimodal comparisons) using Pearson's correlation. The figure shows Pearson's correlations for all comparisons averaged across participants.

We predicted that face and voice RDMs would be correlated in ROIs that represent person-identity independently from modality. However, our results showed no significant correlations between face and voice RDMs in face-selective, voice-selective, or multimodal ROIs (Figure 3). It is possible that comparing RDM across different scanning sessions taking place on separate days did not allow us to detect subtle consistencies in the representational geometry for face-identities and voice-identities. To address this concern, we also compared face and voice RDMs within the same scanning session. However, we still found no significant correlations between face and voice RDMs. Therefore, using this method we found no evidence of modality-general person-identity representations in our ROIs.

We also predicted that there would be correlations between RDMs within the same modality in

regions that represent only face-identity or only voice-identity. No correlations between face

RDMs or between voice RDMs in any ROI were significant after correction for multiple

comparisons.

Analysis B: RSA investigating identity discriminability

Our second main analysis tested the generalisation of pattern discriminants from one modality

to the other. More specifically, we computed crossmodal RDMs and we tested whether linear

discriminants computed on pairs of faces could be used to discriminate between pairs of

voices, and vice-versa. We also tested whether each ROI could discriminate between pairs of

stimuli within the same modality. Mean LDC distances across all cells in crossmodal, face, and

voice RDMs were compared against zero.

718
719
Figure 5: Results of RSA investigating identity discriminability. Mean LDC between identities in face RDMs,
voice RDMs, and crossmodal RDMs in face-selective, voice-selective, and multimodal ROIs. There are two types
of crossmodal RDMs: (a) face discriminant applied to voices (F-V), and (b) voice discriminant applied to faces
(V-F). Bars show mean LDC values averaged across participants, error bars show standard error, and grey circles
show mean LDC values for individual participants. We tested whether the mean LDC values were significantly
greater than zero using one-sample t-tests across all 30 participants. Stars represent significant tests at $p \leq 0150$

(FDR corrected for all 48 comparisons). These results show generalisation of the pattern discriminants from one
modality to the other in the rpSTS and in the lSTS/STG. In addition, face-selective ROIs discriminate between
face-identities, and voice-selective ROIs discriminate between voice-identities. Note that in this figure the rpSTS
is classed as a face-selective ROI for consistency purposes only, but in fact it demonstrated multimodal properties.
730

731 **Table 2.** One-sample *t*-test results for mean LDC values in crossmodal RDMs. Stars represent statistical
732 significance at $p \leq .0150$ (FDR corrected for all 48 comparisons in face, voice, and crossmodal RDMs). The rpSTS
733 is classed as a face-selective ROI for consistency purposes only, but in fact it demonstrated multimodal properties.

	df	t	Crossmodal RDMs (face-voice) Sig. (1-tailed)	d	t	Crossmodal RDMs (voice-face) Sig. (1-tailed)	d
Face-selective ROIs							
rFFA	27	-0.198	.5779	0.04	-0.529	.6993	0.10
rOFA	28	0.374	.3557	0.07	0.624	.2689	0.12
rpSTS	29	4.091	.0002*	0.75	4.582	.0001*	0.84
Voice-selective ROIs							
rSTS/STG	29	1.928	.0319	0.35	2.093	.0226	0.38
rTVA	29	2.064	.0240	0.38	1.662	.0537	0.30
lSTS/STG	29	2.443	.0104*	0.45	3.543	.0007*	0.65
lTVA	29	0.062	.4755	0.01	1.891	.0343	0.35
Multimodal ROIs							
OFC	20	1.698	.0525	0.37	0.841	.0250	0.18
FP	29	-0.062	.5244	0.01	0.285	.3888	0.05
rTP-aIT	29	0.023	.4910	0.00	0.153	.4398	0.03
lTP-aIT	29	0.301	.3830	0.05	0.075	.4703	0.01
Prec./P.Cing.	25	0.660	.2577	0.13	0.220	.4138	0.04

736 **Table 3.** One-sample *t*-test results for mean LDC values in face and voice RDMs. Stars represent statistical
737 significance at $p \leq .0150$ (FDR corrected for all 48 comparisons in face, voice, and crossmodal RDMs). The rpSTS
738 is classed as a face-selective ROI for consistency purposes only, but in fact it demonstrated multimodal properties.

	df	t	Face RDMs Sig. (1-tailed)	d	t	Voice RDMs Sig. (1-tailed)	d
Face-selective ROIs							
rFFA	27	7.764	.0001*	1.47	-0.753	.7711	0.14
rOFA	28	6.707	.0001*	1.25	0.995	.1641	0.18
rpSTS	29	4.378	.0001*	0.80	5.871	.0001*	1.07
Voice-selective ROIs							
rSTS/STG	29	1.850	.0373	0.34	5.025	.0001*	0.92
rTVA	29	2.945	.0031*	0.54	5.447	.0001*	0.99
lSTS/STG	29	1.019	.1583	0.19	8.667	.0001*	1.58
lTVA	29	2.846	.0040*	0.52	7.834	.0001*	1.43
Multimodal ROIs							

OFC	20	-0.662	.7424	0.14	2.337	.0150*	0.51
FP	29	0.799	.2153	0.15	4.007	.0002*	0.73
rTP-aIT	29	1.617	.0583	0.30	2.685	.0059*	0.49
lTP-aIT	29	-2.369	.9877	0.43	1.630	.0570	0.30
Prec./P. Cing.	25	2.538	.0089*	0.50	5.524	.0001*	1.08

We predicted that in brain regions with modality-general person identity representations the

mean LDC values for crossmodal RDMs would be significantly greater than zero. Our results

showed that mean LDC values in these RDMs were significantly greater than zero in the

rpSTS, and in the voice-selective lSTS/STG (Figure 5; Table 2). These results show that the

rpSTS could discriminate pairs of face-identities based on pattern discriminants computed from

pairs of voice-identities (and vice-versa), and therefore appears to form modality-independent

person-identity representations.

We note that while the mean LDC values for crossmodal RDMs in the lSTS/STG were

significant, the mean LDC value for face RDMs was not. While this result suggests that this

region was able to discriminate identities based on crossmodal information, it is unlikely that a

modality-general representation could exist without face-identity discrimination. Therefore,

this result should be interpreted with caution. It is possible that in addition to the rpSTS, the

lpSTS also contains a modality-general person-identity representation and it could be driving

the positive result in the lSTS/STG. However, we were not able to test this because we could

not localise the lpSTS in our participants using our face localiser.

We also predicted that mean LDC values for face RDMs and voice RDMs would be

significantly greater than zero in ROIs that represent face-identity and voice-identity,

respectively. We found that mean LDC values in face RDMs were significantly greater than

zero in all ROIs originally defined as face-selective (rFFA, rOFA, rpSTS), in the TVAs, and in

the multimodal Prec./P. Cing. (Figure 5; Table 3). These results show that all these regions

could discriminate between face-identities. A follow up analysis in which all overlapping

rpSTS voxels were removed from the rTVA showed that the significant result for faces in

rTVA was driven by the rpSTS. Mean LDC values in voice RDMs were significantly greater

than zero in all voice-selective ROIs (TVAs, STS/STG), in the rpSTS (originally defined as

face-selective), and in the multimodal OFC, FP, rTP-aIT and Prec./P. Cing. (Figure 5; Table 3).

It is possible that the discrimination of identities in our ROIs was driven by different-gender

identity pairs (female-male). To investigate this possibility, for each ROI and condition that

showed mean LDC values significantly greater than zero (Figure 5 & Tables 2,3) and for each

participant we compared the mean LDC values for different-gender identity pairs (calculated

across 36 pairs) with the mean LDC values for same-gender identity pairs (calculated across 30

pairs: female-female & male-male) in each RDM (we used paired *t*-tests, and used FDR

correction for all 19 comparisons). Results for the rpSTS showed no significant difference

between the discriminability of different-gender and same-gender identity pairs for face, voice,

or crossmodal RDMs (all $p>.0533$), demonstrating that person-identity discrimination in this

region was not driven by discriminating gender. In contrast, mean LDC values for different-

gender identity pairs were significantly higher than mean LDC values for same-gender identity

pairs for face RDMs in the rFFA and rOFA (both $p \leq .0010$), and for voice RDMs in the

bilateral TVAs and STS/STG (all $p\leq.0005$), suggesting that gender contributed to the

discrimination in these regions. However, mean LDC values for same-gender identity pairs

were still significantly greater than zero (one-sample *t*-tests) for face RDMs in the rFFA and

rOFA (both $p<.0001$) and for voice RDMs in the bilateral TVAs and STS/STG (all $p\leq.0239$),

suggesting that identity discrimination in these regions is not solely driven by differences in

gender.

Exploratory whole-brain searchlight analyses.

Finally, we conducted additional exploratory searchlight analyses across the whole brain to

determine whether there were brain regions with modality-general person-identity

representations that are not included in our ROIs. The first searchlight analysis investigated

correlations between face and voice RDMs across the whole brain, and we did not find any

regions showing such correlations between face and voice representational geometries.

The second searchlight analysis investigated crossmodal generalization of discriminants for

pairs of identities across the whole brain. We found a number of clusters in which the mean

LDC in crossmodal RDMs was significantly greater than zero (FWE corrected threshold $p \leq$

.05), and below we report t-values and MNI coordinates for the peak grey matter voxels in each

cluster. Anatomical labels for peak voxels are based on the Harvard-Oxford cortical and

subcortical structural atlases. The results showed a large cluster (k=1927, p=.007) with peaks in

the right putamen (t=4.33, x=21, y=20, z=-1), the left posterior middle temporal gyrus

(t=4.04, x=-57, y=-19, z=-7), and the right precentral gyrus (t=3.89, x=54, y=8, z=32).

Significant clusters were also found in the right paracingulate gyrus (k=1340, p=.003, t=4.34,

x=6, y=47, z=23), in the left hippocampus (k=160, p=.017, t=4.45, x=-24, y=-37, z=2), in the

right anterior supramarginal gyrus (k=84, p=.006, t=6.18, x=48, y=-22, z=38), in the left cuneal

cortex (k=48, p=.036, t=3.99, x=-18, y=-76, z=29), and a cluster (k=100, p=.039) with peaks in

the left temporooccipital middle temporal gyrus (t=3.58, x=-48, y=-46, z=5) and inferior lateral

occipital cortex (t=3.45, x=-48, y=-67, z=8). Finally, we also found a significant cluster in the

rpSTS at an uncorrected threshold of $p \leq$ .005 (k=592, p=.001, t=4.05, x=48, y=-49, z=11) that

overlapped with our rpSTS ROI.

Discussion

We show evidence of a modality-general person-identity representation in a multimodal region

of the rpSTS, demonstrating that this region was able to discriminate familiar identities based

on modality-general information in faces and voices. More specifically, the rpSTS could

discriminate pattern estimates for pairs of face-identities based on linear discriminants

computed from pattern estimates for pairs of voice-identities, and vice-versa. A crucial and

novel aspect of our study is that we showed that the rpSTS not only discriminates between

identities, but also generalises across multiple naturalistically varying face videos and voice

recordings of the same identity. By always comparing pattern estimates across independent

runs with different face and voice tokens for the same identities, we showed that the face- and

voice-elicited person-identity representations in the rpSTS are stimuli-invariant. Invariant

identity representations were also found for face-identities in face-selective regions (rFFA and

rOFA) and for voice-identities in voice-selective regions (bilateral TVA and STS/STG).

Finally, we did not find evidence of matching representational geometries for faces and voices,

across or within modalities.

A modality-general and invariant person-identity representation in the rpSTS

Our finding of a modality-general person-identity representation in a multimodal region of the

rpSTS supports the Multimodal Processing Model, which proposes that face and voice

information is integrated in multimodal brain regions (Ellis et al., 1997; Campanella and Belin,

2007). In contrast, we did not find support for the prediction from the Coupling of Face and

Voice Processing Model (von Kriegstein et al., 2005; von Kriegstein and Giraud, 2006) that

there would be a modality-general identity representation in face-selective regions of the

fusiform gyrus.

The rpSTS has previously been associated with crossmodal representations of emotion from

faces and voices and shows a preference for people-related stimuli regardless of modality

(Watson et al., 2014a, 2014b). Furthermore, multiple studies have demonstrated overlap

between face-selective and voice-selective regions in the rpSTS (Wright et al., 2003; Watson et

al., 2014a; Deen et al., 2015; Anzellotti and Caramazza, 2017;). It has been proposed that the

STS integrates person-specific patterns of movement from faces, voices, and bodies to assist in

person-identity recognition (Yovel and O'Toole, 2016). It is possible that the intrinsic

relationship between a person's idiosyncratic facial movements and manner of speech

contributes to the integration of face- and voice-identity information in the rpSTS.

Our finding of a modality-general identity representation in the rpSTS is also in agreement

with two recent studies showing across-modality classification of pattern estimates for familiar

faces and voices in the rpSTS (Anzellotti and Caramazza, 2017) and a more anterior part of the

STS (Hasan et al., 2016). In contrast to these previous studies, we showed that the rpSTS also

demonstrates face- and voice-elicited representations of person-identity that are invariant to

different tokens of the same face and voice. The ability to "tell people together" by identifying

different tokens of a face and voice as belonging to the same person is as important as the

ability to "tell people apart" (i.e. discriminate between different people) (Burton, 2013;

Anzellotti and Caramazza, 2014). Hasan et al. (2016) were unable to investigate invariant

representations because they used a single face image and a single voice recording for each

identity, which in turn were derived from the same original stimulus, making interpretation of

their results difficult (Lavan, 2017). Anzellotti and Caramazza (2017) used two face and voice

tokens for each identity but did not train and test their classifier on different tokens, and

therefore did not demonstrate representations that were invariant to different tokens of the

same face and voice in this study. Finally, in contrast to these previous studies, we used a

larger set of identities and multiple naturalistically varying tokens in order to better capture the

level of robust invariant recognition required in everyday life. While behavioural studies have

shown the importance of within-person variability for recognition (Jenkins et al., 2011; Burton,

2013; Burton et al., 2016), this is rarely taken into account in neuroimaging experiments, which

typically use highly similar or artificial stimuli for the same person.

Invariant representations of face-identity and voice-identity

The face-selective rFFA and rOFA were able to discriminate between the faces of different

people while also showing invariance to the different videos of each person's face. This finding

is in agreement with Anzellotti et al. (2014) and Guntupalli et al. (2017), who showed

representations of face-identity in the FFA (and OFA, in Anzelotti et al., 2014) that generalise

across different viewpoints of the face. However, in contrast with these studies, which used

stimuli with low within-person variability, we show that representations in these regions

generalise across highly variable face videos, and can thus discriminate between different face-

identities, rather than between individual face *images*.

Voice-selective regions in STS/STG and the TVAs bilaterally could discriminate between

different speakers while showing invariance to the different recordings of each voice. These

findings are in line Formisano et al. (2008), who showed representations of speaker identity

that generalise across utterances of different vowels in the lateral Heschl's gyrus/sulcus and in

the right STS. We extend this finding by showing that generalisation across different

recordings of the same voice is possible even when using short sentences with variable speech

content that were recorded in different settings.

We also found invariant discrimination of face- and voice-identity in a multimodal region in

the precuneus/posterior cingulate. This region has been previously associated with the

processing of familiar faces and voices (Shah et al., 2001), and has been found to discriminate

between different face-identities (Visconti Di Oleggio Castello et al., 2017). Our results

suggest that representations of faces and voices may be interspersed in this region, but are not

shared across modalities. Finally, we showed invariant representations of voice-identity, but

not face-identity, in the frontal pole, a region that has been previously associated with the

processing of familiar voices (Nakamura et al., 2001). It should be noted that although we

initially localised the frontal pole as a multimodal region, our results showed that it did not

respond significantly to faces in the main experimental runs.

Representational geometries

We did not find matching representational geometries across faces and voices in rpSTS despite

finding crossmodal generalisation of the pattern discriminants. It is possible that all identities

were equally distinct from each other within each modality (i.e. the nature of person-identity

code in these regions does not result in variable representational distances between identities).

In addition, the rpSTS shows both modality-specific and modality-general representations, and

it is possible that the former had stronger influence on the representational geometry.

Beauchamp et al. (2004) showed that the pSTS contains intermixed visual, auditory, and

multisensory patches, and future studies could use higher-resolution neuroimaging methods to

probe person-identity representations in this region.

In all other ROIs, we also did not find any evidence of stable representational geometries for

face-identities or voice-identities only. Again, it could be that identities were equally distinct

across from each other within each modality, or it could be that experimental conditions would

need to be improved to obtain more reliable representational geometries.

Anterior temporal lobe and searchlight results

We did not find evidence of face-, voice-, or person-identity representations in the anterior temporal lobe. This was surprising given that this region has been previously associated with the processing of person-identity (Ellis et al., 1989; Gainotti, 2011). The fact that our TP-aIT ROIs responded more to voices that to faces suggests that our multimodal region localiser was not optimal for detecting multimodal responses in the anterior temporal lobe. Moreover, our sequences were not tailored to detect fMRI responses in this region (Axelrod and Yovel, 2013), and therefore more research using specialised scanning parameters for the localisation of this region is warranted.

It is possible that modality-general representations exist outside face- and/or voice-selective regions, and our exploratory searchlight results revealed person-identity representations in the paracingulate gyrus, right insular cortex, left nucleus accumbens, left anterior postcentral gyrus, and left hippocampus. Quiroga et al. (2005, 2009) found that cells in the hippocampus (and also amygdala and entorhinal cortex) were highly responsive to specific identities, and responded to both the face and name of that person. It will be interesting to further probe the role of the hippocampus (and the other regions found during the searchlight analyses) in person-identity recognition.

Conclusion

To conclude, we showed a modality-general person-identity representation that generalises across different, naturalistically varying face videos and voice recordings of the same person in a multimodal region of the rpSTS. This supports the Multimodal Processing Model for face and voice integration. We also found evidence of video-invariant face-identity representations

937 in face-selective regions (rFFA, rOFA), and sound-invariant voice-identity representations in

938 voice-selective regions (TVA, STS/STG). Future studies could focus on the nature and type of

939 face and voice information that is represented in these different regions, and in how these

940 representations are formed, both through development, and during the process of becoming

941 familiar with someone.

References

References

Anzellotti S, Caramazza A (2014) The neural mechanisms for the recognition of face identity

in humans. Front Psychol 5:1–6.

Anzellotti S, Caramazza A (2016) From parts to identity: invariance and sensitivity of face

representations to different face halves. Cereb Cortex 26:1900–1909.

Anzellotti S, Caramazza A (2017) Multimodal representations of person identity individuated

with fMRI. Cortex 89: 85–97.

Anzellotti S, Fairhall SL, Caramazza A (2014).Decoding representations of face identity that

are tolerant to rotation. Cereb Cortex 24:1988–1995.

Axelrod V, Yovel G (2013) The challenge of localizing the anterior temporal face area: A

possible solution. Neuroimage 81:371–380.

Axelrod V, Yovel G (2015) Successful decoding of famous faces in the fusiform face area.

PLoS One 10: e0117126.

Beauchamp MS, Argall BD, Bodurka J, Duyn JH, Martin A (2004) Unraveling multisensory

integration: patchy organization within human STS multisensory cortex. Nat Neurosci

7:1190–1192.

Belin P, Zatorre RJ, Lafaille P, Ahad P, Pike B (2000) Voice-selective areas in human auditory

cortex. Nature 403:309–312.

Brainard DH (1997) The psychophysics toolbox. Spat vis 10:433-436.

Burton AM (2013) Why has research in face recognition progressed so slowly? The

importance of variability. Q J Exp Psychol 66:1467–1485.

Burton AM, Kramer RSS, Ritchie KL, Jenkins R (2016) Identity from variation:

Representations of faces derived from multiple instances. Cogn Sci 40:202–223.

Campanella S, Belin P (2007) Integrating face and voice in person perception. Trends Cogn Sci

11:535–543.

Carlin JD, Kriegeskorte N (2017) Adjudicating between face-coding models with individual-

face fMRI responses. PLoS Comput Biol 13: e1005604.

Collins JA, Koski JE, Olson IR (2016) More than meets the eye: The merging of perceptual

and conceptual knowledge in the anterior temporal face area. Front Hum Neurosci 10:1–

11.

Deen B, Koldewyn K, Kanwisher N, Saxe R (2015) Functional organization of social

perception and cognition in the superior temporal sulcus. Cereb Cortex 25:4596–4609.

Ellis AW, Young AW, Critchley EMR (1989) Loss of memory for people following temporal

lobe damage. Brain 112:1469–1483.

Ellis HD, Jones DM, Mosdell N (1997) Intra- and inter-modal repetition priming of familiar

faces and voices. Br J Psychol 88:143–156.

Formisano E, De Martino F, Bonte M, Goebel R (2008) "Who" is saying "what"? Brain-based

decoding of human voice and speech. Science 322:970–973.

Fox, CJ, Iaria G, Barton JJS (2009) Defining the face processing network: Optimization of the

functional localizer in fMRI. Hum Brain Mapp 30:1637–1651.

Gainotti G (2011) What the study of voice recognition in normal subjects and brain-damaged

patients tells us about models of familiar people recognition. Neuropsychologia 49:2273–

2282.

Goesaert E, Op de Beeck HP (2013) Representations of facial identity information in the

ventral visual stream investigated with multivoxel pattern analyses. J Neurosci 33:8549–

8558.

Guntupalli JS, Wheeler KG, Gobbini MI (2017) Disentangling the representation of identity

from head view along the human face processing pathway. Cereb Cortex 27:46–53.

Hasan BAS, Valdes-Sosa M, Gross J, Belin P (2016) "Hearing faces and seeing voices":

Amodal coding of person identity in the human brain. Sci Rep 6:37494.

Jenkins R, White D, Van Montfort X, Burton AM (2011) Variability in photos of the same

face. Cognition 121:313–323.

Jenkinson M, Beckmann CF, Behrens TE, Woolrich MW, Smith SM (2012)

Fsl. Neuroimage 62:82-790.

Joassin F, Pesenti M, Maurage P, Verreckt E, Bruyer R, Campanella S (2011) Cross-modal

interactions between human faces and voices involved in person recognition. Cortex

47:367–376.

Julian JB, Fedorenko E, Webster J, Kanwisher N (2012) An algorithmic method for

functionally defining regions of interest in the ventral visual pathway. Neuroimage

60:2357–2364.

Kanwisher N, McDermott J, Chun MM (1997) The fusiform face area: a module in human

extrastriate cortex specialized for face perception. J Neurosci 17:4302–4311.

Kriegeskorte N, Formisano E, Sorger B, Goebel R (2007) Individual faces elicit distinct

response patterns in human anterior temporal cortex. Proc Natl Acad Sci U S A,

104:20600–20605.

Kriegeskorte N, Kievit RA (2013) Representational geometry: Integrating cognition,

computation, and the brain. Trends Cogn Sci 17:401–412.

Kriegeskorte N, Mur M, Bandettini PA (2008a) Representational similarity analysis -

connecting the branches of systems neuroscience. Front Syst Neurosci 2:1–28.

Kriegeskorte N, Mur M, Ruff DA, Kiani R, Bodurka J, Esteky H, Tanaka K, Bandettini PA

(2008b) Matching categorical object representations in inferior temporal cortex of man

and monkey. Neuron 60:1126–1141.

Lavan N (2017) Commentary: "Hearing faces and seeing voices": Amodal coding of person

identity in the human brain. Front Neurosci 11:303.

Ledoit O, Wolf M (2004) A well-conditioned estimator for large-dimensional covariance

matrices. J Multivar Anal 88:365-411.

Nakamura K, Kawashima R, Sugiura M, Kato T, Nakamura A, Hatano K, Nagumo S, Kubota

K. Fukuda H, Ito K, Kojima S (2001) Neural substrates for recognition of familiar voices:

A PET study. Neuropsychologia 39:1047–1054.

Nestor A, Plaut DC, Behrmann M (2011) Unraveling the distributed neural code of facial

identity through spatiotemporal pattern analysis. Proc Natl Acad Sci U S A 108:9998–

10003.

Nili H, Wingfield C, Walther A, Su L, Marslen-Wilson W, Kriegeskorte N (2014) A toolbox

for representational similarity analysis. PLoS Comput Biol 10:e1003553.

Pelli DG (1997) The VideoToolbox software for visual psychophysics: Transforming numbers

into movies. Spat vis 10:437-442.

Pernet CR, McAleer P, Latinus M, Gorgolewski KJ, Charest I, Bestelmeyer PEG, Watson RH,

Fleming D, Crabbe F, Valdes-Sosa M, Belin P (2015) The human voice areas: Spatial

organization and inter-individual variability in temporal and extra-temporal cortices.

NeuroImage 119:164–174.

Pitcher D, Dilks DD, Saxe RR, Triantafyllou C, Kanwisher N (2011) Differential selectivity

for dynamic versus static information in face-selective cortical regions. NeuroImage

56:2356–2363.

Quiroga RQ, Reddy L, Kreiman G, Koch C, Fried I (2005) Invariant visual representation by

single neurons in the human brain. Nature 435:1102–1107.

Quiroga RQ, Kraskov A, Koch C, Fried I (2009) Explicit encoding of multimodal percepts by

single neurons in the human brain. Curr Biol 19:1308-1313.

Schweinberger SR, Herholz A, Sommer W (1997) Recognizing famous voices. J Speech Lang

Hear Res 40:453–463.

Shah NJ, Marshall JC, Zafiris O, Schwab A, Zilles K, Markowitsch HJ, Fink GR (2001) The

neural correlates of person familiarity. A functional magnetic resonance imaging study with clinical implications. Brain 124:804–815.

Verosky SC, Todorov A, Turk-Browne NB (2013) Representations of individuals in ventral temporal cortex defined by faces and biographies. Neuropsychologia 51:2100–2108.

Visconti Di Oleggio Castello M, Halchenko YO, Guntupalli JS, Gors JD, Gobbini MI (2017) The neural representation of personally familiar and unfamiliar faces in the distributed system for face perception. Sci Rep 7:1–14.

Van Lancker D, Krieman J, Emmorey K (1985) Familiar voice recognition: Patterns and parameters. Part I: Recognition of backward voices. J Phon 13:19-38.

von Kriegstein K, Kleinschmidt A, Sterzer P, Giraud, AL (2005) Interaction of face and voice areas during speaker recognition. J Cogn Neurosci 17:367–376.

von Kriegstein K, Giraud AL (2006) Implicit multisensory associations influence voice recognition. PLoS Biol 4:e326.

von Kriegstein K, Kleinschmidt A, Giraud AL (2006) Voice recognition and cross-modal responses to familiar speakers' voices in prosopagnosia. Cereb Cortex 16:1314–1322.

von Kriegstein K, Dogan O, Grüter M, Giraud AL, Kell CA, Grüter T, Kleinschmidt A, Kiebel SJ (2008) Simulation of talking faces in the human brain improves auditory speech recognition. Proc Natl Acad Sci U S A 105:6747–6752.

Walther A, Nili H, Ejaz N, Alink A, Kriegeskorte N, Diedrichsen J (2016) Reliability of dissimilarity measures for multi-voxel pattern analysis. Neuroimage 137:188–200.

Watson R, Latinus M, Charest I, Crabbe F, Belin P (2014a) People-selectivity, audiovisual integration and heteromodality in the superior temporal sulcus. Cortex 50:125–136.

Watson R, Latinus M, Noguchi T, Garrod O, Crabbe F, Belin P (2014b) Crossmodal adaptation in right posterior superior temporal sulcus during face-voice emotional integration. J Neurosci 34:6813–6821.

Winkler AM, Ridgway GR, Webster MA, Smith SM, Nichols TE (2014) Permutation inference

for the general linear model. Neuroimage 92:381-397.

Wright TM, Pelphrey KA, Allison T, McKeown MJ, McCarthy G (2003) Polysensory

interactions along lateral temporal regions evoked by audiovisual speech. Cereb Cortex

13:1034–1043.

Yovel G, O'Toole AJ (2016) Recognizing people in motion. Trends Cogn Sci 20:383–395.