More accurate transcript assembly via parameter advising

Dan DeBlasio, Kwanho Kim and Carl Kingsford
Computational Biology Department
Carnegie Mellon University
Pittsburgh, PA USA 15213.
{deblasio,carlk}@cs.cmu.edu, kwanhok@andrew.cmu.edu

Abstract

Background: Computational tools used for genomic analyses are becoming increasingly sophisticated and complex. While these applications often provide more accurate results than their predecessors, a new problem is emerging in that these pieces of software have a large number of tunable parameters. Choosing the wrong parameter values for an application may lead to significant results being overlooked or false results being reported.

Results: We take some first steps towards generating a truly automated genomic analysis pipeline by developing a method for automatically choosing input-specific parameter values for reference-based transcript assembly. We extend the parameter advising framework, first developed for multiple sequence alignment, to optimize parameter choices for the `Scallop` transcript assembler. In doing so, we provide the first practical method for finding advisor sets, collections of parameter vectors, for complex applications with large numbers of tunable parameters.

Conclusions: By choosing parameter values for each input, the area under the curve (AUC) when comparing assembled transcripts to a reference transcriptome is increased by 28.9% over using only the default parameter choices on 1595 RNA-Seq samples in the Sequence Read Archive. This approach is general, and when applied to `StringTie` it increases AUC by 13.1% on a set of 65 RNA-Seq experiments from ENCODE. Parameter advisors for both `Scallop` and `StringTie` are available on Github.

1 Introduction

As the field of computational biology has matured, there has been a significant increase in the amount of data that needs to be processed and a corresponding increase in the reliance of users without computational expertise on the highly complicated programs that perform the analyses. At the same time, the number and sophistication of such tools has also increased. While the accuracy of such applications is constantly improving, a new problem has emerged: the sometimes overwhelming number of tunable parameters that each of these sophisticated pieces of software brings with them. Changing an application's parameter settings can have a large impact on the quality of the results produced (see Figure 1). When incorrect or non-ideal parameter choices are used, poorter results may be obtained or false conclusions may be reported.

The default parameter choices that most users rely on for these programs are typically optimized by the algorithm designer to maximize performance on the average case. This can be a problem since the most interesting experiments are often not "average."

Default Parameter Vector

Optimized Parameter Vector

Reference Transcriptome

Figure 1: **Influence of parameter choice on the produced transcriptome.** The 3 transcriptomes are those assembled using `Scallop`'s default parameter vector, an optimized parameter vector, and the reference transcriptome for positions 30231125 to 30260786 on Chromosome 2 in `SRR543291/HISAT`. The red arrows highlight the two transcripts from the reference that are not recovered using the default parameter vector.

Manually tuning the parameter settings of an application often produces more accurate results, but it is very time consuming. The tuning process can be accelerated for users with domain and/or algorithmic knowledge, as these experts can make more informed decisions about the correct direction to proceed when altering parameter values. But tuning the parameter choices to increase accuracy for one input does not imply that the results will be improved for all inputs. This means that, for optimum performance, tuning must be repeated for each new piece of data. In the case of high-throughput genomic analysis, this manual procedure is utterly infeasible. For these applications, without some sort of automatic parameter choice system, the defaults must be used.

To address the automated parameter choice problem for multiple sequence alignment (MSA), DeBlasio and Kececioglu [1] have defined a framework to automatically select the parameter values for an input. This process, called "parameter advising," has been shown to greatly increase accuracy of MSA without sacrificing wall-clock running time in most cases, and it can readily be applied to new domains. A parameter advisor, depicted in Figure 2, has two components: (1) a set of parameter vectors – assignments of a value to each of the tunable parameters for the application, called an "advisor set"; and (2) an assessment criteria – a method to rank the quality of multiple solutions, called an "advisor estimator". The advisor selects the appropriate parameter vector by first running the application on the input using each parameter vector in the set, and selecting the parameter vector that produces the best result according to the accuracy estimator. Parameter advising for a given application is fast in practice. The instantiations of the application being tuned are independent processes that can be executed in parallel. Assuming that the number of processors available is at least the number of parameter vectors in the advisor set, the only additional wall time is the assessment of the results using the accuracy estimator (which can also be performed in parallel) and the comparison of these values, both of which are negligible compared to the running

Figure 2: **The Scallop parameter advisior.** The advisor's input mirrors that of Scallop (an RNA-Seq sample that has been aligned to the reference genome). A set of candidate assemblies is created by running Scallop on each parameter vector in the advisor set. The advisor then returns the assembly with the highest AUC value, obtained by running GFFCompare and GTFCuff.

time of the application in most cases.

Parameter advising is an example of *a posteriori* parameter selection — it examines an application's output to select a parameter setting. In contrast, separate work has been done in other fields on *a priori* selection, where the parameters are chosen in advance by looking at the raw input alone, or a subsample of the input along with its result. This includes work such as SATZilla [2] for choosing from a collection of SAT solvers, ParamILS [3] which finds optimal settings for the CPLEX computational optimization tool, and KmerGenie [4] for finding appropriate k-mer sizes for genomic assembly. *A priori* prediction is necessary in cases when it is not feasible to apply multiple configurations, but more information is available when performing *a posteriori* assessment since the full final solution can be examined.

In this work, we improve the performance of reference-based transcriptome assembly by extending parameter advising. Transcriptome assembly takes an RNA-Seq sample and a reference genome as input and reconstructs the set of transcripts that are present. Common tools for reference-based transcript assembly include Scallop [5], Cufflinks [6], StringTie [7], and TranscComb [8]. Refence-based assemblers first align reads to the reference genome using a tool such as HISAT [9], STAR [10], TopHat [11], or SpliceMap [12]. Using the read splice locations (the positions where a read maps to non-neighboring locations on a genome), the assembler constructs the exons and splice-

junctions of each transcript. The produced transcriptome consists of a combination of transcripts that can be mapped to ones we already know and transcripts that are unique to the sample that was assembled. These transcriptomes are used to perform analyses such as expression quantification [13] and differential expression [14, 15].

Figure 1 shows an example of how much impact using non-optimal parameter vectors can have on a transcriptome assembly. If the default parameters had been used, two transcripts at this location alone would not have been identified; however, both of these transcripts are present in the reference transcriptome and supported by the sequencing reads.

For transcriptome assembly, a natural choice for the estimator is the sensitivity and precision of recovering known transcripts. These measures can be combined in the area under the curve (AUC) metric, which is commonly used to benchmark reference-based transcript assembly tools. AUC measures the area under the receiver operating characteristic (ROC) curve, which plots the sensitivity and precision of the computed transcriptome as the minimum transcript coverage threshold is changed, using the set of assembled transcripts that match with the reference as positives and all others as negatives. The average coverage of a transcript is the average number of reads that are aligned to each position along the transcript's length. As the threshold on this value increases, the induced subset of transcripts that are above this threshold is reduced in size. These subsets each have an associated sensitivity and precision with respect to the reference transcriptome and represent a point in a two-dimensional space. Together these points form the ROC curve. This measure is intuitively somewhat flawed though, since all un-mapped transcripts are considered errors and reduce the AUC measure even if they are not errors introduced by the assembly process. Arguably, these are the transcripts we are most interested in recovering using reference-based transcript assembly.

The `Scallop` transcript assembler has a larger number of tunable parameters than previous applications of parameter advising. Because of the high-dimensionality of the parameter space, the existing methods for finding advisor sets are not viable. However, there are certain properties of the interaction between parameter choices and accuracy that can be exploited for transcript assembly. If the accuracy landscape when adjusting parameters does not contain many non-global local maxima, iterative optimization techniques can be used to find an advising set. We describe the requirements an application domain must meet in order for these optimization techniques to be used, and we show that transcriptome assembly with `Scallop` appears to satisfy these requirements.

Contributions The contributions of this work are threefold: first, we show for the first time that advising sets of parameter vectors in certain domains can be found using methods other than exhaustive enumeration, in this case iterative optimization; second, we take some of the first steps towards producing a fully automated transcript analysis pipeline by automating sample-specific parameter selection; and third, we show that even with its drawbacks AUC is a better measure to use for parameter optimization in reference-based transcript assembly than existing other *de novo* metrics.

We show that by applying the parameter advising framework, we can greatly increase the quality of the transcriptomes produced using the `Scallop` assembly tool. Using this approach, the area under the curve shows a median increased of 8.7% over using only the default parameter vector on a set of 10 RNA-Seq experiments contained in the ENCODE database that are commonly used for benchmarking. In a high-throughput pipeline the median improvement is even larger, 28.9% higher AUC than the default parameter vector on over 1500 samples from the Sequence Read Archive.

We also confirm that this method can increase AUC for other programs by applying it to `StringTie`, another popular reference-based transcript assembler. For a set of 65 examples from the ENCODE database, we are able to increase its AUC by 13.1% over using only the default parameter vectors.

2   Developing a parameter advisor for transcript assembly

Constructing a `Scallop` parameter advisor is expedited because there is a reference transcriptome and thus we can use the readily accepted benchmarking measure of AUC as the "advisor estimator", but finding an advisor set is especially challenging. `Scallop` has 18 tunable parameters compared to approximately 5 for multiple sequence alignment, the previous application of parameter advising. This means the previously developed method of enumerating a parameter vector universe and then using combinatorial optimization to find an advisor set is infeasible. The `Scallop` transcript assembler generates a transcriptome from a set of reads that have been aligned to a reference genome. It first splits the genome into regions of non-overlapping reads, which are called bundles. These bundles can be thought of as genes or groups of overlapping genes. Then, within each bundle a splice graph is constructed based on the split reads that define possible exon boundaries. Paths through the splice graph define potential transcripts, and the final set of transcripts is formed by decomposing the splice graphs into paths while trying to respect as many of the read mappings as possible. The 18 tunable parameters of `Scallop` govern various stages of this process and are: maximum dynamic programming table size (DP), maximum edit distance (ED), maximum intron contamination coverage (ICC), maximum number of exons (NE), minimum bundle gap (BG), minimum exon length (EL), minimum flank length (FL), minimum mapping quality (MQ), minimum number of hits in a bundle (NH), minimum router count (RC), minimum splice boundary hits (SBH), minimum subregion gap (SG), minimum subregion length (SL), minimum subregion overlap (SO), minimum transcript length, base (TLB), minimum transcript length, increase (TLI), uniquely mapped reads only (UM), and whether to the secondary alignment (US).

We calculate the AUC of a transcript assembly by having `Scallop` not filter its output based on minimum transcript coverage (the average number of reads that are aligned to each position along the transcript's length), and then allowing the tools `GFFCompare`[1] and `GTFCuff`[2] to calculate an AUC by thresholding this value. In this work, as opposed to Shao and Kingsford (2017, [5]), we choose to not separately evaluate multi-exon transcripts and single-exon transcripts but rather maximize a combined AUC.

2.1   Analyzing parameter behavior

Iterative optimization strategies such as gradient ascent [16], simulated annealing [17], and coordinate ascent [18, sec. 5.4.3], work by systematically searching high-dimensional spaces based on a specific optimization criteria. For these methods to work well the parameter landscape should be free from a large number of local maxima as well as large discontinuities.

To determine the behavior of the parameters of `Scallop`, we calculate the AUC of the assemblies produced when varying a single parameter's value while keeping the remaining parameters at the

---

[1] https://github.com/gpertea/gffcompare
[2] https://github.com/Kingsford-Group/rnaseqtools

(a)   Single Parameter Behaviour   (b)   Paired Parameter Behaviour

Figure 3: **AUC for various values of the "minimum subregion gap" and "minimum transcript length base" parameters.** The points in the plot show the area under the curve (vertical axis) for the transcriptome produced by changing the value each of the parameters either (a) alone or (b) together leaving all other parameters their default values on SRR534291/`HISAT` from `ENCODE10`.

default. Figure 3a shows the effect of varying the "minimum subregion gap" and "minimum transcript length, base" parameters. Figure 3b shows the relationship between the parameters and AUC when varying both at the same time. Note that throughout this work, we multiply area under the curve values by 10^4 for ease of presentation. AUC is a value in the range $[0, 1]$, but generally for transcript assembly the value is very small, typically < 0.1.

We examined the parameter behavior curves for several experiments from the ENCODE database, and found that the curves for all 16 continuous parameters and all of the pairs tested contained only one visible local maximum. These tests suggest that there may be very few local maxima in the high-dimensional parameter space which means iterative optimization procedures are less likely to get stuck at poor local maxima.

2.2 Finding an advisor set using coordinate ascent

The greedy coordinate-ascent-based procedure that we use here starts at the default parameter vector. One dimension (parameter) at a time, we examine the AUC of the parameter vector with that parameter changed by one step in each direction and update our current vector if we see an improvement. We continue tuning one dimension until no more improvements are made. Our procedure is deterministic meaning we would never take a step that decreases (or maintains) AUC, unlike many implementations of coordinate ascent which include some randomness in decision making. The step size for each dimension has a time-versus-granularity tradeoff: the larger the step size, the less time spent in low AUC regions of the landscape; but when the size is too large, the maximum may be repeatedly stepped over without ever being found. Rather than use a computed step size for every coordinate in each iteration like many implementations of coordinate ascent, we overcome this issue using predetermined but decreasing step sizes, taking inspiration from simulated

Figure 4: **Area under the curve for each step of the coordinate ascent procedure for SRR534291 from `ENCODE10` using all 3 aligners.** Each curve in the plot shows the progress of the coordinate ascent landscape exploration for one of `HISAT`, `STAR`, and `TopHat`. Across the horizontal axis is the number of exploratory steps taken in the search and the vertical axis shows the area under the curve for the current best parameter vector.

annealing. We start with large step sizes in each dimension, and any time we interrogate the whole set of parameters without making any change we decrease all of the step sizes by a factor of $\frac{1}{4}$ and repeat the process. We continue optimizing the parameters in this manner until both: (1) all of the step sizes are small (1 for integer parameters and 0.01 for real numbers) and (2) no more improvements can be made within one step from the current parameter vector. For the tunable parameters in `Scallop` that accept only binary input, we tested both options each time the parameter was explored.

Figure 4 shows the trajectory of three coordinate ascent training sessions. The large increases in AUC in the initial iterations are likely the procedure moving away from the multi-exon optimized parameter vector. As the sessions continue, the increase in AUC becomes smaller both because the procedure is narrowing in on the apparent true maximum and the decreases in step size.

Coordinate ascent will find parameter vectors higher AUC for an input, but it is slow so it is not a viable procedure for finding input-specific parameter choices in practice. Instead, we can

use coordinate ascent to find higher AUC parameter vectors for a set of examples, then use the collection of optimal parameters as the advisor set. Since the advisor sets are computed in advance so as long as the the set of examples we use is diverse, meaning it represents the range of possible inputs, the advisor sets can be reused for any new input.

2.3 Data

We use 3 sets to train and validate parameter advising:

- `ENCODE10` contains a collection of 10 RNA-Seq experiments from the ENCODE database [19] that were used to benchmark `Scallop` and have been extensively used to evaluate transcriptome assembly tools [7, 8]. 30 examples were produced by aligning each sample to the human reference genome (GRCh38) using three tools: `HISAT`, `STAR`, and `TopHat`. (Command line arguments are listed in Supplemental Table 3, Experiment identifiers in Supplemental Table 6.) A subset of these examples was used to find the `Scallop` default parameter vector.

- `ENCODE65` contains a collection of 65 RNA-Seq experiments, also from ENCODE, that were not included in `ENCODE10` and that had preexisting alignments in the database. These alignments are produced using an aligner selected by the group that submitted the sample and are mapped to either GRCh37 or GRCh38. (Experiment identifiers in Supplemental Table 7.)

- `SRA` contains a collection of 1595 RNA-Seq experiments from the Sequence Read Archive [20] that have been filtered for quality. We eliminate any sample that contained very few reads unaligned ($<$ 1GB sequence file) or aligned ($<$ 1GB alignment file). All remaining samples were aligned using `STAR` to GRCh38. (Experiment identifiers in Supplemental Tables 8-18.)

3 Validating the transcript assembly parameter advisor

3.1 Finding a `Scallop` advisor set

The `ENCODE10` dataset is reasonable for training because it is highly diverse and is expected produce parameter vectors that should generalize. It contains samples that are widely accepted as benchmarks and has examples that have been generated using a collection of commonly used aligners. The coordinate ascent procedure described in Section 2.2 was used to find improved parameters for each sample. The parameter vectors found are in Supplemental Table 1. Note that only 15 rather than 18 tunable parameters are shown. While all parameter were considered when optimizing parameter choices, for some the final parameter vectors never included non-default parameter values, namely "maximum dynamic programming table size", "maximum edit distance", and "minimum router count."

Most of the parameters values deviate quite far from each other between samples, meaning there is unlikely to be one parameter choice that works well for all of the training examples. The deviation of the parameter vectors from the default is not surprising given that in this work we are optimizing AUC on all transcripts, rather than only multi-exon transcripts as was done previously. When single-exon transcripts are evaluated in concert with multi-exon transcripts, a new default parameter setting could be recommended for some single parameters, such as in the case of "minimum mapping quality" where almost all samples used a value of 11 rather then the default of 1, and "minimum transcript length increase" where most samples found improvement by selecting

values that are much smaller than the default. In fact, we find that the parameter vector found for SRR545723/`TopHat` had higher AUC for all of the samples in the `ENCODE10` and would be the best vector to use as the default.

In reduced resource environments (e.g., when 31 processors are not available), it may be desirable to run fewer parameter settings to keep the number of parallel processes smaller than the number of available threads. We used the oracle set-finding method described by DeBlasio and Kececioglu [1, 21] to find a subset of parameter vectors that maximizes the average AUC for advising.

Advisor subsets are found using an integer linear program that has two sets of binary variables: one variable for each parameter vector, and one for each example/parameter pair. Where an example/parameter pair is a parameter vector used to assemble an example. Constraints are used to ensure that only one pair for each example is chosen and that the associated parameter setting is also chosen. The objective is then to maximize the sum of the accuracies of the chosen pairs while only selecting a predefined number of parameter vectors. Using the samples in `ENCODE10`, we found advising subsets of 1, 2, 4, and 8 parameter vectors. The advising subset choices are shown in the right most columns of Supplemental Table 1. Note that an advising set of size 1 is equivalent to finding a new default parameter vector since it maximizes the average accuracy across the training examples.

3.1.1   Advising on the training set

Figure 5 shows the AUC for all of the samples from `ENCODE10`. For each example (a sample combined with an aligner) there are two values shown: the AUC of the parameter vector produced as a result of coordinate ascent, and the AUC of the leave-one-out advising parameter vector. For the leave-one-out experiment, advising was limited to the 18 parameter vectors that were learned on examples produced using the 2 aligners and 9 samples that were different from the example being tested. This test is used to show the robustness of the advising set. More detailed results on these tests are shown in Supplemental Table 2.

3.2   Assessing the generality of learned parameter vectors

3.2.1   `ENCODE65`

The `ENCODE65` dataset is used to show that on a large number of samples from a range of aligners (possibly using non-default parameter settings) advising for `Scallop` provides a higher AUC transcriptome. Figure 6 shows the relative increase in AUC, the AUC of the transcript assembly produced by the advised parameter vector normalized by that of the default parameters, for all 65 examples in `ENCODE65`. When the default parameter vector performs well there is a smaller increase in AUC, this is somewhat expected since there is less room for improvement for these samples. Using advising on this highly diverse set of samples increases the AUC of each transcriptome by a median of 31.2%. When using the resource limited sets, the median increase remains 18.2%, 19.0% and 24.4% for sets of 2, 4, and 8 parameter settings respectively. Even with these small sets, there is a large increase in AUC.

Figure 7 shows the frequency with which each of the 31 (the whole set of parameter vectors learned on `ENCODE10`), 8, 4, and 2 parameter vectors provides the maximum AUC when running parameter advising on the `ENCODE65` set. Not all 31 parameter vectors provide the best AUC over the 65

Figure 5: **Increase in AUC for examples in ENCODE10.** Each of the 30 examples is listed on the horizontal axis. Each bar's height is the normalized difference between the default AUC and that of the assembly produced using either coordinate ascent (blue) or leave-one-out (red).

samples, but more parameter settings are maximal across the samples as you increase the size of the advisor set. Only 4 parameter vectors of the set of 8 provide an assembly with the maximum AUC for all of the samples in ENCODE65, as well as only 2 of the 4.

Random Advisor Sets. To confirm that the increase in accuracy is due to our advisor set construction method and not an artifact of having multiple choices of parameter vectors, a collection of random parameter vectors were generated and used for parameter advising. A range was defined for each tunable parameter by examining all of the values that provided an increase in AUC for any example at any stage in coordinate ascent. A random vector was then constructed by selecting parameter values for each parameter uniformly at random in these ranges. In total, 30 such parameter vectors were generated to match the advisor set size developed using coordinate ascent. This randomization procedure was then replicated 100 times to ensure stability of the average.

Figure 8 shows the AUC achieved by parameter advising on Scallop using the the coordinate-ascent-derived advising set versus the AUC of advising using the random advisor sets. The default parameter vector was left out of the all advising sets. Because of this, many of the randomly generated advisor sets (29 of 65) led to a decrease in accuracy relative to the default. On some examples the performance is similar between the two sets, but the average increase in AUC is much higher for the coordinate ascent advisor set (median AUC increase of 31.23 versus 5.59). In all of

Figure 6: **AUC improvement for ENCODE65.** Each point is a single experiment positioned by the AUC of the default Scallop parameters (horizontal axis) and the ratio of the advised AUC over the default (vertical). A value above 1.0 indicates an improvement.

Figure 7: **Frequency of parameter vector use for advising the samples of ENCODE65.** The horizontal axis shows labels of the parameter vectors from Supplemental Table 1 that produced the highest AUC transcriptome for any sample in the dataset. The vertical axis is the fraction of samples that have that parameter vector as the maximum. The four groups of bars show the use in the full set of 30 parameter vectors and the reduced sets of 2, 4, and 8 parameter vectors.

Figure 8: **Comparison to randomly generated advisor sets.** Each point in the chart represents one example from `ENCODE65` positioned by the AUC value of using a randomly generated advisor set (horizontal axis) or the trained advisor set (vertical axis) averaged over 100 random replications. Points above the diagonal line show an improvement of training over random.

the 65 examples, the coordinate ascent sets outperform the random ones.

3.2.2 `SRA`

Our `SRA` dataset gives some insight into the improvement that can be gained in a high-throughput environment. It contains a large number of samples that have all been preprocessed in the same way with respect to the aligner. The advising ratio for the 1595 samples in `SRA` is shown in Figure 9 compared with the area under the curve for the transcriptome produced using the `Scallop` default parameter settings. Because, in general, the samples in `SRA` have a smaller initial area under the curve than those in Figure 6 (AUC values of 241.3 and 325.0 respectively), the median improvement is higher at 28.9%. For several samples in the set the AUC increases by more than a factor of 3. These improvements are also seen for the resource-limited advisor sets where the median improvement is 25.6%, 24.1% and 24.3% with 2, 4, and 8 parameter vectors, respectively. Notice that the increase in AUC actually goes down slightly when increasing the size from 2 to 4. This is likely an artifact of the reduced advisor sets not being subsets of each other. This means that

Figure 9: **AUC improvement the `SRA` assemblies.** Each point is a single experiment positioned by the AUC of the default `Scallop` parameters (horizontal axis) and the ratio of the advised AUC over the default (vertical). A value above 1.0 indicates an improvement. For this test the default was excluded from the advising set, but it can be included in practice to ensure the AUC is never reduced.

Figure 10: **Frequency of parameter vector use for advising the samples of `SRA`.** The horizontal axis shows labels of the parameter vectors from Supplemental Table 1 that produced the highest AUC transcriptome for any sample in the dataset. The vertical axis is the fraction of samples that have that parameter vector as the maximum. The four groups of bars show the use in the full set of 30 parameter vectors and the reduced sets of 2, 4, and 8 parameter vectors.

the parameter vectors and sets may be slightly overfit to the training data. Figure 10 shows the frequency with which each of the 31, 8, 4, and 2 parameter vectors provides the maximum AUC when running parameter advising on the `SRA` set. Because all of the examples in `SRA` were aligned using the same aligner many of the choices are maximal more frequently. Surprisingly, even though all of the examples are aligned using `STAR`, many of the higher-frequency parameter vectors had been optimized for examples that were aligned using `TopHat` (IDs 1–10). Ties, if any existed, would be resolved in alphabetical order of the experiment name then aligner but no ties for the maximum AUC were found in `SRA` or `ENCODE65`.

3.3 Running time

The wall time of running coordinate ascent is much larger than the running time of any single instance of `Scallop`. For the 30 examples from `ENCODE10`, running coordinate ascent for any single example took between about 40 hours and over 22 days.

Figure 11: **AUC improvement the `ENCODE65` assemblies using `StringTie`.** Each point is a single experiment positioned by the AUC of the default `Scallop` parameters (horizontal axis) and the ratio of the advised AUC over the default (vertical). A value above 1.0 indicates an improvement.

Figure 12: **Relative increase in accuracy over default of using various transcript assembly metrics for coordinate ascent.** The bars represent the difference in AUC between the optimal parameter choice for each metric and the defaults, normalized by the default AUC for each of the examples from `ENCODE10`.

Running an advisor should take only as much wall-time as running a single instance of `Scallop`. Running `Scallop` using the default parameter vector for these same samples takes between ∼7 minutes and 1 hour. Even if no parallelization was possible, parameter advising would be able to run in a fraction of the time of running coordinate ascent.

3.4   Advising for `StringTie`

In order to show the generalizability of this method, we also applied it to the `StringTie` transcript assembler. As before, we ran coordinate ascent on the 10 experiments in `ENCODE10`, now using `StringTie`, to select the 30 non-default parameter vectors. Since `StringTie` has only 9 tunable parameters, the coordinate ascent time was much shorter, but the increase in accuracy was still observed. For the 30 coordinate ascent runs, we saw a median increase in AUC of 12.2% on `ENCODE10`. We also saw 10.0% increase in AUC on the similar leave-one-out experiments as those performed above. (`StringTie` parameter vectors and individual `ENCODE10` AUC values are shown in Supplemental Tables 4 and 5 respectively.)

Figure 11 shows the advising ratio for the 65 RNA-Seq samples from `ENCODE65`. For these examples the median gain in AUC is 13.1% over using only the default parameter vectors. For the `StringTie` assembler, samples with lower AUC using the default parameter vectors still generally have higher advising ratios but this correlation is not as strong as with `Scallop`.

3.5   Justification for using AUC as the advising accuracy estimator

Comparison to the reference transcriptome is the commonly used metric to benchmark reference-based assemblers. However, the performance of AUC is theoretically bounded by the completeness of the reference transcriptome. By definition, all transcripts in a sample that do not map to the reference provide a reduction of AUC, even those that represent true novelty. To understand just how much novelty is being lost by using AUC as an optimization metric, we constructed a simulated dataset using the samples in `ENCODE10`. We restricted the "reference" transcriptome to be the collection of transcripts from the reference that map to assembled transcripts seen at any accepted parameter choice in coordinate ascent. We call this the "whole reference" which produces a "whole AUC". Then, using a holdout set to simulate the reasonable situation where we do not know some of the transcripts, we produced a smaller subset of this reference. We call this the "partial reference" and in turn we can optimize the "partial AUC". The transcripts were held out with a probability based on the percentage of accepted assemblies contained them. We expect the resulting partial reference to resemble the actual reference transcriptome in a sense that it contains the majority of frequently encountered transcripts for which there is a strong signal, since they would have a low probability of being removed, while missing some that are rare since they are more likely to be removed.

Figure 12 shows the improvement of the parameter vectors found using coordinate ascent when optimizing whole AUC, partial AUC, and several *de novo* assembly metrics (which do not use the reference transcriptome) compared to the default `Scallop` parameter vector. The *de novo* metrics are `Transrate` [22], "number of reads" mapped to the transcriptome using `Salmon`, and a linear combination of the features from `Transrate`, number of reads, and other novel features combined as a weighted sum (labeled as "linear").

To learn the weights of the weighted sum we trained a linear separator to distinguish transcripts that are mapped to the reference from those that do not, where the labeled transcripts came from a set of examples from `ENCODE10`. We then averaged these transcript-level values to obtain an assembly level value we used for coordinate ascent.

Whole AUC in this scenario is the ground truth since the method for construction guarantees that the selected reference contains all of the possible transcripts in the experiment and nothing else. The transcript assemblies constructed using the parameter vectors optimized using partial AUC as the objective recover more of the ground truth than those constructed using the default parameter vector. For the other metrics, we see that the transcript assemblies constructed with the parameter vectors found though optimization often showed a decrease in accuracy with respect to the transcripts constructed using the default parameter vector. These metrics are being lead astray by not incorporating the knowledge contained in the reference transcriptome.

Note that an alternate method to test how much is lost by optimizing AUC as opposed to other metrics would be to use a simulated RNA-seq sample where we know all of the transcripts that are present then creating whole and partial reference transcriptomes using these transcripts. What would be missing from the simulation is the extraneous sequencing reads included in sequencing data that comes from amplification, sequencing, or assembly errors. Therefore, using tests based on non-simulated samples are more realistic.

4   Conclusions

Our results show that sample-specific parameter vectors are important for developing any genomic pipeline that includes transcriptome assembly as a step. In this work, we begin to answer the question of how to produce transcriptome assemblies effectively for any input without sacrificing quality or expanding manpower. This is done using a combination of parameter tuning though exploration using coordinate ascent and the established method of parameter advising. Two key points that made this merger viable and distinguish transcriptome assembly from other domains are: (1) because the parameter landscape likely has few local maxima, coordinate ascent rather than exhaustive enumeration can be used to find advisor sets, and (2) that a small, but representative, number of training examples is sufficient to provide a large increase in AUC over the default parameter setting.

The coordinate ascent procedure is a very useful means for finding parameter settings that increase the AUC of predicted transcriptomes. The best results can generally be achieved by simply following this procedure for each new input, although at a high running time. Our implementation of coordinate ascent does not allow steps to be taken in multiple directions at once. It is thus difficult to efficiently parallelize this process. In other words, coordinate ascent finds more accurate parameter vectors at the cost of large computational time. Instead, we have developed a method, which can be reapplied to any domain that has the same parameter behavior we observed, to find an advising set that is as diverse as the training examples used.

One drawback of using a single example to find each parameter vector in the set is that coordinate ascent is likely to overfit to the training examples. We have shown that even with this potential issue, we are able to improve the quality of the transcripts produced according to the AUC measure.

All of the results that we have shown assume that all transcripts in a sequencing sample can be assembled with a single choice of parameter vector. While this is an assumption made by most

transcript assemblers, it may not be true in practice. One extension of this work is to provide *transcript-level* parameter choices to help improve the assembly quality. This would require the adaptation of AUC, or some other metric that could work well for parameter optimization, to provide transcript-level assessment.

The method we have described automates the task of parameter selection for `Scallop` and `StringTie`, and improves the quality of produced transcriptomes according to the area under the curve measure comparing the output to the reference transcriptome database. As we have shown, this measure works better at the task of parameter optimization than the existing *de novo* measures. But our results also show that there is room to improve this measure since in Figure 12 partial AUC is never able to recover all of the "novelty" present in the sample. The unknown transcripts can sometimes be the most interesting, and this measure of accuracy penalizes novelty by definition, and may not recover it if its it highly divergent from those we already know. In order for the transcript assemblies constructed using the parameter vectors found by optimizing the *de novo* metrics to be optimal, there would be a lot of false positives found when constructing a transcript assembly using the default parameter vector. This seems unlikely even in light of the current debate about the reference transcriptome [23, 24]. In the future, it would be ideal to find some new measure that is some hybrid between AUC and *de novo* assessment that could both use current knowledge but still be able to detect novel transcripts. When this is available, it can replace AUC as the measure for constructing and using advising for transcript assembly.

Acknowledgements

The authors would like to thank the members of the Kingsford Group for their helpful comments through out this project, in particular Mingfu Shao, Jonathan King, Heewook Lee, and Guillaume Marçais.

Funding

This research is funded in part by the Gordon and Betty Moore Foundation's Data-Driven Discovery Initiative through Grant GBMF4554 to C.K., by the US National Institutes of Health (R01HG007104 and R01GM122935). This work was partially funded by The Shurl and Kay Curci Foundation and by the generosity of Eric and Wendy Schmidt by recommendation of the Schmidt Futures program.

References

[1] Dan DeBlasio and John Kececioglu. *Parameter advising for multiple sequence alignment*, volume 26 of *Computational Biology series*. Springer International Publishing, Cham, Switzerland, 2017.

[2] Lin Xu, Frank Hutter, Holger H Hoos, and Kevin Leyton-Brown. `SATzilla`: portfolio-based algorithm selection for SAT. *J. Artif. Intel. Res.*, 32:565–606, 2008.

[3] Frank Hutter, Holger H. Hoos, Kevin Leyton-Brown, and Thomas Stützle. `ParamILS`: an automatic algorithm configuration framework. *J. Artif. Intel. Res.*, 36(1):267–306, September 2009.

[4] Rayan Chikhi and Paul Medvedev. Informed and automated k-mer size selection for genome assembly. *Bioinformatics*, 30(1):31–37, June 2013.

[5] Mingfu Shao and Carl Kingsford. Accurate assembly of transcripts through phase-preserving graph decomposition. *Nature Biotechnology*, 35:1167–1169, 2017.

[6] C. Trapnell, B.A. Williams, G. Pertea, A. Mortazavi, G. Kwan, M.J. Van Baren, S.L. Salzberg, B.J. Wold, and L. Pachter. Transcript assembly and quantification by RNA-Seq reveals unannotated transcripts and isoform switching during cell differentiation. *Natue Biotechnology*, 28(5):511–515, 2010.

[7] Mihaela Pertea, Geo M Pertea, Corina M Antonescu, Tsung-Cheng Chang, Joshua T Mendell, and Steven L Salzberg. `StringTie` enables improved reconstruction of a transcriptome from RNA-Seq reads. *Nature Biotechnology*, 33:290–295, February 2015.

[8] Juntao Liu, Ting Yu, Tao Jiang, and Guojun Li. `TransComb`: genome-guided transcriptome assembly via combing junctions in splicing graphs. *Genome Biology*, 17(1):213, October 2016.

[9] Daehwan Kim, Ben Langmead, and Steven L Salzberg. `HISAT`: a fast spliced aligner with low memory requirements. *Nature Methods*, 12:357–360, March 2015.

[10] Alexander Dobin, Carrie A. Davis, Felix Schlesinger, Jorg Drenkow, Chris Zaleski, Sonali Jha, Philippe Batut, Mark Chaisson, and Thomas R. Gingeras. `STAR`: ultrafast universal RNA-Seq aligner. *Bioinformatics*, 29(1):15–21, 2013.

[11] Daehwan Kim, Geo Pertea, Cole Trapnell, Harold Pimentel, Ryan Kelley, and Steven L. Salzberg. `TopHat2`: accurate alignment of transcriptomes in the presence of insertions, deletions and gene fusions. *Genome Biology*, 14(4):R36, April 2013.

[12] K.F. Au, H. Jiang, L. Lin, Y. Xing, and W.H. Wong. Detection of splice junctions from paired-end RNA-Seq data by `splicemap`. *Nucleic Acids Research*, 38(14):4570–4578, 2010.

[13] Rob Patro, Geet Duggal, Michael I Love, Rafael A Irizarry, and Carl Kingsford. `Salmon` provides fast and bias-aware quantification of transcript expression. *Nature Methods*, 14(4):417–419, 2017.

[14] Michael I Love, Wolfgang Huber, and Simon Anders. Moderated estimation of fold change and dispersion for RNA-Seq data with `deseq2`. *Genome Biology*, 15(12):550, 2014.

[15] Alyssa C Frazee, Geo Pertea, Andrew E Jaffe, Ben Langmead, Steven L Salzberg, and Jeffrey T Leek. Flexible isoform-level differential expression analysis with ballgown. *Nature Biotechnology*, 33:243—246, March 2015.

[16] Augustin Cauchy. Méthode générale pour la résolution des systèmes d'équations simultanées. *Comptes Rendus Hebdomadaire des Séances de l'Academie des Sciences*, 25(536):536–538, 1847.

[17] S. Kirkpatrick, C. D. Gelatt, and M. P. Vecchi. Optimization by simulated annealing. *Science*, 220(4598):671–680, May 1983.

[18] Willard I. Zangwill. *Nonlinear Programming: A Unified Approach*. Prentice-Hall International, Englewood Cliffs, N.J, 1969.

[19] The ENCODE Project Consortium. An integrated encyclopedia of DNA elements in the human genome. *Nature*, 489:57–74, August 2012.

[20] Rasko Leinonen, Hideaki Sugawara, and Shumway, M. on behalf of the International Nucleotide Sequence Database Collaboration. The sequence read archive. *Nucleic Acids Research*, 39:D19–D21, November 2010.

[21] Dan DeBlasio and John Kececioglu. Learning parameter-advising sets for multiple sequence alignment. *IEEE/ACM Transactions on Computational Biology and Bioinformatics*, 14(5):1028–1041, 2017.

[22] Richard Smith-Unna, Chris Boursnell, Rob Patro, Julian M Hibberd, and Steven Kelly. `TransRate`: reference-free quality assessment of de novo transcriptome assemblies. *Genome Research*, 26(8):1134–1144, August 2016.

[23] Mihaela Pertea, Alaina Shumate, Geo Pertea, Ales Varabyou, Florian P Breitwieser, Yu-Chi Chang, Anil K Madugundu, Akhilesh Pandey, and Steven L Salzberg. CHESS: a new human gene catalog curated from thousands of large-scale RNA sequencing experiments reveals extensive transcriptional noise. *Genome Biology*, 19(1):208, November 2018.

[24] Irwin Jungreis, Michael L. Tress, Jonathan Mudge, Cristina Sisu, Toby Hunt, Rory Johnson, Barbara Uszczynska-Ratajczak, Julien Lagarde, James Wright, Paul Muir, Mark Gerstein, Roderic Guigo, Manolis Kellis, Adam Frankish, Paul Flicek, and The GENCODE Consortium. Nearly all new protein-coding predictions in the CHESS database are not protein-coding. *bioRxiv*, 360602, 2018.