Bagging Improves Reproducibility of Functional Parcellation of the Human Brain

Aki Nikolaidis (1), Anibal Solon Heinsfeld (1), Ting Xu (1), Pierre Bellec (2), Joshua Vogelstein (3), Michael Milham (1).

1- The Child Mind Institute, 101 East 56th Street. New York, NY 10022
2- John's Hopkins University 3400 N. Charles St Baltimore, MD 21218
3- University of Montreal, PO Box 6128 Downtown STN Montreal QC H3C 3J7 CANADA

Abstract:
Increasing the reproducibility of neuroimaging measurement addresses a central impediment to the clinical impact of human neuroscience. Recent efforts demonstrating variance in functional brain organization within and between individuals shows a need for improving reproducibility of functional parcellations without long scan times. We apply bootstrap aggregation, or bagging, to the problem of improving reproducibility in functional parcellation. We use two large datasets to demonstrate that compared to a standard clustering framework, bagging improves the reproducibility and test-retest reliability of both cortical and subcortical functional parcellations across a range of sites, scanners, samples, scan lengths, and clustering parameters. With as little as six minutes of scan time bagging creates more reproducible parcellations than standard approaches with twice as much data. This suggests bagging may be a key method for improving functional parcellation and bringing functional neuroimaging-based measurement closer to clinical impact.

Keywords: reproducibility, bagging, parcellation, cluster ensembles, reliability, discriminability, biomarkers, striatum, thalamus, subcortical, basal ganglia, fMRI, bootstrap

1. Introduction

Reproducibility is a prerequisite for building solid domain knowledge in the neurosciences, and recent efforts have focused on addressing problems that lead to lack of reproducibility (Millman, Brett, Barnowski, & Poline, 2018; Nichols et al., 2017; Zuo et al., 2014; Zuo, Biswal, & Poldrack, 2019). Given that functional parcellation remains a central goal for neuroscience, finding methods to enhance reproducibility of functional parcellation is important for improving robustness of findings. The past decade has yielded a high degree of success in the identification of large-scale functional networks that are highly reproducible across studies and laboratories, and can be measured at the individual level with moderate to high test-retest reliability (Arslan et al., 2018; Buckner, Krienen, Castellanos, Diaz, & Yeo, 2011; Noble et al., 2017; Yang et al., 2012; Yeo et al., 2011; X. N. Zuo et al., 2010). In contrast, efforts to delineate functionally-defined areal parcels have yielded more variable results across studies, with few focusing on the individual level (Glasser et al., 2016; Xu et al., 2016). Among those that have attempted to quantify either the reproducibility or reliability of parcellation results, several have pointed to the need for optimization of methodologies. Critically, the minimum data requirements (25+ minutes) needed to achieve desirable levels of reliability appear to supercede most clinical and cognitive neuroscience datasets already collected or currently underway (Laumann et al., 2015; Xu et al., 2016; Zuo, Xu, & Milham, 2019). As such, there is an increasing need for methods that can optimize the value of resting state acquisitions with insufficient data.

Here, we draw upon advances in the machine learning literature, bagging and ensemble clustering in particular, to assess whether we can bring down the minimum data needed to achieve reproducible and reliable functional parcellations. The motivation behind bagging, a resampling technique that aggregates bootstrap samples (Breiman, 1996), is to reduce variability in the estimation process through averaging (Dudoit & Fridlyand, 2003). While originally designed for prediction, bagging has more recently become an important technique for ensemble clustering

(Fischer & Buhmann, 2003; Hong, Kwong, Wang, & Ren, 2009; Jia, Xiao, Liu, & Jiao, 2011; Li &

Ding, 2008; Zhou, 2012). The essential advantage of ensemble clustering derives from the added

value of combining multiple cluster assignments into a single clustering (Strehl & Ghosh, 2002).

In other words, the aggregation of cluster solutions themselves become the features for ensemble

clustering. Numerous studies have found that the instability and sensitivity inherent to the cluster

optimization procedure are significantly attenuated by cluster ensembles generated through

bagging (Dudoit & Fridlyand, 2003; Hoyos-Idrobo, Schwartz, Varoquaux, & Thirion, 2015; Jia et

al., 2011; Li & Ding, 2008; Strehl & Ghosh, 2002; Zhou, 2012), making this a promising area of

research in machine learning.

Here, we examine the impact of bagging on the reproducibility and reliability of

functionally-defined cortical and subcortical parcellations generated using resting state fMRI data.

We leverage and extend the Bootstrap Analysis of Stable Clusters (BASC) framework. BASC

applies multi-level bagging to create group and individual-level functional parcellations. We

extend this framework to leverage the power of nilearn (https://nilearn.github.io/), Scikit learn

(Pedregosa et al., 2011), and Nipype (Gorgolewski et al., 2011) by building an open source python

package   for   BASC,   PyBASC   (Nikolaidis   et   al.,   2019);   GitHub:

https://github.com/AkiNikolaidis/PyBASC;   PyPI: https://pypi.org/project/PyBASC/)   Though

introduced to the imaging literature nearly a decade ago (Bellec, Rosa-neto, Lyttelton, Benali, &

Evans, 2010), the full merits of bagging are yet to be tested or appreciated in functional

parcellation.

Our strategy for establishing and assessing reproducibility is motivated by the COBIDAS

report (Nichols et al., 2017) and broader outlines for the establishment of reproducibility in

metrology and biomedical science (JCGM, 2008). These efforts have highlighted a range of

challenges in reproducibility the field faces as we aim for more robust estimates of brain

organization and biomarker discovery (Table 2; (Zuo, Biswal, et al., 2019; Zuo, Xu, et al., 2019).

In brief, we focus on creating functional parcels that improve 1-Between Sample Reproducibility:

similarity in group-level parcellations obtained between independent samples; 2-Between

Session Reproducibility: similarity of group and individual level parcellations obtained in the same

sample at different time points; 3-Reliability: consistency of differences among individuals on

repeat assessments at distinct time points (See Methods 4.5-4.6 for more detailed definitions of

these terms).

Keeping in line with extensive efforts at both cortical (Bellec et al., 2010; Craddock, James,

Holtzheimer, Hu, & Mayberg, 2012; Kelly et al., 2009; Kelly et al., 2012; Margulies et al., 2007)

and subcortical parcellation (Barnes et al., 2010; Choi, Yeo, & Buckner, 2012; Garcia-Garcia et

al., 2017; Janssen, Jylänki, Kessels, & van Gerven, 2015), we perform functional parcellation at

multiple resolutions in both cortex (k = 7, 20, 197, 444) and subcortex (k = 10, 18) to assess the

impact of bagging on reproducibility and reliability of these parcellations. While several cortical

parcellations are well established (Glasser et al., 2016; Yeo et al., 2011), subcortex is an area

where parcellations are less well-studied (Choi et al., 2012; Janssen et al., 2015). Subcortical

regions are also in need of methods to improve reproducibility and reliability given that they show

connectivity with notably lower reliability than the rest of the brain (Noble et al., 2017; O'Connor

et al., 2017).

Functional parcellations often are created with strong spatial constraints to create more

homogenous parcel shapes with smoother parcel boundaries (Craddock et al., 2012; Schaefer et

al., 2018; Xu et al 2016). Such constraints can be considered a version of spatial regularization

that enhances the generalizability of resulting parcellations. To provide the best test of the impact

of bagging on parcellation reproducibility we use minimal spatial constraints in the current

approach, enabling parcels that are discontinuous and even bilaterally homologous. Such an

approach yields parcels with noisier boundaries than would be the case with stronger spatial

constraints, such as Craddock et al. 2012, but our approach a allows the parcellation a better fit

to a given sample and provides a stricted and more direct test of the impact of bagging.

The present study leverages openly available datasets that are well suited for the

establishment of minimum data requirements for reproducibility (Table 1). We use the Hangzhou

Normal University (HNU1) test retest dataset (Zuo et al., 2014), which is comprised of 30

participants each scanned 10 times for 10 minutes over the course of 30 days. We also use the

Genomics Superstruct Project (GSP) dataset (Holmes et al., 2015), from which we select a subset

of 300 participants with two 6 minute resting state scans, which we age and sex matched to the

HNU1 dataset. Given the extensive computational burden of the current set of analysis, we run a

full spectrum of parameters in the subcortical parcellation, and an extensive, but reduced set on

the cortical parcellation. **We demonstrate that compared to a standard clustering framework,**

bagging improves the reproducibility and reliability of both cortical and subcortical

functional parcellations across a range of sites, scanners, samples, scan lengths, and

clustering parameters. These results suggest that bagging may be an important

component for achieving more robust parcellations in functional neuroimaging.

131
Figure 1- Bagging Improves Group Level Within Study/Between Sample Subcortical
Reproducibility. Comparing the parcellations from 10 groups of 30 participants from the GSP
sample to one another. The dotted red line shows the highest mean reproducibility of the standard
parcellation approach. A-B Spatial correlation between mean group adjacency matrix of 10 GSP
groups with 10 and 18 clusters. C-D Adjusted Rand Index between cluster labels of 10 GSP
groups with 10 and 18 clusters.
138

141   <u>Figure 2- Bagging Improves Between Study/Between Sample Cortical Reproducibility</u>. We
142   compared a reference parcellation created from the 12 minute combined scan from 300
143   individuals from the GSP to 10 repeated parcellations of 10 minutes of HNU1 data. A) Spatial
144   correlation between the group mean adjacency matrix for the GSP and HNU1 parcellations. B)
145   Adjusted Rand Index between the cluster labels for the GSP and HNU1 parcellations.

Bootstrap Aggregates

<u>Figure 3- Bagging Improves Between Sample Subcortical Reproducibility.</u> Bagging improves the
reproducibility of subcortical brain parcellation between the GSP and HNU1 datasets, though
results more mixed than the cortical results. We compared a reference parcellation created from
the 12 minute combined scan from 300 individuals from the GSP to 10 repeated parcellations of
10 minutes of HNU1 data. The dotted red line shows the highest mean reproducibility of the
standard parcellation approach. A) Spatial correlation between the group mean adjacency matrix
for the GSP and HNU1 parcellations. B) Adjusted Rand Index between the cluster labels for the
GSP and HNU1 parcellations.

166
167
168
Figure 4 - Visualization of Between Study Cortical Parcellations. We show the similarity of the
HNU1 parcellation to the GSP reference parcellation with 20 clusters as shown in Figure 2.
Notably, both the group and individual level parcellations with 400 bootstraps are closer to the
GSP reference parcellation than either of the standard parcellations. A) Group-level parcellation
with standard approach, B) and bootstrapping. C) GSP Reference parcellation. D) Individual-level
parcellation with Bootstrapping, E) and standard approach.

175
176

Figure 5 - Visualization of Between Study Subcortical Parcellations. We show the similarity of the HNU1 parcellation to the subcortical GSP reference parcellation with 10 clusters as shown in Figure 3. Both the group and individual level bootstrapped parcellations are notably more similar to the GSP reference than either of the standard parcellation counterparts. A) Group-level parcellation with standard approach, B) and bootstrapping. C) GSP Reference parcellation. D) Individual-level parcellation with Bootstrapping, E) and standard approach.

2 Results

2.1 Between Sample Reproducibility

Improving between sample reproducibility is key for creating generalizable scientific discovery. We assess two different levels of between sample reproducibility here: within study and between study, and we hypothesized that bagging should have a beneficial impact on both levels. As a first step, we investigated the effect of bagging on the within study/between sample reproducibility of our subcortical parcellations (Figure 1). We split the 300 GSP participants into 10 groups of 30, and computed the correlation of the group mean adjacency matrices (Figure 1 A, B), and the ARI of their cluster labels between groups (Figure 1 C, D). We found that while increasing the time of the scan from 6 to 12 minutes significantly improved reproducibility when measured by both correlation and ARI (K = 10; Correlation: Kruskal-Wallis chi-squared = 58.517, df = 1, p-value < 0.0001; ARI: Kruskal-Wallis chi-squared = 10.788, df = 1, p-value < 0.005), we found that the impact of bagging improved reproducibility more than increasing the scan length (K = 10; Correlation: Kruskal-Wallis chi-squared = 401.26, df = 1, p-value < 0.0001; ARI: Kruskal-Wallis chi-squared = 278.9, df = 1, p-value < 0.0001), indicating that the 6 minute scans could become more reproducible than scans twice as long with the use of bagging. We also found that bagging significantly decreased the variance in the reproducibility estimates for both 6 minute and 12 minute scans, but had a greater impact on the 12 minute scans (6 min ARI variance 0 vs 400 bootstraps: F = 0.716, num df = 267, denom df = 267, p-value < 0.01; 12 min ARI variance 400 vs 0 bootstraps F = 1.6712, num df = 89, denom df = 89, p-value < 0.05).

As a further test of generalizability we tested between study/between sample reproducibility of both cortical parcellation between the GSP and HNU1 studies (Figure 2; Figure 4). These studies differ on many criteria including scanner type and population, while the GSP data was collected in the USA with Siemens 3T Magnetom Tim Trio scanners, the HNU1 data was collected

in China with a GE 3T scanner. We hypothesized that bagging should not only improve the

reproducibility of the parcellations, but also that it may have an impact on the consistency of the

replication parcellations as well. We conducted a range of tests to assess these concepts. First,

using the 300 individuals from the GSP study to create a reference cortical parcellation, we

assessed the correlation of the group mean adjacency matrices (Figure 2 A), and the adjusted

rand index (ARI) of the group cluster labels (Figure 2 B). We demonstrated that cortical

parcellations were more reproducible between studies using bagging; for example, for K = 444,

bagging improves ARI (Kruskal-Wallis test comparing 400 vs 0 bootstraps: chi-squared = 14.30;

p < 0.0005). We also found that bagging improved the consistency of reproducibility, meaning

that across runs bagging produced cluster solutions whose varied less between one another (Test

of unequal variance of ARI 400 vs 0 bootstraps: F = 94.8, p < 0.0001).

Third, we found that bagging had a significant impact on the between study/between

sample reproducibility of subcortical parcellation, comparing the GSP reference to the HNU1

dataset (Figure 3; Figure 5). Both correlation and ARI of the parcellations improves with scan time

from 10 to 50 minutes as expected. However, we expected that bagging would improve the

parcellation labels to improve equally for both the 10 and 50 minute replication samples. What we

found instead, is that while both improved significantly from 0 to 400 bootstraps, the 10 minute

HNU1 dataset improved much more than the 50 minute (K = 10, 10 minute: t = -13.087, df =

21.389, p-value < 0.0001; 50 minute: t = -3.2407, df = 21.75, p-value < 0.005). When visualized

(Figure 5), we see this difference is largely due to the fact that both the GSP reference and the

10 minute HNU1 scans split the bilateral caudate into two clusters, whereas the 50 minute HNU1

parcellation did not. In fact, the 50 minute HNU1 replication and reference data yielded a

seemingly better quality parcellation overall, with less variance on the edges between parcels,

and more homotopic similarity, which can be expected given homotopic connectivity is known to

be especially high (Zuo et al., 2010). We also visualized the voxelwise differences in parcellation

labels on average over all HNU bootstrapped conditions and found most differences could be

found in the boundary regions between parcels (See Supplementary Figure 1). Of note here, is

that the clusters created have minimal spatial constraints applied to them, implying that neither

the cluster solutions themselves, nor the improvement in reproducibility come from the clusters

being forced into a similar spatially or anatomically constrained configuration. In fact we see many

clusters in the HNU1 50 minute Reference and Replication solution that are anatomically distinct

but functionally united bilateral homologues (ie the left and right putamen cluster together, the left

and right caudate cluster together, etc).

<u>Figure 6- Bagging Improves Within Sample/Between Scan Subcortical Reproducibility.</u> We split
the 300 participants of the GSP dataset into 10 groups of 30, and compare the parcellations of
their first and second functional scan to one another. The dotted red line shows the highest mean
reproducibility of the standard parcellation approach. A-B show the improvement in bagged
parcellations measured by spatial correlation of the group mean adjacency matrix for 10 and 18
clusters respectively. C-D show the improvement in bagged parcellations measured by the
adjusted Rand index of the cluster labels for 10 and 18 clusters respectively.

Figure 7- Bagging Improves Between Session Cortical Parcellation. We compared the HNU1
reference to the HNU1 replication cortical parcellation. A) Spatial correlation between the group
mean adjacency matrix for the reference and replication parcellations. B) Adjusted Rand Index
between the cluster labels for the reference and replication parcellations.

Figure 8-Bagging Improves Between Session Reproducibility of Subcortical Parcellations. We
compared the HNU1 reference to the HNU1 replication subcortical parcellations across different
lengths of time. The dotted red line shows the highest mean reproducibility of the standard
parcellation approach. A) Spatial correlation between the group mean adjacency matrix for the
reference and replication parcellations. B) Adjusted Rand Index between the cluster labels for the
reference and replication parcellations.

Figure 9- Group Bagging Alone Improves Between Session Reproducibility. We compare the subcortical parcellations of the 50 minute replication and reference datasets from HNU1. The dotted red line shows the highest mean reproducibility of the standard parcellation approach. A & B show the improvement in the spatial correlation of the group-level mean adjacency matrix for K = 10 and K = 18, while C & D show the improvement in the adjusted rand index of the group cluster labels for K = 10 and K = 18.

Figure 10 - Visualization of Between Session Cortical Parcellations. We show the similarity of the HNU1 reference parcellation to the subcortical HNU1 replication parcellation with 20 clusters as shown in Figure 7. Both the group and individual level bootstrapped parcellations are notably more similar to the HNU1 reference than either of the standard parcellation counterparts. We see notably more evidence for large-scale network similarities between the HNU1 reference and the bootstrapped parcellations at both the individual and group level, though the individual level is less obvious. A) Group-level parcellation with standard approach, B) and bootstrapping. C) HNU1 Reference parcellation. D) Individual-level parcellation with Bootstrapping, E) and standard approach.

311
312
<u>Figure 11 - Visualization of Between Session Subcortical Parcellations.</u> We show the similarity of
the HNU1 reference parcellation to the subcortical HNU1 replication parcellation with 10 clusters,
as shown in Figure 8. Both the group and individual level bootstrapped parcellations are notably
more similar to the HNU1 reference than either of the standard parcellation counterparts. Group-
level parcellation with standard approach (A), and bootstrapping (B). HNU1 Reference
parcellation (C). Individual-level parcellation with Bootstrapping (D), and standard approach (E).

2.2 Between Session and Between Scan Reproducibility

Whereas creating parcellations with high between sample reproducibility is key for generalizing

scientific discovery, creating parcellations with higher between session and between scan

reproducibility is key for decreasing uncertainty in measuring change over time. We tested

between scan reproducibility using the subcortical parcellations of the GSP dataset. We tested

between session reproducibility using both subcortical and cortical parcellations of the HNU1

dataset.

First we found that our subcortical parcellations of the GSP dataset, where we compared

the effect of bagging on between scan reproducibility of 10 separate groups of 30 participants,

had higher between scan reproducibility with bagging with as little as 6 minutes of data (Figure

6). This suggests that long scan times are not required for bagging to have a significantly

beneficial impact on a parcellation's between scan reproducibility of the group mean adjacency

matrix and cluster labels (K = 10; Correlation: Kruskal-Wallis chi-squared = 14.286, df = 1, p-value

< 0.0005; ARI: Kruskal-Wallis chi-squared = 10.566, df = 1, p-value < 0.005).

We also found that our cortical parcellations had higher between session reproducibility

with bagging than without in the HNU1 dataset (Figure 7; Figure 10). Comparing the K = 444

parcellation, we see significant improvements in both between session reproducibility of group

mean adjacency matrices (t = -57.86, df = 9.2157, p-value = < 0.0001), and group cluster labels

(t = -16.353, df = 9.1687, p-value < 0.0001). If parcellations have higher between session

reproducibility on average, but have high variance across repeated parcellations we might not

have a good grasp on the extent to which a particular parcellation will match across time.

Therefore, it's also important for the variance in the between session reproducibility of our

parcellations to decrease. We found that bagging also significantly decreases the variance in

between session reproducibility of the group mean adjacency matrix (F = 83.456, num df = 9,

denom df = 9, p-value < 0.0001), suggesting that the bagged parcellations are not only more

reproducible, but that this reproducibility is more stable as well.

Finally, we tested the effect of bagging on the between session reproducibility of

subcortical parcellations in the HNU1 dataset (Figure 8; Figure 11). We found that scan length

had a highly significant impact on the between session reproducibility of parcellations. For

instance, comparing 5 and 50 minute group mean adjacency matrix correlation and cluster label

ARI with 0 bootstraps (K = 10; Correlation: Kruskal-Wallis chi-squared = 14.137, df = 1, p-value

< 0.0005; ARI: Kruskal-Wallis chi-squared = 12.176, df = 1, p-value < 0.0005), and with 400

bootstraps (K = 10; Correlation: Kruskal-Wallis chi-squared = 29.268, df = 1, p-value < 0.0001; ARI: Kruskal-Wallis chi-squared = 29.271, df = 1, p-value < 0.0001). Notably, the impact of time was enhanced in the bagging condition, suggesting bagging and scan time can work synergistically to provide parcellations with high between session reproducibility. We also found that while between-session reproducibility was improved with bagging, these reproducibility estimates were not improved as was the case with longer datasets (K = 10; Correlation: F = 0.5374, num df = 9, denom df = 9, p-value > 0.05; ARI: F = 0.22301, num df = 9, denom df = 9, p-value < 0.05). We also visualized the voxelwise differences in parcellation labels on average over all HNU bootstrapped conditions and found most differences could be found in the boundary regions between parcels, along a dorsal-anterior ventral-posterior gradient (See Supplementary Figure 2), supporting the existence of small scale gradients in thalamic functional organization (Lambert, Simon, Colman, & Barrick, 2017).

We also see that the improvement in between session reproducibility from bagging is significantly greater than increasing scan length. For example, for the 0 bootstrap condition, increasing the scan time from 20 minutes to 50 minutes does not yield a significant improvement in between session reproducibility of group mean adjacency matrix correlation or ARI (K=10; Correlation: Kruskal-Wallis chi-squared = 2.9041, df = 1, p-value >0.05; ARI: Kruskal-Wallis chi-squared = 0.79683, df = 1, p-value > 0.05), but increasing the bagging from 0 to 400 has a significant effect on the between session reproducibility of the 20 minute data (K=10; Correlation: Kruskal-Wallis chi-squared = 29.268, df = 1, p-value < 0.0001; ARI: Kruskal-Wallis chi-squared = 17.579, df = 1, p-value < 0.0001). This demonstrates that bagging can improve reproducibility even more than doubling scan time, replicating our previous findings with the between-sample reproducibility in the GSP dataset. We also found that bagging had a significant impact on reducing the variance in between session reproducibility across multiple parcellations, replicating our results with the cortical parcellation (20 Minutes; K = 10; Correlation: F = 311.14, num df =

19, denom df = 19, p-value < 0.0001; ARI: F = 9.7003, num df = 19, denom df = 19, p-value <

0.0001). While the cortical parcellation demonstrated that only 10 minutes of data was needed for

bagging to improve between session reproducibility in the HNU1 data, with the subcortical

parcellation we saw that bagging did not improve the reproducibility for less than 20 minutes of

data. This may be due to random elements of sampling those first 3, 5, 10, or 15 minute portions

of the HNU1 dataset, or differences in the parcellation favored by lower amounts of data compared

to higher amounts, as we saw in comparing the HNU1 50 minute parcellation to the GSP 12

minute reference parcellation in section 2.1.

Importantly, we also find that even bagging at the group level alone is enough to improve

the between session reproducibility of the functional parcellations (Figure 9). This shows that

individual level parcellations that are not bagging enhanced can be bagged to improve the group-

level representation. This finding is important for other multi-level cluster estimation problems,

such as diffusion weighted parcellation, which may benefit from the addition of group-level

bagging (Glasser et al., 2016; Klein et al., 2007; Mars et al., 2011). Finally, we see that bagging

at the individual level alone also improves individual between session reproducibility. This is key

for many approaches aiming to improve individual-level parcellation (Gordon et al., 2017;

Laumann et al., 2015; Xu et al., 2016).

<u>Figure 12 - Bagging Improves Univariate Subcortical ICC.</u> A,B,C show the top 50%, 75%, and
95% ICC values for the individual-level mean adjacency matrices in the 10 GSP groups. D and E
show the mean squared error within individuals and between individuals respectively. We see
that bagging improves ICC. It also has a dramatic impact on both within subject variance (MSE)
and between subject variance (MSR), with samples with the lowest drop in MSR showing the
greatest pickup in ICC.
404

409 <u>Figure 13-Bagging Improves Multivariate Reliability in Subcortical Parcellation.</u> Figure A and B
410 show the discriminability results for the subcortical parcellation for K = 10 and K = 18 respectively.
411 The dashed red line shows the top mean performance for the non-bagged parcellations. Bagging
412 leads to improved discriminability for longer scan times.

Figure 14 - Bagging Increases Group-Individual Parcellation Similarity. Overall this figure shows
how bagging improves coherence between individual and group parcellations. The dotted red line
shows the highest mean coherence of the standard parcellation approach. A and B show the
improvement in correlation between the group-mean adjacency matrix and each individual's mean
adjacency matrix for the K = 10 and K = 18 subcortical parcellation respectively. C & D show the
improvement of the adjusted Rand Index between the clusters labels of the group and individual
level parcellations.

2.3 Reliability

We found that bagging led to improvements in univariate estimates of reliability calculated with ICC of the voxel-wise mean adjacency matrices (Figure 12 A,B,C). Each of the entries in these matrices is the number of times across individual-level bootstraps that two voxels are put into the same cluster. As such, the individual mean adjacency matrix is a representation of the average clustering solution across bootstrap aggregations for a given individual. ICC is calculated based on the relative size of variance between subjects compared to variance within subjects. We see that bagging has a large impact on both between subject variance (MSR), and within subject variance (MSE). Notably, the decrease in MSE is slightly higher than the decrease in MSR, leading to a rise in ICC (Figure 12 D,E). In this case, ICC does not capture that bagging leads to a ten-fold decrease in variance, both within and between subjects' individual-level parcellation estimates.

Motion can be a source of highly reproducible signal in MRI data and can highly influence estimates of reliability (Power, Barnes, Snyder, Schlaggar, & Petersen, 2012; Yan et al., 2013). We wanted to make sure the impact of bagging wasn't being driven by motion, and so we regressed out mean framewise displacement from each individual mean adjacency matrix and calculated ICC, MSE, and MSR. As was the case without motion regression, here we see that bagging improves the ICC, MSE, and MSR of parcellations (Supplementary Figure 4).

The individual voxel-voxel ICCs were moderate, reflecting that each of the voxel-voxel relationships that make up the individual parcellations are not highly statistically reliable; however, it is still possible that when taken as a whole, the parcellation patterns in these adjacency matrices would be reliably distinct between individuals. We tested this using the multivariate metric of reliability called discriminability (Figure 13). This method allows us to consider the extent to which individual parcellation patterns are unique to that individual compared to the rest of the group. We

found that discriminability of the parcellations for 0 bootstraps was heavily impacted by the

amount of data acquired, and was quite high for 25 and 50 minutes of data (25 minute mean =

0.761; 50 minute mean = 0.817). We found that discriminability was significantly increased

through bagging but not for all lengths of data. It seems that the individual-level signals were not

strong enough in 3-15 minutes of data to improve the discriminability of parcellation through

bagging in the HNU1 data (all p > 0.05); however, we did see significant improvements from 0 to

400 bootstraps for 20 minutes (Kruskal-Wallis chi-squared = 7.1762, df = 1, p-value < 0.01), 25

minutes (Kruskal-Wallis chi-squared = 29.44, df = 1, p-value < 0.0001); and 50 minutes (Kruskal-

Wallis chi-squared = 24.584, df = 1, p-value < 0.0001), showing individual parcellation became

even more highly discriminable for 20 (mean = 0.71), 25 (mean = 0.89), and 50 (mean = 0.92)

minutes.

Finally, when making generalizations from group-level information to the individual, it's

critically important that the group-level information is representative of the individual (Adolf &

Fried, 2019; Fisher, Medaglia, & Jeronimus, 2018). Such group-to-individual generalizability is

critical for deploying any group-defined models on individual level data, and as such is central for

any kind of biomarker discovery process. Given that recent work has demonstrated that individual-

level brain networks can differ substantially from group level estimates (Gordon, Laumann,

Adeyemo, & Petersen, 2015; Laumann et al., 2015), we wanted to test whether bagging could

improve the group-to-individual generalizability of parcellation, improving their potential for

scientific and clinical applications (Figure 14). We found that bagging led to significantly more

generalizable parcellations (Twenty minute parcellation; 0 vs 400 bootstraps; K = 10; Correlation:

Kruskal-Wallis chi-squared = 800.81, df = 1, p-value < 0.0001; ARI: Kruskal-Wallis chi-squared =

248.43, df = 1, p-value < 0.0001), and increasing scan time did as well (K=10; Correlation:

Kruskal-Wallis chi-squared = 50.985, df = 1, p-value < 0.0001; ARI: Kruskal-Wallis chi-squared =

16.593, df = 1, p-value < 0.0001). We also found that bagging led to an overall decrease in the

variance of the group-individual similarity (K = 10; Correlation: F = 0.56163, num df = 599, denom

df = 599, p-value < 0.0001; ARI: F = 0.85283, num df = 1199, denom df = 1199, p-value < 0.01),

but this decreased variance was less pronounced here than in other analyses.

3. DISCUSSION

3.1 Overview- We find that bagging improves the reproducibility of group-level functional

parcellations with as little as six minutes of data, improving reproducibility more than by doubling

scan time. We find that bagging may be a potentially valuable means of bringing down data

requirements for reproducible study of functional brain organization. Bagging enhanced

parcellations are also more reliable on the individual level, with an order of magnitude decrease

in the MSE and MSR of individual-level parcellations. With twenty or more minutes we see

increases in already highly discriminable individual-level parcellations, meaning that the highly

detailed, individual-specific attributes of parcellations can be enhanced through bagging. We find

that bagging enhanced parcellations also have higher between session and between scan

reproducibility, meaning that they are better suited for within-sample repeated measures that are

commonly used in intervention or other longitudinal studies in clinical and cognitive neuroscience.

Finally, we found that bagging improved group-to-individual generalization of parcellations, which

is key for using any common parcellation across participants. Overall, this indicates that bagging

enhanced parcellations outperform the standard approach on a wide variety of reproducibility and

reliability indices, and should be considered for further implementation in cutting-edge cluster and

gradient-based parcellation and approaches for potential improvements in making more robust

measurements of the connectome (Glasser et al., 2016; Laumann et al., 2015; Schaefer, Kong,

& Yeo, 2016; Xu et al., 2016).

3.2 Implications Reaching clinical impact for cognitive and clinical neuroscience necessitates the

development of robust domain knowledge that can be used by researchers in academia and

industry to create the advances that will change people's lives. One of the largest impediments to

the development of such robust domain knowledge is the widespread reproducibility problem in

human neuroscience. It has been estimated that the United States spends about $28,000,000,000

on non-reproducible preclinical research (Freedman & Gibson, 2015), and some estimate that

irreproducibility may reach as high as 90% (Begley & Ioannidis, 2015). According to a recent poll

in Nature, 86% agree that there is a crisis of reproducibility in their field ("Checklists work to

improve science," 2018). Therefore investigating, establishing, and disseminating methods that

may improve the reproducibility of human neuroscience findings is an essential step towards

moving human neuroscience closer to clinical impact.

Given that functional parcellation misalignment has been found to control most of the

variance in functional connectivity weights (Bijsterbosch, Beckmann, Woolrich, Smith, & Harrison,

2019; Bijsterbosch et al., 2018), it's possible that some issues in reproducibility arise due to

irreproducible mapping of functional networks from inaccurately applied parcellations. While the

field has not established any 'best' technique for functional parcellation (Arslan et al., 2018),

bagging does not rely on any particular clustering technique. In fact, bagging can be applied

across a wide range of cluster and gradient based functional parcellation approaches. With

continuing advances in functional and multi-modal parcellations, bagging can be employed in new

methodological approaches to continually improve parcellation reproducibility, reliability, and

group-individual coherence.

The cluster ensemble literature has shown that bagging is one of several methods that

may improve clustering. Other approaches include combining cluster solutions across multiple

numbers of clusters (Kuncheva & Hadjitodorov, 2004), varying random parameters of the

clustering algorithm, or combining multiple clustering techniques (Hu & Yoo, 2004; Lancichinetti

& Fortunato, 2012). This implies that there may be other avenues to pursue ways in which both

ensemble methods or bagging can be used to improve the generalizability of functional

parcellations and other MRI approaches that use clustering (Blumensath et al., 2013; Craddock

et al., 2012). For example, prior work has demonstrated the utility of using clustering for tissue

class segmentation in lesion detection (Bosc et al., 2003; Juang & Wu, 2010), and these efforts

may be furthered by the use of cluster ensemble methods for detecting and evaluating differences

lesions more reproducibly across samples and timepoints.

The impact of bagging on reproducibility observed between completely independent

samples is particularly promising, as it suggests a means of improving the generalizability of

parcellation atlases across sites, scanners, and populations. The choice of a parcellation is an

important step in the creation of a connectome, and it has a significant impact on the sensitivity

of the resulting connectome to phenotypic differences (Abraham et al., 2017). Recent work has

demonstrated that up to 60% of the variance in the edges of a connectome derive from the

variance in the match of the reference parcellation to the data in question (Bijsterbosch et al.,

2019); this is troublesome because when parcellations do not generalize well between samples,

the resulting connectome edges will conflate differences between group network structure with

differences in underlying parcellation fit (Zuo & Xing, 2014). In this way, enhancing the

reproducibility of the parcellation fit between samples may also increase sensitivity of network

edges to phenotypic differences between groups and individuals. This is an important step for

creating the robust brain-behavior associations required for efforts aimed at using brain networks

as biomarkers for various phenotypic variables.

It may be possible that with improved reliability of parcellations we may be able to also

elucidate brain-behavior relationships with more robustness than previously possible. The

strength of the association between two variables is limited to the reliability of the variables in

question (Zuo & Xing, 2014). With improvements in between session reproducibility of

measurement we also improve the ability to clinically assess changes over time that may occur

in a clinical trial or behavioral intervention, or in the case of a longitudinal development study,

such as the ongoing ABCD study (Volkow et al., 2018). As measurement error decreases over

time, it becomes more feasible for estimating the change over time that occurs as the result of a

process of interest rather than uncontrolled variance.

An important recurrent finding was that bagging decreased the variance in the

reproducibility estimates. While the importance of improving reproducibility of parcellations are

key for improving the fit of a parcellation across samples or over time, if the improvements are

highly variable then it's unclear when a procedure such as bagging is helping or hurting for a given

case. Seeing that bagging significantly reduced this variance is not only indicative that it is more

likely to produce reproducible parcellations, but also that each time it is applied to a given dataset

these parcellations are likely to be more in line with one another. We show that cluster ensembles

have a better grasp on the central tendency of the data for each participant and the group as a

whole, and by demonstrating that bagging improves the consistency of parcellations we show that

bagging also helps prevent small perturbations in the data from having outsized effects on the

parcellation results. Given that an individual system may be unique in ways that share little

relationship to group models (Medaglia 2017), and extensive individual-variation has been

demonstrated in functional networks (Gordon 2015; Xu 2016), it's also critical that if group models

are used, they are as representative of each individual in the group as possible. In other words,

group-individual representativeness is critical to make accurate assessments of individual-level

functional connectivity. Otherwise, differences between individuals in edge-wise connectivity will

be the result of the parcellation fit, rather than actually the functional connection of interest

(Bijsterbosch 2018; Bijsterbosch 2019). We saw bagging had a significant impact in not only

reducing variance across repeated group level parcellations, but also in reducing variance across

individuals, and between the individuals and the group level maps, without decreasing

individualization of the parcellations. These results offer compelling evidence that bagging

provides parcellations that better generalize from group to individual, and may give more

reproducible individual level estimates of the underlying connectome as well.

3.3 Limitations- It is also worth noting that the functional parcellations created in the current work are not intended to be new reference atlases that are more reproducible than all others. Instead, we intend to demonstrate that bagging can help create functional parcellations generalize better between multiple sessions and samples. Most likely, the application of such cluster ensemble methods on multi-modal structural and functional data would lead to even greater improvements on the test-retest reliability of the parcellation, such as those applied in recent advanced efforts (Glasser et al., 2016; Xu et al., 2016). We also did not examine the impact of bagging on the reliability and reproducibility of the resulting edges of the parcellation, though this is important work that should be considered in the future. Another limitation of the current study is that we did not exhaustively test the space of cluster methods, even though PyBASC inherently is capable of such extensions (See Supplementary Methods). Bagging and cluster ensembles are notable for being agnostic to clustering technique and have been successfully demonstrated in a wide range of clustering techniques however, and we feel this limitation is notable but not a significant one.

3.4 Future Directions- The current effort aimed at establishing the role of bagging in improving reproducibility and reliability of functional parcellations, but the number of tests were far from exhaustive. There are more ways that bagging and cluster ensembles could be leveraged to improve measurements of the brain. For instance, varying and aggregating over a range of time series window lengths, cluster techniques, or resampling methods may lead to better individual-level and group-level estimates. Some research has demonstrated that selecting diverse sets of cluster solutions for aggregation can outperform simply aggregating all cluster solutions (Hadjitodorov, Kuncheva, & Todorova, 2006). Such a diversity selection approach could also be employed in a similar context and may likely improve reproducibility and reliability of the cluster solutions as well.

4. Materials and Methods

4.1 Overview

We aimed to approach a full-scale assessment of the impact of bagging on between sample reproducibility, between session reproducibility, and between session reliability. Towards this end, we apply PyBASC, a multi-level bagging approach for functional parcellation (See Methods Section 4.4 on PyBASC).

Data Source	Sample Size	Data Length	Age	Sex	Voxel Size	TR
HNU1	30	10x 10-Minute	24.37, +/- 2.37	50/50 % F/M	3.4, 3.4, 3.4 mm	2000ms
GSP	300	2x 6-Minute	23.67, +/- 2.15	50/50 % F/M	3.0, 3.0, 3.0 mm	3000ms

Table 1: Overview of datasets used in the current study. HNU1- Hanzhou Normal University. GSP- Genomics Superstruct Project.

4.2 HNU1 and GSP Data

We assessed the impact of bagging on reproducibility of functional parcellation using the HNU1 (Zuo et al., 2014), and GSP (Holmes et al., 2015). In the HNU1 dataset, 10 minute resting state scans were acquired in 30 young adults every three days for a month, for a total of 10 sessions

per person. To test between session reproducibility and reliability we split the even and odd

numbered sessions into fifty minute reference and replication datasets. From the 300 participants

in the GSP, we created 10 groups of 30 age and gender matched participants to assess within

study/between sample reproducibility. Using all 300 GSP participants combined, we also created

a reference parcellation and compared it to the HNU1 replication dataset to assess the impact of

bagging on the between study/between sample reproducibility.

4.3 MRI Data

4.3.1 MRI Acquisition- *HNU1. Anatomical*: 3D SPGR images were acquired on a GE 3T scanner

(General Electric, Milwaukee, WI) with an 8 Channel head coil. Flip angle: 8 Degrees. TI: 450ms,

TE: 60ms, TR: 8.06s, 180 slices, slice thickness 1mm. Acquisition time: 5:01. *Rest*: T2* BOLD

EPI sequence, GE 3T, 8 Channel head coil. Flip angle 90 Degree. TE 30ms, TR 2000ms, 43

slices, slice thickness: 3.4 mm. Acquisition time: 10:00.

GSP Anatomical: T1 MEMPRAGE images were acquired on Siemens 3T Magnetom Tim

Trio scanner (Siemens Medical Solutions, Erlangen, Germany) with a 12 channel headcoil. Flip

angle: 7 degrees. TI 1.1s, TE:1.5 / 3.4 / 5.2 / 7.0. TR 2.2s. 144 slices, slice thickness 1.2mm.

Acquisition time: 2:12. *Rest*: T2* BOLD epfid2d1_72 sequence, Siemens 3T Magnetom Tim Trio,

12 channel headcoil. Flip angle 85 degrees. TE 30ms, TR 3.0s, 47 slices, 3mm slice thickness.

Acquisition time: 6:12.

4.3.2 Preprocessing- *Anatomical:* 1) AFNI skull stripping. 2) MNI 152 2 mm template anatomical

nonlinear registration with FNIRT. 3) Data transformed to 3mm. *Functional:* 1) Transformed to 3

mm. 2) Nuisance regression applied (white matter, CSF, global signal, motion, linear, and

quadratic components of motion). 3) Friston 24-Parameter model used for volume realignment.

4) Nuisance band pass filtering between 0.01 and 0.1 Hz. 5) Spatial smoothing applied 6mm

FWHM. Preprocessing in GSP and HNU1 structural and rest data were identical with the addition

of de-spiking to the GSP resting state data. (HNU1- CPAC 1.0; GSP- CPAC Version 1.2).

651
652
653
<u>Figure 15 Parcellation Overview</u>- A) Outline of different steps in standard clustering approach. B)
Creating cluster ensembles through bagging follows the same overall structure as A, with the
addition of individual level time-series resampling at step 3, and bagging across individuals in step
6. Red arrows show when bootstrap resampling occurs to create multiple resampled individual
(3) and group-level data (6). Blue arrows show when bootstrap aggregation happens to create
averaged individual (5) and group-level data (7).
660

4.4 PyBASC Parcellation

We first apply clustering in the same manner as is commonly applied in functional parcellation methods when not using bagging (Figure 1; Craddock et al., 2012; van den Heuvel, Mandl, & Pol, 2008). 1) We start with preprocessed functional MRI data; 2) this data is transformed from voxel representation to a supervoxel representation through feature reduction such as Ward's criterion based hierarchical agglomerative clustering 3) time series for each supervoxel is extracted, and a correlation matrix is calculated, 4) clustering is applied to extract a specific number of clusters (K) for each individual's correlation matrix and an adjacency matrix is created, and 5) individual level adjacency matrices are averaged together and 6) clustered again to reveal the group level clustering.

This approach can be extended by adding bagging to both within each individual's time series and across individuals to create resampled groups, as in the case in BASC (Figure 1B). We explain this process briefly here (See Supplementary Methods for more detail). At the individual level, bagging is applied using a circular block bootstrap (window size = sqrt(number of time steps)), which has been shown to outperform autoregressive process modeling and other methods (Adolf, Baecke, Kahle, Bernarding, & Kropf, 2011; Adolf et al., 2014; Bellec, Marrelec, & Benali, 2008). We used this method on the individual time series to create many resampled 4D functional scans for each individual, and clustering is applied to each individual and resulting in cluster solutions for each individual-level bootstrap. These cluster solutions are transformed to an adjacency matrix and are averaged together to create a mean adjacency matrix for each participant. We then bagged across individuals to create resampled groups (6), which are then averaged to create the group mean adjacency matrix (7) that is clustered to create the final parcellation (8). This multilevel bagging approach has been previously applied in the original BASC implementation in Octave and has been explained in greater detail elsewhere (Bellec et al., 2010; Garcia-Garcia et al., 2017); See supplementary materials for more details about PyBASC). Here we have created a python based implementation of this framework, PyBASC, to

conduct the following reproducibility and reliability assessments. Overall, PyBASC and BASC

follow the same algorithmic structure, however there are a few differences worth noting for the

application here: 1) Dimension reduction is conducted through a region growing algorithm in

BASC, whereas in PyBASC Ward's criterion hierarchical clustering is applied. 2) Dimension

reduction is applied at the group level in BASC, though can be at the individual or group level in

PyBASC. Here we apply individual-level dimension reduction for subcortical parcellation and

group-level dimension reduction for cortical parcellation to reduce computational load.

In the current work, we applied parcellation to both cortical and subcortical regions across

a range of number of clusters (Subcortical K = 10, 18; Cortical K = 7, 20, 197, 444). We chose K

= 10, and 18 for the subcortical parcellation given our work and other literature has repeatedly

shown these parcellations fit best for the striatum and thalamus (Behrens et al., 2003; Choi et al.,

2012; Garcia-Garcia et al., 2017; Johansen-Berg et al., 2005). We chose K = 7, 20, 197, and 444

following previous analysis exploring multi-scale parcellation with BASC (Bellec, 2013; Bellec et

al., 2010). Also worth noting, many functional parcellations have strong spatial constraints placed

on the clusters (Craddock et al., 2012; Schaefer et al., 2018), which plays a significant role in

homogenizing parcel shape and smoothing parcel boundaries. In this way such constraints can

be considered a spatial regularizer for the cluster optimization procedure, thus increasing the

reproducibility of the clustering outcomes. To better appreciate the ability of bagging to enhance

reproducibility of parcellation, we use minimal spatial constraints which are only implemented in

our dimension reduction step.

Level of Generalization	Participants		MRI		Data Used	Figures
	Pop.	Sample	Scanner	Data		
Between Sample Reproducibility I	=	X	X	X	GSP 10 groups	1
Between Sample Reproducibility II	X	X	X	X	GSP 300 HNU Replication	2, 3, 4, 5
Between Scan Reproducibility	=	=	=	X	GSP 10 groups TRT	6
Between Session Reproducibility	=	=	=	X	HNU Reference & Replication	7, 8, 9,10, 11
Reliability	=	=	=	X	GSP 10 groups TRT HNU Reference & Replication	12, 13, 14

Table 2- Group-Level Analyses. Level of Generalization depicts which type of generalizability we tested with each analysis, see Methods sections 4.5-4.6. Columns show which kind of parameters would be kept constant (=) or changed (x) across analyses in the current study.

4.5 Reproducibility

4.5.1 Concept- The definitions of concepts of reproducibility and replicability are numerous and often conflicting (Barba, 2018). We choose to follow the Joint Committee for Guides in Metrology (JCGM). This group is comprised of eight international organizations specializing in measurement, including the International Standards Organization (ISO), which the COBIDAS report follows closely (Nichols et al., 2017). According to the JCGM, Reproducibility is the

similarity between the results of measurements of the same or similar measurands carried out

under changed conditions of measurement (JCGM, 2008).

<u>4.5.2 Data Requirements-</u> The changed conditions may include the method of measurement,

observer, measuring instrument, reference standard, location, conditions of use, and time.

Notably, statements of reproducibility must include a description of the specific conditions

changed. In other words, when discussing reproducibility, it's important to be specific about what

is being changed and across which dimension(s) measurements are being reproduced.

Reproducibility across sessions but not samples requires multiple assessments of the same

sample, and is known as between session reproducibility. Similarly, reproducibility across

investigators requires different investigators but can use the same method and data, which is

often referred to as computational reproducibility (Millman et al., 2018). We extend this formal

definition of reproducibility to include reproducibility across samples, which we call between

sample reproducibility.

To support our tests of between sample, between session, and between scan

reproducibility, we created several reference and replication datasets using the HNU1 and GSP

datasets. In the HNU1 dataset, we created a test-retest dataset by combining the ten, 10-minute

sessions into two five-session, 50-minute scans. Our reference and replication datasets were

created through a concatenation of each participant's even and odd numbered session's

respectively. To assess the interaction of bagging and length of acquired data on reproducibility,

we performed parcellation across the first 3, 5, 10, 15, 20, and 25, and 50 minutes of the

replication data. We split the 300 participants of the GSP data into 10 groups of 30 participants

that were age and sex matched to the HNU1 dataset, and we used these 10 groups to assess

both between sample and between scan reproducibility, given these two 6-minute scans were

acquired in the same session. We also concatenated both 6 minute sessions and used all 300

participants of the GSP dataset to create a large reference parcellation, and we compared this

reference to the replication sets of the HNU1 data to test between sample reproducibility.

4.5.3 Testing Methods- To measure between session reproducibility, we assessed the similarity

between the reference and each of the replication datasets using spatial correlation of these

group-level mean adjacency matrices, and the adjusted Rand Index of the group-level cluster

labels. Given that bagged clustering is non-deterministic, we assessed the variance in our

parcellations by repeating our parcellations 20 times for each replication dataset across each

amount of scan time and bootstrap aggregation for the subcortical parcellation. For the cortical

parcellation we repeated the parcellations 10 times, with the HNU1 ten minute replication data..

Since the standard, non-bagged, clustering approach clustering is deterministic, we needed a

method to assess the variance in between session reproducibility of the parcellations. To

overcome this issue, we created 20 new datasets for each amount of the scan lengths by

resampling the 50 minute replication dataset (See supplementary methods for details on this

resampling method). We applied PyBASC without bagging across each of these 20 datasets to

estimate the variance in between session reproducibility for the standard parcellation condition.

We assessed the effect of bagging on within study/between sample reproducibility of

functional parcellation by comparing the parcellations between 10 age and sex-matched groups

of 30 participants from the GSP dataset. Since we had 10 groups, we did not need to resample

and repeat our bagged or standard parcellations as above. We used each of the two 6 minute

scans for each group, as well as a concatenated 12 minute scan. We compared the similarity of

group-level parcellations between the 10 groups for each scan length, and we compared the

parcellations of the ten groups for both 6 minute scans. Second, we assessed the effect of

bagging on between study/between sample reproducibility. We used the same 12 minute scans

from all 300 GSP participants together to create a reference parcellation. For assessing cortical

parcellation reproducibility, we compared the GSP reference to the 10 minute HNU1 data. For

assessing subcortical parcellation reproducibility we assessed the GSP parcellation against a

range of HNU1 scan lengths.

4.6 Reliability & Discriminability

4.6.1 Concept- Reliability is a metric of the inter- and intra-individual stability of a measurement across multiple occasions (Zuo & Xing, 2014), and can be measured with many different indices. Intraclass correlation (ICC) is a descriptive statistic that relates the within-participant to between subject variance to get an indication of univariate reliability (Shrout & Fleiss, 1979). ICC is most commonly considered as the intra-individual variability relative to the inter-individual variability. Discriminability is multivariate metric of reliability that takes the full set of features across all observations into account to compute a multivariate index of reliability (https://github.com/neurodata/r-mgc).

4.6.2 Data Requirements- Calculating test retest reliability requires at least two observations of the same individuals in the same group. In the current study, we compute ICC using two measurements from each individual in both the HNU1 and GSP samples.

4.6.3 Testing Methods- We assessed whether bagging would improve both the univariate and multivariate reliability of our functional parcellations, and how length of scan acquisition would have an impact on these results. Using the same set of functional parcellations across multiple datasets calculated in Section 4.5 Reproducibility, namely the reference and multi-length replication datasets, we calculated the ICC for each cell in the individual level mean adjacency matrix data, and discriminability for the individual mean adjacency matrix as a whole.

Acknowledgements: We would like to thank Lei Ai and Yu Tong for their assistance with the GSP and HNU1 datasets.

Funding: AN is supported by R21MH118556-02 and a NARSAD Young Investigator Award from the Brain and Behavior Research Foundation.

805
806 **References**
807

Abraham, A., Milham, M. P., Di Martino, A., Cameron Craddock, R., Samaras, D., Thirion, B., &

Varoquaux, G. (2017). Deriving reproducible biomarkers from multi-site resting-state data:

An Autism-based example. *NeuroImage*, Vol. 147, pp. 736–745.

https://doi.org/10.1016/j.neuroimage.2016.10.045

Adolf, D., Baecke, S., Kahle, W., Bernarding, J., & Kropf, S. (2011). Applying multivariate

techniques to high-dimensional temporally correlated fMRI data. *Journal of Statistical*

Planning and Inference, *141*(12), 3760–3770.

Adolf, D., Weston, S., Baecke, S., Luchtmann, M., Bernarding, J., & Kropf, S. (2014). Increasing

the reliability of data analysis of functional magnetic resonance imaging by applying a new

blockwise permutation method. *Frontiers in Neuroinformatics*, *8*, 72.

Adolf, J. K., & Fried, E. I. (2019). Ergodicity is sufficient but not necessary for group-to-individual

generalizability. *Proceedings of the National Academy of Sciences of the United States of*

America, *116*(14), 6540–6541.

Arslan, S., Ktena, S. I., Makropoulos, A., Robinson, E. C., Rueckert, D., & Parisot, S. (2018).

Human brain mapping: A systematic comparison of parcellation methods for the human

cerebral cortex. *NeuroImage*, *170*, 5–30.

Barba, L. A. (2018). Terminologies for Reproducible Research. Retrieved from

http://arxiv.org/abs/1802.03311

Barnes, K. A., Cohen, A. L., Power, J. D., Nelson, S. M., Dosenbach, Y. B. L., Miezin, F. M., …

Schlaggar, B. L. (2010). Identifying Basal Ganglia divisions in individuals using resting-state

functional connectivity MRI. *Frontiers in Systems Neuroscience*, *4*(June), 18.

Begley, C. G., & Ioannidis, J. P. A. (2015). Reproducibility in science: improving the standard for

basic and preclinical research. *Circulation Research*, *116*(1), 116–126.

Behrens, T. E. J., Johansen-Berg, H., Woolrich, M. W., Smith, S. M., Wheeler-Kingshott, C. A.

M., Boulby, P. A., … Matthews, P. M. (2003). Non-invasive mapping of connections

between human thalamus and cortex using diffusion imaging. *Nature Neuroscience*, Vol. 6,

pp. 750–757. https://doi.org/10.1038/nn1075

Bellec, P. (2013). Mining the Hierarchy of Resting-State Brain Networks: Selection of

Representative Clusters in a Multiscale Structure. *2013 International Workshop on Pattern*

Recognition in Neuroimaging, 54–57. ieeexplore.ieee.org.

Bellec, P., Marrelec, G., & Benali, H. (2008). A bootstrap test to investigate changes in brain

connectivity for functional MRI. *Statistica Sinica*, *18*, 1253–1268.

Bellec, P., Rosa-neto, P., Lyttelton, O. C., Benali, H., & Evans, A. C. (2010). NeuroImage Multi-

level bootstrap analysis of stable clusters in resting-state fMRI. *NeuroImage*, *51*(3), 1126–

1139.

Bijsterbosch, J. D., Beckmann, C. F., Woolrich, M. W., Smith, S. M., & Harrison, S. J. (2019).

The relationship between spatial configuration and functional connectivity of brain regions

revisited. *eLife*, *8*. https://doi.org/10.7554/eLife.44890

Bijsterbosch, J. D., Woolrich, M. W., Glasser, M. F., Robinson, E. C., Beckmann, C. F., Van

Essen, D. C., … Smith, S. M. (2018). The relationship between spatial configuration and

functional connectivity of brain regions. *eLife*, Vol. 7. https://doi.org/10.7554/elife.32992

Blumensath, T., Jbabdi, S., Glasser, M. F., Van Essen, D. C., Ugurbil, K., Behrens, T. E. J., &

Smith, S. M. (2013). Spatially constrained hierarchical parcellation of the brain with resting-

state fMRI. *NeuroImage*, *76*, 313–324.

Bosc, M., Heitz, F., Armspach, J. P., Namer, I., Gounot, D., & Rumbach, L. (2003). Automatic

change detection in multimodal serial MRI: application to multiple sclerosis lesion evolution.

NeuroImage, *20*(2), 643–656.

Breiman, L. (1996). Bagging predictors. *Machine Learning*, *24*(2), 123–140.

Buckner, R. L., Krienen, F. M., Castellanos, A., Diaz, J. C., & Yeo, B. T. T. (2011). The

organization of the human cerebellum estimated by intrinsic functional connectivity. *Journal*

of Neurophysiology, *106*(July 2011), 2322–2345.

Checklists work to improve science. (2018). *Nature*, *556*(7701), 273–274.

Choi, E. Y., Yeo, B. T. T., & Buckner, R. L. (2012). The organization of the human striatum

estimated by intrinsic functional connectivity. *Journal of Neurophysiology*, *108*(8), 2242–

2263.

Craddock, R. C., James, G. A., Holtzheimer, P. E., Hu, X. P., & Mayberg, H. S. (2012). A whole

brain fMRI atlas generated via spatially constrained spectral clustering. *Human Brain*

Mapping, *33*(8), 1914–1928.

Dudoit, S., & Fridlyand, J. (2003). Bagging to improve the accuracy of a clustering procedure.

Bioinformatics , *19*(9), 1090–1099.

Fischer, B., & Buhmann, J. M. (2003). Bagging for path-based clustering. *IEEE Transactions on*

Pattern Analysis and Machine Intelligence, *25*(11), 1411–1415.

Fisher, A. J., Medaglia, J. D., & Jeronimus, B. F. (2018). Lack of group-to-individual

generalizability is a threat to human subjects research. *Proceedings of the National*

Academy of Sciences of the United States of America, *115*(27), E6106–E6115.

Freedman, L. P., & Gibson, M. C. (2015). The impact of preclinical irreproducibility on drug

development. *Clinical Pharmacology and Therapeutics*, *97*(1), 16–18.

Garcia-Garcia, M., Nikolaidis, A., Bellec, P., Craddock, R. C., Cheung, B., Castellanos, F. X., &

Milham, M. P. (2017). Detecting stable individual differences in the functional organization

of the human basal ganglia. *NeuroImage*. https://doi.org/10.1016/j.neuroimage.2017.07.029

Glasser, M. F., Coalson, T. S., Robinson, E. C., Hacker, C. D., Harwell, J., Yacoub, E., … Van

Essen, D. C. (2016). A multi-modal parcellation of human cerebral cortex. *Nature*,

536(7615), 171–178.

Gordon, E. M., Laumann, T. O., Adeyemo, B., & Petersen, S. E. (2015). Individual Variability of

the System-Level Organization of the Human Brain. *Cerebral Cortex* , bhv239.

Gordon, E. M., Laumann, T. O., Gilmore, A. W., Newbold, D. J., Greene, D. J., Berg, J. J., …

Dosenbach, N. U. F. (2017). Precision Functional Mapping of Individual Human Brains.

Neuron, *95*(4), 791–807.e7.

Gorgolewski, K., Burns, C. D., Madison, C., Clark, D., Halchenko, Y. O., Waskom, M. L., &

Ghosh, S. S. (2011). Nipype: A Flexible, Lightweight and Extensible Neuroimaging Data

Processing Framework in Python. *Frontiers in Neuroinformatics*, *5*.

https://doi.org/10.3389/fninf.2011.00013

Hadjitodorov, S. T., Kuncheva, L. I., & Todorova, L. P. (2006). Moderate diversity for better

cluster ensembles. *An International Journal on Information Fusion*, *7*(3), 264–275.

Holmes, A. J., Hollinshead, M. O., O'Keefe, T. M., Petrov, V. I., Fariello, G. R., Wald, L. L., …

Buckner, R. L. (2015). Brain Genomics Superstruct Project initial data release with

structural, functional, and behavioral measures. *Scientific Data*, *2*, 150031.

Hong, Y., Kwong, S., Wang, H., & Ren, Q. (2009). Resampling-based selective clustering

ensembles. *Pattern Recognition Letters*, *30*(3), 298–305.

Hoyos-Idrobo, A., Schwartz, Y., Varoquaux, G., & Thirion, B. (2015). Improving sparse recovery

on structured images with bagged clustering. *Pattern Recognition in NeuroImaging (PRNI),*

2015 International Workshop on, 73–76. IEEE.

Hu, X., & Yoo, I. (2004). Cluster Ensemble and Its Applications in Gene Expression Analysis.

Proceedings of the Second Conference on Asia-Pacific Bioinformatics - Volume 29, 297–

302. Darlinghurst, Australia, Australia: Australian Computer Society, Inc.

Janssen, R. J., Jylänki, P., Kessels, R. P. C., & van Gerven, M. A. J. (2015). Probabilistic

model-based functional parcellation reveals a robust, fine-grained subdivision of the

striatum. *NeuroImage*, *119*, 398–405.

JCGM. (2008). Evaluation of measurement data—Guide to the expression of uncertainty in

measurement. *Int. Organ. Stand. Geneva ISBN*, *50*, 134.

Jia, J., Xiao, X., Liu, B., & Jiao, L. (2011). Bagging-based spectral clustering ensemble

selection. *Pattern Recognition Letters*, *32*(10), 1456–1467.

Johansen-Berg, H., Behrens, T. E. J., Sillery, E., Ciccarelli, O., Thompson, A. J., Smith, S. M., &

Matthews, P. M. (2005). Functional–Anatomical Validation and Individual Variation of

Diffusion Tractography-based Segmentation of the Human Thalamus. *Cerebral Cortex* ,

15(1), 31–39.

Juang, L.-H., & Wu, M.-N. (2010). MRI brain lesion image detection based on color-converted

K-means clustering segmentation. *Measurement*, *43*(7), 941–949.

Kelly, A. M. C., Di Martino, A., Uddin, L. Q., Shehzad, Z., Gee, D. G., Reiss, P. T., … Milham,

M. P. (2009). Development of Anterior Cingulate Functional Connectivity from Late

Childhood to Early Adulthood. *Cerebral Cortex* , *19*(3), 640–657.

Kelly, C., Toro, R., Di Martino, A., Cox, C. L., Bellec, P., Castellanos, F. X., & Milham, M. P.

(2012). A convergent functional architecture of the insula emerges across imaging

modalities. *NeuroImage*, *61*(4), 1129–1142.

Klein, J. C., Behrens, T. E. J., Robson, M. D., Mackay, C. E., Higham, D. J., & Johansen-Berg,

H. (2007). Connectivity-based parcellation of human cortex using diffusion MRI:

Establishing reproducibility, validity and observer independence in BA 44/45 and SMA/pre-

SMA. *NeuroImage*, *34*(1), 204–211.

Kuncheva, L. I., & Hadjitodorov, S. T. (2004). Using diversity in cluster ensembles. *2004 IEEE*

International Conference on Systems, Man and Cybernetics (IEEE Cat. No.04CH37583), *2*,

1214–1219 vol.2. ieeexplore.ieee.org.

Lambert, C., Simon, H., Colman, J., & Barrick, T. R. (2017). Defining thalamic nuclei and

topographic connectivity gradients in vivo. *NeuroImage*, *158*, 466–479.

Lancichinetti, A., & Fortunato, S. (2012). Consensus clustering in complex networks. *Scientific*

Reports, *2*, 336.

Laumann, T. O., Gordon, E. M., Adeyemo, B., Snyder, A. Z., Joo, S. J., Chen, M.-Y., …

Petersen, S. E. (2015). Functional System and Areal Organization of a Highly Sampled

935   Individual Human Brain. *Neuron*, *87*(3), 657–670.

936 Li, T., & Ding, C. (2008). Weighted Consensus Clustering. In *Proceedings. Proceedings of the*

937   *2008 SIAM International Conference on Data Mining* (pp. 798–809). Society for Industrial

938   and Applied Mathematics.

939 Margulies, D. S., Kelly, A. M. C., Uddin, L. Q., Biswal, B. B., Castellanos, F. X., & Milham, M. P.

940   (2007). Mapping the functional connectivity of anterior cingulate cortex. *NeuroImage*, *37*(2),

941   579–588.

942 Mars, R. B., Jbabdi, S., Sallet, J., O'Reilly, J. X., Croxson, P. L., Olivier, E., … Rushworth, M. F.

943   S. (2011). Diffusion-Weighted Imaging Tractography-Based Parcellation of the Human

944   Parietal Cortex and Comparison with Human and Macaque Resting-State Functional

945   Connectivity. *Journal of Neuroscience*, Vol. 31, pp. 4087–4100.

946   https://doi.org/10.1523/jneurosci.5102-10.2011

947 Millman, K. J., Brett, M., Barnowski, R., & Poline, J.-B. (2018). Teaching Computational

948   Reproducibility for Neuroimaging. *Frontiers in Neuroscience*, *12*, 727.

949 Nichols, T. E., Das, S., Eickhoff, S. B., Evans, A. C., Glatard, T., Hanke, M., … Yeo, B. T. T.

950   (2017). Best practices in data analysis and sharing in neuroimaging using MRI. *Nature*

951   *Neuroscience*, *20*(3), 299–303.

952 Nikolaidis, A., Heinsfeld, A. S., Xu, T., Bellec, P., Vogelstein, J., & Milham, M. (2019). Bagging

953   Improves Reproducibility of Functional Parcellation (p. 343392).

954   https://doi.org/10.1101/343392

955 Noble, S., Spann, M. N., Tokoglu, F., Shen, X., Constable, R. T., & Scheinost, D. (2017).

956   Influences on the Test–Retest Reliability of Functional Connectivity MRI and its

957   Relationship with Behavioral Utility. *Cerebral Cortex* , *27*(11), 5415–5429.

958 O'Connor, D., Potler, N. V., Kovacs, M., Xu, T., Ai, L., Pellman, J., … Milham, M. P. (2017). The

959   Healthy Brain Network Serial Scanning Initiative: a resource for evaluating inter-individual

960   differences and their reliabilities across scan conditions and sessions. *GigaScience*, *6*(2),

1–14.

Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., … Duchesnay, É.

(2011). Scikit-learn: Machine Learning in Python. *Journal of Machine Learning Research:*

JMLR, *12*(Oct), 2825–2830.

Power, J. D., Barnes, K. A., Snyder, A. Z., Schlaggar, B. L., & Petersen, S. E. (2012). Spurious

but systematic correlations in functional connectivity MRI networks arise from subject

motion. *NeuroImage*, *59*(3), 2142–2154.

Schaefer, A., Kong, R., Gordon, E. M., Laumann, T. O., Zuo, X.-N., Holmes, A. J., … Yeo, B. T.

T. (2018). Local-Global Parcellation of the Human Cerebral Cortex from Intrinsic Functional

Connectivity MRI. *Cerebral Cortex* , *28*(9), 3095–3114.

Schaefer, A., Kong, R., & Yeo, B. T. T. (2016). Chapter 1 - Functional connectivity parcellation

of the human brain. In G. Wu, D. Shen, & M. R. Sabuncu (Eds.), *Machine Learning and*

Medical Imaging (pp. 3–29). Academic Press.

Shrout, P. E., & Fleiss, J. L. (1979). Intraclass correlations-uses in assessing rater reliability.

Psychological Bulletin, *86*(2), 420–428.

Strehl, A., & Ghosh, J. (2002). Cluster Ensembles --- A Knowledge Reuse Framework for

Combining Multiple Partitions. *Journal of Machine Learning Research: JMLR*, *3*(Dec), 583–

617.

van den Heuvel, M., Mandl, R., & Pol, H. H. (2008). Normalized cut group clustering of resting-

state fMRI data. *PloS One*, *3*(4). https://doi.org/10.1371/journal.pone.0002001

Volkow, N. D., Koob, G. F., Croyle, R. T., Bianchi, D. W., Gordon, J. A., Koroshetz, W. J., …

Weiss, S. R. B. (2018). The conception of the ABCD study: From substance use to a broad

NIH collaboration. *Developmental Cognitive Neuroscience*, *32*, 4–7.

Xu, T., Opitz, A., Craddock, R. C., Wright, M. J., Zuo, X.-N., & Milham, M. P. (2016). Assessing

Variations in Areal Organization for the Intrinsic Brain: From Fingerprints to Reliability.

Cerebral Cortex , *26*(11), 4192–4211.

Yan, C.-G., Cheung, B., Kelly, C., Colcombe, S., Craddock, R. C., Di Martino, A., … Milham, M.

P. (2013). A comprehensive assessment of regional variation in the impact of head

micromovements on functional connectomics. *NeuroImage*, *76*, 183–201.

Yang, Z., Zuo, X.-N., Wang, P., Li, Z., LaConte, S. M., Bandettini, P. A., & Hu, X. P. (2012).

Generalized RAICAR: discover homogeneous subject (sub)groups by reproducibility of their

intrinsic connectivity networks. *NeuroImage*, *63*(1), 403–414.

Yeo, B. T. T., Krienen, F. M., Sepulcre, J., Sabuncu, M. R., Lashkari, D., Hollinshead, M., …

Buckner, R. L. (2011). *The organization of the human cerebral cortex estimated by intrinsic*

functional connectivity. 1125–1165.

Zhou, Z.-H. (2012). *Ensemble Methods: Foundations and Algorithms*. CRC Press.

Zuo, X.-N., Anderson, J. S., Bellec, P., Birn, R. M., Biswal, B. B., Blautzik, J., … Milham, M. P.

(2014). An open science resource for establishing reliability and reproducibility in functional

connectomics. *Scientific Data*, *1*, 140049.

Zuo, X.-N., Biswal, B. B., & Poldrack, R. A. (2019). *Reliability and Reproducibility in Functional*

Connectomics. Frontiers Media SA.

Zuo, X. N., Kelly, C., Adelstein, J. S., Klein, D. F., Castellanos, F. X., & Milham, M. P. (2010).

Reliable intrinsic connectivity networks: Test-retest evaluation using ICA and dual

regression approach. *NeuroImage*, *49*(3), 2163–2177.

Zuo, X.-N., Kelly, C., Di Martino, A., Mennes, M., Margulies, D. S., Bangaru, S., … Milham, M.

P. (2010). Growing together and growing apart: regional and sex differences in the lifespan

developmental trajectories of functional homotopy. *The Journal of Neuroscience: The*

Official Journal of the Society for Neuroscience, *30*(45), 15034–15043.

Zuo, X.-N., & Xing, X.-X. (2014). Test-retest reliabilities of resting-state FMRI measurements in

human brain functional connectomics: a systems neuroscience perspective. *Neuroscience*

and Biobehavioral Reviews, *45*, 100–118.

Zuo, X.-N., Xu, T., & Milham, M. P. (2019). Harnessing reliability for neuroscience research.

1014

5. Supplementary Materials.

5.1 Supplementary Methods

5.1.1 Standard Clustering Resampling Datasets- Without bagging, Ward's criterion hierarchical

agglomerative cluster is deterministic and has no variance over multiple runs. To offer a better

understanding of the sampling variance that could lead to differences in clustering when bagging

is not applied, we apply resampling to the original replication datasets when comparing them to a

given reference. To create the multiple 3 and 5 minute datasets for the non bootstrapped

condition, we randomly sampled continuous 3 or 5 minute blocks of the full 50 minute replication

dataset. To create the 10, 15, 20, 25, and 50 minute resampled datasets, we randomly sampled

continuous 5 minute blocks of the full 50 minute replication dataset. We did not calculate

resampling in the GSP datasets because we compared the 10 groups against one another.

5.1.2 PyBASC Originally, this method was implemented in Octave, and we have recently

implemented this method in Python to take advantage of the broad range of powerful libraries

available for machine learning and neuroimaging, including NiBabel, Nilearn, Scikit Learn, and

NiPype. This enables PyBASC to be highly flexible and extensible in adopting new clustering

algorithms and implementations, but more importantly allows for dramatic increases in

computational power through the use of NiPype's easy-to-use and adjust multi-core processing

capabilities. We have also made edits to the processing that make PyBASC run very efficiently

with minimal memory loads. This makes PyBASC just as easy to run on a laptop as on a large

server in the cloud. Here, we briefly address the PyBASC overall methodology. For more

information, we have also explained these methods in more detail elsewhere (Garcia-Garcia et

al., 2017). PyBASC has a wide range of functionalities that can be customized according to user

preferences. Well- performing default values are provided where applicable, but users can choose

1) the number of initial supervoxels, 2) the number of individual and 3) group- level bootstraps,

the 4) region to be parcellated and 5) the secondary region (optional) to use as the basis of cross-

network clustering. Users can also define the affinity threshold and distance metric used in the

clustering procedures.

<u>5.1.3 Individual-Level-</u> First to reduce the dimensionality of the voxel wise time series, and to allow

for better computational efficiency, we apply a hierarchical feature agglomeration from Scikit

Learn with a neighboring voxel spatial constraint to each individual's data (Subcortical

Parcellation: 600 supervoxels; Cortical Parcellation: 1800 supervoxels). Then, a circular block

bootstrap procedure is applied to create resampled time series data from the original functional

image. We follow prior recommendations to set the block length to greater than 20 time steps

(Adolf et al., 2014), and more specifically, equal to the square root of the number of points in a

time series (Bellec et al., 2010; Bellec et al., 2008) Each of these resampled time series are then

clustered using the clustering technique of choice. Currently k-means, Ward's criterion

hierarchical agglomerative, spectral clustering, and Gaussian mixture models are implemented.

With each application of clustering, the cluster labels are transformed into an adjacency matrix of

0s and 1s representing whether a given voxel belongs to the same cluster as another voxel. Each

of these adjacency matrices are in supervoxel space, which differs between individuals. Therefore

the dimension reduction procedure is reversed to create a voxel wise adjacency matrix that puts

all individual-level data back into the same space. All adjacency matrices are averaged together

to create an individual mean adjacency matrix (IMA), which represents a summary of all clustering

assignments across all bootstraps. The IMA can be clustered to produce a final consensus cluster

assignment for each individual, or it can used in group-level bagging.

<u>5.1.4 Group Level-</u> PyBASC applies bagging to IMAs across individuals, recreating resampled

groups of IMAs from the original pool of participants. The IMAs for each group-level bootstrap are

averaged and another group adjacency matrix is created through clustering. The adjacency matrix

across all bootstraps are averaged to create a group mean adjacency matrix (GMA), and this

GMA is clustered to create the final group-level clustering. The GMA is the final output of the

group-level bagging, along with the cluster labels. While the IMA represents a summary of the

clusterings across all bootstraps for each individual, the GMA represents a summary of the

clustering across all bootstraps for the group. We compare each individual's IMA to the GMA as

a detailed way of assessing similarities between the individual and group-level clusterings.

1069

1070

1071

1072

1073

1074

1075

1076

1077

1078

1079

1080

5.2 Supplementary Results

GSP-HNU Difference Maps

1082

10 min   50 min

5.2.1- Here we we compare the voxelwise cluster assignment differences between the
Reference GSP dataset created with 400 bootstraps and the 10 and 50 minute HNU
parcellations. Bright blue corresponds to all comparisons being different between the two
parcellations across all replication samples with 400 bootstraps, and dark purple shows where
there are no differences between parcellations. We find that both 10 and 50 minute parcellations
mostly differ from the GSP in transition zones between parcels. In particular we see these
difference maps reveal a superior-inferior thalamic transition zone, and a putamen-pallidum
transition zone. Notably, the HNU 50 minute parcellation differs from the GSP reference in
differential classification of the caudate. Whereas the 50 minute HNU data clusters the bilateral
caudate into the same cluster, both the GSP and the 10 minute HNU data cluster the caudate
into separate, non-homologous clusters.

1094

1095

1096

HNU Repeatability Difference Maps

10 min   50 min

1097

5.2.2- Here we compare differences the HNU Replication and Reference parcellations. Bright
yellow corresponds to all comparisons being different between the two parcellations across all
replication samples with 400 bootstraps, and dark purple shows where there are no differences
between parcellations. Notably we see differentiation between reference and the 10 minute
parcellation is higher than the 50 minute replication set. Furthermore, we see a reprise of the
transition zones seen in S1, notably a clear superior-inferior transition, and a putamen-pallidum
transition as well.

1105

1106   5.2.3- Individual-level bagging improves between session reproducibility of individual-level
1107   parcellations across a range of bagging levels and range of scan times.. We compare the
1108   individual mean stability matrix for each participant (A, B) and the individualized cluster
1109   labels (C, D).

1110

1111

1112

5.2.4- Univariate Reliability in GSP with motion regressed out. Motion can be a source of highly
reproducible signal in MRI data. We wanted to make sure the impact of bagging wasn't being
driven by motion, and so we regressed out motion from each individual mean adjacency matrix
before calculating ICC. As was the case without motion regression, here we see that bagging
improves the ICC of parcellations. A,B,C show the top 50%, 75%, and 95% ICC values for the
individual-level mean adjacency matrices. Each point corresponds to the 50th, 75th, and 95th
percentile ICC values for the individual-level mean adjacency matrices for each of the 10 GSP
groups. D and E show the mean squared error within individuals and between individuals
respectively. We see that bagging improves ICC, it has a dramatic impact on both MSE and
MSR, with samples with the lowest drop in MSR showing the greatest pickup in ICC.

1123