Machine learning to classify animal species in camera trap images: applications in ecology

Michael A. Tabak[1,2], Mohammed S. Norouzzadeh[3], David W. Wolfson[1], Steven J. Sweeney[1], Kurt C. VerCauteren[4], Nathan P. Snow[4], Joseph M. Halseth[4], Paul A. Di Salvo[1], Jesse S. Lewis[5], Michael D. White[6], Ben Teton[6], James C. Beasley[7], Peter E. Schlichting[7], Raoul K. Boughton[8], Bethany Wight[8], Eric S. Newkirk[9], Jacob S. Ivan[9], Eric A. Odell[9], Ryan K. Brook[10], Paul M. Lukacs[11], Anna K. Moeller[11], Elizabeth G. Mandeville[2,12], Jeff Clune[3], Ryan S. Miller[1]

[1] Center for Epidemiology and Animal Health; United States Department of Agriculture; 2150 Centre Ave., Bldg B, Fort Collins, CO 80526
[2] Department of Zoology and Physiology; University of Wyoming; 1000 E. University Ave., Laramie, WY 52071
[3] Computer Science Department; University of Wyoming; 1000 E. University Ave., Laramie, WY 52071
[4] National Wildlife Research Center; United States Department of Agriculture; 4101 Laporte Ave., Fort Collins, CO 80521
[5] College of Integrative Sciences and Arts; Arizona State University; 66307 South Backus Mall, Mesa, AZ 85212
[6] Tejon Ranch Conservancy, 1037 Bear Trap Rd, Lebec, CA, 93243
[7] Savannah River Ecology Laboratory; Warnell School of Forestry and Natural Resources, University of Georgia; PO Drawer E, Aiken, SC 29802, USA
[8] Range Cattle Research and Education Center; Wildlife Ecology and Conservation; University of Florida; 3401 Experiment Station, Ona, Florida 33865
[9] Colorado Parks and Wildlife; 317 W. Prospect Rd., Fort Collins, CO 80526
[10] Department of Animal and Poultry Science; University of Saskatchewan; 5 Campus Drive, Saskatoon, SK, Canada S7N 5A8
[11] Wildlife Biology Program, Department of Ecosystem and Conservation Sciences; W.A. Franke College of Forestry and Conservation; University of Montana; 32 Campus Drive, Missoula, MT 59812
[12] Department of Botany; University of Wyoming; 1000 E. University Ave., Laramie, WY 52071

Running Title: Machine learning to classify animals

Word Count: 6,987 includes tables, figures, and references

Corresponding Authors:
Michael Tabak & Ryan Miller
Center for Epidemiology and Animal Health
United States Department of Agriculture
2150 Centre Ave., Bldg B
Fort Collins, CO 80526
+1-970-494-7272
Michael.a.tabak@aphis.usda.gov

Abstract

1. Motion-activated cameras ("camera traps") are increasingly used in ecological and

management studies for remotely observing wildlife and have been regarded as among the most

powerful tools for wildlife research. However, studies involving camera traps result in millions

of images that need to be analyzed, typically by visually observing each image, in order to

extract data that can be used in ecological analyses.

2. We trained machine learning models using convolutional neural networks with the ResNet-18

architecture and 3,367,383 images to automatically classify wildlife species from camera trap

images obtained from five states across the United States. We tested our model on an

independent subset of images not seen during training from the United States and on an out-of-

sample (or "out-of-distribution" in the machine learning literature) dataset of ungulate images

from Canada. We also tested the ability of our model to distinguish empty images from those

with animals in another out-of-sample dataset from Tanzania, containing a faunal community

that was novel to the model.

3. The trained model classified approximately 2,000 images per minute on a laptop computer

with 16 gigabytes of RAM. The trained model achieved 98% accuracy at identifying species in

the United States, the highest accuracy of such a model to date. Out-of-sample validation from

Canada achieved 82% accuracy, and correctly identified 94% of images containing an animal in

the dataset from Tanzania. We provide an R package (Machine Learning for Wildlife Image

Classification; MLWIC) that allows the users to A) implement the trained model presented here

and B) train their own model using classified images of wildlife from their studies.

4. The use of machine learning to rapidly and accurately classify wildlife in camera trap images

can facilitate non-invasive sampling designs in ecological studies by reducing the burden of

manually analyzing images. We present an R package making these methods accessible to

ecologists. We discuss the implications of this technology for ecology and considerations that

should be addressed in future implementations of these methods.

Keywords: artificial intelligence, camera trap, convolutional neural network, deep learning, deep

neural networks, image classification, machine learning, R package, remote sensing, wildlife

game camera

Introduction

An understanding of species' distributions is fundamental to many questions in ecology (MacArthur, 1984; Brown, 1995). Observations of wildlife can be used to model species distributions and population abundance and evaluate how these metrics relate to environmental conditions (Elith, Kearney, & Phillips, 2010; Tikhonov et al., 2017). However, developing statistically sound data for species observations is often difficult and expensive (Underwood, Chapman, & Connell, 2000) and significant effort has been devoted to correcting bias in more easily collected or opportunistic observation data (Royle & Dorazio, 2008; MacKenzie et al., 2017). Recently, technological advances have improved our ability to observe animals remotely. Sampling methods such as acoustic recordings, images from crewless aircraft (or "drones"), and motion-activated cameras that automatically photograph wildlife (i.e., "camera traps") are commonly used (Blumstein et al., 2011; O'Connell et al., 2011; Getzin et al., 2012). These tools offer great promise for increasing efficiency of observing wildlife remotely over large geographical areas with minimal human involvement and have made considerable contributions to ecology (Rovero et al., 2013; Howe et al., 2017). However, a common limitation is these methods lead to a large accumulation of data – audio and video recordings and images – which must be first classified in order to be used in ecological studies predicting occupancy or abundance (Swanson et al., 2015; Niedballa et al., 2016). The large burden of classification, such as manually viewing and classifying images from camera traps, often constrains studies by reducing the sampling intensity (e.g., number of cameras deployed), limiting the geographical extent and duration of studies. Recently, machine learning has emerged as a potential solution for automatically classifying recordings and images.

Machine learning methods have been used to classify wildlife in camera trap images with

varying levels of success and human involvement in the process. One application of a machine

learning approach has been to distinguish empty and non-target animal images from those

containing the target species to reduce the number of images requiring manual classification.

This approach has been generally successful, allowing researchers to remove up to 76% of

images containing non-target species (Swinnen et al., 2014). Development of methods to identify

several wildlife species in images has been more problematic. Yu et al. (2013) used sparse

coding spatial pyramid matching (Lazebnik, Schmid, & Ponce, 2006) to identify 18 species in

images, achieving high accuracy (82%), but their approach necessitates each training image to be

manually cropped, requiring a large time investment. Attempts to use machine learning to

classify species in images without manual cropping have achieved far lower accuracies: 38%

(Chen et al., 2014) and 57% (Gomez Villa, Salazar, & Vargas, 2017). However, more recently

Norouzzadeh et al. (2018) used convolutional neural networks with 3.2 million classified images

from camera traps to automatically classify 48 species of Serengeti wildlife in images with 95%

accuracy.

Despite these advances in automatically identifying wildlife in camera trap images, the

approaches remain study specific and the technology is generally inaccessible to most ecologists.

Training such models typically requires extensive computer programming skills and tools for

novice programmers (e.g., an R package) are limited. Making this technology available to

ecologists has the potential to greatly expand ecological inquiry and non-invasive sampling

designs, allowing for larger and longer-term ecological studies. In addition, automated

approaches to identifying wildlife in camera trap images have important applications in detecting

invasive species or sensitive species and improving their management.

We sought to develop a machine learning approach that can be applied across study sites and

provide software that ecologists can use for identification of wildlife in their own camera trap

images. Using over three million identified images of wildlife from camera traps from five

locations across the United States, we trained and tested deep learning models that automatically

classify wildlife. We provide an R package (Machine Learning for Wildlife Image Classification;

MLWIC) that allows researchers to classify camera trap images from North America or train

their own machine learning models to classify images. We also address some basic issues in the

potential use of machine learning for classifying wildlife in camera trap images in ecology.

Because our approach nearly eliminates the need for manual curation of camera trap images we

also discuss how this new technology can be applied to improve ecological studies in the future.

Materials and Methods

Camera trap images

Species in camera trap images from five locations across the United States (California, Colorado,

Florida, South Carolina, and Texas) were identified manually by researchers (see Appendix S1

for a description of each field location). Images were either classified by a single wildlife expert

or evaluated independently by two researchers; any conflicts were decided by a third observer

(Appendix S1). If any part of an animal (e.g., leg or ear) was identified as being present in an

image, this was included as an image of the species. This resulted in a total of 3,741,656

classified images that included 28 species or groups (see Table 1) across the study locations. We

present these images and their classifications for other scientists to use for model development as

the North American Camera Trap Images (NACTI) dataset. Images were re-sized to a resolution

of 256 x 256 pixels using a custom Python script before running models to increase processing

speed. A subset of images (approximately 10%) was withheld using conditional sampling to be

used for testing of the model (described below). This resulted in 3,367,383 images used to train

the model and 374,273 images used for testing.

Machine learning process

Supervised machine learning algorithms use training examples to "learn" how to complete a task

(Mohri, Rostamizadeh, & Talwalkar, 2012; Goodfellow, Bengio, & Courville, 2016). One

popular class of machine learning algorithms is artificial neural network, which loosely mimics

the learning behavior of the mammalian brain (Gurney, 2014; Goodfellow et al., 2016). An

artificial neuron in a neural network has several inputs, each with an associated weight. For each

artificial neuron, the inputs are multiplied by the weights, summed, and then evaluated by a non-

linear function, which is called the activation function (e.g., Sigmoid, Tanh, or Sine). Usually

each neuron also has an extra connection with a constant input value of 1 and its associated

weight, called a "bias," for neurons. The result of the activation function can be passed as input

into other artificial neurons or serve as network outputs. For example, consider an artificial

neuron with three inputs (I_1, I_2, and I_3); the output (θ) is calculated based on:

$$\theta = Tanh(w_1 I_1 + w_2 I_2 + w_3 I_3 + w_4 I_b) \text{ (eqn 1)},$$

where w_1, w_2, w_3 and w_4 are the weights associated with each input, I_b is the bias, and $Tanh(x)$

is the activation function (Fig. 1). To solve complex problems multiple neurons are needed, so

we put them into a network. We arrange neurons in a hierarchical structure of layers; neurons in

each layer take input from the previous layer, process them, and pass the output to the next layer.

Then, an algorithm, called backpropagation (Rumelhart, Hinton, & Williams, 1986), tunes the

parameters of the neural network (weights and bias values) enabling it to produce the desired

output when we feed an input to the network. This process is called training. To adjust the

weights, we define a loss function as a measure of the difference between the predicted (current)

output of the neural network and the correct output (Y). The loss function (L) is the mean

squared error:

$$L = \frac{1}{n}\sum_{i=1}^{n}(Y - \theta)^2 \text{ (eqn2).}$$

We compute the contribution of each weight to the loss value ($\frac{dL}{dW}$) using the chain rule in

calculus. Weights are then adjusted so the loss value is minimized. In this "weight update" step,

all the weights are updated to minimize L:

$$w_i = w_{i\,initial} - \eta\frac{dL}{dW} \text{ (eqn 3),}$$

where η is the learning rate and is chosen by the scientist. A higher η indicates larger steps are

taken per training sample, which may be faster, but a value that is too large will be imprecise and

can destabilize learning. After adjusting the weights, the same input should result in an output

that is closer to the desired output. For more details of backpropagation and training, see

Goodfellow et al., 2016.

In fully connected neural networks, each neuron in every layer is connected to (provides input to)

every neuron in the next layer. Conversely, in convolutional neural networks, which are inspired

by the retina of the human eye, several convolutional layers exist in which each neuron only

receives input from a small sliding subset of neurons ("receptive field") in the previous layer. We

call the output of a group of neurons the "feature map," which depicts the response of a neuron

to its input. When we use convolutional neural networks to classify animal images, the receptive

field of neurons in the first layer of the network is a sliding subset of the image. In subsequent

layers, the receptive field of neurons is a sliding subset of the feature map from previous layers.

We interpret the output of the final layer as the probability of the presence of species in the

image. A softmax function is used at the final layer to ensure that the outputs sum to one. For

more details on this process, see Simonyan & Zisserman, 2014.

Deep neural networks (or "deep learning") are artificial networks with several (> 3) layers of

structure. In our example, we provided a set of animal images from camera traps of different

species and their labels (species identifiers) to a deep neural network, and the model learned how

to identify species in other images that were not used for training. Once a model is trained, we

can use it to classify new images. The trained model uses the output of the final layer in the

network to assign a confidence to each species or group it evaluates, where the total confidence

assigned to all groups for each image sums to one. Generally, the majority of the confidence is

attributed to one group, the "top guess." For example, for 90% of the images in our test dataset,

the model attributed > 95% confidence to the top guess. Therefore, for the purpose of this paper,

we mainly discuss accuracy with regard to the top guess, but our R package presents the five

groups with the highest confidence, the "top five guesses," and the confidence associated with

each guess.

Neural network architecture refers to several details about the network including the type and

number of neurons and the number of layers. We trained a deep convolutional neural network

(ResNet-18) architecture because it has few parameters, but performs well; see He et al. (2016)

for full details of this architecture. Networks were trained in the TensorFlow framework (Adabi

et al., 2016) using Mount Moran, a high performance computing cluster (Advanced Research

Computing Center, 2012). First, since invasive wild pigs (*Sus scrofa*) are a subject of several of

our field studies, we developed a "Pig/no pig" model, in which we determined if a pig was either

present or absent in the image. In the "Species Level" model, we identified images to the species

level when possible. Specifically, if our classified image dataset included < 2,000 images for a

species, it was either grouped with taxonomically similar species (by genera, families, or order),

or it was not included in the trained model (Table 1). In the "Group Level" model, species were

grouped with taxonomically similar species into classifications that had ecological relevance

(Appendix S2). The Group Level model contained fewer groups than the Species Level model,

so that more training images were available for each group. We used both models because if the

Species Level model had poor accuracy, we predicted the Group Level model would have better

accuracy since more training images would be available for several groups. As it is the most

broadly applicable model and is the one implemented in the MLWIC package, we will mainly

discuss the Species Level model here, but show results from the Group Level to demonstrate

alternative approaches.

For each of the three models, 90% of the classified images for each species or group were used

to train the model and 10% of the images were used to test it in most cases. However, we wanted

to evaluate the model's performance for each species present at each study site, so we altered

training-testing allocation for the rare situations where there were few classified images of a

species at a site. Specifically, with 1-9 classified images for a species at a site, we used all of

these images for testing and none for training; for site-species pairs with 10-30 images, 50%

were used for training and testing; and for > 30 images per site for each species, 90% were

allocated to training and 10% to testing (Appendices S3 - S7 show the number of training and

test images for each species at each site).

Evaluating model accuracy

Model testing was conducted by running the trained model on the withheld images that were not used to train the model. Accuracy (A) was assessed as the proportion of images in the test dataset (N) that were correctly classified (C) by the top guess ($A = C/N$). Top 5 accuracy ($A5$) was defined as the proportion of images in the test dataset that were correctly classified by any of the top 5 assignments ($C5$; $A5 = C5/N$). For each species or group we calculated the rate of false positives (FP) as the proportion of images classified as this species or group ($N_{model\ group}$) by the model's top guess that contained a different species according to human observers ($N_{true\ other}$; $FP = N_{true\ other}/N_{model\ group}$). We calculated the rate of false negatives for each species (FN) as the proportion of images observers classified as a specific species or group ($N_{true\ group}$) that the model's top guess classified differently ($N_{model\ other}$; $FN = N_{model\ other}/N_{true\ group}$). This assumes the observers were correct in their classification of images. We fit generalized additive models (GAMs) to the relationship between accuracy and the logarithm (base 10) of the number of images used to train the model. We also calculated the accuracy and rates of error specific to each of the five data sets from which images were acquired.

To evaluate how the model would perform for a completely new study site in North America, we used a dataset of 5,900 classified images of ungulates (moose, cattle, elk, and wild pigs) from Saskatchewan, Canada by running the Species Level model on these images. We also evaluated the ability of the model to operate on images with a completely different species community (from Tanzania) to determine the model's ability to correctly classify images as having an animal

or being empty when encountering new species that it has not been trained to recognize. This

was done using 3.2 million classified images from the Snapshot Serengeti dataset (Swanson et

al., 2015).

Results

Our models performed well, achieving $\geq 97.5\%$ accuracy of identifying the correct species with

the top guess (Table 2). The model determining presence or absence of wild pigs had the highest

accuracy of all of our models (98.6%; Pig/no pig; Table 2). For the Species Level and Group

Level models, the top 5 accuracy was $> 99.9\%$. The model confidence in the correct answer

varied, but was mostly $> 95\%$; see Fig. 2 for confidences for each image for three example

species. Supporting a similar finding for camera trap images in Norouzzadeh et al. (2018), and a

general trend in deep learning (Goodfellow et al., 2016), species and groups that had more

images available for training were classified more accurately (Fig. 3, Table 1). GAMs relating

the number of training images with accuracy predicted 95% accuracy could be achieved when

approximately 71,000 training images were available for a species or group. However, these

models were not perfect fits to the data, and for several species and groups, 95% accuracy was

achieved with fewer than 70,000 images (Fig. 3). We found there was not a large effect of

daytime vs. nighttime on accuracy in the Species Level model as daytime accuracy was 98.2%

and nighttime accuracy was 96.6%. The top 5 accuracies for both times of day were $\geq 99.9\%$.

When we subsetted the testing dataset by study site, we found that site-specific accuracies ranged

from 90-99% (Appendices S3 - S7). The model performed poorly $(0 – 22\%$ accuracy) for species

in the four instances when the model did not include training images from that site (when < 10

classified images were available for the species/study site combination; Appendices S3 - S7).

Upon further investigation, we found these images were difficult to classify manually. For

example, striped skunks in Florida were misclassified in both of the images from this study site

(Appendix S5). These images both contained the same individual at the same camera, and most

wildlife experts would not classify it as a skunk (Appendix S8).

When we conducted out-of-sample validation by using our model to evaluate images of

ungulates from Canada, we achieved an overall accuracy of 81.8% with a top 5 accuracy of

90.9%. When we tested the ability of our model to accurately predict presence or absence of an

animal in the image using the Serengeti Snapshot dataset, we found that 85.1% were classified

correctly as empty, while 94.3% of images containing an animal were classified as containing an

animal. Our trained model was capable of classifying approximately 2,000 images per minute on

a Macintosh laptop with 16 gigabytes (GB) of RAM.

Discussion

To our knowledge, our Species Level model achieved the highest accuracy (97.5%) to date in

using machine learning for wildlife image classification (a recent paper achieved 95% accuracy;

Norouzzadeh et al., 2018). This model performed almost as well during the night as during the

day (accuracy = 97% and 98%, respectively). We provide this model as an R package (MLWIC),

which is especially useful for researchers studying the species and groups available in this

package (Table 1) in North America, as it performed well in classifying ungulates in an out-of-

sample test of images from Canada. The model can also be valuable for researchers studying

other species by removing images without any animals from the dataset before beginning manual

classification, as we achieved high accuracy in separating empty images from those containing

animals in a dataset from Tanzania. This R package can also be a valuable tool for any

researchers that have classified images, as they can use the package to train their own model that

can then classify any subsequent images collected.

Optimizing camera trap use and application in ecology

The ability to rapidly identify millions of images from camera traps can fundamentally change

the way ecologists design and implement wildlife studies. Camera trap projects amass large

numbers of images which require a sizable time investment to manually classify. For example,

the Snapshot Serengeti project (Swanson et al., 2015) amassed millions of images and employed

28,000 volunteers to manually classify 1.5 million images (Swanson et al., 2016; Palmer et al.,

2017). We found researchers can classify approximately 200 images per hour. Therefore, a

project that amasses 1 million images would require 10,000 hours for each image to be doubly

observed. To reduce the number of images that need to be classified manually, ecologists using

camera traps often limit the number of photos taken by reducing the size of camera arrays,

reducing the duration of camera trap studies, and imposing limits on the number of photos a

camera takes (Kelly et al., 2008; Scott et al., 2018). This constraint can be problematic in many

studies, particularly those addressing rare or elusive species that are often the subject of

ecological studies (O'Connell et al., 2011), as these species often require more effort to detect

(Tobler et al., 2008). Using deep learning methods to automatically classify images essentially

eliminates one of the primary reasons camera trap arrays are limited in size or duration. The

Species Level model in our R package can accurately classify 1 million images in less than nine

hours with minimal human involvement.

Another reason to limit the number of photos taken by camera traps is storage limitations on

cameras (Rasambainarivo et al., 2017; Hanya et al., 2018). When classifying images manually,

we might try to use high resolution photos to improve technicians' abilities to accurately classify

images, but higher resolution photos require more storage on cameras. Our results show a model

can be accurately trained and applied using low-resolution (256 x 256 pixel) images, but many of

these images were re-sized from a higher resolution, which might contain more information than

those which originated at a low resolution. Nevertheless, we hypothesize a model can be

accurately trained using images from low resolution cameras, and our R package allows users

who have such images to test this hypothesis. If supported, this can make camera trap data

storage much more efficient. Typical cameras set for 2048 x 1536 pixel resolution will run out of

storage space when they reach approximately 1,250 photos per GB of storage. Taking low

resolution images instead can increase the number of photos stored per GB to about 10,000 and

thus decrease the frequency at which researchers must visit cameras to change storage cards by a

factor of eight. Minimizing human visitation also will reduce human scents and disturbances that

could deter some species from visiting cameras. In the future, it may be possible to implement a

machine learning model on a game camera (Elias et al., 2017) that automatically classifies

images as empty or containing animals so that empty images are discarded immediately and not

stored on the camera. This type of approach could dramatically reduce the frequency with which

technicians need to visit cameras. Furthermore, if models effectively use low-resolution images,

it is not necessary for researchers to purchase high resolution cameras. Instead, researchers can

purchase lower cost, lower resolution cameras and allocate funding toward purchasing more

cameras and creating larger camera arrays.

Applications to management of invasive and sensitive species

By removing some of the major burdens associated with the use of camera traps, our approach can be utilized by ecologists and wildlife managers to conduct more extensive camera trapping surveys than were previously possible. One potential use is in monitoring the distribution of sensitive or invasive species. For example, the distribution of invasive wild pigs in North America is commonly monitored using camera traps. Humans introduce this species into new locations that are often geographically distant from their existing range (Tabak et al., 2017), which can quickly lead to newly-established populations. Camera traps could be placed in areas at risk for introduction and provide constant surveillance. An automated image classification model that simply 'looks' for pigs in images could monitor camera trap images and alert managers when images with pigs are found, facilitating removal of animals before populations establish. Additionally, after wild pigs have been eradicated from a region, camera traps could be used to monitor the area to verify eradication success and automatically detect re-colonization or reintroduction events. Similar approaches can be used in other study systems to more rapidly detect novel invasive species arrivals, track the effects of management interventions, monitor species of conservation concern, or monitor sensitive species following reintroduction efforts.

Limitations

Using out-of-sample model validation on a dataset from Canada revealed a lower accuracy (82%) than at study sites from which our model was trained. Additionally, when we did not include images of species/site combinations in training the model, due to low sample sizes, the model performed poorly (Appendices S3 - S7; but these images were often difficult to classify

even by wildlife experts, Appendix S8). One potential explanation is the model evaluated both

the animal and the environment in the image and these are confounded in the species

identification (Norouzzadeh et al., 2018). Therefore, the model may have lower accuracies in

environments that were not in the training dataset. Ideally, the training dataset would include

training images representing the range of environments in which a species exists. Our model

includes training images from diverse ecosystems, making it relevant for classifying images from

many locations in North America. A further limitation is in our reported overall accuracy, which

is reported across all of the images that were available for testing, and we had considerable

imbalance in the number of images per species (Table 1). We provide accuracies for each

species, so the reader can more directly inspect model accuracy. Finally, our model was trained

using images that were classified by human observers, which are capable of making errors

(O'Connell et al., 2011; Meek, Vernes, & Falzon, 2013), meaning some of the images in our

training dataset were likely misclassified. Supervised machine learning algorithms require such

training examples, and therefore we are unaware of a method for training such models without

the potential for human classification error. Instead, we must acknowledge that these models will

make mistakes due to imperfections in both human observation and model accuracy.

Future directions

As this new technology becomes more widely available, ecologists will need to decide how it

will be applied in ecological analyses. For example, when using machine learning model output

to design occupancy and abundance models, we can incorporate accuracy estimates that were

generated when conducting model testing. The error of a machine learning model in identifying a

species is similar to the problem of imperfect detection of wildlife when conducting field

surveys. Wildlife are often not detected when they are present (false negatives) and occasionally

detected when they are absent (false positives); ecologists have developed models to effectively

estimate occupancy when data have these types of errors (Royle & Link, 2006; Guillera-Arroita

et al., 2017). We can use Bayesian occupancy and abundance models where the central

tendencies of the prior distributions for the false negative and false positive error rates are

derived from testing the machine learning model (e.g., values in Table 1). While we would

expect false positive rates in occupancy models to resemble the false positive error rates for the

machine learning model, false negative error rates would be a function of the both the machine

learning model and the propensity for some species to avoid detection by cameras when they are

present (Tobler et al., 2015).

Another area in need of development is how to group taxa when few images are available for the

species. We grouped species when few images were available for model training using an

arbitrary cut off of approximately 2,000 images per group (Table 1). We had few images of

horses (*Equus* spp.), but the model identified these images relatively well (93% accuracy),

presumably because they are phenotypically different from other species in our dataset. We also

had few images of opossums (*Didelphis virginiana*), but we did not group this species because it

is phenotypically different from other species in our dataset and was of ecological interest in our

studies; we achieved lower accuracy for this species (78%). We also included a group for rodents

from species for which we only had few images (*Erethizon dorsatum*, *Marmota flaviventris*,

Genomys spp., *Mus* spp., *Neotoma* spp., *Peromyscus* spp., *Tamais* spp., and *Rattus* spp.). The

model achieved relatively low accuracy for this group (79%), presumably because there were

few images for training (3,279) and members of this group are phenotypically different, making

it difficult for the model to train on this group. When researchers develop new machine learning

models, they will need to consider the available data, the species or groups in their study, and the

ecological question that the model will help address.

Here, we mainly focused on the species or class that the model predicted with the highest

confidence (the top guess), but in many cases researchers may want to incorporate information

from the model's confidence in the guess and additional model guesses. For example, if we are

interested in the highest overall accuracy, we could only consider images where the confidence

in the top guess is > 95%. If we subset the results from our model test in this manner, we remove

10% of the images, but total accuracy increases to 99.6%. However, if the objective of a project

is to identify rare species, researchers may want to focus on all images in which the model

predicts that species to be in the top 5 guesses (the 5 species or groups that the model predicts to

have the highest confidence). In our model test, the correct species was in the top 5 guesses in

99.9% of the images, indicating that this strategy may be viable.

We expect the performance of machine learning models to improve in the future (Jordan &

Mitchell, 2015), allowing ecologists to further exploit this technology. Our model required

manual identification of many images to obtain high levels of accuracy (Table 1). Our model was

also limited in that we were only able to classify the presence or absence of species; we were not

able to determine the number of individuals, their behavior, or demographics. Similar machine

learning models are capable of including the number of animals and their behavior in

classifications (Norouzzadeh et al., 2018), but we could not include these factors because they

were rarely recorded manually in our dataset. As machine learning techniques improve, we

expect models will require fewer manually classified images to achieve high accuracy in

identifying species, counting individuals, and specifying demographic information. Furthermore,

as scientists begin projects intending to use machine learning to classify images, they may be

more willing to spend time extracting detailed information from fewer images instead of

obtaining less information from all images. This development would create a larger dataset of

information from images that can be used to train models. As machine learning algorithms

improve and ecologists begin considering this technology when they design studies, we think

that many novel applications will arise.

As camera trap use is a common approach to studying wildlife worldwide, there are likely now

large datasets of classified images. If scientists work together and share these datasets, we can

create large image libraries that span continents (Steenweg et al., 2017); we may eventually be

able to train a machine learning model that can identify many global species and be used by

researchers globally. Further, effectively sharing images and classifications can potentially be

integrated with a web-based platform, similar to that employed by Camera Base

(http://www.atrium-biodiversity.org/tools/camerabase) or eMammal (https://emammal.si.edu/).

Acknowledgements

We thank the hundreds of volunteers and employees who manually classified images and

deployed camera traps. We thank Dan Walsh for facilitating cooperation amongst groups.

Camera trap projects were funded by the U.S. Department of Energy under award # DE-

EM0004391 to the University of Georgia Research Foundation; USDA Animal and Plant Health

Inspection Service, National Wildlife Research Center and Center for Epidemiology and Animal

Health; Colorado Parks and Wildlife; Canadian Natural Science and Engineering Research

Council; University of Saskatchewan; and Idaho Department of Game and Fish.

Data Accessibility

The trained Species Level model is available in the R package MLWIC from github

(https://github.com/mikeyEcology/MLWIC). We provide the 3.7 million classified images as the

North American Camera Trap Images (NACTI) dataset in a digital repository.

Author Contributions

MAT, RSM, KCV, NPS, SJS, and DWW conceived of the project; DWW, JSL, MAT, RKB,

BW, PAD, JCB, MDW, BT, PES, NPS, KCV, JMH, ESN, JSI, EAO, RKB, PML, and AKM

oversaw collection and manual classification of wildlife in camera trap images from the study

sites; MSN and JC developed and programmed the machine learning models; MAT led the

analyses and writing of the R package; EGM assisted with R package development and

computing; MAT and RSM led the writing. All authors contributed critically to drafts and gave

final approval for submission.

References

Adabi, M., Barhab, P., Chen, J., Chen, Z., Davis, A., Dean, J., … Zheng, X. (2016). TensorFlow:
    a system for large-scale machine learning (Vol. 16, pp. 265–283). Presented at the 12th
    USENIX Symposium on Operating Systems Design and Implementation, USENIX
    Association.

Advanced Research Computing Center. (2012). *Mount Moran: IBM System X cluster*. Laramie,
    WY: University of Wyoming. https://arcc.uwyo.edu/guides/mount-moran

Blumstein, D. T., Mennill, D. J., Clemins, P., Girod, L., Yao, K., Patricelli, G., … Kirschel, A.

N. G. (2011). Acoustic monitoring in terrestrial environments using microphone arrays:

applications, technological considerations and prospectus: Acoustic monitoring. *Journal*

of Applied Ecology, *48*(3), 758–767. doi:10.1111/j.1365-2664.2011.01993.x

Brown, J. H. (1995). *Macroecology*. University of Chicago Press.

Chen, G., Han, T. X., He, Z., Kays, R., & Forrester, T. (2014). Deep convolutional neural

network based species recognition for wild animal monitoring (pp. 858–862). IEEE

International Conference on Image Processing (ICIP). doi:10.1109/ICIP.2014.7025172

Elias, A. R., Golubovic, N., Krintz, C., & Wolski, R. (2017). Where's the bear?: automating

wildlife image processing using IoT and Edge Cloud Systems (pp. 247–258). ACM

Press. doi:10.1145/3054977.3054986

Elith, J., Kearney, M., & Phillips, S. (2010). The art of modelling range-shifting species.

Methods in Ecology and Evolution, *1*(4), 330–342. doi:10.1111/j.2041-

210X.2010.00036.x

Getzin, S., Wiegand, K., & Schöning, I. (2012). Assessing biodiversity in forests using very

high-resolution images and unmanned aerial vehicles. *Methods in Ecology and Evolution*,

3(2), 397–404. doi:10.1111/j.2041-210X.2011.00158.x

Gomez Villa, A., Salazar, A., & Vargas, F. (2017). Towards automatic wild animal monitoring:

Identification of animal species in camera-trap images using very deep convolutional

neural networks. *Ecological Informatics*, *41*, 24–32. doi:10.1016/j.ecoinf.2017.07.004

Goodfellow, I., Bengio, Y., & Courville, A. (2016). *Deep Learning* (1st ed.). Cambridge,

Massachusetts: MIT Press.

Guillera-Arroita, G., Lahoz-Monfort, J. J., van Rooyen, A. R., Weeks, A. R., & Tingley, R.

(2017). Dealing with false-positive and false-negative errors about species occurrence at

multiple levels. *Methods in Ecology and Evolution*, *8*(9), 1081–1091. doi:10.1111/2041-

210X.12743

Gurney, K. (2014). *An Introduction to Neural Networks* (1st ed.). London: CRC Press. Retrieved

from https://www.taylorfrancis.com/books/9781482286991

Hanya, G., Otani, Y., Hongo, S., Honda, T., Okamura, H., & Higo, Y. (2018). Activity of wild

Japanese macaques in Yakushima revealed by camera trapping: Patterns with respect to

season, daily period and rainfall. *PLOS ONE*, *13*(1), e0190631.

doi:10.1371/journal.pone.0190631

He, K., Zhang, X., Ren, S., & Sun, J. (2016). Deep Residual Learning for Image Recognition. In

Proceedings of the IEEE conference on computer vision and pattern recognition (pp.

770–778). IEEE. doi:10.1109/CVPR.2016.90

Howe, E. J., Buckland, S. T., Després-Einspenner, M.-L., & Kühl, H. S. (2017). Distance

sampling with camera traps. *Methods in Ecology and Evolution*, *8*(11), 1558–1565.

doi:10.1111/2041-210X.12790

Jordan, M. I., & Mitchell, T. M. (2015). Machine learning: trends, perspectives, and prospects.

Science, *349*(6245), 255–260. doi:10.1126/science.aaa8415

Kelly, M. J., Noss, A. J., Di Bitetti, M. S., Maffei, L., Arispe, R. L., Paviolo, A., … Di Blanco,

Y. E. (2008). Estimating Puma Densities from Camera Trapping across Three Study

Sites: Bolivia, Argentina, and Belize. *Journal of Mammalogy*, *89*(2), 408–418.

doi:10.1644/06-MAMM-A-424R.1

Lazebnik, S., Schmid, C., & Ponce, J. (2006). Beyond bags of features: spatial pyramid matching

for recognizing natural scene categories. In *Computer vision and pattern recognition*

(Vol. 2, pp. 2169–2178). New York: IEEE.

MacArthur, R. H. (1984). *Geographical ecology: patterns in the distribution of species*.

Princeton, New Jersey: Princeton University Press.

MacKenzie, D. I., Nichols, J. D., Royle, J. A., Pollock, K. H., Bailey, L. L., & Hines, J. E.

(2017). *Occupancy Estimation and Modeling: Inferring Patterns and Dynamics of*

Species Occurrence (2nd ed.). London, UK: Academic Press.

Meek, P. D., Vernes, K., & Falzon, G. (2013). On the reliability of expert identification of small-

medium sized mammals from camera trap photos. *Wildlife Biology in Practice*, *9*(2).

doi:10.2461/wbp.2013.9.4

Mohri, M., Rostamizadeh, A., & Talwalkar, A. (2012). *Foundations of Machine Learning*. MIT

Press.

Niedballa, J., Sollmann, R., Courtiol, A., & Wilting, A. (2016). camtrapR : an R package for

efficient camera trap data management. *Methods in Ecology and Evolution*, *7*(12), 1457–

1462. doi:10.1111/2041-210X.12600

Norouzzadeh, M. S., Nguyen, A., Kosmala, M., Swanson, A., Palmer, M. S., Packer, C., &

Clune, J. (2018). Automatically identifying, counting, and describing wild animals in

camera-trap images with deep learning. *Proceedings of the National Academy of*

Sciences, 201719367. doi:10.1073/pnas.1719367115

O'Connell, A. F., Nichols, J. D., & Karanth, K. U. (Eds.). (2011). *Camera traps in animal*

ecology: methods and analyses. Tokyo ; New York: Springer.

Palmer, M. S., Fieberg, J., Swanson, A., Kosmala, M., & Packer, C. (2017). A 'dynamic'

landscape of fear: prey responses to spatiotemporal variations in predation risk across the

lunar cycle. *Ecology Letters*, *20*(11), 1364–1373. doi:10.1111/ele.12832

Rasambainarivo, F., Farris, Z. J., Andrianalizah, H., & Parker, P. G. (2017). Interactions between

carnivores in Madagascar and the risk of disease transmission. *EcoHealth*, *14*(4), 691–

703. doi:10.1007/s10393-017-1280-7

Rovero, F., Zimmermann, F., Bersi, D., & Meek, P. (2013). 'Which camera trap type and how

many do I need?' A review of camera features and study designs for a range of wildlife

research applications. *Hystrix, the Italian Journal of Mammalogy*, *24*(2), 1–9.

Royle, J. A., & Dorazio, R. M. (2008). *Hierarchical modeling and inference in ecology*. New

York: Academic Press.

Royle, J. A., & Link, W. A. (2006). Generalized site occupancy models allowing for false

positive and false negative errors. *Ecology*, *87*(4), 835–841.

Rumelhart, D. E., Hinton, G. E., & Williams, R. J. (1986). Learning representations by back-

propagating errors. *Nature*, *323*(6088), 533–536. doi:10.1038/323533a0

Scott, A. B., Phalen, D., Hernandez-Jover, M., Singh, M., Groves, P., & Toribio, J.-A. L. M. L.

(2018). Wildlife presence and interactions with chickens on Australian commercial

chicken farms assessed by camera traps. *Avian Diseases*, *62*(1), 65–72.

doi:10.1637/11761-101917-Reg.1

Simonyan, K., & Zisserman, A. (2014). Very deep convolutional networks for large-scale image

recognition. *ArXiv:1409.1556 [Cs]*. Retrieved from http://arxiv.org/abs/1409.1556

Steenweg, R., Hebblewhite, M., Kays, R., Ahumada, J., Fisher, J. T., Burton, C., … Rich, L. N.

(2017). Scaling-up camera traps: monitoring the planet's biodiversity with networks of

remote sensors. *Frontiers in Ecology and the Environment*, *15*(1), 26–34.

doi:10.1002/fee.1448

Swanson, A., Kosmala, M., Lintott, C., & Packer, C. (2016). A generalized approach for

producing, quantifying, and validating citizen science data from wildlife images.

Conservation Biology, *30*(3), 520–531. doi:10.1111/cobi.12695

Swanson, A., Kosmala, M., Lintott, C., Simpson, R., Smith, A., & Packer, C. (2015). Snapshot

Serengeti, high-frequency annotated camera trap images of 40 mammalian species in an

African savanna. *Scientific Data*, *2*, 150026. doi:10.1038/sdata.2015.26

Swinnen, K. R. R., Reijniers, J., Breno, M., & Leirs, H. (2014). A novel method to reduce time

investment when processing videos from camera trap studies. *PLoS ONE*, *9*(6), e98881.

doi:10.1371/journal.pone.0098881

Tabak, M. A., Piaggio, A. J., Miller, R. S., Sweitzer, R. A., & Ernest, H. B. (2017).

Anthropogenic factors predict movement of an invasive species. *Ecosphere*, *8*(6),

e01844. doi:10.1002/ecs2.1844

Tikhonov, G., Abrego, N., Dunson, D., & Ovaskainen, O. (2017). Using joint species

distribution models for evaluating how species-to-species associations depend on the

environmental context. *Methods in Ecology and Evolution*, *8*(4), 443–452.

doi:10.1111/2041-210X.12723

Tobler, M. W., Carrillo-Percastegui, S. E., Leite Pitman, R., Mares, R., & Powell, G. (2008). An

evaluation of camera traps for inventorying large- and medium-sized terrestrial rainforest

mammals. *Animal Conservation*, *11*(3), 169–178. doi:10.1111/j.1469-1795.2008.00169.x

Tobler, M. W., Zúñiga Hartley, A., Carrillo-Percastegui, S. E., & Powell, G. V. N. (2015).

Spatiotemporal hierarchical modelling of species richness and occupancy using camera

trap data. *Journal of Applied Ecology*, *52*(2), 413–421. doi:10.1111/1365-2664.12399

Underwood, A. ., Chapman, M. ., & Connell, S. . (2000). Observations in ecology: you can't

make progress on processes without understanding the patterns. *Journal of Experimental*

Marine Biology and Ecology, *250*(1–2), 97–115. doi:10.1016/S0022-0981(00)00181-7

Yu, X., Wang, J., Kays, R., Jansen, P. A., Wang, T., & Huang, T. (2013). Automated

identification of animal species in camera trap images. *EURASIP Journal on Image and*

Video Processing, *2013*(1). doi:10.1186/1687-5281-2013-52

Tables and Figures

Table 1: Accuracy of the Species Level model

Species or group name	Scientific name	Number of training images	Number of test images	Accuracy	Top 5 accuracy	False positive rate	False negative rate
Moose	*Alces alces*	8,967	997	0.98	1.00	0.02	0.02
Cattle	*Bos taurus*	1,817,109	201,903	0.99	1.00	0.01	0.01
Quail	*Callipepla californica*	2,039	236	0.90	0.96	0.11	0.10
Canidae	Canidae	20,851	2,321	0.89	0.99	0.08	0.11
Elk	*Cervus canadensis*	185,390	20,606	0.98	1.00	0.01	0.02
Mustelidae	Mustelidae	1,991	223	0.76	0.98	0.12	0.24
Corvid	Corvidae	4,037	452	0.79	1.00	0.15	0.21
Armadillo	*Dasypus novemcinctus*	8,926	993	0.87	0.99	0.08	0.13
Turkey	*Meleagris gallopavo*	3,919	447	0.88	1.00	0.12	0.12
Opossum	*Didelphis virginiana*	1,804	210	0.78	0.96	0.15	0.22

Horse	*Equus* spp.	2,517	281	0.93	0.99	0.05	0.07
Human	*Homo sapiens*	88,667	9,854	0.96	1.00	0.03	0.04
Rabbits	Leporidae	17,768	1,977	0.96	1.00	0.06	0.04
Bobcat	*Lynx rufus*	22,889	2,554	0.90	0.99	0.05	0.10
Striped skunk	*Mephitis mephitis*	10,331	1,154	0.95	0.99	0.03	0.05
Unidentified deer	*Odocoileus* spp.	86,502	9,613	0.96	1.00	0.02	0.04
Rodent	Rodentia	3,279	366	0.79	0.98	0.17	0.21
Mule deer	*Odocoileus hemionus*	76,878	8,543	0.98	1.00	0.03	0.02
White-tailed deer	*Odocoileus virginianus*	12,238	1,360	0.81	1.00	0.22	0.19
Raccoon	*Procyon lotor*	42,948	4,781	0.88	1.00	0.10	0.12
Mountain lion	*Puma concolor*	13,272	1,484	0.93	0.98	0.03	0.07
Squirrel	*Sciurus* spp.	59,072	6,566	0.96	1.00	0.05	0.04
Wild pig	*Sus scrofa*	287,017	31,893	0.97	1.00	0.02	0.03

	Vulpes vulpes and *Urocyon*						
Fox	*Cinereoargentus*	10,749	1,204	0.91	0.99	0.07	0.09
Black Bear	*Ursus americanus*	79,628	8,850	0.94	1.00	0.02	0.06
Vehicle		23,413	2,602	0.93	1.00	0.04	0.07
Bird	Aves	61,063	6,787	0.94	1.00	0.05	0.06
Empty		414,119	46,016	0.96	1.00	0.06	0.04
Total		3,367,383	374,273	0.98	1.00		

Table 2: Accuracy (across all images for all species) of the three deep learning tasks analyzed

Model	Accuracy (%)
Pig/no pig	98.6
Species Level	97.5
Group Level	97.8

Figure 1: Within an artificial neural network, inputs (I) are multiplied by their weights (w), summed, and then evaluated by a non-linear function, which also accounts for bias (I_b). The output (θ) can be passed as input into other neurons or serve as network outputs. Backpropagation involves adjusting the weights so that a model can provide the desired output.

Fig. 2: Histograms represent the confidence assigned by all of the top five guesses by the Species Level model for each of these three example species when it was present in an image. The dashed line represents 95% confidence; the majority of model-assigned confidences were greater than this value.

Fig. 3: Machine learning model accuracy increased with the size of the training dataset. Points represent each species or group of species. The line represents the result of generalized additive models relating the two variables.

Supporting Information

Appendix S1. Site descriptions for each of the study locations

Appendix S2. Accuracy of the Group Level for each species

Appendix S3. Accuracy of the Species Level model at the Tejon research site in California.

Appendix S4. Accuracy of the Species Level model in Colorado

Appendix S5. Accuracy of the Species Level model at Buck Island Ranch in Florida

Appendix S6. Accuracy of the Species Level model at the Camp Bullis Military Training Center in Texas

Appendix S7. Accuracy of the Species Level model at the Savannah River Ecology Laboratory in South Carolina

Appendix S8. Image classified as a striped skunk by humans, but cattle by the Species Level model