A regulatory-sequence classifier with a neural network for genomic information processing

Koh Onimaru[1,2,✉]**, Osamu Nshimura**[1,2]**, and Shigehiro Kuraku**[1,2]

[1]Phyloinformatics Unit, RIKEN Center for Life Science Technologies (CLST), 2-2-3 Minatojima-minamimachi, Chuo-ku,Kobe, 650-0047, Japan
[2]Laboratory for Phyloinformatics unit, RIKEN Center for Biosystems Dynamics Research (BDR), 2-2-3 Minatojima-minamimachi, Chuo-ku, Kobe, Hyogo, 650-0047, Japan.

Genotype-phenotype mapping is one of the fundamental challenges in biology. The difficulties stem in part from the large amount of sequence information and the puzzling genomic code, particularly of non protein-coding regions such as gene regulatory sequences. Recently, deep learning-based methods are shown to discern gene regulatory sequences from genomes. However, there is room for improvement in the prediction accuracy. Here, we devise newly designed convolution layers that process genomic sequence information more efficiently, and develop a software, DeepGMAP to train and compare different deep-learning based models (https://github.com/koonimaru/DeepGMAP). Firstly, we demonstrate that the new convolution layers, FRSS (forward- and reverse sequence scan) layers, enhance the predictive power for gene regulatory sequences. Secondly, we show problems in previous studies associated with data structures that causes overfitting. Finally, we show several visualization methods to obtain insights into the syntax of gene regulatory sequences.

gene regulatory sequence | convolutional neural network | DNase-seq | machine learning
Correspondence:
koh.onimaru@riken.jp

Introduction

In the last decade, the development of DNA sequencing technologies has been dramatically increasing the amount of genome sequence data derived from diverse species (1) to individual humans (2). The next demanding challenge is the deeper understandings of what genome sequences encode about phenotypes and how to extract functional information from them (3). Such sequence-based understandings would ultimately yield the predictability of phenotypes from genome sequences (i.e., genotype-phenotype mapping). While the syntax of protein-coding genes is well understood (thereby some extent of phenotypic consequences is predictable such as nonsense mutations), there is a big room to explore for the basic rules of non-coding sequences. Several projects including ENCODE (4–6), ROADMAP (7), and FANTOM (8) have accumulated epigenomic data to annotate further characteristics of non-coding sequences. However, the comprehensive understanding of the association between epigenomic signatures and sequence information remains limited.

Recently, this problem has been addressed by deep learning-based methods (9–11). In these studies, deep learning models, such as convolutional neural network (CNN) and recurrent neural network (RNN), are trained with input genomic sequences that are labeled by epigenomic data to predict functional non-coding sequences. Once trained, this type of classifiers can infer the effect of mutations in non-coding genomic regions from individual genome sequences. However, even though these deep learning-based classifications outperformed other methods, such as support vector machine (12), the accuracy of prediction is still far from satisfactory. In addition, as it is generally known, it remains elusive that what deep learning-based models learn and what kinds of "understandings" underlie their predictions (13, 14). In the present study, firstly, we demonstrate a CNN-based classifier that can out-perform state-of-art models. Secondly, we show problems in previous studies associated with data structures that causes overfitting. Finally, we show ways to open the black box of trained models, which potentially reveals the general syntax behind regulatory sequences.

Results

To improve the prediction accuracy for regulatory sequences, we devised a deep learning-based method that includes three main features: a) integrating information from forward and reverse DNA sequences; b) simplifying data structure; c) a new quality index to filter out low-quality data from a training data set.

As training data, we downloaded several alignment files of chromatin accessibility assays and ChIP-seq experiments from the ENCODE project, and regions enriched with reads were determined as peaks by MACS2 peak caller (15). These data were used to label genome sequences. We divided the genome sequence of mice and humans into 1000 base-pair (bp) windows, and converted the four letters of DNA symbols into one-hot vectors. To assign epigenomic signals, we labeled each window as 1 (signal positive) or 0 (signal negative) if it overlaps with a signal region (see Methods for details). To reduce a potential artifact caused by the boundaries of windows, we also added windows that are shifted by the half size of the windows to the 3' side (Fig. 1c; we refer to this window structure as 1-kbp window/0.5-kbp stride). These data were used to train convolutional neural network models (see Supplementary Fig. 1 for the overall scheme).

To find an effective architecture of neural networks, we first compared the performance of previously described models, such as CNN-based models (DeepSEA and Basset) and a CNN-RNN hybrid (DanQ; see Supplementary Table 1 for

Fig. 1. The forward- and reverse-sequence scan (FRSS) layers and data structures. a, Subdivision of genome sequences into windows, and assignment of epigenomic signals. A peak region (red rectangle) is determined from epigenomic data, and assigned as "1" to overlapping genomic regions (blue filled rectangle), otherwise "0" (blue empty rectangle). **b**, The architecture of the FRSS layers. An input sequence is scanned by the first convolution kernels and rotated kernels in parallel. After relu operation, pooling, and the second convolution, the two parallel outputs are combined through summation. **c**, Illustration of 180 degree rotation of kernels. In this example, a 9×4 kernel is trained to detect a sequence, AGCTAAAG (left). The geometric rotation of the kernel (right) results in the reverse complement of the original sequence.

the details of the models). As a quick benchmark, we trained them with a subset of mouse DNase-seq data (Supplementary Table 2) because DNase-seq data appear to include diverse regulatory elements (16). To reduce computation time, we limited the number of training epochs to one, which means that models were trained with the full data set only once. For evaluation, we used whole chromosome 2 sequence, which was excluded from training data sets, and calculated the prediction accuracy of models, using the following two scores, area under the receiver-operation curve (AUROC) and the precision-recall curve (AUPRC). Because AUROC is not a proper criterion when the large portion of data is negatively labeled, we considered AUPRC as a more important criterion (17). As a result, the DeepSEA architecture showed a better performance than Basset and DanQ (Table 1). The poor performance of DanQ seemed inconsistent with the previous report, but was probably due to the insufficient amount of training as the DanQ model required 60 epochs for a good performance (11).

Based on this result, we next explored better models by modifying the DeepSEA architecture. Firstly, as more stratified convolutional networks are known to perform better (18), we inserted an additional convolution layer between the third convolution layer and the first fully connected layer of the DeepSEA model (with a reduced kernel number in some layers and smaller pooling patches). As expected, the four-layer convolutions achieved a slightly better accuracy (conv4 in Table 1). We next focused on the characteristic of genome sequences—the forward and reverse strands. The information on reverse strand sequences was ignored or used as independent data in previous studies. However, for example, transcription factors with leucine zipper and helix-loop-helix

domains bind both strands through dimerization, which results in palindromic binding motifs (19, 20). Inspired by this fact, we devised a set of layers that can integrate information from the both strands (Fig. 1 and Methods). We arranged the one-hot vectors that represent AGCT in a symmetric manner so that a 180-degree rotation of the one-hot vectors results in a reverse complementary sequence (Fig. 1b). Thus, reverse-sequence information can be processed by rotating the kernels 180 degrees. The hidden layers derived from the two strands are combined by an element-wise addition after the second convolution. We named these two layers as FRSS (forward- and reverse-sequence scan) layers. The replacement of the first two convolutional layers in the DeepSEA model with FRSS (conv3-FRSS in Table 1) improved the accuracy of prediction more than the simple addition of a convolution layer (conv4). Moreover, a four-layer convolution model with FRSS achieved higher AUPRC scores than the other models (conv4-FRSS in Table 1 and see Supplementary Fig. 2 for a visual comparison). Raising the kernel numbers of each convolution layers also slightly improved the performance (conv4-FRSS+ in Table 1), but also increased computation time (the right most column in Table 1). We also found that the FRSS layers increased the learning efficiency of the DanQ model by a level comparable with conv4-FRSS (DanQ-FRSS in Table 1). These results were consistently reproduced by repeated training and testing (Supplementary Table 3), indicating that the benchmark is robust against random initialization. Together, these results show that the FRSS layers enhance the predictive power of deep learning-based models.

Next, we examined the structure and quality of training data using the conv4-FRSS model. In some of previous studies,

Table 1. A performance comparison between models

	129_ES_E14		forebrain E11.5		forelimb E11.5		mean		time[b]
	AUROC	AUPRC	AUROC	AUPRC	AUROC	AUPRC	AUROC	AUPRC	
DeepSEA	0.9234	0.6038	0.9141	0.6380	0.9315	0.5734	0.9230	0.6051	0.1773
Basset	0.9085	0.5796	0.9107	0.6280	0.9175	0.5476	0.9123	0.5851	0.0847
DanQ	0.9057	0.5785	0.9076	0.6214	0.9046	0.5164	0.9059	0.5721	0.4586
DanQ block[a]	0.9053	0.5699	0.9063	0.6168	0.9030	0.5031	0.9049	0.5633	0.4832
conv4	0.9300	0.6234	0.9146	0.6426	0.9351	0.5884	0.9266	0.6181	0.2548
conv3-FRSS	0.9364	0.6447	0.9171	0.6496	0.9421	0.6098	0.9319	0.6347	0.3636
conv4-FRSS	**0.9414**	**0.6571**	**0.9178**	**0.6520**	**0.9476**	**0.6280**	**0.9356**	**0.6457**	0.3729
conv4-FRSS+	**0.9418**	**0.6631**	**0.9183**	**0.6549**	**0.9475**	**0.6347**	**0.9359**	**0.6509**	0.5802
DanQ-FRSS	0.9365	0.6523	0.9162	0.6485	0.9453	0.6222	0.9327	0.6410	0.7905

[a]Tensorflow has several LSTM cells, and this model uses LSTMBlockCell, and the above uses LSTMCell. [b]the mean time (second) of 20 minibatch updates.

Table 2. A performance comparison between data structures

Data structure	chromosome 2 (true test)		chromosome 1 (overfitting test)	
	AUROC	AUPRC	AUROC	AUPRC
DeepSEA-type	0.9623	0.4841	0.9694	0.4741
1 kb window/0.5 kb stride[a]	0.9356	0.6457	0.9453	0.6293
1 kb window/0.4 kb stride	0.9352	0.6528	0.9457	0.6386
1 kb window/0.3 kb stride	**0.9398**	**0.6570**	**0.9515**	**0.6618**
1 kb window/0.2 kb stride	0.9397	0.6530	0.9581	0.6962
1 kb window/0.1 kb stride	0.9368	0.6396	0.9689	0.7757
Hotspot peaks	0.9287	0.6267	-	-

The mean values of the three mouse DNase-seq data are shown. The columns under chromosome 2 are the results of true tests (the higher is better). The columns under chromosome 1 are overfitting tests (if the scores are higher than those of true tests, that is the sign of overfitting). [a]The same data with the mean values of conv4-FRSS in Table 1.

epigenetic signals were distributed into 200 base-pair (bp) windows of genome sequences and 400 bp extra-sequences were added to the left and right sides of windows (10) (we call this DeepSEA-type data in this study; Fig. 1c). For comparison, we trained conv4-FRSS with the DeepSEA-type data structure. As a result, training with the DeepSEA-type data showed a higher AUROC, but a lower AUPRC (DeepSEA-type in Table 2). The high value of the AUROC is probably attributed to an increase in negative labels. In addition, we tried several window and stride sizes, and found that models can be trained most efficiently with 1 kbp-window and 0.3 kbp-stride data. As shown in Table 2, training with small-sized strides such as 0.1 and 0.2kbp (and also DeepSEA-type data) yielded higher AUPRC scores when tested by chromosome 1 sequence, which was included in the training data, than tested by the test data set (chromosome 2, which was excluded from the training data), indicating overfitting to repeatedly appearing sequences in the training data set. This result presumably explains unusually high AUPRC scores reported by Min, X. et al. 2017 (21), which is inconsistent with Zhou & Troyanskaya 2015 (10)). Because Min, X. et al. 2017 trained CNN-based classifiers with 2-bp stride data and evaluated their model by re-sampling training data, the high AUPRCs in their report seemed to result from overfitting. We next examined peak callers. While we applied MACS2 to de-termine peak regions, previous studies used peak regions provided by the ENCODE project, which applied Hotspot (22) as a peak caller. As shown in Table 2, training with Hotspot peaks yields a lower prediction accuracy (in Table 2). These results indicate that the design of data structures is a critical factor to train models efficiently, and that the data augmenation by small striding, which several studies have applied (21, 23), is not an optimal strategy to train models.

In order to validate the above quick benchmark, we extended the list of training data. Firstly, we newly trained conv4-FRSS with the same set of 125 human DNase-seq data that Zhou & Troyanskaya, 2015 (10) used (Supplementary Table 2 for the lists of data), and found that conv4-FRSS significantly out-performed DeepSEA and DanQ (Fig. 2a and Supplementary Table 4;; the scores of DeepSEA and DanQ were obtained from their publications). We also trained conv4-FRSS with 365 and 93 of human and mouse DNase-seq peaks generated by MACS2, respectively (Supplementary Table 2 for the lists of data). As shown in Fig. 2a and Supplementary Table 4, we noticed that training with mouse data showed higher performance than with human data. The cause may be attributed to genome size difference, genetic variation (should be lower inbred mice), or species-specific trends such as gene density and GC contents. We also focused on CTCF ChIP-seq data, because (a) CTCF has a general function for

Fig. 2. Performance analyses of models with extended data sets. PRCs obtained from their original reports; conv4-FRSS, predictions trained with the same peak files, but a different data structure (1kbp-window/0.3kbp-stride); hg38 and mm10 data, 361 and 93 DNase-seq data sets generated by the MACS2 peak caller; filtered hg38 and mm10 data, DNase-seq data with high cFRiPs. p, two-sided Wilcoxon–Mann–Whitney test. Boxes, the lower to upper quantile values of the data; orange lines, the median; whiskers, the range of the data (Q1-IQR×1.5 and Q3-IQR×1.5 for the lower and upper bounds, respectively); flier points, those past the end of the whiskers. c, An example of CTCF binding site predictions on HoxD cluster of mice and dogs. Regions with prediction values >=0.2 are visualized. Blue bars, CTCF binding sites predicted by conv4FRSS (the bluer is more probable); mouse/dog liver CTCF, alignment data from ENCFF627DYN and ERR022304 (24), respectively; CTCF motif (FIMO), sites that are detected by FIMO (black boxes, p<=1e-4; gray boxes, 1e-4 <p<=1e-3); red rectangles, a CTCF peak that is present in mouse genome (solid rectangle) but not in dog genome (dashed rectangle). d, Scatter plots of FRiP and corrected FRiP with AUPRCs (top panels) and peak numbers (bottom panels). corr., Spearman correlation.

genome organization, (b) ENCODE releases plenty of CTCF data in mice and humans, and (c) as seen in the AUPRC scores of DeepSEA (Supplementary Fig. 3; re-analyzed data from Zhou Troyanskaya, 2015 (10)), the prediction accuracy highly depends on the target of ChIP-seq, and that of CTCF is the highest among transcription factors. As a result, the conv4-FRSS model was efficiently trained with both human and mouse CTCF data, and scored more than 0.70 of AUPRC on median (Fig. 2b, and 2c for a visual comparison between predictions and original signals). A comparison between the model predictions and CTCF motif regions detected by FIMO (25) [CTCF motif (FIMO) in Fig. 2c] shows that the model can predict CTCF binding regions where the canonical CTCF motif is not located. Furthermore, using the dog genome (CanFam3.1), we performed a cross-species prediction of CTCF binding regions with the model trained solely with mouse data. As shown in the bottom panel of Fig. 2c, the model predictions match with the real CTCF signals of dog liver (24) and detect species-specific differences (red rectangles in Fig. 2c), indicating the generality of the model. Together, we conclude that conv4-FRSS is applicable to diverse data.

In the above training with extended data set, we suspected that several classes with low AUPRCs were attributed to data quality. To examine this hypothesis, we calculated a known quality index, FRiP (fraction of reads in peaks (26)) of mouse CTCF data, and found that classes with low AUPRCs tended to have low FRiPs (Fig. 2d) with some exceptions (arrows in Fig. 2d). Because FRiP is calculated by reads in peaks per total reads, it could inflate when the read number of source data is too low. To correct such inflation, we multiplied FRiP by fraction of genomic regions covered by at least one read. As shown in Fig. 2d, the corrected FRiPs (cFRiPs) divided high and low AUPRC data more clearly. In addition, cFRiP showed stronger correlation with the total peak numbers of data than the original one (Fig. 2e and Supplementary Table 5). Even though the other data set showed weaker relations between FRiP and AUPRC, data with optimal cutoff values of cFRiP increased the average of AUPRCs, except human CTCF data (filtered hg38 and mm10 data in Fig. 2a and 2b, and Supplementary Fig. 4). These results suggest two points. First, the correction method reasonably represents a true quality of data. Second, the linear correlation between peak numbers and cFRiPs implies that the quality of data is not saturated enough to detect all true peaks (thereby there is a possibility that the model learn not cell specific patterns but sample quality). Therefore, while the ENCODE project seems to consider $\geq 1\%$ FRiP as good dat (26), the results suggest that higher stringency of quality control is required for the precise annotation of genomes.

To obtain insights into how the models predict regulatory sequences and what the syntax of them is, we sought to visualize the model (conv4-FRSS) trained with the subset of mouse DNase-seq data. Firstly, as previous studies did, we analyzed individual kernels of the first layer, which directly interact with DNA sequences and thus represent DNA motifs

that are important for classifying regulatory sequences. We have converted the weight variables to probability matrices by using a softmax-like operation, and detected that models have learned many known transcription factor motifs, such as CTCF, Sox9, OCT4 and KLF4 (Fig. 3a, and Supplementary Fig. 5). Because the combination of transcription factor motifs is an important factor for gene regulation (27), we visualized linkages between kernels and layers (Fig. 3b is linkages to 129 ES E14 class of the three DNase-seq data as an example and Supplementary Fig. 6 for larger images of linkages to three classes). Because of numerous kernels and variables, the comprehensive visualization of linkages is impossible. Therefore, we calculated strength of linkages by summing weight variables of each kernel and top 10% of linkages to each class was shown in Fig. 3b and Supplementary Fig. 6. This shallow visualization showed that the information from the first layer ("hidden1") was gathered to relatively few nodes of the last convolution layer ("hidden4"). We also found that most of strongly contributing kernels were shared between three classes. In addition, even if a kernel is shared between two classes, the linkages to the last layers were different (kernels with a light blue rectangle and red colored linkages in Supplementary Fig. 6), suggesting that different combinations of kernels were used for the class-specific predictions. Another interesting point is the time development of kernels and connections. As shown in Fig. 7, the model seems to learn GC-rich sequences (probably recognizing CpG islands or the CTCF binding motif) in early training stages, and kernels are connected by relatively a few nodes of the second layer ("hidden2"). In later stages, the model increases the variation and connection of kernels. Together, these visualizations suggest that the model seems to discern regulatory sequences by the combination of kernels.

Next, we applied the activation maximization method (28–30), in which we look for a sequence that maximizes neuron activities in the final layer of a trained model by training the sequence itself (see Methods for formal mathematical expressions). Firstly, we trained a sequence to activate the 129 ES E14 specific neuron in the last output layer. As with the image recognition studies (28–30), this method generated randomly repeated sequences that probably capture 129 ES E14-class specific traits (left panel in Fig. 4). Using a motif comparison software, Tomtom (31), we found that the generated sequence contains several OCT4/SOX2 and KLF4 motifs, which are important for the pluripotency of embryonic stem cells (32). For comparison, we also trained a sequence to activate all of the three neurons, resulting in a CTCF motif-rich sequence (right panel in Fig. 4). This result is consistent with the general role of CTCF as an enhancer looping factor (33). In addition, the generated sequence also contained small motifs next to the well-known CTCF motif (dashed boxes in the right panel of Fig. 4), which resembled the other part of the alternative long CTCF motif (33/34 bp-long, including an additional GGNANTGCA or TGCANTNCC sequence) (24). Thus, the detection of longer motifs than the kernel size would be one of the advantages of this activation maximization method. Taken together, these visualization

Fig. 3. Visualization of trained kernels and their connections. a, Examples of known motifs (top) that match with kernels. b, Connections of kernels and layers of conv4 with FRSS. As an example, connections that are linked to 129 ES E14 DNase-seq class are shown. Dots of hidden1-4, the outputs of convolution operations of kernels; fc1 and fc2, the fully-connected layers (because of too many neurons, they are represented as gray bars); labels, the last output layer; blue lines, connections between kernels and layers. Larger images are available in Supplementary Fig. 6.

methods would be useful to understand how deep learning models predict enhancer sequences.

Discussion

We have demonstrated that a new convolution architecture, FRSS efficiently discerns the patterns of DNA sequences. Furthermore, the analyses of data quality and structure revealed that training efficiencies highly depend on how to filter and process source data. The visualization methods are still immature, but we hope that these methods would provide clues to understanding the syntax of gene regulatory sequences. In conclusion, our study would be a new paradigm to develop deep learning-based sequence classifiers.

Methods

Data set and processing. The genome sequences of humans (hg38) and mice (mm10) were downloaded from UCSC (http://hgdownload.soe.ucsc.edu/goldenPath/). Mitochondrial DNA sequences were excluded from analyses. The

genomic sequences were divided into 1-kbp windows with a variety of strides as described in the main text. The filtered alignment files of epigenomic data were downloaded from the ENCODE website (https://www.encodeproject.org/; see Supplementary Table 2 for details). A peak caller, MACS2 was used to determine signal peak regions with options: "callpeak –call-summits -t <target bam file> -c <control bam file>-f <BAM or BAMPE> -g <hs or mm> -q 0.01" for ChIP-seq, and "callpeak –call-summits -q 0.01 –nomodel –shift -100 –extsize 200 -t <target bam file> -f <BAM or BAMPE> -g <hs or mm>" for DNase-seq. Using the outputs of MACS2, bedtools (34), and our codes, genomic regions were labeled as positive if a window overlaps with the summits of a peak. Data with less than 10,000 peaks were excluded from training data. For comparative analyses in Fig. 2a and 2b, peak files were downloaded from http://hgdownload.cse.ucsc.edu/goldenPath/hg19/encodeDCC/. For a cross-species comparison, Can-Fam 3.1 was downloaded from NCBI (https://www.ncbi.nlm.nih.gov/genome/?term=dog), and the short reads of CTCF ChIP-seq data (ERR022304)

Fig. 4. Results of the activation maximization method. Sequences trained to activate the 129 ES E14 specific neuron in the last layer (left panel) and all neurons in the last layer (right panel), respectively. Boxes in the left panel, OCT4/SOX2 binding motifs; dashed boxes in the left panel, KLF4 binding motifs; boxes in the right panel, CTCF binding motifs; dashed boxes, motifs similar to the second part of the alternative longer CTCF motif.

was downloaded from EMBL-EBI ArrayExpress (https://www.ebi.ac.uk/arrayexpress/experiments/E-MTAB-437/).

The DNA symbols, A, G, C, T and N were converted into one-hot vectors: (1, 0, 0, 0), (0, 1, 0, 0), (0, 0, 1, 0), (0, 0, 0, 1), and (0, 0, 0, 0), respectively. Therefore, one training sample became a 1000×4 tensor. With a mini-batch number 100 for the stochastic gradient descent and channel dimension 1 (a dimension for colors if the input was image data), the final shape of input tensor was 100×1000×4×1, with a label tensor of size mini-batch number×class number [i,e, 100 label vectors and each label looks like (0, 0, 0, 1, 0, 1, ..., 0); Supplementary Fig. 1 for a visual illustration].

Model designs and implementation. Tensorflow r1.8 for python (https://www.tensorflow.org/) with CUDA Driver Version 9.0 and cuDNN v7.0.5 was used as the main machine learning library for model implementation. Tensorflow library was compiled from the source codes with the bazel compiler (https://bazel.build/; with options, "-c opt --copt=-mavx --copt=-mavx2 --copt=-mfma --copt=-mfpmath=both --copt=-msse4.2 --config=cuda -k //tensorflow/tools/pip_package:build_pip_package"). For convolutions, we used a module, tensorflow.nn.conv2d with options "strides=[1, 1, 1, 1], padding=VALID". For the Basset model, because we did not see any positive ef-

fects by batch normalization, we removed this operation. For RNN layers, we used the long short-term memory cells (35) (tensorflow.nn.rnn_cell.LSTMCell or tensorflow.contrib.rnn.LSTMBlockCell without the peephole option), and tensorflow.nn.bidirectional_dynamic_rnn for output calculations. The operations and hyperparameters of models were listed in Supplementary Table 1.

For the forward- and reverse-sequence scan (FRSS) layers, convolution kernels were rotated 180 degrees to extract reverse complementary information in the first and second layers in parallel with normal convolutions as follows. Let W^ℓ a weight tensor, shape of M×N×H×K (M, kernel height; N, kernel width; H, input channel number; K, output channel number) in the ℓth convolution layer, defined as ($m = 0, ..., M-1$; $n = 0, ..., N-1$; $h = 0, ..., H-1$; $k = 0, ..., K-1$). The rotated tensor W^ℓ_{rc} can be written as $[W^\ell_{rc}]_{m,n,h,k} = w^\ell_{(M-1-m),(N-1-n),h,k}$. Then, the first part of the FRSS layers is

$$X^1 = pool(relu(conv(W^0, X^0))),$$
$$X^1_{rc} = pool(relu(conv(W^0_{rc}, X^0))),$$

where X^ℓ is a input/output tensor shape of B×S×N×H (B, mini batch number; S, sequence length; N, input width; H, input channel number) in the ℓth convolution layer, X^ℓ_{rc} is

the output of convolution with the rotated tensor, *conv* is the convolution operation, *relu* is the rectified linear unit, and *pool* is the max pooling operation. And, the second part of the FRSS layers is

$$X^2 = pool(relu(conv(W^1, X^1)) + relu(conv(W_{rc}^1, X^1))).$$

Note that the variables of W_{rc}^ℓ are not independent training targets, but are the copies of those of W^ℓ.

Training and testing models. Stochastic gradient-based optimization was used for training models. For human data, chromosome 8, and 9 were excluded from training data. For mouse data, chromosome 2 was excluded. The excluded sequences were used to test trained models. hg19 genome was used for a comparison with previously reported AUPRCs (Fig. 2a and b). A training data set was subdivided into mini-batches containing 100 sequences. In the quick benchmark, because the fraction of positively labeled genomic windows were too small, negative samples were randomly downsampled to 25%. To speed up learning rate and compensate the limited data size, each mini-batch was further divided into two sub mini-batches, and updates were made alternately twice per sub mini-batch (i.e., four updates per mini-batch). A loss function for training our models and the DeepSEA model is

$$\frac{1}{n}\sum_{k=0}^{n-1} y_k \log(\hat{y}_k) + (1-y_k)\log(1-\hat{y}_k) + \lambda_1 \|W\|_2^2 + \lambda_2 \|H\|_1,$$

where y_k is labels, $\hat{y}_k$ is predictions after the sigmoid operation, $\|W\|_2^2$ is the L2 regularization of all variables, $\|H\|_1$ is the L1 regularization of predictions before the sigmoid operation, λ_1 is 5×10^{-7}, and λ_2 is 1×10^{-8}. For the rest of models, the loss function without the regularization terms was used. RMSprop (36) and Adam (37) optimization algorithms were used to train the DanQ model and the others, respectively. To monitor training accuracy, models were tested by mini-batch data, and evaluated by the F1 score ($\frac{2\cdot precision\cdot recall}{precision+recall}$) as a temporal accuracy. When a mean of F1 scores of the last three tests exceeded a certain threshold (0.75), models were tested by three mini-batch sets that had been randomly excluded from a train data set, and saved when it recorded the highest F1 score.

NVIDIA TITAN X (Pascal; 3584 CUDA Cores; Total amount of global memory, 12190 Mbytes; GPU Max Clock rate, 1531 MHz) was used for GPU-computing. Intel® Xeon® Processor E5-2640 v4 (2.40GHz) was used for CPU-computing (Supplementary Note for the full spec of our machine). Total training time was dependent on the number of classes, the amount of training data, and model architectures. For example, conv4-FRSS took three hours to train with the subset of mm10 DNase-seq data (three classes), and 11 hours with hg38 DNase-seq (365 classes). The bottle neck was in part to send tensor data from GPU to CPU for evaluation of

the temporal accuracy of training models. In previous studies, training time was reported as 85 hours in the Basset paper with NVIDIA Tesla K20m and 164 classes, and as about 15 days in the DanQ paper with NVIDIA Titan Z and 919 classes. However, a fair comparison of training time with previous studies is difficult owing to different machines, languages, and data set.

To test trained models, chromosome 2 (or chromosome 8 and 9) sequence was divided into the same window size and stride with those of the training data. AUROC and AUPRC were calculated with functions in the scikit-learn library version 0.19.1 (http://scikit-learn.org/stable/). Predictions were visualized by the integrative genomics viewer (38) in Fig. 2 and Supplementary Fig. 2.

FRiP calculation and correction. To calculate FRiPs, firstly, mitochondrial regions and black-listed regions (https://sites.google.com/site/anshulkundaje/projects/blacklists) were removed from peak files. A module, "countReadsPerBin.CountReadsPerBin" in deeptools (39) was used to count reads in peaks, then divided by total reads. For a correction, FRiP was multiplied by the fraction of genome regions covered by at least one read.

Visualizing the inside of a trained model. Variables in each kernel were converted a probability matrix by a softmax-like operation. Tomtom (31) version 4.12.0 and meme motif database version 12.15 (http://meme-suite.org/meme-software/Databases/motifs/motif_databases.12.15.tgz) were used to identify closely related known transcription factor binding motifs. For visualizing kernels in the first layer of FRSS, the probability matrices were scaled by information content. Motif logos except Tomtom outputs were generated by our customized codes using cairocffi library.

To visualize the connections of kernels and layers, we looked through how values flow in the network as follows. The first input sequence is a tensor of size B×1000×4×1 or 1000×4×1 (B is a minibatch number, and here can be ignored). By the first convolution, in which each of 320 kernels has 9×4 matrix, the number of the output sequences is 320 and each sequence length becomes 982×1 (982×1×320 as a whole). After 2×1 max pooling, the sequence length is reduced to 496×1×320. Therefore, "hidden1" in Fig. 3b and Supplementary Fig. 6 is composed of 320 dots and each dot contains 496×1 values. Since these 320 dots are the outputs of 320 kernels, each dot has a corresponding kernel (the bottom part of Fig. 3B, but strongly connected kernels to "hidden2" are shown). From "hidden1" to "hidden2", the number of kernels is 480, and each kernel has 320 matrices of size 9×1. Each of 320 matrices in a kernel operates a convolution with one of the 320 outputs from the first convolution. Then, each kernel sums the 320 convolution results, which generates 480 outputs (the dots of "hidden2" in Fig. 3b) with a sequence of length 488 in each (i.e., a tensor of size 488×1×480). Namely, if a matrix of a kernel has big positive values, a corresponding output from the first convolution (a dot of "hidden1") strongly contributes to one of 480 outputs (a dot of "hidden2"). Therefore, the sum of 9 values in a matrix of a kernel approxi-

mates the strength of a connection between two dots of "hidden1" and "hidden2". The same algorithm was applied to the other convolution layers. The connections between the fully-connected layers are simpler, as each variable represents one connection between layers. In the figures, we showed only top 10 % of strong connections. The networks were written by our customized codes using cairocffi library.

The activation maximization method. Let $\hat{y}_i(X^0)$ be the score of the class i $i = 0, 1, 2$, computed by the conv4 with FRSS model for a sequence X^0. To find a sequence that is specific to the class i, we sought to optimize the following problem:

$$\underset{X^0}{argmax} \frac{\hat{y}_i(X^0)}{\sum_{k \neq i} \hat{y}_k(X^0)} - \lambda \|X^0\|_2^2,$$

where λ is 5.0×10^{-3}. For the common sequence (right panel in Fig. 4), the problem was:

$$\underset{X^0}{argmax} \prod \hat{y}_i(X^0) - \lambda \|X^0\|_2^2.$$

These formulae are slightly different from the previous studies (29, 30) because our model used the sigmoid function for the last output, but the others used the softmax. The Adam optimizer was used to optimize the target sequence. The initialization of variables of X^0 was set to be mean=0.02, std-dev=0.02, and was a critical factor for this optimization problem. Training with different initialization conditions sometimes did not converge, suggesting that the optimization landscape is rugged and there is a possibility that the results shown in Fig. 4 are not the optimal solution. The generated sequences were visualized by our customized codes using cairocffi library. Tomtom (31) was used to find motifs in the generated sequences.

Code availability

All codes used in this paper is available at https://github.com/koonimaru/DeepGMAP.

ACKNOWLEDGEMENTS
We thank Dr. Yuichiro Hara for critical comments, Dr. Mitsutaka Kadota for discussions about unpublished data. This work was supported in part by JSPS KAKENHI Grant Number 17K15132, Special Postdoctoral Researcher Program of RIKEN, and a research grant from MEXT to the RIKEN Center for Life Science Technologies and RIKEN Center for Biosystems Dynamics Research.

Bibliography

1. Jennifer R.S. Meadows and Kerstin Lindblad-Toh. Dissecting evolution and disease using comparative vertebrate genomics, 2017. ISSN 14710064.

2. 1000 Genomes Project Consortium, Goncalo R Abecasis, Adam Auton, Lisa D Brooks, Mark A DePristo, Richard M Durbin, Robert E Handsaker, Hyun Min Kang, Gabor T Marth, and Gil A McVean. An integrated map of genetic variation from 1,092 human genomes. *Nature*, 491(7422):56–65, 2012. ISSN 1476-4687. doi: 10.1038/nature11632.

3. Claudius F. Kratochwil and Axel Meyer. Closing the genotype-phenotype gap: Emerging technologies for evolutionary genetics in ecological model vertebrate systems. *BioEssays*, 37(2):213–226, 2015. ISSN 15211878. doi: 10.1002/bies.201400142.

4. Feng Yue, Yong Cheng, Alessandra Breschi, Jeff Vierstra, Weisheng Wu, Tyrone Ryba, Richard Sandstrom, Zhihai Ma, Carrie Davis, Benjamin D. Pope, Yin Shen, Dmitri D. Pervouchine, Sarah Djebali, Robert E. Thurman, Rajinder Kaul, Eric Rynes, Anthony Kirilusha, Georgi K. Marinov, Brian A. Williams, Diane Trout, Henry Amrhein, Katherine Fisher-Aylor, Igor Antoshechkin, Gilberto DeSalvo, Lei Hoon See, Meagan Fastuca, Jorg Drenkow, Chris Zaleski, Alex Dobin, Pablo Prieto, Julien Lagarde, Giovanni Bussotti, Andrea Tanzer, Olgert Denas, Kanwei Li, M. A. Bender, Miaohua Zhang, Rachel Byron, Mark T. Groudine, David McCleary, Long Pham, Zhen Ye, Samantha Kuan, Lee Edsall, Yi Chieh Wu,

Matthew D. Rasmussen, Mukul S. Bansal, Manolis Kellis, Cheryl A. Keller, Christopher S. Morrissey, Tejaswini Mishra, Deepti Jain, Nergiz Dogan, Robert S. Harris, Philip Cayting, Trupti Kawli, Alan P. Boyle, Ghia Euskirchen, Anshul Kundaje, Shin Lin, Yiing Lin, Camden Jansen, Venkat S. Malladi, Melissa S. Cline, Drew T. Erickson, Vanessa M. Kirkup, Katrina Learned, Cricket A. Sloan, Kate R. Rosenbloom, Beatriz Lacerda De Sousa, Kathryn Beal, Miguel Pignatelli, Paul Flicek, Jin Lian, Tamer Kahveci, Dongwon Lee, W. James Kent, Miguel Ramalho Santos, Javier Herrero, Cedric Notredame, Audra Johnson, Shinny Vong, Kristen Lee, Daniel Bates, Fidencio Neri, Morgan Diegel, Theresa Canfield, Peter J. Sabo, Matthew S. Wilken, Thomas A. Reh, Erika Giste, Anthony Shafer, Tanya Kutyavin, Eric Haugen, Douglas Dunn, Alex P. Reynolds, Shane Neph, Richard Humbert, R. Scott Hansen, Marella De Bruijn, Licia Selleri, Alexander Rudensky, Steven Josefowicz, Robert Samstein, Evan E. Eichler, Stuart H. Orkin, Dana Levasseur, Thalia Papayannopoulou, Kai Hsin Chang, Arthur Skoultchi, Srikanta Gosh, Christine Disteche, Piper Treuting, Yanli Wang, Mitchell J. Weiss, Gerd A. Blobel, Xiaoyi Cao, Sheng Zhong, Ting Wang, Peter J. Good, Rebecca F. Lowdon, Leslie B. Adams, Xiao Qiao Zhou, Michael J. Pazin, Elise A. Feingold, Barbara Wold, James Taylor, Ali Mortazavi, Sherman M. Weissman, John A. Stamatoyannopoulos, Michael P. Snyder, Roderic Guigo, Thomas R. Gingeras, David M. Gilbert, Ross C. Hardison, Michael A. Beer, and Bing Ren. A comparative encyclopedia of DNA elements in the mouse genome. *Nature*, 515(7527):355–364, 2014. ISSN 14764687. doi: 10.1038/nature13992.

5. Bradley E Bernstein, Ewan Birney, Ian Dunham, Eric D Green, Chris Gunter, and Michael Snyder. An integrated encyclopedia of DNA elements in the human genome. *Nature*, 489: 57–74, 2012. ISSN 1476-4687. doi: 10.1038/nature11247.

6. Cricket A. Sloan, Esther T. Chan, Jean M. Davidson, Venkat S. Malladi, J. Seth Strattan, Benjamin C. Hitz, Idan Gabdank, Aditi K. Narayanan, Marcus Ho, Brian T. Lee, Laurence D. Rowe, Timothy R. Dreszer, Greg Roe, Nikhil R. Podduturi, Forrest Tanaka, Eurie L. Hong, and J. Michael Cherry. ENCODE data at the ENCODE portal. *Nucleic Acids Research*, 44 (D1):D726–D732, 2016. ISSN 13624962. doi: 10.1093/nar/gkv1160.

7. Bradley E. Bernstein, John A. Stamatoyannopoulos, Joseph F. Costello, Bing Ren, Aleksandar Milosavljevic, Alexander Meissner, Manolis Kellis, Marco A. Marra, Arthur L. Beaudet, Joseph R. Ecker, Peggy J. Farnham, Martin Hirst, Eric S. Lander, Tarjei S. Mikkelsen, and James A. Thomson. The NIH roadmap epigenomics mapping consortium, 2010. ISSN 10870156.

8. Robin Andersson, Claudia Gebhard, Irene Miguel-Escalada, Ilka Hoof, Jette Bornholdt, Mette Boyd, Yun Chen, Xiaobei Zhao, Christian Schmidl, Takahiro Suzuki, Evgenia Ntini, Erik Arner, Eivind Valen, Kang Li, Lucia Schwarzfischer, Dagmar Glatz, Johanna Raithel, Berit Lilje, Nicolas Rapin, Frederik Otzen Bagger, Mette Jørgensen, Peter Refsing Andersen, Nicolas Bertin, Owen Rackham, A. Maxwell Burroughs, J. Kenneth Baillie, Yuri Ishizu, Yuri Shimizu, Erina Furuhata, Shiori Maeda, Yutaka Negishi, Christopher J. Mungall, Terrence F. Meehan, Timo Lassmann, Masayoshi Itoh, Hideya Kawaji, Naoto Kondo, Jun Kawai, Andreas Lennartsson, Carsten O. Daub, Peter Heutink, David A. Hume, Torben Heick Jensen, Harukazu Suzuki, Yoshihide Hayashizaki, Ferenc Müller, Alistair R.R. Forrest, Piero Carninci, Michael Rehli, and Albin Sandelin. An atlas of active enhancers across human cell types and tissues. *Nature*, 507(7493):455–461, 2014. ISSN 14764687. doi: 10.1038/nature12787.

9. David R. Kelley, Jasper Snoek, and John L. Rinn. Basset: Learning the regulatory code of the accessible genome with deep convolutional neural networks. *Genome Research*, 26(7): 990–999, 2016. ISSN 15495469. doi: 10.1101/gr.200535.115.

10. Jian Zhou and Olga G Troyanskaya. Predicting effects of noncoding variants with deep learning–based sequence model. *Nature Methods*, 12(10):931–934, 2015. ISSN 1548-7091. doi: 10.1038/nmeth.3547.

11. Daniel Quang and Xiaohui Xie. DanQ: A hybrid convolutional and recurrent deep neural network for quantifying the function of DNA sequences. *Nucleic Acids Research*, 44(11), 2016. ISSN 13624962. doi: 10.1093/nar/gkw226.

12. Mahmoud Ghandi, Dongwon Lee, Morteza Mohammad-Noori, and Michael A. Beer. Enhanced Regulatory Sequence Prediction Using Gapped k-mer Features. *PLoS Computational Biology*, 10(7), 2014. ISSN 15537358. doi: 10.1371/journal.pcbi.1003711.

13. Ravid Shwartz-Ziv and Naftali Tishby. Opening the Black Box of Deep Neural Networks via Information. Preprint at http://arxiv.org/abs/1703.00810. 2017.

14. Guillaume Alain and Yoshua Bengio. Understanding intermediate layers using linear classifier probes. Preprint at http://arxiv.org/abs/1610.01644. 2016.

15. Yong Zhang, Tao Liu, Clifford A. Meyer, Jérôme Eeckhoute, David S. Johnson, Bradley E. Bernstein, Chad Nussbaum, Richard M. Myers, Myles Brown, Wei Li, and X. Shirley Shirley. Model-based analysis of ChIP-Seq (MACS). *Genome Biology*, 9(9), 2008. ISSN 14747596. doi: 10.1186/gb-2008-9-9-r137.

16. Robert E. Thurman, Eric Rynes, Richard Humbert, Jeff Vierstra, Matthew T. Maurano, Eric Haugen, Nathan C. Sheffield, Andrew B. Stergachis, Hao Wang, Benjamin Vernot, Kavita Garg, Sam John, Richard Sandstrom, Daniel Bates, Lisa Boatman, Theresa K. Canfield, Morgan Diegel, Douglas Dunn, Abigail K. Ebersol, Tristan Frum, Erika Giste, Audra K. Johnson, Ericka M. Johnson, Tanya Kutyavin, Bryan Lajoie, Bum Kyu Lee, Kristen Lee, Darin London, Dimitra Lotakis, Shane Neph, Fidencio Neri, Eric D. Nguyen, Hongzhu Qu, Alex P. Reynolds, Vaughn Roach, Alexias Safi, Minerva E. Sanchez, Amartya Sanyal, Anthony Shafer, Jeremy M. Simon, Lingyun Song, Shinny Vong, Molly Weaver, Yongqi Yan, Zhancheng Zhang, Zhuzhu Zhang, Boris Lenhard, Muneesh Tewari, Michael O. Dorschner, R. Scott Hansen, Patrick A. Navas, George Stamatoyannopoulos, Vishwanath R. Iyer, Jason D. Lieb, Shamil R. Sunyaev, Joshua M. Akey, Peter J. Sabo, Rajinder Kaul, Terrence S. Furey, Job Dekker, Gregory E. Crawford, and John A. Stamatoyannopoulos. The accessible chromatin landscape of the human genome. *Nature*, 489(7414):75–82, 2012. ISSN 00280836. doi: 10.1038/nature11232.

17. Jesse Davis and Mark Goadrich. The relationship between Precision-Recall and ROC curves. In *Proceedings of the 23rd international conference on Machine learning - ICML '06*, pages 233–240, 2006. ISBN 1595933832. doi: 10.1145/1143844.1143874.

18. Christian Szegedy, Wei Liu, Yangqing Jia, Pierre Sermanet, Scott Reed, Dragomir Anguelov, Dumitru Erhan, Vincent Vanhoucke, and Andrew Rabinovich. Going deeper with convolutions. *Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition*, 7-12:1–9, 2015. ISSN 10636919. doi: 10.1109/CVPR.2015.7298594.

19. J. N.Mark Glover and Stephen C. Harrison. Crystal structure of the heterodimeric bZIP transcription factor c-Fos–c-Jun bound to DNA, 1995. ISSN 00280836.

20. Toshiyuki Shimizu, Atsuki Toumoto, Kentaro Ihara, Masato Shimizu, Yoshimasa Kyogoku, Nobuo Ogawa, Yasuji Oshima, and Toshio Hakoshima. Crystal structure of PHO4 bHLH domain-DNA complex: Flanking base recognition. *EMBO Journal*, 16(15):4689–4697, 1997. ISSN 02614189. doi: 10.1093/emboj/16.15.4689.

21. Xu Min, Wanwen Zeng, Shengquan Chen, Ning Chen, Ting Chen, and Rui Jiang. Predicting enhancers with deep convolutional neural networks. *BMC Bioinformatics*, 18, 2017. ISSN 14712105. doi: 10.1186/s12859-017-1878-3.

22. Sam John, Peter J Sabo, Robert E Thurman, Myong-Hee Sung, Simon C Biddie, Thomas A Johnson, Gordon L Hager, and John A Stamatoyannopoulos. Chromatin accessibility predetermines glucocorticoid receptor binding patterns. *Nat. Genet.*, 43(3):264–268, 2011. ISSN 1061-4036.

23. Shashank Singh, Yang Yang, Barnabas Poczos, and Jian Ma. Predicting Enhancer-Promoter Interaction from Genomic Sequence with Deep Neural Networks. *bioRxiv*, pages 1–12, 2016. doi: 10.1101/085241.

24. Dominic Schmidt, Petra C. Schwalie, Michael D. Wilson, Benoit Ballester, Ângela Gonalves, Claudia Kutter, Gordon D. Brown, Aileen Marshall, Paul Flicek, and Duncan T. Odom. Waves of retrotransposon expansion remodel genome organization and CTCF binding in multiple mammalian lineages. *Cell*, 148(1-2):335–348, 2012. ISSN 00928674. doi: 10.1016/j.cell.2011.11.058.

25. Charles E. Grant, Timothy L. Bailey, and William Stafford Noble. FIMO: Scanning for occurrences of a given motif. *Bioinformatics*, 27(7):1017–1018, 2011.

26. Stephen G. Landt, Georgi K. Marinov, Anshul Kundaje, Pouya Kheradpour, Florencia Pauli, Serafim Batzoglou, Bradley E. Bernstein, Peter Bickel, James B. Brown, Philip Cayting, Yiwen Chen, Gilberto DeSalvo, Charles Epstein, Katherine I. Fisher-Aylor, Ghia Euskirchen, Mark Gerstein, Jason Gertz, Alexander J. Hartemink, Michael M. Hoffman, Vishwanath R. Iyer, Youngsook L. Jung, Subhradip Karmakar, Manolis Kellis, Peter V. Kharchenko, Qunhua Li, Tao Liu, X. Shirley Liu, Lijia Ma, Aleksandar Milosavljevic, Richard M. Myers, Peter J. Park, Michael J. Pazin, Marc D. Perry, Debasish Raha, Timothy E. Reddy, Joel Rozowsky, Noam Shoresh, Arend Sidow, Matthew Slattery, John A. Stamatoyannopoulos, Michael Y. Tolstorukov, Kevin P. White, Simon Xi, Peggy J. Farnham, Jason D. Lieb, Barbara J. Wold, and Michael Snyder. ChIP-seq guidelines and practices of the ENCODE and modENCODE consortia, 2012. ISSN 10889051.

27. Daria Shlyueva, Gerald Stampfel, and Alexander Stark. Transcriptional enhancers: From properties to genome-wide predictions, 2014. ISSN 14710064.

28. Dumitru Erhan, Yoshua Bengio, Aaron Courville, and Pascal Vincent. Visualizing higher-layer features of a deep network. *Bernoulli*, (1341):1–13, 2009.

29. Karen Simonyan, Andrea Vedaldi, and Andrew Zisserman. Deep Inside Convolutional Networks: Visualising Image Classification Models and Saliency Maps. Preprint at http://arxiv.org/abs/1312.6034. *arXiv.org*, 2013.

30. Jason Yosinski, Jeff Clune, Anh Nguyen, Thomas Fuchs, and Hod Lipson. Understanding Neural Networks Through Deep Visualization. Preprint at http://arxiv.org/abs/1506.06579. 2015.

31. Shobhit Gupta, John A. Stamatoyannopoulos, Timothy L. Bailey, and William Stafford Noble. Quantifying similarity between motifs. *Genome Biology*, 8(2), 2007. ISSN 14747596. doi: 10.1186/gb-2007-8-2-r24.

32. Kazutoshi Takahashi and Shinya Yamanaka. Induction of Pluripotent Stem Cells from Mouse Embryonic and Adult Fibroblast Cultures by Defined Factors. *Cell*, 126(4):663–676, 2006. ISSN 00928674. doi: 10.1016/j.cell.2006.07.024.

33. Chin Tong Ong and Victor G. Corces. CTCF: An architectural protein bridging genome topology and function, 2014. ISSN 14710064.

34. Aaron R. Quinlan and Ira M. Hall. BEDTools: A flexible suite of utilities for comparing genomic features. *Bioinformatics*, 26(6):841–842, 2010. ISSN 13674803. doi: 10.1093/bioinformatics/btq033.

35. Sepp Hochreiter and Jürgen Schmidhuber. Long Short-Term Memory. *Neural Computation*, 9(8):1735–1780, 1997. ISSN 0899-7667. doi: 10.1162/neco.1997.9.8.1735.

36. Geoffrey E. Hinton, Nitish Srivastava, and Kevin Swersky. Lecture 6e- rmsprop: Divide the gradient by a running average of its recent magnitude. *COURSERA: Neural Networks for Machine Learning*, pages 26–31, 2012. doi: https://www.coursera.org/learn/neural-networks/lecture/YQHki/rmsprop-divide-the-gradient-by-a-running-average-of-its-recent-magnitude.

37. Diederik P. Kingma and Jimmy Ba. Adam: A Method for Stochastic Optimization. pages 1–15, 2014. ISSN 09252312. doi: http://doi.acm.org.ezproxy.lib.ucf.edu/10.1145/1830483.1830503.

38. James T. Robinson, Helga Thorvaldsdóttir, Wendy Winckler, Mitchell Guttman, Eric S. Lander, Gad Getz, and Jill P. Mesirov. Integrative genomics viewer, 2011. ISSN 10870156.

39. Fidel Ramírez, Devon P. Ryan, Björn Grüning, Vivek Bhardwaj, Fabian Kilpert, Andreas S. Richter, Steffen Heyne, Friederike Dündar, and Thomas Manke. deepTools2: a next generation web server for deep-sequencing data analysis. *Nucleic acids research*, 44(W1):W160–W165, 2016. ISSN 13624962. doi: 10.1093/nar/gkw257.