Hierarchical Domain Structure Reveals the Divergence of Activity among TADs and Boundaries

Lin An[1], Tao Yang[1], Jiahao Yang[2], Johannes Nuebler[3], Guanjue Xiang[1], Ross C. Hardison[4], Qunhua Li[5*], Yu Zhang[5*]

[1]Bioinformatics and Genomics program, Pennsylvania State University, University Park, PA, [2]Tsinghua University, Beijing, China, [3] Institute for Medical Engineering and Science, Massachusetts Institute of Technology, Cambridge, MA, [4]Department of Biochemistry and Molecular Biology, Pennsylvania State University, University Park, PA, [5] Department of Statistics, Pennsylvania State University, University Park, PA

*To whom correspondence should be addressed.

Email addresses:

LA: lua137@psu.edu; TY: txy146@psu.edu; JY: yangjh14@mails.tsinghua.edu.cn; JN: jnuebler@mit.edu; RH: rch8@psu.edu; QL: qunhua.li@psu.edu; YZ: yzz2@psu.edu.

Abstract

The spatial organization of chromatin in the nucleus has been implicated in many aspects of regulated gene expression. Maps of high frequency interactions between different segments of chromatin have revealed Topologically Associating Domains (TADs), within which most of the regulatory interactions are thought to occur. Recent studies have shown that TADs are not homogeneous structural units, but rather they appear to be organized into a hierarchy. However, precise identification of hierarchical TAD structures remains a challenge. We present OnTAD, an Optimized Nested TAD caller from Hi-C data, to identify hierarchical TADs. Compared to existing methods, OnTAD has significantly improved accuracy and running speed. Results from OnTAD reveal new biological insights on the role of different TAD levels, boundary usage in gene regulation, the loop extrusion model, and compartmental domains. The software and documentation for OnTAD are available at: https://github.com/anlin00007/OnTAD

Background

Previous studies have shown that the human genome is spatially organized at different levels in the nucleus, with each level of organization playing a role in gene regulation [1]. Starting with the original Chromatin Conformation Capture (3C) assay [2] for measuring chromatin interaction

frequencies, many higher throughput, sequencing-based methods such as 4C, 5C, ChIA-PET,

Hi-C, and Hi-ChIP have been developed to measure 3D interaction frequencies at different

resolutions [3–8]. These maps of interaction frequencies between segments of chromatin are

interpreted in terms of chromatin structures. Among the methods, Hi-C [9] obtains measurement

of chromatin interaction frequencies across the entire genome. Within some local regions in a

genome, interactions are significantly higher than they are to adjacent regions; these highly

interacting regions are termed 'Topologically Associating Domains' (TADs) [10,11]. The proteins

CTCF and cohesin are frequently enriched at TAD boundaries, and they have been implicated

in the formation of an isolated local environment [11]. Furthermore, the positions of many TADs

are similar across different cell-types and even conserved between species [11,12]. As a result,

TADs have been widely interpreted as a basic architectural unit within which many gene

regulatory interactions occur. To date, several computational methods have been developed to

locate TADs in the genome. For example, Dixon et al. [11] developed a 'Directionality Index'

based on the shift of interaction direction from upstream to downstream to estimate boundaries

of TADs. Other methods, such as TOPDOM [13] and Insulation Score [14], convert the TAD

boundary finding problem to a local minimum identification problem by calculating average

interaction frequency of surrounding regions at each locus.

While many earlier TAD calling methods treat TADs as a single structure, recent high-

resolution studies have shown that TADs contains internal substructures, with sub-TADs nested

within larger TADs [15–19]. Several recently developed TAD calling methods aimed to identify

nested TAD structures. For example, TADtree [15] identifies TADs based on a relationship

between the enrichment of contact frequency and TAD size, and assembles TADs into a TAD

tree that best fit the contact matrix. rGMAP [16] assumes that the interaction frequency in sub-

TADs is different from those in larger TADs, and applies a Gaussian Mixture model to identify

both types of TADs. Arrowhead [17] identifies corners of TADs at multiple sizes, allowing TADs

and subTADs to be detected simultaneously. 3D-Net [18] utilizes a maximization of network

modularity to identify TADs at different levels. And finally, IC-Finder [19] uses a hierarchical

clustering method to identify the TAD hierarchy.

Although the aforementioned methods provide useful tools for identifying TADs and their

internal substructure, we still lack comprehensive understanding of the functions of the

hierarchical structures within TADs. Recent work on low-resolution Hi-C data [20] has shown

that, at the large scale (> 1Mb), TADs can form a hierarchy of domains-within-domains

("metaTAD") through TAD-TAD interactions, and the successive levels of metaTAD organization

correlate with key epigenomic and expression features. This raises the natural question: do the

hierarchical levels within TADs also correlate with distinctive functional roles in chromosome

organization and gene regulation? However, most existing TAD callers focus on identifying the

locations of TADs and subTADs, rather than the hierarchical organization within TADs, making

them less suitable for investigating the biological functions of TAD hierarchy. Furthermore, many

existing callers are computationally inefficient for high-resolution Hi-C data and often lack a

principled approach to choosing algorithmic parameters [16]. These issues limit the utility of

existing TAD callers for investigating finer TADs structures using high-resolution data.

We present OnTAD, an Optimized Nested TAD caller that efficiently and robustly

uncovers hierarchical TAD structures from Hi-C data. Our approach first identifies candidate

TAD boundaries by scanning through the genome with a sliding window at a series of different

window sizes, using an approach inspired by TOPDOM [13]. Then, the candidate boundaries

are assembled into the optimized hierarchical TADs structures using a recursive dynamic

programming algorithm based on a scoring function. Our systematic evaluation shows that

OnTAD substantially outperforms existing TAD callers for both TAD boundary identification and

hierarchical TAD assembly. Using OnTAD, we uncovered novel insights on the potential

biological functions of TAD structures. In particular, we observed that active epigenetic states

are substantially more enriched in inner TADs than in outer TADs. OnTAD results revealed two

categories of TADs, those with or without hierarchical structures, that appear functionally distinct.

Compared to nonhierarchical TADs, the boundaries of TADs with hierarchical structures show a

higher CTCF enrichment, more active epigenetic states, and a higher level of gene expression.

In addition, we observed an apparent asymmetry in TAD boundary sharing, supporting the

asymmetric loop extrusion model for the formation of TADs [21]. Together, these results

demonstrate that OnTAD is a powerful tool for inferring different levels of chromatin organization

across a genome in high-resolution Hi-C data, which should facilitate improved investigations

into the roles of chromatin organization in gene regulation.

Results

The OnTAD algorithm

OnTAD takes a Hi-C contact matrix as the input and calls TADs in two steps. In the first step,

the method finds candidate TAD boundaries using an adaptive local minimum search algorithm

inspired by TOPDOM [13]. Specifically, it scans along the diagonal of a Hi-C matrix using a W

by W diamond-shaped window (Figure 1a), calculating the average contact frequency within

each window. The locations at which the average contact frequency reaches a significant local

minimum (1.96 standard deviations less than local maximum) are identified as candidate TAD

boundaries (see Methods). Because the sizes of TADs are unknown, OnTAD repeats the above

steps using a series of window-sizes, W= 1,2.,…,K, to uncover all possible boundaries for TADs

in different sizes. Here, K depends on the resolution of the Hi-C matrix and the maximum TAD

size that the user aims to call. For instance, for a 10kb resolution Hi-C matrix and a maximum

TAD size of 2Mb, K=2000/10=200. The union of the candidate boundaries of all window sizes is

used to assemble TADs in the next step (Figure 1b).

In the second step, OnTAD assembles TADs by selectively connecting pairs of candidate

boundaries using a dynamic programming algorithm (see Methods). To form a TAD between a

pair of boundaries, OnTAD requires the mean contact frequency within the potential TAD area

between the boundaries to exceed that of the surrounding area outside of the TAD by a user-

defined margin (λ); otherwise, no TAD is formed between the boundaries. The dynamic

programming algorithm is formulated to recursively identify the optimal partition of the genome

for yielding the largest rightmost subTADs within each identified TAD according to a score

function (Supplementary Figure 1) that de-convolutes the contact frequency signals across the

TAD hierarchy (Supplementary Figure 2). At the end of the recursive procedure, the optimized

solution that maximizes the score function is obtained (defined in Methods), producing a

hierarchical TAD organization that best fits the observed Hi-C contact matrix. The locations of

the identified TADs are provided to the users as a plain text file and a bedgraph file ready for

visualization on genome browsers.

Comparison with existing TAD calling methods

We compared OnTAD with four representative TAD calling methods (DomainCaller, rGMAP,

Arrowhead and TADtree) using the Hi-C data in GM12878 from Rao et al.[17]. Each method

was run using the settings recommended in its manual (see Supplementary file 1 for the version

and parameters for each method). All the evaluations were performed using 10kb resolution for

the normalized genome-wide Hi-C data, unless specified otherwise. We also tested OnTAD on

raw data, and the results obtained were similar to those observed for normalized data

(Supplementary Figure 9).

Accuracy of TAD boundary detection

We first evaluated the accuracy of TAD boundary detection using enrichment of architectural

proteins at boundaries as a reference for accuracy. CTCF is an architectural protein implicated

in formation of TAD structures [10]. Thus, we expect a high concentration of CTCF signal (from

ChIP-seq data) at accurately called TAD boundaries. We computed the average CTCF ChIP-

seq signal in the boundaries identified by each TAD calling method as well as their

neighborhood regions. As shown in Figure 2a (left panel), all methods showed enrichment of

CTCF signal in the identified TAD boundaries over that in the surrounding regions (fold change >

1.63). Among them, OnTAD had the highest CTCF enrichment (mean signal 1.22X greater than

that of the second highest method, T-test p-value = 1.91e-28). A similar result was obtained for

the enrichment of the RAD21 and SMC3 subunits of the cohesin complex, which are also key

components in the formation of TADs [21]. The boundaries identified by OnTAD showed a

higher enrichment than those identified by other methods (mean signal 1.14X and 1.04X greater

than that of the second highest method, T-test p-value = 9.34e-16 and 1.91e-12, respectively)

(Figure 2a middle and right panel). The stronger enrichment of CTCF and cohesin signals

suggests that OnTAD produces more accurate calls of TAD boundaries than the other methods.

Accuracy of TAD assembly

We next evaluated the accuracy of TAD calling. If TADs are accurately called, one would expect

that a high proportion of the variation in the contact frequencies in the Hi-C matrix is explained

by TAD calls. We developed a metric called TAD-adjR^2, which is a modified version of the

adjusted R^2 (see Methods), to measure the proportion of Hi-C signal variation explained by TAD

calls. Because contact frequencies decay over the genomic distance between a pair of

interacting loci, we stratified the contacts by their genomic distance and calculated TAD-adjR^2

within each stratum. As shown in Figure 2b, OnTAD has a higher TAD-adjR^2 than that of the

other methods across almost the entire span of genomic distances examined (0-1.5Mb)

(Average TAD-adjR^2: OnTAD: 0.33, Arrowhead: 0.26, DomainCaller: 0.26, rGMAP: 0.23 and

TADtree: 0.06). This high level of explained Hi-C variance indicates that OnTAD produces a

better classification between TADs and non-TAD regions compared to other methods.

Reproducibility of TAD calls and boundaries

Another important criterion for TAD calling is the reproducibility of the identified TADs and their

boundaries. To measure the reproducibility of TAD boundaries, we calculated the agreement of

boundaries (Figure 2c-e) between two TAD calling results using the Jaccard index. To measure

the reproducibility of TADs, we treated each region covered by a TAD as a cluster of bins in the

genome, and then measured the agreement of cluster assignments between two TAD calling

results using the adjusted rand index (Supplementary Figure 3a-c). We evaluated the

reproducibility in three scenarios: 1) between biological replicates (GM12878, 10Kb) (Figure 2c,

Supplementary Figure 3a); 2) across different resolutions (5Kb, 10Kb, 25Kb) (Figure 2d,

Supplementary Figure 3b); and 3) at different sequencing depths (original sequencing depth

versus 1/4, 1/8, 1/16 and 1/32 of the total number of reads) (Figure 2e, Supplementary Figure

3c). As shown in Figure 2c-e and Supplementary Figure 3b, both the boundaries and the TADs

identified by OnTAD were fairly reproducible, consistently having either the highest or the

second highest Jaccard index or Adjusted Rand index in all scenarios.

Run time comparison

We recorded the run time of different methods on the same high-performance computing cluster

(Xeon E5-2680CPU and 72Gb RAM). OnTAD ran notably faster than all the other methods

(Supplementary Table 1). For example, it took OnTAD 655 seconds to analyze 10Kb resolution

data for the whole genome, which was 3X faster than Arrowhead, 24X faster than DomainCaller,

28X faster than rGMAP, and 263X faster than TADtree.

Level of TAD hierarchy is related to gene activity and epigenomic states

We systematically studied the biological features of the TAD hierarchy, again using the Hi-C

data in GM12878 from Rao et al.[17]. Overall, 75.7% of the genome was covered by the TADs

identified by OnTAD; the rest of the genome was not assigned to any TADs, and we refer to

these TAD-free regions as gaps. Among all TADs identified by OnTAD, the majority (92.2%)

contained or belonged to hierarchical structures, while a small fraction had no hierarchical

structure. We referred to the former as 'hierarchical TADs' or 'nested TADs', and the latter as

'singletons' (Figure 3a). We hypothesized that chromatin organized into these two types of

TADs may be playing distinctive roles in regulation, and thus we examined their association with

various epigenetic marks.

Boundaries of hierarchical TADs have a higher CTCF enrichment

We first compared the CTCF enrichment (see Methods) at the boundaries of the two types of

TADs. Indeed, the boundaries of hierarchical TADs were substantially more enriched with CTCF

signal than singleton boundaries (Figure 3b) (mean CTCF signals are 3.51 and 2.25,

respectively, T-test p-value = 1.52e-18). This enrichment of CTCF signal arose from a higher

average number of CTCF peaks at the boundaries of hierarchical TADs. The mean number of

CTCF peaks per boundary of a hierarchical TAD was 0.451, whereas it was only 0.181 for

boundaries of singleton TADs (T-test p-value = 4.52e-30).

Hierarchical TADs have a stronger association with active epigenetic states

Chromatin interactions are strongly associated with local, active epigenetic profiles [12,17, 22].

We thus expected to observe a positive association between the enrichment of active epigenetic

states and the levels of TADs. Starting with the 36 epigenetic states defined by IDEAS

segmentation [23] on 6 ENCODE cell lines, we evaluated the association between active

epigenetic states and TAD hierarchies. We classified hierarchical TADs into five levels, with

level one being the outermost TADs, level two being the immediate subTADs nested under one

layer of level one TAD, and so forth until level five, which contains the subTADs nested under

four or more layers of TADs in the hierarchy. We observed that the proportion of active

epigenetic states increase along the levels of TADs (Figure 3c, d). In contrast, singletons are

notably less active compared with hierarchical TADs (especially when level >2). In fact,

singleton TADs showed enrichments similar to those for the gap regions. A similar pattern of

enrichment for active states in hierarchical TADs was also observed in other cell types (K562

and HUVEC) (Supplementary Figure 4). Taken together, our results showed that hierarchical

TADs are on average more active than singletons; and within hierarchical TADs, inner TADs

(e.g., subTADs) are more active than outer TADs.

Hierarchical TADs have more active gene expression

We further investigated how gene expression is associated with TAD hierarchies. Using the

RNA-seq data of GM12878 from the ENCODE consortium ([www.encodeproject.org)](www.encodeproject.org) [24], we

defined expressed genes as those with FPKM > 5. Then within TADs at each level, we

computed the density of expressed genes (the number of expressed genes per bin, i.e., 10Kb

region). If a gene was covered by more than one TAD, we associated it with the innermost

TADs. We found that, as the TAD level increases, the density of expressed genes also

increases, i.e., genes are more frequently activated within inner TADs than outer TADs (ANOVA

test p-value of < 2.2e-16) (Figure 3e). Similarly, we observed the same trend of positive

association between density of expressed genes and the TAD level (ANOVA test p-value <

2.2e-16) in the K562 cell line (Figure 3f).

Shared TAD boundaries are asymmetric and more active than other boundaries

It has been reported that TAD boundaries are interaction hotspots [25]. We also observed that,

for TADs at all levels, the number of expressed genes and the enrichment of active epigenetic

states are significantly higher at the TAD boundaries than at the internal regions of TADs (all T-

test p-values < 0.001) (Supplementary Figure 5a&b). Thus we undertook an additional analysis

of TAD boundaries.

We observed that the boundaries of hierarchical TADs were frequently shared by

multiple TADs. We hypothesized that the boundary usage may play an important role in

maintaining hierarchical structures and regulating gene activities. To investigate this hypothesis,

we classified boundaries into five categories, according to the maximum number of TADs that

use a boundary on one of the two sides of the boundary (Figure 4a). A boundary is classified as

level one if it is used by no more than one TAD on either side, level two if it is used by exactly

two TADs on one side and less or equal to two TADs on the other side, and so forth to level five

if it is used by five or more TADs on either side. For example, a boundary shared by two TADs

to its left and three TADs to its right was classified as level three. The number of boundaries

assigned to each category is shown in Supplementary Figure 7.

Epigenetic and genomic profiles

We examined the enrichment of active epigenetic states at different boundary levels. We

observed a significant positive correlation between the enrichment (fold change) of active

epigenetic states and the number of times each boundary is shared (e.g., Tss state: Pearson

coefficient = 0.89; TssCtcf state: Pearson coefficient = 0.92) (Figure 4b). We further studied the

relationship between gene expression level and boundary sharing. Again, we observed a

significant positive association between the number of times a boundary was shared and the

gene expression level (ANOVA test p-value = 1.97e-05). In particular, the gene expression level

at the boundaries that were shared by 5 or more TADs was substantially higher than that at

boundaries that were shared by fewer TADs (Figure 4c). At a higher level boundary, multiple

genomic loci (the boundary plus the other ends of the TADs) must be in proximity in three-

dimensional space. This situation is reminiscent of chromatin hubs, and thus, we call the

boundaries shared by 5 or more TADs "hub-boundaries". We posited that hub-boundaries are

more active in gene regulation than boundaries that are shared by fewer TADs.

The asymmetric loop extrusion model

Interestingly, we also observed some asymmetry in boundary usage and TAD formation in

hierarchical TADs. Specifically, we have observed (1) a significant difference in boundary usage

between the left and the right boundaries of the same outer TAD (Z-test p-value < 2.2e-16) and

(2) a significant difference in the numbers of TADs formed by a boundary on its left and right

sides (Z-test p-value < 2.2e-16) (Supplementary Table 2).

We therefore asked if the observed asymmetry is related to the mechanism of loop formation. A

recent study in yeast suggested that loops are formed in an asymmetric process, where the loop

extrusion complex anchors on one side and DNA reels through from the other side [26]. We

here hypothesize that loop extruders are preferentially loaded at or near a specific TAD

boundary. Then the asymmetric loop extrusion would start from this site on one end, and it

could stop at different sites on the other end. Thus, the TADs formed by multiple stops of loop

extrusion in this process would all share the anchor site as the boundary on one side, but each

has a different boundary on the other side, leading to the observed asymmetric boundary usage

(Figure 4d). Another recent study in *Drosophila* Schneider 2 (S2) cells showed that promoters

prefer to interact with enhancers downstream of the transcriptional unit [27], leading to a

directional preference in TAD formation. Indeed, as shown in Figure 4b, the boundaries shared

by multiple TADs are highly enriched with promoters, thus the observed orientation asymmetry

in TAD formation around these boundaries could reflect this interaction preference in promoters.

While some proteins (e.g. Ycg1 HEAT-repeat and Brn1 kleisin subunits) have been found to be

related to the anchor sites in yeast [28], little is known about the proteins supporting the anchor

sites in human. We therefore performed a transcription factor (TF) enrichment analysis using

161 TF ChIP-seq data from the ENCODE consortium [29–31]. By comparing the fold

enrichment of each TF signal in hub-boundary (level 5) with the ones at low level (level 1), we

found a group of TFs that were highly enriched in hub-boundaries (Fold Change > 2 in either

GM12878 (n = 8) or K562 (n = 37)) (Figure 4e). These hub-boundary-enriched TFs were

strongly associated with chromosome organization function in Gene Ontology Analysis (FDR =

1.33e-06). They were also shown to be highly connected (p-value < 1.0e-16) in the protein-

protein interaction database, STRING (Supplementary Figure 7), suggesting that they may

potentially form a protein complex. Together, these results suggest that the enriched TFs may

play an important role in forming the anchor sites in the asymmetric extrusion process.

Hierarchical TAD calling unveils distinct epigenetic features of inner TADs

It has been reported that genomic loci within the same TADs tend to possess similar epigenetic

features [22], while loci in different adjacent TADs may show different epigenetic features [17].

However, it remains unclear if the divergence of epigenetic profiles also takes place at the

subTAD level. To explore the possible answer to this question, we performed OnTAD on Hi-C

data from the mouse G1E-ER4 cell [32]. We observed that the majority of TADs (87.1%) are in

active compartments. As shown in the OnTAD genome browser track in Figure 5, the region of

(chr19:11.3Mb – 12.2Mb) contains multiple nested TADs. Among them, two adjacent subTADs

(11.8Mb – 11.9Mb and 11.9Mb – 12.0Mb) that belong to the same outer TAD (chr19: 11.5Mb –

12.0Mb) exhibit distinct epigenetic features, with enriched repressive epigenetic signal

(H3K27me3) in the left subTAD and enriched active epigenetic signal (H3K27ac, H3K4me3 and

H3K36me3) in the right subTAD. This demonstrates that, although TADs were traditionally

considered to be a fundamental unit of chromatin organization, epigenetic features can be

distinctively different between subTADs. Our results show that the subTADs identified by

OnTAD better represent homogeneous units associated with epigenetic functions, capturing

distinct functional features within subTADs. By identifying these subTADs, OnTAD enables a

finer investigation of the hierarchy of chromatin organization and its functionally homogeneous

structures.

Interestingly, we observed that whereas the outer TAD (11.8Mb – 12.0Mb) had clear CTCF

signals at its boundaries, the shared boundary between the two subTADs (11.8Mb – 11.9Mb

and 11.9Mb – 12.0Mb) had no CTCF signals from the CTCF ChIP-seq data. This indicates that

the formation of these two subTADs is probably independent of CTCF. Furthermore, we

performed a high-resolution compartment analysis (See Methods). It showed that the two

subTADs fall in different compartments. These results can be interpreted within the framework

of recently proposed 'compartmental domains' [33,34], which are hypothesized to be formed by

A/B compartment without the involvement of CTCF. We will discuss this mechanism further in

the discussion.

Discussion

While hierarchical structures in TAD formation have been reported [15,16,18,19], the

involvement of these hierarchies in gene regulation mechanisms remains poorly understood.

This is partly due to the lack of a method that systematically identifies TAD hierarchies from Hi-

C data and investigates the association of TAD hierarchies with epigenetic features. Here we

introduce OnTAD, a new method to uncover the hierarchical TAD structures from Hi-C data.

Based on a dynamic programming procedure that recursively finds the best domain partition of

Hi-C contact matrix in a hierarchical manner, OnTAD identifies the hierarchy of TADs and their

boundaries. It produces a convenient output for visualizing the hierarchy in a genome browser,

greatly facilitating the investigation of the interplay between hierarchical TADs and other

epigenetic features in gene regulation. Our comprehensive evaluation shows that OnTAD

substantially outperforms the existing TAD calling methods in both accuracy and computational

efficiency. These results demonstrated the effectiveness of OnTAD for identifying TAD
hierarchies and investigating their biological functions.
342
Using the results from OnTAD, we investigated how hierarchies within TADs were associated
with features related to function. In particular, we observed that, on average, hierarchical TADs
were significantly more active than TADs without hierarchies (i.e. singletons). The active
epigenetic states and active genes were also significantly more enriched in the boundaries
shared by multiple TADs (e.g. hub-boundaries) than those used exclusively by a single TAD.
These observations echo those on the hierarchy of metaTADs, which also showed a positive
association between the enrichments in promotor activity and gene density and boundary usage
[20]. Interestingly, we also observed a significant asymmetry in boundary usage between the left
and right boundaries in the hierarchical TADs and an asymmetry in the orientation of TAD
formation around hub-boundaries, supporting the asymmetric loop extrusion model [26] and
preferential orientation of promoter interaction [27].
354
Our results pose several interesting questions about the mechanisms utilized to form these
structures. First, how are these hierarchical TADs structures formed? Are they produced by
hierarchical chromatin folding in single cells, or does the nesting reflect a collection of different
interaction patterns in individual cells that looks like a hierarchy when the data from a population
of cells is aggregated in bulk cell Hi-C data? Single-allele chromatin interactions do reveal
regulatory hubs [35], supporting the interpretation that these complex interactions occur in
individual cells. A recent single-cell analysis of high-throughput Oligopaint labeling and imaging
on Chr21 of A549 cell, showed that both TAD and sub-TAD structures exist in single cells [36].
Furthermore, nested TAD structures could be formed by multi-site interactions in a single cell
[36]. However, as acknowledged by the authors, it is still possible that some other domain
structures resulted from population averaging. In principle, OnTAD can also be applied to
single-cell Hi-C data to explore this question. However, the genome coverage in current single-
cell Hi-C data is still low and can only support the analysis at the resolution of ~100Kb, limiting
the detection of finer domain structures (typically ~50Kb for subTADs we identified). Future
studies with higher resolution single-cell Hi-C data will be valuable for addressing this question
at a genome-wide scale.
371
Second, what are the mechanisms to form the hierarchical structures? As observed in our
analyses (Figure 5), though the majority of the outer TAD boundaries were bound by CTCF,

some subTADs appear to be formed without CTCF binding at their boundaries. The formation

of the latter can be explained by the recently proposed 'compartmental domains' mechanism

[34], which forms domains by establishing A/B compartments without the involvement of CTCF

or loop extrusion. Because OnTAD does not rely on CTCF information for TAD identification, it

can capture all domain structures, regardless the formation mechanisms. The example in Figure

5 could be explained by joint processes of loop extrusion (for the outer TAD) and establishment

of 'compartmental domains' [34] for the inner TADs.

In summary, we have demonstrated that the hierarchies of TAD structures are

associated with gene regulation and have provided a powerful tool for exploring this association.

Though previous results based on low-resolution data suggest that the majority of TAD

structures are conservative across cell lines [11], recent analyses found that certain locally

frequent interaction regions within TADs are cell type specific [25]. It will be particularly

interesting to use OnTAD to systematically investigate how the finer domain structures within

TADs differ across cell types, for example, how the levels of hierarchy differ across cell types,

and how the changes in hierarchy are associated with differential gene regulation. The

biological insights generated by analyses of the finer domain structures should help improve our

understanding of the role of chromatin conformation in gene regulation.

Methods

Notations and data preprocessing

Let X denote a symmetric Hi-C matrix, where each entry (i,j) in the matrix is a value quantifying

the strength of the chromatin interaction of between bins i and j. The Hi-C matrix can be raw

contact matrix or the normalized matrix produced by the normalization procedures such as ICE

[37] and KR [17]. Let $X[a{:}b,\ c{:}d] = \{(i,j){:}\ a \leq i \leq b,\ c \leq j \leq d\}$ denote a sub-matrix of X. A candidate

TAD between bins a and b corresponds to a diagonal block matrix $X_{[a,b]}{=}X[a{:}b,\ a{:}b]$, where the

mean of the entries in $X_{[a,b]}$ is expected to be higher than that in its neighboring matrices.

Because of the distance dependency in Hi-C data, i.e., the dependence of contact frequency on

the proximity of the interaction loci, we normalize the Hi-C matrix before TAD calling by

subtracting the mean counts at each distance.

Identification of candidate TAD boundaries

We identify candidate TAD boundaries using a procedure motivated from the TOPDOM method

[13]. This procedure scans the diagonal of the Hi-C matrix, using a sliding square submatrix

whose bottom corner locates on the diagonal (Figure 1a), and computes the mean Hi-C signals

covered by the submatrix at each location, which is the TOPDOM statistic in [13]. As shown in

[13], when the corner of the submatrix lands on a TAD boundary, the TOPDOM statistic reaches

a local minimum. Thus, the local minimums of the TOPDOM statistic can be used as candidate

boundaries. The original TOPDOM paper only computed the statistics at a fixed window size. To

identify all candidate TAD boundaries for TADs in different sizes, the TOPDOM statistics are

calculated at all window sizes (W), ranging from 1 to a maximum TAD size (d) specified by

users. Here, we set the minimum size =3 bins, because structures smaller than 3 bins are too

small to form a domain. We set the maximum size=200 for 10kb Hi-C data, because TADs are

known to be smaller than a few Mbs.

For each window size W, we first obtained a set of local minimums of the TOPDOM statistics,

which are defined as the smallest value in the neighborhood of [i-Lsize, i+Lsize]. To reduce

false positives due to noise, the local minimums that are not significantly smaller than the local

maximums in the same neighborhood are pruned. Here we required the local minimums to be at

least 1.96S smaller than the local maximums to be qualified as a candidate boundary, where S

is the standard deviation of the TOPDOM statistic in the entire matrix. The parameter 1.96 is

chosen based on the 95% confidence level of a normal distribution, which reasonably

approximates the distribution of TOPDOM scores.

Figure 1b shows examples of the local minimums on the genome at different window sizes.

Because different window sizes capture the information of TADs in different sizes, we took the

union of the pruned local minimums over all window sizes, and used the corresponding bins as

candidate TAD boundaries. We selected z according to the procedure described in the section

of Parameter Selection. For all the analyses in this work, we used Lsize = 5. It can be adjusted

by users.

Recursive TAD calling algorithm

We developed a TAD calling algorithm to assemble TADs from the candidate boundaries.

Several issues need to be considered in the design of the algorithm in order to produce

biologically meaningful TADs. First, because a region may be shared by multiple TADs, the

scores of these TADs can be strongly correlated. Second, in the TADs with nested structures,

the scores of the TADs and their nested sub-TADs are convoluted. Third, some boundaries may

be shared between TADs. Last, the algorithm needs to be computationally efficient to call TADs

in the genome scale.

To address these issues, we developed a recursive algorithm to identify the TADs that give the

optimal partition of the genome according to a scoring function g(X) related to the strength of Hi-

C signals (see the next section). Our algorithm assumes that any given two TADs are either

disjoint (but can share one boundary) or nested (i.e. one TAD is completely within the other).

This assumption is required for the dynamic programming to find an optimal solution in

polynomial time. While this assumption sometimes may not be true, it greatly reduces the

complexity of the problem while still enabling us to 1) de-convolute nested TAD structures, 2)

impose shared boundaries, and 3) obtain an efficient algorithmic solution. Our evaluation

showed that the majority of the genome follows this assumption (see the subsection below).

Even when it is violated, i.e., the boundaries of the TADs cross each other, our method can still

produce a reasonable approximation (Supplementary Fig.1C).

Briefly, the algorithm works as follows. Given a matrix $X_{[a,b]}$, the algorithm starts at the root level

to first find the best bin i ($a{\le}i{<}b$) to partition the matrix into two submatrices, $X_{[a,i]}$ and $X_{[i,b]}$, such

that $X_{[i,b]}$ is the largest right-most TAD in $X_{[a,b]}$. Since $X_{[a,i]}$ and $X_{[i,b]}$ are disjointed, the TADs

within each submatrix can be called separately in a recursive manner. At each recursive step,

the parent matrix is partitioned into two sub-matrices, and TADs are called within each sub-

matrix using the same recursive formula (Supplementary Fig.2A). The recursion stops when $i{=}a$,

i.e., the sub-matrix $X_{[a,i]}$ contains no TAD. After a recursive step is completed, it identifies the

best TADs in the current branch according to the scoring function, de-convolutes the TAD

signals in the parent matrix by removing signals of inner TADs, and evaluates if the parent

matrix itself is a TAD. This process is repeated until the recursion returns to the root level

(Supplementary Fig.2B). Note that, because every TAD is the largest right-most TAD of a parent

matrix in a recursive branch, this recursive procedure guarantees to traverse all TADs, even

though only the largest right-most TAD is called at each step.

Evaluation of the violation of the hierarchical TAD assumption

To investigate the frequency of the violation of the hierarchical TAD assumption, we ran OnTAD

on high resolution (10Kb) in-situ Hi-C data in GM12878. We segregated regions around the

corner of each TAD into four 5*5 quadrants and calculated the average contact frequency of

each quadrant (Supplementary figure 8). If this assumption holds, the interaction frequency is

expected to be high in the quadrant within TAD (quadrant 1) and relatively low in at least one of

the two quadrants (2 & 3) on the two sides outside of TAD corner. As shown in the

Supplementary figure 8, the mean frequency patterns of the four quadrants for most of the TAD

corners are consistent with our expectations. This suggests that this assumption holds for a

majority of the genome. The violation can be remedied by removing the signals from the called

TADs and then rerunning OnTADs on the de-clumped Hi-C data to identify additional TADs.

The scoring function

Our scoring function $g(X_{[a,b]})$ for matrix $X_{[a,b]}$ is defined as

481
$$g(X_{[a,b]}) = max_i \begin{cases} 0 & i = a \\ \max\left(0, g(X_{[a,i]}) + h(X_{[i,b]})\right) & i = a+1, \dots, b-1 \end{cases} \tag{1}$$

where $h(X_{[i,b]}) = g(X_{[i,b]}) + \Delta(X_{[i,b]}|\text{sub TADs})$

Here, $g(X_{[a,b]})$ is the score of TADs within $X_{[a,b]}$, not including the score for $X_{[a,b]}$ itself being a

TAD. It is calculated by finding the best left boundary of the largest right-most TAD in $X_{[a,b]}$.

$h(X_{[i,b]})$ is the score of the largest right-most TAD in $X_{[a,b]}$. It is the sum of the score of TADs

within $X_{[i,b]}$ and the score of $X_{[i,b]}$ itself being a TAD, namely $\Delta(X_{[i,b]}|\text{sub TADs})$. For any

diagonal block matrix to be called a TAD, its mean signal is required to be greater than the

means of its neighboring regions on both sides. We therefore define

$$\Delta(X_{[i,b]}|sub\ \text{TADs})$$
$$= m(X_{[i,b]}|\text{sub TADS})$$
$$- \max\left(\overline{X[(i-(b-i+1)):(b-(b-i+1)),i:b]}, \overline{X[i:b,(i+(b-i+1)):(b+(b-i+1))]}\right) - \lambda$$

where $m(X_{[i,b]}|\text{sub TADs})$ denotes the mean of $X_{[i,b]}$, excluding the TADs within $X_{[i,b]}$, returned by

the   recursion; λ is   a   user-specified   nonnegative   penalty   parameter   ;

$X[(i-(b-i+1)):(b-(b-i+1)),i:b]$ and $X[i:b,(i+(b-i+1)):(b+(b-i+1))]$ are two (b-i+1)-by-(b-i+1) off-

diagonal matrices in the adjacent flanking regions of $X_{[i,b]}$; and finally, and $\bar{X}$ denotes the mean

of X. We note that $\Delta(X_{[i,b]}|sub\ \text{TADs})$ is calculated based on the TADs returned from $g(X_{[i,b]})$.

That is, we do not directly optimize $g(X_{[i,b]}) + \Delta(X_{[i,b]}|sub\ \text{TADs})$. The parameter λ serves as a

threshold for TAD calling. That is, a TAD will be called only when the mean contact frequency

within the potential TAD area between the boundaries exceeds that of the surrounding area

outside of the TAD by the margin of λ. The procedure for selecting λ is described in Parameter

Selection.

When the score of a candidate TAD is <0, it is likely not a real TAD. We therefore set a lower

bound on the score at 0 and do not output the "TAD" with a score 0.

Parameter Selection

We selected the value of λ based on the False Discovery Rate (FDR) of TADs identification.

The FDR is calculated as follows. First, the entries in the real Hi-C matrix are permuted within

each genomic distance. This results in a null Hi-C matrix that has the same marginal signal

distribution as the original Hi-C matrix but without biologically meaningful TAD structures. Next,

OnTAD is run on both the original and the permuted Hi-C matrix for a series of λ. The TADs

identified from the original Hi-C matrix are treated as 'discoveries' (R), which is a mixture of

false and true discoveries, and those from the permuted Hi-C matrix are treated as 'false

discoveries' (V), which is used to approximate the proportion of false discoveries in R. Recall

that OnTAD assigns each TAD a score according to the scoring function (1). Given a TAD size,

the magnitude of the score reflects the strength of evidence to call TAD. Because larger TADs

tend to have a lower mean contact frequency after removing their inner TADs, the score is

usually smaller for larger TADs. Therefore, we computed the FDR accounting for TAD size.

Specifically, for a given value of λ, the identified TADs are first stratified by their sizes and

scores. Let n be the total number of TADs identified on the original matrices, and R_i and V_i be

the numbers of TADs in the ith stratum from the original and the permuted matrices,

respectively. Then if a TAD (j) is in the ith stratum, the probability for the TAD to be a false

discovery (a.k.a. local false discovery rate [38] is

$$p_j = \min\left(\frac{V_i}{R_i}, 1\right)$$

The overall FDR for the TAD identification is computed as the average of the probability to be a

false discovery over all TADs identified on the original matrix, based on the relationship between

local fdr and FDR [38]:

$$FDR = \frac{\sum_{j=1}^{n} p_j}{n}$$

The above FDR calculation is repeated for each value of λ, and the λ corresponding to the FDR

cutoff of 0.05 is selected.

In our analysis, the stratum is formed by dividing the TAD calls into 25 equal shares according

to the ranking of TAD size (or TAD score, respectively) on the real matrix. This leads to

25*25=625 strata in total. As shown in Supplementary table 3, the FDR is close to 0.05 at λ =

0.1 for GM12878 dataset (10kb). To test the robustness of the tuned parameter, we also

performed the same procedure on the mouse G1E-ER4 Hi-C data from Hsu et al. [32] at 10Kb

resolution. The FDR was also controlled at the 0.05 level when λ = 0.1 (Supplementary table 4).

Therefore, we used λ = 0.1 as the default value in our analyses. In the OnTAD software, we

allow users to specify the value of λ to offer more flexibility.

Another important tuning parameter is Lsize, which is the span of the interval (i.e. the interval

size = 2*Lsize +1) for searching local minimums of the TOPDOM statistics. This parameter

affects the selection of candidate boundaries. If Lsize is too large, some potential boundaries

will be missed. If Lsize is too small, the candidate boundary set may include many false

positives, increasing the computational burden for the assembly step and the quality of final

results. We chose Lsize in the similar way as for choosing λ on GM12878 data (10kb).

Specifically, we ran OnTAD for different values of Lsize (range=3-10), corresponding to the

interval size of 7-21 bins. We chose this range because it is sufficient to cover various TAD

sizes. As shown in Supplementary table 5, Lsize=5 (i.e. interval size=11) renders an FDR close

to 0.05. Therefore, we chose Lsize=5 for all analyses. To evaluate the robustness of this choice,

we evaluate the similarity of the identified TAD structures between Lsize=5 and Lsize=6-10, and

found that they are similar, with the median of the adjusted rand indices >0.75 (Supplementary

figure 10). It indicates the result is relatively insensitive to the value of Lsize when Lsize=5~10.

Computation complexity of the TAD calling algorithm

We performed an analysis on the computational complexity for our recursive algorithm. For an

lxl Hi-C matrix, if all bins are potential boundaries, then the recursion needs to visit $l(l+1)/2$

diagonal block sub-matrices. As there are l size 1 diagonal block matrices, the computation

complexity for computing the scores of all size 1 matrices is O(l). Given the scores of size 1

matrices, we can calculate the scores of size 2 matrices. There are (l-1) of them, each

enumerating through (2-1) partitions. Hence the time complexity is O((2-1)(l-1)). Following the

same calculation, the scores of one sub-matrix of size k will be computed by enumerating (k-1)

partitions. As there are (l-k+1) of them, the time complexity is O((k-1)(l-k+1)). Similar calculation

can be done for the mean of sub-matrices. As a result, the total complexity to obtain the scores

of all sub-matrices from size 1 to l is O(l^3).

Empirically, the computational complexity is much lower than the above due to some further

reductions. First, because potential TAD boundaries are limited to the TOPDOM local minimums,

this substantially reduces the number of partitions from O(l^3) to O(m^3), where m is the number of

candidate boundaries. Second, because TADs usually are smaller than 2Mb, the maximum TAD

size to be called (d) typically is much smaller than l. This constraint effectively reduces the time

complexity of our algorithm from O(m^3) to O(md^2). Furthermore, because TADs usually are

formed between neighboring boundaries, we set a constraint in the recursive procedure to limit

the TADs to be formed only between candidate boundaries that are no more than five neighbors

apart.

TAD-adjR^2 for assessing accuracy of TAD calling

Because TADs are regions with frequent local interactions, a reasonable TAD caller is expected

to classify the regions with high contact frequencies as TADs and the regions with low contact

frequencies as non-TADs, i.e. gaps between TADs. At any given genomic distance, the

variation between Hi-C signals should be largely explained by the classification of TADs. How

well the variation can be explained by the classification of TADs can reflect the accuracy of TAD

calling. Based on this intuition, we developed a metric similar to the R-square in regression

models to evaluate the accuracy of TAD calling. Let Y_i denote the contact frequency of the ith

bin, n denote the number of bins at the same genomic distance as this bin, p denotes the

number of called TADs whose sizes are greater than or equal to the genomic distance. For bins

within TAD, $\hat{Y}_i$ denotes the average contact frequency at given genomic distance within that

TAD, excluding regions covered by higher level TADs. For those bins not in any TADs, $\hat{Y}_i$ is the

average of contact frequency in the gap region at that genomic distance. And $\bar{Y}$ denote the

overall mean contact frequency across all the bins at a given genomic distance. For each

genomic distance, the TAD-adjR^2 is defined as

$$\hat{R}^2_{tad} = 1 - \frac{\frac{1}{n-p-1}\sum_{i=1}^{n}\left(Y_i - \hat{Y}_i\right)^2}{\frac{1}{n-1}\sum_{i=1}^{n}(Y_i - \bar{Y})^2}$$

This quantity essentially measures the proportion of variance in Hi-C signal that is explained by

the classification of TADs, adjusting for the number of TADs and genomic distance.

Enrichment of expressed genes

To evaluate the activity of gene expression, we downloaded the RNA-seq data from ENCODE

(See Data), merged the biological replicates of RNA-seq data, and computed the average

FPKM for each gene. Genes with FPKM > 5 were deemed as expressed genes. For each TAD

level, we compute the density of expressed gene as the number of expressed genes per 10Kb.

For TADs with nested structures, genes covered by the inner level TADs are excluded in the

calculation of gene density for outer TADs.

Enrichment of CTCF or cohesin protein signals

To compute the enrichment of CTCF (or cohesin protein) signals at the identified boundaries

and their surrounding regions, we computed the average CTCF (or cohesin proteins) signals

from ChIP-seq data at the identified boundaries and the bins within their 10bins flanking regions.

The processed signals in bigwig file was used in this process.

Epigenetic state enrichment

We downloaded the IDEAS segmentation (see Data), which segments the genome into 36

epigenetic states based on 10 epigenomic marks [23]. We used it to evaluate the enrichment of

epigenetic state in the identified (sub)TADs and boundaries. Let n_i denote the total number of

200bp windows that have IDEAS-assigned epigenetic states at a TAD boundary i, and $n_{s,i}$

denote the number of 200bp windows annotated as state s at a TAD boundary i. For a given

state s, its enrichment in a set of M boundaries is computed as

$$E(s) = \frac{\sum_{i=1}^{M} n_{s,i} + 1}{B_s \sum_{i=1}^{M} n_i + 1}$$

where B_s is the proportion of state s in the whole genome. The 1's in the formula of E(s) are

added to avoid dividing by 0.

A/B compartments calling

We used CscoreTool [39] to infer A/B compartments from mouse G1E-ER4 Hi-C data (10Kb

resolution, default parameter). The A/B compartments is determined by correlation coefficient

between compartment score and ATAC-seq signal. If a positive correlation coefficient is

observed, then regions with score>0 are in compartment A. Otherwise, if the correlation

coefficient is below 0, the regions with score < 0 are in compartment A. We reversed the

compartment scores on the chromosomes that has correlation coefficient < 0. Thus,

compartment A is shown with positive score and compartment B is shown with negative score.

Data

Hi-C data: The human Hi-C data is obtained from Rao et al. 2014 (GEO accession number:

GSE63525). Among them, three cell types (B-lymphoblastoid cells (GM12878), umbilical vein

endothelial cells (HUVEC) and erythrocytic leukemia cells (K562)) were included in this study.

The normalized (by Knight-Ruiz balancing method) Hi-C matrices at 5Kb, 10Kb and 25Kb

resolutions were used in this study. The mouse Hi-C data is obtained from Hsu et al. 2017

[32](GEO accession number: GSE95476). The 10Kb raw Hi-C matrices from G1E-ER4 and two

Brd2 knockouts were used in this study.

Transcriptomic data: The gene expression data were downloaded from the ENCODE project

(https://www.encodeproject.org/). The processed signal (FPKM) was used to measure the

expression activity.

Epigenomic data: The histone modification data were downloaded from the NIH Roadmap

Epigenomics project (http://www.roadmapepigenomics.org/), including H2A.Z, H3K27ac,

H3K27me3, H3K36me3, H3K4me1, H3K4me2, H3K4me3, H3K79me2, H3K9ac, H3K9me3 and

H4K20me1. The ChIP-seq data of CTCF and cohesin protein (Rad21 and Smc3) were

downloaded from ENCODE project (https://www.encodeproject.org/). The downloaded data

were in BigWig format. The 'bigWigAverageOverBed' was used to segment signal into windows

according to the resolution of Hi-C data. The mouse ChIP-seq data were downloaded from the

VISION project (http://www.bx.psu.edu/~giardine/vision/).

Epigenetic states: The IDEAS segmentation of the 6 ENCODE cell type/tissues (GM12878,

H1h-ESC, Hela-S3, HepG2, HUVEC, K562) was downloaded from (http://main.genome-

browser.bx.psu.edu/). The 36-state IDEAS model trained on 10 marks (H3K4me1, H3K4me2,

H3K4me3, H3K9ac, H3K27ac, H3K27me3, H3K36me3, H3K20me1, PolII and CTCF), as well

as DNase-seq and Faire-seq, was applied to this study.

Figure Legends

Figure 1 | Overview of the OnTAD pipeline. a, OnTAD uses a sliding diamond-shaped window to calculate the average contact frequency within the window at each locus on the genome. The five loci marked by letters 'a'-'e' are examples being evaluated as potential TAD boundaries, with 'd' being a clear false positive. **b,** Identification of candidate TAD boundaries in OnTAD. Blue curve: the average contact frequency of the diamond-shaped windows, calculated at different window sizes (W) and different loci. Red arrows: the location of significant local minimums of the average contact frequency, i.e. candidate TAD boundaries. **c,** OnTAD assembles candidate boundary pairs using a Dynamic Programming algorithm (see methods) **d,** Visualization of the final output from OnTAD. In the genome browser, the identified hierarchical TAD is displayed as a series of horizontal bars, where each (sub)TAD is represented as a horizontal bar colored according to its TAD level.

Figure 2 | Evaluation of TAD calling methods. a, Average ChIP-Seq signal at TAD boundaries and surrounding regions (+/- 10 bins) (from left to right, CTCF, SMC3 and RAD21). **b,** Proportions of Hi-C signal variability explained by the called TADs (measured by TAD-adjR^2) at different genomic distance between two interacting loci. (Average TAD-adjR^2: OnTAD: 0.33, Arrowhead: 0.26, DomainCaller: 0.26, rGMAP: 0.23 and TADtree: 0.06). **c-e,** Reproducibility of TAD boundaries (Jaccard index): **c,** between two biological replicates (GM12878, 10Kb) **d,** between resolutions (5Kb vs 10Kb) and (10Kb vs 25Kb). **e,** across different down sampled sequencing depths (GM12878, original vs 1/4, 1/8, 1/16 and 1/32 of the original sequencing depth, raw data was used). Note: TADtree was not included in **d**, because it has difficulty handling data with 5Kb resolution due to its large memory consumption. It also has difficulty for chr1-3 at 10Kb resolution either. Thus these three chromosomes were excluded for all TAD callers in all comparisons.

Figure 3 | Hierarchical TADs are more active than singletons. a, An illustration of hierarchical levels of TADs. The levels are assigned from external to internal. The TADs covered by cyan dash line are assigned to level 1, by blue dash line are assigned to level 2, by orange dash line are assigned to level 3, and singletons are also assigned to level 1 (cyan). **b,** mean CTCF signal at the boundaries specific to hierarchical TADs (light green), specific to singletons (cyan), and shared between hierarchical TADs and singletons (orange). The boundaries of hierarchical TADs have the highest enrichment of CTCF signal. **c-d,** Enrichment of epigenetic states at the regions covered by different levels of TADs. The enrichment (fold

change) of active states (marked in orange in **c**) increases as the TAD level increases. The

trend is visualized for the states of Tss, Enh and PromCtcf in **d.** The whole-genome average is

used as the background for calculating enrichments. **e-f,** Density of expressed gene in different

levels of TADs in GM12878 (**e**) and K562 (**f**).

Figure 4 | Hub-boundaries are highly active in gene regulation. a, An illustration of the TAD

boundary levels. The boundary levels are defined as the maximum number of TADs that use a

boundary on either its left or right side. The yellow, purple and red dots refer to boundaries of

level 1, 2, and 3, respectively. **b,** Enrichment of epigenetic states at different levels of TAD

boundaries. Hub-boundaries (i.e. boundaries with level =5) are significantly enriched with Tss

related states than others. (Active epigenetic states are marked in orange) **c,** Distribution of

gene expression levels for genes whose transcription start sites overlap with TAD boundaries.

Genes are classified by the level of TAD boundaries. **d,** Illustration of hierarchical TAD and

asymmetric loop extrusion. The red boundary denotes the 'anchor' site that starts the loop

extrusion in asymmetric loop extrusion model. Boundaries in other colors are the stopping sites

of the loop extrusion. The hierarchical TADs are formed by multiple stops of the loop extrusion

that share the same start site. **e**, TFs enriched (Fold Change >2) at hub-boundaries in

GM12878 and K562 cell lines. The fold change of ChIP-seq TF peaks at hub-boundaries (level

=5) against level 1 boundaries is shown.

Figure 5 | subTADs exhibit distinctive epigenetic profiles. The captured region is

chr19:11.3Mb – 12.2Mb in mouse G1E-ER4. The Hi-C heatmap shows a nested TAD structure

in this region. OnTAD results are displayed in the genome browser track: blue line denotes level

1 TAD, green line denotes level 2 TAD, purple denotes level 3 TAD and orange denotes level 4

TAD. The two subTADs (orange lines) exhibit distinctive epigenetic features, with one enriched

with repressive signals (H3K27me3) and silenced expression (low RNA-Seq signal) and the

other enriched with active signals (H3K27ac, H3K4me3, and H3K36me3) and expression (high

RNA-Seq signal). The shared boundary (marked by dash box) between these two subTADs has

no CTCF peak, indicating the formation of these two subTADs may not involve loop extrusion.

Supplementary figure 1 | Illustration of convoluted TAD structures. a, Candidate TADs (a,c)

and (b,d) are both suboptimal, as their scores may be driven by a real TAD (b,c). **b,** Two real

TADs (a,c) and (b,c) are nested, which makes the score of (a,c) convoluted with the score of

(b,c). **c,** Real TADs (a,c) and (b,d) are partially overlapping, which may be recaptured as nested

TADs (b,c), (a,c) and (a,d).

Supplementary figure 2 | Illustration of the recursive TAD calling algorithm. a, At the first

step of the algorithm, the entire Hi-C matrix is partitioned into two matrices, the one forming the

largest right-most TAD (i.e. triangles marked in black) and the remaining part, according to a

score function. Then the same function is called on each sub-matrix to recursively identify

nested TAD structures. **b,** Each recursion step identifies the best set of TADs in its matrix under

consideration according to the score function, and returns the TAD calls back to its parent until

the root.

Supplementary figure 3 | TAD reproducibility under different measurements. a, Adjusted

rand index between TADs from two biological replicates (GM12878, 10Kb). **b**, Adjusted rand

index across TADs from Hi-C data in multiple resolutions (GM12878, 5Kb, 10Kb and 25Kb).

TADtree is not included because it has difficulty finishing the computation on high resolution

data due to its high memory consumption. **c**, Adjusted rand index between TADs from Hi-C data

in original sequencing depth and in different down sampled sequencing depth (GM12878, 1/4,

1/8, 1/16 and 1/32 of original sequencing depth).

Supplementary figure 4 | Enrichment of epigenetic states at the boundaries of different

levels of TADs. Enrichment of epigenetic states at the regions covered by different levels of

TADs. The enrichment (fold change) of active states (orange states) increases as the TAD level

increases. **a,** K562 **b,** Huvec

Supplementary figure 5 | Comparison between boundaries and inside TADs a, Distribution

of RNA-seq signal (FPKM) at the boundaries (blue) and within TADs (red) **b,** Enrichment of

active epigenetic states at the TAD boundaries (solid line) versus inside TADs (dashed line). Y-

axis denotes fold enrichment of three active epigenetic states (Tss, Enh and PromCtcf). X-axis

denotes the boundaries and TADs at different levels.

Supplementary figure 6 | Distribution of the levels of TAD boundaries.

Supplementary figure 7 | Protein-protein interaction network of hub-boundary-enriched

TFs from STRING database. Each node denotes a TF that are at least 2-fold enriched at hub-

boundary over level1 boundary (n=37). Each edge denotes the interaction potential between

two TFs, with thicker edges corresponding to higher interaction confidence. Interaction data was

downloaded from STRING database (https://string-db.org/)

Supplementary figure 8 | Contact frequency is unbalanced between the two sides of

hierarchical TAD corners. The regions around TAD corners are segregated into four

quadrants (1-4 on the top right figure). We then averaged contact frequency of each TAD corner

by quadrants. As shown in the heatmap, the majority quadrant 2 and 3 shows unequal average

contact frequencies, suggesting that the inner TADs tend to be formed on one side of the outer

TADs, rather than on both sides. Quadrant 1 has the highest average contact frequency

because it is within TADs.

Supplementary Figure 9 | Comparison of OnTAD results between raw Hi-C and

normalized Hi-C in GM12878 (10kb). a, Enrichment of CTCF signal at identified TAD

boundaries and surrounding regions (+/- 10 bins) in raw Hi-C matrix and normalized Hi-C matrix.

Y-axis: The average ChIP-Seq signal. **b**, TAD-adjR^2 of OnTAD results at difference genomic

distance in raw Hi-C matrix and normalized Hi-C matrix. The results on normalized data show a

slightly higher enrichment of CTCF at boundary and a higher TAD-adjR^2. The normalized Hi-C

matrices were generated by Knight-Ruiz balancing [40] method. **c**, The proportion of boundaries

identified in raw data that are recovered in normalized data. Grey: exact match; Green: one bin

offset allowed when matching the boundaries identified in raw and normalized data. Half of the

boundaries identified in the raw data precisely match with the boundaries identified in the

normalized data. If we allow one bin offset when matching the locations of the boundaries, over

71% of the high-level TAD boundaries (level 2+) are matched between the results from raw data

and normalized data.

Supplementary Figure 10| Similarity between the (sub)TADs identified at Lsize = 5 and at

other Lsizes.

Supplementary Table 1 | Comparison of running time of different methods on high

resolution Hi-C data (GM12878 10Kb) (unit: seconds).

Supplementary Table 2 | Number of TADs on each side of a boundary that share this

boundary (GM12878 10Kb).

Supplementary Table 3 | The FDR and number of TADs under each penalty value. (GM12878, average on 100 permutations)

Supplementary Table 4 | The FDR and number of TADs under each penalty value. (G1E-ER4, average on 100 permutations)

Supplementary Table 5 | The FDR and number of TADs under each Lsize. (GM12878, average on 100 permutations)

Supplementary File1 | Commands for operating other TAD calling methods.

Declarations

Acknowledgments

This work was supported by the NIH R01 GM121613, NIH R01GM109453 and NIH R24 DK106766, NIH training grant T32 GM102057 (CBIOS training program to The Pennsylvania State University), a Huck Graduate Research Innovation Grant, and 4D Nucleome NIH Initiative DK107980 (Center for 3D Structure and Physics of the Genome).

Availability of data and materials

OnTAD is available at https://github.com/anlin00007/OnTAD.

Authors' contributions

YZ and LA implemented OnTAD. YZ and QL conceived the method. LA, TY, GX and JY conducted the analysis. LA, YZ, QL, TY and RCH wrote the manuscript with assistance from the other authors. JN assisted the interpretation of the results. All authors read and approved the final manuscript.

Competing interests

The authors declare that they have no competing interests.

Reference

1. Won H, De La Torre-Ubieta L, Stein JL, Parikshak NN, Huang J, Opland CK, et al. Chromosome conformation elucidates regulatory relationships in developing human brain. Nature. 2016;

2. Dekker J, Rippe K, Dekker M, Kleckner N. Capturing chromosome conformation. Science (80-).
2002;
3. Dekker J, Marti-Renom MA, Mirny LA. Exploring the three-dimensional organization of
genomes: Interpreting chromatin interaction data. Nat. Rev. Genet. 2013.
4. Fullwood MJ, Ruan Y. ChIP-based methods for the identification of long-range chromatin
interactions. J Cell Biochem. 2009;
5. Mumbach MR, Rubin AJ, Flynn RA, Dai C, Khavari PA, Greenleaf WJ, et al. HiChIP: Efficient
and sensitive analysis of protein-directed genome architecture. Nat Methods. 2016;
6. Dekker J. The three "C" s of chromosome conformation capture: Controls, controls, controls.
Nat Methods. 2006;
7. Dostie J, Richmond TA, Arnaout RA, Selzer RR, Lee WL, Honan TA, et al. Chromosome
Conformation Capture Carbon Copy (5C): A massively parallel solution for mapping interactions
between genomic elements. Genome Res. 2006;
8. Zhao Z, Tavoosidana G, Sjölinder M, Göndör A, Mariano P, Wang S, et al. Circular
chromosome conformation capture (4C) uncovers extensive networks of epigenetically
regulated intra- and interchromosomal interactions. Nat Genet. 2006;
9. Lieberman-Aiden E, Van Berkum NL, Williams L, Imakaev M, Ragoczy T, Telling A, et al.
Comprehensive mapping of long-range interactions reveals folding principles of the human
genome. Science (80-). 2009;
10. Dixon JR, Gorkin DU, Ren B. Chromatin Domains: The Unit of Chromosome Organization.
Mol. Cell. 2016.
11. Dixon JR, Selvaraj S, Yue F, Kim A, Li Y, Shen Y, et al. Topological domains in mammalian
genomes identified by analysis of chromatin interactions. Nature. 2012;
12. Dixon JR, Jung I, Selvaraj S, Shen Y, Antosiewicz-Bourget JE, Lee AY, et al. Chromatin
architecture reorganization during stem cell differentiation. Nature. 2015;
13. Shin H, Shi Y, Dai C, Tjong H, Gong K, Alber F, et al. TopDom: An efficient and deterministic
method for identifying topological domains in genomes. Nucleic Acids Res. 2015;
14. Crane E, Bian Q, McCord RP, Lajoie BR, Wheeler BS, Ralston EJ, et al. Condensin-driven
remodelling of X chromosome topology during dosage compensation. Nature. 2015;
15. Weinreb C, Raphael BJ. Identification of hierarchical chromatin domains. Bioinformatics.
2016;
16. Yu W, He B, Tan K. Identifying topologically associating domains and subdomains by
Gaussian Mixture model and Proportion test. Nat Commun. 2017;
17. Rao SSP, Huntley MH, Durand NC, Stamenova EK, Bochkov ID, Robinson JT, et al. A 3D map
of the human genome at kilobase resolution reveals principles of chromatin looping. Cell. 2014;
18. Norton HK, Emerson DJ, Huang H, Kim J, Titus KR, Gu S, et al. Detecting hierarchical genome
folding with network modularity. Nat Methods. 2018;
19. Haddad N, Vaillant C, Jost D. IC-Finder: Inferring robustly the hierarchical organization of
chromatin folding. Nucleic Acids Res. 2017;
20. Fraser J, Ferrai C, Chiariello AM, Schueler M, Rito T, Laudanno G, et al. Hierarchical folding
and reorganization of chromosomes are linked to transcriptional changes in cellular
differentiation. Mol Syst Biol. 2015;
21. Sanborn AL, Rao SSP, Huang S-C, Durand NC, Huntley MH, Jewett AI, et al. Chromatin
extrusion explains key features of loop and domain formation in wild-type and engineered

genomes. Proc Natl Acad Sci. 2015;

22. Ho JWK, Jung YL, Liu T, Alver BH, Lee S, Ikegami K, et al. Comparative analysis of metazoan
chromatin organization. Nature. 2014;

23. Zhang Y, An L, Yue F, Hardison RC. Jointly characterizing epigenetic dynamics across multiple
human cell types. Nucleic Acids Res. 2016;

24. Dunham I, Kundaje A, Aldred SF, Collins PJ, Davis CA, Doyle F, et al. An integrated
encyclopedia of DNA elements in the human genome. Nature. 2012;

25. Schmitt AD, Hu M, Jung I, Xu Z, Qiu Y, Tan CL, et al. A Compendium of Chromatin Contact
Maps Reveals Spatially Active Regions in the Human Genome. Cell Rep. 2016;

26. Ganji M, Shaltiel IA, Bisht S, Kim E, Kalichava A, Haering CH, et al. Real-time imaging of DNA
loop extrusion by condensin. Science (80-). 2018;

27. Zheng M, Tian SZ, Capurso D, Kim M, Maurya R, Lee B, et al. Multiplex chromatin
interactions with single-molecule precision. Nature. 2019;566:558–62.

28. Kschonsak M, Merkel F, Bisht S, Metz J, Rybin V, Hassler M, et al. Structural Basis for a
Safety-Belt Mechanism That Anchors Condensin to Chromosomes. Cell. 2017;

29. Gerstein MB, Kundaje A, Hariharan M, Landt SG, Yan KK, Cheng C, et al. Architecture of the
human regulatory network derived from ENCODE data. Nature. 2012;

30. Wang J, Zhuang J, Iyer S, Lin XY, Whitfield TW, Greven MC, et al. Sequence features and
chromatin structure around the genomic regions bound by 119 human transcription factors.
Genome Res. 2012;

31. Wang J, Zhuang J, Iyer S, Lin XY, Greven MC, Kim BH, et al. Factorbook.org: A Wiki-based
database for transcription factor-binding data generated by the ENCODE consortium. Nucleic
Acids Res. 2013;

32. Hsu SC, Gilgenast TG, Bartman CR, Edwards CR, Stonestrom AJ, Huang P, et al. The BET
Protein BRD2 Cooperates with CTCF to Enforce Transcriptional and Architectural Boundaries.
Mol Cell. 2017;

33. Rowley MJ, Nichols MH, Lyu X, Ando-Kuri M, Rivera ISM, Hermetz K, et al. Evolutionarily
Conserved Principles Predict 3D Chromatin Organization. Mol Cell. 2017;67:837–852.e7.

34. Rowley MJ, Corces VG. Organizational principles of 3D genome architecture. Nat Rev Genet.
2018;

35. Oudelaar AM, Davies JOJ, Hanssen LLP, Telenius JM, Schwessinger R, Liu Y, et al. Single-allele
chromatin interactions identify regulatory hubs in dynamic compartmentalized domains. Nat
Genet. 2018;

36. Bintu B, Mateo LJ, Su JH, Sinnott-Armstrong NA, Parker M, Kinrot S, et al. Super-resolution
chromatin tracing reveals domains and cooperative interactions in single cells. Science (80-).
2018;

37. Imakaev M, Fudenberg G, McCord RP, Naumova N, Goloborodko A, Lajoie BR, et al. Iterative
correction of Hi-C data reveals hallmarks of chromosome organization. Nat Methods. 2012;

38. Efron B. Size, power and false discovery rates. Ann Stat. 2007;

39. Zheng X, Zheng Y. CscoreTool: Fast Hi-C compartment analysis at high resolution.
Bioinformatics. 2018;

40. Knight PA, Ruiz D. A fast algorithm for matrix balancing. IMA J Numer Anal. 2013;

Figure 1

Figure 2

Figure 3

Figure 4

Figure 5

Supplementary figure 1

a

b

c

Supplementary figure 2

(A) Explore all allowable partitions via recursive partitioning

(B) Best sub partitions are recursively identified and returned

Input matrix

Final result

Supplementary figure 3

Supplementary figure 4

a

b

Supplementary figure 5

a

b

Supplementary figure 6

Supplementary figure 7

Supplementary figure 8

Supplementary figure 9

Supplementary figure 10