Limits on visual awareness for multiple objects: a bottleneck in low-level edge detection rather than high-level representational architecture

Regine Zopf[1,2], Stefan R. Schweinberger[2,4] and Anina N. Rich[1,2,3]

1. Perception in Action Research Centre & Department of Cognitive Science, Faculty of Human Sciences, Macquarie University, Sydney, Australia

2. ARC Centre of Excellence in Cognition and its Disorders, Australia

3. Centre for Elite Performance, Training & Expertise, Macquarie University, Sydney, Australia

4. Department of Psychology, Friedrich Schiller University, Jena, Germany

Corresponding Author:
Dr Regine Zopf
Department of Cognitive Science
Australian Hearing Hub, 16 University Avenue
Macquarie University, NSW 2109
Australia
Email: Regine.Zopf@mq.edu.au
Telephone: +61 (0)2 9850 2956

Keywords: multiple object perception; action; continuous flash suppression paradigm; hands; tools

Abstract

Our capacity to become aware of, and perceive, multiple objects is limited. Cohen et al. (2015, Journal of Cognitive Neuroscience) suggested that visual awareness of multiple objects is (partly) influenced by the representational architecture in higher visual cortex (beyond V1-V3). Using continuous flash suppression (CFS) and visual masking paradigms they found that certain category combinations (e.g., faces/buildings) are more effective in blocking one another from reaching awareness than others (e.g., cars/chairs). Furthermore, they found significant brain-behaviour correlations: more category-pair representational similarity in higher visual cortex was related to longer category-pair breakthrough reaction times. As the cortical representations of hands and tools have been found to overlap, these categories form an ideal test for this theory. Here, we conducted CFS experiments to test this high-level representational architecture bottleneck model and predicted longer CFS breakthrough times for hands/tools compared to hand and other objects pairs. In contrast to predictions of the representational architecture model, we found that participants were generally faster at detecting targets masked by either hands or tools compared to other stimulus category masks (Experiment 1). We replicated this pattern when participants gave vocal responses (Experiment 2), ruling out a simple manual response facilitation explanation. Furthermore, we found the same relative inefficient mask effect for hands in the context of those stimuli used by Cohen et al. (2015) and replicated their behavioural pattern (Experiment 3). To explore alternative explanations for these effects, we analysed category-specific local image characteristics and found that the category average for the amount of edges either across the entire image or within the target area (e.g. hands have less detail compared to cars) were the best predictors for the category differences in breakthrough times. Because edge detection is linked to low-level visual mechanisms (LGN, V1), this suggests a low-level rather than a high-level bottleneck as a major factor influencing visual awareness in the CFS multiple object task. Furthermore, the amount of edges was linked to animacy and real-world object size (fewer edges for animate compared to inanimate objects and for small inanimate compared to large inanimate objects). Because animacy and real-world object size are predictors for neural similarity in higher-visual cortex, these could be potential explanations for the previously reported correlations between breakthrough time and neural similarity. Overall, our findings challenge the idea that the neural representational architecture in higher visual cortex predicts limitations for visual awareness. Instead, they

suggest low-level mechanisms can account for category-specific limitations, at least in the context of a CFS multiple object task.

Introduction

We live in a rich and complex world and are typically surrounded by many different types of objects. However, our ability to perceive and become aware of multiple objects at the same time is limited (Cohen, Dennett, & Kanwisher, 2016; Kim & Blake, 2005; Treisman & Gelade, 1980; Wolfe, Cave, & Franzel, 1989). The mechanisms that underlie these limitations have typically been associated with perceptual inhibitory interactions in low-level visual cortex (Tong, Meng, & Blake, 2006) or with limited attentional capacities in the fronto-parietal network (Desimone & Duncan, 1995). Understanding how our capacity limits are generated is a key question in understanding awareness.

One recent proposal is that perception of multiple objects might be limited by the representational architecture of the higher visual system (Cohen, Konkle, Rhee, Nakayama, & Alvarez, 2014). The idea is that the extent to which high-level visual categories (such as faces, bodies and chairs) have spatially separable neural representations predicts the capacity to simultaneously process multiple items. In a series of experiments using a range of paradigms that involve the presentation of multiple object stimuli next to each other (visual search paradigm: Cohen, Alvarez, Nakayama, & Konkle, 2017; visual memory paradigm: Cohen et al., 2014) or overlapping (visual masking and continuous flash suppression paradigms: Cohen, Nakayama, Konkle, Stantic, & Alvarez, 2015), Cohen and colleagues found that certain category combinations (e.g., faces/buildings) were more effective in interfering with target processing than others (e.g., cars/chairs). Furthermore, reduced performance for specific category pairs was predicted by more pair representational similarity in higher visual cortex (Cohen et al., 2014, 2015, 2017). This high-level representational architecture theory thus offers a mechanism to underpin our lack of capacity for multiple object perception.

As hand and tool representations in higher visual cortex are close to each other and partly overlap (Bracci, Cavina-Pratesi, Ietswaart, Caramazza, & Peelen, 2012), these categories form an ideal test for this theory. On the basis of the high-level representational architecture model we can make specific predictions about the behavioural task performance for multiple object paradigms involving hands and tools. We predicted reduced task performance for hand/tool pairs compared to other pairs (e.g. hands/cars). Furthermore, previous representational similarity analyses have also shown that neural representation of hands is somewhat closer to that for small than large objects (Kriegeskorte, Mur, Ruff, et al., 2008).

Thus, the high-level representational architecture model also predicts reduced task performance for hands and small objects compared to hand and large object pairs. Finally, hands are commonly involved in our interactions with the external world. To be successful in these interactions we have to be able to quickly and dynamically update our perception involving multiple objects. Each interaction involves at least two objects - at least one effector (e.g. a hand or a hammer) and one target (e.g. a phone or a nail). Thus, finding out more about the visual perceptual limitations for processing of multiple objects in the context of bodily information is important for understanding perceptual factors that play a role in interactions between body and environment.

To test if high-level limitations predict visual awareness in the context of viewing hands we employed a continuous flash suppression (CFS) paradigm. This paradigm has been used by several researchers to study processing across different visual object types (Almeida, Mahon, Nakayama, & Caramazza, 2008; Cohen et al., 2015; Hesselmann, Darcy, Ludwig, & Sterzer, 2016; Ludwig, Kathmann, Sterzer, & Hesselmann, 2015; Stein, Sterzer, & Peelen, 2012). The CFS task involves presenting a stream of rapidly changing mask images to one eye and a static target image to the other eye (Tsuchiya & Koch, 2005; Tsuchiya, Koch, Gilroy, & Blake, 2006). The separate images are fused in the brain and participants tend to experience a continuous stream of the flashing mask images. This initially suppresses awareness for the static target image, but this may become visible after some time. Typically, the mask images are Mondrian-style patterns because these are highly effective in target suppression. Cohen et al. (2015) developed a version of the CFS task in which object stimuli are presented as masks. This allows a measure of how long it takes targets to break through the visual suppression from the distracting masks for different types of category combinations (e.g., a tool target breaking through suppression from masking hands). We chose this particular paradigm because it assesses the interaction of multiple stimuli in a context where the stimuli are partly overlapping in stimulus space. This is similar to hand and environment interactions. Hand actions are dynamic with many changes that have to be registered over time and hands often overlap with the object they are manipulating. Thus, using the Cohen et al. (2015) object CFS task allows us to test model predictions specifically for hand and tool stimuli while also employing a paradigm that has some similarity to hand-environment interactions.

One of the crucial aspects of comparing category-level interactions is to select stimuli that have similar variability. Our hand category consisted of just one type of stimulus (basic category level) with many different exemplars of hands (Rosch, Mervis, Gray, Johnson, &

Boyes-Braem, 1976). In other higher-level category sets of tools, small objects and large objects (superordinate categories), there is a much greater variability between category exemplars (e.g., a tool could be a hammer, pliers, screwdriver etc). We therefore also included other basic category sets that consisted of only one type of object (hammers, phones and cars) to provide an appropriate control for category-level and variance in the hand condition.

We tested if the high-level neural representational architecture model can predict CFS breakthrough time rank-orders. Following Cohen et al. we tested pairs of stimuli in the CFS paradigm and hands/tools indicates a hand target competing with tool masks as well as a tool target competing with hand masks. Neural hand and tool representations overlap (Bracci et al., 2012) and neural representations for small objects are further away from hand and tool representations then they are from each other; large object representations are even further away in neural representational similarity space (Kriegeskorte, Mur, Ruff, et al., 2008). Thus, we derived and tested the following rank-order predictions (also see Figure 2): *1st Rank*: The fastest breakthrough times for hand/large object and tool/large object pairs. *2nd Rank*: Somewhat slower breakthrough times for hand/small objects, tool/small object and small object/large object pairs because these representations are closer together. *3rd Rank*: Even slower breakthrough times for hand/tool pairs due to the overlap and *4th Rank*: slowest breakthrough times for within-category pairs because the high-level neural architecture model predicts the most overlap for stimuli from the same category.

Methods Experiment 1

In Experiment 1 we tested if known characteristics of neural high-level object representations predict CFS breakthrough times for the categories of: hands, tools, hammers, small objects, phones, large objects and cars.

Participants

As in Cohen et al. (2015), we tested 20 participants. Our sample consisted of 17 females and 3 males (M = 21.05 years, SD=2.65, range 18-27 years, 2 left-handed according to self-report, 12 right-dominant eye). All participants had normal or corrected-to-normal vision (contact lenses only) and received $20 for their participation. The data of one participant had to be replaced due to technical difficulties that resulted in an incomplete data set. This research was conducted in accordance with the ethical standards laid down in the 1964 Declaration of Helsinki and was approved by the Macquarie University Ethics Review Committee (Human Research). Written informed consent was obtained from all participants prior to the start of the experiment.

Stimuli

We prepared our stimuli in line with the steps in Cohen et al. (2015) to minimize low-level differences between stimulus sets. We selected visually variable stimuli (see Figure 1A and 1B, the complete set of stimuli is available here: https://bit.ly/2Krq7Ab) and, also in the interest of high stimulus set variability, selected 60 stimuli per category (Cohen et al. 2015 used 30 stimuli) and presented these in both mirrored and non-mirrored versions. Stimuli for all three experiments were prepared at the same time and selected from our own databases as well as from the Bank of Standardized Stimuli (BOSS, sites.google.com/site/bosstimuli/, Brodeur, Dionne-Dostie, Montreuil, & Lepage, 2010), Konklab image sets (http://konklab.fas.harvard.edu/#, Konkle & Oliva, 2012) and the Tarrlab (www.tarrlab.org, Stimulus images courtesy of Michael J. Tarr, Center for the Neural Basis of Cognition and Department of Psychology, Carnegie Mellon University. Funding provided by NSF award 0339122). All stimuli were centred and gray-scaled. We normalized the intensity histogram (i.e., contrast and luminance) across all images and power at all spatial frequencies and orientations using the SHINE toolbox (Willenbockel et al., 2010).

Continuous Flash Suppression Task

Using the CSF task, we measured the time for target categories to break through suppression from distracting mask categories. We determined eye dominance for each participant before the experiment using the Miles test (Miles, 1930). We used a mirror stereoscope (ScreenScope, Stereoaids, Albany, Australia, stereoaids.com.au) to present mask stimuli to the dominant eye and target stimuli to the non-dominant eye (Figure 1C). Before running the task, we presented a frame and fixation dot to each eye and asked participants if these were clearly visible with each eye and if they overlapped when both eyes were open. We adjusted the stereoscope mirror angles as needed. The mask images were large (16.5° visual angle) and centred in the middle of the screen. The target images were small (3° visual angle) and presented in the centre of the screen either just above or below a small central fixation dot. To facilitate fusion of target and mask images, the target image was presented through a square Gaussian aperture (i.e., the outer 5% of the image was smoothed) and a thin black frame with the size of the mask image was presented to both eyes. A new mask image was shown every ~167 ms (6 Hz). This has been the optimal temporal frequency for suppression in other CFS studies (Drewes, Zhu, & Melcher, 2018; Zhu, Drewes, & Melcher, 2016). Note that this is a slower rate compared to Cohen et al. (2015), who used ~117 ms (8.5 Hz); nevertheless we found comparable breakthrough times (see Experiment 3). A trial started with the presentation of the black fixation dot for 250 ms which then turned red for 200 ms to alert participants that the trial was about to start. From the start of the trial, the static target gradually became more visible (0% to 100% opacity in 13 steps with each new mask presentation) over ~2170 ms. After that, the mask gradually became less visible (100% to 40% opacity in 37 steps with each new mask presentation) over ~6180 ms. If there was no response, the trial ended after ~8350 ms. Over the course of the trial, up to 50 different mask images randomly selected from the set of 120 options (mirrored and non-mirrored versions of our 60 unique stimuli per category).

Participants were instructed to detect the appearance of the small target item and respond with the space bar when they detected it. This stopped the stimulus presentation, and they then gave a forced choice response indicating if the target was presented above or below fixation by pressing one of two keyboard keys ('1' or '2'). Participants were instructed to give the first response as fast as possible and the second response as accurately as possible. Participants completed 10 practice trials before each block and received visual feedback

('correct', 'incorrect' or 'no response') for 1 s after every trial. The next trial started immediately after the feedback screen.

Mask stimuli were presented in blocks – separately for each of the seven category sets (hands, tools, hammers, small objects, phones, large objects, cars). For 10 participants we used a random order of the 7 conditions, and for the other 10 participants used the reverse of those 10 orders. In each mask block, there were 20 target trials for each category; in contrast to Cohen et al. 2015, we also presented targets from the same category as the mask. For each category, in half of the trials (10 target trials) the target appeared above and in the other half below fixation. In total, there were 140 trials within each block; target categories and target locations presented in a random order. There were two breaks within each mask block and a break between mask blocks. The experiment took approximately 75 minutes to complete. Stimulus presentation was controlled with MATLAB (The MathWorks, Natick, MA) and the Psychtoolbox (Brainard, 1997; Pelli, 1997). Stimuli were presented on an ASUS monitor with a refresh rate of 60 Hz and a screen resolution of 1920 x 1080. The eye to monitor distance was approximately 57 cm.

Figure 1. Stimuli and Continuous Flash Suppression (CFS) trial design. A) In Experiments 1 and 2, we presented hands, tools, hammers, small objects, phones, large objects and cars. Three stimulus exemplars for each set are depicted. B) In Experiment 3, we presented hands, faces, bodies, houses, cars and chairs. Three stimulus exemplars for each set are depicted. C) On each CFS task trial, mask images were presented in the dominant eye and target images in the non-dominant eye.

Data Analysis

Our variable of interest was the breakthrough reaction time which is how long it took participants to press the space bar to indicate target detection. Trials without a response were excluded from analysis. We then also excluded trials on which the subsequent location response was incorrect: participants were 98.60% (SD=1.07) correct across all trials. Finally, trials with response times < 300 msec or > three standard deviations from the participant's mean across all trials were also excluded, leading to the removal of a further 1.64% of the trials.

We developed a novel version of analysis methods that are frequently used in the context of neuroimaging data representational similarity analyses (RSA, Nili et al., 2014). First, we used 2D mosaic plots for visualisation of the breakthrough reaction times (see Figures 2-5). This

allows display of the matrix of breakthrough reaction times for all mask and target combinations in one plot and facilitates examination of the data pattern. Second, we employed correlation analyses to assess the similarity between specific models and the data. This allowed us to assess and compare the relatedness of different candidate models. Because our model predictions did not specify linear relationships but instead simply a rank order for category pairs (e.g., slower breakthrough times for hand/tool pairs compared to hand/large object pairs), we used rank-order correlations. Specifically, we used Kendall's rank correlation coefficient τ_A ('tau-a'), which is the proportion of values that are consistently ordered in both variables and is suitable for comparisons of models that predict tied ranks (Nili et al., 2014).

We used permutation tests for statistical inference. To estimate the sampling distribution of the correlation coefficients under the null hypothesis, we randomly shuffled each participant's data set of mean target/mask pair breakthrough times and then calculated data-model correlation coefficients for 10,000 times. We calculated two-sided p-values as the proportion of absolute sampled correlation coefficients that were greater or equal to the absolute observed correlation coefficient. Exact p-values were calculated with the R function permp (statmod package) (Phipson & Smyth, 2010). We corrected our analyses for multiple comparisons using Bonferroni adjusted alpha significance levels.

Results Experiment 1

The breakthrough time data pattern for all mask and target combinations did not resemble the predicted high-level representational architecture model (Figure 2A). Hand and tool combinations did not lead to slower breakthrough times compared to other hand and object categories. In contrast, they resulted in some of the fastest breakthrough times (dark colours). Overall, we did not find significant data-model correlations for the high-level representational architecture model (tau-a mean=-0.002 p=0.93).

What can be clearly seen is that there are general mask effects: hand and tool masks resulted in the fastest mean breakthrough time across different target combinations (hands mean RT=1447 ms; tools mean RT=1526 ms; hammers mean RT=1475 ms; small objects mean RT=1712; phones mean RT=1694; large objects mean RT=1759; cars mean RT=1695). This suggests that hands and tools both are relatively inefficient masks. This is not just due to the category level (basic vs supraordinate) as it is present for both levels (e.g., the tool category as well as the hammer) compared to all other categories. If we test a post-hoc model that has

hands and tools as relative inefficient masks, there is a significant data-model correlation (exploratory analysis; Bonferroni corrected significance threshold of $p<0.025$, tau-a mean=0.191, $p<0.001$). These correlations were significantly higher than the correlations for the high-level representational architecture model (permutation test p-values for the difference: $p<0.001$).

These results show that target stimuli reach awareness faster when competing with hands or tools than when competing with other stimuli. We conducted a second experiment to further understand the mechanism for this effect and to test if we can replicate this pattern. It is possible that the effect is not due to differences in mask efficiency *per se*. Instead, it could be due to the strong association between hands or tools and controlling manual actions. Thus, viewing hands and tools over several seconds in the CFS paradigm could speed up manual motor breakthrough times (Longo & Haggard, 2009). This would then result in quicker reaction times to targets when these masks are used. In Experiment 2, we therefore used vocal (non-manual) responses to test if these hands and tools relative inefficient mask effects replicate.

Figure 2. Results Experiment 1 (A) and Experiment 2 (B). Mosaic data plots depict breakthrough times for all mask and target combinations. Darker colours are faster and lighter colours slower breakthrough times. Across both experiments fast breakthrough times are found for targets when hands were masks. Mosaic model plots depict the predictions for the rank order of mask and target combinations (e.g., hands & cars fastest and hands & hands slowest breakthrough times). We found no significant data-model correlations for the high-level representational architecture model. We found significant correlations for the hand/tool inefficient mask model. Asterisks indicate significance of individual models and lines significant pairwise comparisons, both assessed using permutation tests. Multiple model comparison was accounted for using Bonferroni corrections. Error bars represent 95% confidence intervals.

Experiment 2

In Experiment 2, participants gave vocal responses. We tested if the speed up of breakthrough reaction times in the context of hand and tool mask that we found in Experiment 1 replicates when using a non-manual response modality.

Methods

We implemented the same methods as in Experiment 1 with the exceptions that we obtained vocal reaction times (see details below) and that we tested the predictions of both the high-level representational architecture and the hands/tools inefficient mask model (see Figure 2B).

Participants

We tested 20 new participants (18 female, M = 20.25 years, SD=1.48, range 18-24 years, 2 left-handed according to self-report, 13 right-dominant eye). All participants had normal or corrected-to-normal vision (contact lenses only) and received $20 for their participation. One participant had to be replaced due to technical difficulties.

Vocal Responses in the Continuous Flash Suppression Task

In Experiment 2, participant gave vocal instead of manual responses to indicate target detection and location. To this end we used a voice key. Participants were instructed to respond with a 'ba' sound as soon as the small target was detected, followed by a location categorization with another 'ba' sound or no sound. For half of the participants a second 'ba' sound indicated above fixation and for the other half it indicated below fixation. We used 'ba' as this gave a consistent sharp consonant sound to trigger the voice key reliably.

Participants were 97.48% (SD=3.06) correct across trials, and data trimming as described for Experiment 1 led to the removal of a further 1.56% of the trials.

Results Experiment 2

Vocal reaction times in Experiment 2 were generally slower compared to the manual reaction times in Experiment 1. This is in line with other studies comparing these response modalities (Eimer & Schlaghecken, 2001). As can be seen in Figure 2B, we found the fastest reaction times for the hand masks (hands mean RT= 1733 ms). We also found relatively fast reaction times again for the tool masks (tools mean RT=1863 ms, hammers mean RT=1788 ms). In this experiment, the reaction times in the large object conditions were also similar to the tool

conditions (large objects mean RT=1813 ms; small objects mean RT=1919 ms; phone mean RT=2054 ms; car mean RT=2119 ms). Nevertheless, we found significant data-model correlations for the hands/tools inefficient mask model (Bonferroni corrected significance threshold of $p<0.025$, tau-a mean=0.212, $p<0.001$). These correlations were significantly higher than the high-level representational architecture model correlations (permutation test p-values for the difference: p<0.001), for which we did not find significant data-model correlations (Bonferroni corrected significance threshold of p<0.025, tau-a mean=-0.0003, p=0.98). Overall, even with a non-manual response modality, we found the fastest breakthrough times for the hand masks ruling out a simple manual response facilitation explanation. Furthermore, we found no significant correlations for the high-level representational architecture model and found that the hand/tool inefficient mask model yielded better data-model correlations.

Post-hoc exploratory analysis for Experiments 1 and 2: Local category-specific image characteristics

If it is not clearly neural architecture that drives these different hand and tool mask effects, can we identify what does influence their capacity to act as effective masks in CFS paradigms? One obvious potential factor is the differences between categories in low-level visual characteristics. Although we globally matched (i.e., for the entire image) characteristics such as size, colour, contrast, luminance and spatial frequency content across all images, there could still be category-specific local image characteristics that could influence breakthrough times. One possibility is that hands, due to their shape, might not cover the entire target area, which could facilitate target breakthrough from suppression. We thus calculated the average percentage of object across the target area and also across the entire image for each mask category. We used these object-coverage mean values to create object-coverage models as predictors for breakthrough times for different category masks (Figure 3).

A further image characteristic that could influence breakthrough times is the amount of edges (local clustering of contrast changes). In fact, it has previously been suggested that the amount of edges could determine CFS because increased spatial density of Mondrian masks lead to longer breakthrough times (Drewes et al., 2018), although the authors were unable to tease apart effects of general contrast energy and edge content (see Discussion below). As we found the lowest CFS breakthrough times for hands and tools, it is possible that these

categories contain the lowest edge content of our stimuli. To estimate the number of edges in each image, we used the Matlab edge detection function. We employed the widely used *Canny* method with the low and high thresholds 0.1 and 0.2 (Canny, 1986). We also analysed the edges employing the *prewitt* method (Prewitt, 1970) and found comparable results, suggesting that the pattern of results was not dependent on the particular choice of edge detector. We calculated the average percentage of edges for all images across each category. We used these edge-content mean values to create edge-content models as predictors for breakthrough times for different category masks (Figure 3).

Although hammers and tools had the lowest object coverage in the target area, most likely due to their elongated shape, this was not the case for hands. We obtained significant data-model correlations for object coverage models (considering comparisons for five models, Bonferroni corrected significance threshold of $p<0.01$; Experiment 1 %object entire image tau-a mean=0.085, $p<0.001$, %object target image tau-a mean=0.148, $p<0.001$; Experiment 2: %object entire image tau-a mean=0.065, $p=0.003$, %object target image tau-a mean=0.178, $p<0.001$). However, our analysis also revealed that the data-model correlations for the object coverage for the entire image were significantly smaller compared to the hand/tool inefficient mask model (Experiment 1: tau-a mean=0.191; Experiment 2: tau-a mean=0.212, permutation test p-values for the difference, considering all four paired comparisons for object coverage and edge content models Bonferroni corrected significance threshold of p<0.0125: Experiment 1: %object entire image $p<0.001$, %object target area $p=0.023$; Experiment 2: %object entire image $p<0.001$, %object target area $p=0.079$).

Hands had the least amount of edges both across the entire image and specifically in the target area. Tools and hammers also had a lower edge content compared to several other categories (also see Figure 6). The correlation between data and edge-content models for both experiments were significantly above zero (considering comparisons for five models Bonferroni corrected significance threshold of $p<0.01$; Experiment 1 %edge entire image tau-a mean=0.231, $p<0.001$, %edge target area =0.217, $p<0.001$; Experiment 2: %edge entire image tau-a mean=0.303, $p=0.002$, %edge target area tau-a mean=0.292, $p<0.001$). The edge-content model correlation coefficients (except for the edge-target area model in Experiment 1) were also significantly larger than for the hands/tools inefficient mask model (Experiment 1: tau-a mean=0.191; Experiment 2: tau-a mean=0.212, permutation test p-values for the difference, considering all four paired comparisons for object coverage and edge content models Bonferroni corrected significance threshold of $p<0.0125$: Experiment 1: %edge entire

image *p*<0.001, %edge target area *p*=0.091; Experiment 2: %edge entire image *p*<0.001, %edge target area *p*<0.001). Thus, this exploratory analysis suggests that the category-specific edge content provides the best predictor for the data and could underlie the hand and tool specific effects.

In Experiment 3 we tested whether the edge-content explanation could account for the results of Cohen et al. (2015) by using the same categories as they have previously employed.

Figure 3. Post-hoc exploratory analysis for Experiments 1 (A) and 2 (B): local category-specific image characteristics. We calculated category specific values for the amount of edges (local luminance changes) as well as the amount of image covered by the object both specifically in the target area and also for the entire image. For the amount of edges we found very similar or higher data-model correlations compared to the hands/tools inefficient mask model. Asterisks indicate significance of individual models and lines significant pairwise comparisons, both assessed using permutation tests. Multiple model comparison was accounted for using Bonferroni corrections. Error bars represent 95% confidence intervals.

Experiment 3

In Experiment 3, we asked the question if we can also find relative inefficiency of hand masks when including other object categories such as those employed by Cohen et al. (2015). This also allowed us to test the edge-content model on another set of categories. Furthermore, we could test if we can replicate the pattern reported by Cohen et al. (2015) and investigate to what extent it might be related to the amount of category-specific edge content.

Participants

We tested 20 new participants (18 female, M = 23.55 years, SD=4.57, range 18-36 years, all right-handed according to self-report, 10 right-dominant eye). All participants had normal or corrected-to-normal vision (contact lenses only) and received Euro 7.50 for their participation. This research was conducted in accordance with the ethical standards laid down in the 1964 Declaration of Helsinki and was approved by the Ethics Committee of the Faculty for Social and Behavioural Sciences, Friedrich Schiller University Jena. Written informed consent was obtained from all participants prior to the start of the experiment.

Methods

In Experiment 3, we employed the same methods as in Experiment 1 with a few exceptions. First, the study was conducted in Germany and thus we translated the instructions and feedback into German. Stimuli were presented on a BENQ monitor with a refresh rate of 60 Hz and a screen resolution of 1680 x 1050. In addition to the hand category we included face, body, building, car and chair category sets.

Participants were 98.66% (SD=0.91) correct across trials, and data trimming as described above led to the removal of 1.56% of the trials.

Results Experiment 3

In line with Experiments 1 and 2, we found that hands were the most inefficient masks (shortest mean breakthrough times, RT mean for hands = 1548 ms) and numerically had the lowest edge content in the context of the object categories employed by Cohen et al. (2015). In our first analysis (Figure 4), we compared the full data set (including hands) to hands-inefficient, edge-content and object-coverage models. We found the largest data-model correlations for the edge-content models (considering comparisons for five models Bonferroni corrected significance threshold of $p<0.01$; %edge target area tau-a mean=0.226,

p<0.001; %edge entire image tau-a mean=0.226, *p*<0.001; %edge hand inefficient mask model tau-a mean =0.148, *p*<0.001; %object entire image tau-a mean=-0.002, *p*=0.947, %object target area tau-a mean=0.079, *p*=0.003). These were significantly larger than the correlations for the hands-inefficient mask model (permutation test p-values for the model differences, Bonferroni corrected significance threshold of *p*<0.025: %edge entire image *p*<0.001, %edge target area *p*<0.001). Thus, in line with the previous experiments edge-content models were the best predictor for the mask category reaction time order.

Figure 4. Data, models and correlation analyses for Experiment 3. Models include the hand inefficient mask model and models for category specific edge content as well as the amount of image covered by the object both specifically in the target area and also for the entire image. The edge-content models showed the highest data-model correlations of all the models. Asterisks indicate significance of individual models and lines significant pairwise comparisons, both assessed using permutation tests. Multiple model comparison was accounted for using Bonferroni corrections. Error bars represent 95% confidence intervals.

In a second analysis (Figure 5), we tested if we were able to replicate the pattern reported by Cohen et al. (2015). We only included the categories of faces, bodies, buildings, cars and chairs. As can be seen in Figure 5A, there are general mask effects (car masks have overall longer breakthrough times compared to other masks) and also general target effects (face targets have overall shorter breakthrough times compared to other targets). This suggest that the data pattern is not symmetrical across different mask and target pair combinations (e.g. face mask and body target pairs longer breakthrough times compared to body mask and face target pairs). We transformed our data so it had the same format as Cohen et al. (2015): We excluded within-category mask and target pairs and collapsed across mask and target pairs (e.g., face mask and body target averaged with body mask and face target) (Figure 5A). The general effects between different masks and targets are no longer obvious in the collapsed data but they may nevertheless underlie the pair rank order. This highlights the importance of showing mask /target pairs separately in a non-collapsed format (for example, using our mosaic plots).

The collapsed pairs can be seen in a bar graph (Figure 5B) as in Cohen et al. (2015, Figure 4B). Our data showed a similar range of breakthrough times (from 1724 to 2010 ms). They also show a similar pattern with faces/buildings, faces/bodies and faces/ chairs among the lowest and cars/bodies, cars/buildings and cars/chairs among the highest breakthrough times. In contrast, we found longer breakthrough times for bodies & buildings compared to Cohen et al. (2015). We correlated the rank order of our data with theirs and found a significant correlation (Spearman's rho = 0.71, p=0.019).

We then also derived a model based on the rank order of the data by Cohen et al. (2015) with faces/buildings the highest rank (1st rank = fastest breakthrough times) and car/chair pairs the lowest rank (10th rank = slowest breakthrough times) (see Figure 5C). We derived the corresponding edge content and object coverage models by collapsing values across mask and target pairs. Using a correlation analysis between the models and our data (considering comparisons for five models Bonferroni corrected significance threshold of p<0.01) we found significant correlations between our data and the Cohen et al. order model (tau-a mean=0.2, p< 0.001). We also found significant correlations for the edge-content models (for both tau-a mean =0.2, p<0.001), but not the object-coverage models (%object entire image tau-a mean=-0.044, p=0.435, %object target area tau-a mean=-0.053, p=0.351). The edge-content model correlation coefficients were numerically and statistically not different to the Cohen et al. (2015) order model correlations (permutation test p-values for the model differences,

Bonferroni corrected significance threshold of $p<0.025$: Cohen et al. versus %edge entire image $p = 0.9737$, Cohen et al. versus %edge target area $p = 0.9737$). This suggests that both the specific category order (related to category neural similarity) and the edge content are able to account for the data pattern in Experiment 3.

Overall, we replicated the behavioural findings by Cohen et al. (2015) and found that edge-content was a good predictor for the data pattern.

Experiment 3: Data collapsed across pairs

Figure 5. Data and models for Experiment 3 as in Cohen et al. (2015). A) Only includes categories of faces, bodies, buildings, cars and chairs; within-category mask and target pairs are excluded and we collapsed data across mask and target pairs (e.g., face mask and body target averaged with body mask and face target) as in Cohen et al. (2015). B) The collapsed mask and target pairs as ordered in Cohen et al. (2015). We found a significant correlation with the rank-order Cohen et al. (2015) reported previously (Spearman´s rho = 0.71, p=0.019). C) Cohen et al. (2015) order model (which previously showed high correlations with the high-level neural category representations), edge-content and object-coverage models as well as data-model correlations. The Cohen et al. (2015) model and edge content models had the highest data-model correlation coefficients and were not significant different. Asterisks indicate significance of individual models assessed using permutation tests. Multiple model comparison was accounted for using Bonferroni corrections. Error bars represent 95% confidence intervals.

Discussion

We conducted three CFS experiments to test if the high-level neural representational architecture for visual categories can predict suppression of visual awareness. In particular we investigated this in the context of hand stimuli, reflecting the importance of multiple object processing in the context of interaction. These stimuli form a particularly useful test category for the hypothesis because neural representations for hands and tools have been shown to overlap (Bracci et al., 2012). We predicted longer CFS breakthrough times for hand/tool compared to hand/other object pairs due to their neural overlap. In contrast to these predictions, in Experiment 1, we found that participants tended to be generally faster at detecting targets when paired with either hand and tool CFS masks, compared to other object category masks. These data did not correlate with a model based on higher-level neural representational architecture, but instead seemed to indicate a model where hands and tools were inefficient masks relative to other categories. We then tested this inefficiency model against new data in Experiment 2 and found significant positive correlations. We also found support for a hands relative inefficient mask effect in the context of those stimuli used in a previous multiple object CFS experiment by Cohen et al. (2015) and replicated their behavioural findings (Experiment 3).

When investigating the underlying mechanisms for these effects in more detail, we verified that the relative inefficiency of hands and tools was not due to facilitation of manual responses: we replicated the effect using vocal responses (Experiment 2). When analysing category-specific local image characteristics, we found that edge content (i.e., average percentage of mask image that is edge) but not object coverage (i.e., average percentage of mask image that is covered by a visual object) was the best predictor for category differences in breakthrough times across all analyses. Hand stimuli had on average the lowest edge content and this might be the underlying factor as to why hands are relatively inefficient masks. Edge content was also a good predictor for the data analysed without hands and collapsed across category pairs as in Cohen et al. (2015).

In previous work, increased spatial density was related to increased CFS breakthrough times (Drewes et al., 2018). In this previous research, which used Mondrian masks, an increase of spatial density resulted in changes in global spatial frequency content, contrast and luminance as well as edge content. Thus, it was not possible to disentangle if increased CFS breakthrough times were due to increased contrast energy or due to increased edge-detection

workload. Here we employed images with matched global spatial frequency content, contrast and luminance (Willenbockel et al., 2010) and found that edge content significantly correlated with breakthrough times across different category sets. This demonstrates that increased edge-detection workload itself can be linked to CFS breakthrough times. Edge detection happens very early in the visual processing stream both at the subcortical level (lateral geniculate nucleus in the thalamus) and in early visual cortex (Hubel & Wiesel, 1962). Thus, the specific mechanism that links edge content and suppression times is likely related to a low-level visual mechanism. Overall, our findings provide novel evidence for a low-level perceptual bottleneck for visual awareness of multiple objects.

Our findings in Experiments 1 and 2 do not provide evidence for a high-level mechanism limiting visual awareness for multiple objects. In Experiment 3, we replicated the CFS pattern reported by Cohen et al. (2015) using the same category sets. These authors showed high correlations between this pattern and the neural category similarity in high-level visual cortex. However, in Experiments 1 and 2 we were not able to predict, based on known neural similarity, the CFS pattern for a different set of categories involving hand, tool and object stimuli. Instead of support for the neural representational architecture model, we found general mask effects that correlated with edge content across all experiments. We note that our new visualisation and correlation methods have allowed us to detect and investigate such general mask effects. Cohen et al. (2015) previously showed averages across mask and target pairs (e.g. face mask and body target averaged with body mask and face target), which means there is no potential to detect differences between specific category masks or targets. Overall, the high-level representational architecture model was not able predict the data pattern across any of our CFS experiments, whereas the edge model was a consistent predictor, supporting a lower-level explanation for the differences between categories.

This lack of evidence for the high-level representational architecture model could be task-specific. The CFS paradigm involves fast presentations of large masks over a relatively long trial time. This would challenge processing capacity in early visual cortex, which could then result in large effects of edge content on reaction time measures (Drewes et al., 2018). Evidence for the high-level representational architecture and processing of multiple object stimuli has also been reported in paradigms where the multiple object stimuli were spatially distributed (visual search paradigm: Cohen et al., 2017; visual memory paradigm: Cohen et al., 2014). It is possible that these multiple object tasks tap mostly into selective attention mechanisms that are indeed influenced by the neural high-level spatial distribution of the

processing of visual categories. However, it is important to investigate the role of edge content also for these tasks to rule out low-level perceptual explanations.

If a low-level edge-detection mechanism is indeed the main factor underlying the category-pair-specific CFS pattern, how can we explain the significant behaviour-brain correlations of breakthrough times with category-pair-specific neural similarity in high-level but not low-level visual cortex reported by Cohen et al.? The pattern of CFS breakthrough times correlated significantly with neural similarity between category pairs in ventral and lateral occipitotemporal and also in occipitoparietal cortex. In contrast, the correlation with neural similarity in early visual cortex was significantly smaller and not different from zero (Cohen et al., 2015). First, we consider the correlations for higher-level visual cortex. Neural representational similarity between two categories decreases as the spatial distinction between fMRI activation patterns for these categories increases. Previous work has shown that animacy and real-world object size are preferentially processed in different spatial parts of ventral and lateral occipitotemporal cortex which showed a tri-partitioning into animate, inanimate-small and inanimate large objects (Konkle & Caramazza, 2013). This study also found a smaller and less consistent distinction along animacy and real-world size in parts of the occipitoparietal cortex. Such major spatial differences are likely a main contributor to the pattern of neural similarities for different category pairs (Kriegeskorte, Mur, Ruff, et al., 2008). To investigate if we can also find a tri-partitioning for edge content, we conducted a post-hoc analysis and divided our object categories into animate, inanimate small objects and inanimate large objects (Figure 6). We found that across the object categories, the edge content increased from animate to large inanimate objects (edge content entire image: mean animate= 2.48%, mean inanimate small= 3.15%, mean inanimate large= 4.05%; all paired comparisons p<0.001). Thus, because animacy and real-world object size are related to spatial clustering in high-level cortex as well as show differences in edge-content, this tri-partitioning could be the underlying explanation for the correlations between category-pair breakthrough times and neural similarity.

Second, we consider the low and non-significant correlations for early visual cortex. The fMRI representational similarity analysis employed by Cohen et al. (2015) was based on multi-voxel pattern correlations (Kriegeskorte, Mur, & Bandettini, 2008). However, differences in local edge-content could lead to differences in cortical processing in V1 that have a spatial resolution that cannot be picked up by fMRI. Different categories and different amounts of edges could also generally increase or decrease voxel activation. This, however,

would not affect the representational similarity measure because it is based on correlations and mean differences in level of activity are normalized. Alternatively, considering the bottleneck concept, there might be no change in fMRI activation, but only a temporal effect (i.e., longer processing and activation for more edge content), which would not be detectable with fMRI. Furthermore, edge-detection partially occurs in subcortical areas (Hubel & Wiesel, 1962), which were not included in previous brain-behaviour correlations. Future work could investigate these alternatives by taking both animacy and real-world size as well as edge content and activation in low-level visual areas into account when analysing brain-behaviour relationships for multiple object processing (e.g., see Cohen et al., 2017 for controlling for animacy).

Figure 6. Average edge content for entire image (A) and target area (B) for all visual categories. Visual categories are sorted in animate and inanimate as well as in small and large inanimate objects. Error bars represent 95% confidence intervals.

In this study we also found out more about the perceptual factors that might play a role in interactions between body and environment. We did not find evidence for the idea that neural mechanisms in high-level visual cortex specialised for hand stimuli play a role in visual awareness when both hand and object stimuli are presented in the CFS paradigm. However, we did find that hands were less efficient masks compared to other categories, and that this was driven by the relative edge-content in these stimuli. Similarly, our tool stimuli tended to be less efficient masks and had relatively few edges compared to other categories. This could be specific to our exemplars but it seems likely that generally hands and tools tend to have fewer details compared to many other categories of stimuli; this could be investigated in future studies including other stimulus sets. If it is true, due to visual object statistics, a low-level perceptual bottleneck could indirectly facilitate perception in body and tool interactions. And *vice versa*, such a potential mechanism could be taken into account when designing new artificial extensions for our bodies to be used for interactions. For example, artificial extensions should minimize any visible edges and details that are functionally not relevant.

Overall, our findings using a CFS paradigm and hand stimuli as well as a range of other categories do not support the idea that the neural representational architecture in higher visual cortex predicts limitations for visual awareness. Instead our analyses suggest that low-level edge-detection mechanisms might be mainly responsible for category-specific limitations, at least in the context of a CFS multiple object task.

Acknowledgements

RZ is supported by a Discovery Early Career Research Award from the ARC (DE140100499). We thank Marlene Wessels for assistance programming and data collection for Experiment 2. We thank Susan Wardle for helpful discussions and Serje Robidoux for statistical advice.

To access our stimuli, data, presentation and analyses scripts please use this Open Science Framework (OSF) link: https://bit.ly/2Krq7Ab.

References

Almeida, J., Mahon, B. Z., Nakayama, K., & Caramazza, A. (2008). Unconscious processing dissociates long categorical lines. *Proceedings of the National Academy of Sciences of the United States of America, 105*(39), 15214-15218.

Bracci, S., Cavina-Pratesi, C., Ietswaart, M., Caramazza, A., & Peelen, M. V. (2012). Closely overlapping responses to tools and hands in left lateral occipitotemporal cortex. *Journal of Neurophysiology, 107*(5), 1443-1456. doi:10.1152/jn.00619.2011

Brainard, D. H. (1997). The Psychophysics Toolbox. *Spatial Vision, 10*(4), 433-436. doi:10.1163/156856897X00357

Brodeur, M. B., Dionne-Dostie, E., Montreuil, T., & Lepage, M. (2010). The Bank of Standardized Stimuli (BOSS), a new set of 480 normative photos of objects to be used as visual stimuli in cognitive research. *PloS One, 5*(5), e10773. doi:10.1371/journal.pone.0010773

Canny, J. (1986). A computational approach to edge detection. *IEEE Transactions on Pattern Analysis and Machine Intelligence, 8*, 679-698.

Cohen, M. A., Alvarez, G. A., Nakayama, K., & Konkle, T. (2017). Visual search for object categories is predicted by the representational architecture of high-level visual cortex. *Journal of Neurophysiology, 117*(1), 388-402. doi:10.1152/jn.00569.2016

Cohen, M. A., Dennett, D. C., & Kanwisher, N. (2016). What is the Bandwidth of Perceptual Experience? *Trends in Cognitive Sciences, 20*(5), 324-335. doi:10.1016/j.tics.2016.03.006

Cohen, M. A., Konkle, T., Rhee, J. Y., Nakayama, K., & Alvarez, G. A. (2014). Processing multiple visual objects is limited by overlap in neural channels. *Proceedings of the National Academy of Sciences of the United States of America, 111*(24), 8955-8960. doi:10.1073/pnas.1317860111

Cohen, M. A., Nakayama, K., Konkle, T., Stantic, M., & Alvarez, G. A. (2015). Visual Awareness Is Limited by the Representational Architecture of the Visual System. *Journal of Cognitive Neuroscience, 27*(11), 2240-2252. doi:10.1162/jocn_a_00855

Desimone, R., & Duncan, J. (1995). Neural mechanisms of selective visual attention. *Annual Review of Neuroscience, 18*, 193-222.

Drewes, J., Zhu, W., & Melcher, D. (2018). The edge of awareness: Mask spatial density, but not color, determines optimal temporal frequency for continuous flash suppression. *Journal of Vision, 18*(1), 12. doi:10.1167/18.1.12

Eimer, M., & Schlaghecken, F. (2001). Response facilitation and inhibition in manual, vocal, and oculomotor performance: evidence for a modality-unspecific mechanism. *Journal of Motor Behavior, 33*(1), 16-26. doi:10.1080/00222890109601899

Hesselmann, G., Darcy, N., Ludwig, K., & Sterzer, P. (2016). Priming in a shape task but not in a category task under continuous flash suppression. *Journal of Vision, 16*(3), 17. doi:10.1167/16.3.17

Hubel, D. H., & Wiesel, T. N. (1962). Receptive fields, binocular interaction and functional architecture in the cat's visual cortex. *Journal of Physiology, 160*, 106-154.

Kim, C. Y., & Blake, R. (2005). Psychophysical magic: rendering the visible 'invisible'. *Trends in Cognitive Sciences, 9*(8), 381-388. doi:10.1016/j.tics.2005.06.012

Konkle, T., & Caramazza, A. (2013). Tripartite organization of the ventral stream by animacy and object size. *Journal of Neuroscience, 33*(25), 10235-10242. doi:10.1523/JNEUROSCI.0983-13.2013

Konkle, T., & Oliva, A. (2012). A real-world size organization of object responses in occipitotemporal cortex. *Neuron, 74*(6), 1114-1124. doi:10.1016/j.neuron.2012.04.036

Kriegeskorte, N., Mur, M., & Bandettini, P. (2008). Representational similarity analysis - connecting the branches of systems neuroscience. *Frontiers in Systems Neuroscience, 2*, 4. doi:10.3389/neuro.06.004.2008

Kriegeskorte, N., Mur, M., Ruff, D. A., Kiani, R., Bodurka, J., Esteky, H., . . . Bandettini, P. A. (2008). Matching categorical object representations in inferior temporal cortex of man and monkey. *Neuron, 60*(6), 1126-1141. doi:10.1016/j.neuron.2008.10.043

Longo, M. R., & Haggard, P. (2009). Sense of agency primes manual motor responses. *Perception, 38*(1), 69-78.

Ludwig, K., Kathmann, N., Sterzer, P., & Hesselmann, G. (2015). Investigating category- and shape-selective neural processing in ventral and dorsal visual stream under interocular suppression. *Human Brain Mapping, 36*(1), 137-149. doi:10.1002/hbm.22618

Miles, W. R. (1930). Ocular dominance in human adults. *Journal of General Psychology, 3*, 412-430.

Nili, H., Wingfield, C., Walther, A., Su, L., Marslen-Wilson, W., & Kriegeskorte, N. (2014). A toolbox for representational similarity analysis. *PLoS Computational Biology, 10*(4), e1003553. doi:10.1371/journal.pcbi.1003553

Pelli, D. G. (1997). The VideoToolbox software for visual psychophysics: transforming numbers into movies. *Spatial Vision, 10*(4), 437-442.

Phipson, B., & Smyth, G. K. (2010). Permutation P-values should never be zero: calculating exact P-values when permutations are randomly drawn. *Statistical Applications in Genetics and Molecular Biology, 9*, Article39. doi:10.2202/1544-6115.1585

Prewitt, J. M. S. (1970). Object enhancement and extraction. In B. Lipkin & A. Rosenfels (Eds.), *Picture Processing and Psychopictorics* (pp. 75-149). New York: Academic.

Rosch, E., Mervis, C. B., Gray, W. D., Johnson, D. M., & Boyes-Braem, P. (1976). Basic objects in natural categories. *Cognitive Psychology, 8*, 382-439.

Stein, T., Sterzer, P., & Peelen, M. V. (2012). Privileged detection of conspecifics: evidence from inversion effects during continuous flash suppression. *Cognition, 125*(1), 64-79. doi:10.1016/j.cognition.2012.06.005

Tong, F., Meng, M., & Blake, R. (2006). Neural bases of binocular rivalry. *Trends in Cognitive Sciences, 10*(11), 502-511. doi:10.1016/j.tics.2006.09.003

Treisman, A. M., & Gelade, G. (1980). A feature-integration theory of attention. *Cognitive Psychology, 12*, 97-136.

Tsuchiya, N., & Koch, C. (2005). Continuous flash suppression reduces negative afterimages. *Nature Neuroscience, 8*(8), 1096-1101. doi:10.1038/nn1500

Tsuchiya, N., Koch, C., Gilroy, L. A., & Blake, R. (2006). Depth of interocular suppression associated with continuous flash suppression, flash suppression, and binocular rivalry. *Journal of Vision, 6*(10), 1068-1078. doi:10.1167/6.10.6

Willenbockel, V., Sadr, J., Fiset, D., Horne, G. O., Gosselin, F., & Tanaka, J. W. (2010). Controlling low-level image properties: the SHINE toolbox. *Behavior Research Methods, 42*(3), 671-684. doi:10.3758/BRM.42.3.671

Wolfe, J. M., Cave, K. R., & Franzel, S. L. (1989). Guided search: an alternative to the feature integration model for visual search. *Journal of Experimental Psychology: Human Perception and Performance, 15*(3), 419-433.

Zhu, W., Drewes, J., & Melcher, D. (2016). Time for Awareness: The Influence of Temporal Properties of the Mask on Continuous Flash Suppression Effectiveness. *PloS One, 11*(7), e0159206. doi:10.1371/journal.pone.0159206