Seeing versus Knowing: The Temporal Dynamics of Real and Implied Colour Processing in the Human Brain

Abbreviated title: Real and Implied Colour Processing in the Brain

Lina Teichmann*[1,2], Tijl Grootswagers[1,2,3], Thomas Carlson[2,3], Anina N. Rich[1,2,4]
1| Perception in Action Research Centre & Department of Cognitive Science, Macquarie University, Sydney, Australia
2| ARC Centre of Excellence in Cognition & its Disorders, Macquarie University, Sydney, Australia
3| School of Psychology, University of Sydney, Australia
4| Centre for Elite Performance, Training and Expertise, Macquarie University, Sydney, Australia

Corresponding author's email: lina.teichmann@hdr.mq.edu.au

CONFLICT OF INTERESTS: none

ACKNOWLEDGEMENTS:
This research was supported by the Australian Research Council (ARC) Centre of Excellence in Cognition and its Disorders, International Macquarie University Research Training Program Scholarships to LT & TG, an ARC Future Fellowship (FT120100816) and ARC Discovery project (DP160101300) to TC and an ARC Discovery project (DP170101840) to ANR.

Abstract

Colour is a defining feature of many objects, playing a crucial role in our ability to

rapidly recognise things in the world around us and make categorical distinctions. For example,

colour is a useful cue when distinguishing lemons from limes or blackberries from raspberries.

That means our representation of many objects includes key colour-related information. The

question addressed here is whether the neural representation activated by *knowing* that

something is red is the same as that activated when we *actually see* something red, particularly

in regard to timing. We addressed this question using neural timeseries

(magnetoencephalography, MEG) data to contrast real colour perception and implied object

colour activation. We applied multivariate pattern analysis (MVPA) to analyse the brain

activation *patterns* evoked by colour accessed via real colour perception and implied colour

activation. Applying MVPA to MEG data allows us here to focus on the temporal dynamics of

these processes. Male and female human participants (N=18) viewed isoluminant red and

green shapes and grey-scale, luminance-matched pictures of fruits and vegetables that are red

(e.g., tomato) or green (e.g., kiwifruit) in nature. We show that the brain activation pattern

evoked by real colour perception is similar to implied colour activation, but that this pattern is

instantiated at a later time. These results demonstrate that a common colour representation can

be triggered by activating object representations from memory and perceiving colours. We

show here that a difference between these processes lies in the time it takes to access the

common colour representation.

Introduction

23
Throughout our lives, we learn statistical regularities about objects in our environment.
We acquire knowledge about their typical perceptual features, which motor actions are required
to interact with them, and in which context they usually appear. For example, we know that a
tomato is round and red, we can eat it and it appears in the wider context of food. Our neural
representations of objects therefore need to encompass a conceptual combination of these learnt
attributes spanning from perception to action and semantic knowledge (Martin, Haxby,
Lalonde, Wiggs, & Ungerleider, 1995). The activation of object representations is likely to
involve a widespread, distributed activation of several brain regions (Patterson, Nestor, &
Rogers, 2007) with some brain areas responding preferentially to object colour (e.g., Seymour,
Williams, & Rich, 2015). Several neuroimaging studies have compared perceiving colour and
accessing object-colour knowledge from memory, finding evidence that similar brain areas are
involved in these two processes (e.g., Bannert & Bartels, 2013; Martin et al., 1995;
Vandenbroucke, Fahrenfort, Meuwese, Scholte, & Lamme, 2014). Using
magnetoencephalography (MEG), we look at the neural timecourse of 'real' (by which we
mean 'induced by wavelengths of light') colour perception versus implied object-colour
activation from memory.
Associations between objects and typical or *implied colours* are acquired through
experience (Bartleson, 1960; Hering, 1920) and are activated effortlessly and involuntarily
(Bramão, Inácio, Faísca, Reis, & Petersson, 2010; Chiou, Sowman, Etchell, & Rich, 2014).
The activation of object-colour knowledge is part of the dynamic interaction between
perceptual processes and activation of prior conceptual knowledge to evaluate sensory input
(Collins & Olson, 2014; Engel, Fries, & Singer, 2001; Goldstone, de Leeuw, & Landy, 2015).
One of the central questions is how object-colour knowledge interacts or overlaps with colour
representations generated by external stimuli. Is knowing that an object is typically a certain

colour the same as seeing that colour? There is behavioural evidence that object-colour

knowledge can influence colour perception. Hansen, Olkkonen, Walter, and Gegenfurtner

(2006) found that participants overcompensated for implied colours when they were asked to

change the colour of colour-diagnostic objects to be achromatic. For example, a banana would

be adjusted towards the blue side of grey, showing the influence of the implied colour yellow.

Similarly, Witzel (2016) showed that participants selected an image of an object as achromatic

more often when its colour was modified to be the opposite of its implied colour (e.g., a bluish-

grey banana). These results suggest that colour perception can be influenced by previously

learnt object-colour associations (see Firestone and Scholl (2016) for debates about the extent

to which activation of colour from memory is identical to colour perception). Brain-imaging

data, recorded with functional magnetic resonance imaging (fMRI), suggest that brain

activation corresponding to implied object colour activation shares characteristics with real

colour perception: Retrieving the knowledge that a banana is yellow activates brain areas in or

around the V4 complex, which is involved in colour perception (Bannert & Bartels, 2013;

Barsalou, Simmons, Barbey, & Wilson, 2003; Chao & Martin, 1999; Rich et al., 2006;

Simmons et al., 2007; Vandenbroucke et al., 2014). This suggests that activation of implied

colour rests on a similar neural architecture as real colour perception.

These results suggest that similar brain areas are active when perceiving colour and

accessing implied colour, which may drive the behavioural interactions between the two (e.g.,

Hansen et al., 2006). Real colour activations occur very early in visual processing, whereas

implied colour presumably is only activated once the object is processed at a higher level.

Hence, there could be a temporal delay for activity driven by implied colour in comparison to

activity driven by perceived colour. As the signal measured by fMRI is slow, it is not a suitable

method to distinguish fine temporal differences between real and implied object colour

processing. In the current study, we use multivariate pattern analysis (MVPA) on MEG data

(Grootswagers, Wardle, & Carlson, 2017) to compare the brain activation patterns evoked by

colour perception and implied object colour activation. MEG has fine temporal resolution, and

with MVPA we can detect patterns across the sensors at each time point that are reliable enough

to train an algorithm to classify different categories of stimulus. Here, we use these methods to

test whether a classifier trained on 'real colour' can successfully decode 'implied colour'. Such

cross-generalisation can only occur if there is sufficient similiarity in the neural signals. This

approach enables us to contrast the temporal dynamics of real and implied colour processing,

shedding light on the interaction between perceptual processing and activation of object

representations.

82
83
84   **Materials and Methods**

Participants. 20 healthy volunteers (12 female, mean age = 27.6 years, SD = 6.6 years)

completed the study. All participants reported normal or corrected-to-normal vision including

normal colour vision. Participants gave informed consent before the experiment and were

reimbursed with $20/hour. During the MEG recording, participants were asked to complete a

target-detection task to ensure they were attentive. Two participants performed more than three

standard deviations below the group mean on this task, suggesting they did not pay attention

to the stimuli, and were therefore excluded from analysis, leaving 18 participants in total. The

study was approved by the Macquarie University Human Research Ethics Committee.

93   *Experimental Design*

Procedure. While lying in the magnetically shielded room (MSR) for MEG recordings,

participants first completed a colour flicker task (Kaiser, 1991) to equate the coloured stimuli

in perceptual luminance. Then they completed the main target-detection task. We used only

two colours to increase the power of our analysis. If there are luminance differences between

the colour categories, the classifier can use this strong signal to discriminate the categories

instead of relying on colour. While previous studies have shown the greatest behavioural

effects for colours along the daylight axis (yellow-blue, Hansen et al. (2006)), these are not

feasible colours for the current design: equiluminant blue and yellow stimuli no longer look

clearly blue and yellow. We chose red and green as the two colours as they can be matched for

luminance, and we included varying exemplars of these two hue categories to ensure any

potential remaining slight differences in luminance could not be used by a classifier to

distinguish the colour categories.

In the colour flicker task, participants were presented with red and green circles (5x5

degrees visual angle) in the centre of the screen. The colours alternated at a rate of 30Hz.

Participants completed 2 runs of 5 trials each. In each trial, one red-green combination was

used. The red colour was kept consistent throughout each trial while participants were asked

to use a button box to adjust the luminance level of green and report when they perceived the

least amount of flickering. The HSV (hue, saturation, value) values for each green shade were

then recorded. This procedure was repeated in the second run. The average HSV values

between the two runs was then computed, yielding five shades of red and green equated for

perceptual luminance. Using different shades of red and green which were each equated for

perceptual luminance minimises the degree that any luminance difference between the

categories could influence the results (see table 1 [supplementary materials] summarising

individual HSV values used).

In the main target-detection task (Figure 1A), participants completed eight blocks of

440 trials each. There were two different types of blocks: *implied colour* and *real colour*. Block

types alternated for each participant and the overall order was counterbalanced across

participants. In the *implied colour* blocks, participants viewed luminance-equated (SHINE

toolbox Willenbockel et al. (2010)) grey-scale images of colour diagnostic objects (see Figure

1A). Equating the overall luminance ensures that differences in MEG response patterns are not

caused by luminance differences between the red and green category. To increase variability

in the stimulus set, half the stimuli depicted a single item on the screen (e.g., one strawberry)

and the other half were multiple, partially overlapping items (e.g., three strawberries). Having

several different stimuli in each category helps to minimise the influence of low-level features

such as edges and shapes on the results. In the *real colour* blocks, participants viewed five

different abstract shapes. Each shape was filled in one of the red and green shades which had

been equated for perceptual luminance with the colour flicker task. Each shape occurred

equally often in red and green. To match the stimuli presented in the *implied colour* block, half

of the shapes were single shapes (e.g., one square) on the screen while the other half consisted

of partially overlapping shapes (e.g., three squares). All stimuli (objects and shapes) contained

the same number of pixels (Figure 1A).

In both block types, presentation location varied randomly within 100 pixels around the

central fixation cross. Changing the spatial location of the stimulus images adds variability to

the retinal image, again reducing the influence low-level visual features have on the results.

Participants were asked to press a button when they saw an image of the target shape (cross)

or target object (capsicum). Every block had 40 target trials. All target trials were discarded

before the MEG data analysis. On average, participants detected 98.51% (SD = 0.013%) of

target stimuli.

Figure 1: (A) Target-detection task and stimuli for both implied colour (top panel) and real colour (bottom panel) blocks. Participants were asked to press a button as soon as they saw the target (capsicum or cross). If they pressed the button after a target (correct detection) the fixation cross would turn green briefly, if they missed the target it would turn red. **(B)** Cross-validation approach used for real (top) and implied (bottom) colour decoding analyses. Every row shows which trials were used for the training set (clear) and which trials were used for the testing set (shaded). Trials with the same exemplar are never in the training and the testing set. In the real colour decoding analysis, we split the data in 5 different ways, always leaving one pair of the same shape with matched luminance out. In the implied colour decoding analysis, we split the data in 25 different ways, leaving all possible exemplar pairs out once. The classification accuracy is an average of the classifier performance for each of these divisions.

Apparatus and Pre-processing. The stimuli had a visual angle of approximately 5 x 5

degrees and were projected onto a translucent screen mounted in the magnetically shielded

room. Stimuli were presented using MATLAB with Psychtoolbox extension (Brainard & Pelli,

1997; Kleiner et al., 2007; Pelli, 1997). The neuromagnetic recordings were obtained with a

whole-head axial gradiometer MEG (KIT, Kanazawa, Japan), containing 160 axial

gradiometers. The frequency of recording was 1000Hz. FieldTrip (Oostenveld, Fries, Maris, &

Schoffelen, 2011) was used to pre-process the data. We used a low-pass filter of 200Hz and a

high-pass filter of 0.03Hz online. Stimulus onsets were determined with a photodiode that

detected light change when a stimulus came on the screen. Trials were epoched from -100 to

800ms relative to stimulus onset and downsampled to 200Hz (5ms resolution). All target trials

were removed. We performed no further preprocessing steps (e.g., channel selection, artefact

correction).

Decoding Analysis. We conducted four separate decoding analyses using linear

discriminant classifiers (LDA). CosmoMVPA (Oosterhof, Connolly, & Haxby, 2016) was used

to conduct these analyses. First, to test whether we can decode perception of red versus green,

we analysed the data from the real colour (shape) blocks. We tested whether we could decode

the colour of our abstract shapes for each person. The classifier was trained on distinguishing

the activity patterns evoked by red versus green shapes at each timepoint using 80% of the

data. We then used the classifier to predict the colour of each stimulus at every timepoint in

the remaining 20% of the data. To divide the data into training and testing set, we left out one

exemplar pair with matched luminance (e.g., red and green L-shape, matched for perceptual

luminance). This process was repeated over all folds so that each exemplar pair was in the

training and the testing set once (5-fold cross-validation). Hence, the colours in each fold were

balanced (Figure 1B).

Second, to assess whether we can decode implied colour from grey-scale objects, we

trained a classifier to distinguish trials of grey-scale objects that are associated with red versus

green. We used an independent exemplar cross-validation approach (Carlson, Tovar, Alink, &

Kriegeskorte, 2013) for the implied colour decoding analysis to rule out that the classification

is driven by visual features such as shape. We selected trials based on label for both colour

categories (e.g., all strawberry and kiwifruit trials). We then trained our classifier to distinguish

between activity patterns evoked by all stimuli *except* the selected stimuli. The selected trials

were then used as testing set. Thus, the classifier did *not* train on any trials of the test objects,

ensuring that the classifier cannot rely on specific shapes. We repeated this process 25 times to

have every possible combination of green and red objects used once as the testing set, and

report the average classification performance over all these combinations (Figure 1B).

Last, we conducted a cross-decoding analysis across the two different block types,

training the classifier on all real colour trials and testing on all implied colour trials. This cross-

decoding analysis is highly conservative as everything about the stimuli differs between real

colour and object colour trials, the only potential link is the implied colour of the objects to the

real colour of the abstract shapes. It is, however, quite likely that accessing the colour

information about objects takes longer than perceiving colour directly. This means that even if

a similar pattern is elicited by the two colour types, we may not see it in a direct cross-decoding

analysis. We therefore also conducted a time-generalisation analysis (Carlson, Hogendoorn,

Kanai, Mesik, & Turret, 2011; King & Dehaene, 2014), training the classifier at each timepoint

on the real colour trials and then testing on each timepoint in implied colour trials, yielding an

accuracy score for all pairs of training and testing timepoints. This technique allows us to test

for similar activation patterns that do not occur at the same time.

To assess whether decoding accuracy was significantly above chance, in all analyses,

we used random effects Monte-Carlo cluster statistic using Threshold Free Cluster

Enhancement (TFCE, Smith and Nichols (2009)) a cluster-forming statistic, as implemented

in CosmoMVPA (Oosterhof et al., 2016). The TFCE statistic represents the support from

neighbouring time points, allowing optimal detection of sharp peaks, as well as sustained

weaker effects. We conducted a permutation test to generate null distributions of the TFCE

statistic. For each subject, the colour labels at each timepoint were randomly shuffled 100 times

and the decoding analysis was repeated using the shuffled labels. To keep the temporal

structure, the same label permutations were applied to all time points in the data. Next, a group-

level null distribution was constructed by randomly drawing from the subject null-distributions

10,000 times (1000 times for the time-generalisation analysis). Then, to correct for multiple

comparisons, the most extreme value of the null distribution over time points was taken in

order to construct an overall null distribution across the time-series. The 95th percentile of this

corrected null distribution was used to threshold the observed decoding results for significance.

204
Results

For our real colour decoding analysis, we trained the classifier to distinguish red from

green shapes and then tested whether it could distinguish red from green shapes in an

independent set of data. The classifier was able to predict the colour above chance in a cluster

stretching from 70 to 320 ms, reflecting a signal modulated by colour (Figure 2A).

To examine whether we can decode implied object colour, the classifier was trained on

a subset of the object trials and then tested on an independent set. The testing set included only

exemplars (e.g., all strawberry and kiwifruit trials) that the classifier did not train on. Our data

show that the classifier can distinguish between the objects belonging to the red and green

category significantly above chance in a cluster stretching from 195 to 220 ms and from 275

to 295 ms (Figure 2B). While this suggests that there is categorical difference between objects

associated with red and green, the results of this particular analysis could be driven by an

overall difference in object characteristics other than colour (e.g., if red objects tend to have

more round edges than green objects).

Figure 2: Classification accuracies for (A) real colour, (B) implied colour, and (C) cross-colour decoding over time. Vertical, dotted lines show stimulus on- and offset. Dashed line indicates chance level (50%). Shading indicates error bars around the mean (standard deviation of decoding accuracies across participants divided by the square root of the number of participants). Coloured dots depict significant timepoints corrected for multiple comparisons.

To test whether there is a representational overlap of real and object colour processing

we ran a cross-decoding analysis. For this analysis, we trained the classifier to distinguish

between the red and green shapes and tested its performance on the grey-scale objects to see

whether cross-generalisation between real and implied object colour is possible. In this

analysis, the classifier is trained on identical shapes that only vary in terms of colour. Hence,

this is the most conservative way of testing whether there is a representational overlap between

real and implied colours. The cross-colour decoding was not significant at any point in the

timeseries (Figure 2C).

Accessing implied colour presumably requires first accessing the general concept of

the object. Therefore, real and implied colours may have a similar representation but colour

information could be accessed later when activated via objects in comparison to when colour

is perceived. To examine whether this is the case we ran a cross-decoding time-generalisation

analysis. We trained a classifier to distinguish between red and green shapes at every timepoint

and then tested whether it could cross-generalise to the grey-scale objects at any timepoint. The

results of the cross-generalisation analysis are summarised in Figure 3.

The time-generalisation analysis revealed similar activation patterns between real and

implied colours when the classifier is trained on real colour at an earlier timepoint and tested

on implied colour at a later one (Figure 3A and 3B). These generalisation accuracies were

statistically above chance, even with our conservative correction for multiple comparisons

(Figure 3C). Inspecting the training timepoint with maximum decoding (140 ms) indicates that

there is above-chance decoding at later testing timepoints with peak decoding at 200 ms after

stimulus onset (Figure 3B). The results show that we can cross-decode between real and

implied colours when we *train* the classifier on *real* colours at timepoints between 140 to 160

ms and *test* it on *implied* colours at a cluster from 200 to 215 ms (Figure 3C). Combining the

off-diagonal shift of the significant timepoints shows a median delay of 55 ms for implied

colour testing times compared to real colour training times (Figure 3D). Importantly, these

results cannot be driven by anything else than colour as the classifier is trained on real colour

trials in which the only different stimulus characteristic was colour and tested on implied colour

trials which were achromatic. The results highlight that there are similarities between real

colour and implied object colour patterns but this pattern is instantiated later for implied object

colours than for real colours. Note that above-chance cross-decoding does not mean we can

interpret that the processes involved in real and implied colour processing are identical.

However, the results show that there are sufficient similarities for the classifier to cross-

Figure 3: Results of the time-generalisation analysis. In this analysis, the classifier was trained on the real colour trials and tested on the implied colour trials. Panel A shows the classification accuracy at every possible train-test-time combination. Lighter colours indicate higher classification accuracy. Panel B shows the timecourse of the classification accuracy when the classifier relies on the training data at 140ms (peak decoding at 200ms). Shading indicates error bar around the mean (standard deviation of decoding accuracies across participants divided by the square root of the number of participants). Panel C shows all training-testing-timepoint combinations where classification is significantly above chance (based on permutation, corrected for multiple comparisons). Panel D shows the time shift of all significant timepoints from the diagonal. The delay of colour representations activated via implied colour activation in comparison to real colour perception is ~55ms .

252   generalise from brain activation patterns evoked by perceiving red and green to brain activation

253   patterns evoked by viewing grey-scale images of objects that are associated with red and green.

254   These results predict that it takes more time to access implied colour than real colour

as one presumably has to first access the concept of the object. We decided post-hoc to test this

prediction and collected colour categorisation accuracies and reaction times on our stimuli from

a new sample of 100 participants on Amazon's Mechanical Turk. Participants were presented

with the red and green shapes and the grey-scale objects, each presented individually for

100ms, and randomly intermingled. Participants were asked to indicate as quickly and

accurately as possible whether the stimulus was (typically) red or green by responding with

either "m" or "z" using a keyboard. This allowed us to first confirm that the objects we had

selected were indeed typically associated with red or green, and second, to test whether there

was a time difference between real and implied colour categorisation. Response-key mappings

were randomly determined for each participant. Four participants were excluded from the

analysis as their accuracy scores were more than 2 standard deviations below the group mean.

For the remaining 96 participants, choosing which colour is displayed was faster for the

coloured shapes (M=506.74ms, 95% CI [491.71, 521.77]) than indicating the implied colour

of the grey-scale images (M=607.15ms, 95% CI [589.98, 624.31]). Real colour responses were

also more accurate (M=91.57%, 95% CI [90.89, 92.25]) than implied colour responses

(M=80.32%, 95% CI [79.37, 81.26]). Using Mturk introduces variance to the experimental

setup, including monitor settings for colour, computer and internet speeds, all of which will

increase the noise in the data; we do not, therefore, interpret the specific difference in timing.

Despite the variability, there is a clear difference between the time taken for categorising colour

in the two conditions. These results are consistent with real colour perception being faster and

easier than recalling implied colours, in line with the prediction from our decoding results.

Discussion

In this study, we compared the temporal activation profiles of colour perception and implied

colour to examine the interaction between perceptual processing and access to object

representations. We applied MVPA to time-series MEG data and show that both real and

implied colour can be decoded. Furthermore, our results indicate that real and implied colour

processing share a sufficient degree of similarity to allow for cross-generalisation with a

temporal shift. The activity pattern distinguishing colours was instantiated on average 55ms

later for implied colours than for real colour, highlighting that there are similarities between

colour representations accessed via 'real' colour and via implied colour, but that there is a

temporal asynchrony between these processes.

287   There are several possible explanations for a temporal difference between accessing

colour representations via real colour and implied colour. One possibility is that the time

difference reflects greater individual variability in the temporal activation profile of implied

colours in comparison to real colours. Implied colours may be accessed at slightly different

timepoints for different people and thus the cross-decoding accuracy that is above chance for

each participant only overlaps at a later timepoint. There are also more interesting potential

explanations. First, it could be due to actual differences in neural processes. Colour

representations accessed via colour perception are immediately available whereas implied

colour activation presumably only happens once the object is processed to some higher level.

Thus, the delay could reflect differences between bottom-up and top-down access to colour

representations. This is a plausible interpretation of the temporal delay and corresponds with

earlier findings of early visual areas being involved in implied colour activation (Bannert &

Bartels, 2013; Vandenbroucke et al., 2014). Second, it is possible that the binding of colour

and shape information happens later in the visual processing hierarchy compared to initial

processing of separate features, and that the comparison of typical and perceived colour can

therefore only happen later once shape-colour binding is complete. This view is consistent with

results of a recent fMRI study, which showed that object-colour and object-shape activated

from memory can be distinguished in areas associated with colour (V4) and shape (lateral

occipital cortex, LOC) perception, respectively, but that the conjunction of colour *and* shape

can be decoded only later along the visual hierarchy (anterior temporal lobe, ATL; Coutanche

and Thompson-Schill (2014)). Similarly, Seymour et al. (2015) showed that colour *per se* can

be decoded in early visual areas but object surface colour (bound to form) can only be decoded

in areas further along the ventral visual stream. These findings also correspond to patient work

(Patterson et al., 2007) and previous transcranial magnetic stimulation studies (Chiou et al.,

2014) which point towards the ATL as the hub for object-knowledge (for a recent review see

Lambon Ralph, Jefferies, Patterson, & Rogers, 2017). Finally, it could also be that the delay

reflects the greater complexity of the grey-scale objects relative to the abstract shapes, hence

binding the features may take slightly longer. From the data we cannot disentangle these

interpretations. Our results clearly highlight, however, that there is a similar structure to the

brain response to externally perceived and internally activated colour representations, and that

time seems to be the key difference.

We interpret our cross-decoding results as evidence that representation of implied

colour involves some of the same mechanisms as those involved in colour perception. This is

in line with previous studies showing that the same brain regions are active when retrieving

object representations from memory and perceiving those object features (for reviews see

Martin, 2007; Patterson et al., 2007). For example, Vandenbroucke et al. (2014) and Bannert

and Bartels (2013) showed that early visual cortex is involved when real and implied colour

are processed. Using fMRI, Vandenbroucke et al. (2014) trained a classifier on data recorded

while participants viewed red and green shapes, and then tested the classifier on data recorded

while participants viewed line-drawings of colour-diagnostic objects filled with ambiguous

colours between red and green. Behavioural results suggested participants were slightly more

likely to respond 'red' to the ambiguous colour presented on a line drawing of a typically red

object than a line drawing of a typically green object. In their fMRI data, the classifier

categorised the colour consistent with what the participant perceived. That means the classifier

categorised colours to be red when shown on objects that are typically red and green for objects

that are typically green at above chance levels. They interpret these data as evidence for an

influence of implied object colours on the creation of a subjective experience of colour.

Consistent with this study, Bannert and Bartels (2013) trained a classifier to distinguish fMRI

data from trials where four different colours were presented. They showed that the classifier

can cross-generalise to grey-scale colour-diagnostic objects. Both fMRI studies highlight that

there are similar activation patterns across voxels in the visual cortex for real and implied

colour processing. Our results provide further evidence that object-colour knowledge and

colour perception instantiate similar patterns, this time in the temporal domain.

What is driving the successful decoding performance? Here, we decoded real and

implied object colour. For the real colour decoding, we used shapes that were identical across

colour categories and used five different levels of stimulus luminance for each category that

were perceptually matched. Therefore, the only distinguishing feature between the shapes was

colour. That means that for the real-colour decoding analysis *and* the cross-generalisation (i.e.,

training on shapes and testing on objects), we can rule out visual differences other than colour

as a driving factor. For the implied colour blocks, visual differences are a bigger concern.

Previous studies have used line-drawings instead of photos of objects to reduce local low-level

differences between stimuli (e.g., Vandenbroucke et al., 2014). Line-drawings can reduce some

of these differences (e.g., local luminance differences due to texture) but cannot completely

rule out any contribution of low-level effects (e.g., shapes). In addition, there is a considerable

trade-off between line-drawings in terms of similarity of the objects to real world objects which

can slow down recognition and implied colour effects (Olkkonen, Hansen, & Gegenfurtner,

2008; Vurro, Ling, & Hulbert, 2013). We therefore used isoluminant, grey-scale photos of

objects and dealt with differences in low-level features (e.g., edges) by using an independent

exemplar cross-validation approach. We trained the classifier to distinguish typically red and

green objects using all objects except one typically-red and one typically-green object. The

classifier was then tested on the left-out pair. We thereby considerably reduced the likelihood

of the implied colour classification being driven by low-level features as the classifier never

trained and tested on the same exemplars. While limiting the influence low-level features could

have on the implied object colour decoding, it is still possible that the results in this particular

analysis are driven by object features other than colour. Visual differences, however, are not a

concern for the key cross-decoding analysis. Here, we used identical shapes in the training set,

making low-level features a highly unlikely source of contribution to classifier performance.

These controls allow us to infer that the classifier is using (implied) colour to distinguish the

categories.

Our results speak to the important aspect of temporal differences between colour

evoked by external stimulation and internal activation. Activating conceptual knowledge of

objects from memory is thought to involve a widespread network of brain areas involved in

perception and action of different object features (Martin, 2007; Patterson et al., 2007). To

access the implied colour of an object requires that the conceptual representation of that object

is activated first. Using time-generalisation methods (King & Dehaene, 2014), we show here

that in comparison to real colour perception, which can be decoded rapidly, accessing object-

colour knowledge takes ~55ms longer. This is consistent with our behavioural data showing

that real colour judgments are faster than implied colour judgments. These results increase our

existing knowledge of how real and implied colour are processed by showing that colour

representations via external stimulation are also instantiated during internal activation, but with

a delay. Applying MVPA to our MEG data allows us to capture this temporal difference,

highlighting the value of this method for dissociating activation of object features from

memory from perception of object features in the real world.

Our results highlight that the activation of implied colours can occur independent of a

task that focuses on colour. Participants completed a target-detection task in which attending

to colour was not a useful strategy. The targets were ambiguous in colour (e.g., a capsicum can

be either red or green), and this avoided biasing participants towards deliberately thinking

about the implied colour of the objects. Using a task that is irrelevant to the classifier

performance allowed us to explore the involuntary activation of implied colours rather than the

signals associated with perhaps actively imagining colours or retrieving colour names. Not

attending to the feature that is relevant for the classifier probably reduced our decoding

accuracy in general (e.g., Brouwer & Heeger, 2013; Jackson, Rich, Williams, & Woolgar,

2016), but clearly supports previous studies showing that there is an *involuntary* activation of

object-colour independent of task demands (Bannert & Bartels, 2013; Vandenbroucke et al.,

2014).

Overall, the decoding accuracies across our analyses are quite low. As outlined above,

this is probably partially due to colour being irrelevant for the task. In addition, it is important

to note that we did not use extensive pre-processing, meaning we ran our analyses on

effectively raw data. We use our multivariate decoding analyses for *interpretation* (Hebart &

Baker, 2017) – if decoding is above chance, this means there is a signal that allows a categorical

distinction between the conditions. Minimal pre-processing (e.g., no trial averaging, filtering,

channel-selection, trial-selection) ensures that there is no potential influence of plurality of

methods or specific pre-processing choices; it also means that the data overall are noisier which

can result in relatively low decoding accuracies. However, it is crucial to note that low decoding

accuracies does not necessarily mean that the effects are weak, as decoding accuracies are not

effect sizes (cf. Hebart & Baker, 2017). Here, we show with rigorous methodological controls

and strict correction for multiple comparisons that there is significant cross-generalisation from

real colour to implied colour.

Previous fMRI studies showed that early visual areas are involved in real colour

perception and implied colour activation (Bannert & Bartels, 2013; Rich et al., 2006;

Vandenbroucke et al., 2014), but other studies implicate anterior temporal regions in object

colour knowledge. For example, a transcranial magnetic stimulation study showed that the

behavioural effects of implied colour knowledge on object recognition are disrupted when

stimulating the anterior temporal lobe (Chiou et al., 2014), complementing patient studies

suggesting this area holds conceptual object information (e.g., Ralph, Matthew, & Patterson,

2008). This highlights that activating object attributes, including implied colour, goes beyond

low-level visual areas. Our study adds time as a novel aspect to this discussion by comparing

the temporal profiles of colour representations accessed via real colour perception and implied

colour activation.

In conclusion, our data show that there is a common representation of real and implied

colour but that this representation is accessed later when triggered by activating implied colour

than by perceiving real colour. This is in line with previous studies suggesting that the same

brain areas are involved in object-feature activation from memory *and* object-feature

perception. Our results highlight that applying MVPA to time-series MEG data is a valuable

approach to exploring the interaction between object-feature inputs and predictions or

representations based on prior knowledge. This opens multiple avenues for future studies

examining the dynamic interactions between perceptual processes and activation of prior

conceptual knowledge.

References

Bannert, M. M., & Bartels, A. (2013). Decoding the yellow of a gray banana. *Current Biology, 23*(22), 2268-2272.

Barsalou, L. W., Simmons, W. K., Barbey, A. K., & Wilson, C. D. (2003). Grounding conceptual knowledge in modality-specific systems. *Trends in cognitive sciences, 7*(2), 84-91.

Bartleson, C. J. (1960). Memory colors of familiar objects. *JOSA, 50*(1), 73-77.

Brainard, D. H., & Pelli, D. G. (1997). The psychophysics toolbox. *Spatial vision, 10*, 433-436.

Bramão, I., Inácio, F., Faísca, L., Reis, A., & Petersson, K. M. (2010). The influence of color information on the recognition of color diagnostic and noncolor diagnostic objects. *The Journal of general psychology, 138*(1), 49-65.

Brouwer, G. J., & Heeger, D. J. (2013). Categorical clustering of the neural representation of color. *Journal of Neuroscience, 33*(39), 15454-15465.

Carlson, T., Hogendoorn, H., Kanai, R., Mesik, J., & Turret, J. (2011). High temporal resolution decoding of object position and category. *Journal of vision, 11*(10), 9-9.

Carlson, T., Tovar, D. A., Alink, A., & Kriegeskorte, N. (2013). Representational dynamics of object vision: the first 1000 ms. *Journal of vision, 13*(10), 1-1.

Chao, L. L., & Martin, A. (1999). Cortical regions associated with perceiving, naming, and knowing about colors. *Journal of cognitive neuroscience, 11*(1), 25-35.

Chiou, R., Sowman, P. F., Etchell, A. C., & Rich, A. N. (2014). A conceptual lemon: theta burst stimulation to the left anterior temporal lobe untangles object representation and its canonical color. *Journal of cognitive neuroscience, 26*(5), 1066-1074.

Collins, J. A., & Olson, I. R. (2014). Knowledge is power: How conceptual knowledge transforms visual cognition. *Psychonomic bulletin & review, 21*(4), 843-860.

Coutanche, M. N., & Thompson-Schill, S. L. (2014). Creating concepts from converging features in human cortex. *Cerebral cortex, 25*(9), 2584-2593.

Engel, A. K., Fries, P., & Singer, W. (2001). Dynamic predictions: oscillations and synchrony in top–down processing. *Nature Reviews Neuroscience, 2*(10), 704-716.

Firestone, C., & Scholl, B. J. (2016). Cognition does not affect perception: Evaluating the evidence for "top-down" effects. *Behavioral and brain sciences, 39*.

Goldstone, R. L., de Leeuw, J. R., & Landy, D. H. (2015). Fitting perception in and to cognition. *Cognition, 135*, 24-29.

Grootswagers, T., Wardle, S. G., & Carlson, T. A. (2017). Decoding dynamic brain patterns from evoked responses: A tutorial on multivariate pattern analysis applied to time series neuroimaging data. *Journal of cognitive neuroscience*.

Hansen, T., Olkkonen, M., Walter, S., & Gegenfurtner, K. R. (2006). Memory modulates color appearance. *Nature neuroscience, 9*(11), 1367-1368.

Hebart, M. N., & Baker, C. I. (2017). Deconstructing multivariate decoding for the study of brain function. *Neuroimage*.

Hering, E. (1920). *Grundzüge der Lehre vom Lichtsinn*: Springer.

Jackson, J., Rich, A. N., Williams, M. A., & Woolgar, A. (2016). Feature-selective Attention in Fronto-parietal Cortex: Multivoxel Codes Adjust to Prioritize Task-relevant Information. *Journal of cognitive neuroscience*.

Kaiser, P. (1991). Flicker as a function of wavelength and heterochromatic flicker photometry. *Limits of vision (Kulikowski JJ, Walsh V, Murray IJ, eds)*, 171-190.

King, J., & Dehaene, S. (2014). Characterizing the dynamics of mental representations: the temporal generalization method. *Trends in cognitive sciences, 18*(4), 203-210.

Kleiner, M., Brainard, D., Pelli, D., Ingling, A., Murray, R., & Broussard, C. (2007). What's new in Psychtoolbox-3. *Perception, 36*(14), 1.

Lambon Ralph, M. A., Jefferies, E., Patterson, K., & Rogers, T. T. (2017). The neural and computational bases of semantic cognition. *Nature Reviews Neuroscience, 18*(1), 42.

Martin, A. (2007). The representation of object concepts in the brain. *Annu. Rev. Psychol., 58*, 25-45.

Martin, A., Haxby, J. V., Lalonde, F. M., Wiggs, C. L., & Ungerleider, L. G. (1995). Discrete cortical regions associated with knowledge of color and knowledge of action. *Science, 270*(5233), 102.

Olkkonen, M., Hansen, T., & Gegenfurtner, K. R. (2008). Color appearance of familiar objects: Effects of object shape, texture, and illumination changes. *Journal of vision, 8*(5), 13-13.

Oostenveld, R., Fries, P., Maris, E., & Schoffelen, J.-M. (2011). FieldTrip: open source software for advanced analysis of MEG, EEG, and invasive electrophysiological data. *Computational intelligence and neuroscience, 2011*, 1.

Oosterhof, N. N., Connolly, A. C., & Haxby, J. V. (2016). CoSMoMVPA: multi-modal multivariate pattern analysis of neuroimaging data in Matlab/GNU Octave. *Frontiers in neuroinformatics, 10*.

Patterson, K., Nestor, P. J., & Rogers, T. T. (2007). Where do you know what you know? The representation of semantic knowledge in the human brain. *Nature Reviews Neuroscience, 8*(12), 976-987.

Pelli, D. G. (1997). The VideoToolbox software for visual psychophysics: Transforming numbers into movies. *Spatial vision, 10*(4), 437-442.

Ralph, L., Matthew, A., & Patterson, K. (2008). Generalization and differentiation in semantic memory. *Annals of the New York Academy of Sciences, 1124*(1), 61-76.

Rich, A. N., Williams, M. A., Puce, A., Syngeniotis, A., Howard, M. A., McGlone, F., & Mattingley, J. B. J. N. (2006). Neural correlates of imagined and synaesthetic colours. *44*(14), 2918-2925.

Seymour, K., Williams, M., & Rich, A. (2015). The representation of color across the human visual cortex: distinguishing chromatic signals contributing to object form versus surface color. *Cerebral cortex, 26*(5), 1997-2005.

Simmons, W. K., Ramjee, V., Beauchamp, M. S., McRae, K., Martin, A., & Barsalou, L. W. (2007). A common neural substrate for perceiving and knowing about color. *Neuropsychologia, 45*(12), 2802-2810.

Smith, S. M., & Nichols, T. E. (2009). Threshold-free cluster enhancement: addressing problems of smoothing, threshold dependence and localisation in cluster inference. *Neuroimage, 44*(1), 83-98.

Vandenbroucke, A., Fahrenfort, J., Meuwese, J., Scholte, H., & Lamme, V. (2014). Prior knowledge about objects determines neural color representation in human visual cortex. *Cerebral cortex, 26*(4), 1401-1408.

Vurro, M., Ling, Y., & Hulbert, A. (2013). Memory color of natural familiar objects: Effects of surface texture and 3-D.

Willenbockel, V., Sadr, J., Fiset, D., Horne, G. O., Gosselin, F., & Tanaka, J. W. (2010). Controlling low-level image properties: the SHINE toolbox. *Behavior research methods, 42*(3), 671-684.

Witzel, C. (2016). An Easy Way to Show Memory Color Effects. *i-Perception, 7*(5), 2041669516663751. doi:10.1177/2041669516663751

Supplementary Materials

Table 1: HSV values for the colours used in the real experiment. Five consistent levels of luminance were used for red while green was perceptually matched to the reds for each participant with a colour flicker task. Hue and saturation were kept consistent throughout.

Red: Five consistent levels of luminance

	Red1			Red2			Red3			Red4			Red5		
	H	S	V	H	S	V	H	S	V	H	S	V	H	S	V
	0.00	0.90	0.70	0.00	0.90	0.77	0.00	0.90	0.84	0.00	0.90	0.91	0.00	0.90	0.98

Green: Perceptually matched per participant

	Green1			Green2			Green3			Green4			Green5		
Participant	H	S	V	H	S	V	H	S	V	H	S	V	H	S	V
1	0.333	0.9	0.405	0.333	0.9	0.435	0.333	0.9	0.48	0.333	0.9	0.51	0.333	0.9	0.505
2	0.333	0.9	0.405	0.333	0.9	0.455	0.333	0.9	0.48	0.333	0.9	0.47	0.333	0.9	0.52
3	0.333	0.9	0.405	0.333	0.9	0.425	0.333	0.9	0.45	0.333	0.9	0.495	0.333	0.9	0.49
4	0.333	0.9	0.4	0.333	0.9	0.475	0.333	0.9	0.39	0.333	0.9	0.455	0.333	0.9	0.475
5	0.333	0.9	0.44	0.333	0.9	0.475	0.333	0.9	0.485	0.333	0.9	0.52	0.333	0.9	0.56
6	0.333	0.9	0.525	0.333	0.9	0.525	0.333	0.9	0.53	0.333	0.9	0.535	0.333	0.9	0.56
7	0.333	0.9	0.39	0.333	0.9	0.415	0.333	0.9	0.42	0.333	0.9	0.475	0.333	0.9	0.495
8	0.333	0.9	0.385	0.333	0.9	0.415	0.333	0.9	0.515	0.333	0.9	0.49	0.333	0.9	0.485
9	0.333	0.9	0.415	0.333	0.9	0.43	0.333	0.9	0.445	0.333	0.9	0.475	0.333	0.9	0.48
10	0.333	0.9	0.395	0.333	0.9	0.415	0.333	0.9	0.435	0.333	0.9	0.47	0.333	0.9	0.45
11	0.333	0.9	0.45	0.333	0.9	0.43	0.333	0.9	0.495	0.333	0.9	0.485	0.333	0.9	0.47
12	0.333	0.9	0.42	0.333	0.9	0.455	0.333	0.9	0.48	0.333	0.9	0.51	0.333	0.9	0.55
13	0.333	0.9	0.42	0.333	0.9	0.425	0.333	0.9	0.415	0.333	0.9	0.455	0.333	0.9	0.455
14	0.333	0.9	0.5	0.333	0.9	0.47	0.333	0.9	0.48	0.333	0.9	0.505	0.333	0.9	0.565
15	0.333	0.9	0.46	0.333	0.9	0.445	0.333	0.9	0.485	0.333	0.9	0.525	0.333	0.9	0.52

16	0.333	0.9	0.455	0.333	0.9	0.52	0.333	0.9	0.495	0.333	0.9	0.54	0.333	0.9	0.545
17	0.333	0.9	0.41	0.333	0.9	0.445	0.333	0.9	0.43	0.333	0.9	0.47	0.333	0.9	0.475
18	0.333	0.9	0.43	0.333	0.9	0.455	0.333	0.9	0.575	0.333	0.9	0.615	0.333	0.9	0.57
MEAN	**0.33**	**0.90**	**0.43**	**0.33**	**0.90**	**0.45**	**0.33**	**0.90**	**0.47**	**0.33**	**0.90**	**0.50**	**0.33**	**0.90**	**0.51**