Title: The integration of visual and target signals in V4 and IT during visual object search

Authors: Noam Roth and Nicole C. Rust
Affiliation: Department of Psychology, University of Pennsylvania, Philadelphia, PA USA

Running title: V4 and IT during visual object search

Corresponding author:
Nicole Rust
Department of Psychology
University of Pennsylvania
Goddard Labs, 428
Philadelphia, PA 19104
Phone: (215) 898-4587
Email: nrust@psych.upenn.edu

Number of pages: 34
Number of figures: 13
Words, abstract (of 250): 236
Words, introduction (of 650): 636
Words, discussion (of 1500): 1329

Conflicts of interest: None.

Acknowledgements: We thank Margot P. Wohl and Krystal Henderson for their technical contributions. This work was supported by the National Eye Institute of the US National Institutes of Health (award number R01EY020851), the Simons Foundation (through an award from the Simons Collaboration on the Global Brain), and the McKnight Endowment for Neuroscience.

ABSTRACT

Many everyday tasks require us to flexibly map incoming sensory information onto behavioral responses based on context. One example is the act of searching for a specific object, which requires our brain to compare the items in view with a remembered representation of a sought target to determine whether a target match is present. During object search, this comparison is thought to be implemented, in part, via the combination of top-down modulations reflecting target identity with feed-forward visual representations. However, it remains unclear whether these top-down signals are integrated at a single locus within the ventral visual pathway (e.g. V4) or at multiple stages (e.g. both V4 and inferotemporal cortex, IT). To investigate, we compared neural responses in V4 and IT recorded as rhesus monkeys performed a task that required them to identify when a target object appeared across variation in position, size and background context. We found non-visual, task-specific signals in both V4 and IT. To evaluate the plausibility that V4 was the only locus for the integration of top-down signals, we evaluated a number of feed-forward accounts of processing from V4 to IT, including a model in which IT preferentially sampled from the best V4 units, as well as a model that allowed for nonlinear IT computation. IT task-specific modulation could not be accounted for by any of these feed-forward descriptions, suggesting that during object search, top-down signals are integrated directly within IT itself.

SIGNIFICANCE

To find specific objects, the brain must combine top-down information reflecting the identity of a sought target with visual information about objects in view. While top-down signals exist at multiple stages along the ventral visual pathway, the route with which they arrive there is unclear. Here we present evidence that task-relevant signals in one high-level visual brain area, IT, cannot be described as being inherited from an earlier stage of processing, V4, but rather must be integrated directly within IT itself. This study is the first to systematically compare V4 and IT during an object search task in which objects can appear in different real-world configurations, and it provides important constraints on the neural computations responsible for finding visual targets.

INTRODUCTION

Finding a sought object requires our brains to perform at least two non-trivial computations. First, we must determine the identities of the objects in view, across variation in details such as their position, size, and background context. Second, we must compare this visual representation (of what we are looking at) with a remembered representation (of what we are looking for) to determine whether our target is in view. Considerable evidence suggests that computations in the primate ventral visual pathway, including brain areas V1, V2, V4 and IT, support the process of invariant object recognition (reviewed by DiCarlo et al. 2012). Within V4 and IT, many neurons are also modulated by information about target identity as well as whether an image is a target match (Haenny et al. 1988; Maunsell et al. 1991; Eskandar et al. 1992; Leuschow et al. 1994; Gibson and Maunsell 1997; Chelazzi et al. 1998; Chelazzi et al. 2001; Bichot et al. 2005; Pagan et al. 2013; Kosai et al. 2014; Roth and Rust 2018). However, the route by which these signals arrive in V4 and IT remains unclear.

Here we present two proposals describing how top-down signals reflecting the identity of a sought target and/or whether the object in view is a target match might arrive within V4 and IT during object search. In the first (Fig 1a), V4 serves as the sole locus of the combination of visual and top-down information, and IT receives this information via feed-forward propagation from V4. In the second (Fig 1b), top-down information is integrated directly in IT, either exclusively or in addition to its integration in V4.

Figure 1. *Proposals for how top-down target and/or target match information might arrive within V4 and IT during object search.* **a)** The class of "IT: inherited" proposals predict that top-down information is integrated only in V4, and this information is then inherited by IT via feed-forward propagation. **b)** The class of "IT: integrated" proposals predict that top-down information is integrated directly in IT. This class includes proposals in which top-down information is integrated in both IT and V4 (red) as well as proposals in which top-down information is integrated exclusively in IT but is then fed-back to V4 (cyan).

Indirect support for top-down integration directly in IT (Fig 1b) comes from studies reporting that non-visual, task-relevant signals increase in a gradient-like fashion across the early visual hierarchy (i.e. V1, V2 and V4) during covert spatial attention and feature-based attention tasks (reviewed by Noudoost et al. 2010), consistent with the integration of top-down signals at multiple stages. By extension, top-down signals could be integrated in both V4 and IT during visual target search. Importantly, if a gradient of top-down modulation were to exist between V4 and IT, this would not necessarily imply multiple stages of top-down integration (Fig 1b, red), as a gradient is also consistent with top-down integration in IT followed by feedback to V4 (Fig 1b, cyan). Evidence supports this scheme in V1, V2 and V4 (Buffalo et al. 2010).

In contrast, proposals in which V4 serves as the sole locus of top-down integration (Fig 1a) predict matched amounts of top-down modulation between V4 and IT, and the few studies that have measured it are most consistent with this prediction, both during visual target search (Chelazzi et al. 1998; Chelazzi et al. 2001) as well as one covert spatial attention task (Moran

and Desimone 1985). Additionally, while one might postulate that because receptive fields are
smaller in V4, the brain would be more likely to integrate top-down signals in IT when a task
requires spatial invariance (such as detecting the change in a feature despite its position), V4
feature-based attention effects have in fact been demonstrated to extend globally across the
visual field (reviewed by Maunsell and Treue 2006; Cohen and Maunsell 2011). It remains
unclear whether this type of spatially global, top-down modulation in V4 is sufficient to account
for top-down modulation in IT within a feed-forward framework (Fig 1a).
138
The means by which the brain integrates top-down information in the ventral visual pathway
may very well depend on the specific task and its computational demands. Here we focus on
challenging the hypothesis that top-down integration happens exclusively in V4 (Fig 1a) with a
task that is seemingly better optimized for top-down integration in IT. Specifically, our
experiments are designed to exploit differences in the visual representation of object identity
between these two brain areas.
145

METHODS

Experimental Design

Experiments were performed on two adult male rhesus macaque monkeys (*Macaca mulatta)* with implanted head posts and recording chambers. All procedures were performed in accordance with the guidelines of the University of Pennsylvania Institutional Animal Care and Use Committee. A portion of the data recorded in one brain area (IT) was presented in an earlier report (Roth and Rust 2018).

Visual stimuli

Images were presented in a circular aperture with a radius of 5 degrees, centered at fixation (Fig 3a). Images contained objects presented at different positions, sizes and background contexts (Fig 3c). Sizes included: size-1x (~1.2 degrees), size-1.5x (~1.8 degrees) and size-2.25x (~2.7 degrees). Positions included position-fixation (0 degrees horizontal and vertical), position-right (1.55 degrees to the right, 0.67 degrees below fixation), position-left (1.55 degrees to the left, 0.67 degrees below fixation) and position-up (0 degrees horizontal;1 degree above fixation). Changes in size and position were combined to produce the following five transformations (Fig 3c): "Up" (position-up, size-1.5x); "Left" (position-left; size-1.5x); "Right" (position-right; size-1.5x); "Big" (position-fixation; size-2.25x); and "Small" (position-fixation; size-1x). In addition, a different natural image background was chosen for each of the transformations Up, Big and Small whereas Left and Right were presented on a gray background (Fig 3c). The complete image set included 4 objects, each presented at the five transformations described above, for a total of 20 images. The rationale behind selecting these particular transformations was to make the task of object identification (invariant to identity-preserving transformation) challenging for both V4 and IT, based on results from our previous work (Rust and DiCarlo 2010).

As described below, our experiment included two types of trials, "Cue trials" and "Test trials". The set of 20 images described above were the only images presented on Test trials. Cue trials also included a version of each object (size-1.5x) presented at position-fixation on a gray background.

The invariant delayed-match-to-sample (IDMS) task

Monkey behavioral training and testing utilized standard operant conditioning, head stabilization and infrared video eye tracking. Custom software (http://mworks-project.org) was used to present stimuli on an LCD monitor with an 85 Hz refresh rate.

The monkeys performed an invariant delayed-match-to-sample task (Fig 3). As an overview, the task required the monkeys to make a saccade when a target object appeared within a sequence of distractor images (Fig 3a). Objects were presented at differing positions, sizes and background contexts as described above and shown in Figure 3c3c. Stimuli consisted of a fixed set of 20 images that included 4 target objects, each presented at 5 different identity-preserving transformations (Fig 3b). Each short block (~3 min) was run with a fixed target object before another target was pseudorandomly selected. Our design included two types of trials: cue trials and test trials (Fig 3a). Only test trials were analyzed for this report.

A trial began when the monkey fixated on a red dot (0.15°) in the center of a gray screen, within
a square window of ±1.5°. Fixation was followed by a 250 ms delay before a stimulus appeared.
Cue trials, which indicated the current target object, were presented at the beginning of each
short block or after three subsequent error trials. To minimize confusion, cue trials were
designed to be distinct from test trials and began with the presentation of an image of each
object that was distinct from the images used on test trials (a large version of the object
presented at the center of gaze on a gray background; Fig 3a). Test trials began with a
distractor image, and neural responses to the first distractor were discarded to minimize non-
stationarities such as stimulus onset effects. During the IDMS task, all images were presented
at the center of gaze, in a circular aperture that blended into a gray background (Fig 3c).
203
In each block, 5 images were presented as target matches and the other 15 as distractors.
Distractor images were drawn randomly without replacement until each distractor was presented
once on a correct trial, and the images were then re-randomized. On most test trials, a target
match followed the presentation of a random number of 1-6 distractors (Fig 3a). On a small
fraction of trials, 7 distractors were shown, and the monkeys were rewarded for fixating through
all distractors. Each image was presented for 400 ms (or until the monkeys' eyes left the fixation
window) and was immediately followed by the presentation of the next stimulus. Monkeys were
rewarded for making a saccade to a response target within a window of 75 – 600 ms after the
target match onset. In monkey 1, the response target was positioned 10 degrees below fixation;
in monkey 2 it was 10 degrees above fixation. If the monkeys had not yet moved their eyes after
400 ms following target onset, a distractor stimulus was immediately presented. A trial was
classified as a 'false alarm' if the eyes left the fixation window via the top (monkey 1) or bottom
(monkey 2) outside the allowable correct response period and travelled more than 0.5 degrees.
In contrast, all other instances in which the eyes left the fixation window during the presentation
of distractors were characterized as fixation breaks. A trial was classified as a 'miss' when the
monkey continued fixating beyond 600 ms following the onset of the target match. Within each
block, 4 repeated presentations of each of the 20 images were collected, and a new target
object was then pseudorandomly selected. Following the presentation of all 4 objects as targets,
the targets were re-randomized. At least 10 repeats of each condition were collected on correct
trials. When more than 10 repeats were collected, the first 10 were used for analysis. Overall,
monkeys performed this task with high accuracy. Disregarding fixation breaks (monkey 1: 8% of
trials, monkey 2: 11% of trials), percent correct on the remaining trials was: monkey 1: 94%
correct, 2% false alarms, and 4% misses; monkey 2: 98% correct, ~1% false alarms, and ~1%
misses. Behavioral performance was comparable for the sessions corresponding to recordings
from the two areas (V4 percent correct overall = 96.5%; IT percent correct overall = 91.4%).
229
V4 receptive fields at and near the center of gaze are small: on average they have radii of 0.56
degrees at the fovea, extending to radii of 1.4 at an eccentricity of 2.5 degrees (Desimone and
Schein 1987; Gattass et al. 1988). We thus took considerable care to ensure that that the
images were approximately placed in the same region of these receptive fields across repeated
trials. In the second monkey, adequate fixational control could not be achieved through training.
We thus applied a procedure in which we shifted each image at stimulus onset 25% toward the
center of gaze (e.g. if the eyes were displaced 0.5 degrees to the left, the image was
repositioned 0.125 degrees to the left and thus 0.375 degrees from fixation). Image position
then remained fixed until the onset of the next stimulus.

Neural recording

The activity of neurons in V4 and IT was recorded via a single recording chamber for each brain area in each monkey. In both monkeys, chamber implantation and recording in IT preceded V4, and the IT recording chamber was implanted on the right hemisphere whereas the V4 recording chamber was implanted on the left hemisphere. While IT receptive fields span the vertical meridian, thus allowing us to access the visual representation of both sides with a single chamber, V4 receptive fields are confined to the contralateral hemifield. To simulate V4 coverage of the ipsilateral visual field, on roughly half of the V4 recording sessions, (n = 7/15sessions in Monkey 1, n = 11/20 sessions in Monkey 2), we presented the images reflected across the vertical axis. We then treated all V4 units recorded during these sessions as if they were in the left hemisphere (and thus as receptive fields that were located in the right visual field).

Chamber placement for the IT chambers was guided by anatomical magnetic resonance images in both monkeys, and in one monkey, Brainsight neuronavigation (https://www.rogue-research.com/). Both V4 chambers were guided by Brainsight neuronavigation. The region of IT recorded was located on the ventral surface of the brain, over an area that spanned 4 mm lateral to the anterior middle temporal sulcus and 15-19 mm anterior to the ear canals. Both V4 chambers were centered 1 mm posterior to the ear canals and 29 mm lateral to the midline, positioned at a 30 degree angle. V4 recording sites were confirmed by a combination of receptive field location and position in the chamber, corresponding to results reported previously (Gattass et al. 1988). Specifically, we recorded from units within and around the inferior occipital sulcus, between the lunate sulcus and superior temporal sulcus. V4 units in lower visual field were confirmed as having receptive field centers that traversed from the vertical to horizontal meridian as recordings shifted from posterior to anterior. As expected, V4 units in the fovea and near the upper visual field were found lateral to those in the lower visual field, and had receptive field centers that traversed from the horizontal meridian to the vertical meridian as recordings traversed medial to lateral and increased in depth.

Neural activity was recorded with 24-channel U-probes and V-probes (Plexon, Inc) with linearly arranged recording sites spaced with 100 mm intervals. Continuous, wideband neural signals were amplified, digitized at 40 kHz and stored using the OmniPlex Data Acquisition System (Plexon, Inc.). Spike sorting was done manually offline (Plexon Offline Sorter). At least one candidate unit was identified on each recording channel, and 2-3 units were occasionally identified on the same channel. Spike sorting was performed blind to any experimental conditions to avoid bias. A multi-channel recording session was included in the analysis if the animal performed the task until the completion of at least 10 correct trials per stimulus condition, there was no external noise source confounding the detection of spike waveforms, and the session included a threshold number of task-modulated units (>4 on 24 channels). The sample size for IT (number of units recorded) was chosen to approximately match our previous work (Pagan et al. 2013; Pagan and Rust 2014a). The sample size for V4, was selected to be 3-fold that number, to match the ratio between numbers of units estimated in V4 as compared to IT (DiCarlo et al. 2012).

For many of the analyses presented in this paper, we measured neural responses by counting spikes in a window that began 40 ms after stimulus onset in V4 and 80 ms after stimulus onset in IT. We counted spikes in a 170 ms window in both areas, such that the spike counting windows were of equal length. Counting windows always preceded the monkeys' reaction times.

289   On 7.7% of all correct target match presentations, the monkeys had reaction times faster than
290   250 ms, and those instances were excluded from analysis to ensure that spikes in both V4 and
291   IT were only counted during periods of fixation.
292
In IT, we recorded neural responses across 20 experimental sessions (Monkey 1: 10 sessions,
and Monkey 2: 10 sessions). In V4, we recorded neural responses across 35 experimental
sessions (Monkey 1: 15 sessions, and Monkey 2: 20 sessions). When combining the units
recorded across sessions into a larger pseudopopulation, we began by screening for units that
met three criteria. First, units needed to be modulated by our task, as quantified by a one-way
ANOVA applied to our neural responses (80 conditions * 10 repeats, $p < 0.01$). Second, units
needed to pass a loose criterion on recording stability, as quantified by calculating the variance-
to-mean ratio (Fano factor) for each unit, computed by fitting the relationship between the mean
and variance of spike count across the 80 conditions (Fano factor < 5). Finally, units needed to
pass a loose criterion on unit recording isolation, quantified by calculating the signal-to-noise
ratio (SNR) of the waveform as the difference between the maximum and minimum points of the
average waveform, divided by twice the standard deviation across the differences between each
waveform and the mean waveform (SNR > 2). In IT, this yielded a pseudopopulation of 204
units (of 563 possible units), including 108 units from monkey 1 and 96 units from monkey 2. In
V4, this yielded a pseudopopulation of 650 units (of 970 possible units), including 382 units from
monkey 1 and 268 units from monkey 2.
309
310   **V4 receptive field mapping**
311
To measure the location and extent of V4 receptive fields, bars were presented for 500 ms, one
per trial, centered on a 5 x 5 invisible grid. Bar orientation, length, and width as well as the grid
center and extent were adjusted for each recording session based on preliminary hand
mapping. On each trial, the monkey was required to maintain fixation on a small response dot
(0.125°) to receive a reward. The responses to at least five repeats were collected at each
position for each recording session. Only those units that produced clear visually evoked
responses at a minimum of one position were considered for receptive field position analysis.
The center of the receptive field was estimated by the maximum of the response across the 5x5
grid of oriented bar stimuli and confirmed by visual inspection.
321
322   **Quantifying single-unit modulations**
323
To quantify the degree to which individual V4 and IT units were modulated by task-relevant
variables (Figs 6, 9, 10), such as changes in visual and target identity, we applied a bias-
corrected, ANOVA-like procedure described in detail by (Pagan and Rust 2014b) and
summarized here. As an overview, this procedure is designed to parse each unit's total
response variance into variance that can be attributed to each type of experimental parameter
as well as variance that can be attributed to trial variability. Total variance is computed across
the spike count responses for each unit across 16 conditions (4 images * 4 targets for each
transformation) and 10 trials. Variances are then transformed into measures of spike count
modulation (in the units of standard deviation around each unit's grand mean spike count) via a
procedure that includes bias correction for over-estimates in modulation due to noise.
334
To capture all types of modulation with intuitive groupings, the procedure begins by developing
an orthonormal basis of 16 vectors. The number of basis vectors for each type of modulation is
imposed by the experimental design. In particular, this basis b included vectors b_i that reflected

1) the grand mean spike count across all conditions, 2) whether the object in view was a target
or a distractor ('target match'), 3) visual image identity ('visual'), 4) target object identity ('target
identity'), and 5) nonlinear interactions between target and object identity not captured by target
match modulation ('residual'). The initially designed set of vectors is converted into an
orthonormal basis via a Gram-Schmidt orthogonalization process.

The resulting basis spans the space of all possible responses for our task. Consequently, we
can re-express each trial-averaged vector of spike count responses to the 16 experimental
conditions for each transformation, R, as a weighted sum of these basis vectors. The weight
corresponding to a basis vector for each unit reflect modulation of that unit's responses by that
experimental parameter. To quantify the amounts of each type of modulation reflected by each
unit, we began by computing the squared projection of each basis vector b_i and R. To correct
for bias caused by over-estimates in modulation due to noise, an analytical bias correction,
described and verified in (Pagan and Rust 2014b), was then subtracted from this value. The
squared weight for each basis vector b_i is calculated as:

(1) $w_i^2 = (R \cdot b_i^T)^2 - \frac{\sigma_t^2 \cdot (b_i^T)^2}{m}$

where σ_t^2 indicates the trial variance, averaged across conditions (n=16), and m indicates the
number of trials (m=10). If more than one dimension existed for a type of modulation, we
summed values of the same type (eq. 2). Next, we applied a normalization factor (1/(n-1)) where
n=16) to convert these summed values into variances. As a final step, we computed the square
root of these quantities to convert them into modulation measures that reflected the number of
spike count standard deviations around each unit's grand mean spike count. Modulation for
each parameter type X was thus computed as:

(2) $\sigma_X = \sqrt{\frac{1}{n-1} \cdot \sum_{i=j}^{k} w_i^2}$

for the weights w_j through w_k corresponding to basis vectors b_j through b_k for that parameter
type, where the number of basis vectors corresponding to each parameter type were: target
match = 1; visual = 3; target identity = 3; residual = 8.

When estimating modulation for individual units, (Fig 6), the bias-corrected squared values were
rectified for each unit before taking the square root. When estimating modulation population
means (Fig 9b-e, Fig 10), the bias-corrected squared values were averaged across units before
taking the square root. When estimating modulation population means within the broader 170
ms bins for V4 and IT respectively (bar graphs shown in Fig 9b-e, Fig 10, right), the modulations
shown are roughly equal to the sum (or integral) of the modulations in the 50 ms sliding bins
(Fig 9b-e, Fig 10, left) summed across the 40-20 ms or 80-250 ms bins in V4 and IT
respectively. However, because we computed the modulations separately in the different bin
sizes before bias-correcting, averaging across units, and taking the square root, this relationship
is not exactly equivalent to an integral. Because these measures were not normally distributed,
standard error about the mean was computed via a bootstrap procedure. On each iteration of
the bootstrap (across 1000 iterations), we randomly sampled values from the modulation values
for each unit in the population, with replacement. Standard error was computed as the standard
deviation across the means of these resampled populations.

Population performance: Visual object invariance

To determine performance of the V4 and IT populations at classifying visual object identity (Fig 7), we computed 4-way object discrimination performance. As an overview, we formulated the problem as four one-versus-rest linear classifications, and then took the maximum of these classifications as a population's decision (Hung et al. 2005). Here we begin by describing the general form of linear classifier that we used, a Fisher Linear Discriminant (FLD), and we then describe the training and testing scheme for measuring cross-validated performance.

The general form of a linear decoding axis is:

(3) $f(\boldsymbol{x}) = \boldsymbol{w}^T \boldsymbol{x} + b,$

where **w** is an N-dimensional vector containing the linear weights applied to each of N units, and b is a scalar value. We fit these parameters using an FLD, where the vector of linear weights was calculated as:

(4) $\boldsymbol{w} = \Sigma^{-1}(\mu_1 - \mu_2)$

and b was calculated as:

(5) $b = \boldsymbol{w} \cdot \frac{1}{2}(\mu_1 + \mu_2) = \frac{1}{2}\mu_1^T\Sigma^{-1}\mu_1 - \frac{1}{2}\mu_2^T\Sigma^{-1}\mu_2$

Here μ_1 and μ_2 are the means of two classes (e.g. two object classes, respectively) and the mean covariance matrix is calculated as:

(6) $\Sigma = \frac{\Sigma_1 + \Sigma_2}{2}$

where Σ_1 and Σ_2 are the regularized covariance matrices of the two classes. These covariance matrices were computed using a regularized estimate equal to a linear combination of the sample covariance and the identity matrix I (Pagan and Rust 2014a):

(7) $\Sigma_i = \gamma \Sigma_i + (1 - \gamma) \cdot I$

We determined γ by exploring a range of values from 0.01 to 0.99, and we selected the value that maximized average performance across all iterations, measured with the cross-validation "regularization" trials set aside for this purpose (see below). We then computed performance for that value of γ with separately measured "test" trials, to ensure a fully cross-validated measure. Because this calculation of the FLD parameters incorporates the off-diagonal terms of the covariance matrix, FLD weights are optimized for both the information conveyed by individual units as well as their pairwise interactions.

To classify which of four objects was in view, we used a standard "one-versus-rest" classification scheme. Specifically, one linear classifier was determined for each object based on the training data. To determine the population decision about which object was presented, a response vector **x**, corresponding to the population response of one of the four objects, was then applied to each of the classifiers, and the classifier with the largest output (the classifier with the largest positive *f*(**x**)) was taken as the population decision. To train the classifiers, we used an iterative resampling procedure. On each iteration of the resampling, we randomly shuffled the trials for each condition and for each unit, and (for numbers of units less than the

419 full population size) randomly selected units. On each iteration, 8 trials from each condition were
420 used for training the decoder, 1 trial from each condition was used to determine a value for
421 regularization, and 1 trial from each condition was used for cross-validated measurement of
422 performance.
423
We compared classifier performance for the "reference" cases (when cross-validated test trials
were selected from the same transformation used to train the classifier; Fig 7a--b, black) versus
the "generalization" cases (when test trials were selected from transformations different than the
one used for training, Fig 7a-b, cyan). To summarize the results for a given transformation,
reference and generalization performance was compared for the same test data: e.g. In the
case of the transformation "Up", reference performance was computed by training and cross-
validated testing on "Up" and generalization performance was computed as the average of
training on all other transformations and testing on "Up".
432
To ensure that visual classification performance was not biased by the target match signal, we
computed performance for targets and distractors separately and averaged their results.
Specifically, we computed visual classification performance for the four objects presented as
target matches or for different combinations of the four objects presented as distractors. Each
set of 4 distractors was selected to span all possible combinations of mismatched object and
target identities (e.g. objects 1, 2, 3, 4 paired with targets 4, 3, 2, 1), of which there are 9
possible sets. As a final measure of visual classification performance, we averaged across 10
performance values (1 target match and 9 distractor combinations) as well as, when relevant,
multiple transformations. One performance value was computed on each iteration of the
resampling procedure, and mean and standard error of performance was computed as the
mean and standard deviation of performance across 1000 resampling iterations. Standard error
thus reflected the variability due to the specific trials assigned to training and testing and, for
populations smaller than the full size, the specific units chosen. Finally, generalization capacity
was computed on each resampling iteration by taking the ratio of the chance-subtracted
reference performance and the chance-subtracted generalization performance (where chance =
25%).
449
450 **Population performance: Target match information**
451
To determine the ability of the V4 and IT populations to classify target matches versus
distractors (Figs 11 & 12), we applied two types of decoders: a linear classifier (an FLD,
described above) and a Maximum Likelihood decoder (a decoder that can classify based on
linear as well as nonlinearly formatted target match information). Both decoders were cross-
validated with the same resampling procedure. On each iteration of the resampling, we
randomly shuffled the trials for each condition and for each unit, and (for numbers of units less
than the full population size) randomly selected units (with the exception of Fig 11c, cyan, where
we selected the 'best' units, as described below). On each iteration, 8 trials from each condition
were used for training the decoder, 1 trial from each condition was used to determine a value for
regularization of the FLD linear classifier (see below) and 1 trial from each condition was used
for a cross-validated measurement of performance.
463
To circumvent issues related to the format of visual information, classifier analyses were
performed per transformation ("Big", "Up", "Left" and "Small"). The data for each transformation
consisted of 16 conditions (4 visual objects viewed under 4 different target contexts). To ensure
that decoder performance relied only on target match information and not on other factors, such

as differences in the numbers of each class, each classification was computed for 4 target
matches versus 4 (of 12 possible) distractors. Each set of 4 distractors was selected to span all
possible combinations of mismatched object and target identities (e.g. objects 1, 2, 3, 4 paired
with targets 4, 3, 2, 1), of which there are 9 possible sets. Performance was computed on each
resampling iteration by averaging the binary performance outcomes across the 9 possible sets
of target matches and distractors, each which contained 8 cross-validated test trials, and across
the four transformations used. For both types of classifiers, mean and standard error of
performance was computed as the mean and standard deviation of performance across 1000
resampling iterations. Standard error thus reflected the variability due to the specific trials
assigned to training and testing and, for populations smaller than the full size, the specific units
chosen.
479

To compute linear classifier performance (Fig 11), we used a 2-way Fisher Linear Discriminant,
described as in the general form above. In this case, the classes described in eqs. 4-6
correspond to target matches and distractors. To compute neural population performance, we
began by computing the dot product of the test data and the linear weights **w**, adjusted by *b* (Eq.
5). Each test trial was then assigned to one class, and proportion correct was then computed as
the fraction of test trials that were correctly assigned, according to their true labels. To compute
linear classifier performance for the best V4 units (Fig 11c, cyan), we ranked units by their d'
based on the training data and sub-selected top-ranked units to measure cross-validated
performance. Unit d' was computed as:
489

(8) $d' = \frac{|\mu_{Match} - \mu_{Distractor}|}{\sigma_{pooled}}$,

where μ_{Match} and $\mu_{Distractor}$ correspond to the mean across the set of target match and

distractors, $\sigma_{pooled} = \sqrt{\frac{\sigma_{Match}^2 + \sigma_{Distractor}^2}{2}}$, and σ_{Match} and $\sigma_{Distractor}$ correspond to the standard

deviation across the set of target matches and distractors, respectively.

As a measure of total target match information (Fig 12; combined linear and nonlinear), we
implemented a maximum likelihood decoder (Pagan et al. 2013; Pagan et al. 2016). We began
by using the set of training trials to compute the average response r_{uc} of each unit u to each of
the 2 conditions c (target matches versus distractors). We then computed the likelihood that a
test response k was generated from a particular condition as a Poisson-distributed variable:

(9) $lik_{u,c}(k) = \frac{(r_{uc})^k \cdot e^{-r_{uc}}}{k!}$

The likelihood that a population response vector was generated in response to each condition
was then computed as the product of the likelihoods of the individual units. We assigned the
population response to the category with the maximum likelihood, and we computed
performance as the fraction of trials in which the classification was correct based on the true
labels of the test data.
506
507
508

Statistical analysis

Because our measures were not normally distributed, we computed P values via resampling
procedures. When comparing the magnitudes of single unit modulation values between V4 and
IT (Fig 6, Fig 9b-e, Fig 10), a bootstrap procedure was applied in which values were randomly
sampled from the values for each unit, with replacement, across many iterations. We calculated
P values as the fraction of resampling iterations on which the difference was flipped in sign
relative to the actual difference between the means of the full data set (for example, if the mean
of visual modulation in V4 was larger than the mean of visual modulation in IT, the fraction of
iterations in which the mean of visual modulation in IT was larger than the mean of visual
modulation in V4).

When comparing generalization capacity between the V4 and IT populations (Fig 7d), we began
by computing generalization capacity for each of 1000 resampling iterations of the reference
and generalization classifiers. We calculated *P* values as the fraction of resampling iterations on
which the difference was flipped in sign relative to the actual difference between the means of
the full data set (for example, if the mean of generalization capacity in IT was larger than the
mean of generalization capacity in V4, the fraction of iterations in which the mean of
generalization capacity in V4 was larger than the mean of generalization capacity in IT).

When comparing population decoding measures (Figs 7a-c, 11c, & 12c), 1000 iterations of
cross-validated population performance were computed, and *P* values were calculated as the
fraction of classifier iterations on which the difference was flipped in sign relative to the actual
difference between the means across classifier iterations (for example, if the mean of decoding
measure 1 was larger than the mean of decoding measure 2, the fraction of iterations in which
the mean of measure 2 was larger than the mean of measure 1). When evaluating whether a
population decoding measure was different from chance (Figs 11-12), P values were calculated
as the fraction of classifier iterations on which performance was greater than chance
performance (50%).

RESULTS

As an overview of our experiments, we trained two monkeys to perform an "invariant delayed-match-to-sample" (IDMS) task that required them to report when target objects appeared. On any given trial of the IDMS task, monkeys were instructed about the object that they were searching for, but they did not know the specific position, size and background context with which it would appear. The task was designed to exploit well-established differences in the nature of visual object representations between V4 and IT, where both brain areas have been demonstrated to reflect similar total amounts of information for object identification tasks, but in V4 this information is more implicitly formatted (i.e. nonlinearly separable; Fig 2a, left) whereas in IT this information is more explicitly formatted (i.e. more accessible to a linear population read-out; Fig 2a right; reviewed by DiCarlo et al. 2012). At the level of individual neurons, the response property supporting IT population linear separability is thought to be object "tolerance", or the preservation of rank-order tuning for objects across identity preserving transformations (Ito et al. 1995; Li et al. 2009). Object tolerance is most intuitively described for changes in object position and spatially large IT receptive fields that have the same tuning for object identity across all regions of their receptive field (Fig 2b, right). In contrast, V4 receptive fields are smaller, and are stimulated by different regions of the image when an object moves to a new position (Fig 2c), and this can lead to a change in the rank-order tuning for objects at different positions (Fig 2b, left).

Figure 2. *Differences between V4 and IT visual object representations.* **a)** Cartoon depiction of the population representation of object identity in V4 and IT plotted as the response of two hypothetical neurons. In these plots, each point indicates the population response on a single trial, each cloud of points depicts the dispersion of responses across repeated trials, the color of the points indicate the identity of the object contained in each image, and the shape of the points indicate the identity-preserving transformation at which each object appears. In V4, representations of object identity are nonlinearly separable, as indicated by the nonlinear boundary required to separate the two objects. In IT, representations of object identity are more linearly separable, as indicated by the linear boundary. **b)** The single-neuron property underlying V4 nonlinear and IT linear population representations is thought to be object tolerance, where increased IT linear separability (right) follows from the increased preservation of rank-order responses across identity-preserving transformations, and increased V4 nonlinear separability (left) follows from larger changes in rank-order preferences across different transformations. **c)** Illustration of how rank-order preferences for objects can change when receptive fields are small and objects are moved to a new position. In the left image, a region of giraffe object drives the neuron to fire; in the right image, the same neuron is driven by the background of an image containing a different object (squirrel).

In the context of the IDMS task where monkeys were searching for an object that could appear at different transformations, the visual information required to solve the task (i.e. identity of the object in view) is expected to exist in both V4 and IT, but this information is expected to be formatted in a more linear manner in IT. In question is whether this difference in information format between V4 and IT coincides with the preferential integration of top-down information in

IT (Fig 1b). Equivalently, in question is whether during the IDMS task the brain somehow manages to integrate invariant information about object identity in V4 where receptive fields are small – which it may in fact be able to do, given the spatially global top-down modulations documented in V4 feature-based attention experiments (Maunsell and Treue 2006; Cohen and Maunsell 2011) - or whether it preferentially targets IT, where receptive fields are larger.

Some of the data presented here were also included in an earlier publication (Roth and Rust 2018). There, we reported that during IDMS, neural signals in IT reflected behavioral confusions on the trials in which the monkeys made errors, and IT target match signals were configured in a manner that minimized their interference with IT visual representations. The focus of the current report is a determination of how these signals arrive in IT via a systematic comparison between IT and its input brain area, V4.

The invariant delayed-match-to-sample task (IDMS)

Monkeys performed an invariant delayed-match-to-sample (IDMS) task in short blocks of trials (~3 minutes on average) with a fixed target object. Each block began with a cue trial that indicated the target for that block (Fig 3a 'Cue Trial'). The remainder of the block was comprised primarily of test trials (Fig 3a, 'Test trial'). Test trials began with the presentation of a distractor and on most trials this was followed by 0-5 additional distractors (for a total of 1-6 distractor images) and then an image containing the target match. The monkeys' task required them to maintain fixation during the presentation of distractors and make a saccade in response to the appearance of a target match to receive a juice reward. To minimize the possibility that monkeys would predict the target match, on a small fraction of the trials the target match did not appear and the monkeys were rewarded for maintaining fixation through 7 distractors. Unlike other classic DMS tasks (Eskandar et al. 1992; Chelazzi et al. 1993; Leuschow et al. 1994; Miller and Desimone 1994; Pagan et al. 2013) our experimental design does not incorporate a cue at the beginning of each test trial, to better mimic real-world object search, where target matches are not repeats of the same image presented shortly before. One benefit of this task design is that it better isolates target match modulation from other types of stimulus repetition effects, including repetition suppression (Miller and Desimone 1994). This distinction is important for this study, as our goal was to systematically compare the magnitudes of top-down modulation in V4 and IT and repetition suppression is likely to be a largely feed-forward process.

Figure 3. *The invariant delayed-match-to-sample task (IDMS).* **a)** Monkeys initiated trials by fixating on a small dot. Each block (~3 minutes in duration) began with a cue trial which indicated the target object. On subsequent trials, a random number (1-7) of distractors were presented, and on most trials, this was followed by the target match. Monkeys were required to maintain fixation throughout the distractors and make a saccade to a response dot within a window 75 - 600 ms following the onset of the target match to receive a reward. In cases where the target match was presented for 400 ms and the monkey had still not broken fixation, a distractor stimulus was immediately presented. **b)** A schematic of the full experimental design, which included 80 conditions: looking "at" each of 4 objects, each presented at 5 identity-preserving transformations (for 20 images in total), viewed in the context of looking "for" each object as a target. In this design, target matches (gray) fall along the diagonal of each "looking at" / "looking for" transformation slice whereas distractors (white) fall off the diagonal. **c)** Images

used in the task: 4 objects were presented at each of 5 identity-preserving transformations ("up", "left", "right", "big", "small"), for 20 images in total. In any given block, 5 of the images were presented as target matches and 15 were distractors. **d)** Percent correct for each monkey, calculated based on both misses and false alarms (but disregarding fixation breaks), shown as a function of the number of distractors preceding the target match. Error bars indicate standard error across experimental sessions. **e)** Histograms of reaction times during correct trials (ms after stimulus onset), with means labeled.

Our experimental stimuli consisted of a fixed set of 20 images: 4 objects presented at each of 5 transformations (Fig 3b). These specific images were selected in order to make the task of classifying object identity challenging for the IT population and these specific transformations were selected based on findings from our previous work (Rust and DiCarlo 2010). In a given target block (e.g. a 'banana block'), a subset of 5 of the images were target matches and the remaining 15 were distractors (Fig 3c). The full experimental design amounted to 20 images (4 objects presented at 5 identity-preserving transformations), all viewed in the context of each of the 4 objects as a target, resulting in 80 experimental conditions (Fig 3b). In this design, "target matches" fall along the diagonal of each looking at / looking for matrix slice (where a matrix "slice" corresponds to the conditions at one fixed transformation; Fig 3b, gray). For each of the 80 conditions, we collected at least 10 repeats on correct trials. Behavioral performance was high overall (Fig 3d). The monkeys' mean reaction times (computed as the time their eyes left the fixation window relative to the target match stimulus onset) were 311 ms and 363 ms for monkey 1 and 2, respectively (Fig 3e).

To systematically compare the responses of V4 and IT during this task, we applied a population-based approach in which we fixed the images and their placement in the visual field across all the units that we studied, and we sampled from units whose receptive fields overlapped the stimuli. Specifically, we presented images at the center of gaze, with a diameter of 5 degrees. Neurons in IT typically have receptive fields that extend beyond 5 degrees and extend into all four quadrants (Fig 3a top; Op De Beeck and Vogels 2000). In contrast, V4 receptive fields are smaller, retinotopically organized, and confined to the contralateral hemifield (Fig 3a bottom; Desimone and Schein 1987; Gattass et al. 1988). To compare these two brain areas, we applied extensions of approaches developed in our earlier work in which we compared the responses of a set of randomly sampled IT units with a population of V4 units whose receptive fields tiled the image (Rust and DiCarlo 2010). This required sampling V4 units with receptive fields in both upper and lower visual fields, which we achieved through recording at different positions within and around the inferior occipital sulcus. This also required measuring units with receptive fields on both sides of the vertical meridian, which we approximated by isolating our recordings to one hemisphere but reflecting the images along the vertical axis in approximately half the sessions.

Figure 4. *V4 and IT receptive field locations.* Images were displayed at the center of gaze and were 5 degrees in diameter. Red circles indicate the location and size of the images. **a)** Schematic of expected receptive field locations and sizes for neurons in IT (top; Op De Beeck and Vogels 2000) V4 (bottom; Desimone and Schein 1987; Gattass et al. 1988). **b)** We targeted V4 units with receptive fields that tiled the images. After approximate receptive field

localization with hand mapping, receptive field locations were determined with oriented bar
stimuli presented in a 5 x 5 grid of different positions (see Methods). Shown are the receptive
field centers of a subset of recorded V4 units; one dot is shown for each unique receptive field
location recorded. On approximately half of the sessions, images were reflected across the
vertical axis, and for these sessions, the receptive field centers are plotted in the ipsilateral
visual field. Monkey 1: gray; Monkey 2: white.

693
694
695
Because V4 receptive fields in the region of the field that we recorded are small, one issue of
concern is the replicability of retinal image placement across trials. We quantified the stability of
monkeys' eye positions across repeated trials as the spatial deviation in retinal image
placement across trials, measured relative to the mean position across trials, and we
determined the proportion of eye positions that were within windows corresponding to V4
receptive field sizes at the range of eccentricities we recorded (Gattass et al. 1988). In monkey
1, 85% of eye positions fell within windows corresponding to the average RF sizes at the fovea
(average foveal receptive field size = 0.56 degrees), and 97% of eye positions were within
windows corresponding to RF sizes at an eccentricity of 2.5 degrees (average receptive field
size at 2.5 degrees = 1.4 degrees). To achieve similar precision in Monkey 2, fixational control
was improved by employing a procedure in which eye position was determined just before
stimulus onset and the image was shifted at stimulus onset such that it was positioned closer to
the center of gaze (see Methods). The image then remained in the same, fixed position for the
duration of the image viewing period. The resulting retinal stability was comparable to monkey 1:
on average, 95, and 99% of presentations occurred within windows with a radius of 0.56 and 1.4
degrees, respectively. These approaches were also effective in producing similar distributions of
neural trial-by-trial variability between the two monkeys and between the two brain areas, as
measured by the mean and standard deviation of the variance-to-mean ratio (Fano factor)
across units (mean +/- std, Monkey 1: V4 = 1.61+/-0.65; IT = 1.62 +/- 0.68; Monkey 2: V4 = 1.49
+/- 0.54; IT = 1.28 +/- 0.36).

716
As two monkeys performed this task, we recorded neural activity from small populations using
24-channel probes that were acutely lowered into V4 or IT before each session. With the
rationale that V4 contains approximately 3-fold more units than IT near the fovea (DiCarlo et al.
2012), we aimed to collect 3-fold more units from V4. Following a screen for units based on their
stability, isolation, and task modulation (see Methods), our data included 650 V4 units and 204
IT units (Monkey 1: 382 units in V4 and 108 in IT; Monkey 2: 268 units in V4 and 96 in IT). The
data reported here were extracted from trials with correct responses. For all analyses except
Figs 9-10, we counted spikes in equal length windows in V4 and IT but adjusted for the
difference in latency between the two brain areas (170 ms, V4: 40-210 ms; IT: 80-250 ms
following stimulus onset). These windows always preceded the monkeys' reaction times and
thus corresponded to periods of fixation. Distributions of peak, grand mean, and baseline firing
rates computed for these spike count windows are shown in Figure 5. Observed firing rates
were similar to those recorded in V4 and IT in an earlier study that measured the responses of
well-isolated single units to larger numbers of images (Rust and DiCarlo 2012).

731
732
733
734

Figure 5. *Firing rate distributions.* Stimulus-evoked firing rates were computed as the average firing rate in a window 40-210 ms (V4) or 80–250 ms (IT) following stimulus onset whereas baseline firing rates were computed during the 170 ms period of fixation preceding stimulus onset. a) Maximum firing rates across the 80 stimulus conditions. The last bin includes units with maximum firing rates greater than 40 Hz and the broken axis extends to a proportion of 0.07 in V4 and 0.06 in IT. b) Grand mean firing rates across the 80 stimulus conditions. The last bin includes units with grand mean firing rates greater than 30 Hz and the broken axis extends to a proportion of 0.01 in V4. c) Baseline firing rates. In all panels, arrows indicate the means (V4: n = 650 units; IT: n = 204 units).

Visual modulation as a benchmark for verifying V4 and IT data:

When making systematic comparisons between V4 and IT, there are important factors to consider. For example, should the information contained in the V4 and IT populations be compared with equal numbers of units? Similarly, what are appropriate benchmarks for determining whether the samples recorded from each brain area are representative? As an example, imagine a scenario in which the same information about whether an image is a target match or a distractor is reflected in both V4 and IT to the same degree, but the V4 neurons recorded in an experiment all have small, overlapping receptive fields confined to the same, small region of the visual field. In contrast, IT neurons, by virtue of their large receptive fields, would have access to much more of the visual field. From this data we might erroneously find that the magnitude of total target match information is larger in IT than V4 by way of non-representative sampling.

As a benchmark for assessing whether the data we recorded from each brain area were representative, we compared the amount of visual modulation present in each brain area, at each transformation, with the following rationale. First, all the visual information contained in IT is thought to arrive there after first travelling through V4 (Felleman and Van Essen 1991), and consequently, samples of V4 and IT are comparable only if visual information is equal or higher in the V4 sample. Second, by comparing visual information at each transformation separately, we circumvent issues related to the differences in the format of visual information between the two brain areas described in Fig 2a.

To compare the amounts of visual information in our recorded V4 and IT populations, we computed a single-unit measure of visual modulation described by (Pagan and Rust 2014b) and included in a number of our earlier reports (Pagan et al. 2013; Pagan and Rust 2014a; Roth and Rust 2018). The advantage of this measure is that it disentangles modulations due to changes in visual identity from other factors, such as top-down target modulation, whereas many other traditional measures (e.g. single-neuron d' or ROC) do not. More specifically, while measures like single-unit d' are in fact proportional to modulation by the variable of interest (e.g. visual modulation), they are also inversely proportional to other types of modulation (e.g. target modulation), when they exist, because these other types of modulation act as a form of noise or "nuisance variability" that lowers d' (Pagan and Rust 2014b). Consequently, for a given value of single-neuron d', it remains ambiguous whether that value arose from a particular amount of visual modulation in the absence of other modulation types or by larger visual modulation in the presence of other modulation types, and this disambiguation has important consequences for comparing the magnitudes of visual modulation in our recorded V4 and IT data. To resolve this ambiguity, our measure applies an extension of an ANOVA, and like the ANOVA, parses a unit's

total response variance into that which can be attributed to modulation by each type of stimulus variable (e.g. changes in the visual image, changes in target identity, etc.), as well as their nonlinear interactions. We also apply a bias-correction procedure to correct for the over-estimation of these variances due to limited samples, developed and tested extensively in simulation (Pagan and Rust 2014b). Finally, because variance non-intuitively scales as the square of response changes (i.e. when firing rates double, variances quadruple), we calculate modulation in units of standard deviation, computed as the square root of the bias-corrected variance quantities. In sum, this measure of visual modulation quantifies the modulation in a unit's spike count that can be attributed to changes in the identity of the object in view, and it is computed separately for each of the 5 transformations.

For three of the five transformations ('left', 'small', 'up'), mean visual modulation was statistically indistinguishable between V4 and IT (Fig 6a-c). For one transformation ('big'; Fig 6d) mean visual modulation was larger in V4, but we retained this transformation for subsequent analyses because its incorporation reflected a worst-case scenario against the sampling problem of concern (i.e. one in which V4 has been inadequately sampled). In contrast, for the final transformation ('right'; Fig 6e), the V4 population had significantly lower performance than IT ($p < 1e10^{-5}$), and investigation of the recorded receptive field locations (Fig 4b) revealed that this was likely due to incomplete sampling at that location. As such, we disregarded this transformation from further analyses. Subsequent analyses are focused on the 4 of 5 transformations in which visual modulation, averaged across transformations, was not statistically distinguishable in V4 as compared to IT, either in the pooled data or in either monkey (Fig 6f; Monkey 1: V4 mean = 0.30, IT mean = 0.27, p = 0.07; Monkey 2: V4 mean = 0.18, IT mean = 0.19, p = 0.93). The fact that visual modulation is matched between V4 and IT across these four transformations suggests that the two populations can and should be compared with approximately matched numbers of units, consistent with previous reports (Rust and DiCarlo 2010).

Figure 6. *Comparison of visual modulation in V4 and IT.* Shown are distributions of visual modulation magnitudes across units, parsed by transformation for V4 (open bars, n = 650 units) and IT (gray, n = 204 units) and plotted on a log axis. Following a bias correction to remove the impact of trial variability, visual modulation was computed in units of standard deviation around each unit's grand mean spike count. The first bin includes units with negligible visual modulation (modulation < 0.001) and the broken axis indicates that these bars should extend to the proportions labeled just above. Means of each distribution, including units with negligible visual modulation, are indicated by arrows and values are indicated at the bottom of each panel. The p-values at the top of each panel were computed via a bootstrap significance test evaluating the probability that differences in the means between V4 and IT can be attributed to chance. **a-e)** Distributions parsed by transformation. Visual modulation corresponding to the transformation 'right' was higher in IT as compared to V4, due to incomplete sampling of receptive fields at this location (Fig 4b), and was thus disregarded from further analyses. **f)** Distributions of visual modulation, averaged for each unit across the transformations 'left', 'small', 'up', and 'big'.

A comparison of visual object invariance in V4 and IT

As depicted in Figure 2, information about object identity, across changes in identity-preserving transformations, is reported to be more accessible to a linear read-out in IT as compared to V4 (Rust and DiCarlo 2010). To determine whether this difference between V4 and IT was reflected during the IDMS task, we measured the ability of a 4-way linear object identity classifier, trained at each transformation, to generalize to other transformations. Specifically, "reference performance" was measured as cross-validated classifier performance when the training and testing trials came from the same transformation. "Generalization performance" was measured as cross-validated classifier performance when the testing trials came from the three transformations that were not used for training. To avoid confounding visual and target match modulation, each type of performance was computed separately for target matches and distractors (in all possible combinations) and then averaged (see Methods). Finally, "generalization capacity" was measured as the ratio of generalization over reference performance after subtracting the value expected by chance (where chance = 25%).

Fig 7a depicts how reference and generalization performance grew as a function of population size in each brain area. In V4, generalization performance remained modest across all population sizes whereas V4 reference performance grew at a faster rate. In IT, both reference and generalization performance grew at non-negligible rates. Fig 7b summarizes the results in the two brain areas by plotting the endpoints of the plots in Fig 7a. Generalization capacity, computed as the ratio of generalization over reference performance, was higher in IT as compared to V4 (V4 = 0.16; IT = 0.46; p < 0.001), consistent with IT reflecting a more linearly-separable object representation. This plot also reveals slightly lower reference performance in V4 for matched numbers of units (Fig 7b) despite the two populations reflecting matched average single-unit visual modulation (Fig 6f). We have determined that this small difference can be attributed to the slightly higher variance-to-mean ratio in V4 as compared to IT (reported above, mean Fano factor V4 = 1.56; mean Fano factor IT = 1.46), as opposed to other factors such how the information is tiled across the stimulus space or differences in task-relevant modulation (not shown).

To confirm that IT generalization capacity remained higher even under conditions in which more total visual information was available in V4, we also computed generalization capacity for the full V4 population (n = 650 units). As shown in Figure 7c, generalization capacity remained higher in IT even under these conditions (mean V4 = 0.20; mean IT = 0.47; p < 0.001). Higher generalization capacity also held for each of the transformations individually (Fig 7d; 'Big' p < 0.001; 'Left' p < 0.001; 'Small' p = 0.048; 'Up' p < 0.001).

Figure 7. *Comparison of visual object invariance across identity-preserving transformations in V4 versus IT.* **a)** Performance of V4 and IT on a 4-way linear read-out of object identity, assessed either with cross-validated trials of the same transformation ("Reference") or when asked to generalize to transformations not used for training ("Generalization"; see text). **b)** Reference and generalization performance for matched numbers of units (n = 204 for both V4 and IT populations), replotted from the endpoints in panel a. Generalization capacity was computed as the ratio of generalization over reference performance after subtracting the value expected by chance (where chance = 25%). **c)** Reference and generalization performance for the full recorded V4 population (n = 650 units) as compared to the full recorded IT population

replotted from panel b (n = 204 units). **d)** Generalization capacity computed for matched
numbers of units in V4 and IT (n = 204 units), applied to each transformation separately. Single
asterisks denote $p < 0.05$; double asterisks denote $p < 0.01$; triple asterisks denote $p < 0.001$. In
all panels, error bars (standard error) reflect the variability that can be attributed to the specific
subset of trials chosen for training and testing and, for subsets of units smaller than the full
population, the specific subset of units chosen.

886
887
888
In sum, the results presented thus far demonstrate that, consistent with earlier reports, V4 and
IT can be compared with approximately matched numbers of units, and that visual
representations of object identity are more accessible to a linear population read-out in IT during
the IDMS task. As explained above, the rationale behind this experiment included seemingly
optimizing the task for top-down integration preferentially in IT over V4 by exploiting differences
in how V4 and IT represent object identity invariant to identity-preserving transformations (Fig
2). The results presented thus far suggest that this goal was realized insofar as the visual
representations of object identity were in fact measurably different in V4 and IT during this task.
In question is whether these differences corresponded with differences in the amount and/or
format of non-visual, task-relevant information reflected in the two brain areas.

899
900
901   **Conceptualizing IDMS target match computation**

902
To interpret the different types of signals that might be reflected in V4 and IT during IDMS, it is
useful to conceptualize how target match signals – which reflect the solution to IDMS – might be
computed. When considered in terms of a single 4x4 "looking at" vs. "looking for" slice of the
experimental design matrix (Fig 3b), target match signals are reflected as diagonal structure (Fig
8a, right, 'Target match (four objects)'). In the most straightforward description of target match
computation, congruent 'visual' information (vertical structure) and 'target identity' information
(horizontal structure) combine in a nonlinear fashion to compute target match detectors that are
selective for one object presented as a target match ('Target match (one object)'). Finally, these
are pooled across the four different objects to create 'Four object target match detectors' that
respond whenever a target is in view (Fig 8a). Consequently, the class of proposals presented
in Fig 1a, where top-down modulation is integrated exclusively in V4, has at least two variants.
In the first, target match signals exist in V4 and arrive in IT via a feed-forward process (Fig 8b),
possibly with some linear pooling to produce target match invariance (across object identity). In
the second, target identity signals (as opposed to target match signals) are reflected in V4, and
IT target match signals are computed in IT via the nonlinear combination of these inputs (Fig
8c).

919
920
921
Figure 8. *Conceptualizing IDMS target match computation.* **a)** An idealized depiction of how
target match signals, which reflect the solution to the IDMS task, might be computed. For
simplicity, the computation is described for one 4x4 slice of the experimental design matrix,
which corresponds to viewing each of four objects ('Looking AT') in the context of each of four
objects as a target ('Looking FOR') at one transformation. In the first stage of this idealization of
target match computation, a unit reflecting visual information and a unit reflecting persistent
target identity information (i.e. working memory) are combined, and the result is passed through

a threshold. The resulting unit reflects target match information for one object. Next, four of these units (each with a different object preference) are linearly combined to produce a unit that signals whether a target match is present, regardless of the identity of the object. **b)** A variant of the class of "IT: Inherited" proposals (Fig 1a) in which target match information is computed in V4 and then fed forward to IT. **c)** A variant of the class of "IT: Inherited" proposals in which visual and target identity information are both present in V4 and then fed forward to IT, where they are combined to compute the target match signal. **d-e)** The response matrices corresponding to 3 example units from V4 and IT. Response matrices were plotted as the average firing rates across trials, and rescaled from the minimum (black) to maximum (white) response across all experimental conditions.

We found examples of nearly all of these types of idealized units in V4 and/or IT (Figures 8d-e). In both areas, we found 'purely visual' units that responded selectively to images but were not modulated by other factors, such as target identity or whether an image was presented as a target match (Fig 8d-e, 'Purely visual'). In contrast, one notable difference between V4 and IT was the existence of a handful of IT units (~10/204) that reflected the remarkable property of responding to nearly every image presented as a target match (every object at every transformation) but not when those same images were presented as distractors (Fig 8e, 'Target match (four object)'). We did not find any such units in V4. However, in both V4 and IT, we found units that responded preferentially to individual objects presented as target matches as compared to distractors (Fig 8d-e, 'Target match (one object)'). We note that while these illustrative examples were chosen because they reflect intuitive forms of pure selectivity, many (if not most) units tended to reflect less intuitive mixtures of visual and task-relevant modulation.

To more quantitatively compare the types of signals reflected in V4 and IT, we extended the procedure presented in Fig 6 to not only quantify 'visual' modulation (i.e. modulation that can be attributed to changes in the identity of the visual image), but also other types of non-overlapping modulations that could be attributed to: 'target identity' modulation - changes in the identity of a sought target; 'target match' modulation - changes in whether an image was a target match or a distractor; and 'residual' modulation - nonlinear interactions between visual and target identity that are not target match modulation (e.g. an enhanced response to a particular distractor condition). When considered in terms of a single 4x4 "looking at" vs. "looking for" slice of the experimental design matrix (Fig 3b), these modulations produce vertical, horizontal, diagonal, and off-diagonal structure, respectively (Fig 9a). Notably, this analysis defines target match modulation as a differential response to the same images presented as target matches versus distractors, or equivalently, diagonal structure in the transformation slices presented in Fig 9a. Consequently, units similar to both the 'target match (one object)' unit as well as the 'target match (four object)' unit (Fig 8d-e) reflect target match modulation, as both units have a diagonal component to their responses. What differentiates these two types of units is that the 'Target match (one object)' unit also reflects selectivity for image and target identity, which is reflected in this analysis as a mixture of target match, visual, and target identity modulation.

Figure 9. *Evolution of different types of single unit modulations in V4 and IT.* **a)** To illustrate the different types of task-relevant signals that could be present in V4 and IT, shown is a slice through the IDMS experimental design (Figure 3b), corresponding to one transformation. Shown

are visual modulations, which differentiate between different objects in view (vertical structure);
target identity modulations, which differentiate between different target objects (horizontal
structure); target match modulations, which differentiate between whether objects appear as a
target match versus a distractor (diagonal structure); and residual modulations, which
differentiate between any other types of conditions (e.g. a response to a particular distractor
condition such as looking for object 4 when looking at object 2). **b-e)** Modulations were
computed for each type of experimental parameter in units of the standard deviations around
each unit's grand mean spike count (see Results). In each panel, average modulation
magnitudes across units in V4 (n = 650) and IT (n = 204) shown on the left as a function of time
(ms after stimulus onset). Modulation magnitudes, computed in spike count bins 50 ms wide and
shifted by 10 ms, are plotted corresponding to the midpoint of each bin, and consequently, end
25 ms before the termination of the last bin. The bar plots show average signal magnitudes
quantified within broader spike counting windows indicated by the rectangles on the left (V4: 40-
210 ms, red rectangle; IT: 80-250 ms, gray rectangle). Modulation in broader bins can loosely
be envisioned as the integral of modulation in narrower bins, however, due to bias correction,
this is not exactly the case (see Methods). Single asterisks denote $p < 0.05$; double asterisks
denote $p < 0.01$; triple asterisks denote $p < 0.001$; 'ns' indicates $p > 0.05$. Error bars reflect the
standard error of modulation across units, computed via a bootstrap procedure.
996
To compare these different types of task-relevant signals between V4 and IT, we applied the
analysis to 50 ms spike count windows positioned at sliding locations relative to stimulus onset,
as well as the same counting windows described for Fig 6 (170 ms; V4: 40-210 ms; IT: 80-250
ms; Fig 9b-e). As expected, visual modulation did not exist before stimulus onset, and visual
signals arrived in V4 ~ 40 ms earlier than in IT in both animals (Fig 9b). In contrast, modulations
reflecting information about whether an image was a target match or a distractor ('target match'
modulation) were considerably smaller in V4 as compared to IT in both animals (Fig 9c; monkey
1 $p < 0.001$; monkey 2 $p < 0.001$). In monkey 1, V4 target match modulations increased
throughout the viewing period, and V4 reached levels that were similar to those found in IT by
~200 ms, but this rise occurred with a delay in V4 relative to IT (Fig 9c, top). This late rise was
not replicated in monkey 2, where target match modulations were smaller in V4 as compared to
IT throughout the viewing period (Fig 9c, bottom).
1009
Modulations reflecting information about the identity of the target ('target identity' modulation)
were present in both V4 and IT before stimulus onset (Fig 9d), consistent with persistent
working memory signals in both brain areas. These persistent signals were stronger in IT as
compared to V4 in monkey 1 ($p < 0.001$) but comparable in size between V4 and IT in monkey 2
($p = 0.19$). Lastly, we found that in both V4 and IT, residual modulation was small relative to the
other types of modulations (Fig 9e). Residual modulation was larger in IT than V4 in both
monkeys (monkey 1 $p = 0.04$, monkey 2 $p = 0.005$). To summarize these results, we found that
in both monkeys, visual modulation was matched between V4 and IT whereas target match
signals were weaker in V4, as were residual signals. We also found persistent target identity
signals that were reflected in both areas before and throughout the stimulus-evoked period.
1020
As a complementary analysis, we also quantified the total amount of non-visual, 'cognitive'
modulation (combined target match, target identity, and residual modulation), and compared it to
the evolution of the visual modulation (Fig 10). In both brain areas, total cognitive modulation
was considerable throughout the analysis window. During the latency-corrected stimulus-evoked
period, cognitive modulations were 34% and 77% the size of the visual modulations in V4 and
IT, respectively. These results demonstrate that considerable non-visual, task-relevant

modulations exist in both brain areas, and they also suggest that these are smaller in V4 as
compared to IT.
1029
1030
1031
Figure 10. *Single unit cognitive modulations in V4 and IT cortex.* **a-b)** Cognitive modulations
(V4: light red; IT: light gray) were computed as the sum of target identity, target match, and
residual modulations, and are shown alongside visual modulations (V4: dark red; IT: dark gray).
Mean modulation magnitudes are computed in the same manner and shown with the same
conventions as Fig 9. Labels in the bar plots above the cognitive modulation magnitudes
indicate the proportional size of cognitive relative to visual modulations in each brain area.
1038
1039
1040 **Could target match signals arrive in IT from V4 under the assumption of uniform**
1041 **sampling?**
1042
The data presented above in Fig 9 demonstrate that there were differences between V4 and IT
in the magnitude of target match modulation when considered on average, across all units and
all transformations. However, due to differences in the nature of the representation between
these two brain areas (such as smaller V4 receptive fields), it could be the case that for any
given unit, only a limited subset of the transformations are encoded and there for relevant for
comparisons between the two brain areas. Below we compare the amount of target match
information in V4 versus IT in a manner that takes these potential differences into account.
Specifically, we compute the population performance of a weighted linear read-out of each
population, where the weights are assigned to be proportional to the amount of target match
information reflected in a unit's responses and the weights are determined separately for each
transformation. This process ensures that a unit's responses are not considered for
transformations at which that unit was not informative.
1055
Target match signals, reflected as diagonal matrix structure (e.g. target match units for one
object or across multiple objects; Fig 8a) translate into a linearly separable representation of the
same images presented as target matches as compared to distractors (Fig 11a). To quantify the
amount of linearly separable target match information in V4 and IT, we computed the cross-
validated performance of a weighted linear classifier to perform this 2-way classification at each
transformation separately, and we then averaged population performance across the different
transformations (Fig 11b, see Methods). The specific linear read-out we used, a Fisher Linear
Discriminant, weights each unit proportional to its d' for this task, adjusted for any correlations
that exist between units (see Methods). To determine whether weighted, uniform sampling of V4
could account for target match information in IT, we randomly selected IT units up to the total
numbers of units that we recorded (Fig 11c, gray), and compared this to a random selection of
V4 units for matched sized populations (and thus always a subset of the V4 data Fig 11c, red).
As expected based on the results presented in Fig 7c, cross-validated population performance
was higher than chance in V4, but was significantly higher in IT as compared to V4 in both
monkeys (Fig 11c, gray versus red). We also compared population performance when all V4
units were included for each monkey (~3x V4 as compared to IT; Fig 11c, red) and found that
performance in V4 remained considerably lower than IT. These results suggest that IT target
match information is not directly inherited from V4 under the assumption of a uniform sampling
of V4 by IT.
1075

Figure 11. *A comparison of linearly separable target match information in V4 and IT.* **a-b)** The IDMS task can be envisioned as a two-way classification of the same images presented as target matches versus as distractors. Shown are cartoon depictions where each point depicts a hypothetical population response for a population of two neurons on a single trial, and clusters of points depict the dispersion of responses across repeated trials for the same condition. Included are the hypothetical responses to the same images presented as target matches (black) and as distractors (gray). The dotted line depicts a hypothetical linear decision boundary. **a)** A schematic of two neurons that each respond to one object as a target match. In this scenario, target matches and distractors are linearly separable. **b)** A schematic of the IDMS task, where four images must be classified as target matches as compared to distractors, applied to a linearly separable representation. **c)** Performance of a linear classifier trained to classify whether an object was a target match or a distractor, invariant of the object's identity (at one transformation). Performance was assessed at each identity-preserving transformation ('Big', 'Left', 'Small', 'Up'), and then averaged. Performance was higher in IT (gray) than in V4, both when V4 units were sampled uniformly from the full population (red), when V4 units were sampled by choosing the best possible V4 units based on the training data (cyan); monkey 1: n = 108 units, monkey 2: n = 96 units, and when all V4 units were included for each monkey (red); monkey 1: n = 382, monkey 2: n = 268. Error bars (standard error) reflect the variability that can be attributed to the specific subset of trials chosen for training and testing, and, for subsets of units smaller than the full population, the specific subset of units chosen. Dashed line indicates chance performance.

Could target match signals arrive in IT via input from the "best" V4 neurons?

While the results presented above suggest that target match signals are unlikely to arrive in IT from V4 under the assumption of uniform sampling, evidence from other studies suggests that the brain can learn to preferentially read-out the subset of neurons that carry the most task-relevant information with extensive training (Law and Gold 2009) and the monkeys involved in these experiments were trained extensively. Could a version of the feed-forward proposal in which IT preferentially samples the "best" V4 neurons account for our data? To allow us to address this question, we sampled 3-fold more units in V4 as compared to IT, consistent with anatomical estimates of the ratios of neurons between the two brain areas (DiCarlo et al. 2012).

To assess whether a "best" sampling description of V4 by IT could account for our data, we recomputed performance for V4 and IT populations that were matched in size, but when only the N top-ranked V4 units were included for different sized N. Notably, this analysis differs from the analysis presented above in which all V4 units were included insofar as the computation and assignment of weights based on limited samples is a process that contains some noise, and in scenarios where only a subset of units carry a signal, performance is expected to increase until all signal-carrying units are included, but then can fall slightly with the inclusion of units that do not reflect any signal. In this analysis, units were ranked based on the training data before computing cross-validated performance. We found that V4 performance was slightly higher for the best units as compared to randomly selected units (Fig 11c, cyan vs. red), however, performance for the best V4 units remained lower than IT performance in both monkeys (Fig 11c, cyan vs. gray, p<0.001). These results suggest that during IDMS, IT target match modulation cannot be accounted for via feed-forward propagation of this modulation from V4, even if IT were to sample from the "best" V4 subset (Fig 8b).

Could target match signals arrive in IT via nonlinear combinations of input from V4?

To evaluate the variant of the matched proposal in which IT target match signals are computed via nonlinear combinations of inputs arriving from V4 (Fig 8c), we quantified the "total" target match information in each brain area, regardless of its format. Specifically, combinations of visual and target identity signals (reflected in different units) map to target match information present in a nonlinearly separable format (Fig 12a) whereas target match signals map to target match information that is linear (Fig 11a). Here we employ a measure of total target match information quantifies information regardless of its format (both linear and nonlinear).

Total target match information was measured as cross-validated performance on the same 2-way classification as presented in Fig 9, but for a maximum likelihood (as opposed to linear) classifier (see Methods). This nonlinear classifier assesses the total amount of target match information regardless of its format (combined linear and nonlinear). Cross-validated population performance was higher than chance in V4 (Fig 12b, red; in both monkeys, compared at n = 108 in monkey 1 and n = 96 in monkey 2, p<0.001), but was also higher in IT as compared to V4 (Fig 12b, gray; in both monkeys, compared at n = 108 in monkey 1, p <0.001 and n = 96 in monkey 2, p=0.009).

Taken together, these results rule out feed-forward accounts of processing from V4 to IT, including descriptions in which V4 preferentially samples from the best V4 units (Fig 11c), as well as descriptions that allow for nonlinear IT computation (Fig 12). These results thus suggest that IT target match information is not exclusively inherited via feed-forward projections arriving from V4 (Fig 1a; Fig 8b-c), but rather, at least some component of top-down information must be integrated directly in IT itself during the IDMS task (Fig 1b).

Figure 12. *A comparison of total (linear and nonlinear) target match information in V4 and IT.* **a)** A schematic of two neurons, one 'visual' neuron and one 'target identity' neuron. In this scenario, target match information exists, but is present in a non-linearly separable format. **b)** A schematic of the IDMS task where four images must be classified as target matches versus distractors, applied to a nonlinearly separable representation. **c)** Performance of a nonlinear, maximum likelihood classifier trained to classify between whether an object was a target match or a distractor, invariant of object identity. Performance was assessed at each identity-preserving transformation, and then averaged. Error bars (standard error) reflect the variability that can be attributed to the specific subset of trials chosen for training and testing, and, for subsets of units smaller than the full population, the specific subset of units chosen. Dashed line indicates chance performance.

The relationship between the visually-evoked response and target match modulation in individual units

The results presented above establish that during the IDMS task, visual information about object identity is reflected in a more linear manner in IT as compared to V4 (Fig 7) and this coincides with more target match modulation in IT (Figs 11,12). How does the relationship between the

visually-evoked response and the magnitude of target match modulation manifest in the responses of individual units in each brain area? Conceptually, the increase in target match modulation in IT as compared to V4 could be reflected in a similar manner in the two brain areas, such as multiplicative rescaling, but with a larger multiplicative factor in IT. In this scenario, both brain areas would exhibit tuning for target match modulation that is matched in bandwidth to the visually-evoked tuning for images. Alternatively, increases in target match modulation in IT over V4 could result from similar target match modulation magnitudes for each image at which it appears, but with broader tuning across images in IT. We note that these two possibilities are not mutually exclusive.

To explore these issues, we computed the magnitude of target match modulation as a function of the effectiveness of each image at driving individual units to fire. Specifically, we ranked the responses of each unit to the 16 images (4 objects * 4 transformations; averaged across target matches and distractors), and then examined the responses to target matches and distractors separately, after averaging across all units (Fig 13a). Shown are results computed after subtracting the baseline firing rate from each unit's responses, where negative values correspond to responses below baseline. In both V4 and IT, target match modulation for the highest ranked images was reflected as target match enhancement, and both brain areas exhibited weak target match suppression for the least effective images (Fig 13a). The net impact of target match modulation (averaged across all ranks) was target match enhancement in both brain areas, with stronger net modulation in IT (the difference in the average response to target matches and distractors, averaged across all ranks, divided by the average response to target matches: V4 = +0.07; IT = +0.46; Fig 13a).

Next we computed tuning bandwidths separately for the visually-evoked response and for target match enhancement. To determine the bandwidth of the visually-evoked response, we determined the number of image ranks with responses significantly above the baseline response (for data averaged across target matches and distractors; Wilcoxon rank sum test; criterion $p = 0.05$). We found the visually-evoked bandwidths to be slightly broader in V4 (bandwidth= 14 images; Fig 13a left, black arrow) as compared to IT (bandwidth = 11 images; Fig 13a right, black arrow). To determine the bandwidths of target match enhancement, we computed the number of images for which the responses to target matches were significantly higher than the responses to distractors (Wilcoxon rank sum text; criterion $p = 0.05$). In V4, target match enhancement was more narrowly tuned than the visually-evoked response (target match enhancement bandwidth = 5 images; visually-evoked response bandwidth = 14 images; Fig 13a left, cyan versus black arrows). In IT, these bandwidths were more similar (target match enhancement bandwidth = 9 images; visually-evoked response bandwidth = 11 images; Fig 13a, right; cyan versus black arrows).

To determine whether the observed differences in target match bandwidths between V4 and IT followed simply from target match modulation that was larger in IT, we plotted the responses to target matches against the responses to distractors, similar to a quantile-quantitle or Q-Q plot. In these plots, rescaling the responses by different multiplicative factors but with a fixed bandwidth amounts to changing the slope of the lines around a fixed pivot point (Fig 13b, top) whereas changing the bandwidths results in different points of intersection with the unity line (Fig 13b, bottom). Our data were not well-described as a change in slope around a fixed pivot point, but rather by more narrowly tuned target match enhancement in V4 (Fig 13c). Notably, this narrower bandwidth cannot be explained by a more narrowly tuned visually-evoked response in V4, because the visually-evoked response was slightly broader in V4 as compared

1223   to IT (as described above, Fig 13a). These results suggest that increased target match
1224   modulation in IT over V4 results from a combination of the two scenarios presented above: it is
1225   both larger for the image ranks at which it appears and it is more broadly tuned across images.
1226
The 16 images included in this analysis differed from one another across changes in both object
identity as well as object transformation. To determine whether broader target match
enhancement in IT as compared to V4 depended differentially on these two factors, we
performed the same analysis by ranking each unit per transformation (after averaging across
object identity; Fig 13d) or ranking by object identity (after averaging across transformations; Fig
13e). Across transformations, the bandwidth of target match enhancement was considerably
narrower in V4 (1 transformation; Fig 13d left, cyan arrow) as compared to IT (4
transformations; Fig 13d right, cyan arrow). Once again, this difference could not be accounted
for by a difference in the bandwidth of the visually-evoked response, as this was broader in V4
(4 transformations; Fig 13d left; black arrow) than IT (3 transformations; Fig 13d right; black
arrow). Across object identity, the bandwidth of target match enhancement was slightly narrower
in V4 (2 objects; Fig 13e left, cyan arrow) as compared to IT (3 objects; Fig 13e right, cyan
arrow) whereas the visually-evoked response remained slightly broader in V4 (4 objects; Fig
13e left, black arrow) as compared to IT (3 objects; Fig 13e right, black arrow).
1241
Together, these results suggest that the increase in target match modulation in IT as compared
to V4 can be attributed to both an increase in the magnitude of target match modulation for the
images that are most effective at driving individual units to fire as well as an increase in
bandwidth over the number of images that have this modulation. These IT bandwidth increases,
in turn, appear to follow from broader tuning of target match enhancement across both identity-
preserving transformations as well as object identity, with a larger influence of the former as
compared to the latter.
1249
1250
1251
Figure 13. *Comparison of the visually-evoked response and target match modulation in*
individual units. **a)** The spike count responses to target matches (V4: left, red; IT: right, dark
gray) and distractors (V4: left, pink; IT: right, light gray) to the 16 different images that made it
through the screen presented in Fig 6, ranked by image preference. After subtracting the
baseline responses (computed 170 ms before the onset of the first image in each trial), the
responses of each unit to each image were ranked by their average response across target
matches and distractors. Shown are means and standard errors across all units, after sorting
each unit by image rank (V4: n=650; IT: n=204). The bandwidth of the visually-evoked response
(V_{bw}; black arrows) was computed as the number of images for which the response (averaged
across targets and distractors) was significantly larger than baseline (Wilcoxon rank sum test;
criterion p = 0.05). Target match bandwidth (TM_{bw}; cyan arrows) was computed as the number
of images for which the target match response was significantly higher than the distractor
response (Wilcoxon rank sum test; criterion p = 0.05). **b)** Schematics showing the hypothetical
responses to target matches plotted against hypothetical responses to distractors, similar to a
quantile-quantile (Q-Q) plot. Top: shown are two hypothetical populations whose responses are
both multiplicatively rescaled but with different factors. This manifests in these plots as changes
in the slope of these lines around a fixed pivot point (white dot). Bottom: shown are two
hypothetical populations whose responses differ by both their magnitudes of target match
modulation as well as the bandwidth of this tuning; changes in bandwidth manifest as different
points of intersection with the unity line (red and gray large dots). **c)** V4 and IT spike count

responses, plotted as described for panel b. Points of intersection with the unity line are
indicated with large red and gray dots and for comparison, the cyan arrows from panel a are
included. **d)** Responses to ranked objects (averaged across transformation identity), plotted with
the same conventions as panel a. **e)** Responses to ranked images (averaged across object
identity), plotted with the same conventions as panel a.

DISCUSSION

Finding sought objects requires the brain to compare visual information about the objects in view with information about the currently sought target to compute a signal that reports when a target match has been found. During object search, information about the identity of a sought target and/or whether it is a target match is thought to be fed-back to mid to higher stages of the ventral visual pathway, including V4 and IT, but the specific path this information takes is unclear. In this study, we sought to differentiate between scenarios in which top-down information is integrated directly in IT (Fig 1b) versus those in which it is integrated in V4 and arrives in IT via feed-forward propagation (Fig 1a). We evaluated a number of feed-forward descriptions between V4 and IT, and found none of them could account for the amount of non-visual, task-relevant information present in IT. These included a model in which IT uniformly samples target match signals from V4 (Fig 12, red), a model in which IT preferentially samples target match signals from the best V4 units (Fig 12, cyan), and a model that allowed for IT nonlinear processing of inputs arriving from V4 (Fig 13). Together, these results suggest that during IDMS, top-down, task-specific signals in IT are not exclusively inherited from V4 but rather are integrated within IT, at least in part.

We found non-visual, task-specific signals to be sizeable in V4 (~40% of the size of visual modulation), consistent with many other reports (Moran and Desimone 1985; Haenny et al. 1988; Motter 1994b; Motter 1994a; Luck et al. 1997; McAdams and Maunsell 1999; McAdams and Maunsell 2000; Chelazzi et al. 2001; Ogawa and Komatsu 2004; Bichot et al. 2005; Hayden and Gallant 2005; Mirabella et al. 2007; Cohen and Maunsell 2009; Kosai et al. 2014). At the same time, we also found that non-visual, task-specific modulations to be even larger in IT (~80% the size of visual modulation). In a previous study, during a visual target search task in which monkeys made a saccade to a target match following the presentation of a sample image, non-visual, task-specific signals were reported to be more similar in V4 and IT (63% and 70% of the visually-evoked response in V4 and IT, respectively; Chelazzi et al. 1998; Chelazzi et al. 2001). One notable difference between our study and this earlier work is that our study compared V4 and IT during a version of the delayed-match-to-sample task in which sought target objects could appear at different positions, sizes and background contexts. The fact that top-down, task-specific signals were considerably larger in IT versus V4 in our task may follow from the fact that IT contains a more explicit, linear representation of object identity across these transformations than V4 (reviewed by DiCarlo et al. 2012). Consequently, top-down modulation may be targeted directly to IT in situations that require an invariant object representation whereas the brain might target the pathway differently when tasks have different computational requirements. For example, because V4 receptive fields are smaller and retinotopically organized, V4 might serve as the primary locus for the integration of top-down signals for tasks that require spatial specificity, such as covert spatial attention tasks, and in these tasks little top-down integration might occur in IT (Moran and Desimone 1985). Only one earlier study has reported on the responses of IT neurons in the context of a DMS task in which, objects could appear at different identity-preserving transformations (Leuschow et al. 1994), but this study did not measure signals in V4.

Our results, which demonstrate larger non-visual, task-relevant modulations in IT as compared to V4, are consistent with more general interpretations that the magnitudes of top-down modulation exist in a gradient-like fashion hierarchically along the ventral visual pathway (reviewed by Noudoost et al. 2010). As described above, such gradients are consistent both with the integration of top-down modulation at multiple stages of the pathway (Fig 1a) as well as

integration at a single locus, followed by feedback within the pathway itself (Fig 1b, right). One
study (Buffalo et al. 2010) provided evidence supporting the latter description in V1, V2 and V4
in the form of noting that not only the magnitude of modulation was greater in higher visual
areas, but it also arrived earlier, consistent with a feed-back description. In our data, this issue
was ambiguous: we found that in one monkey, the arrival of target match modulation was
delayed in V4 as compared to IT (Fig 10c, Monkey 1) whereas in the other monkey, target
match modulation was small throughout the viewing period (Figure 10c, Monkey 2).
1339
In an earlier series of reports, we compared the responses of IT and its projection area,
perirhinal cortex, during a more classic version of the delayed-match-to-sample task (that did
not incorporate variation in the objects' transformations; Pagan et al. 2013; Pagan and Rust
2014a; Pagan et al. 2016). We found that the responses of perirhinal cortex were well-described
by a model in which top-down, task-relevant signals were integrated within or before IT
consistent with a feed-forward process between IT and perirhinal cortex. The results presented
here extend this understanding to suggest that the locus of top-down integration during DMS
search tasks is unlikely to exclusively be V4, and that some amount of top-down integration is
likely to happen directly within IT itself.
1349
Computing a target match signal requires the combination of the visual representation of the
currently viewed scene with a remembered representation of the sought target (e.g. Fig 9a). In
an analysis of the same IT data presented here, we found that the IT population misclassified
trials on which the monkeys made errors, supporting notions that the IT target match signal is in
fact related to the neural signals used to make target match behavioral judgments (Roth and
Rust 2018). The additional target match information present in IT that is not also present in V4
could reflect the implementation of this comparison in IT itself, or alternatively, the comparison
might be implemented in a higher order brain area and fed-back to IT cortex. The timing of the
arrival of this signal in IT (which peaks at ~150 ms; Fig 10c) relative to the monkeys' median
reaction times (~335 ms; Fig 3e), does not rule out the former scenario, but with our data we
cannot definitively distinguish between these alternatives. Additionally, in this study monkeys
were trained extensively on the images used in these experiments and future experiments will
be required to address the degree to which these results hold under more everyday conditions
in which monkeys are viewing images and objects for the first time.
1364
In this study, the IDMS task was implemented in short blocks with a fixed target such that a cue
image did not need to appear at the beginning of each trial. This design was inspired by studies
reporting that when a cue image is presented shortly before a target match (e.g. in the same
trial), active target match modulation intermingles with passive, repetition suppression (Miller
and Desimone 1994), which we have also found to be true (Pagan et al. 2013). For example,
whereas approximately balanced numbers of IT units reflect net target match enhancement
versus target match suppression in a classic DMS design (Pagan et al. 2013), IT units nearly
universally reflect target match enhancement during the IDMS task (Roth and Rust 2018). This
distinction is important for this study, as our goal was to systematically compare the magnitudes
of top-down modulation in V4 and IT whereas repetition suppression is likely to be a largely
feed-forward process. At the same time, the block design we employed here also imposes some
drawbacks, including less frequent changes of the target identity, and thus less frequent
changes of the issuance of new top-down information. Future experiments will be required to
assess how these results compare in the context of more dynamic and more realistic object
search conditions (where presumably one ceases to look for the same target upon finding it).
1380

References:

Bichot, N. P., A. F. Rossi and R. Desimone (2005) Parallel and serial neural mechanisms for visual search in macaque area V4. Science 308(5721): 529-534.

Buffalo, E. A., P. Fries, R. Landman, H. Liang and R. Desimone (2010) A backward progression of attentional effects in the ventral stream. Proc Natl Acad Sci U S A 107(1): 361-365.

Chelazzi, L., J. Duncan, E. K. Miller and R. Desimone (1998) Responses of neurons in inferior temporal cortex during memory-guided visual search. J. Neurophysiology 80: 2918-2940.

Chelazzi, L., E. K. Miller, J. Duncan and R. Desimone (1993) A neural basis for visual search in inferior temporal cortex. Nature 363: 345-347.

Chelazzi, L., E. K. Miller, J. Duncan and R. Desimone (2001) Responses of neurons in macaque area V4 during memory-guided visual search. Cereb Cortex 11(8): 761-772.

Cohen, M. R. and J. H. Maunsell (2009) Attention improves performance primarily by reducing interneuronal correlations. Nat Neurosci 12(12): 1594-1600.

Cohen, M. R. and J. H. Maunsell (2011) Using neuronal populations to study the mechanisms underlying spatial and feature attention. Neuron 70(6): 1192-1204.

Desimone, R. and S. J. Schein (1987) Visual properties of neurons in area V4 of the macaque: sensitivity to stimulus form. J Neurophysiol 57(3): 835-868.

DiCarlo, J. J., D. Zoccolan and N. C. Rust (2012) How does the brain solve visual object recognition? Neuron 73(3): 415-434.

Eskandar, E. N., B. J. Richmond and L. M. Optican (1992) Role of inferior temporal neurons in visual memory I. Temporal encoding of information about visual images, recalled images, and behavioral context. Journal of Neurophysiology 68: 1277-1295.

Felleman, D. J. and D. C. Van Essen (1991) Distributed hierarchical processing in the primate cerebral cortex. Cereb Cortex 1(1): 1-47.

Gattass, R., A. P. Sousa and C. G. Gross (1988) Visuotopic organization and extent of V3 and V4 of the macaque. J Neurosci 8(6): 1831-1845.

Gibson, J. R. and J. H. R. Maunsell (1997) The sensory modality specificity of neural activity
related to memory in visual cortex. Journal of Neurophysiology 78: 1263-1275.

Haenny, P. E., J. H. Maunsell and P. H. Schiller (1988) State dependent activity in monkey
visual cortex. II. Retinal and extraretinal factors in V4. Exp Brain Res 69(2): 245-259.

Hayden, B. Y. and J. L. Gallant (2005) Time course of attention reveals different mechanisms
for spatial and feature-based attention in area V4. Neuron 47(5): 637-643.

Hung, C. P., G. Kreiman, T. Poggio and J. J. DiCarlo (2005) Fast readout of object identity from
macaque inferior temporal cortex. Science 310(5749): 863-866.

Ito, M., H. Tamura, I. Fujita and K. Tanaka (1995) Size and position invariance of neuronal
responses in monkey inferotemporal cortex. J Neurophysiol 73(1): 218-226.

Kosai, Y., Y. El-Shamayleh, A. M. Fyall and A. Pasupathy (2014) The role of visual area V4 in
the discrimination of partially occluded shapes. J Neurosci 34(25): 8570-8584.

Law, C. T. and J. I. Gold (2009) Reinforcement learning can account for associative and
perceptual learning on a visual-decision task. Nat Neurosci 12(5): 655-663.

Leuschow, A., E. K. Miller and R. Desimone (1994) Inferior temporal mechanisms for invariant
object recognition. Cerebral Cortex 5: 523-531.

Li, N., D. D. Cox, D. Zoccolan and J. J. DiCarlo (2009) What response properties do individual
neurons need to underlie position and clutter "invariant" object recognition? J Neurophysiol
102(1): 360-376.

Luck, S. J., L. Chelazzi, S. A. Hillyard and R. Desimone (1997) Neural mechanisms of spatial
selective attention in areas V1, V2, and V4 of macaque visual cortex. J Neurophysiol 77(1): 24-
42.

Maunsell, J. H., G. Sclar, T. A. Nealey and D. D. DePriest (1991) Extraretinal representations in
area V4 in the macaque monkey. Vis Neurosci 7(6): 561-573.

Maunsell, J. H. and S. Treue (2006) Feature-based attention in visual cortex. Trends Neurosci
29(6): 317-322.

McAdams, C. J. and J. H. Maunsell (1999) Effects of attention on orientation-tuning functions of
single neurons in macaque cortical area V4. J Neurosci 19(1): 431-441.

McAdams, C. J. and J. H. Maunsell (2000) Attention to both space and feature modulates
neuronal responses in macaque area V4. J Neurophysiol 83(3): 1751-1755.

Miller, E. K. and R. Desimone (1994) Parallel neuronal mechanisms for short-term memory.
Science 263(5146): 520-522.

Mirabella, G., G. Bertini, I. Samengo, B. E. Kilavik, D. Frilli, C. Della Libera and L. Chelazzi
(2007) Neurons in area V4 of the macaque translate attended visual features into behaviorally
relevant categories. Neuron 54(2): 303-318.

Moran, J. and R. Desimone (1985) Selective attention gates visual processing in the extrastriate
cortex. Science 229(4715): 782-784.

Motter, B. C. (1994a) Neural correlates of attentive selection for color or luminance in
extrastriate area V4. J Neurosci 14(4): 2178-2189.

Motter, B. C. (1994b) Neural correlates of feature selective memory and pop-out in extrastriate
area V4. J Neurosci 14(4): 2190-2199.

Noudoost, B., M. H. Chang, N. A. Steinmetz and T. Moore (2010) Top-down control of visual
attention. Curr Opin Neurobiol 20(2): 183-190.

Ogawa, T. and H. Komatsu (2004) Target selection in area V4 during a multidimensional visual
search task. J Neurosci 24(28): 6371-6382.

Op De Beeck, H. and R. Vogels (2000) Spatial sensitivity of macaque inferior temporal neurons.
J Comp Neurol 426(4): 505-518.

Pagan, M. and N. C. Rust (2014a) Dynamic target match signals in perirhinal cortex can be
explained by instantaneous computations that act on dynamic input from inferotemporal cortex.
J Neurosci 34(33): 11067-11084.

Pagan, M. and N. C. Rust (2014b) Quantifying the signals contained in heterogeneous neural
responses and determining their relationships with task performance. J Neurophysiol 112(6):
1584-1598.

Pagan, M., E. P. Simoncelli and N. C. Rust (2016) Neural Quadratic Discriminant Analysis:
Nonlinear Decoding with V1-Like Computation. Neural Comput: 1-29.

Pagan, M., L. S. Urban, M. P. Wohl and N. C. Rust (2013) Signals in inferotemporal and
perirhinal cortex suggest an untangling of visual target information. Nat Neurosci 16(8): 1132-
1139.

Roth, N. and N. C. Rust (2018) Inferotemporal cortex multiplexes behaviorally-relevant target
match signals and visual representations in a manner that minimizes their interference. PLoS
ONE In press.

Rust, N. C. and J. J. DiCarlo (2010) Selectivity and tolerance ("invariance") both increase as
visual information propagates from cortical area V4 to IT. J Neurosci 30(39): 12978-12995.

Rust, N. C. and J. J. DiCarlo (2012) Balanced increases in selectivity and tolerance produce
constant sparseness along the ventral visual stream. J Neurosci 32(30): 10170-10182.

1473

Figure 1

Figure 2

a Cue trial: Banana block

800 ms   400 ms

Test trial: 1-7 distractors

distractor   distractor   target match

400 ms   400 ms   400 ms

b Target matches   Distractors

Looking FOR
1
2
3
4

Looking AT
1 2 3 4

Transformation
1 2 3 4 5

c Target matches:

Object 1

Distractors:

Object 2

Object 3

Object 4

up   left   right   big   small

d

Monkey 1

Performance
100
90
80

1 2 3 4 5 6 7
Number of
distractors shown

Monkey 2
100

97.5

95
1 2 3 4 5 6 7
Number of
distractors shown

e

Monkey 1
x̄ = 311 ms

Proportion
0.1
0

200   400   600
Time after stimulus
onset (ms)

Monkey 2
x̄ = 363 ms

0.1

0
200   400   600
Time after stimulus
onset (ms)

Figure 3

Figure 4

Figure 5

Figure 6

Figure 7

Figure 8

Figure 9

Figure 10

Figure 11

Figure 12

Figure 13