METHOD

CellFishing.jl: an ultrafast and scalable cell search method for single-cell RNA-sequencing

Kenta Sato[1,2*], Koki Tsuyuzaki[2], Kentaro Shimizu[1] and Itoshi Nikaido[2,3]

Abstract

Recent technical improvements in single-cell RNA sequencing (scRNA-seq) have enabled massively parallel profiling of transcriptomes, thereby promiting large-scale studies encompassing a wide range of cell types of multicellular organisms. With this background, we propose CellFishing.jl, a new method for searching atlas-scale data sets for similar cells with high accuracy and throughput. Using multiple scRNA-seq data sets, we validate that our method demonstrates comparable accuracy to and is markedly faster than the state-of-the-art software. Moreover, CellFishing.jl is scalable to more than one million cells, and the throughput of the search is approximately 1,350 cells per second (i.e., 0.74 ms per cell).

Keywords: scRNA-seq; Cell searching; Cell typing; Locality-sensitive hashing

Background

The development of high-throughput single-cell RNA sequencing (scRNA-seq) technology for the past several years has enabled massively parallel profiling of transcriptome expressions at the single-cell level. In contrast to traditional RNA sequencing methods that profile the average of bulk samples, scRNA-seq has the potential to reveal heterogeneity within phenotypes of individual cells as it can distinguish the transcriptome expression of each cell by attaching a distinct cellular barcode [1, 2]. In addition, several protocols have been developed that utilize unique molecular identifiers (UMIs) to more accurately quantify expression by removing duplicated counts resulting from the amplification of molecules [3–8]. The advent of library preparation for multiplexed sequencing with cellular barcoding and the refinement of cDNA amplification method with UMIs lead to a higher throughput and more reliable quantification of single-cell expression profiles.

These technologies have opened the door to research that comprehensively sequences and annotates massive numbers of cells to create a cell atlas for organs or multicellular organisms. Shekhar *et al.* [9] sequenced and performed unsupervised classification of 25,000 mouse retinal bipolar cells and identified novel cell types and marker genes, suggesting that sequencing a large number of cells is an essential factor for detecting underrepresented cell types. Similarly, Plass *et al.* [10] sequenced more than 20,000 planarian cells and rendered a single lineage tree representing continuous differentiation. We also see collaborative efforts to create a comprehensive catalog covering all cells types composing an organism, such as the Human Cell Atlas [11] and the Tabula Muris [12] project. This trend of sequencing higher numbers of cells is expected to continue until a complete list of cell types is generated.

Emergence of these comprehensive single-cell sequencing studies shows a pressing demand for software to find similar cells by comparing their transcriptome expression patterns. Since discrete cell annotations are not always available or are even impossible to generate due to continuous cell state dynamics, software for cell-level searching is useful for comparative analysis. However, finding similar cells based on their transcriptome expression profiles is computationally challenging due to the unprecedented numbers of genes and cells. Recently, Kiselev *et al.* [13] developed a software package and web service named scmap to perform an approximate nearest neighbor search of cells using a product quantizer [14]. The scmap package contains two variations: scmap-cluster and scmap-cell. Scmap-cluster can be used to search for cell clusters that are defined by discrete cluster labels and hence requires cluster annotations in addition to expression profiles of reference cells. On the contrary, scmap-cell can be used to directly find similar cells only from their expression profiles and is applicable to scRNA-seq data without requiring cluster annotations for cells. The authors of scmap-cell claim that creating a search index is more rapid than employing machine-learning methods.

*Correspondence: bicycle1885@gmail.com
[1]Department of Biotechnology, Graduate School of Agricultural and Life Sciences, The University of Tokyo, Bunkyo-ku, 113-8657, Tokyo, Japan
Full list of author information is available at the end of the article

However, the scalability of scmap-cell is limited and is not applicable to extremely large data sets. Srivastava *et al.* [15] have also developed a web service named CellAtlasSearch that searches existing scRNA-seq experiments using locality-sensitive hashing (LSH) and graphical processing units (GPUs) to accelerate the search. In LSH, expression profiles are hashed into bit vectors, and their similarities are estimated from the Hamming distance between bit vectors calculated by LSH [16]. However, it requires GPUs to extract maximum performance, and its implementation details are neither openly accessible nor well-described in their paper.

In this paper, we present CellFishing.jl (**cell fi**nder via ha**shing**), a novel software package used to find similar cells based on their expression patterns with high accuracy and throughput. CellFishing.jl employs LSH, like CellAtlasSearch, to reduce the computational time and space required for searching; however, it does not require dedicated accelerators, and its implementation is freely available as an open-source software package written in the Julia programming language [17]. It also utilizes an indexing technique of bit vectors to rapidly narrow down candidates of similar cells. Moreover, cell databases once created can be saved to a disk and quickly loaded for later searches. Here, we demonstrate the effectiveness and scalability of our approach using real scRNA-seq data sets, one of which includes more than one million cells.

Results

Workflow overview of CellFishing.jl
CellFishing.jl first creates a search database of reference cells from a matrix of transcriptome expression profiles of scRNA-seq experiments, and then searches the database for cells with an expression pattern similar to the query cells. The schematic workflow of CellFishing.jl is illustrated in Figure 1. When building a database, CellFishing.jl uses a digital gene expression (DGE) matrix as an input along with some metadata, if provided. It next applies preprocessing to the matrix, resulting in a reduced matrix, and subsequently hashes the column vectors of this reduced matrix to low-dimensional bit vectors. The preprocessing phase consists of five steps: feature (gene) selection, cell-wise normalization, variance stabilization, feature standardization, and dimensionality reduction. The information provided by these steps is stored in the database, and the same five steps are applied to the DGE matrix of query cells. In the hashing phase, random hyperplanes are generated from a pseudo-random number generator, and the column vectors of the reduced matrix are encoded into bit vectors according to the compartment in which the vector exists. This technique, termed LSH, is used to estimate the similarity

between two data points by their hashed representation [16]. The bit vectors are indexed using multiple associative arrays that can be utilized for subsequent searches [18]. The implementation is written in the Julia language; the database object can be saved easily as a file, and the file can be transferred to other computers, which facilitates quick, comparative analyses across different scRNA-seq experiments.

Figure 1 Schematic workflow of CellFishing.jl. CellFishing.jl first builds a database (DB) object that stores data preprocessors, indexed bit vectors, and cell metadata, if provided. The metadata can store any information including cell names, cell types, and transcript expressions of marker genes. When building a database, the DGE matrix of reference cells is preprocessed to extract important signals and then hashed into bit vectors by LSH. The preprocessors and the indexed bit vectors are stored in the database object. M, D, and T on the left side of the figure refer to the number of genes, number of reduced dimensions, and length of the bit vectors, respectively. N and N' above the two DGE matrices represent the number of cells within the reference and query data, respectively. While searching the database for similar cells, the prebuilt preprocessors stored in the database are reused in a similar workflow that is involved in database building up to the hashing phase. The database object can be saved onto a disk and can be loaded from there.

Data sets
We selected five data sets as benchmarks from scRNA-seq experiments, each including at least 10,000 cells, and one including more than 1.3 million cells, which was the largest publicly available data set. Cells without a cell type or cluster annotation were filtered out for evaluation. The data sets after filtering are summarized in Table 1.

Wagner *et al.* [19] recently reported that if there is no biological variation, excessive zero counts within a DGE matrix (dropouts) have not been observed

in data generated from inDrop [5], Drop-seq [6], and Chromium [7] protocols. Similarly, Chen *et al.* [20] conducted a more thorough investigation and concluded that negative binomial models are preferred over zero-inflated negative binomial models for modeling scRNA-seq data with UMIs. We confirmed a similar observation using our control data generated from Quartz-Seq2 [8]. Therefore, we did not take into account the effects of dropout events in this study.

Randomized singular value decomposition (SVD)
SVD is commonly used in scRNA-seq to enhance the signal-to-noise ratio by reducing the dimensions of the transcriptome expression matrix. However, computing the full SVD of an expression matrix or eigendecomposition of its covariance matrix is time consuming and requires large memory space especially when the matrix contains a large number of cells. Since researchers are usually interested in only a few dozen of the top singular vectors, it is common practice to compute only those important singular vectors. This technique is called low-rank matrix approximation, or truncated SVD. Recently, Halko *et al.* [23] developed approximated low-rank decomposition using randomization and were able to demonstrate its superior performance compared with other low-rank approximation methods. To determine the effectiveness of the randomized SVD, in this study, we benchmarked the performance of three SVD algorithms (full, truncated, and randomized) for real scRNA-seq data sets and evaluated the relative errors of singular values calculated using the randomized SVD. Full SVD is implemented using the `svd` function of Julia and the truncated SVD is implemented using the `svds` function of the Arpack.jl package, which computes the decomposition of a matrix using implicitly restarted Lanczos iterations; the same algorithm is used in Seurat [24] and CellRanger [7]. We implemented the randomized SVD as described in [25] and included the implementation in the CellFishing.jl package. We then computed the top 50 singular values and the corresponding singular vectors for the first four data sets listed in Table 1 and measured the elapsed time. All mouse cells (1,886 total) of the Baron2016 data set were excluded because merging expression profiles of human and mouse is neither trivial nor our focus here. The data sizes of the four data sets after feature selection were 2,190 × 8,569, 3,270 × 27,499, 3,099 × 21,612, and 2,363 × 54,967 in this order. From the benchmarks, we found that the randomized SVD remarkably accelerates the computation of low-rank approximation for scRNA-seq data without introducing large errors in the components corresponding to the largest singular values (Figure 2). It must be noted that in our application, obtaining exact singular vectors is not particularly important; rather computing

the subspace with high variability spanned by approximated singular vectors is more important because each data point is eventually projected onto random hyperplanes during hashing. Therefore, evaluating relative errors of singular values suffices to quantify the precision of randomized SVD.

Figure 2 Benchmarks of randomized SVD. **a** Elapsed time of different SVD algorithms. The *blue, orange,* and *green points* indicate the elapsed time of the full, truncated, and randomized SVD, respectively. **b** Relative errors of the randomized SVD. The *error bars* denote the standard deviation of ten trials. The relative error of the i-th largest singular value σ_i is defined as $\left|1 - \frac{\hat{\sigma}_i}{\sigma_i}\right|$, where $\hat{\sigma}_i$ is an approximated value of σ_i. The error bars denote the standard deviation of ten trials. The approximation error for a real matrix A with a low-rank matrix is bounded by a singular value as illustrated in the following formula: $\max_{\text{rank}(X) \leq j} ||A - X|| = \sigma_{j+1}$, where $||\cdot||$ denotes the operator norm of a matrix.

Similarity estimation using bit vectors
In LSH, the angular distance between two expression profiles can be estimated from the Hamming distance between their hashed bit vectors. Assuming θ is the angle between two numerical vectors representing the expression profiles, the estimator of θ derived from two bit vectors p and q is $\theta \approx \frac{\pi}{T} d_H(p, q)$, where T is the length of a bit vector and $d_H(\cdot, \cdot)$ is a function that calculates the Hamming distance between the two bit vectors. This estimator is unbiased but occasionally suffers from its high variance, which can pose a problem. To counter this issue, CellFishing.jl employs an orthogonalization technique that creates more informative hyperplanes from random hyperplanes before

Table 1 Summary of scRNA-seq data sets

Data set	#Cells	#Clusters	Protocol	Cell types
Baron2016 [21]	10,455	14	inDrop	pancreas cells of human and mouse
Shekhar2016 [9]	27,499	19	Drop-seq	retinal bipolar neurons of mouse
Plass2018 [10]	21,612	51	Drop-seq	mature and progenitor cells of planarian
TabulaMuris[†][12]	54,967	57	Chromium	cell atlas of mouse
1M_neurons [22]	1,306,127	60	Chromium	brain cells of mouse

[†] Not including cells sequenced with Smart-Seq2.

hashing data points by orthogonalizing the normal vectors of these random hyperplanes [26]. We confirmed the variance reduction effect of this orthogonalization technique by comparing the estimators with the exact values using randomly sampled expression profiles, as shown in Figure 3a. The effect was consistent for all other data sets as expected (Additional file 1, Figure 9,11,13).

As can be seen in Figure 3a, the estimator of the angular distance becomes less variable as the length of the bit vectors increases due to the central limit theorem. However, using more extended bit vectors requires more computational time and space. To investigate reasonable candidates for the length of bit vectors, we compared the Hamming and cosine distances of 100 random cells (Figure 3b). The Shekhar2016 data set shows that only 28% of random cells could find their true nearest neighbor in the top ten candidates nominated by 64-bit vectors, while 45%, 75%, and 85% could find their true neighbor by 128-, 256-, and 512-bit vectors, respectively. This result suggests that hashing expression profiles with 64-bit vectors is insufficient to find neighboring cells.

CellFishing.jl indexes bit vectors in order to accelerate the cell searching process. The algorithm used in this bit search progressively expands the search space that is centered at the query bit vector; thus, using longer bit vectors is not feasible in practice because the search space rapidly expands as more bits are used. In our preliminary experiments, index searches using longer than or equal to 512 bits often consumed more time than linear searches for a wide range of database sizes due to this expansion of the search space. As a result, we limited the length of the bit vectors to 128 or 256 bits in the following experiments. To further reliably find similar cells with these limited bits, CellFishing.jl generates mutually independent bit indexes from a reduced matrix. When searching a database, CellFishing.jl separately searches these bit indexes within the database and aggregates the results by ranking candidate cells by the total Hamming distance from the query. This requires more time than using a single bit index, but as we show in the following section, it appreciably reduces the risk of overlooking potentially neighboring cells.

Self-mapping evaluation

To compare the performance of CellFishing.jl with that of scmap-cell, we performed five-fold cross-validations by mapping one-fifth of cells randomly sampled from a data set to the remaining four-fifth of cells from the same data set, and computed the consistency and Cohen's kappa score [27] of the neighboring cell's label. A value of 1 in the consistency score indicates the perfect agreements of cluster (cell type) assignments and 0 indicates no agreements, while a value of 1 in Cohen's kappa score indicates the perfect agreements and 0 indicates random assignments. We obtained the ten nearest neighbors for each cell, which is the default parameter of scmap-cell, but only the nearest neighbor was used to compute the scores. This evaluation assumes that cells with similar expression patterns belong to the same cell-type cluster, and hence a query cell and its nearest neighbors ought to have the same cluster assignment. In CellFishing.jl, we varied only the number of bits and number of indexes, which control the trade-off between estimation accuracy and computational cost; other parameters (i.e., the number of features and number of dimensions of a reduced matrix) were fixed to the defaults. In scmap-cell, DGE matrices were normalized and log-transformed using the `normalize` function of the scater package [28], and we varied two parameters: the number of centroids (landmark points calculated by k-means clustering of cells, used to approximate the similarity between cells) and the number of features, in order to find parameter sets that achieve better scores.

Figure 4a,b shows the consistency and Cohen's kappa scores of CellFishing.jl and scmap-cell with different parameter sets. The overall scores were high (>0.94) for both methods, with the exception of the Plass2018 data set. With the default parameters (see Figure 4 for a description), CellFishing.jl consistently outperformed scmap-cell in both consistency and Cohen's kappa score for all data sets. In CellFishing.jl, using multiple independent hashes significantly improved the scores, suggesting that using 128 or 256 bits is insufficient to reliably estimate the similarity between cells. Instead of log transformation, using the Freeman–Tukey transformation [19, 29] resulted in almost similar scores (Additional file 2). In scmap-cell,

Figure 3 Locality-sensitive hashing of expression profiles (Shekhar2016). **a** Distributions of estimation errors for angles. The *blue lines* show the distributions without orthogonalization, and the *orange lines* show the distributions with orthogonalization. Five hash values were generated independently, and their estimation errors in radian were computed for 100 cells randomly sampled from Shekhar2016. **b** Scatter plots of the Hamming distance versus the cosine distance. The rows are four different bit lengths (64, 128, 256, and 512 bits) and the columns are six cells randomly sampled from Shekhar2016. The Hamming distance is normalized to $[0, 1]$ for comparison across different bit lengths, and the cosine distance is truncated at 0.3 for brevity.

increasing the centroids or incorporating more features did not remarkably improve the scores.

In this evaluation, we also measured the elapsed time of indexing and querying. The measured values do not include the cost of reading data from a disk because it varies depending on the file format and the disk type. In both indexing and querying, CellFishing.jl was faster than scmap-cell by a large margin, as shown in Figure 4c,d. For example, comparing the median of the elapsed time with the default parameters in the TabulaMuris data set, CellFishing.jl was 20 times faster for the indexing time (32.7 vs. 661.9 s) and 108 times faster for the querying time (7.2 vs. 780.6 s).

Since cell types have highly skewed or long-tail distributions (Additional file 1, Figure 1,3–5), the global evaluation scores used tend to be dominated by large subpopulations and could overlook underrepresented cell types. The cluster-specific consistency scores for each cluster assignment are visualized in Figure 5. Here, the parameters were fixed to the defaults for both CellFishing.jl and scmap-cell. From this figure, CellFishing.jl evidently includes minor cell types, although the scores are relatively unstable for those cell types. For example, while Baron2016 contains only eighteen Schwann cells and seven T cells, CellFishing.jl found these cell types with high consistency ($>$0.8). Also, CellFishing.jl shows comparable or better consistency scores than scmap-cell for the majority of the cell types.

The consistency scores of Plass2018 are relatively lower than those of the other data sets. This could be because Plass2018 contains more progenitor or less-differentiated cells, and thus it is more difficult to distinguish these cell types from their expression pro-

files. As indicated in Figure 6, a significant number of neoblasts and progenitors are assigned to neoblast 1, which is the largest subpopulation (29.35%) of the data set. These subtypes of neoblasts and progenitors are almost indistinguishable from the t-SNE (t-distributed Stochastic Neighbor Embedding) plot (see [10], Figure 1B), which suggests that these cell types have very slight differences in their expression profiles. Still, when comparing CellFishing.jl and scmap-cell, the former more clearly discriminates these cell types.

To see the effects of selected features, we evaluated the scores by exchanging features selected by CellFishing.jl and scmap-cell. When CellFishing.jl used features selected by scmap-cell, we could not detect meaningful differences in the consistency scores except within Plass2018, which improved the score by around 1.7%. Likewise, when scmap-cell used features selected by CellFishing.jl, we could not detect meaningful differences except within Shekhar2016, which decreased the score by around 5.5%. These results seem to indicate that while scmap-cell selects better features, it has limited effects on the performance of CellFishing.jl.

Mapping cells across different batches

Researchers are often interested in searching for cells across different experiments or batches. To verify the robustness of our method in this situation, we performed cell mapping from one batch to other batches and evaluated the performance scores. Shekhar2016 consists of two different batches (1 and 2), which exhibit remarkable differences in their expression patterns (see [9], Figure S1H). We mapped cells from one batch to the other using CellFishing.jl and scmap-cell, and calculated the consistency and Cohen's kappa

Figure 4 Comparison between CellFishing.jl and scmap-cell by self-mapping. **a** Consistency scores. **b** Cohen's kappa scores. **c** Index times. **d** Query times. Each data point corresponds to a five-fold cross-validation. The `n-bits` and `n-lshashes` parameter of CellFishing.jl are the number of bits and the number of independent locality-sensitive hashes, respectively (`n-bits=128` and `n-lshashes=4` are the defaults). The `n-centroids-factor` and `n-features` parameter of scmap-cell are the multiplier of the default number of centroids (i.e, $\lfloor\sqrt{N}\rfloor$, where N refers to the number of reference cells) parameter and the number of features parameter, respectively (`n-centroids-factor=1` and `n-features=500` correspond to the defaults).

score. Similarly, we selected two batches (plan1 and plan2, derived from wild-type samples) from Plass2018 and mapped cells from one batch to the remaining batches. This data set exhibits relatively weak batch effects. The default parameters were used in this experiment. Figure 7a shows the results of these two data sets for consistency scores. In both data sets, the consistency scores of CellFishing.jl were close to the mean score obtained from the self-mapping experiment. Moreover, their distances from the mean score in CellFishing.jl were smaller than those in scmap-cell, suggesting that CellFishing.jl is more robust to batch

effects. The results of the Cohen's kappa scores were consistent with these results (Additional file 1, Figure 21). We predict that the differences in scores between batches are due to differences in cluster sizes. For example, batch 1 of Shekhar2016 contains many more rod bipolar cells than batch 2, while the latter contains more minor cell types than the former (Figure 7b). The discrepancy in cluster sizes across batches leads to a difference in scores because each cluster has a different consistency score, as observed in the self-mapping experiment.

Figure 5 Cluster-specific consistency scores. **a-d** Cluster-specific consistency scores of Baron2016 (human), Shekhar2016, Plass2018, and TabulaMuris (Chromium). The *blue* and *orange points* denote the consistency scores of CellFishing.jl and scmap-cell, respectively. Cluster labels are ordered by the cluster size, from top to bottom and then left to right in decreasing order.

Mapping cells across different species

Comparing transcriptome expressions across different species provides important information on the function of unknown cell types. Since the Baron2016 data set includes cells derived from human and mouse, we attempted to match cells between both species. To match genes from different species, we downloaded a list of homologous genes between human and mouse from the Vertebrate Homology database of Mouse Genome Informatics and removed non-unique relations from the list. A total of 12,413 one-to-one gene pairs were included. We compared the performance of CellFishing.jl and scmap-cell with the default parameters. The consistency scores of CellFishing.jl and scmap-cell map-ping from human to mouse were 0.681 and 0.563, respectively, and from mouse to human were 0.787 and 0.832, respectively. The Cohen's kappa scores of CellFishing.jl and scmap-cell mapping from human to mouse were 0.599 and 0.455, respectively, and from mouse to human were 0.715 and 0.753, respectively. These results show that CellFishing.jl and scmap-cell are roughly comparable for cell mapping accuracy across different species.

Mapping cells across different protocols

Mapping cells across different sequencing protocols is also important. To validate the robustness of CellFish-ing.jl in this case, we used TabulaMuris, which con-

Figure 6 Proportions of cluster assignments for CellFishing.jl and scmap-cell. The rows are labels of query cells and the columns are labels of their nearest neighbor. Cluster labels are ordered by the cluster size, from top to bottom (rows) or left to right (columns) in decreasing order. The values are derived from a cross-validation with the default parameters and normalized row-wise (i.e., the sum of values in a row is 1).

sists of two data sets derived from different sequencing platforms, and mapped 44,807 cells sequenced with Smart-Seq2 [30] to 54,967 cells with Chromium. The default parameters were used in this experiment. Because cluster labels are not identical between the two data sets, it is not possible to compute the consistency or Cohen's kappa score. Thus, the matrices of cluster assignments are visualized in Figure 8. On the whole, these two matrices show very similar assignment patterns, although CellFishing.jl failed to detect a large number of fibroblast cells.

Saving and loading databases

CellFishing.jl is designed to search many scRNA-seq experiments, and the database objects can be serialized into a disk and later deserialized. For this purpose, CellFishing.jl provides a pair of functions to save and load a database object into and from a file, and the load function can read a gzip- or zstd-compressed file. To verify the feasibility of this approach, we measured the elapsed time of saving and loading a database object with cell names as metadata, as well as the memory and file size of the object. The results are summarized in Table 2. Compressing a file of a serialized

database significantly reduces the size in both gzip and zstd formats (32–48%), which saves disk space required for storing database objects. While file compression imposes some decompression overhead on data loading, we found it quick in relative to querying, especially when compressed in the zstd format. From these results, we expect that CellFishing.jl can be used to quickly search across several scRNA-seq experiments by building and serializing their database objects in advance.

Scalability for large data sets

To check the scalability of our approach for large data sets, we measured the index time, query time, and the memory size of a database by changing the number of cells within the database. In this benchmark, we randomly sampled 10,000 cells from the 1M_neurons data set as queries and then randomly sampled $N = 2^{13}, 2^{14}, \ldots, 2^{20}$ cells from the remaining cells to create a database ($2^{13} = 8,192$ and $2^{20} = 1,048,576$, which covers a wide range of high-throughput scRNA-seq experiments); there are no overlapping cells between or within the query and database sets. The number of bit indexes was fixed to the default (i.e., 4) in all cases.

Table 2 Performance of saving and loading database objects and their memory and file size.

Data set	#bits	Memory size [MiB]	File size [MiB]			Save time [ms]	Load time [ms]		
			raw	gzip	zstd		raw	gzip	zstd
Baron2016-human	128	3.1	2.9	1.9	1.9	2.4	2.6	21.9	8.1
	256	5.4	5.2	3.5	3.3	3.9	5.7	35.1	12.8
Shekhar2016	128	8.2	7.8	5.2	5.3	5.9	8.5	51.7	22.8
	256	14.6	14.1	9.7	9.7	9.9	10.6	91.2	34.6
Plass2018	128	6.7	6.4	4.3	4.3	5.2	8.1	42.6	17.1
	256	12.0	11.6	7.9	7.8	9.3	8.8	79.8	32.1
TabulaMuris-chromium	128	13.8	13.0	6.8	7.7	9.2	13.3	91.3	36.1
	256	24.9	24.2	13.0	14.6	15.3	21.6	161.9	63.7

The raw columns denote the file format without compression.   Each value is the median of ten measurements.

Figure 7 Cell mapping across batches. **a** Consistency scores of cell mapping (Shekhar2016 and Plass2018). The *red lines* denote the mean score of the corresponding self-mapping experiment with the same parameters. **b** Distribution of cluster sizes (Shekhar2016).

For comparison, we also benchmarked the performance of the linear search that scans all hash values in a database instead of using indexes. The elapsed time does not include the time of loading expression profiles from a file.

The benchmark results are summarized in Table 3. As for the index search, the query time is sublinear to the database size, while the index time and memory size are roughly linear. For example, when 128-bit vectors are used, the query time becomes only 3.0 times longer in the same range, as the database size becomes 128 times larger from $N = 2^{13}$ to 2^{20}. The linearities of the index time and memory size are expected, because when building a database all the reference cells need to be scanned and stored, though these are not wholly proportional to the database size because some overhead costs are included in the measured values (e.g., generating and storing projection matrices). Also, the memory usage per cell is only 183.4 bytes for 128-bit vectors and 366.1 bytes for 256-bit vectors when $N = 2^{20}$, which is approximately 22 and 11 times smaller than storing UMI counts of 1,000 genes in 32-bit integers, respectively.

The index time remains almost unchanged between the index and the linear search, suggesting that the computational cost of creating hash indexes is, in effect, negligible. In contrast, the gap of the query time between the two search methods expands as the database becomes larger, which can be attributed to the searching phase of bit vectors because the cost of the preprocessing phase is constant (Figure 9). In addition, even though indexing bit vectors requires extra memory, the relative difference from a database without indexes is approximately equal to or less than three times, and the absolute memory size of a database with indexes is small enough for modern computing environments, including laptops.

We also evaluated the consistency scores and found that they were slightly improved by incorporating more cells into a database (when using 128-bit vectors, the consistency scores were 0.777 and 0.824 for

Figure 8 Cluster assignments across different protocols (TabulaMuris). **a** CellFishing.jl. **b** scmap-cell. The rows are the query's cluster labels (Smart-Seq2) and the columns are its neighbor's cluster labels (Chromium).

$N = 2^{13}$ and $N = 2^{20}$, respectively) (Additional file 1, Figure 22). This result suggests that building a database with more cells plays an important role in identifying cell types. The consistency scores did not vary significantly between the index and linear search as expected, because nearest neighbors found by the index search have the same Hamming distances as those found by the linear search. In summary, indexing bit vectors is effective in reducing the search time for high-throughput scRNA-seq data and is scalable for extremely large data sets containing more than one million cells.

Discussion
Our LSH-based method is particularly suitable for middle or large scale scRNA-seq data sets because it circumvents costly brute-force search by using indexes

for low-dimensional bit vectors. We considered relatively large data sets consisting of at least ten thousand cells, one of which contains more than one million cells, and confirmed our approach outperforms scmap-cell, the state-of-the-art method for cell searching, in both accuracy and throughput using real scRNA-seq data sets. Searching across multiple experiments will be feasible because our method is reasonably robust to batch differences, and serialized database objects can be loaded quickly. In this paper, we did not compare our method with CellAtlasSearch, mainly because its source code is not freely available, and its algorithm is not well described in the original paper, which makes it difficult to compare the performance fairly. Moreover, CellAtlasSearch requires a GPU to achieve its maximum performance, but this is not always available on server machines.

Table 3 Scalability of CellFishing.jl (1M_neurons)

	#bits	index	Database size N							
			2^{13} (1.0)	2^{14} (2.0)	2^{15} (4.0)	2^{16} (8.0)	2^{17} (16.0)	2^{18} (32.0)	2^{19} (64.0)	2^{20} (128.0)
Index time [s]	128	−	1.3 (1.0)	2.4 (1.9)	4.7 (3.7)	9.0 (7.1)	17.7 (13.9)	34.3 (27.0)	68.5 (53.9)	132.3 (104.1)
	128	+	1.4 (1.0)	2.4 (1.8)	4.7 (3.5)	9.2 (6.8)	17.7 (13.0)	34.6 (25.3)	69.9 (51.1)	135.9 (99.5)
	256	−	1.5 (1.0)	2.7 (1.8)	4.9 (3.2)	9.8 (6.5)	18.5 (12.2)	37.0 (24.3)	75.4 (49.5)	145.8 (95.8)
	256	+	1.5 (1.0)	2.8 (1.9)	5.2 (3.5)	10.2 (6.8)	19.4 (13.0)	38.5 (25.8)	79.0 (53.0)	152.8 (102.6)
Query time [s]	128	−	2.9 (1.0)	4.0 (1.4)	6.6 (2.3)	11.6 (3.9)	21.6 (7.4)	41.4 (14.1)	81.3 (27.7)	165.3 (56.4)
	128	+	2.5 (1.0)	2.5 (1.0)	2.8 (1.1)	2.8 (1.1)	3.3 (1.3)	3.6 (1.4)	5.6 (2.2)	7.4 (3.0)
	256	−	3.2 (1.0)	4.7 (1.5)	7.7 (2.4)	13.8 (4.3)	25.7 (8.0)	49.8 (15.4)	102.7 (31.9)	207.8 (64.5)
	256	+	4.0 (1.0)	4.6 (1.1)	5.1 (1.3)	6.0 (1.5)	7.1 (1.8)	10.4 (2.6)	15.9 (4.0)	25.7 (6.4)
Memory size [MiB]	128	−	1.3 (1.0)	1.8 (1.4)	2.8 (2.2)	4.8 (3.7)	8.8 (6.8)	16.8 (12.9)	32.8 (25.2)	64.7 (49.7)
	128	+	3.0 (1.0)	4.8 (1.6)	8.3 (2.8)	14.8 (5.0)	27.1 (9.1)	51.0 (17.1)	93.0 (31.3)	183.4 (61.6)
	256	−	1.9 (1.0)	2.9 (1.6)	4.9 (2.6)	8.9 (4.8)	16.9 (9.0)	32.9 (17.6)	64.9 (34.7)	128.8 (68.9)
	256	+	5.2 (1.0)	8.9 (1.7)	15.8 (3.0)	28.8 (5.5)	53.7 (10.2)	101.4 (19.4)	193.0 (36.8)	366.1 (69.9)

Plus and minus signs in the index column denote the index search and the linear search, respectively.   The values enclosed by parentheses are relative to those of $N = 2^{13}$.   Each value is the median of five measurements.

Figure 9 Computational costs of different phases. The upper and lower plots show the costs of the linear and index searches, respectively. The elapsed time of each phase was measured using the `time_ns` function and divided by the number of query cells to compute the average time per cell.

The application of cell searching is not limited to mapping cells between different data sets. The task of finding similar cells within a data set is a subroutine in many analysis methods, such as data smoothing [19], clustering [31], community detection [32], and visualization [33]. As we have demonstrated in the self-mapping experiment, our LSH-based method can find similar cells within a data set with high accuracy and throughput; thus, it would be possible to speed up analysis by utilizing our cell search method in lieu of the currently available method.

The feature selection used in CellFishing.jl is relatively simple and rapid. We confirmed that it works well with our search method; however, we also found that the criterion based on the dropout rate used in scmap-cell performed slightly better in a data set. This fact suggests that our simple selection method is not necessarily suitable for all scRNA-seq data sets, and a more careful feature selection, such as adding marker genes selected by domain experts or more careful selection methods such as GiniClust [34], may significantly improve the accuracy of cell typing. For this purpose, CellFishing.jl provides for addition and removal of specific features to or from a feature set.

Handling batch effects is still a persistent problem in scRNA-seq. We performed cell mapping experiments across different batches and protocols and confirmed that the performance of our approach is at least comparable to scmap-cell. We consider that the robustness of CellFishing.jl comes from projecting expression profiles to a space with dataset-specific variability, as previously reported by Li *et al.* [35]. This type of technique is also discussed in the context of information retrieval and is termed *folding-in* [36]. Although substantial literature exists on the removal of batch effects in scRNA-seq data [37–39], the existing methods require merging raw expression profiles of reference and query cells to obtain their batch-adjusted profiles, and the computational costs are relatively high; these characteristics are not suitable for our low-memory/high-throughput search method. In contrast, folding-in is very affordable because projection matrices can be computed when building a database and reused for any query.

In this work, we have focused on unsupervised cell searching: no cellular information is required except their transcriptome expression data. This makes our method even more useful because it is widely applicable to any scRNA-seq data with no cell annotations. However, incorporating cell annotations or prior knowledge of reference cells could remarkably improve our method's performance. For example, if cell-type annotations are available, it would be possible to generate tailored hash values separating cell types more efficiently by focusing on their marker genes. Further research is needed in this direction.

Conclusions

In summary, the new cell search method we propose in this manuscript outperforms the state-of-the-art method and is scalable to large data sets containing more than one million cells. We confirmed that our method considers very rare cell types and is reasonably robust in response to differences between batches, species, and protocols. The low-memory footprint and database serialization facilitate comparative analysis between different scRNA-seq experiments.

Methods

Preprocessing

In the preprocessing step, biological signals are extracted from a DGE matrix. When building a database of reference cells, CellFishing.jl takes a DGE matrix of M rows and N columns, with the rows being features (genes) and the columns being cells, along with some metadata (e.g., cell names). In scRNA-seq analysis, it is common practice to filter out low-abundance or low-variance features because these do not contain enough information to distinguish differences among cells [40]. In the filtering step of CellFishing.jl, features that have smaller maximum count across cells than a specific threshold are excluded. We found that this criterion is rapid and sometimes more robust than other gene filtering methods, such as selecting highly variable genes [41]. The optimal threshold depends on various factors such as sequencing protocol and depth. CellFishing.jl uses a somewhat conservative threshold that retains at least 10% of features by default; however, retaining an excessive amount of features would not be detrimental with regard to accuracy because CellFishing.jl uses the principal components of the data matrix in a later step. One parameter can change the threshold, and it is possible to specify a list of features to be retained or excluded if, for example, some marker genes are known *a priori*.

The filtered DGE matrix is then normalized so that the total counts are equal across all the cells, which reduces the differences in the library size among cells [42]. After normalization, each count x is transformed by log transformation $\log(x + 1)$, which is a common transformation in scRNA-seq, or FTT $\sqrt{x} + \sqrt{x+1}$ [29]. FTT is a variance-stabilizing transformation assuming the Poisson noise, which is observed as a technical noise in scRNA-seq [19, 42]. Also, the computation of FTT is significantly faster than that of log transformation. The user can specify a preferable transformation, and the choice will be saved in a preprocessor object. In this paper, we used log transformation if not otherwise specified. After transformation, the feature counts are standardized so that their mean and variance are equal to zero and one, respectively.

Finally, the column vectors in the matrix are projected onto a subspace to reduce the number of dimensions. The advantages of this projection are threefold: (1) computational time and working space for preprocessing are saved; (2) the number of bits required for hash expression profiles is reduced; and (3) batch effects between the query and the database are mitigated. As recently reported [35], projecting data onto a subspace defined by variability in reference cells greatly reduces unwanted technical variation and improves the accuracy of cell-type clustering. A similar approach is found elsewhere [6]. In CellFishing.jl, a subspace with high variance is calculated by applying the SVD to the reference data matrix. Since the number of cells may be extremely large and singular vectors corresponding to small singular values are irrelevant, CellFishing.jl uses a randomized SVD algorithm [23, 25] that approximately computes singular vectors corresponding to the top D singular values. The dimension of the subspace D is set to 50 by default, but it can be changed easily by passing a parameter. The net result of the preprocessing phase is a matrix of D rows and N columns. The information of the preprocessing phase (e.g., gene names and projection matrices) is stored in the database object, and the same process is applied to the count vectors of query cells.

Hashing expression profiles

LSH is a technique used to approximately compute the similarity between two data points [16], which hashes a numerical vector $x \in \mathbb{R}^D$ to a bit vector $p \in \{0, 1\}^T$ that preserves some similarity or distance between the original vectors. Hashed values (bits) of LSH collide with high probability if two original vectors are similar. This is the fundamental property of hash functions used in LSH, because by comparing binary hash values of numerical vectors their similarity can be estimated, which bypasses the time-consuming distance computation between the numerical vectors.

In LSH, it is common to use T hash functions to generates T bits; each hash function returns zero or one for an input vector, and the results of multiple hash functions for the vector are bundled into a bit vector of length T. More formally, given a similarity function $\text{sim}(\cdot, \cdot) : \mathbb{R}^D \times \mathbb{R}^D \to [0, 1]$ that measures some similarity between two data points, an LSH function $h(\cdot) : \mathbb{R}^D \to \{0, 1\}$ is defined as a function that satisfies the following relation:

$$\Pr_{h \in \mathcal{F}}[h(x) = h(y)] = \text{sim}(x, y), \tag{1}$$

where $\Pr_{h \in \mathcal{F}}[h(x) = h(y)]$ is the probability of hash collision for a hash function $h(\cdot)$ generated from a family of hash functions $\mathcal{F}$ given a pair of points x and

y. The existence of a family of hash functions that satisfies equation 1 depends on the similarity function $\text{sim}(\cdot, \cdot)$. Similarity, if exists, can be approximated by randomly generating hash functions from $\mathcal{F}$ as follows:

$$\text{sim}(x, y) = \mathbb{E}_{h \in \mathcal{F}}\left[\mathbb{I}[h(x) = h(y)]\right]$$

$$\approx \frac{1}{T} \sum_{i=1}^{T} \mathbb{I}[h_i(x) = h_i(y)], \tag{2}$$

where $\mathbb{E}_{h \in \mathcal{F}}[\cdot]$ is an expectation over $\mathcal{F}$, $\mathbb{I}[\cdot]$ is the indicator function, and $\{h_i(\cdot)\}_{i=1}^{T}$ is a set of hash functions sampled from $\mathcal{F}$.

In this work, we used a signed random projection LSH (SRP-LSH) to hash expression profiles, as it estimates angular similarity between two numerical vectors, which is reasonable to measure the similarity between expression profiles, and is straightforward to implement. Briefly, SRP-LSH divides a set of data points in a space into two disjoint sets by drawing a random hyperplane on the space, then the data points in a set of the two are hashed to zeros, with the remaining points hashed to ones. This procedure is repeated T times to get a bit vector of length T for each data point. Intuitively, the closer two points are to each other, the more likely it is that they occur in the same half-space with respect to a random hyperplane. Therefore, we can stochastically estimate the similarity of two points by calculating the Hamming distance of their bit vectors. In SRP-LSH, the angular similarity function $\text{sim}(x, y) = 1 - \frac{\theta(x, y)}{\pi}$, where $\theta(x, y)$ refers to the angle between two vectors x and y, is estimated from equation 2. In this way, we randomly generate T hyperplanes, calculate their hash values, and bundle their zero or one bits into a bit vector of length T.

While SRP-LSH dramatically reduces the computational time and space of the approximate search of neighboring cells, it suffers from its high variance of the similarity estimator. To alleviate the problem, CellFishing.jl orthogonalizes the vectors perpendicular to the random hyperplanes (normal vectors) because it reduces the variance of the estimator by removing the linear dependency among hyperplanes without introducing estimation bias [26]. Specifically, T normal vectors of length D are generated independently from the standard isotropic Gaussian distribution and then orthogonalized using the QR decomposition. If T is larger than D, the T vectors are divided into $\lceil T/D \rceil$ batches of vectors, each of which contains at most D vectors, and the vectors in a batch are orthogonalized separately.

Indexing hash values
Although comparing bit vectors is much faster than comparing numerical vectors, it is still lengthy pro-

cess to scan all the bit vectors in a database, especially in a large database. To reduce the computational cost of hash searching, CellFishing.jl creates search indexes in the space of bit vectors. Specifically, CellFishing.jl creates multi-index hash (MIH) [18] tables to find the nearest neighbors quickly in the Hamming space $\mathcal{H}_T := \{0, 1\}^T$. Briefly, an MIH divides bit vectors into shorter subvectors and indexes them separately using multiple associative arrays (tables); when searching for the nearest neighbors of a query, it divides the query bit vector in the same way and picks candidates of neighbors from the tables of the subvectors. It then computes the full Hamming distances between the query and the candidates by scanning the list of the candidates and finally returns the k-nearest neighbors. The search algorithm progressively expands the search space in $\mathcal{H}_T$ to find all k-nearest neighbors in the database; hence, the result is equivalent to that of the brute-force search, disregarding a possible difference in the order of ties with the same Hamming distance. The main point here is that dividing and separately indexing the bit vectors dramatically reduces the search space that needs to be explored. For example, when attempting to find all bit vectors within r-bit differences from a query using a table, the number of buckets of the table we need to check is $\sum_{i=0}^{r} \binom{T}{i}$, where T is the length of the bit vectors and $\binom{n}{k}$ is the number of combinations choosing k distinct items from n. This value rapidly increases even for a small r, which would easily exceed the number of elements in the table. For instance, the total number of combinations for $T = 128$ and $r = 9$ is roughly 20.6 trillion, which is the same order of magnitude as the estimated number of cells in the human body [43]. To avoid the problem, CellAtlasSearch seems to stop searching at some cutoff distance from the query bit vector [15], but choosing a good threshold for each cell is rather difficult. Instead, by dividing a bit vector of length T into m subvectors of the same length (we assume T is divisible by m for brevity), when $r < m$, it is possible to find at least one subvector that perfectly matches the corresponding subvector of the query with the pigeonhole principle. This partial matching can be used to find candidate bit vectors quickly using a table data structure. Even when there are no perfect matches in subvectors, the search space greatly shrinks by the division. Our implementation uses a direct-address table to index subvectors, and because the buckets of the table are fairly sparse (i.e., mostly vacant), we devised a data structure, illustrated in Figure 10, in order to exploit the sparsity and CPU caches. In addition, we found that inserting a data prefetch instruction greatly improves the performance of scanning candidates in buckets, because it reduces cache misses when bit vectors do not fit into the CPU caches. Please refer to [18]

and our source code for details of the algorithm and the data structure.

Figure 10 Data structure indexing subvectors. Given a subvector of the query bit vector, the subindex calculates the locations of the bit vectors in the database that contains the subvector in the same position. The subindex consists of three arrays: *filled*, *offsets*, and *buckets*. The *filled* array is a bit vector of length 2^s, where s is the length of indexed subvectors (in this figure, $T = 12$ and $s = 4$), and supports bit counting in a specific range with a constant time, which is used to calculate the location of the *offsets* array for a given subvector (highlighted four bits of the query). The *offsets* and *buckets* arrays are jointly used to obtain the locations of the *database* array at which bit vectors with a given subvector are stored.

The technique of dividing and indexing bit vectors reduces the cost of the search. However, it is still difficult in practice using long bit vectors due to expansion of the search space. To overcome this problem, we use multiple MIH indexes that are independent of each other. We refer to the number of MIH indexes as L; thus, the number of bits stored in a database per cell is TL. The L indexes separately find their own k-nearest neighbors of a given query and thus collect kL possibly duplicated neighboring candidates for each query. These candidates are passed to the next ranking phase. In our method, the two parameters T and L control the trade-off between accuracy and computational cost of the search.

Ranking cells
After collecting kL candidates from the L indexes, CellFishing.jl orders the kL cells to return only the top k cells. The algorithm computes total Hamming distances from a query and retains the top k candidates with the smallest Hamming distances. Candidates with identical distances, if any, are ordered in an arbitrary but deterministic way.

Implementation
CellFishing.jl is an open-source package written in the Julia language [17] and is distributed under the

MIT License. Julia is a high-performance dynamic programming language for technical computing, which compiles the source code at run-time and makes it easier to install CellFishing.jl, since the user does not need to compile the source code during installation. The entire code of the package is written in Julia, as it makes the code simpler while its performance is closely comparable to other compiled programming languages such as C. The installation can be done using a package manager bundled with Julia. The source code and the documentation of CellFishing.jl are hosted on GitHub: `https://github.com/bicycle1885/CellFishing.jl`.

The maximum performance of CellFishing.jl is achieved by exploiting the characteristics of modern processors. For example, CellFishing.jl heavily uses the POPCNT instruction (to count the number of 1 bits) and the PREFETCHNTA instruction (to prefetch data into caches from memory) introduced by the Streaming SIMD Extensions to compute the Hamming distance between bit vectors. These instructions are available on most processors manufactured by Intel or AMD. Since Julia compiles the source code at run-time, suitable instructions for a processor are automatically selected. Also, the linear algebra libraries included in Julia, such as OpenBLAS and LAPACK, contribute to the performance of the preprocessing and hashing phases. We consider that using accelerators such as GPUs is not particularly important in CellFishing.jl because these phases do not represent a major bottleneck.

Reproducibility
The script files used in this study are included in an additional file. To ensure reproducibility, all experiments were run using Snakemake [44], a Python-based workflow management tool for bioinformatics. We used Julia 0.7.0-beta2 to run CellFishing.jl 0.1.1 and R 3.5.0 to run scmap 1.2.0. R and scmap were installed in a Docker image built on top of Bioconductor's Docker image (`https://hub.docker.com/r/bioconductor/release_base2/`, R3.5.0_Bioc3.7) [45], with the Dockerfile included in the additional file. All the plots and tables in this manuscript were generated in a Jupyter notebook [46], which is also included in the same additional file. We used Linux machines with Intel Xeon Gold 6126 CPU (629.4 GiB of memory, hard disk drive) or Intel Xeon CPU E5-2637 v4 (251.6 GiB of memory, hard disk drive) to benchmark the run-time performance. Performance comparisons between CellFishing.jl and scmap-cell were performed on the same machine.

Consent for publication
Not applicable.

Availability of data and materials
CellFishing.jl is implemented in the Julia programming language, and the source code is freely available under the MIT license at `https://github.com/bicycle1885/CellFishing.jl`. All analyses and figures in this paper can be reproduced using the scripts at `https://github.com/bicycle1885/cellfishing-experiments`. The Baron2016 and Shekhar2016 data sets were downloaded from the Gene Expression Omnibus with accession numbers GSE84133 and GSE81904, respectively. The list of homologous genes between human and mouse was downloaded from the Vertebrate Homology database of Mouse Genome Informatics at `http://www.informatics.jax.org/homology.shtml`. The cluster annotation file of Shekhar2016 was downloaded from `https://portals.broadinstitute.org/single_cell/study/retinal-bipolar-neuron-drop-seq`. The Plass2018 data set was downloaded from `https://shiny.mdc-berlin.de/psca/`. The TabulaMuris data set was downloaded from `https://figshare.com/articles/Single-cell_RNA-seq_data_from_Smart-seq2_sequencing_of_FACS_sorted_cells_v2_/5829687` and `https://figshare.com/articles/Single-cell_RNA-seq_data_from_microfluidic_emulsion_v2_/5968960`. The 1M_neurons data set was downloaded from `https://support.10xgenomics.com/single-cell-gene-expression/datasets/1.3.0/1M_neurons`.

Competing interests
The authors declare that they have no competing interests.

Funding
This work was supported by MEXT KAKENHI Grant Number 16K16152. This work was supported by the Japan Science and Technology Agency (JST). This work was partially supported by JST CREST grant number JPMJCR16G3, Japan.

Author's contributions
KST, KT, KSH and IN designed the study. KST implemented all the software. KT validated all the R scripts. KST, KT, and IN wrote the manuscript. All authors have read and approved the final manuscript.

Acknowledgements
We thank Hirotaka Matsumoto for helpful discussions. We also thank Mr. Akihiro Matsushima and Mr. Manabu Ishii for their assistance with the IT infrastructure for the data analysis. We are also grateful to all members of the Laboratory for Bioinformatics Research, RIKEN Center for Biosystems Dynamics Research for giving us helpful advice.

Author details
[1]Department of Biotechnology, Graduate School of Agricultural and Life Sciences, The University of Tokyo, Bunkyo-ku, 113-8657, Tokyo, Japan. [2]Laboratory for Bioinformatics Research RIKEN Center for Biosystems Dynamics Research, Wako, 351-0198, Saitama, Japan. [3]Bioinformatics Course, Master's/Doctoral Program in Life Science Innovation (T-LSI), School of Integrative and Global Majors (SIGMA), University of Tsukuba, Wako, 351-0198, Saitama, Japan.

References
1. Islam, S., Kjällquist, U., Moliner, A., Zajac, P., Fan, J.B., Lönnberg, P., Linnarsson, S.: Characterization of the single-cell transcriptional landscape by highly multiplex RNA-seq. Genome Research **21**(7), 1160–1167 (2011). doi:10.1101/gr.110882.110
2. Hashimshony, T., Wagner, F., Sher, N., Yanai, I.: CEL-Seq: Single-Cell RNA-Seq by Multiplexed Linear Amplification. Cell Reports **2**(3), 666–673 (2012). doi:10.1016/j.celrep.2012.08.003
3. Kivioja, T., Vähärautio, A., Karlsson, K., Bonke, M., Enge, M., Linnarsson, S., Taipale, J.: Counting absolute numbers of molecules using unique molecular identifiers. Nature Methods **9**(1), 72–74 (2012). doi:10.1038/nmeth.1778
4. Islam, S., Zeisel, A., Joost, S., La Manno, G., Zajac, P., Kasper, M., Lönnberg, P., Linnarsson, S.: Quantitative single-cell RNA-seq with unique molecular identifiers. Nature Methods **11**(2), 163–166 (2014). doi:10.1038/nmeth.2772. arXiv:1011.1669v3
5. Klein, A.M., Mazutis, L., Akartuna, I., Tallapragada, N., Veres, A., Li, V., Peshkin, L., Weitz, D.A., Kirschner, M.W.: Droplet barcoding for

6. single-cell transcriptomics applied to embryonic stem cells. Cell **161**(5), 1187–1201 (2015). doi:10.1016/j.cell.2015.04.044. 15334406
6. Macosko, E.Z., Basu, A., Satija, R., Nemesh, J., Shekhar, K., Goldman, M., Tirosh, I., Bialas, A.R., Kamitaki, N., Martersteck, E.M., Trombetta, J.J., Weitz, D.A., Sanes, J.R., Shalek, A.K., Regev, A., McCarroll, S.A.: Highly parallel genome-wide expression profiling of individual cells using nanoliter droplets. Cell **161**(5), 1202–1214 (2015). doi:10.1016/j.cell.2015.05.002. 15334406
7. Zheng, G.X.Y., Terry, J.M., Belgrader, P., Ryvkin, P., Bent, Z.W., Wilson, R., Ziraldo, S.B., Wheeler, T.D., McDermott, G.P., Zhu, J., Gregory, M.T., Shuga, J., Montesclaros, L., Underwood, J.G., Masquelier, D.A., Nishimura, S.Y., Schnall-Levin, M., Wyatt, P.W., Hindson, C.M., Bharadwaj, R., Wong, A., Ness, K.D., Beppu, L.W., Deeg, H.J., McFarland, C., Loeb, K.R., Valente, W.J., Ericson, N.G., Stevens, E.A., Radich, J.P., Mikkelsen, T.S., Hindson, B.J., Bielas, J.H.: Massively parallel digital transcriptional profiling of single cells. Nature Communications **8**, 14049 (2017). doi:10.1038/ncomms14049. 065912
8. Sasagawa, Y., Danno, H., Takada, H., Ebisawa, M., Tanaka, K., Hayashi, T., Kurisaki, A., Nikaido, I.: Quartz-Seq2: A high-throughput single-cell RNA-sequencing method that effectively uses limited sequence reads. Genome Biology **19**(1), 1–24 (2018). doi:10.1186/s13059-018-1407-3
9. Shekhar, K., Lapan, S.W., Whitney, I.E., Tran, N.M., Macosko, E.Z., Kowalczyk, M., Adiconis, X., Levin, J.Z., Nemesh, J., Goldman, M., McCarroll, S.A., Cepko, C.L., Regev, A., Sanes, J.R.: Comprehensive Classification of Retinal Bipolar Neurons by Single-Cell Transcriptomics. Cell **166**(5), 1308–132330 (2016). doi:10.1016/j.cell.2016.07.054
10. Plass, M., Solana, J., Wolf, F.A., Ayoub, S., Misios, A., Glažar, P., Obermayer, B., Theis, F.J., Kocks, C., Rajewsky, N.: Cell type atlas and lineage tree of a whole complex animal by single-cell transcriptomics. Science **1723**(April), 1723 (2018). doi:10.1126/science.aaq1723
11. Regev, A., Teichmann, S.A., Lander, E.S., Amit, I., Benoist, C., Birney, E., Bodenmiller, B., Campbell, P., Carninci, P., Clatworthy, M., Clevers, H., Deplancke, B., Dunham, I., Eberwine, J., Eils, R., Enard, W., Farmer, A., Fugger, L., Göttgens, B., Hacohen, N., Haniffa, M., Hemberg, M., Kim, S., Klenerman, P., Kriegstein, A., Lein, E., Linnarsson, S., Lundberg, E., Lundeberg, J., Majumder, P., Marioni, J.C., Merad, M., Mhlanga, M., Nawijn, M., Netea, M., Nolan, G., Pe'er, D., Phillipakis, A., Ponting, C.P., Quake, S., Reik, W., Rozenblatt-Rosen, O., Sanes, J., Satija, R., Schumacher, T.N., Shalek, A., Shapiro, E., Sharma, P., Shin, J.W., Stegle, O., Stratton, M., Stubbington, M.J.T., Theis, F.J., Uhlen, M., Van Oudenaarden, A., Wagner, A., Watt, F., Weissman, J., Wold, B., Xavier, R., Yosef, N.: The human cell atlas. eLife **6**, 1–30 (2017). doi:10.7554/eLife.27041. 121202
12. Tabula Muris: Single-cell transcriptomic characterization of 20 organs and tissues from individual mice (2017). doi:10.1101/237446
13. Kiselev, V.Y., Yiu, A., Hemberg, M.: scmap: projection of single-cell RNA-seq data across data sets. Nature Methods **15**(5), 359–362 (2018). doi:10.1038/nmeth.4644
14. Douze, M., Schmid, C., Jégou, H., Douze, M., Schmid, C.: Product Quantization for Nearest Neighbor Search Herve. IEEE Transactions on Pattern Analysis and Machine Intelligence **33**(1), 117–128 (2011). doi:10.1109/TPAMI.2010.57. arXiv:1011.1669v3
15. Srivastava, D., Iyer, A., Kumar, V., Sengupta, D.: CellAtlasSearch: a scalable search engine for single cells. Nucleic Acids Research (May), 1–7 (2018). doi:10.1093/nar/gky421
16. Charikar, M.S.: Similarity estimation techniques from rounding algorithms. Proceedings of the thiry-fourth annual ACM symposium on Theory of computing - STOC '02, 380 (2002). doi:10.1145/509961.509965
17. Bezanson, J., Edelman, A., Karpinski, S., Shah, V.B.: Julia: A Fresh Approach to Numerical Computing. SIAM Review **59**(1), 65–98 (2017). doi:10.1137/141000671. arXiv:1411.1607v4
18. Norouzi, M., Punjani, A., Fleet, D.J.: Fast Exact Search in Hamming Space With Multi-Index Hashing. IEEE Transactions on Pattern Analysis and Machine Intelligence **36**(6), 1107–1119 (2014). doi:10.1109/TPAMI.2013.231. arXiv:1307.2982v3

19. Wagner, F., Yan, Y., Yanai, I.: K-nearest neighbor smoothing for single-cell RNA-Seq data (2017). doi:10.1101/217737

20. Chen, W., Li, Y., Easton, J., Finkelstein, D., Wu, G., Chen, X.: UMI-count modeling and differential expression analysis for single-cell RNA sequencing. Genome Biology **19**(1), 70 (2018). doi:10.1186/s13059-018-1438-9

21. Baron, M., Veres, A., Wolock, S.L., Faust, A.L., Gaujoux, R., Vetere, A., Ryu, J.H., Wagner, B.K., Shen-Orr, S.S., Klein, A.M., Melton, D.A., Yanai, I.: A Single-Cell Transcriptomic Map of the Human and Mouse Pancreas Reveals Inter- and Intra-cell Population Structure. Cell Systems **3**(4), 346–360 (2016). doi:10.1016/j.cels.2016.08.011. 15334406

22. 10x Genomics, Inc.: 1.3 Million Brain Cells from E18 Mice. Accessed: 2018-7-5 (2017). https://support.10xgenomics.com/single-cell-gene-expression/datasets/1.3.0/1M_neurons

23. Halko, N., Martinsson, P.G., Tropp, J.A.: Finding Structure with Randomness: Probabilistic Algorithms for Constructing Approximate Matrix Decompositions. SIAM Review **53**(2), 217–288 (2011). doi:10.1137/090771806. 0909.4061

24. Butler, A., Hoffman, P., Smibert, P., Papalexi, E., Satija, R.: Integrating single-cell transcriptomic data across different conditions, technologies, and species. Nature Biotechnology **36**(5), 411–420 (2018). doi:10.1038/nbt.4096

25. Li, H., Linderman, G.C., Szlam, A., Stanton, K.P., Kluger, Y., Tygert, M.: Algorithm 971. ACM Transactions on Mathematical Software **43**(3), 1–14 (2017). doi:10.1145/3004053. 1412.3510

26. Ji, J., Li, J., Yan, S., Zhang, B., Tian, Q.: Super-bit locality-sensitive hashing. Advances in Neural Information Processing Systems, 108–116 (2012)

27. Cohen, J.: Weighted kappa: Nominal scale agreement provision for scaled disagreement or partial credit. Psychological Bulletin **70**(4), 213–220 (1968). doi:10.1037/h0026256

28. McCarthy, D.J., Campbell, K.R., Lun, A.T.L., Wills, Q.F.: Scater: pre-processing, quality control, normalization and visualization of single-cell RNA-seq data in R. Bioinformatics **33**(8), 777 (2017). doi:10.1093/bioinformatics/btw777

29. Freeman, M.F., Tukey, J.W.: Transformations Related to the Angular and the Square Root. The Annals of Mathematical Statistics **21**(4), 607–611 (1950). doi:10.1214/aoms/1177729756. arXiv:1011.1669v3

30. Picelli, S., Björklund, Å.K., Faridani, O.R., Sagasser, S., Winberg, G., Sandberg, R.: Smart-seq2 for sensitive full-length transcriptome profiling in single cells. Nature Methods **10**(11), 1096–1098 (2013). doi:10.1038/nmeth.2639. NIHMS150003

31. Sinha, D., Kumar, A., Kumar, H., Bandyopadhyay, S., Sengupta, D.: dropClust: efficient clustering of ultra-large scRNA-seq data. Nucleic Acids Research (January), 1–9 (2018). doi:10.1093/nar/gky007

32. Zitnik, M., Sosic, R., Leskovec, J.: Prioritizing network communities (2018), 1–9 (2018). doi:arXiv:1805.02411v2. 1805.02411

33. Van Der Maaten, L.: Accelerating t-SNE using Tree-Based Algorithms. Journal of Machine Learning Research **15**, 1–21 (2014). doi:10.1007/s10479-011-0841-3. 1307.1662

34. Jiang, L., Chen, H., Pinello, L., Yuan, G.C.: GiniClust: Detecting rare cell types from single-cell gene expression data with Gini index. Genome Biology **17**(1), 1–13 (2016). doi:10.1186/s13059-016-1010-4

35. Li, H., Courtois, E.T., Sengupta, D., Tan, Y., Chen, K.H., Goh, J.J.L., Kong, S.L., Chua, C., Hon, L.K., Tan, W.S., Wong, M., Choi, P.J., Wee, L.J.K., Hillmer, A.M., Tan, I.B., Robson, P., Prabhakar, S.: Reference component analysis of single-cell transcriptomes elucidates cellular heterogeneity in human colorectal tumors. Nature Genetics **49**(5), 708–718 (2017). doi:10.1038/ng.3818

36. Berry, M.W., Drmac, Z., Jessup, E.R.: Matrices, Vector Spaces, and Information Retrieval. SIAM Review **41**(2), 335–362 (1999). doi:10.1137/S0036144598347035. arXiv:1011.1669v3

37. Johnson, W.E., Li, C., Rabinovic, A.: Adjusting batch effects in microarray expression data using empirical Bayes methods. Biostatistics **8**(1), 118–127 (2007). doi:10.1093/biostatistics/kxj037

38. Haghverdi, L., Lun, A.T.L., Morgan, M.D., Marioni, J.C.: Batch effects in single-cell RNA-sequencing data are corrected by matching mutual nearest neighbors. Nature Biotechnology **36**(5), 421–427 (2018). doi:10.1038/nbt.4091

39. Risso, D., Perraudeau, F., Gribkova, S., Dudoit, S., Vert, J.-P.: A general and flexible method for signal extraction from single-cell RNA-seq data. Nature Communications **9**(1), 284 (2018). doi:10.1038/s41467-017-02554-5

40. Lun, A.T.L., McCarthy, D.J., Marioni, J.C.: A step-by-step workflow for low-level analysis of single-cell RNA-seq data. F1000Research **5**, 2122 (2016). doi:10.12688/f1000research.9501.1

41. Brennecke, P., Anders, S., Kim, J.K., Kołodziejczyk, A.a., Zhang, X., Proserpio, V., Baying, B., Benes, V., Teichmann, S.a., Marioni, J.C., Heisler, M.G.: Accounting for technical noise in single-cell RNA-seq experiments. Nature Methods **10**(11), 1093–1095 (2013). doi:10.1038/nmeth.2645

42. Grün, D., Kester, L., van Oudenaarden, A.: Validation of noise models for single-cell transcriptomics. Nature Methods **11**(6), 637–640 (2014). doi:10.1038/nmeth.2930

43. Bianconi, E., Piovesan, A., Facchin, F., Beraudi, A., Casadei, R., Frabetti, F., Vitale, L., Pelleri, M.C., Tassani, S., Piva, F., Perez-Amodio, S., Strippoli, P., Canaider, S.: An estimation of the number of cells in the human body. Annals of Human Biology **40**(6), 463–471 (2013). doi:10.3109/03014460.2013.807878

44. Koster, J., Rahmann, S.: Snakemake–a scalable bioinformatics workflow engine. Bioinformatics **28**(19), 2520–2522 (2012). doi:10.1093/bioinformatics/bts480

45. Gentleman, R.C., Carey, V.J., Bates, D.M., Bolstad, B., Dettling, M., Dudoit, S., Ellis, B., Gautier, L., Ge, Y., Gentry, J., Hornik, K., Hothorn, T., Huber, W., Iacus, S., Irizarry, R., Leisch, F., Li, C., Maechler, M., Rossini, A.J., Sawitzki, G., Smith, C., Smyth, G., Tierney, L., Yang, J.Y., Zhang, J.: Bioconductor: open software development for computational biology and bioinformatics. Genome Biology **5**(10), 80 (2004). doi:10.1186/gb-2004-5-10-r80

46. Kluyver, T., Ragan-kelley, B., Pérez, F., Granger, B., Bussonnier, M., Frederic, J., Kelley, K., Hamrick, J., Grout, J., Corlay, S., Ivanov, P., Avila, D., Abdalla, S., Willing, C.: Jupyter Notebooks—a publishing format for reproducible computational workflows. Positioning and Power in Academic Publishing: Players, Agents and Agendas, 87–90 (2016). doi:10.3233/978-1-61499-649-1-87

Additional Files

Additional file 1 — Additional figures
Additional plots referred in the manuscript (PDF).

Additional file 2 — Analysis notebook
Compiled Jupyter notebook to run analysis of experiments (HTML).

Additioanl file 3 — Experiment scripts
Archived script files to reproduce the experiments (TAR).