A comparative study of machine learning algorithms in predicting severe complications

after bariatric surgery

Yang Cao[1,2*], Xin Fang[2*], Johan Ottosson[3], Erik Näslund[4], Erik Stenberg[3]

[1]Clinical Epidemiology and Biostatistics, School of Medical Sciences, Örebro University,

Örebro, Sweden;

[2]Unit of Biostatistics, Institute of Environmental Medicine, Karolinska Institutet, Stockholm,

Sweden;

[3]Department of Surgery, Faculty of Medicine and Health, Örebro University, Örebro,

Sweden;

[4]Division of Surgery, Department of Clinical Sciences, Danderyd Hospital, Karolinska

Institutet, Stockholm, Sweden

[*]**For correspondence**: xin.fang@ki.se; yang.cao@ki.se

Competing interest: The authors declare that no competing interests exist.

Funding: This work was supported by grants from the Örebro Region County Council (E.S.),

Örebro University (E.S.), Stockholm County Council (E.N.), SRP Diabetes (E.N.) and the

NovoNordisk foundation (E.N.).

Abstract

Accurate models to predict severe postoperative complications could be of value in the

preoperative assessment of potential candidates for bariatric surgery. Traditional statistical

methods have so far failed to produce high accuracy. To find a useful algorithm to predict the

risk for severe complication after bariatric surgery, we trained and compared 29 supervised

machine learning (ML) algorithms using information from 37,811 patients operated with a

bariatric surgical procedure between 2010 and 2014 in Sweden. The algorithms were then

tested on 6,250 patients operated in 2015. Most ML algorithms showed high accuracy (>90%)

and specificity (>0.9) in both the training and test data. However, none achieved an acceptable

sensitivity in the test data. ML methods may improve accuracy of prediction but we did not

yet identify one with a high enough sensitivity that can be used in clinical praxis in bariatric

surgery. Further investigation on deeper neural network algorithms is needed.

Introduction

Morbid obesity is a global public health threat of growing proportions(Ng et al., 2014).
Bariatric surgery offers the best chance for long-term weight-loss and resolution of
comorbidities(Sjostrom et al., 2004). Although modern bariatric surgery is considered to be
safe, severe postoperative complications still occur(Finks et al., 2011; Stenberg et al., 2014).
Accurate prediction models for severe postoperative complications could aid preoperative
decision making for surgeons, anesthesiologists and patients. These models could also serve
as basis for case-mix comparisons between different centers. Some prediction models based
on linear regression of patient-specific data allow for relatively simple and interpretable
inference; however, they have so far been proven inaccurate and can thus not be used in
clinical practice(Geubbels et al., 2015; Stenberg et al., 2018).

In contrast, some machine learning (ML) methods have been shown to provide quite accurate
predictions, and have increasingly been used in diagnosis and prognosis of different diseases
and health conditions(Anderin et al., 2015; Kourou et al., 2015; Pan et al., 2017). ML
methods are data-driven analytic approaches that specialize in the integration of multiple risk
factors into a predictive algorithm(Passos et al., 2016). Over the past several decades, ML
tools have become more and more popular for medical researchers. A variety of ML
algorithms, including artificial neural networks, decision trees, Bayesian networks, and
support vector machines (SVMs) have been widely applied with the aims to detect key
features of the patient conditions and to model the disease progression after treatment from
complex health information and medical datasets. The application of different ML methods
for feature selection and classification in multidimensional heterogeneous data can provide
promising tools for inference in medical practices. These highly nonlinear approaches have
been utilized in medical research for the development of predictive models, resulting in
effective and accurate decision making(Ali, 2017; Jiang et al., 2017).

Although new and improved software packages have significantly eased the implementation

burden for many ML methods in recent years, few studies have used ML methods to examine

the risk factors or predict the prognosis after bariatric surgery, including diabetes

remission(Hayes et al., 2011; Pedersen et al., 2016), complication(Razzaghi et al., 2017),

weight status(Piaggi et al., 2010; Thomas et al., 2017), and adverse events and death(Ehlers et

al., 2017). Even though there is evidence that the use of ML methods can improve our

understanding of postoperative progression of bariatric surgery, an appropriate level of

validation is needed in order for these methods to be considered in the clinical practice.

In this study, we compared different conventional supervised ML algorithms in the modeling

of severe postoperative complication after bariatric surgery. The study was based on the data

from the Scandinavian Obesity Surgery Registry (SOReg). The SOReg is a national quality

and research register, covering virtually all bariatric surgical procedures performed in Sweden

since 2010. The register has been described in detail elsewhere(Hedenbro et al., 2015;

Stenberg et al., 2014), and a prediction model based on logistic regression for the same group

of patients has been described previously(Stenberg et al., 2018). The aim of the current study

was to find an algorithm or algorithms that perform well not only on the training data but also

on the test data that were not used to train the algorithms.

Results

Baseline characteristics of the patients in the training data and the test data are presented in Tables 1 and 2. The percentages of severe complication in the two data sets are 3.2% and 3.0%, respectively. No statistically significant difference was found for percentages of severe complication between the two data sets (Pearson chi-square = 0.8283, p = 0.363).

Univariable analyses indicate that differences of mean age, mean body mass index (BMI), median HbA1c, percentages of comorbidities for hypertension, diabetes, dyslipidaemia, and previous venous thromboembolism, and percentage of revisional surgery between the patients presenting and without severe complication are statistically significant in the training data (Table 1). In the test data, the statistically significant differences were found for age, waist circumference (WC), HbA1c, dyslipidaemia, and revisional surgery (Table 2).

Multivariable logistic regression analysis for the same data was published elsewhere(Stenberg et al., 2018). In brief, revisional surgery, age, low BMI, operation year, WC, and dyspepsia were associated with the an increased risk for severe postoperative complication, however, the performance of the multivariable logistic regression model for predicting the risk in individual patient case was poor. Validation of the model tested on patients operated in 2015 resulted in an area under the receiver operating characteristic (ROC) curve of only 0.53, a Hosmer-Lemshow goodness of fit 17.91 (p=0.056) and Nagelkerke R^2 0.013(Stenberg et al., 2018).

In current study, 19 supervised machine learning algorithms were compared and ten of them were also trained using the synthetic minority oversampling technique (SMOTE), resulting in 29 ML algorithms. Most of the machine learning algorithms shown high accuracy (>90%) and specificity (>0.9) for both training data and test data (Table 3), except that bagging linear discriminant analysis (LDA), bagging quadratic discriminant analysis (QDA), adaptive boosting (AdaBoost) support vector machine (SVM), and multilayer perceptron (MLP) shown

low accuracy (<60%) for SMOTE training data, and oversampling-based bagging QDA

shown low accuracy for test data (accuracy = 56.1%) (Table 3).

Although most of the algorithms shown low sensitivity for both the training data and the test

data, some of them exhibited promising prediction ability in the training data. Sensitivities of

oversampling-based bagging QDA, random forest, AdaBoost extremely randomized

(AdaExtra) trees, AdaBoost gradient regression (AdaGradient) trees, bagging k-nearest

neighbor (KNN), and deep learning neural network (NN) are 0.707, 0.965, 0.980, 0.968,

0.996, and 0.757 for SMOTE training data, respectively (Table 3). Even for test data,

oversampling-based bagging QDA and AdaBoost SVM show significant higher prediction

ability than other algorithms. The sensitivities of the two algorithms are 0.417 and 0.364,

respectively (Table 3). However, they still do not achieve an acceptable level for practical

application.

When considering sensitivity and specificity together, most of the algorithms did not show

better prediction ability than a random predictor, i.e. an area under ROC curve of 0.5. The

areas under the ROC curves for all the algorithms, except for oversampling-based random

forest, AdaExtra trees, and adaGradient trees, and KNN, are around 0.5 (Figures 1 - 4).

Although oversampling-based random forest, AdaExtra trees, AdaGradient trees, and KNN

show outstanding prediction ability on the SMOTE training data (areas under ROC curves are

above 0.9), their performance on the test data are not optimistic (Figures 2 and 3).

The performance of the three regression-based algorithms (logistic regression, LDA, QDA),

SVM, and the two neural network-based algorithms (MLP and deep learning NN) was poor in

any situation. However the bagging MLP and deep learning NN outperforms the tree-based

algorithms (Figures 2 and 4) for test data, their areas under ROC curves for the test data are

0.58 and 0.56, respectively (Figure 4) that are greatest among all the algorithms.

Discussion

Historically, laparoscopic gastric bypass has for a long time been the most common bariatric procedure in Sweden, although laparoscopic sleeve gastrectomy has increased in popularity over more recent years(Stenberg et al., 2014; The international federation for the surgery of obesity and metabolic disorders, 2017). The surgical technique is highly standardized with more than 99% of all gastric bypass procedure being the antecolic, antegastric, laparoscopic gastric bypass (so called Lönnroth technique)(Olbers et al., 2003). Virtually all patients receive pharmacologic prophylaxis for deep venous thrombosis and intraoperative antibiotic prophylaxis(Hedenbro et al., 2015; Stenberg et al., 2014). Patients who have bariatric surgery are exposed to the risk of having postoperative complications, which may increase the complexity of managing safety and healthcare costs.

Previous studies on postoperative complications of bariatric surgery have mainly used scoring for identifying patients who are more likely to have complications after surgery. However, these methods are not sensitive enough for clinical application(Geubbels et al., 2015; Stenberg et al., 2018). The potential of ML tools as clinical decision support in identifying risk factors and predicting health outcomes is therefore worth investigation on complications associated with bariatric surgery. To our knowledge, there is only one study that compared the performance of different ML algorithms in predicting the postoperative complications in imbalanced bariatric surgery data set(Razzaghi et al., 2017). Although the study indicates that the combination of a suitable feature selection method with ensemble ML algorithm equipped with SMOTE can achieve higher performance in predictive models for bariatric surgery risks, the ML algorithms were not validated using external test data. After all, for prediction purpose, we are not very interested in whether or not an algorithm accurately predicts severe complication for patients used to train the algorithm, since we already know which of those

patients have severe complications, but are interested in whether the algorithms may

accurately predict the future patients based on their clinical measurements.

Our study compared in total 29 ML algorithms using real world data. Although the

sensitivities of the algorithms were generally low, the study indicates that some ML

algorithms were able to achieve higher accuracy than tradition logistic regression

models(Geubbels et al., 2015; Stenberg et al., 2018). Four of 29 algorithms were able to

achieve high sensitivity (>0.95) and two achieved moderate sensitivity (>0.70) in the training

data, including three tree-based algorithms, bagging KNN, bagging QDA, and deep learning

NN. We should notice that all the high or moderate sensitivities were obtained from SMOTE

training data and/or using ensemble algorithms. Our findings support the previous study that

ensemble ML algorithms equipped with SMOTE can achieve higher performance metrics for

imbalanced data(Razzaghi et al., 2017).

Despite showing promising capability of prediction in training data, none of the 29 ML

algorithms satisfactorily predicted severe postoperative complication after bariatric surgery in

the test data. Why did the algorithms do a poor job of predicting the patients who had severe

complication in test data? One potential explanation for this may be related to the limited

number of severe postoperative complication in the current dataset, which cannot reveal the

underlying relationship between risk factors and adverse health outcomes. Although there are

several known risk factors, each of them only imposes a small increase in the risk for

postoperative complication(Finks et al., 2011; Longitudinal Assessment of Bariatric Surgery

et al., 2009; Maciejewski et al., 2012; Stenberg et al., 2014). Another likely explanation may

be that preoperatively known variables are insufficient to predict postoperative complications.

In previous studies, the highest accuracy for prediction of postoperative complication has

been models including operation data, mainly intraoperative complication and conversion to

open surgery(Geubbels et al., 2015; Stenberg et al., 2014). Although including intraoperative

adverse events and conversion to open surgery may improve the accuracy of prediction

models, such models would not be useful in the preoperative assessment for patients or for

case mix comparisons. Furthermore, because the algorithms try to minimize the total error

rate out of all classes, irrespective of which class the errors come from, they are not

appropriate for imbalanced data such as what we used in our study(Maalouf et al., 2018).

Compared with traditional generalized linear predictive models, non-linear ML algorithms are

more flexible and may achieve higher accuracy but at the expense of less interpretability.

Although there are interpretable models such as regression, Naïve Bayes, decision tree and

random forests, several models are not designed to be interpretable(James et al., 2013). The

aim of the methods is to extract information from the trained model to justify their prediction

outcome, without knowing how the model works in details. The trade-off between prediction

accuracy and model interpretability is always an issue when we have to consider in building a

ML algorithm. A common quote on model interpretability is that with an increase in model

complexity, model interpretability goes down at least as fast. Fully nonlinear methods such as

bagging, boosting and support vector machines with nonlinear kernels are highly flexible

approaches that are harder to interpret. Deep learning algorithms are notorious for their un-

interpretability due to the sheer number of parameters and the complex approach to extracting

and combining features. Feature importance is a basic (and often free) approach to

interpreting the model. Although some nonlinear algorithms such as tree-based algorithms

(e.g. random forest) may allow to obtain information on the feature importance, we cannot

obtain such information from many ML algorithms.

Therefore, recent attempts have been made to improve interpretability for the black-box

algorithms even such as deep learning. Local interpretable model-agnostic explanations

(LIME) is one of them to make these complex models at least partly understandable. LIME is

a more general framework that aims to make the predictions of 'any' ML model more

interpretable. In order to remain model-independent, LIME works by modifying the input to

the model locally(Mishra et al., 2017; Ribeiro et al., 2016). So instead of trying to understand

the entire model at the same time, a specific input instance is modified and the impact on the

predictions are monitored.

Regarding specific algorithm, though their motivations differ, the logistic regression and LDA

or QDA methods are closely connected, therefore we were not surprised that LDA or QDA

did not show significant improvement in prediction than logistic regression(Stenberg et al.,

2018). KNN takes a complete different approach from classification which is completely non-

parametric(James et al., 2013). Therefore, we can expect it to outperform parametric models

such as logistic and LDA. However, KNN cannot tell us which predictor are of importance.

QDA serves as a compromise between the non-parametric KNN and the LDA and logistic

regression. Though not as flexible as KNN, QDA can perform better in the limited training

data situation. MLP is a class of feedforward artificial neural network, which consists of at

least three layers of nodes. Its multiple layers and non-linear activation can distinguish data

that is not linearly separable. Deep learning NNs are high-level NNs including convolutional

NN and recurrent NN et al. In our study, the deep learning NN with five hidden layers

outperforms the conventional MLP with two hidden layers, especially on SMOTE training

data (areas under ROC curves are 0.67 vs. 0.37), which deserves further investigation in the

future.

Our study demonstrates that ensemble learning may improve predictions by combining

several base algorithms. However, usually there are several ensemble methods available, such

as bagging, boosting, and stacking(Zhou, 2012). A number of studies have shown that, when

decomposing a classifier's error into bias and variance terms, AdaBoost is more effective at

reducing bias, bagging is more effective at reducing variance, and stacking may improve

predictions in general(Kotsiantis et al., 2007). There is no golden rule on which method works

best. The choice of specific ensemble methods is case by case and depends enormously on the

data.

There are some limitations in our study. First, the study was limited to data registered within

the SOReg. Cardiovascular and pulmonary comorbidities other than sleep apnea are not

mandatory variables within the registry and could thus not be included in the model. Although

these comorbidities are known risk factors for postoperative complications(Finks et al., 2011;

Gupta et al., 2011; Maciejewski et al., 2012), they are not highly prevalent in European

studies(Geubbels et al., 2015). Second, although we compared 29 ML algorithms investigated

in our study, they are convenient and feasible methods for general medical researchers.

Because of computational complexity and less interpretability, many complicated and

advanced ML algorithms were not yet investigated in our study. However, our study at least

points out a promising way for future investigations, i.e. deep learning NN equipped with

SMOTE. Last but not the least, the exhaustive grid search was used in our hyperparameter

optimization, which is extremely resource consuming and not optimal for complex ML

algorithms, therefore other advanced methods such as gradient-based or evolutionary

optimization would be considered in the future.

Conclusion

ML algorithms have the potential to improve the accuracy in predicting the severe

postoperative complication among the 44,061 Swedish bariatric surgery patients during 2010

- 2015. Because the imbalance nature of the data where the number of the interested outcome

is relative small, oversampling technique needs to be adopted to balance the two outcomes

(presenting or without severe complication). Ensemble algorithms outperform base

algorithms. In general, deep learning NN results in better predictions for unseen patients.

Materials and Methods

Patients and features

Patients registered in the SOReg between 2010 and 2015 were included in the present study. All patients who underwent a bariatric procedure between 2010 and 2014 were used as training data in the ML. Data from patients who underwent a bariatric surgical procedure in 2015 were used as test data to validate the algorithm's performance in predicting sever postoperative complication within 30 days after surgery. In total, 37,811 and 6,250 bariatric patients from SOReg were included in the training data and test data, respectively. In total 16 features were included in ML, including five continuous features (age, HbA1c, body mass index [BMI], waist circumstance [WC]), and operation year) and 11 binary features (sleep apnoea, hypertension, diabetes, dyslipdaemia, dyspepsia, depression, musculoskeletal pain, previous venous thromboembolism, revisional surgery, and severe postoperative complication). The last binary feature, i.e. severe postoperative complication, was used as output variable for the supervised ML classifiers. All the continuous features were standardized to have mean 0 and standard deviation 1 before they enter the classifier. HbA1c was log transformed before standardization because of its asymmetric distribution.

Descriptive and inferential statistical methods

Demographic and baseline characteristics of the patients were presented using descriptive statistical methods. Continuous variables were portrayed as mean and standard deviation (SD), or median and interquartile range where suitable, while categorical variables were outlined as counts and percentages. The difference between the patient presenting and without severe postoperative complication was tested using the Student's t-test or the Mann-Whitney U test for normally or asymmetrically distributed continuous variables, respectively; and χ^2 test was used for binary variables.

ML algorithms

In current study, eight base ML algorithms, i.e. logistic regression, linear discriminant

analysis (LDA), quadratic discriminant analysis (QDA), decision tree, k-nearest neighbor

(KNN), support vector machine (SVM), multilayer perceptron (MLP) and deep learning

neural network (NN), and 11 ensemble algorithms, i.e. adaptive boosting (AdaBoost) logistic

regression, bagging LDA, bagging QDA, random forest, extremely randomized (Extra) trees,

AdaBoost Extra trees, gradient regression tree, AdaBoost Gradient trees, bagging KNN,

AdaBoost SVM, and bagging MLP, were implemented.

Ensemble learning

In order to improve generalizability and robustness over a single ML algorithm, we also used

ensemble methods to combine multiple base or ensemble algorithms. Five ensemble methods

were applied in our study:

• AdaBoost for logistic regression, Extra trees, gradient regression trees, and

SVM(Schapire, 2003);

• bagging for LDA, QDA, KNN, and MLP(Kotsiantis et al., 2007);

• random forests for decision tree(Liaw & Wiener, 2002);

• Extra trees for decision tree(Geurts et al., 2006);

• gradient boosted regression trees for decision tree(Friedman, 2002).

Initialization and optimization of hyperparameters

ML algorithms involve a number of hyperparameters that have to be fixed before running the

algorithms. In contrast to the parameters that are learned by training, hyperparameters

determine the structure of a ML algorithm and how the algorithm is trained. The initial values

of the hyperparmeters for each ML algorithm used in our study are the default values

specified in the employed software packages based on recommendations or experience(Probst

et al., 2018). In KNN algorithm, ten nearest neighbors were used. In MLP algorithm, two

hidden layer were used with five and two neurons, respectively. In deep learning NN

algorithm, the sequential linear stack of layers was used, with five hidden layers (three dense

layers and two dropout regularization layers). For the detailed hyperparameterization of the

algorithms, please refer the scikit-learn user manual at http://scikit-

learn.org/stable/supervised_learning.html(Pedregosa et al., 2011) and the Keras

Documentation at https://keras.io/.

The hyperparameter optimization is defined as a tuple of hyperparameters that yields an

optimal algorithm which minimizes a predefined loss function (i.e. cross entropy loss function

in our study, see Annex 1) on a held-out validation set of the training data. The most wildly

used however exhaustive grid search was used to perform hyperparameter optimization in our

study, which specified subset of the hyperparameter space of a ML algorithm and was

evaluated by cross-validation using the training data(Bergstra & Bengio, 2012).

Cross validation

For training data, k-fold ($k = 5$ in our analyses) cross-validated predictions were used as

predicted values. This approach involves randomly dividing the training data into k groups, or

folds, of approximately equal size. Then an algorithm is trained on the k-1 folds and the rest

one fold is retained as the validation fold for testing the algorithm. The process is repeated

until the algorithm is validated on all the k folds. For each patient in the training data, the

predicted value that he/she obtained is the prediction when he/she was in the validation fold.

Therefore, only cross-validation strategies that assign all patients to a validation fold exactly

once can be used for the cross-validated prediction(James et al., 2013).

SMOTE

The bariatric surgery data is extreme imbalanced, i.e. only 1,408 of 44,061 (3.2%) patients

experienced severe postoperative complication after bariatric surgery. The imbalance often

results in serious bias in the performance metrics(Batista et al., 2004). Therefore, we

performed synthetic minority oversampling technique (SMOTE) to tackle the

imbalance(Chawla et al., 2002). SMOTE generates a synthetic instance by interpolating m

instances (for a given integer value m) of the minority class that lies close enough to each

other to achieve the desired ratio between the majority and minority classes. In our study, a

1:1 ratio between the patients presenting severe postoperative complication and without

severe postoperative complication was achieved in the training data, i.e. SMOTE training

data. The aforementioned nine of the 11 ensemble ML algorithms and the deep learning NN

were also implemented for the SMOTE training data.

Performance metrics

The performance of the in total 29 ML algorithms were evaluated using accuracy, sensitivity,

specificity, and area under the receiver operating characteristic (ROC) curve. ROC curve

shows the trade-off that the algorithms set the different threshold values for the posterior

probability for the prediction.

Terminology and derivations of accuracy, sensitivity, specificity, and area under the ROC

curve are given in Annex 1.

Software and hardware

The descriptive and inferential statistical analyses were performed using Stata 15.1

(StataCorp, College Station). ML algorithms were achieved using packages scikit-learn 0.19.1

(scikit-learn, http://scikit-learn.org/)(Pedregosa et al., 2011) and Keras 2.1.6 (Keras,

https://keras.io/) in Python 3.6 (Python Software Foundation, https://www.python.org/).

All the computation was conducted in a computer with 64-bit Windows 7 Enterprise operation

system (Service Pack 1), Intel ® Core ^{TM} i5-4210U CPU @ 2.40 GHz, and 16.0 GB installed

random access memory.

Author contributions

346 Yang Cao, Xin Fang, Conceptualization, Data curation, Software, Formal analysis, Writing-

347 original draft; Yang Cao, Supervision, Investigation, Visualization, Methodology; Erik

348 Stenberg Data curation, Conceptualization, Validation, Investigation, Writing-original draft;

349 Johan Ottosson, Erik Näslund, Investigation, Writing-original draft.

Author ORCIDs

352 Yang Cao, https://orcid.org/0000-0002-3552-9153

353 Xin Fang, https://orcid.org/0000-0002-6846-7147

354 Johan Ottosson, https://orcid.org/0000-0002-9243-2390

355 Erik Näslund, https://orcid.org/0000-0002-0166-6344

356 Erik Stenberg, https://orcid.org/0000-0001-9189-0093

Ethics

359 The study was approved by the Regional Ethics Committee in Stockholm and was conducted

360 in accordance with the ethical standards of the Helsinki Declaration (6th revision).

          Table 1. Base line characteristics of the training patients

	All N=37,811	No serious complication N=36,591 (96.8%)	Having serious complication N=1,220 (3.2%)	p-value
Age in years, mean ± SD	41.2 ± 11.2	41.1 ± 11.2	42.9 ± 10.7	<0.001[*]
Sex, n (%)				
Female	28,682 (75.9%)	27,766 (75.9%)	916 (75.1%)	0.521[†]
Male	9,129 (24.1%)	8,825 (24.1%)	304 (24.9%)	
BMI in kg/m^2, mean ± SD	42.12 ± 5.66	42.13 ± 5.66	41.79 ± 5.58	0.0355[*]
WC in cm, mean ± SD	126.0 ± 14.0	126.0 ± 14.0	126.2 ± 13.8	0.6018[*]
HbA1c, median (P25, P75)	38 (35, 42)	38 (38, 32)	38 (35, 43)	0.0090[‡]
Comorbidity, n (%)				
Sleep apnoea	3,792 (10.0%)	3,656 (10.0%)	136 (11.2%)	0.186[†]
Hypertension	9,760 (25.8%)	9,404 (25.7%)	356 (29.2%)	0.006[†]
Diabetes	5,407 (14.3%)	5,204 (14.2%)	203 (16.6%)	0.018[†]
Dyslipidaemia	3,802 (10.1%)	3,667 (10.0%)	135(11.1%)	0.233[†]
Dyspepsia	3,970 (10.5%)	3,803 (10.4%)	167 (13.7%)	<0.001[†]
Depression	5,609 (14.8%)	5,409 (14.8%)	200 (16.4%)	0.119[†]
Musculoskeletal pain	4,905 (13.0%)	4,754 (13.0%)	151 (12.4%)	0.529[†]
Previous venous thromboembolism	918 (2.4%)	875 (2.39%)	43 (3.52%)	0.011[†]
Revisional surgery	1,367 (3.6%)	1,261 (3.5%)	106 (8.7%)	<0.001[†]

363   SD: standard deviation; BMI, body mass index; WC, waist circumference; P25, the 25th percentile;

364   P75, the 75th percentile.

365   [*]t-test was used; [†]χ^2 test was used; [‡]Mann-Whitney U test was used.

366   Table 2. Base line characteristics of the test patients

	All N=6,250	No serious complication N=6,062 (97.0%)	Having serious complication N=188 (3.0%)	p-value
Age in years, mean ± SD	41.2 ± 11.5	41.2 ± 11.5	42.9 ± 11.8	0.0423*
Sex, n (%)				
Female	4,832 (77.3%)	4,682 (77.2%)	150 (79.8%)	0.411†
Male	1,418 (22.7%)	1,380 (22.8%)	38 (20.2%)	
BMI in kg/m^2, mean ± SD	41.22 ± 5.87	41.20 ± 5.89	41.95 ± 5.40	0.0848*
WC in cm, mean ± SD	123.3 ± 14.1	123.2 ± 14.0	126.2 ± 14.7	0.0086*
HbA1c, median (P25, P75)	37 (34, 41)	37 (34, 41)	38 (35, 44)	0.0017‡
Comorbidity, n (%)				
Sleep apnoea	622 (10.0%)	607 (10.0%)	15 (8.0%)	0.359†
Hypertension	1,563 (25.0%)	1,506 (24.8%)	57 (30.3%)	0.088†
Diabetes	761 (12.2%)	734 (12.1%)	27 (14.4%)	0.352†
Dyslipidaemia	518 (8.3%)	493 (8.13%)	25 (13.3%)	0.011†
Dyspepsia	645 (10.3%)	620 (10.2%)	25 (13.3%)	0.173†
Depression	1,096 (17.5%)	1,053 (17.4%)	43 (22.9%)	0.051†
Musculoskeletal pain	1,315 (21.0%)	1,268 (20.9%)	47 (25.0%)	0.176†
Previous venous thromboembolism	182 (2.9%)	177 (2.99%)	5 (2.7%)	0.834†
Revisional surgery	61 (1.0%)	54 (0.9%)	7 (3.7%)	<0.001†

367   SD: standard deviation; BMI, body mass index; WC, waist circumference; P25, the 25th percentile;

368   P75, the 75th percentile.

369   *t-test was used; †χ^2 test was used; ‡Mann-Whitney U test was used.

Table 3. Performance of the algorithms

Algorithm	Training data			Test data		
	Accuracy (%)	Specificity	Sensitivity	Accuracy (%)	Specificity	Sensitivity
Logistic	96.9	1.000	0.000	97.1	1.000	0.000
AdaBoost Logistic	96.9	1.000	0.000	97.1	1.000	0.000
Oversampling AdaBoost Logistic	46.5	0.382	0.547	76.9	0.786	0.227
LDA	96.9	1.000	0.000	97.1	1.000	0.000
Bagging LDA	96.9	1.000	0.000	97.1	1.000	0.000
Oversampling Bagging LDA	46.3	0.370	0.556	79.0	0.807	0.212
QDA	92.8	0.954	0.107	94.7	0.973	0.076
Bagging QDA	93.2	0.958	0.103	95.5	0.982	0.068
Oversampling bagging QDA	55.4	0.401	0.707	56.1	0.566	0.417
Decision tree	93.5	0.963	0.038	93.1	0.958	0.045
Random Forest	96.9	1.000	0.000	97.0	1.000	0.000
Oversampling Random Forest	94.5	0.925	0.965	96.6	0.995	0.008
ExtRa Trees	96.6	0.997	0.006	96.7	0.996	0.015
AdaBoost ExtRa Trees	96.6	0.996	0.004	96.6	0.995	0.008
Oversampling AdaExtra Trees	93.0	0.881	0.980	95.3	0.982	0.015
Gradient regression trees	96.9	1.000	0.000	97.1	1.000	0.008
AdaBoost Gradient trees	96.8	0.998	0.000	97.0	0.999	0.000
Oversampling AdaGradient trees	97.0	0.972	0.968	97.0	0.999	0.000
KNN	96.9	1.000	0.000	97.1	1.000	0.000
Bagging KNN	96.9	1.000	0.000	97.1	1.000	0.000
Oversampling Bagging KNN	79.4	0.592	0.996	82.3	0.841	0.235
SVM	96.9	1.000	0.000	97.1	1.000	0.000
AdaBoost SVM	96.9	1.000	0.000	97.1	1.000	0.000
Oversampling AdaBoost SVM	53.6	0.397	0.675	60.6	0.614	0.364
MLP	96.9	1.000	0.000	97.1	1.000	0.000
Bagging MLP	96.9	1.000	0.000	97.1	1.000	0.000
Oversampling bagging MLP	45.7	0.226	0.687	96.6	0.994	0.015
Deep learning NN	96.9	1.000	0.000	97.1	1.000	0.000
Oversampling deep learning NN	62.1	0.484	0.757	93.3	0.959	0.068

372 AdaBoost, adaptive boosting; LDA, linear discriminant analysis; QDA, quadratic discriminant
373 analysis; ExtRa, extremely randomized; AdaExtra, adaptive boosting extremely randomized;
374 AdaGradient, adaptive boosting gradient; KNN, k-nearest neighbor; SVM, support vector machine;
375 MLP, multilayer perceptron; NN, neural network

377
378 Figure 1. ROC curves of logistic regression, LDA and QDA

380   Figure 2. ROC curves of tree-based algorithms

Figure 3. ROC curves of KNN and SVM

Figure 4. ROC curves of neural network algorithms

References

Ali, A.-R. (2017). Deep Learning in Oncology–Applications in Fighting Cancer.   Retrieved from
https://www.techemergence.com/deep-learning-in-oncology/
Anderin, C., Gustafsson, U. O., Heijbel, N., & Thorell, A. (2015). Weight loss before bariatric surgery
and postoperative complications: data from the Scandinavian Obesity Registry (SOReg). *Ann*
Surg, 261(5), 909-913.
Batista, G. E., Prati, R. C., & Monard, M. C. (2004). A study of the behavior of several methods for
balancing machine learning training data. *ACM SIGKDD explorations newsletter, 6*(1), 20-29.
Bergstra, J., & Bengio, Y. (2012). Random search for hyper-parameter optimization. *Journal of*
Machine Learning Research, 13(Feb), 281-305.
Chawla, N. V., Bowyer, K. W., Hall, L. O., & Kegelmeyer, W. P. (2002). SMOTE: Synthetic minority
over-sampling technique. *Journal of Artificial Intelligence Research, 16*, 321-357.
Ehlers, A. P., Roy, S. B., Khor, S., Mandagani, P., Maria, M., Alfonso-Cristancho, R., & Flum, D. R.
(2017). Improved Risk Prediction Following Surgery Using Machine Learning Algorithms.
eGEMs (Generating Evidence & Methods to improve patient outcomes), 5(2), 3.
Finks, J. F., Kole, K. L., Yenumula, P. R., English, W. J., Krause, K. R., Carlin, A. M., ... & Michigan
Bariatric Surgery Collaborative. (2011). Predicting risk for serious complications with bariatric
surgery: results from the Michigan Bariatric Surgery Collaborative. *Ann Surg, 254*(4), 633-640.
Friedman, J. H. (2002). Stochastic gradient boosting. *Computational Statistics & Data Analysis, 38*(4),
367-378.
Geubbels, N., de Brauw, L. M., Acherman, Y. I. Z., van de Laar, A. W. J. M., & Bruin, S. C. (2015). Risk
Stratification Models: How Well do They Predict Adverse Outcomes in a Large Dutch Bariatric
Cohort? *Obesity Surgery, 25*(12), 2290-2301.
Geurts, P., Ernst, D., & Wehenkel, L. (2006). Extremely randomized trees. *Machine learning, 63*(1), 3-
42.
Gupta, P. K., Franck, C., Miller, W. J., Gupta, H., & Forse, R. A. (2011). Development and Validation of
a Bariatric Surgery Morbidity Risk Calculator Using the Prospective, Multicenter NSQIP
Dataset. *Journal of the American College of Surgeons, 212*(3), 301-309.
Hayes, M. T., Hunt, L. A., Foo, J., Tychinskaya, Y., & Stubbs, R. S. (2011). A model for predicting the
resolution of type 2 diabetes in severely obese subjects following Roux-en Y gastric bypass
surgery. *Obes Surg, 21*(7), 910-916.
Hedenbro, J. L., Naslund, E., Boman, L., Lundegardh, G., Bylund, A., Ekelund, M., ... & Naslund, I.
(2015). Formation of the Scandinavian Obesity Surgery Registry, SOReg. *Obes Surg, 25*(10),
1893-1900.
James, G., Witten, D., Hastie, T., & Tibshirani, R. (2013). *An introduction to statistical learning with*
Application in R (Vol. 112). New York: Springer.
Jiang, F., Jiang, Y., Zhi, H., Dong, Y., Li, H., Ma, S., ... & Wang, Y. (2017). Artificial intelligence in
healthcare: past, present and future. *Stroke Vasc Neurol, 2*(4), 230-243.
Kotsiantis, S. B., Zaharakis, I., & Pintelas, P. (2007). Supervised machine learning: A review of
classification techniques. *Emerging artificial intelligence applications in computer*
engineering, 160, 3-24.
Kourou, K., Exarchos, T. P., Exarchos, K. P., Karamouzis, M. V., & Fotiadis, D. I. (2015). Machine
learning applications in cancer prognosis and prediction. *Comput Struct Biotechnol J, 13*, 8-
17.
Liaw, A., & Wiener, M. (2002). Classification and regression by randomForest. *R news, 2*(3), 18-22.
Longitudinal Assessment of Bariatric Surgery, C., Flum, D. R., Belle, S. H., King, W. C., Wahed, A. S.,
Berk, P., ... & Wolfe, B. (2009). Perioperative safety in the longitudinal assessment of bariatric
surgery. *N Engl J Med, 361*(5), 445-454.

Maalouf, M., Homouz, D., & Trafalis, T. B. (2018). Logistic regression in large rare events and imbalanced data: A performance comparison of prior correction and weighting methods. *Computational Intelligence, 34*(1), 161-174.

Maciejewski, M. L., Winegar, D. A., Farley, J. F., Wolfe, B. M., & DeMaria, E. J. (2012). Risk stratification of serious adverse events after gastric bypass in the Bariatric Outcomes Longitudinal Database. *Surg Obes Relat Dis, 8*(6), 671-677.

Mishra, S., Sturm, B. L., & Dixon, S. (2017). *LOCAL INTERPRETABLE MODEL-AGNOSTIC EXPLANATIONS FOR MUSIC CONTENT ANALYSIS.* Paper presented at the The 18th ISMIR Conference, Suzhou, China.

Ng, M., Fleming, T., Robinson, M., Thomson, B., Graetz, N., Margono, C., ... & Gakidou, E. (2014). Global, regional, and national prevalence of overweight and obesity in children and adults during 1980-2013: a systematic analysis for the Global Burden of Disease Study 2013. *Lancet, 384*(9945), 766-781.

Olbers, T., Lonroth, H., Fagevik-Olsen, M., & Lundell, L. (2003). Laparoscopic gastric bypass: development of technique, respiratory function, and long-term outcome. *Obes Surg, 13*(3), 364-370.

Pan, L., Liu, G., Lin, F., Zhong, S., Xia, H., Sun, X., & Liang, H. (2017). Machine learning applications for prediction of relapse in childhood acute lymphoblastic leukemia. *Sci Rep, 7*(1), 7402.

Passos, I. C., Mwangi, B., & Kapczinski, F. (2016). Big data analytics and machine learning: 2015 and beyond. *Lancet Psychiatry, 3*(1), 13-15.

Pedersen, H. K., Gudmundsdottir, V., Pedersen, M. K., Brorsson, C., Brunak, S., & Gupta, R. (2016). Ranking factors involved in diabetes remission after bariatric surgery using machine-learning integrating clinical and genomic biomarkers. *Npj Genomic Medicine, 1*.

Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., ... & Duchesnay, E. (2011). Scikit-learn: Machine Learning in Python. *Journal of Machine Learning Research, 12*, 2825-2830.

Piaggi, P., Lippi, C., Fierabracci, P., Maffei, M., Calderone, A., Mauri, M., ... & Santini, F. (2010). Artificial neural networks in the outcome prediction of adjustable gastric banding in obese women. *PLoS One, 5*(10), e13624.

Probst, P., Bischl, B., & Boulesteix, A.-L. (2018). Tunability: Importance of hyperparameters of machine learning algorithms. *arXiv preprint arXiv:1802.09596*. Retrieved from https://arxiv.org/abs/1802.09596

Razzaghi, T., Safro, I., Ewing, J., Sadrfaridpour, E., & Scott, J. D. (2017). Predictive Models for Bariatric Surgery Risks with Imbalanced Medical Datasets. Clemson, South Carolina: TigerPrints.

Ribeiro, M. T., Singh, S., & Guestrin, C. (2016). *Why should i trust you?: Explaining the predictions of any classifier.* Paper presented at the Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, San Francisco, California, USA

Schapire, R. E. (2003). The boosting approach to machine learning: An overview *Nonlinear estimation and classification* (pp. 149-171): Springer.

Sjostrom, L., Lindroos, A. K., Peltonen, M., Torgerson, J., Bouchard, C., Carlsson, B., ... & Swedish Obese Subjects Study Scientific, G. (2004). Lifestyle, diabetes, and cardiovascular risk factors 10 years after bariatric surgery. *N Engl J Med, 351*(26), 2683-2693.

Stenberg, E., Cao, Y., Szabo, E., Naslund, E., Naslund, I., & Ottosson, J. (2018). Risk Prediction Model for Severe Postoperative Complication in Bariatric Surgery. *Obes Surg*.

Stenberg, E., Szabo, E., Agren, G., Naslund, E., Boman, L., Bylund, A., ... & Scandinavian Obesity Surgery Registry Study, G. (2014). Early complications after laparoscopic gastric bypass surgery: results from the Scandinavian Obesity Surgery Registry. *Ann Surg, 260*(6), 1040-1047.

The international federation for the surgery of obesity and metabolic disorders. (2017). *Third IFSO Global Registry Report 2017*. Retrieved from Oxfordshire, United Kindom: http://www.ifso.com/wp-content/themes/ypo-theme/pdfs/3rd-ifso-report-21-august-2017.pdf

485   Thomas, D. M., Kuiper, P., Zaveri, H., Surve, A., & Cottam, D. R. (2017). Neural Networks to Predict
486   Long-term Bariatric Surgery Outcomes. *Bariatric Times, 14*(12), 14-17.
487   Zhou, Z.-H. (2012). *Ensemble methods: foundations and algorithms*. New York: CRC press.

490   Annex 1: Terminology and derivations

491   Cross Entropy loss (Log loss):

492
$$V(f(\vec{x}), y) = -y\ln(f(\vec{x})) - (1 - y)\ln(1 - f(\vec{x}))$$

where y is true classifier $\in \{0, 1\}$ and $f(\vec{x})$ is predicted value.

True or false refers to the predicted outcome being correct or wrong, while positive or negative refers

to presenting severe complication or no severe complication.

ACC: accuracy

SEN: sensitivity

SPE: specificity

TP: number of true positives, i.e. patient presenting severe complication correctly predicted as positive

TN: number of true negatives, i.e. patient without severe complication correctly predicted as negative

FP: number of false positives, i.e. patient without severe complication wrongly predicted as positive

FN: number of false negatives, i.e. patient presenting severe complication wrongly predicted as

negative

Total: total number of the patients, i.e. TP+TN+FP+FN

P: number of patients presenting severe complication, i.e. TP+FN

N: number of patients without severs complication, i.e. TN+FP

AUC: area under the receiver operating characteristic (ROC) curve for binary outcome

T: threshold for a patient is classified as presenting severe complication if X>T, where X is predicted

probability of a patients presenting severe complication by an algorithm.

$ACC = \dfrac{TP + TN}{Total} \times 100\%$

$SEN = \dfrac{TP}{P}$

$SPE = \dfrac{TN}{N}$

$AUC = \displaystyle\int_0^1 SEN_T (1 - SPE)_T \, dT$