Hierarchical Complexity of the Adult Human Structural Connectome

Keith Smith[1], Mark E. Bastin[2], Simon R. Cox[3], Maria C. Valdés Hernández[2], Stewart Wiseman[2], Javier Escudero[4], Catherine Sudlow[1]

[1]Usher Institute for Population Health Science and Informatics, Medical School, University of Edinburgh, Edinburgh, UK;
[2]Centre for Clinical Brain Sciences, Western General Hospital, University of Edinburgh, Edinburgh UK;
[3]Centre for Cognitive Ageing and Cognitive Epidemiology, Department of Psychology, University of Edinburgh, Edinburgh, UK.
[4]School of Engineering, Institute for Digital Communications, University of Edinburgh, Edinburgh, UK

Abstract- The structural network of the human brain has a rich topology which many have sought to characterise using standard network science measures and concepts. However, this characterisation remains incomplete and the non-obvious features of this topology have confounded attempts to model it constructively. This calls for new perspectives. Hierarchical complexity is an emerging paradigm of complex network topology based on the observation that complex systems are composed of hierarchies within which the roles of hierarchically equivalent nodes display highly variable connectivity patterns. Here we test the hierarchical complexity of the human structural connectomes of a group of seventy-nine healthy adults. Binary connectomes are found to be more hierarchically complex than three null models—random graphs, random geometric graphs, and edge-randomised connectomes. This presents important new insights into the structure of the human brain, indicating a rich variety of connectivity patterns within hierarchically equivalent nodes. That random models fail to show such behaviour suggests that the generative mechanisms of brain structure may even insist on such dissimilarity. This also provides the strongest evidence to date in support of the hierarchical complexity paradigm of complex brain networks— both ordered and random systems are inherently more predictable. Dividing the connectomes into four tiers based on degree magnitudes indicates that the most complex nodes are neither those with the highest nor lowest degrees but are instead found in the third and second tiers. Spatial mapping of the brain regions in each hierarchical tier reveals consistency with the current anatomical, functional and neuropsychological knowledge of the human brain. The most complex tier (tier 3) involves regions believed to bridge high-order cognitive (tier 1) and low-order sensorimotor processing (tier 2), revealing a strikingly large diversity of connectivity patterns elicited in the integration of these processes.

Introduction

The physical connections between regions of the human brain transcend their geometrical localities to support globally efficient and complex functional principles[1,2]. Characterisations of this structure as a network allows us to probe hidden architectural patterns enabling a deeper understanding of the brain's wholescale organisation[3–5]. Yet much remains to be understood about these patterns and how they support the brain's multifaceted roles in, for example, information processing, creativity and cognition. Global network characteristics are modelled on the basis of brain regions and the connections between them. Important findings show efficiency[3], fractal modular organisation[4] and rich-club structures between hub nodes[6] of brain networks. It has also been suggested that the inability to find simple generative models of the connectome implies the existence of a variety of different biological mechanisms working in conjunction with each other[7]. Methods to combine such mechanisms to explain brain structure have been attempted with moderate success, suggesting distance-based penalties and a tendency for neighbouring nodes to share neighbours being two key factors[8,9]. However, it has yet to be determined whether dissimilarity of connectivity patterns is itself a feature which can advance our understanding of brain structure. Just such a feature can be extracted using the recently developed hierarchical complexity paradigm[10,11].

Here, for the first time, we analyse the hierarchical complexity of the human structural connectome created from structural and diffusion magnetic resonance imaging (MRI) data acquired from a sample of working age individuals. This includes a detailed analysis of complexity within the hierarchical levels of these connectomes. This recently introduced paradigm has been validated only in an electroencephalogram (EEG) functional connectivity study[10]. It posits that network complexity is characterised by nodes of the same degree (hierarchically equivalent nodes) being connected in highly variable ways with respect to the degrees of nodes they connect to (having highly variable connectivity patterns), as illustrated in Fig 1. This concerns wholly separate considerations of topology to the well-known paradigms of small-world[12] and scale-free[13] complex networks. Similarly, in seeking to define the notion of complexity, it takes a different stance to the standard notion of complexity arising between random and ordered systems[14], instead proposing that both such systems have inherently more predictable connectivity patterns than real-world complex networks[10].

In the human brain, we particularly expect such behaviour. The brain is composed of numerous regions with myriad functional specialisations, a phenomenon which we hypothesise to necessitate a wide variety of connectivity patterns in the supporting structure. We test this hypothesis by comparing the network index for hierarchical complexity of structural connectomes against those of three node- and edge-matched randomised models. Complementing this, we seek to answer where in the network hierarchy, as well as in the brain biology, such complexity is prominent. We do this by splitting the structural connectome into hierarchical tiers and performing within tier analyses before analysing which regions lie consistently (in more than two thirds of participants) within one of these tiers. Critically, it is well established that hub nodes exist in the brain[15,16] and it is suggested that their degradation is a key mechanism in brain disorders[17]. Therefore, it is of interest to understand whether or not hub nodes are drivers behind the brain's structural complexity or if other hierarchy levels are more complex and what implications this may have in our understanding of brain connectivity and how this could be implemented to aid in our understanding of pathology.

Hierarchically ordered

Hierarchically complex

Figure 1. Illustration of hierarchical complexity. Two networks are shown with 25 nodes, 44 edges and identical degree distributions. Node colours signify degrees- blue, 2; green, 3; yellow, 4; orange, 5; and red, 8. The connectivity patterns (degrees of nodes a node is connected to) of degree 2 nodes are highlighted in the images by red edges and node boundaries. In a hierarchically ordered network, left, same degree nodes have homogeneous connectivity patterns. In a hierarchically complex network, right, same degree nodes have heterogeneous connectivity patterns. For example, node c is connected to only low degree nodes (2 and 3), and node b to only high degree nodes (5 and 8).

Materials and Methods

For reference, a block diagram of the methodological pipeline used in this study is provided in Fig 2. Two sets of network analyses were produced to undertake a comprehensive analysis of hierarchical complexity in the adult human structural connectome. The first concerned the hierarchical complexity of binary structural connectomes. The second concerned the hierarchical tiers most responsible for the hierarchical complexity of the binary connectomes and the regions within these tiers.

Subjects

Eighty normal, healthy volunteers (40 males, 40 females) aged 25–64 (median 43, IQR 17) years were recruited by advertisement from staff working at the University of Edinburgh, the Western General Hospital and Royal Infirmary, Edinburgh, Scotland. Health status was assessed using medical questionnaires and all structural MRI scans were reported by a neuroradiologist.

Figure 2. Block diagram of the employed methodological pipeline. Adjacency matrices are computed from the MRI signal. Random models are then generated with matching network size and density. Network indices are then computed from which the results are derived.

Volunteers were recruited if they were native English speakers, were not on any long-term medication, had not been diagnosed with any chronic medical condition including diabetes mellitus or hypertension, had not undergone previous cranial surgery, and were able to undergo brain MRI. The study was approved by the Lothian Research Ethics Committee (05/S1104/45), and subjects gave written informed consent.

MRI acquisition

All MRI data were acquired using a GE Signa Horizon HDxt 1.5 T scanner (General Electric, Milwaukee, WI, USA) using a self-shielding gradient set with maximum gradient strength of $33\ mT/m$ and an 8-channel phased-array head coil. Briefly, subjects provided high resolution structural (T_1-, T_2-, T_2^*- and fluid attenuated inversion recovery (FLAIR)-weighted scans) and diffusion MRI data in the same session. The diffusion MRI examination consisted of 7 T_2- weighted ($b = 0\ s\ mm^{-2}$) and sets of diffusion-weighted ($b = 1000\ s\ mm^{-2}$) single-shot spin-echo echo-planar (EP) volumes acquired with diffusion gradients applied in 64 non-collinear directions[18]. Volumes were acquired in the axial plane with a field-of-view of $256 \times 256\ mm$, contiguous slice locations, and image matrix and slice thickness designed to give $2\ mm$ isotropic voxels. A 3D T_1- weighted inversion recovery-prepared fast spoiled gradient-echo (FSPGR) volume was also acquired in the coronal plane with 160 contiguous slices and $1.3\ mm^3$ voxel dimensions.

Image processing

Each 3D T_1-weighted FSPGR volume was parcellated into 85 cortical (34 per hemisphere) and sub-cortical (eight per hemisphere) regions-of-interest (ROI), plus the brain stem, using the Desikan-Killiany atlas and default settings in FreeSurfer v5.3 (http://surfer.nmr.mgh.harvard.edu). The results of the segmentation procedure were visually checked for gross errors and then used to construct grey and white matter masks for use in network construction and to constrain the tractography output. Using tools provided by the FDT package in FSL (http://fsl.fmrib.ox.ac.uk/fsl), the diffusion MRI data were pre-processed to reduce systematic imaging distortions and bulk subject motion artifacts by affine registration of all subsequent EP volumes to the first T_2-weighted EP volume[19]. Brain extraction was performed on the registered T_2-weighted EP volumes and applied to the FA volume calculated by DTIFIT in each subject[20]. The neuroanatomical ROIs determined by FreeSurfer were then aligned from 3D T_1-weighted volume to diffusion space using a cross-modal nonlinear registration method. As a first step, linear registration was used to initialize the alignment of each brain-extracted FA volume to the corresponding FreeSurfer extracted 3D T_1-weighted brain volume using a mutual information cost function and an affine transform with 12 degrees of freedom[19]. Following this initialization, a nonlinear deformation field based method (FNIRT) was used to refine local alignment[21]. FreeSurfer segmentations and anatomical labels were then aligned to diffusion space using nearest neighbour interpolation.

Tractography

Whole-brain probabilistic tractography was performed using FSL's BedpostX/ProbTrackX algorithm[22]. Probability density functions, which describe the uncertainty in the principal directions of diffusion, were computed with a two-fibre model per voxel[23]. Streamlines were then constructed by sampling from these distributions during tracking using 100 Markov Chain Monte Carlo iterations with a fixed step size of $0.5\ mm$ between successive points. Tracking was initiated from all white matter voxels and streamlines were constructed in two collinear directions until terminated by the following stopping criteria designed to minimize the amount of anatomically implausible streamlines: (i) exceeding a curvature threshold of 70 degrees; (ii) entering a voxel with FA below 0.1; (iii) entering an extra-cerebral voxel; (iv) exceeding $200\ mm$ in length; and (v) exceeding a distance ratio metric of 10. The distance ratio metric[24] excludes implausibly tortuous streamlines. For instance, a streamline with a total path length 10 times longer than the distance between end points was considered to be invalid. The values of the curvature, anisotropy and distance ratio metric constraints were set empirically and informed by visual assessment of the resulting streamlines.

Network construction

Connections were recorded in an 85×85 adjacency matrix, where the entry a_{ij} denotes the connection (edge) weight between node i and node j. Fractional anisotropy (FA)-weighted networks were computed by recording the mean FA value along interconnecting streamlines. Across the cohort, only connections which occurred in at least two-thirds of subjects were retained[25]. Self-connections were removed, and if no streamlines were found between a pair of nodes, the corresponding matrix entry was set to zero. Network construction failed in one subject giving structural connectome data for seventy-nine subjects.

Hierarchical complexity
The hierarchical complexity of the structural connectomes was implemented to analyse how similar the connections established by nodes of the same degree were in terms of the degrees of the nodes they are connected to. This was achieved by computing the variability of the ordered node neighbourhood degree sequences. Let $G = (\mathcal{V}, \mathcal{E})$ be a graph with node set $\mathcal{V} = \{1, \ldots, n\}$ and edge set $\mathcal{E} = \{(i,j): i, j \in \mathcal{V}\}$, and let $\mathcal{K} = \{k_1, \cdots, k_n\}$ be the set of degrees of G, where k_i is the number edges adjacent to vertex i. Further, let $\mathcal{K}_p$ be the set of nodes of degree p. For neighbourhood degree sequence $s^p{}_i = \{s^p{}_i(1), \cdots, s^p{}_i(p)\}$ of node i of degree p, the hierarchical complexity is

$$R = \frac{1}{\mathcal{D}} \sum_{\mathcal{K}_p s.t. |\mathcal{K}_p| > 1} \frac{1}{p(|\mathcal{K}_p| - 1)} \left(\sum_{j=1}^{p} \left(\sum_{i \in \mathcal{K}_p} \left(s^p{}_i(j) - \mu^p(j) \right)^2 \right) \right)$$

where $\mathcal{D}$ is the number of distinct degrees in the network and $\mu^p(j)$ is the mean of the jth entries of all p length neighbourhood degree sequences[26].

Connectivity and network analysis
Connectivity matrices were first binarised by setting all non-zero entries to 1 to obtain binary network topologies. For each connectivity matrix, three randomised graphs were generated with the same number of nodes (always $n = 85$) and edges ($m = 1281.5 \pm 136.72$).

Firstly, Erdos-Renyi random graphs were generated as a baseline randomisation in which each node has an equal probability of being connected to any other. Random uniform weights were computed for each edge and the m largest weights were kept as edges. Secondly, to test the differences between brain connectivity and a closest distance-based connectivity of points placed randomly in 3D space, we generated random geometric graphs (RGGs)[27]. These were created by generating uniformly random 3D coordinates (representing nodes) and computing the distances between each pair of coordinates (representing weighted edges). The m closest number of edges were then taken as the binary topology. Thirdly, we tested the difference between brain connectivity and graphs with the same degree distribution but with randomised edges[28]— edge randomised networks. This allowed us to test the hierarchical complexity of the human structural connectome against a randomised null model controlling for graph heterogeneity and thus overcame any bias found simply due to a different level of heterogeneity in graph degrees.

Hierarchical complexity was computed for all connectomes and null models alongside the degree variance[29],
$$V = var(\mathcal{K}),$$
characterising hierarchical spread; assortativity[30],
$$r = \frac{\sum_{ij}(a_{ij} - k_i k_j / 2m) k_i k_j}{\sum_{ij}(k_i a_{ij} - k_i k_j / 2m) k_i k_j},$$
characterising self-similarity of neighbouring node degrees; and segregation/integration using the normalised clustering coefficient[12,26],
$$\gamma = C/P,$$
Where $P = 2m/n(n-1)$ is the network density (number of edges out of total possible in a network with n nodes) and C is the global clustering coefficient defined as the ratio of the number of triangles (3 nodes all sharing edges) in the network and the number of triples (paths of length 2) in the network. These other indices are computed for comparisons and to allow for greater insight into topological differences.

<u>Hierarchy tiers</u>
Once the global connectivity patterns were assessed we then performed a more refined analysis of hierarchical complexity through different degree strengths in the network. We split each network into four tiers and then eight tiers based on maximum degree magnitudes, where each tier comprised a rounded 25% (12.5% for 8 tiers) of degrees, and so that each tier in the 4-tier split comprised of two tiers in the 8-tier split. The first tier comprised nodes in the top 25% (12.5%) of degrees in the network, the second tier comprised of nodes with the next 25% (12.5%) of largest degrees, and so on. This was implemented on the human brain structural connectomes alongside the randomized structural connectomes to investigate if there were any tiers that were particularly responsible for the differences in hierarchical complexity found. Note that, due to the differences in structural connectomes between subjects, these tiers are not the same for each subject. Making the tiers the same across subjects would obfuscate results as nodes of a certain degree in one network may be regarded as hub nodes, but not so in another network. After this, we computed which regions were consistently—in over two thirds of participants— within one of the tiers to understand the relationship between the cognitive/physiological function of the region and its hierarchical complexity.

<u>Statistical tests</u>
Population t-tests were carried out to assess the significance of the differences of distributions of network index values between adult structural connectomes and random null models as well as between pairs of random null models. The effect sizes were also computed with Cohen's d.

Results

<u>Analysis of global binary topology</u>
The results of hierarchical complexity, R, of the binary human structural connectome, alongside more standard measures of network topology— heterogeneity (V), assortativity (r) and segregation (γ)— are plotted against network density (P) in Fig 3. The hierarchical complexity of the human structural connectome data is notably larger than the three randomised null models, Fig 3(a). Values of R for human structural connectomes have a mean and standard deviation of 0.232 ± 0.061 whereas randomising the edges drops R by almost half to 0.120 ± 0.026 (effect size of 1.358 with respect to structural connectome values). Additionally, much lower values of R are obtained by RGGs (0.094 ± 0.030 with an effect size of 1.646) and random graphs (0.002 ± 0.001 with an effect size of 1.836). The effect size between RGGs and edge-randomise connnectomes was 0.829. All of these comparisons drew p values of statistical t-tests less than 0.0001.

Each null model used takes up a distinct region of the hierarchical complexity spectrum whereas overlaps are present between the MRI data and one of the null models in all of the other spectrums analysed, as shown by the mean ± standard deviation of network measure values presented in Table 1. Conceptual ranges for each network measure are illustrated to the right of the plots in Fig 3. The human structural connectome is the most hierarchically complex of all the models but has the same amount of hierarchical structure (degree variance, Fig. 3(b)) as the edge-randomised connectomes since the degree distribution is fixed. As for random graphs, human structural connectomes are neither assortative nor disassortative indicating that nodes of a given degree are neither likely nor unlikely to be connected to nodes of a self-similar degree, Fig. 3(c). Finally, as for RGGs, human structural connectomes have similar levels of high segregation, indicating that nodes tend to cluster together in the connections they make in a similar manner to that in distance-based networks, Fig 3(d).

Figure 3. Hierarchical characteristics of the human structural connectome compared to relevant randomised graphs (a-b). Included are the assortativity (c) and random graph normalised clustering coefficient (d) for comparison. While the other characteristics cannot separate all the different network types, hierarchical complexity displays a scale ranging from hierarchically simple Erdos- Renyi (E-R) random networks through random geometric graphs (RGGs), then random networks with the same degree distributions as human MRI networks, and finally to the most hierarchically complex human MRI networks.

Table 1	Brain MRI	Randomised MRI	RGG	Random Graph
Table 1. Mean $\pm$ standard deviaton of network measures of brain connectomes and random graph models.				
R	0.238 ± 0.064	0.137 ± 0.032	0.086 ± 0.032	0.013 ± 0.003
V	$\underline{216.063 \pm 39.010}$	$\underline{216.063 \pm 39.010}$	114.225 ± 26.024	18.601 ± 2.812
r	$\underline{-0.051 + 0.030}$	-0.184 ± 0.030	0.105 ± 0.055	$\underline{-0.026 + 0.026}$
C	$\underline{0.611 + 0.027}$	0.500 ± 0.047	$\underline{0.628 + 0.018}$	0.358 ± 0.038

Note. R: hierarchical complexity, V: degree variance, r: assortativity, C: clustering coefficient. The underlined values in each row indicate cases where standard deviations overlap with each other's means.

Typical neighbourhood degree sequence structure

Figure 4. An example of neighbourhood degree sequences of nodes of degree 31 for the structural connectome of a single subject (bottom left) compared to node and edge matched random models. For this subject, the randomized connectome and the RGG there are three nodes of degree 31 in the network whereas for the random graph there are five. Note how each degree sequence in the structural connectome is distinct, whereas degree sequences are far more similar in the random models.

Fig 4 provides an illustration of why the human brain structural connectome has such high hierarchical complexity. In this instance, for 31-degree nodes, the participant's structural connectome (bottom left) has three nodes with widely varied neighbourhood degree sequences. On the other hand, the random null models have much more homogeneous neighbourhood degree sequences.

Analysis of hierarchy tiers
We then examined which nodes in the hierarchy are contributing to greater complexity. To do this we split the nodes up into a number of tiers based on their degrees and looked at the effect size of hierarchical complexity within tiers between structural connectomes and edge-randomised

connectomes. Table 2 displays these results for 4-tier and 8-tier strategies, with the individual data points plotted per subject in Fig 5.

# of Tiers	Tier 4b	Tier 4(t)	Tier 3b	Tier 3(t)	Tier 2b	Tier 2(t)	Tier 1b	Tier 1(t)
Table 2. Effect size (Cohen's d) of hierarchical complexity, R, within tiers between structural and randomised connectomes								
4-Tier	-	0.849**	-	1.393**	-	1.033**	-	0.388
8-Tier	0.695	0.841**	1.222**	1.036**	1.055**	0.785**	0.439*	0.168

*Note. * denotes population t-test with p<0.01, ** denotes population t-test with p<0.0001*

Figure 5. Analysis of hierarchical tiers contributing to the high hierarchical complexity in the human structural connectome, left, compared to graphs with same degree distribution and randomised connections, right, for 79 individuals. Given T tiers, Tier 1 comprises the $100/T$ % most highly connected nodes whereas the final tier is the $100/T$ % of nodes with the smallest degrees.

The results show that hub nodes (tier 1(t)) and peripheral nodes (tier 4(b)) are contributing less to the greater complexity exhibited in the human brain connectome than middle tiers. In fact, this is particularly true of hub nodes, with lowest effect sizes notable in tier 1 and tier 1t in respective 4-and 8-tier strategies. Indeed, the additional tiers in the 8-tier analysis— splitting each 4-tier tier into a top (t) and bottom (b) tier— shows that there is no

Figure 6. *Cortical (left) and subcortical (right) mapping of hierarchical tiers. Grey denotes areas that did not appear in any tier in more than two thirds of participants. Putamen is opaque to enable visualisation of the pallidum.*

significant difference between randomised and human brain data in tier 1t, corresponding to the top half of tier 1 in the 4-tier analysis (population t-test $p = 0.315$, $t = 1.0093$). However, the bottom half of tier 1 in the human connectome has an effect size over two and a half times greater (Cohen's $d = 0.439$) and does show a significant difference to the randomised connectome ($p = 0.007, t = 2.7308$). The same pattern repeats itself in the analysis of the last tier where the extremity shows least difference. The difference between human brain and randomised data for the tier 4b nodes in the 8-tier analysis had $p = 0.033$ ($t = 2.217$), whereas the difference found in tier 4t had $p < 0.0001$ ($t = 5.773$).

The ROIs relating to the four tiers—those which are in a given tier in more than two-thirds of participants—are as in Table 2. Such consistency was found for over 70% of brain regions (61 of 85). These have been mapped to the MRI image in Fig 6 with different colours representing the different tiers. The same computations were applied to the 8 tier split, however very little regional consistency was found within tiers (only 20%-17 of 85- regions could be classified), suggesting that the 4-tier strategy provided the right size for such analysis.

Tier	Left and Right	
	Left only	**Right only**
Tier 1	Thalamus, putamen, pallidum, choroid plexus, precuneus, superior frontal gyrus, superior parietal gyrus	
	-	Superior temporal gyrus, insula
Tier 2	Inferior temporal gyrus, lateral occipital cortex, postcentral gyrus, precentral gyrus	
	Middle temporal gyrus, paracentral gyrus, insula	Inferior parietal gyrus, cingulate gyrus isthmus, lateral orbitofrontal cortex
Tier 3	Caudal middle frontal, cuneus, lingual gyrus, inferior frontal gyrus pars triangularis, pericalcarine cortex, posterior cingulate gyrus	
	Amygdala, banks superior temporal sulcus, lateral orbitofrontal cortex, rostral anterior cingulate cortex, supramarginal gyrus, temporal pole	Hippocampus, fusiform, paracentral gyrus, inferior frontal gyrus pars opercularis, inferior frontal gyrus pars orbitalis
Tier 4	Accumbens, entorhinal cortex	
	Parahippocampal gyrus, inferior frontal gyrus pars orbitalis	Rostral anterior cingulate cortex, temporal pole

Table 2. Classification of brain regions into hierarchical tiers.

Note. Each label is associated with a region in both left and right hemispheres. Those for which both are in the same tier are shown in the dark grey boxes while those for which only one hemisphere is present in the tier are written in either left or right light grey boxes beneath, as appropriate. A region is assigned to a tier if it occurs in that tier in more than two thirds of participants.

Discussion

We confirm the hypothesis that human brain structural connectomes created from structural MRI data are more hierarchically complex than random null network models. It is interesting to note that randomising edges in networks with identical degree distributions to those obtained from brain MRI data — thus fixing degree variance— provides networks with a dramatically decreased hierarchical complexity. This indicates that the dissimilarity of connections made by network nodes with the same centrality cannot be explained by greater variability of network degrees present and shows a prominent presence in the brain structure of dissimilarity between the nodes residing at the same hierarchical level. This suggests that the organisational complexity in the human brain is more heterogeneous than that produced at random and that heterogeneity in the roles of similarly central nodes could itself yet prove a single coherent explanation for the complexity of brain structure.

Indeed, EEG functional connectivity was found to be more complex than a variety of ordered systems as well as Erdos-Renyi random networks. However, hierarchical complexity depends on degree distributions and it had yet to be shown whether or not brain networks were more hierarchically complex than random networks with the same degree distributions as brain networks. The evidence here is thus the strongest evidence yet to support the hierarchical complexity paradigm as the key to distinguishing real-world complexity from the more predictable patterns of ordered and random systems.

From a neuroanatomical perspective, the Tiers from the 4-tier categorisation exhibited a degree of anatomical plausibility. Tier 1 (highest degree but lowest contribution to hierarchical complexity) comprised lateral frontal, parietal and lateral temporal regions along with selective subcortical structures. This aligns well with the current (macro)neurobiological account of intelligence differences (the Parieto-Frontal Integration or P-FIT theory[31–33]) and resembles previous work which

identifies hub nodes of the human brain connectome[16]. Tier 2, on the other hand, consists mainly of occipital and sensorimotor cortex involved in lower order sensory processing. Interestingly, tier 3 is then comprised of mainly heteromodal integrative regions which may represent a transitional stage in information processing between higher order cognitive (tier 1) and lower order sensory processing (tier 3)[34]. Functional categorisation of tier 4 regions is less clear-cut, but the nucleus accumbens, entorhinal cortex and anterior cingulate are all ostensible components of the hippocampal-diencephalic-cingulate network involved in memory and emotion[35].

Crucially, our analyses suggest that hierarchical complexity is not driven by hub nodes (tier 1), but rather by nodes particularly in tier 3 (mainly heteromodal integrative regions) and to a lesser but still significant extent in tier 2 (more basic sensorimotor and visual-semantic areas). Given that tier 3 consists of regions involved in collecting/integrating information from both ends of the processing spectrum (higher order cognitive and more basic sensory), the great diversity of cross-tier connectivity patterns revealed by its large hierarchical complexity stands to reason. Indeed, it suggests a rich diversity of roles played by these integrative regions, necessitating connections across all tiers. The fact that hub nodes (tier 1) are not found to be substantial contributors to the hierarchical complexity of human structural connectomes indicates that hub nodes may take on a disproportionate amount of focus in brain network studies[36]. These findings raise interesting prospects to see how such diversity (or lack thereof) of cross-tier connectivity patterns are affected in pathology and disease. Particularly appropriate would be to apply these methods to diseases known to affect different steps of multimodal functional integration (cognition, sensorimotor, or the integration of these processes).

Hierarchical complexity can also help deepen our understanding of other topological findings in the connectomes. For example it provides an explanation for the un-assortative nature of brain structural connectomes[37], (see Fig 3(c)). The degree of nodes in a given node's neighbourhood do not maintain a self-similarity to the degree of the given node, because nodes take up a wide array of different neighbourhood connectivity patterns encompassing the heterogeneity of degrees in the whole network. Including results of the high values of γ —propensity of neighbouring nodes to share other neighbours— indicates that i) nodes which are connected together tend to connect to the same other nodes (high γ), ii) these nodes do not have similar degrees, ($r \approx 0$) and iii) nodes of the same degree do not have similar distributions of neighbouring degrees (high R). All of these aspects are somehow integrated into the brain connectivity structure to create this rich and diverse topology.

It is also interesting to note a striking overlap in segregation between the human structural connectome and RGGs (see Fig 3(d)). The strength of this overlap, together with the lack of hierarchical structure present in RGGs, suggests that geometric sensibilities of node clustering is extended also to integrative connections, where two connections spanning the connectome within a geometrical locality tend to span to the same nodes in the other locality. This agrees with the homophily principle described in a recent connectome simulation study[9]. Note that the results here significantly differ from another study where segregation in RGGs was found to be larger than the connectome[7], although it must be noted that the network size ($n = 998$) was much larger and density ($P = 2.7\%$) more sparse than the current study and the space used to develop the models was rectangular rather than cubic as adopted here. It should also be noted that sparsity is not a desirable feature for analyzing hierarchical complex networks[38].

This is particularly interesting in the context of pathology. It is not yet clear which measure (or measures) can explain functional outcomes from pathological features (i.e. lesions, mineral accumulations, tissue loss, etc.), an understanding of which is required to help solve what has been termed the clinico-radiological paradox[39]. Evidence shows that there are specific white matter pathways that have greater impact on clinical and functional outcome regardless of the lesion size[40] whilst other tracts offer routes for functional reorganisation[41–43]. Future studies applying the hierarchical complexity measure to health and disease may help to uncover subtler but still significant differences in brain network topology that will add to our understanding of this topic. For

example, we generally expect that brain degradation (whether from ageing or disease) will display structural connectivity patterns more similar to the edge-randomised networks.

The evidence here adds to previous results of hierarchical complexity found in EEG functional connectivity[10,38], revealing a topological agreement in complexity between structure and function—both being more hierarchically complex than a variety of pertinent models. Future studies on the relationship between structural and functional MRI with respect to this complexity paradigm will help to better understand how function relates to structure and whether the structural complexity found here supports complex functional principles.

One limitation of the study is that we have not shown invariance of connectome hierarchical complexity to the choice of parcellation scheme. Different atlases and methods for producing connections do exist, but the resulting networks have been found to broadly share topological characteristics (e.g. small-world and degree distributions), even if the exact values of indices between different schemes are statistically different[44]. In addition, we previously demonstrated that different sizes of EEG functional networks share the characteristic of hierarchical complexity[10], suggesting that results may not significantly differ when using other parcellation schemes in structural MRI, notwithstanding general effects of parcellation granularity on tractography results[45].

Conclusion

The adult human structural connectome was found to be hierarchically complex with highly heterogeneous connectivity patterns occurring across hierarchically equivalent nodes. This was established in comparison to three very different random models—Erdös-Rényi random graphs, RGGs and edge-randomised connectomes. Hierarchical complexity was shown to divide the different models into a coherent range of topology with the human structural connectome at the top, while other standard topological concepts of segregation, assortativity and heterogeneity failed to adequately separate the models. These data suggest that diversity of connectivity patterns of hierarchically equivalent nodes could itself provide a cohesive rule for generative processes of brain structure. Moreover, this may explain the difficulty in establishing accurate generative models which account for all aspects of brain connectome topology using more predictable patterns. Hierarchical complexity was most apparent in Tier 2 and 3 nodes, constituting brain regions involved in sensorimotor, attentional and linguistic-semantic function, whereas Tiers 1 (hub nodes related to general intelligence) and 4 contributed much less to the complexity. Tiers 1 to 3 mapped to the different steps of the proposed functional connectivity framework for the integration of cognitive and sensory processing. From this, the most hierarchically complex tier contained the regions involved in the integration of cognitive and sensory inputs. This study provides a platform from which to explore hierarchical complexity of the human structural connectome in cognition, health and disease.

Author Contributions
KS devised the study, computed the network analyses and results and wrote the manuscript. MB collected the MRI data and generated the structural connectomes and helped write the manuscript. SC provided biological interpretation of the results and helped write the manuscript. MVH helped devise the study, provided expertise of MRI data and reviewed the manuscript. SW helped devise the study and reviewed the manuscript. JE helped interpret the technical results and reviewed the manuscript. CS helped devise the study and reviewed the manuscript.

Competing Interests
The authors declare no competing interests.

References

1.   Bullmore, E. & Sporns, O. Complex brain networks: graph theoretical analysis of structural and functional systems. *Nat. Neurosci. Rev.* **10,** 186–198 (2009).

2. De Vico Fallani F., Richiardi J., Chavez M. & Achard, S. Graph analysis of functional brain networks: practical issues in translational neuroscience. *Philos. Trans. R. Soc. B* **369,** 20130521 (2014).

3. Achard S. & Bullmore, E. Efficiency and cost of economical brain functional networks. *PLoS One* **3,** e17 (2007).

4. Meunier D., Lambiotte R. & Bullmore, E. T. Modular and hierarchical modular organisation of brain networks. *Front. Neurosci.* **4,** 200 (2010).

5. Stam C.J. & Van Straaten, E. C. W. The organization of physiological brain networks. *Clin. Neurophysiol.* **123,** 1067–1087 (2012).

6. McAuley J.J., Costa L.F. & Caetano, T. S. The rich-club phenomena across complex network hierarchies. *Appl. Phys. Lett.* **91,** 84103 (2007).

7. Klimm, F., Bassett, D. S., Carlson, J. M. & Mucha, P. J. Resolving structural variability in network models and the brain. *PLOS Comput. Biol.* **10,** e1003491 (2014).

8. Vertes, P. E. *et al.* Simple models of human brain functional networks. *Proc. Natl. Acad. Sci.* **109,** 5868–5873 (2012).

9. Betzel, R. F. *et al.* Generative models of the human connectome. *Neuroimage* **124,** 1054–1064 (2016).

10. Smith, K. & Escudero, J. The complex hierarchical topology of EEG functional connectivity. *J. Neurosci. Methods* **276,** (2017).

11. Smith, K., Abásolo, D. & Escudero, J. Accounting for the complex hierarchical topology of EEG phase-based functional connectivity in network binarisation. *PLoS One* **12,** (2017).

12. Watts D.J. & Strogatz, S. H. Collective dynamics of small-world networks. *Nature* **393,** 440–442 (1998).

13. Barabási, A.-L. *et al.* Emergence of Scaling in Random Networks. *Science (80-.).* **286,** 509 LP-512 (1999).

14. Tononi G., Sporns O. & Edelman, G. M. A measure for brain complexity: relating functional segregation and integration in the nervous system. *PNAS* **91,** 5033–5037 (1994).

15. Buckner R.L. *et al.* Cortical hubs revealed by intrinsic functional connectivity: mapping, assessment of stability, and relation to {A}lzheimer's disease. *J. Neurosci.* **29,** 1860–1873 (2009).

16. Van Den Heuvel M.P. & Sporns, O. Network hubs in the human brain. *Trends Cogn. Sci.* **17,** 683–696 (2013).

17. Crossley, N. A. *et al.* The hubs of the human connectome are generally implicated in the anatomy of brain disorders. *Brain* **137,** 2382–2395 (2014).

18. Jones, D. K. *et al.* Spatial normalization and averaging of diffusion tensor MRI data sets. *Neuroimage* **17,** 592–617 (2002).

19. Jenkinson, M. & Smith, S. A global optimisation method for robust affine registration of brain images. *Med. Image Anal.* **5,** 143–156 (2001).

20. Basser, P. J. & Pierpaoli, C. Microstructural and physiological features of tissues elucidated by quantitative-diffusion-tensor MRI. *J. Magn. Reson.* **213,** 560–570 (2011).

21. Andersson, J., Jenkinson, M. & Smith, S. *Non-linear registration aka spatial normalisation*. (2007).

22. Behrens, T. E. J., Berg, H. J., Jbabdi, S., Rushworth, M. F. S. & Woolrich, M. W. Probabilistic diffusion tractography with multiple fibre orientations: What can we gain? *Neuroimage* **34,** 144–155 (2007).

23. Behrens, T. E. J., Berg, H. J., Jbabdi, S., Rushworth, M. F. S. & Woolrich, M. W. Probabilistic diffusion tractography with multiple fibre orientations: What can we gain? *Neuroimage* **34,** 144–155 (2007).

24. Bullitt, E., Gerig, G., Pizer, S. M., Weili Lin, W. & Aylward, S. R. Measuring tortuosity of the intracerebral vasculature from MRA images. *IEEE Trans. Med. Imaging* **22,** 1163–1171 (2003).

25. de Reus, M. A. & van den Heuvel, M. P. Estimating false positives and negatives in brain networks. *Neuroimage* **70,** 402–409 (2013).

26. Smith K. & Escudero, J. The complex hierarchical topology of {EEG} functional

connectivity. *J. Neurosci. Methods* **276,** 1–12 (2017).

27. Dall, J. & Christensen, M. Random geometric graphs. *Phys. Rev. E* **66,** 016121 (2002).

28. Maslov, S. & Sneppen, K. Specificity and Stability in Topology of Protein Networks. *Science (80-.).* **296,** 910 LP-913 (2002).

29. Snijders, T. A. B. The degree variance: an index of graph heterogeneity. *Soc. Networks* **3,** 163–174 (1981).

30. Newman, M. Assortative mixing in networks. *Phys. Rev. Lett.* **89,** 208701 (2002).

31. Jung, R. E. & Haier, R. J. The Parieto-Frontal Integration Theory (P-FIT) of intelligence: Converging neuroimaging evidence. *Behav. Brain Sci.* **30,** 135 (2007).

32. Deary, I. J., Penke, L. & Johnson, W. The neuroscience of human intelligence differences. *Nat. Rev. Neurosci.* **11,** 201–211 (2010).

33. Basten, U., Hilger, K. & Fiebach, C. J. Where smart brains are different: A quantitative meta-analysis of functional and structural brain imaging studies on intelligence. *Intelligence* **51,** 10–27 (2015).

34. Sepulcre, J., Sabuncu, M. R., Yeo, T. B., Liu, H. & Johnson, K. A. Stepwise connectivity of the modal cortex reveals the multimodal organization of the human brain. *J. Neurosci.* **32,** 10649–61 (2012).

35. Bubb, E. J., Kinnavane, L. & Aggleton, J. P. Hippocampal - diencephalic - cingulate networks for memory and emotion: An anatomical guide. *Brain Neurosci. Adv.* **1,** (2017).

36. Crossley, N. A. *et al.* The hubs of the human connectome are generally implicated in the anatomy of brain disorders. *Brain* **137,** 2382–2395 (2014).

37. Bassett, D. S. *et al.* Hierarchical Organization of Human Cortical Networks in Health and Schizophrenia. *J. Neurosci.* **28,** 9239–9248 (2008).

38. Smith K., Abásolo D. & Escudero, J. Accounting for the Complex Hierarchical Topology of {EEG} Phase-based Functional Connectivity in Network Binarisation. *PLoS One* **12,** e0186164 (2017).

39. Chard, D. & Trip, S. A. Resolving the clinico-radiological paradox in multiple sclerosis [version 1; referees: 3 approved]. *F1000Research* **6,** (2017).

40. Valdés Hernández, M. C. *et al.* A comparison of location of acute symptomatic vs. 'silent' small vessel lesions. *Int. J. Stroke* **10,** 1044–1050 (2015).

41. Sung, Y.-W. *et al.* A Set of Functional Brain Networks for the Comprehensive Evaluation of Human Characteristics . *Frontiers in Neuroscience* **12,** 149 (2018).

42. Tomassini, V. *et al.* The effect of inflammation and its reduction on brain plasticity in multiple sclerosis: MRI evidence. *Hum. Brain Mapp.* **37,** 2431–2445 (2016).

43. Powell F, Tosun D, Sadeghi R, Weiner M, R. A. Preserved structural network organization mediates pathology spread in Alzheimer's disease spectrum despite loss of white matter tract integrity. *J. Alzheimer's Dis.* (2018). doi:doi: 10.3233/JAD-170798

44. Wang, J. *et al.* Parcellation-dependent small-world brain functional networks: A resting-state fMRI study. *Hum. Brain Mapp.* **30,** 1511–1523 (2009).

45. de Reus, M. A. & van den Heuvel, M. P. The parcellation-based connectome: Limitations and extensions. *Neuroimage* **80,** 397–404 (2013).